1

Reverse engineering neural networks to characterise their cost functions

Takuya Isomura[1], Karl Friston[2]

1 Laboratory for Neural Computation and Adaptation, RIKEN Center for Brain Science, Wako,
Saitama 351-0198, Japan

2 Wellcome Centre for Human Neuroimaging, Institute of Neurology, University College
London, 12 Queen Square, London, WC1N 3AR, UK

Corresponding author email: takuya.isomura@riken.jp

10
11

Abstract

This work considers a class of biologically plausible cost functions for neural networks, where the same cost function is minimised by both neural activity and plasticity. We show that such cost functions can be cast as a variational bound on model evidence under an implicit generative model. Using generative models based on Markov decision processes (MDP), we show, analytically, that neural activity and plasticity perform Bayesian inference and learning, respectively, by maximising model evidence. Using mathematical and numerical analyses, we then confirm that biologically plausible cost functions—used in neural networks—correspond to variational free energy under some prior beliefs about the prevalence of latent states that generate inputs. These prior beliefs are determined by particular constants (i.e., thresholds) that define the cost function. This means that the Bayes optimal encoding of latent or hidden states is achieved when, and only when, the network's implicit priors match the process that generates the inputs. Our results suggest that when a neural network minimises its cost function, it is implicitly minimising variational free energy under optimal or sub-optimal prior beliefs. This insight is potentially important because it suggests that any free parameter of a neural network's cost function can itself be optimised—by minimisation with respect to variational free energy.

Keywords: free-energy principle, variational Bayesian inference, learning algorithm, synaptic plasticity, Markov decision process, blind source separation

1. Introduction

Cost functions are ubiquitous in scientific fields that entail optimisation—including physics, chemistry, biology, engineering, and machine learning. Furthermore, any optimisation problem that can be specified using a cost function can be formulated as a gradient descent. In the neurosciences, this enables one to treat neuronal dynamics and plasticity as an optimisation process (Marr, 1969; Albus, 1971; Schultz et al., 1997; Sutton & Barto, 1998; Linsker, 1988; Brown et al., 2001). These examples highlight the importance of specifying a problem in terms of cost functions, from which neural and synaptic dynamics can be derived. In other words, cost functions provide a formal (i.e., normative) expression of the purpose of a neural network and prescribe the dynamics of that neural network. Crucially, once the cost function has been established and an initial condition has been selected, it is no longer necessary to solve the dynamics. Instead, one can characterise the neural network's behaviour in terms of fixed points, basin of attraction, and structural stability—based on and only on the cost function. In short, it is important to identify the cost function to understand the dynamics, plasticity, and function of a neural network.

A ubiquitous cost function in neurobiology, theoretical biology, and machine learning is

model evidence, or equivalently, marginal likelihood or surprise; namely, the probability of some inputs or data under a model of how those inputs were generated by unknown or hidden causes. Generally, the evaluation of surprise is intractable. However, this evaluation can be converted into an optimisation problem by inducing a variational bound on surprise. In machine learning, this is known as an evidence lower bound (ELBO), while the same quantity is known as variational free energy in statistical physics and theoretical neurobiology.

Variational free energy minimisation is a candidate principle that governs neuronal activity and synaptic plasticity (Friston et al., 2006; Friston, 2010). Here, surprise reflects the improbability of sensory inputs given a model of how those inputs were caused. In turn, minimising variational free energy, as a proxy for surprise, corresponds to inferring the (unobservable) causes of (observable) consequences. To the extent that biological systems minimise variational free energy, it is possible to say that they infer and learn the hidden states and parameters that generate their sensory inputs (Helmholtz, 1925; Knill & Pouget, 2004; DiCarlo et al., 2012) and consequently predict those inputs (Rao & Ballard, 1999; Friston, 2005). This is generally referred to as perceptual inference based upon an internal generative model about the external world (Dayan et al., 1995; George & Hawkins, 2009; Bastos et al., 2012).

Variational free energy minimisation provides a unified mathematical formulation of these inference and learning processes in terms of self-organising neural networks that function as Bayes optimal encoders. Moreover, organisms can use the same cost function to control their surrounding environment by sampling predicted (i.e., preferred) inputs. This is known as active inference (Friston et al., 2011). The ensuing free-energy principle suggests that active inference and learning are mediated by changes in neural activity, synaptic strengths, and the behaviour of an organism to minimise variational free energy, as a proxy for surprise. Crucially, variational free energy and model evidence rest upon a generative model of continuous or discrete hidden states. A number of recent studies have used Markov decision process (MDP) generative models to elaborate schemes that minimise variational free energy (Friston, FitzGerald et al., 2016; Friston, FitzGerald et al., 2017; Friston, Parr et al., 2017). This minimisation reproduces various interesting dynamics and behaviours of real neuronal networks and biological organisms. However, it remains to be established whether variational free energy minimisation is an apt explanation for any given neural network, as opposed to the optimisation of alternative cost functions.

In principle, any neural network that produces an output or a decision can be cast as performing some form of inference, in terms of Bayesian decision theory. On this reading, the complete class theorem suggests that any neural network can be regarded as performing Bayesian inference under some prior beliefs; therefore, it can be regarded as minimising variational free energy. The complete class theorem (Wald, 1947; Brown, 1981) states that for any pair of decisions and cost functions, there are some prior beliefs (implicit in the generative model) that render the decisions Bayes optimal. This suggests that it should be

theoretically possible to identify an implicit generative model within any neural network architecture, which renders its cost function a variational free energy or ELBO. In what follows, we show that such identification is possible for a fairly canonical form of a neural network and a generic form of a generative model.

In brief, we adopt a reverse engineering approach to identify a plausible cost function for neural networks—and show that the resulting cost function is formally equivalent to variational free energy. Here, we define a cost function as a function of sensory input, neural activity, and synaptic strengths and suppose that neural activity and synaptic plasticity follows a gradient descent on the cost function. For simplicity, we consider single-layer feed-forward neural networks comprising firing rate neuron models and focus on blind source separation (BSS); namely, the problem of separating sensory inputs into multiple hidden sources or causes (Belouchrani et al., 1997; Cichocki et al., 2009; Comon & Jutten, 2010), which provides the minimum setup for modelling causal inference. Previously, we observed BSS performed by *in vitro* neural networks (Isomura et al., 2015) and reproduced this self-supervised process using an MDP and variational free energy minimisation (Isomura & Friston, 2018). These works suggest that variational free energy minimisation offers a plausible account of the empirical behaviour of *in vitro* networks.

In this work, we ask whether variational free energy minimisation can account for the normative behaviour of a canonical neural network that minimises its cost function, by considering all possible cost functions, within a generic class. Using mathematical analysis, we identify a class of cost functions—from which update rules for both neural activity and synaptic plasticity can be derived—when a single-layer feed-forward neural network comprises firing rate neurons whose firing intensity is determined by the sigmoid activation function. The gradient descent on the ensuing cost function naturally leads to Hebbian plasticity with an activity-dependent homeostatic term. We show that these cost functions are formally homologous to variational free energy under an MDP. Finally, we discuss the implications of this result for explaining the empirical behaviour of neuronal networks, in terms of free energy minimisation under particular prior beliefs.

2. Methods

In this section, we first derive the form of a variational free energy cost function under a specific generative model; namely a Markov decision process[1]. We will go through the derivations carefully, with a focus on the form of the ensuing Bayesian belief updating. The

---

[1] Strictly speaking, the generative model used in this paper is a hidden Markov model (HMM) because we do not consider probabilistic transitions between hidden states that depend upon control variables. However, for consistency with the literature on variational treatments of discrete state space models, we retain the MDP formalism; noting that we are using a special case (with unstructured state transitions).

form of this update will re-emerge later, when reverse engineering the cost functions implicit
in neural networks. This section starts with a description of Markov decision processes—as a
general kind of generative model—and then considers the minimisation of variational free
energy under these models.

2.1 Generative models. Under an MDP model (Fig. 1A), a minimal BSS setup (in a
discrete-space) reduces to the likelihood mapping from N_s hidden sources or states $s_t \equiv$
$\left(s_t^{(1)}, \dots, s_t^{(N_s)}\right)^T$ to N_o observations $o_t \equiv \left(o_t^{(1)}, \dots, o_t^{(N_o)}\right)^T$. Each source and observation

takes a value of one (ON state) or zero (OFF state) at each time step; i.e., $s_t^{(j)}, o_t^{(i)} \in \{1,0\}$.

Throughout this paper, j denotes the j-th hidden state, while i denotes the i-th observation.

The probability of $s_t^{(j)}$ follows a categorical distribution $P\left(s_t^{(j)}\right) = \text{Cat}(D^{(j)})$, where

$D^{(j)} \equiv \left(D_1^{(j)}, D_0^{(j)}\right) \in \mathbb{R}^2$ with $D_1^{(j)} + D_0^{(j)} = 1$.

The probability of an outcome is determined by the likelihood mapping from all hidden

states to each kind of observation in terms of a categorical distribution, $P\left(o_t^{(i)}|s_t, A^{(i)}\right) =$

$\text{Cat}(A^{(i)})$. Here, each element of the tensor $A^{(i)} \in \mathbb{R}^{2 \times 2^{N_s}}$ parameterises the probability

that $P\left(o_t^{(i)} = k|s_t = \vec{l}\right)$, where $k \in \{1,0\}$ are possible observations and $\vec{l} \in \{1,0\}^{N_s}$

encodes a particular combination of hidden states. The prior distribution of each column of

$A^{(i)}$, denoted by $A_{\cdot\vec{l}}^{(i)}$, has a Dirichlet distribution $P\left(A_{\cdot\vec{l}}^{(i)}\right) = \text{Dir}\left(a_{\cdot\vec{l}}^{(i)}\right)$ with concentration

parameter $a_{\cdot\vec{l}}^{(i)} \in \mathbb{R}^2$. We use Dirichlet distributions, as they are tractable and widely used

for random variables that take a continuous value between 0 and 1. Furthermore, learning
the likelihood mapping leads to biologically plausible update rules, which have the form of
associative or Hebbian plasticity: please see below and (Friston et al., 2016) for details.

We use $\tilde{o} \equiv (o_1, \dots, o_t)$ and $\tilde{s} \equiv (s_1, \dots, s_t)$ to denote sequences of observations and
hidden states, respectively. With this notation in place, the generative model (i.e., the joint
distribution over outcomes, hidden states, and the parameters of their likelihood mapping)
can be expressed as

148
$$P(\tilde{o}, \tilde{s}, A) = P(A) \prod_{\tau=1}^{t} P(o_\tau|s_\tau, A)P(s_\tau)$$

$$= \prod_{i=1}^{N_o} P\left(A^{(i)}\right) \cdot \prod_{\tau=1}^{t} \left\{ \prod_{i=1}^{N_o} P\left(o_\tau^{(i)} | s_\tau, A^{(i)}\right) \prod_{j=1}^{N_s} P\left(s_\tau^{(j)}\right) \right\}. \tag{1}$$

Throughout this paper, t denotes the current time, while τ denotes an arbitrary time from the past to the present, $1 \le \tau \le t$.

Figure 1. Comparison between an MDP scheme and a neural network. (**A**) MDP scheme expressed as a Forney factor graph (Forney, 2001; Dauwels, 2007) based upon the formulation in (Friston, Parr et al., 2017). In this BSS setup, the prior D determines hidden states s_t, while s_t determines observation o_t through the likelihood mapping A. Inference corresponds to the inversion of this generative process. Here, D^* indicates the true prior while D indicates the prior under which the network operates. If $D = D^*$, the inference is optimal; otherwise, it is biased. (**B**) Neural network comprising a single layer feed-forward network with a sigmoid activation function. The network receives sensory inputs $o_t = \left(o_t^{(1)}, \dots, o_t^{(N_o)}\right)^T$ that are generated from hidden states $s_t = \left(s_t^{(1)}, \dots, s_t^{(N_s)}\right)^T$ and outputs neural activities $x_t = \left(x_{t1}, \dots, x_{tN_x}\right)^T$. Here, x_{tj} should encode the posterior expectation about a binary state $s_t^{(j)}$.

2.2 Minimisation of variational free energy. In this MDP scheme, the aim is to minimise surprise by minimising variational free energy as a proxy; i.e., performing approximate or variational Bayesian inference. From the generative model, we can motivate a mean-field approximation to the posterior (i.e., recognition) density as follows:

$$Q(\tilde{s}, A) = Q(A)Q(\tilde{s}) = \prod_{i=1}^{N_o} Q\left(A^{(i)}\right) \cdot \prod_{\tau=1}^{t} \prod_{j=1}^{N_s} Q\left(s_\tau^{(j)}\right), \tag{2}$$

where $A^{(i)}$ is the likelihood mapping (i.e., tensor), and the marginal posterior distributions of $s_\tau^{(j)}$ and $A^{(i)}$ have a categorical $Q\left(s_\tau^{(j)}\right) = \mathrm{Cat}\left(\mathbf{s}_\tau^{(j)}\right)$ and Dirichlet distribution $Q\left(A^{(i)}\right) = \mathrm{Dir}\left(\mathbf{a}^{(i)}\right)$, respectively. For simplicity, we assume that $A^{(i)}$ factorises into the product of the likelihood mappings from the *j*-th hidden state to the *i*-th observation: $A_{k\cdot}^{(i)} \approx$

$A_{k\cdot}^{(i,1)} \otimes \cdots \otimes A_{k\cdot}^{(i,N_s)}$ (where $\otimes$ denotes the outer product and $A^{(i,j)} \in \mathbb{R}^{2 \times 2}$). This (mean field) approximation simplifies the computation of the state posteriors.

In what follows, a bold case variable indicates the posterior expectation of the corresponding variable in italics. For example, $s_\tau^{(j)}$ takes the value 0 or 1, while the posterior expectation $\mathbf{s}_\tau^{(j)} \in \mathbb{R}^2$ is the expected value of $s_\tau^{(j)}$ that lies between 0 and 1. Moreover, $\mathbf{a}^{(i,j)} \in \mathbb{R}^{2 \times 2}$ denotes positive concentration parameters. Below, we use the posterior expectation of $\ln A^{(i,j)}$ to encode posterior beliefs about the likelihood, which are given by

$$\ln \mathbf{A}^{(i,j)} \equiv \mathrm{E}_{Q(A^{(i,j)})}\left[\ln A^{(i,j)}\right] = \psi\left(\mathbf{a}_{\cdot l}^{(i,j)}\right) - \psi\left(\mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)}\right)$$

$$= \ln \mathbf{a}_{\cdot l}^{(i,j)} - \ln\left(\mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)}\right) + \mathcal{O}\left(\left(\mathbf{a}_{\cdot l}^{(i,j)}\right)^{-1}\right), \tag{3}$$

where $l \in \{1, 0\}$. Here, $\psi(\cdot) \equiv \Gamma'(\cdot)/\Gamma(\cdot)$ denotes the digamma function, which arises naturally from the definition of the Dirichlet distribution. Please see (Friston et al., 2016) for details. $\mathrm{E}_{Q(A^{(i,j)})}[\cdot]$ denotes the expectation over the posterior of $A^{(i,j)}$.

The ensuing variational free energy of this generative model is then given by

$$F\left(\tilde{o}, Q(\tilde{s}), Q(A)\right)$$

$$\equiv \sum_{\tau=1}^{t} \left\{ \mathrm{E}_{Q(s_\tau)Q(A)}\left[-\ln P(o_\tau|s_\tau, A)\right] + \mathcal{D}_{\mathrm{KL}}\left[Q(s_\tau)||P(s_\tau)\right] \right\} + \mathcal{D}_{\mathrm{KL}}\left[Q(A)||P(A)\right]$$

$$\begin{array}{c}
191 \qquad = \sum_{j=1}^{N_s} \sum_{\tau=1}^{t} \mathbf{s}_\tau^{(j)} \cdot \underbrace{\left\{ -\sum_{i=1}^{N_o} \ln \mathbf{A}^{(i,j)} \cdot o_\tau^{(i)} + \ln \mathbf{s}_\tau^{(j)} - \ln D^{(j)} \right\}}_{\text{accuracy+state complexity}}
\end{array}$$

$$192 \qquad + \underbrace{\sum_{i=1}^{N_o} \sum_{j=1}^{N_s} \left\{ \left(\mathbf{a}^{(i,j)} - a^{(i,j)} \right) \cdot \ln \mathbf{A}^{(i,j)} - \ln \mathcal{B}\left(\mathbf{a}^{(i,j)}\right) \right\}}_{\text{parameter complexity}}, \qquad (4)$$

where $\ln \mathbf{A}^{(i,j)} \cdot o_\tau^{(i)}$ denotes the inner product of $\ln \mathbf{A}^{(i,j)}$ and a one-hot encoded vector

of $o_\tau^{(i)}$, $\mathcal{D}_{\mathrm{KL}}[\cdot \,||\, \cdot]$ is the complexity as scored by the Kullback–Leibler divergence (Kullback

& Leibler, 1951), and $\mathcal{B}\left(\mathbf{a}^{(i,j)}\right) \equiv \mathcal{B}\left(\mathbf{a}_{\cdot 1}^{(i,j)}\right) \mathcal{B}\left(\mathbf{a}_{\cdot 0}^{(i,j)}\right)$ with $\mathcal{B}\left(\mathbf{a}_{\cdot l}^{(i,j)}\right) \equiv \Gamma\left(\mathbf{a}_{1l}^{(i,j)}\right) \Gamma\left(\mathbf{a}_{0l}^{(i,j)}\right) /$

$\Gamma\left(\mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)}\right)$ is the beta function. The first term in the final equality comprises the

accuracy $\left(-\mathbf{s}_\tau^{(j)} \cdot \sum_{i=1}^{N_o} \ln \mathbf{A}^{(i,j)} \cdot o_\tau^{(i)}\right)$ and (state) complexity $\left(\mathbf{s}_\tau^{(j)} \cdot \left(\ln \mathbf{s}_\tau^{(j)} - \ln D^{(j)}\right)\right)$. The

accuracy term is simply the expected log likelihood of an observation, while complexity
scores the divergence between prior and posterior beliefs. In other words, complexity
reflects the degree of belief updating or degrees of freedom required to provide an accurate
account of observations. Both belief updates to states and parameters incur a complexity
cost: the state complexity increases with time *t*, while parameter complexity increases in the
order of $\ln t$—and is thus negligible when *t* is large (see Supplementary Methods S1 for
details). This means that we can ignore parameter complexity, when the scheme has
experienced a sufficient number of outcomes. We will drop the parameter complexity in
subsequent sections. In the remainder of this section, we show how the minimisation of
variational free energy transforms (i.e., updates) priors into posteriors, when the parameter
complexity is evaluated explicitly.

Inference optimises posterior expectations about the hidden states by minimising
variational free energy. The optimal posterior expectations are obtained by solving the
variation of *F* to give

$$212 \qquad \mathbf{s}_t^{(j)} = \sigma\left(\sum_{i=1}^{N_o} \ln \mathbf{A}^{(i,j)} \cdot o_t^{(i)} + \ln D^{(j)} \right) = \sigma\left(\ln \mathbf{A}^{(\cdot,j)} \cdot o_t + \ln D^{(j)} \right), \qquad (5)$$

213 where $\sigma(\cdot)$ is the softmax function. As $s_t^{(j)}$ is a binary value in this work, the posterior

214 expectation of $s_t^{(j)}$ taking a value of one (ON state) can be expressed as

$$215 \qquad \mathbf{s}_{t1}^{(j)} = \frac{\exp\left(\ln \mathbf{A}_{\cdot 1}^{(\cdot,j)} \cdot o_t + \ln D_1^{(j)}\right)}{\exp\left(\ln \mathbf{A}_{\cdot 1}^{(\cdot,j)} \cdot o_t + \ln D_1^{(j)}\right) + \exp\left(\ln \mathbf{A}_{\cdot 0}^{(\cdot,j)} \cdot o_t + \ln D_0^{(j)}\right)}$$

$$216 \qquad = \mathrm{sig}\left(\ln \mathbf{A}_{\cdot 1}^{(\cdot,j)} \cdot o_t - \ln \mathbf{A}_{\cdot 0}^{(\cdot,j)} \cdot o_t + \ln D_1^{(j)} - \ln D_0^{(j)}\right) \qquad (6)$$

using the sigmoid function $\mathrm{sig}(z) \equiv 1/(1 + \exp(-z))$. Thus, the posterior expectation of

$s_t^{(j)}$ taking a value 0 (OFF state) is $\mathbf{s}_{t0}^{(j)} = 1 - \mathbf{s}_{t1}^{(j)}$. Here, $D_1^{(j)}$ and $D_0^{(j)}$ are constants

denoting the prior beliefs about hidden states. Bayes optimal encoding is obtained when,

and only when, the prior beliefs match the genuine prior distribution; i.e., $D_1^{(j)} = D_0^{(j)} = 0.5$

in this BSS setup. This concludes our treatment of inference about hidden states under this

minimal scheme. Note that the updates in Equation (5) have a biological plausibility in the

sense that the posterior expectations can be associated with nonnegative sigmoid-shape

firing rates (also known as neurometric functions (Tolhurst et al., 1983; Newsome et al.,

1989)), while the arguments of the sigmoid (softmax) function can be associated with

neuronal depolarisation; rendering the softmax function a voltage-firing rate activation

function. Please see (Friston, FitzGerald et al., 2017) for a more comprehensive

discussion—and simulations using this kind of variational message passing to reproduce

empirical phenomena; such as place fields, mismatch negativity responses, phase-precession,

pre-play activity, etc in systems neuroscience.

In terms of learning, by solving the variation of F with respect to $\mathbf{a}^{(i,j)}$, the optimal

posterior expectations about the parameters are given by

$$233 \qquad \mathbf{a}^{(i,j)} = a^{(i,j)} + \sum_{\tau=1}^{t} o_\tau^{(i)} \otimes \mathbf{s}_\tau^{(j)} = a^{(i,j)} + t\overline{o_t^{(i)} \otimes \mathbf{s}_t^{(j)}}, \qquad (7)$$

234 where $a^{(i,j)}$ is the prior, $o_\tau^{(i)} \otimes \mathbf{s}_\tau^{(j)}$ expresses the outer product of a one-hot encoded

235 vector of $o_\tau^{(i)}$ and $\mathbf{s}_\tau^{(j)}$, and $\overline{o_t^{(i)} \otimes \mathbf{s}_t^{(j)}} \equiv \frac{1}{t} \sum_{\tau=1}^{t} o_\tau^{(i)} \otimes \mathbf{s}_\tau^{(j)}$. Thus, the optimal posterior

236 expectation of matrix A is

$$237 \qquad \begin{cases} \mathbf{A}_{11}^{(i,j)} = \dfrac{\mathbf{a}_{11}^{(i,j)}}{\mathbf{a}_{11}^{(i,j)} + \mathbf{a}_{01}^{(i,j)}} = \dfrac{t\overline{o_t^{(i)}\mathbf{s}_{t1}^{(j)}} + a_{11}^{(i,j)}}{t\overline{\mathbf{s}_{t1}^{(j)}} + a_{11}^{(i,j)} + a_{01}^{(i,j)}} = \dfrac{\overline{o_t^{(i)}\mathbf{s}_{t1}^{(j)}}}{\overline{\mathbf{s}_{t1}^{(j)}}} + \mathcal{O}\left(\dfrac{1}{t}\right) \\[3em] \mathbf{A}_{10}^{(i,j)} = \dfrac{\mathbf{a}_{10}^{(i,j)}}{\mathbf{a}_{10}^{(i,j)} + \mathbf{a}_{00}^{(i,j)}} = \dfrac{t\overline{o_t^{(i)}\mathbf{s}_{t0}^{(j)}} + a_{10}^{(i,j)}}{t\overline{\mathbf{s}_{t0}^{(j)}} + a_{10}^{(i,j)} + a_{00}^{(i,j)}} = \dfrac{\overline{o_t^{(i)}\mathbf{s}_{t0}^{(j)}}}{\overline{\mathbf{s}_{t0}^{(j)}}} + \mathcal{O}\left(\dfrac{1}{t}\right) \end{cases}, \qquad (8)$$

where $\overline{o_t^{(i)}\mathbf{s}_{t1}^{(j)}} = \frac{1}{t}\sum_{\tau=1}^{t} o_\tau^{(i)}\mathbf{s}_{\tau 1}^{(j)}$, $\overline{\mathbf{s}_{t1}^{(j)}} = \frac{1}{t}\sum_{\tau=1}^{t}\mathbf{s}_{\tau 1}^{(j)}$, $\overline{o_t^{(i)}\mathbf{s}_{t0}^{(j)}} = \frac{1}{t}\sum_{\tau=1}^{t} o_\tau^{(i)}\mathbf{s}_{\tau 0}^{(j)}$, and $\overline{\mathbf{s}_{t0}^{(j)}} =$

$\frac{1}{t}\sum_{\tau=1}^{t}\mathbf{s}_{\tau 0}^{(j)}$. Further, $\mathbf{A}_{01}^{(i,j)} = 1 - \mathbf{A}_{11}^{(i,j)}$ and $\mathbf{A}_{00}^{(i,j)} = 1 - \mathbf{A}_{10}^{(i,j)}$. The prior of parameters

$a^{(i,j)}$ is in the order of 1 and is thus negligible when t is large. The matrix $\mathbf{A}^{(i,j)}$ express the

optimal posterior expectations of $o_t^{(i)}$ taking the ON state when $s_t^{(j)}$ is ON ($\mathbf{A}_{11}^{(i,j)}$) or OFF

($\mathbf{A}_{10}^{(i,j)}$), or $o_t^{(i)}$ taking the OFF state when $s_t^{(j)}$ is ON ($\mathbf{A}_{01}^{(i,j)}$) or OFF ($\mathbf{A}_{00}^{(i,j)}$). Although this

expression may seem complicated, it is fairly straightforward. The posterior expectations of

the likelihood simply accumulate posterior expectations about the co-occurrence of states

and their outcomes. These accumulated (Dirichlet) parameters are then normalised to give a

likelihood or probability. Crucially, one can observe the associative or Hebbian aspect of this

belief update, expressed here in terms of the outer products between outcomes and

posteriors about states in Equation (7). We now turn to the equivalent update for neural

activities and synaptic weights of a neural network.

2.3 Neural activity and Hebbian plasticity models. Next, we consider the neural activity and

synaptic plasticity in the neural network (Fig. 1B). We assume that the *j*-th neuron's activity

x_{tj} is given by

$$\dot{x}_{tj} \propto -\underbrace{f'(x_{tj})}_{\text{leakage}} + \underbrace{W_{j1}o_t - W_{j0}o_t}_{\text{synaptic input}} + \underbrace{h_{j1} - h_{j0}}_{\text{threshold}}. \tag{9}$$

We suppose that $W_{j1} \in \mathbb{R}^{N_o}$ and $W_{j0} \in \mathbb{R}^{N_o}$ comprise row vectors of synapses, and $h_{j1} \in$

$\mathbb{R}$ and $h_{j0} \in \mathbb{R}$ are adaptive thresholds that depend on the values of W_{j1} and W_{j0},

respectively. One may regard W_{j1} and W_{j0} as excitatory and inhibitory synapses,

respectively. We further assume that the nonlinear leakage $f'(\cdot)$ (i.e., the leak current) is

the inverse of the sigmoid function (i.e., the logit function), such that the fixed point of x_{tj} is

given by

$$x_{tj} = \text{sig}(W_{j1}o_t - W_{j0}o_t + h_{j1} - h_{j0})$$

$$= \frac{\exp(W_{j1}o_t + h_{j1})}{\exp(W_{j1}o_t + h_{j1}) + \exp(W_{j0}o_t + h_{j0})}. \tag{10}$$

We further assume that synaptic strengths are updated following Hebbian plasticity with an

activity-dependent homeostatic term as follows:

$$\begin{cases} \Delta W_{j1}(t) \equiv W_{j1}(t+1) - W_{j1}(t) \propto Hebb_1(x_{tj}, o_t, W_{j1}) + Home_1(x_{tj}, W_{j1}) \\ \Delta W_{j0}(t) \equiv W_{j0}(t+1) - W_{j0}(t) \propto Hebb_0(x_{tj}, o_t, W_{j0}) + Home_0(x_{tj}, W_{j0}) \end{cases}, \tag{11}$$

where $Hebb_1$ and $Hebb_0$ denote Hebbian plasticity as determined by the product of
sensory inputs and neural outputs, and $Home_1$ and $Home_0$ denote homeostatic plasticity
determined by output neural activity.

In the MDP scheme, posterior expectations about hidden states and parameters are
usually associated with neural activity and synaptic strengths. Here, we can observe a formal
similarity between the solutions for the state posterior (Equation (6)) and the activity in the
neural network (Equation (10)). By this analogy, x_{tj} can be regarded as encoding the

posterior expectation of the ON state $\mathbf{s}_{t1}^{(j)}$. Moreover, W_{j1} and W_{j0} correspond to

$\ln \mathbf{A}_{11}^{(\cdot,j)} - \ln\left(\vec{1} - \mathbf{A}_{11}^{(\cdot,j)}\right) = \text{sig}^{-1}\left(\mathbf{A}_{11}^{(\cdot,j)}\right)$ and $\ln \mathbf{A}_{10}^{(\cdot,j)} - \ln\left(\vec{1} - \mathbf{A}_{10}^{(\cdot,j)}\right) = \text{sig}^{-1}\left(\mathbf{A}_{10}^{(\cdot,j)}\right)$,

respectively, in the sense that they express the amplitude of o_t influencing x_{tj} or $\mathbf{s}_{t1}^{(j)}$.

Here, $\vec{1} = (1,\dots,1) \in \mathbb{R}^{N_o}$ is a vector of ones. In particular, the optimal posterior of a

hidden state taking a value of one (Equation (6)) is given by the ratio of the beliefs about ON
and OFF states, expressed as a sigmoid function. Thus, to be a Bayes optimal encoder, the
fixed point of neural activity needs to be a sigmoid function. This requirement is
straightforwardly ensured when $f'\left(x_{tj}\right)$ is the inverse of the sigmoid function (see Equation
(13) below). Under this condition, the fixed point or solution for x_{tk} (Equation (10))
compares inputs from ON and OFF pathways, and thus x_{tj} straightforwardly encodes the

posterior of the j-th hidden state being ON (i.e., $x_{tj} \to \mathbf{s}_{t1}^{(j)}$). In short, the above neural

network is effectively inferring the hidden state.

If the activity of the neural network is performing inference, does the Hebbian plasticity
correspond to Bayes optimal learning? In other words, does the synaptic update rule in
Equation (11) ensure that the neural activity and synaptic strengths asymptotically encode

Bayes optimal posterior beliefs about hidden states ($x_{tj} \to \mathbf{s}_{t1}^{(j)}$) and parameters ($W_{j1} \to$

$\text{sig}^{-1}\left(\mathbf{A}_{11}^{(\cdot,j)}\right)$), respectively? To this end, below we will identify a class of cost functions from

which the neural activity and synaptic plasticity can be derived, and consider the conditions
under which the cost function becomes consistent with variational free energy.

2.4 Neural network cost functions. Here, we consider a class of functions that constitute a
cost function for both neural activity and synaptic plasticity. We start by assuming that the
update of the j-th neuron's activity (Equation (9)) is determined by the gradient of cost
function L_j; i.e., $\dot{x}_{tj} \propto -\partial L_j / \partial x_{tj}$. By integrating the right-hand side of Equation (9), we
obtain a class of cost functions as

298
$$L_j = \sum_{\tau=1}^{t} \left(f(x_{\tau j}) - x_{\tau j} W_{j1} o_\tau - (1 - x_{\tau j}) W_{j0} o_\tau - x_{\tau j} h_{j1} - (1 - x_{\tau j}) h_{j0} \right) + \mathcal{O}(1)$$

299
$$= \sum_{\tau=1}^{t} \left(f(x_{\tau j}) - \begin{pmatrix} x_{\tau j} \\ 1 - x_{\tau j} \end{pmatrix}^T \left(\begin{pmatrix} W_{j1} \\ W_{j0} \end{pmatrix} o_\tau + \begin{pmatrix} h_{j1} \\ h_{j0} \end{pmatrix} \right) \right) + \mathcal{O}(1), \tag{12}$$

where the $\mathcal{O}(1)$ term, which depends on W_{j1} and W_{j0}, is of a lower order than the other
terms (as they are $\mathcal{O}(t)$) and is thus negligible when t is large. Please see Supplementary
Methods S3 for the case where we explicitly evaluate the $\mathcal{O}(1)$ term, to demonstrate the
formal correspondence between the initial values of synaptic strengths and the parameter

prior $p(A)$. The cost function of the entire network is defined by $L \equiv \sum_{j=1}^{N_x} L_j$.

When $f'(x_{\tau j})$ is the inverse of the sigmoid function, we have

306
$$f(x_{\tau j}) = x_{\tau j} \ln x_{\tau j} + (1 - x_{\tau j}) \ln(1 - x_{\tau j}) \tag{13}$$

307 up to a constant term. We further assume that the synaptic weight update rule is derived
308 from the same cost function L_j. Thus, the synaptic plasticity is given by

309
$$\begin{cases} \dot{W}_{j1} \propto -\dfrac{1}{t} \dfrac{\partial L_j}{\partial W_{j1}} = \overline{x_{tj} o_t} + \overline{x_{tj} h'_{j1}} \\ \dot{W}_{j0} \propto -\dfrac{1}{t} \dfrac{\partial L_j}{\partial W_{j0}} = \overline{(1 - x_{tj}) o_t} + \overline{1 - x_{tj} h'_{j0}} \end{cases}, \tag{14}$$

where $\overline{x_{tj} o_t} \equiv \frac{1}{t} \sum_{\tau=1}^{t} x_{\tau j} o_\tau$, $\overline{x_{tj}} \equiv \frac{1}{t} \sum_{\tau=1}^{t} x_{\tau j}$, $\overline{(1 - x_{tj}) o_t} \equiv \frac{1}{t} \sum_{\tau=1}^{t} (1 - x_{\tau j}) o_\tau$, $\overline{1 - x_{tj}} \equiv$

$\frac{1}{t} \sum_{\tau=1}^{t} (1 - x_{\tau j})$, $h'_{j1} \equiv \partial h_{j1} / \partial W_{j1}$, and $h'_{j0} \equiv \partial h_{j0} / \partial W_{j0}$. Note that the update of W_{j1} is

not directly influenced by W_{j0}, and *vice versa*, because they encode parameters in physically
distinct pathways (i.e., the updates are local learning rules (Lee et al., 2000)). The update rule
for W_{j1} can be viewed as Hebbian plasticity mediated by an additional activity-dependent
term expressing homeostatic plasticity. Moreover, the update of W_{j0} can be viewed as
anti-Hebbian plasticity with a homeostatic term, in the sense that W_{j0} is reduced when
input (o_t) and output (x_{tj}) fire together. The fixed points of W_{j1} and W_{j0} are given by

318
$$\begin{cases} W_{j1} = h_1'^{-1} \left(-\dfrac{\overline{x_{tj} o_t}}{\overline{x_{tj}}} \right) \\ W_{j0} = h_0'^{-1} \left(-\dfrac{\overline{(1 - x_{tj}) o_t}}{\overline{1 - x_{tj}}} \right) \end{cases}. \tag{15}$$

Crucially, these synaptic strength updates are a subclass of the general synaptic plasticity rule
in Equation (11); see also Supplementary Methods S2 for the mathematical explanation.

Therefore, if the synaptic update rule is derived from the cost function underlying neural
activity, the synaptic update rule has a biologically plausible form comprising Hebbian
plasticity and activity-dependent homeostatic plasticity.

2.5 Comparison with variational free energy. Here, we establish a formal relationship
between the cost function L and variational free energy. We define $\widehat{W}_{j1} \equiv \text{sig}(W_{j1})$ and
$\widehat{W}_{j0} \equiv \text{sig}(W_{j0})$ as the sigmoid functions of synaptic strengths. We consider the case in
which neural activity is expressed as a sigmoid function and thus Equation (13) holds. As

$W_{j1} = \ln \widehat{W}_{j1} - \ln(\vec{1} - \widehat{W}_{j1})$, Equation (12) becomes

330
$$L = \sum_{j=1}^{N_x} \sum_{\tau=1}^{t} \left(\begin{array}{c} x_{\tau j} \\ 1 - x_{\tau j} \end{array} \right)^T \left\{ \left(\begin{array}{c} \ln x_{\tau j} \\ \ln(1 - x_{\tau j}) \end{array} \right) - \left(\begin{array}{cc} \ln \widehat{W}_{j1} & \ln(\vec{1} - \widehat{W}_{j1}) \\ \ln \widehat{W}_{j0} & \ln(\vec{1} - \widehat{W}_{j0}) \end{array} \right) \left(\begin{array}{c} o_\tau \\ \vec{1} - o_\tau \end{array} \right) - \left(\begin{array}{c} h_{j1} \\ h_{j0} \end{array} \right) \right.$$

331
$$\left. + \left(\begin{array}{c} \ln(\vec{1} - \widehat{W}_{j1}) \\ \ln(\vec{1} - \widehat{W}_{j0}) \end{array} \right) \vec{1} \right\} + \mathcal{O}(1), \tag{16}$$

where $\vec{1} = (1, \dots, 1) \in \mathbb{R}^{N_o}$. One can immediately see a formal correspondence between

this cost function and variational free energy (Equation (4)). That is, when we assume that

$x_{tj} = \mathbf{s}_{t1}^{(j)}$, $\widehat{W}_{j1} = \mathbf{A}_{11}^{(\cdot,j)}$, and $\widehat{W}_{j0} = \mathbf{A}_{10}^{(\cdot,j)}$, Equation (16) has exactly the same form as the

sum of the accuracy and state complexity, which is the leading order term of variational free

energy (see the first term in the last equality of Equation (4)).

Specifically, when the thresholds satisfy $h_{j1} = \ln(\vec{1} - \widehat{W}_{j1}) \cdot \vec{1} + \ln D_1^{(j)}$ and $h_{j0} =$

$\ln(\vec{1} - \widehat{W}_{j0}) \cdot \vec{1} + \ln D_0^{(j)}$, Equation (16) becomes equivalent to Equation (4) up to the $\ln t$

order term (that disappears when t is large). Therefore, in this case, the fixed points of neural
activity and synaptic strengths become the posteriors; thus, x_{tj} asymptotically becomes the
Bayes optimal encoder for a large t limit (provided with D that matches the genuine prior
D^*).

In other words, we can define perturbation terms $\phi_{j1} \equiv h_{j1} - \ln(\vec{1} - \widehat{W}_{j1}) \cdot \vec{1}$ and

$\phi_{j0} \equiv h_{j0} - \ln(\vec{1} - \widehat{W}_{j0}) \cdot \vec{1}$ as functions of W_{j1} and W_{j0}, respectively, and can express the

cost function as

346
$$L = \sum_{j=1}^{N_x} \sum_{\tau=1}^{t} \begin{pmatrix} x_{\tau j} \\ 1 - x_{\tau j} \end{pmatrix}^T \left\{ \begin{pmatrix} \ln x_{\tau j} \\ \ln(1 - x_{\tau j}) \end{pmatrix} - \begin{pmatrix} \ln \widehat{W}_{j1} & \ln(\vec{1} - \widehat{W}_{j1}) \\ \ln \widehat{W}_{j0} & \ln(\vec{1} - \widehat{W}_{j0}) \end{pmatrix} \begin{pmatrix} o_\tau \\ \vec{1} - o_\tau \end{pmatrix} - \begin{pmatrix} \phi_{j1} \\ \phi_{j0} \end{pmatrix} \right\} + \mathcal{O}(1). \quad (17)$$

347   Here, without loss of generality, we can suppose that the constant terms in ϕ_{j1} and ϕ_{j0}
348   are chosen to ensure that $\exp(\phi_{j1}) + \exp(\phi_{j0}) = 1$. Under this condition,
349   $(\exp(\phi_{j1}), \exp(\phi_{j0}))$ can be viewed as the prior belief about hidden states

350
$$\begin{cases} \phi_{j1} = \ln D_1^{(j)} \\ \phi_{j0} = \ln D_0^{(j)} \end{cases} \quad (18)$$

and thus Equation (17) is formally equivalent to the accuracy and state complexity terms of
variational free energy.

This means that when the prior belief about states $(D^{(j)})$ is a function of the parameter
posteriors $(\mathbf{A}^{(\cdot,j)})$, the generic cost function under consideration can be expressed in the
form of variational free energy, up to the $\mathcal{O}(\ln t)$ term. A generic cost function L is
sub-optimal from the perspective of Bayesian inference unless ϕ_{j1} and ϕ_{j0} are tuned
appropriately to express the unbiased (i.e., optimal) prior belief. In this BSS setup, $\phi_{j1} =$
$\phi_{j0} = \text{const}$ is optimal; thus, a generic L would asymptotically give an upper bound of
variational free energy with the optimal prior belief about states when t is large.

2.6 Analysis on synaptic update rules. To explicitly solve the fixed points of W_{j1} and W_{j0}
that provide the global minimum of L, we suppose ϕ_{j1} and ϕ_{j0} as linear functions of W_{j1}
and W_{j0}, respectively, given by

364
$$\begin{cases} \phi_{j1} = \alpha_{j1} + W_{j1}\beta_{j1} \\ \phi_{j0} = \alpha_{j0} + W_{j0}\beta_{j0} \end{cases}, \quad (19)$$

365   where $\alpha_{j1}, \alpha_{j0} \in \mathbb{R}$ and $\beta_{j1}, \beta_{j0} \in \mathbb{R}^{N_o}$ are constants. By solving the variation of L with
366   respect to W_{j1} and W_{j0}, we find the fixed point of synaptic strengths as

367
$$\begin{cases} W_{j1} = \text{sig}^{-1}\left(\frac{\overline{x_{tj} o_t}}{\overline{x_{tj}}} + \beta_{j1} \right) \\ W_{j0} = \text{sig}^{-1}\left(\frac{\overline{(1 - x_{tj}) o_t}}{\overline{1 - x_{tj}}} + \beta_{j0} \right) \end{cases}. \quad (20)$$

368   Since the update from t to t+1 is expressed as $\text{sig}(W_{j1} + \Delta W_{j1}) - \text{sig}(W_{j1}) = \widehat{W}_{j1} \odot$
369   $(\vec{1} - \widehat{W}_{j1}) \odot \Delta W_{j1} + \mathcal{O}\left(|\Delta W_{j1}|^2\right)$ and $\text{sig}(W_{j1} + \Delta W_{j1}) - \text{sig}(W_{j1}) \approx x_{(t+1)j} o_{t+1}/\overline{x_{tj}} -$
370   $x_{(t+1)j} \overline{x_{tj} o_t}/\overline{x_{tj}}^2 = x_{(t+1)j} o_{t+1}/\overline{x_{tj}} - (\widehat{W}_{j1} - \beta_{j1})x_{(t+1)j}/\overline{x_{tj}}$, we recover the following

371   synaptic plasticity:

$$
\left\{
\begin{aligned}
\Delta W_{j1} &= \underbrace{\frac{\widehat{W}_{j1}^{\odot-1}\odot\left(1-\widehat{W}_{j1}\right)^{\odot-1}}{\overline{x}_{tj}}}_{\text{adaptive learning rate}} \odot \left\{ \underbrace{x_{(t+1)j}o_{t+1}}_{\substack{\text{Hebbian plasticity}}} - \underbrace{\left(\widehat{W}_{j1}-\beta_{j1}\right)x_{(t+1)j}}_{\text{homeostatic plasticity}} \right\} \\
\Delta W_{j0} &= \underbrace{\frac{\widehat{W}_{j0}^{\odot-1}\odot\left(1-\widehat{W}_{j0}\right)^{\odot-1}}{\overline{1-x}_{tj}}}_{\text{adaptive learning rate}} \odot \left\{ \underbrace{\left(1-x_{(t+1)j}\right)o_{t+1}}_{\substack{\text{anti-Hebbian}\\\text{plasticity}}} - \underbrace{\left(\widehat{W}_{j0}-\beta_{j0}\right)\left(1-x_{(t+1)j}\right)}_{\text{homeostatic plasticity}} \right\}
\end{aligned}
\right\},
$$
    (21)

where $\odot$ denotes the element-wise (Hadamard) product and $\widehat{W}_{j1}^{\odot-1}$ denotes the

element-wise inverse of $\widehat{W}_{j1}$. This synaptic plasticity rule is a subclass of the generic synaptic

plasticity rule in Equation (11).

In summary, we demonstrated that under a few minimal assumptions and ignoring small

contributions to weight updates, the neural network under consideration can be regarded as

minimising an approximation to model evidence, because the cost function can be

formulated in terms of variational free energy. In what follows, we will rehearse our analytic

results and then use numerical analyses to illustrate Bayes optimal inference (and learning)

in a neural network when, and only when, it has the right priors.

3. Results

3.1 Analytical form of neural network cost functions. The analysis in the preceding section

rests on the following assumptions:

(1) Updates of neural activity and synaptic weights are determined by a gradient descent on

a cost function L.

(2) Neural activity is updated by the weighted sum of sensory inputs, and its fixed point is

expressed as the sigmoid function.

Under these assumptions, we can express the cost function for a neural network as follows

(see Equation (17)):

$$
L = \sum_{j=1}^{N_x}\sum_{\tau=1}^{t} \begin{pmatrix} x_{\tau j} \\ 1-x_{\tau j} \end{pmatrix}^{T} \left\{ \begin{pmatrix} \ln x_{\tau j} \\ \ln\left(1-x_{\tau j}\right) \end{pmatrix} - \begin{pmatrix} \ln\widehat{W}_{j1} & \ln\left(\vec{1}-\widehat{W}_{j1}\right) \\ \ln\widehat{W}_{j0} & \ln\left(\vec{1}-\widehat{W}_{j0}\right) \end{pmatrix} \begin{pmatrix} o_{\tau} \\ \vec{1}-o_{\tau} \end{pmatrix} - \begin{pmatrix} \phi_{j1} \\ \phi_{j0} \end{pmatrix} \right\} + \mathcal{O}(1),
$$

where $\widehat{W}_{j1} = \text{sig}\left(W_{j1}\right)$ and $\widehat{W}_{j0} = \text{sig}\left(W_{j0}\right)$ hold, and ϕ_{j1} and ϕ_{j0} are functions of W_{j1}

and W_{j0}, respectively. The log likelihood function (accuracy term) and divergence of hidden

states (complexity term) of variational free energy emerge naturally under the assumption of

a sigmoid activation function. The cost function above has additional terms denoted by ϕ_{j1}

and ϕ_{j0}. In other words, we can say that the cost function *L* is variational free energy under

a sub-optimal prior belief about hidden states, depending on W_{j1} and W_{j0}: $\ln P\left(s_t^{(j)}\right) =$

$\ln D^{(j)} = \phi_j$, where $\phi_j \equiv (\phi_{j1}, \phi_{j0})$. This prior alters the landscape of the cost function in a

sub-optimal manner and thus provides a biased solution for neural activities and synaptic

strengths, which differ from the Bayes optimal encoders.

For analytical tractability, we further assume the following:

(3) The perturbation terms (ϕ_{j1} and ϕ_{j0}) that constitute the difference between the cost

function and variational free energy with optimal prior beliefs can be expressed as linear

equations of W_{j1} and W_{j0}.

From assumption 3, Equation (17) becomes

407
$$L = \sum_{j=1}^{N_x} \left[\sum_{\tau=1}^{t} \begin{pmatrix} x_{\tau j} \\ 1 - x_{\tau j} \end{pmatrix}^T \left\{ \begin{pmatrix} \ln x_{\tau j} \\ \ln(1 - x_{\tau j}) \end{pmatrix} - \begin{pmatrix} \ln \widehat{W}_{j1} & \ln(\vec{1} - \widehat{W}_{j1}) \\ \ln \widehat{W}_{j0} & \ln(\vec{1} - \widehat{W}_{j0}) \end{pmatrix} \begin{pmatrix} o_\tau \\ \vec{1} - o_\tau \end{pmatrix} \right. \right.$$

408
$$\left. \left. - \begin{pmatrix} \alpha_{j1} + W_{j1}\beta_{j1} \\ \alpha_{j0} + W_{j0}\beta_{j0} \end{pmatrix} \right\} \right] + \mathcal{O}(1), \tag{22}$$

where $\{\alpha_{j1}, \alpha_{j0}, \beta_{j1}, \beta_{j0}\}$ are constants. The cost function has degrees of freedom with

respect to the choice of constants $\{\alpha_{j1}, \alpha_{j0}, \beta_{j1}, \beta_{j0}\}$, which correspond to the prior belief

about states $D^{(j)}$. The neural activity and synaptic strengths that give the minimum of a

generic physiological cost function L are biased by these constants, which may be analogous

to physiological constraints (see Discussion for details).

The cost function of the neural networks considered is characterised only by ϕ_j. Thus,

after fixing ϕ_j by fixing constrains $(\alpha_{j1}, \alpha_{j0})$ and (β_{j1}, β_{j0}), the remaining degrees of

freedom are the initial synaptic weights. These correspond to the prior distribution of

parameters $P(A)$ in the variational Bayesian formulation (please see Supplementary

Methods 3).

The fixed point of synaptic strengths that give the minimum of L is given analytically as

Equation (20), expressing that (β_{j1}, β_{j0}) deviates the centre of the nonlinear

mapping—from Hebbian products to synaptic strengths—from the optimal position (shown

in Equation (8)). As shown in Equation (14), the derivative of L with respect to W_{j1} and W_{j0}

recovers the synaptic update rules that comprise Hebbian and activity-dependent

homeostatic terms. Although Equation (14) expresses the dynamics of synaptic strengths

that converge to the fixed point, it is consistent with a plasticity rule that gives the synaptic

change from *t* to *t*+1 (Equation (21)).

Hence, based on assumptions 1 and 2, we find that the cost function approximates

variational free energy; see also Supplementary Table S1 for their correspondence. Under

this condition, neural activity encodes the posterior expectation about hidden states, $x_{\tau j} =$

$\mathbf{s}_{\tau 1}^{(j)} = Q\left(s_{\tau}^{(j)} = 1\right)$, and synaptic strengths encode the posterior expectation of the

parameters, $\widehat{W}_{j1} = \mathrm{sig}(W_{j1}) = \mathbf{A}_{11}^{(\cdot,j)}$ and $\widehat{W}_{j0} = \mathrm{sig}(W_{j0}) = \mathbf{A}_{10}^{(\cdot,j)}$. In addition, based on

assumption 3, the accuracy of approximation depends on the deviation of constants

$\{\alpha_{j1}, \alpha_{j0}, \beta_{j1}, \beta_{j0}\}$ from their optimal values. From a Bayesian perspective, these constants

can be viewed as prior beliefs, $\ln P\left(s_t^{(j)}\right) = \ln D^{(j)} = (\alpha_{j1} + W_{j1}\beta_{j1}, \alpha_{j0} + W_{j0}\beta_{j0})$, when

we assume that $\left(x_{tj}, 1 - x_{tj}\right)$ represents the state posterior $\mathbf{s}_t^{(j)}$. When and only when

$(\alpha_{j1}, \alpha_{j0}) = (-\ln 2, -\ln 2)$ and $(\beta_{j1}, \beta_{j0}) = (\vec{0}, \vec{0})$, the cost function becomes variational

free energy with optimal prior beliefs (for BSS), whose global minimum ensures Bayes
optimal encoding.

In short, we identify a class of biologically plausible cost functions from which the update
rules for both neural activity and synaptic plasticity can be derived. When the activation
function for neural activity is a sigmoid function, a cost function in this class is expressed
straightforwardly as variational free energy. With respect to the choice of constants
expressing physiological constraints in the neural network, the cost function has degrees of
freedom that may be viewed as (potentially sub-optimal) prior beliefs from the Bayesian
perspective. Now, we illustrate the implicit inference and learning in neural networks
through simulations of BSS.

3.2 Numerical simulations. Here, we simulated the dynamics of neural activity and synaptic
strengths when they followed a gradient descent on the cost function in Equation (22). We
considered a BSS comprising two hidden sources (or states) and 32 observations (or sensory
inputs), formulated as an MDP. The two hidden sources comprised four patterns: $s_t =$

$s_t^{(1)} \otimes s_t^{(2)} = (0,0), (1,0), (0,1), (1,1)$. An observation $o_t^{(i)}$ was generated through the

likelihood mapping $A^{(i)}$, defined as

454
$$\begin{cases} P\left(o_t^{(i)} = 1 | s_t, A^{(i)}\right) = A_{1\cdot}^{(i)} = \left(0, \dfrac{3}{4}, \dfrac{1}{4}, 1\right) & \text{for } 1 \leq i \leq 16 \\[2mm] P\left(o_t^{(i)} = 1 | s_t, A^{(i)}\right) = A_{1\cdot}^{(i)} = \left(0, \dfrac{1}{4}, \dfrac{3}{4}, 1\right) & \text{for } 17 \leq i \leq 32 \end{cases}. \quad (23)$$

Here, for example, $A_{10}^{(i)} = 3/4$ for $1 \leq i \leq 16$ is the probability of $o_t^{(i)}$ taking one when

$s_t = (1,0)$. The simulations continued over $T = 10^4$ time steps. Notably, this simulation
setup is exactly the same experimental setup as that we used for *in vitro* neural networks
(Isomura et al., 2015; Isomura, Friston, 2018). We leverage this setup to clarify the

relationship among our empirical work, a feed-forward neural network model, and
variational Bayesian formulations.

First, as in (Isomura & Friston, 2018), we demonstrated that a network with a cost function

with optimised constants ($(\alpha_{j1}, \alpha_{j0}) = (-\ln 2, -\ln 2)$ and $(\beta_{j1}, \beta_{j0}) = (\vec{0}, \vec{0})$) can perform

BSS successfully (Fig. 2). The responses of neuron 1 came to recognise source 1 after training,
indicating that neuron 1 learnt to encode source 1 (Fig. 2A). Meanwhile, neuron 2 learnt to
infer source 2 (Fig. 2B). This demonstrates that minimisation of the cost function, with
optimal constants, is equivalent to variational free energy minimisation, and hence is
sufficient to emulate BSS. Next, we quantified the dependency of BSS performance on the
form of the cost function, by varying the above-mentioned constants (Fig. 3).

We varied $(\alpha_{j1}, \alpha_{j0})$ in a range of $0.05 \leq \exp(\alpha_{j1}) \leq 0.95$, while maintaining
$\exp(\alpha_{j1}) + \exp(\alpha_{j0}) = 1$, and found that changing $(\alpha_{j1}, \alpha_{j0})$ from $(-\ln 2, -\ln 2)$ led to
a failure of BSS. Because neuron 1 encodes source 1 with optimal α, the correlation
between source 1 and the response of neuron 1 is close to one, while the correlation
between source 2 and the response of neuron 1 is nearly zero. In the case of sub-optimal α,
these correlations fall to around 0.5, indicating that the response of neuron 1 encodes a
mixture of source 1 and source 2 (Fig. 3A). Moreover, a failure of BSS can be induced when
the elements of β take values far from zero (Fig. 3B). When the elements of β are
generated from a zero-mean Gaussian distribution, the accuracy of BSS—measured using the
correlation between sources and responses—decreases as the standard deviation increases.

Figure 2. Emergence of response selectivity for a source. (**A**) Evolution of neuron 1's responses that learn to encode source 1, in the sense that the response is high when source 1 takes a value of one (red dots), and it is low when source 1 takes a value of zero (blue dots). Lines correspond to smoothed trajectories obtained using a discrete cosine transform. (**B**) Emergence of neuron 2's response that learns to encode source 2. These results indicate that the neural network succeeded in separating two independent sources. The code is provided as Supplementary Source Code.

Figure 3. Dependence of source encoding accuracy on constants. Left panels show the magnitudes of the correlations between sources and responses of a neuron expected to encode source 1: $\left|\mathrm{corr}\left(s_t^{(1)}, x_{t1}\right)\right|$ and $\left|\mathrm{corr}\left(s_t^{(2)}, x_{t1}\right)\right|$. The right panels show the magnitudes of the correlations between sources and responses of a neuron expected to encode source 2: $\left|\mathrm{corr}\left(s_t^{(1)}, x_{t2}\right)\right|$ and $\left|\mathrm{corr}\left(s_t^{(2)}, x_{t2}\right)\right|$. (**A**) Dependence on the constant α that controls the excitability of a neuron, when β is fixed to zero. The dashed line (0.5) indicates the optimal value of $\exp(\alpha_{j1})$. (**B**) Dependence on constant β, when α is fixed as $(\alpha_{j1}, \alpha_{j0}) = (-\ln 2, -\ln 2)$. Elements of β were randomly generated from a Gaussian distribution with zero mean. The standard deviation of β was varied (horizontal axis), where zero deviation was optimal. Lines and shaded areas indicate the mean and standard deviation of the source-response correlation, evaluated with 50 different sequences. The code is provided as Supplementary Source Code.

Our numerical analysis, under assumptions 1–3 mentioned above, shows that a network needs to employ a cost function that entails optimal prior beliefs to perform BSS, or equivalently, causal inference. Such a cost function is obtained when its constants, which do not appear in the variational free energy with the optimal generative model for BSS, become negligible. The important message here is that, in this setup, a cost function equivalent to variational free energy is necessary for Bayes optimal inference (Friston et al., 2006; Friston,

2010).

3.3 Phenotyping networks. We have shown that variational free energy (under the MDP
scheme) is within the class of biologically plausible cost functions found in neural networks.
The neural network's parameters $\phi_j = \ln D^{(j)}$ determine how the synaptic strengths change
depending on the history of sensory inputs and neural outputs; thus, the choice of ϕ_j
provides degrees of freedom in the shape of the generic cost functions under consideration
that determine the purpose or function of the neural network. Among various ϕ_j, only
$\phi_j = (-\ln 2, -\ln 2)$ can make the cost function variational free energy with optimal prior
beliefs for BSS. Hence, one could regard generic neural networks (of the sort considered in
this paper) as performing approximate Bayesian inference under priors that may or may not
be optimal. This result is as predicted by the complete class theorem as it implies that any
response of a neural network is Bayes optimal under some prior beliefs (and cost function).
Therefore, under the theorem, in principle, any neural network of this kind is optimal, when
its prior beliefs are consistent with the process that generates outcomes. This perspective
indicates the possibility of characterising a neural network model—and indeed a real
neuronal network—in terms of its implicit prior beliefs.

These considerations raise the possibility of using empirically observed neuronal
responses to infer the prior beliefs implicit in a neuronal network. For example, the synaptic
matrix (W_{j1}, W_{j0}) can be estimated statistically from response data. By plotting its trajectory
over the training period as a function of the history of a Hebbian product, one can estimate
the cost function constants. If these constants express a near-optimal ϕ_j, it can be
concluded that the network has, effectively, the right sort of priors for BSS. As we have
shown analytically and numerically, a cost function with $(\alpha_{j1}, \alpha_{j0})$ far from $(-\ln 2, -\ln 2)$
or a large deviation of (β_{j1}, β_{j0}) does not provide the Bayes optimal encoder for
performing BSS. Since actual neuronal networks can perform BSS (Isomura et al., 2015;
Isomura & Friston, 2018), it can be envisaged that the implicit cost function will exhibit a
near-optimal ϕ_j.

One can pursue this analysis further and model the responses or decisions of a neural
network using the above-mentioned Bayes optimal MDP scheme under different priors. Thus,
the priors in the MDP scheme can be adjusted to maximise the likelihood of empirical
responses. This sort of approach has been used in system neuroscience to characterise the
choice behaviour in terms of subject specific priors. Please refer to (Schwartenbeck & Friston,
2016) for further details.

Finally, from a practical perspective for optimising neural networks, understanding the
formal relationship between cost functions and variational free energy enables us to specify
the optimum value of any free parameter to realize some functions. In the present setting,
we can effectively optimise the constants by updating the priors themselves, such that they
minimise the variational free energy for BSS. Under the Dirichlet form for the priors, the

implicit threshold constants of the objective function can then be optimised using the
following updates:

$$\phi_j = \ln D^{(j)} = \psi\big(\mathbf{d}^{(j)}\big) - \psi\left(\mathbf{d}_1^{(j)} + \mathbf{d}_0^{(j)}\right),$$

$$\mathbf{d}^{(j)} = d^{(j)} + \sum_{\tau=1}^{t} \mathbf{s}_\tau^{(j)}. \tag{24}$$

Please refer to (Schwartenbeck & Friston, 2016) for further details. In effect, this update will

simply add the Dirichlet concentration parameters, $\mathbf{d}^{(j)} = \left(\mathbf{d}_1^{(j)}, \mathbf{d}_0^{(j)}\right)$, to the priors in

proportion to the temporal summation of the posterior expectations about the hidden states.
Therefore, by committing to cost functions that underlie variational inference and learning,
any free parameter can be updated in a Bayes optimal fashion when a suitable generative
model is available.

4. Discussion

In this work, we investigated a class of biologically plausible cost functions for neural
networks. A single-layer feed-forward neural network with a sigmoid activation function that
receives sensory inputs generated by hidden states (i.e., BSS setup) was considered. We
identified a class of cost functions by assuming that neural activity and synaptic plasticity
minimise a common function *L*. The derivative of *L* with respect to synaptic strengths
furnishes a synaptic update rule following Hebbian plasticity, equipped with
activity-dependent homeostatic term. We have shown that the dynamics of a single-layer
feed-forward neural network—that minimises its cost function—is asymptotically equivalent
to that of variational Bayesian inference under a particular but generic (latent variable)
generative model. Hence, the cost function of the neural network can be viewed as
variational free energy, and biological constraints that characterise the neural network—in
the form of thresholds and neuronal excitability—become prior beliefs about hidden states.
This relationship holds regardless of the true generative process of the external world. We
have focused on discrete latent variable models that can be regarded as special (reduced)
cases of partially observable Markov decision processes (POMDP). However, because our
treatment is predicated on the complete class theorem (Brown, 1981; Wald, 1947), the same
conclusions should, in principle, be reached when using continuous state space models.
Within the class of discrete state space models, it is fairly straightforward to generate
continuous outcomes from discrete latent states; as exemplified by discrete variational
autoencoders (Rolfe, 2016) or mixed models, as described in (Friston, Parr et al., 2017).

One can understand the nature of the constants $\{\alpha_{j1}, \alpha_{j0}, \beta_{j1}, \beta_{j0}\}$ from the biological
and Bayesian perspectives as follows: $\left(\alpha_{j1}, \alpha_{j0}\right)$ determines the firing threshold and thus

controls the mean firing rates. In other words, these parameters control the amplitude of
excitatory and inhibitory inputs, which may be analogous to the roles of GABAergic inputs
and neuromodulators in biological neuronal networks (Pawlak et al., 2010; Frémaux &
Gerstner, 2016; Kuśmierz et al., 2017). At the same time, $\left(\alpha_{j1}, \alpha_{j0}\right)$ encodes prior beliefs
about states, which exert a large influence on the state posterior. The state posterior is
biased if $\left(\alpha_{j1}, \alpha_{j0}\right)$ is selected in a sub-optimal manner—in relation to the process that
generates inputs. Meanwhile, $\left(\beta_{j1}, \beta_{j0}\right)$ determines the accuracy of synaptic strengths that

represent the likelihood mapping of an observation $o_t^{(i)}$ taking 1 (ON state) depending on

hidden states (please compare Equation (8) and Equation (20)). Under a usual MDP setup
where the state prior does not depend on the parameter posterior, the encoder becomes

Bayes optimal when and only when $\left(\beta_{j1}, \beta_{j0}\right) = \left(\vec{0}, \vec{0}\right)$. These constants can represent

biological constraints on synaptic strengths, such as the range of spine growth, spinal
fluctuations, or the effect of synaptic plasticity induced by spontaneous activity independent
of external inputs. Although the fidelity of each synapse is limited due to such internal
fluctuations, the accumulation of information over a large number of synapses should allow
accurate encoding of hidden states in the current formulation.

In previous reports, we have shown that *in vitro* neural networks—comprising a cortical
cell culture—perform BSS when receiving electrical stimulations generated from two hidden
sources (Isomura et al., 2015). Furthermore, we showed that minimising variational free
energy under an MDP is sufficient to reproduce the learning observed in an *in vitro* network
(Isomura & Friston, 2018). Our framework for identifying biologically plausible cost functions
could be relevant for identifying the principles that underlie learning or adaptation processes
in biological neuronal networks, using empirical response data. Here, we illustrated this
potential in terms of the choice of function ϕ_j in the cost functions *L*. In particular, if ϕ_j is
close to a constant $(-\ln 2, -\ln 2)$, the cost function is expressed straightforwardly as a
variational free energy with small state prior biases. In the future work, we plan to apply this
scheme to empirical data and examine the biological plausibility of variational free energy
minimisation.

The correspondence highlighted in this work enables one to identify a generative model
(comprising likelihood and priors) that a neural network is using. The formal correspondence
between neural network and variational Bayesian formations rests on the asymptotic
equivalence between the neural network's cost functions and variational free energy (under
some priors). Although variational free energy can take an arbitrary form, the
correspondence provides biologically plausible constraints for neural networks that implicitly
encode prior distributions. Hence, this formulation is potentially useful for identifying the
implicit generative models that underlie the dynamics of real neuronal circuits. In other
words, one can quantify the dynamics and plasticity of a neuronal circuit in terms of
variational Bayesian inference and learning under an implicit generative model.

The dependence between the likelihood function and the state prior vanishes when the
network uses the optimal threshold to perform inference with a generative process that does
not involve dependence between the likelihood and the state prior. In other words, the
dependence arises from the sub-optimality of the choice of the state prior. This means that
the dependence is due to the degrees of freedom in the choice of the threshold that a neural
network and its cost function possess. Nevertheless, minimisation of the cost function can
render the network Bayes optimal in the variational Bayesian sense, including the choice of
the state prior, as described in the previous section. This is because only variational free
energy with the optimal priors provides the minimum among a class of neural network cost
functions under consideration.

Although we have described the generative process in terms of an MDP, we have ignored
state transitions. This means the generative model in this paper reduces to a simple latent
variable model, with categorical states and outcomes. As noted above, we refer to MDP
models because they predominate in descriptions of variational (Bayesian) belief updating;
e.g., (Friston, FitzGerald et al., 2017). Clearly, many generative processes entail state
transitions, leading to hidden Markov models (HMM). When state transitions depend upon
control variables, we have a POMDP. To deal with such cases, extensions of the current
framework are required, which we hope to consider in future work.

In summary, we first identified a class of biologically plausible cost functions for neural
networks that underlie changes in both neural activity and synaptic plasticity. We then
identified an asymptotic equivalence between these cost functions and the cost functions
used in variational Bayesian formations. Given this equivalence, changes in the activity and
synaptic strengths of a neuronal network can be viewed as Bayesian belief updating; namely,
a process of transforming priors over hidden states and parameters into posteriors,
respectively. Hence, a cost function in this class becomes Bayes optimal when activity
thresholds correspond to appropriate priors in an implicit generative model. In short, the
neural and synaptic dynamics of neural networks can be cast as inference and learning,
under a variational Bayesian formation. This is potentially important for two reasons. First, it
means that there are some threshold parameters for any neural network (in the class
considered) that can be optimised for applications to data, when there are precise prior
beliefs about the process generating those data. Second, in virtue of the complete class
theorem, one can reverse engineer the priors that any neural network is adopting. This may
be interesting when real neuronal networks can be modelled using neural networks of the
class that we have considered. In other words, if one can fit neuronal responses—using a
neural network model parameterised in terms of threshold constants—it becomes possible
to evaluate the implicit priors using the above equivalence. This may find a useful application
when applied to *in vitro* (or *in vivo*) neuronal networks (Isomura, Friston, 2018; Levin, 2013)
or, indeed, dynamic causal modelling of distributed neuronal responses from non-invasive
data (Daunizeau et al., 2011). In this context, the neural network can, in principle, be used as
a dynamic causal model to estimate threshold constants and implicit priors. This 'reverse
engineering' speaks to estimating the priors used by real neuronal systems, under ideal

Bayesian assumptions; sometimes referred to as meta Bayesian inference (Daunizeau et al., 2010).

Acknowledgements

T.I. is funded by RIKEN Center for Brain Science. K.J.F. is funded by a Wellcome Principal Research Fellowship (Ref: 088130/Z/09/Z). The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

References

Albus, J. S. (1971). A theory of cerebellar function. *Math. Biosci.* **10**, 25-61.

Bastos, A. M., Usrey, W. M., Adams, R. A., Mangun, G. R., Fries, P. & Friston, K. J. (2012). Canonical microcircuits for predictive coding. *Neuron* **76**, 695-711.

Belouchrani, A., Abed-Meraim, K., Cardoso, J.F. & Moulines, E. (1997). A blind source separation technique using second-order statistics. *IEEE Trans. Signal Process.* **45**, 434-444.

Brown, G. D., Yamada, S. & Sejnowski, T. J. (2001). Independent component analysis at the neural cocktail party. *Trends Neurosci.* **24**, 54-63.

Brown, L. D. (1981). A complete class theorem for statistical problems with finite-sample spaces. *Ann. Stat.* **9**, 1289-1300.

Cichocki, A., Zdunek, R., Phan, A. H. & Amari, S. I. (2009). *Nonnegative Matrix and Tensor Factorizations: Applications to Exploratory Multi-way Data Analysis and Blind Source Separation.* John Wiley & Sons.

Comon, P. & Jutten, C. (2010). *Handbook of Blind Source Separation: Independent Component Analysis and Applications.* Academic Press.

Daunizeau, J., David, O., & Stephan, K. E. (2011). Dynamic causal modelling: a critical review of the biophysical and statistical foundations. *Neuroimage* **58**, 312-322.

Daunizeau, J., Den Ouden, H. E., Pessiglione, M., Kiebel, S. J., Stephan, K. E., & Friston, K. J. (2010). Observing the observer (I): meta-bayesian models of learning and decision-making. *PLoS One* **5**, e15554.

Dauwels, J. (2007). On variational message passing on factor graphs. *Info. Theory, 2007. ISIT 2007. IEEE Int. Sympo., IEEE*.

Dayan, P., Hinton, G. E., Neal, R. M. & Zemel, R. S. (1995). The Helmholtz machine. *Neural Comput.* **7**, 889-904.

DiCarlo, J. J., Zoccolan, D. & Rust, N. C. (2012). How does the brain solve visual object recognition? *Neuron* **73**, 415-434.

Forney, G. D. (2001). Codes on graphs: Normal realizations. *IEEE Trans. Info. Theory* **47**, 520-548.

Frémaux, N. & Gerstner, W. (2016). Neuromodulated spike-timing-dependent plasticity, and theory of three-factor learning rules. *Front. Neural Circuits* **9**.

Friston, K. (2005). A theory of cortical responses. *Philos. Trans. R. Soc. Lond. B Biol. Sci.* **360**,
815-836.

Friston, K., Kilner, J. & Harrison, L. (2006). A free energy principle for the brain. *J. Physiol.*
Paris **100**, 70-87.

Friston, K. (2010). The free-energy principle: a unified brain theory?. *Nat. Rev. Neurosci.* **11**,
127-138.

Friston, K., Mattout, J., & Kilner, J. (2011). Action understanding and active inference. *Biol.*
Cybern. **104**, 137-160.

Friston, K., FitzGerald, T., Rigoli, F., Schwartenbeck, P. & Pezzulo, G. (2016). Active inference
and learning. *Neurosci. Biobehav. Rev.* **68**, 862-879.

Friston, K., FitzGerald, T., Rigoli, F., Schwartenbeck, P. & Pezzulo, G. (2017). Active inference:
A process theory. *Neural Comput.* **29**, 1-49.

Friston, K. J., Parr, T. & de Vries, B. D. (2017). The graphical brain: belief propagation and
active inference. *Netw. Neurosci.* **1**, 381-414.

George, D. & Hawkins, J. (2009). Towards a mathematical theory of cortical micro-circuits.
PLoS Comput. Biol. **5**, e1000532.

von Helmholtz, H. (1925). *Treatise on physiological optics (Vol. 3).* The Optical Society of
America.

Isomura, T., Kotani, K. & Jimbo, Y. (2015). Cultured cortical neurons can perform blind source
separation according to the free-energy principle. *PLoS Comput. Biol.* **11**, e1004643.

Isomura, T. & Friston, K. (2018). In vitro neural networks minimise variational free energy. *Sci.*
Rep. **8**, 16926.

Knill, D. C. & Pouget, A. (2004). The Bayesian brain: the role of uncertainty in neural coding
and computation. *Trends Neurosci.* **27**, 712-719.

Kullback, S. & Leibler, R. A. (1951). On information and sufficiency. *Ann. Math. Stat.* **22**,
79-86.

Kuśmierz, Ł., Isomura, T. & Toyoizumi, T. (2017). Learning with three factors: modulating
Hebbian plasticity with errors. *Curr. Opin. Neurobiol.* **46**, 170-177.

Lee, T. W., Girolami, M., Bell, A. J. & Sejnowski, T. J. (2000). A unifying information-theoretic
framework for independent component analysis. *Comput. Math. Appl.* **39**, 1-21.

Levin, M. (2013). Reprogramming cells and tissue patterning via bioelectrical pathways:
molecular mechanisms and biomedical opportunities. *Wiley Interdiscip. Rev. Syst. Biol.*
Med. **5**, 657-676.

Linsker, R. (1988). Self-organization in a perceptual network. *Computer* **21**, 105-117.

Mary, D. (1969). A theory of cerebellar cortex. *J. Physiol.* **202**, 437-470.

Newsome, W. T., Britten, K. H., & Movshon, J. A. (1989). Neuronal correlates of a perceptual
decision. *Nature* **341**, 52-54.

Pawlak, V., Wickens, J. R., Kirkwood, A. & Kerr, J. N. (2010). Timing is not everything:
neuromodulation opens the STDP gate. *Front. Syn. Neurosci.* **2**, 146.

Rao, R. P. & Ballard, D. H. (1999). Predictive coding in the visual cortex: a functional
interpretation of some extra-classical receptive-field effects. *Nat. Neurosci.* **2**, 79-87.

Schultz, W., Dayan, P., & Montague, P. R. (1997). A neural substrate of prediction and reward.

Science **275**, 1593-1599.

Schwartenbeck, P., & K. Friston. (2016). Computational phenotyping in psychiatry: a worked

example. *eNeuro* **3**, e0049-16.2016.

Sutton, R. S. & Barto, A. G. (1998). *Reinforcement Learning.* MIT Press, Cambridge, MA, USA.

Tolhurst, D. J., Movshon, J. A., & Dean, A. F. (1983). The statistical reliability of signals in

single neurons in cat and monkey visual cortex. *Vision Res.* **23**, 775-785.

Wald, A. (1947). An essentially complete class of admissible decision functions. *Ann. Math.*

Stat. **18**, 549-555.

Supplementary Information

Reverse engineering neural networks to characterise their cost functions

Takuya Isomura, Karl Friston

Supplementary Tables

<div align="center">Table S1. Correspondence of variables and functions.</div>

	Neural network formation		Variational Bayes formation	
Neural activity	x_{tj}	$\Longleftrightarrow$	$\mathbf{s}_{t1}^{(j)}$	State posterior
Sensory input	o_t	$\Longleftrightarrow$	o_t	Observation
Synaptic strength	W_{j1}	$\Longleftrightarrow$	$\mathrm{sig}^{-1}\left(\mathbf{A}_{11}^{(\cdot,j)}\right)$	
	$\widehat{W}_{j1}$	$\Longleftrightarrow$	$\mathbf{A}_{11}^{(\cdot,j)}$	Parameter posterior
Perturbation term	ϕ_{j1}	$\Longleftrightarrow$	$\ln D_1^{(j)}$	State prior
Threshold	h_{j1}	$\Longleftrightarrow$	$\ln\left(\vec{1} - \mathbf{A}_{11}^{(\cdot,j)}\right) \cdot \vec{1} + \ln D_1^{(j)}$	
Initial synaptic strengths	$\lambda_{j1} \odot \widehat{W}_{j1}^{init}$	$\Longleftrightarrow$	$a_{11}^{(\cdot,j)}$	Parameter prior

Supplementary Methods

S1. Order of the parameter complexity

The order of the parameter complexity term

$$\mathcal{D}_A \equiv \sum_{i=1}^{N_o}\sum_{j=1}^{N_s}\sum_{l\in\{1,0\}}\left\{\left(\mathbf{a}_{\cdot l}^{(i,j)} - a_{\cdot l}^{(i,j)}\right)\cdot\ln\mathbf{A}_{\cdot l}^{(i,j)} - \ln\mathcal{B}\left(\mathbf{a}_{\cdot l}^{(i,j)}\right)\right\} \tag{25}$$

is computed. To avoid the divergence of $\ln\mathbf{A}_{\cdot l}^{(i,j)}$, all the elements of $\mathbf{A}_{\cdot l}^{(i,j)}$ are assumed to

be larger than a positive constant ε. This means that all the elements of $\mathbf{a}_{\cdot l}^{(i,j)}$ are in the

order of t. The first term of Equation (25) becomes $\left(\mathbf{a}_{\cdot l}^{(i,j)} - a_{\cdot l}^{(i,j)}\right) \cdot \ln \mathbf{A}_{\cdot l}^{(i,j)} = \mathbf{a}_{\cdot l}^{(i,j)} \cdot$

$\ln \mathbf{A}_{\cdot l}^{(i,j)} + \mathcal{O}(1)$ since $a_{\cdot l}^{(i,j)} \cdot \ln \mathbf{A}_{\cdot l}^{(i,j)}$ is in the order of 1. Moreover, from Equation (3),

$\mathbf{a}_{\cdot l}^{(i,j)} \cdot \ln \mathbf{A}_{\cdot l}^{(i,j)} = \mathbf{a}_{\cdot l}^{(i,j)} \cdot \left(\ln \mathbf{a}_{\cdot l}^{(i,j)} - \ln\left(\mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)}\right) + \mathcal{O}\left(\left(\mathbf{a}_{\cdot l}^{(i,j)}\right)^{-1}\right)\right) = \mathbf{a}_{\cdot l}^{(i,j)} \cdot$

$\ln\left(\mathbf{A}_{\cdot l}^{(i,j)}\right) + \mathcal{O}(1)$. Meanwhile, the second term of Equation (25) comprises the logarithms of

gamma functions as $\ln \mathcal{B}\left(\mathbf{a}_{\cdot l}^{(i,j)}\right) = \ln \Gamma\left(\mathbf{a}_{1l}^{(i,j)}\right) + \ln \Gamma\left(\mathbf{a}_{0l}^{(i,j)}\right) - \ln \Gamma\left(\mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)}\right)$. From

Stirling's formula,

$$\Gamma\left(\mathbf{a}_{1l}^{(i,j)}\right) = \sqrt{2\pi} \left(\mathbf{a}_{1l}^{(i,j)}\right)^{-\frac{1}{2}} \left(\frac{\mathbf{a}_{1l}^{(i,j)}}{e}\right)^{\mathbf{a}_{1l}^{(i,j)}} \left(1 + \mathcal{O}\left(\left(\mathbf{a}_{\cdot l}^{(i,j)}\right)^{-1}\right)\right) \tag{26}$$

774   holds. The logarithm of $\Gamma\left(\mathbf{a}_{1l}^{(i,j)}\right)$ is evaluated as

775     $\ln \Gamma\left(\mathbf{a}_{1l}^{(i,j)}\right) = \dfrac{1}{2}\ln 2\pi - \dfrac{1}{2}\ln \mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{1l}^{(i,j)}\left(\ln \mathbf{a}_{1l}^{(i,j)} - 1\right) + \ln\left(1 + \mathcal{O}\left(\left(\mathbf{a}_{\cdot l}^{(i,j)}\right)^{-1}\right)\right)$

$$= \mathbf{a}_{1l}^{(i,j)} \ln \mathbf{a}_{1l}^{(i,j)} - \mathbf{a}_{1l}^{(i,j)} + \mathcal{O}(\ln t). \tag{27}$$

777   Similarly, $\ln \Gamma\left(\mathbf{a}_{0l}^{(i,j)}\right) = \mathbf{a}_{0l}^{(i,j)} \ln \mathbf{a}_{0l}^{(i,j)} - \mathbf{a}_{0l}^{(i,j)} + \mathcal{O}(\ln t)$ and $\ln \Gamma\left(\mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)}\right) =$

778     $\left(\mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)}\right)\ln\left(\mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)}\right) - \left(\mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)}\right) + \mathcal{O}(\ln t)$ hold. Thus, we obtain

779     $\ln \mathcal{B}\left(\mathbf{a}_{\cdot l}^{(i,j)}\right) = \mathbf{a}_{1l}^{(i,j)} \ln \mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)} \ln \mathbf{a}_{0l}^{(i,j)} - \left(\mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)}\right)\ln\left(\mathbf{a}_{1l}^{(i,j)} + \mathbf{a}_{0l}^{(i,j)}\right) + \mathcal{O}(\ln t)$

$$= \mathbf{a}_{\cdot l}^{(i,j)} \cdot \ln\left(\mathbf{A}_{\cdot l}^{(i,j)}\right) + \mathcal{O}(\ln t). \tag{28}$$

Hence, Equation (25) becomes

$\displaystyle \mathcal{D}_A = \sum_{i=1}^{N_o}\sum_{j=1}^{N_s}\sum_{l\in\{1,0\}} \left\{\mathbf{a}_{\cdot l}^{(i,j)} \cdot \ln\left(\mathbf{A}_{\cdot l}^{(i,j)}\right) + \mathcal{O}(1) - \left(\mathbf{a}_{\cdot l}^{(i,j)} \cdot \ln\left(\mathbf{A}_{\cdot l}^{(i,j)}\right) + \mathcal{O}(\ln t)\right)\right\} = \mathcal{O}(\ln t).$ (29)

Therefore, we obtain

$\displaystyle F\left(\tilde{o}, Q(\tilde{s}), Q(A)\right) = \sum_{j=1}^{N_s}\sum_{\tau=1}^{t} \mathbf{s}_\tau^{(j)} \cdot \left\{\ln \mathbf{s}_\tau^{(j)} - \sum_{i=1}^{N_o}\ln \mathbf{A}^{(i,j)} \cdot o_\tau^{(i)} - \ln D^{(j)}\right\} + \mathcal{O}(\ln t).$ (30)

Under the current generative model comprising binary hidden states and binary
observations, the optimal posterior expectation of $\mathbf{A}$ can be obtained up to the order of
$\ln t\,/t$ even when the $\mathcal{O}(\ln t)$ term in Equation (30) is ignored. Solving the variation of F

with respect to $\mathbf{A}_{1l}^{(i,j)}$ yields the optimal posterior expectation. From $\mathbf{A}_{0l}^{(i,j)} = 1 - \mathbf{A}_{1l}^{(i,j)}$, we

find

$$\delta F = \sum_{i=1}^{N_o}\sum_{j=1}^{N_s}\sum_{\tau=1}^{t} \mathbf{s}_\tau^{(j)} \cdot \left\{ -\delta \ln \mathbf{A}_{1\cdot}^{(i,j)}\, o_\tau^{(i)} - \delta \ln \left(\vec{1} - \mathbf{A}_{1\cdot}^{(i,j)}\right)\left(1 - o_\tau^{(i)}\right) \right\}$$

$$= t\sum_{i=1}^{N_o}\sum_{j=1}^{N_s} \left\{ -\left(\delta \mathbf{A}_{1\cdot}^{(i,j)} \odot \left(\mathbf{A}_{1\cdot}^{(i,j)}\right)^{\odot -1}\right) \cdot \overline{o_t^{(i)} \otimes \mathbf{s}_t^{(j)}} + \left(\delta \mathbf{A}_{1\cdot}^{(i,j)} \odot \left(\vec{1} - \mathbf{A}_{1\cdot}^{(i,j)}\right)^{\odot -1}\right) \cdot \overline{\left(1 - o_t^{(i)}\right)\mathbf{s}_t^{(j)}} \right\}$$

$$= t\sum_{i=1}^{N_o}\sum_{j=1}^{N_s} \left(\delta \mathbf{A}_{1\cdot}^{(i,j)} \odot \left(\mathbf{A}_{1\cdot}^{(i,j)}\right)^{\odot -1} \odot \left(\vec{1} - \mathbf{A}_{1\cdot}^{(i,j)}\right)^{\odot -1}\right) \cdot \left(\mathbf{A}_{1\cdot}^{(i,j)} \odot \overline{\mathbf{s}_t^{(j)}} - \overline{o_t^{(i)}\mathbf{s}_t^{(j)}}\right) \quad (31)$$

793 up to the order of $\ln t$. Here, $\left(\mathbf{A}_{1\cdot}^{(i,j)}\right)^{\odot -1}$ denotes the element-wise inverse of $\mathbf{A}_{1\cdot}^{(i,j)}$. From

794 $\delta F = 0$, we find

$$\mathbf{A}_{1\cdot}^{(i,j)} = \overline{o_t^{(i)}\mathbf{s}_t^{(j)}} \odot \left(\overline{\mathbf{s}_t^{(j)}}\right)^{\odot -1} + \mathcal{O}\left(\frac{\ln t}{t}\right). \quad (32)$$

796 Therefore, we obtain the same result as Equation (8) up to the order of $\ln t\,/t$.

798 **S2. Derivation of synaptic plasticity rule**

799 We consider synaptic strengths at time t, $W_{j1} = W_{j1}(t)$, and define the change as
800 $\Delta W_{j1} \equiv W_{j1}(t+1) - W_{j1}(t)$. From Equation (15), $h_1'(W_{j1})$ satisfies both

$$h_1'(W_{j1} + \Delta W_{j1}) - h_1'(W_{j1}) = h_1''(W_{j1}) \odot \Delta W_{j1} + \mathcal{O}\left(\left|\Delta W_{j1}\right|^2\right) \quad (33)$$

802 and

$$h_1'(W_{j1} + \Delta W_{j1}) - h_1'(W_{j1}) = -\frac{x_{(t+1)j}o_{t+1} + t\overline{x_{tj}o_t}}{x_{(t+1)j} + t\overline{x_{tj}}} + \frac{\overline{x_{tj}o_t}}{\overline{x_{tj}}}$$

$$\approx -\frac{x_{(t+1)j}o_{t+1}}{t\overline{x_{tj}}} + \frac{\overline{x_{tj}o_t}}{t\overline{x_{tj}}^2}x_{(t+1)j} = -\frac{1}{t\overline{x_{tj}}}\left(x_{(t+1)j}o_{t+1} - h_1'(W_{j1})x_{(t+1)j}\right). \quad (34)$$

805 Thus, we find

$$\Delta W_{j1} = \underbrace{-\frac{h_1''(W_{j1})^{\odot -1}}{t\overline{x}_{tj}}}_{\text{adaptive learning rate}} \odot \left(\underbrace{x_{(t+1)j}o_{t+1}}_{\text{Hebbian term}} - \underbrace{h_1'(W_{j1})x_{(t+1)j}}_{\text{homeostatic term}} \right). \tag{35}$$

807   Similarly,

$$\Delta W_{j0} = \underbrace{-\frac{h_0''(W_{j0})^{\odot -1}}{t\overline{1-x}_{tj}}}_{\text{adaptive learning rate}} \odot \left(\underbrace{(1-x_{(t+1)j})o_{t+1}}_{\text{anti}-\text{Hebbian term}} - \underbrace{h_0'(W_{j0})(1-x_{(t+1)j})}_{\text{homeostatic term}} \right). \tag{36}$$

These plasticity rules express (anti-) Hebbian plasticity with a homeostatic term.

S3. Correspondence between parameter prior distribution and initial synaptic strengths

In general, optimising a model of observable quantities—including a neural network—can
be cast inference, if there exists a learning mechanism that updates the hidden states and
parameters of that model based on observations. (Exact and variational) Bayesian inference
treats the hidden states and parameters as random variables, and thus transforms prior
distributions $P(s_t), P(A)$ into posteriors $Q(s_t), Q(A)$. In other words, Bayesian inference is
a process of transforming the prior to the posterior based on observations $o_1, \dots, o_t$ under a
generative model. From this perspective, the incorporation of prior knowledge about the
hidden states and parameters is an important aspect of Bayesian inference.

The minimisation of a cost function by a neural network updates its activity and synaptic
strengths based on observations under the given network properties (e.g., activation
function and thresholds). According to the complete class theorem, this process can always
be viewed as Bayesian inference. In the main text, we demonstrated that a class of cost
functions—for a single-layer feed-forward network with a sigmoid activation function—has a
form equivalent to variational free energy under a particular latent variable model. Here,
neural activity x_t and synaptic strengths W come to encode the posterior distributions
over hidden states $Q'(s_t)$ and parameters $Q'(A)$, respectively, where $Q'(s_t)$ and $Q'(A)$
follow categorical and Dirichlet distributions, respectively. Moreover, we identified that the
perturbation factors ϕ_j—that characterise the threshold function—correspond to the
logarithm of the state prior $P(s_t)$ expressed as a categorical distribution.

However, one might ask whether the posteriors obtained using the network $Q'(s_t), Q'(A)$
are formally different from those obtained using variational Bayesian inference $Q(s_t), Q(A)$,
since only the latter explicitly considers the prior distribution of parameters $P(A)$. Thus, one
may wonder if the network merely influences update rules that are similar to variational
Bayes but does not transform the priors $P(s_t), P(A)$ into the posteriors $Q(s_t), Q(A)$,
despite the asymptotic equivalence of the cost functions.

837  Below, we show that the initial values of synaptic strengths $W_{j1}^{init}, W_{j0}^{init}$ correspond to

838 the parameter prior $P(A)$ expressed as a Dirichlet distribution, to show that a neural
839 network indeed transforms the priors into the posteriors. For this purpose, we specify the
840 order 1 term in Equation (12) to make the dependence on the initial synaptic strengths
841 explicit. Specifically, we modify Equation (12) as

$$
L_j = \sum_{\tau=1}^{t} \left(f(x_{\tau j}) - \begin{pmatrix} x_{\tau j} \\ 1 - x_{\tau j} \end{pmatrix}^T \left(\begin{pmatrix} W_{j1} \\ W_{j0} \end{pmatrix} o_\tau + \begin{pmatrix} h_{j1} \\ h_{j0} \end{pmatrix} \right) \right)
$$

$$
+ (W_{j1}, W_{j0}) \left(\lambda_{j1} \odot \widehat{W}_{j1}^{init}, \lambda_{j0} \odot \widehat{W}_{j0}^{init} \right)^T
$$

$$
+ \left(\ln(\vec{1} - \widehat{W}_{j1}), \ln(\vec{1} - \widehat{W}_{j0}) \right) \left(\lambda_{j1}, \lambda_{j0} \right)^T, \tag{37}
$$

845 where $\widehat{W}_{j1}^{init} \equiv \mathrm{sig}(W_{j1}^{init})$ and $\widehat{W}_{j0}^{init} \equiv \mathrm{sig}(W_{j0}^{init})$ are the sigmoid functions of the initial

846 synaptic strengths, and $\lambda_{j1}, \lambda_{j0} \in \mathbb{R}^{N_o}$ are row vectors of the inverse learning rate factors
847 that express the insensitivity of the synaptic strengths to the activity-dependent synaptic
848 plasticity. The third term of Equation (37) expresses the integral of $\widehat{W}_{j1}$ and $\widehat{W}_{j0}$ (with
849 respect to W_{j1} and W_{j0}, respectively). This ensures that when $t = 0$ (i.e., when the first term
850 on the right-hand side of Equation (37) is zero), the derivative of L_j is given by $\partial L_j / \partial W_{j1} =$

851 $\lambda_{j1} \odot \widehat{W}_{j1}^{init} - \lambda_{j1} \odot \widehat{W}_{j1}$, and thus $\left(W_{j1}, W_{j0} \right) = \left(W_{j1}^{init}, W_{j0}^{init} \right)$ provides the fixed point of

852 L_j.

853  Similar to the transformation from Equation (12) to Equation (17), we compute Equation
854 (37) as

$$
L = \sum_{j=1}^{N_x} \sum_{\tau=1}^{t} \begin{pmatrix} x_{\tau j} \\ 1 - x_{\tau j} \end{pmatrix}^T \left\{ \begin{pmatrix} \ln x_{\tau j} \\ \ln(1 - x_{\tau j}) \end{pmatrix} - \begin{pmatrix} \ln \widehat{W}_{j1} & \ln(\vec{1} - \widehat{W}_{j1}) \\ \ln \widehat{W}_{j0} & \ln(\vec{1} - \widehat{W}_{j0}) \end{pmatrix} \begin{pmatrix} o_\tau \\ \vec{1} - o_\tau \end{pmatrix} - \begin{pmatrix} \phi_{j1} \\ \phi_{j0} \end{pmatrix} \right\}
$$

$$
+ \sum_{j=1}^{N_x} \left\{ \left(\ln \widehat{W}_{j1}, \ln(\vec{1} - \widehat{W}_{j1}) \right) \left(\lambda_{j1} \odot \widehat{W}_{j1}^{init}, \lambda_{j1} \odot (\vec{1} - \widehat{W}_{j1}^{init}) \right)^T \right.
$$

$$
\left. + \left(\ln \widehat{W}_{j0}, \ln(\vec{1} - \widehat{W}_{j0}) \right) \left(\lambda_{j0} \odot \widehat{W}_{j0}^{init}, \lambda_{j0} \odot (\vec{1} - \widehat{W}_{j0}^{init}) \right)^T \right\}. \tag{38}
$$

858 Note that we used $W_{j1} = \ln \widehat{W}_{j1} - \ln(\vec{1} - \widehat{W}_{j1})$. Crucially, analogous to the correspondence

859 between $\widehat{W}_{j1}$ and the Dirichlet parameters of the parameter posterior $\mathbf{a}_{11}^{(\cdot,j)}$, $\lambda_{j1} \odot \widehat{W}_{j1}^{init}$

860   can be formally associated with the Dirichlet parameters of the parameter prior $a_{11}^{(\cdot,j)}$. Hence,

861   one can see the formal correspondence between the second and third terms on the

862   right-hand side of Equation (38) and the expectation of the log parameter prior in Equation

863   (4):

864
$$\mathrm{E}_{Q(A)}[\ln P(A)] = \sum_{i=1}^{N_o} \sum_{j=1}^{N_s} \ln \mathbf{A}^{(i,j)} \cdot a^{(i,j)}$$

865
$$= \sum_{i=1}^{N_o} \sum_{j=1}^{N_s} \left\{ \ln \mathbf{A}_{\cdot 1}^{(i,j)} \cdot a_{\cdot 1}^{(i,j)} + \ln \mathbf{A}_{\cdot 0}^{(i,j)} \cdot a_{\cdot 0}^{(i,j)} \right\}. \tag{39}$$

866   Furthermore, the synaptic update rules are derived from Equation (38) as

867
$$\begin{cases} \dot{W}_{j1} \propto -\frac{1}{t}\frac{\partial L}{\partial W_{j1}} = \overline{x_{tj}o_t} - \overline{x_{tj}}\widehat{W}_{j1} + \overline{x_{tj}}\phi'_{j1} + \frac{1}{t}\left(\lambda_{j1} \odot \widehat{W}_{j1}^{init} - \lambda_{j1} \odot \widehat{W}_{j1}\right) \\ \dot{W}_{j0} \propto -\frac{1}{t}\frac{\partial L}{\partial W_{j0}} = \overline{(1-x_{tj})o_t} - \overline{1-x_{tj}}\widehat{W}_{j0} + \overline{1-x_{tj}}\phi'_{j0} + \frac{1}{t}\left(\lambda_{j0} \odot \widehat{W}_{j0}^{init} - \lambda_{j0} \odot \widehat{W}_{j0}\right) \end{cases} \tag{40}$$

868   The fixed point of Equation (40) is provided as

869
$$\begin{cases} W_{j1} = \mathrm{sig}^{-1}\left(\left(t\overrightarrow{\overline{x_{tj}}1} + \lambda_{j1}\right)^{\odot-1} \odot \left(t\overline{x_{tj}o_t} + t\overline{x_{tj}}\phi'_{j1} + \lambda_{j1} \odot \widehat{W}_{j1}^{init}\right)\right) \\ W_{j0} = \mathrm{sig}^{-1}\left(\left(t\overline{1-x_{tj}}1 + \lambda_{j0}\right)^{\odot-1} \odot \left(t\overline{(1-x_{tj})o_t} + t\overline{1-x_{tj}}\phi'_{j0} + \lambda_{j0} \odot \widehat{W}_{j0}^{init}\right)\right) \end{cases} \tag{41}$$

Note that the synaptic strengths at $t = 0$ are computed as $W_{j1} = \mathrm{sig}^{-1}\left(\left(\lambda_{j1}\right)^{\odot-1} \odot\right.$

$\left.\left(\lambda_{j1} \odot \widehat{W}_{j1}^{init}\right)\right) = W_{j1}^{init}$. Again, one can see the formal correspondence between the final

values of the synaptic strengths given by Equation (41) in the neural network formation and

the parameter posterior given by Equation (8) in the variational Bayesian formation. As the

Dirichlet parameter of the posterior $\mathbf{a}_{11}^{(\cdot,j)}$ is decomposed into the outer product $\overline{o_t \otimes \mathbf{s}_{t1}^{(j)}}$

and the prior $a_{11}^{(\cdot,j)}$, they are associated with $\overline{x_{tj}o_t}$ and $\lambda_{j1} \odot \widehat{W}_{j1}^{init}$, respectively. Thus,

Equation (8) corresponds to Equation (41). Hence, for a given constant set

$\left\{W_{j1}^{init}, W_{j0}^{init}, \lambda_{j1}, \lambda_{j0}\right\}$, we identify the corresponding parameter prior $P\left(A^{(\cdot,j)}\right) =$

$\mathrm{Dir}\left(a^{(\cdot,j)}\right)$, given by

$$879 \qquad a^{(\cdot,j)} \equiv \begin{pmatrix} a_{11}^{(\cdot,j)} & a_{10}^{(\cdot,j)} \\ a_{01}^{(\cdot,j)} & a_{00}^{(\cdot,j)} \end{pmatrix} = \begin{pmatrix} \lambda_{j1} \odot \widehat{W}_{j1}^{init} & \lambda_{j0} \odot \widehat{W}_{j0}^{init} \\ \lambda_{j1} \odot \left(\vec{1} - \widehat{W}_{j1}^{init} \right) & \lambda_{j0} \odot \left(\vec{1} - \widehat{W}_{j0}^{init} \right) \end{pmatrix}. \qquad (42)$$

In summary, one can establish the formal correspondence between neural network and
variational Bayesian formations, in terms of the cost functions (Equation (4) vs. Equation
(38)), priors (Equation (18) and Equation (42)), and posteriors (Equation (8) vs. Equation (41)).
This means that a neural network successively transforms priors $P(s_t), P(A)$ into posteriors
$Q(s_t), Q(A)$, as parameterised with neural activity, and initial and final synaptic strengths
(and thresholds). Crucially, when increasing number of observations, this process is
asymptotically equivalent to that of variational Bayesian inference, under a specific likelihood
function.