1

A Generalized Similarity Metric

for Predicting Peptide Binding Affinity

Jacob Rodriguez[1,2], Siddharth Rath[1,2,3], Jonathan Francis-Landau[1,4], Yekta Demirci[5],

Burak Berk Üstündağ[6], and Mehmet Sarikaya[1,2,3,7,8*]

[1] GEMSEC, Genetically Engineered Materials Science and Engineering Center, University of

Washington, Seattle, WA 98195, USA

[2] Department of Materials Science and Engineering, University of Washington, Seattle, WA

98195, USA

[3] Molecular Engineering and Science Institute, University of Washington, Seattle, WA 98195,

USA

[4] Department of Mathematics, University of Washington, Seattle, WA 98195, USA

[5] Department of Electrical and Electronics Engineering, Middle East Technical University

[6] Department of Computer and Informatics Engineering, Istanbul Technical University

[7] Department of Chemical Engineering, University of Washington, Seattle, WA 98195, USA

[8] Department of Oral Health Sciences, University of Washington, Seattle, WA 98195, USA

*Corresponding Author

E-mail: sarikaya@uw.edu

Abstract

The ability to capture the relationship between similarity and functionality would enable the predictive design of peptide sequences for a wide range of implementations from developing new drugs to molecular scaffolds in tissue engineering and biomolecular building blocks in nanobiotechnology. Similarity matrices are widely used for detecting sequence homology but depend on the assumption that amino acid mutational frequencies reflected by each matrix are relevant to the system in which they are applied. Increasingly, neural networks and other statistical learning models solve problems related to functional prediction but avoid using known features to circumvent unconscious bias. We demonstrated an *iterative* alignment method that enhances predictive power of similarity matrices based on a similarity metric, the Total Similarity Score. A generalized method is provided for application to amino acid sequences from inorganic and organic systems by benchmarking it on the debut quartz-binder set and 3 peptide-protein sets from the Immune Epitope Database. Pearson and Spearman Rank Correlations show that by treating the gapless Total Similarity Score as a predictor of relative binding affinity, prediction of test data has a 0.5-0.7 Pearson and Spearman Rank correlation. with respect to size of the dataset. Since the benchmarks used herein are from a solid-binding peptide and a protein-peptide system, our proposed method could prove to be a highly effective general approach for establishing the predictive sequence-function relationships of among the peptides with different sequences and lengths in a wide range of biotechnology, nanomedicine and bioinformatics applications.

Author Summary

The significance of this work is to expand the applicability of a known metric for describing the function of tiny proteins also called peptides. The Total Similarity Score (TSS) can describe how 'similar' a peptide, or a group of peptides are to another group of sequences with a known or suspected function. A peptide/group of peptides will always have a high TSS if it contains the same or 'similar' amino acids in the same positions. This metric can therefore be used to select peptides for useful functions based purely on conserved amino acids in unknown positions. The greedy search algorithm used to learn how similar amino acids are to each other has been shown to be marginally effective in this larger dataset. Therefore, we argue that the TSS metric is a highly useful one for predicting peptide affinity but a different machine learning algorithm should be applied to make full use of it.

Introduction

The rapid development of target-specific drugs relies on the development of high-throughput and accurate methods of modelling molecular structures. The biology, pharmacology and bioengineering communities are interested in building widely applicable methods founded in predictive design of molecules that have specificity for biological targets, analytes and biomarkers [1-4]. Small peptides (7 to 40 amino acids) have high potential as both therapeutics [5-7] and high-performance molecular building blocks [8-10] due their diversity of binding affinity both quantitatively and specifically across 2D- and nano-materials.

Towards more accurate and fast predictions of affinity or conformation that would enable high-throughput drug and targeting peptide design, among some of the best

performing methodologies are stochastic models such as NetMHCpan-4.0 [11],

DeepMHC [12] and MHCflurry [13]. These methods use little or no prior information about

the peptides to ensure only random walk identifies relevant patterns. By avoiding

physiochemical properties published in the literature, these models are subject to

inconsistent predictions between test peptide sets even for the same protein target.

Alignment-free neural networks models have shown substantial success in predicting the

binding affinity of the Immune Epitope Database (IEDB, www.iedb.org) datasets [12,14].

To avoid overfitting, they require hundreds of thousands of sequences and are not

optimized for gaps in the binding domains [15,16].

The current state of the art in modelling tools, e.g., molecular dynamics (MD),

molecular mechanics (MM), and Monte Carlo (MC) based methods, predict overall

conformation from which binding energies may be calculated [9]. These approaches

utilize knowledge-based force fields [17,18] and energy minimization techniques to

sample the most probable structures [19]. Though solving conformational structures will

likely enable the most accurate predictions of peptide function, to date structural

information is avoided in models requiring large amounts of data. This is mostly due to

the large computational cost associated with calculating molecular structures of these

large molecules, which is a barrier to the development of both highly complex neural

networks and current MD/MC-based methods. The deeper networks rely less on learning

in space constrained by verified physiochemical trends and more on the number of

parameters and computational power. Less complex and more interpretable models

integrate known patterns while leaving space for optimization methods to learn unknown

patterns in the sequences.

Current alignment-based methods for high-throughput prediction functionality of

amino acid sequence information can be separated into two groups; pairwise [20-22] and

multiple sequence [16,23,24]. In general, pairwise alignment is ideal for shorter

sequences due to its higher computational cost per amino acid and is widely accepted to

be the optimal alignment [25]. Multiple sequence alignment is considered more

appropriate for longer sequences with suspected consensus domains. In both methods

Point Accepted Mutation (PAM) and Blocks Substitution Matrix (BLOSUM) matrices are

still the most widely used, and there are permutations of these matrices to serve more

specific tasks [17,26,27]. Overall, the limitations of PAM and BLOSUM provided

inspiration and guidance for generating matrices with increased accuracy based on larger

and more complete datasets [11,28-30]. Matrices such the PMBEC [27], have been

generated based on the two models that produce a minor increase in performance but

ultimately are vulnerable to the same factors as their predecessors [11]. In 2008, for

example, a miscalculation was discovered in the clustering protocol of the BLOSUM

matrix [31]. Despite extensive characterization of the mistake, BLOSUM is still the

standard for one of the largest alignment-capable databases available to date, BLAST

[11].

In contrast with PAM, BLOSUM, PMBEC [27] and the SAUSAGE Force Field

Matrix [17], the novel OCSimM and 8 property group-derived matrices (A-RMat) were

calculated from 527 physiochemical properties of amino acids [32,33]. AAindex is a vast

resource of high-quality amino acid properties collected from literature dating from the

mid-sixties to today [32,33]. Typically, either variable reduction methods (Principal

Component Analysis [6,34] or Factor Analysis [35]) or heuristic selection is performed to

shrink the huge dataset of over 550 amino acid properties to obtain an interpretable

solution. Variable reduction has significant advantages over a global analysis of

heuristically grouped properties because human error cannot influence the potential

relationships observed [35]. However, these methods still assume the relationship

between high-specificity peptides and low-specificity peptides is described by

physiochemical properties.

Previously, we have successfully used a matrix optimization method to a group of

peptides that were categorized as strong, weak or medium binders based on their binding

affinities to crystalline silica, quartz, using 40 sequences that were originally genetically

selected using M13 phage display peptide library [25]. The novel metric called the Total

Similarity Score (TSS_{A-B}) describes the average Global Alignment score of all peptides

from group-A to all of group-B [25]. The TSS score quantifies the similarity of a peptide to

a functional peptide set (i.e. affinity for a solid material). By keeping random changes to

a similarity matrix that increased the TSS_{S-S} (TSS of strong binders with strong binders),

and decrease the TSS_{S-W} (TSS of strong binders with weak binders), a similarity matrix

was obtained that could predict the semi-quantitative affinity of quartz-binding peptides

with 70-80% success. Despite its high predictive power, TSS has never been applied to

MHC data. Using the MHC data, here we demonstrate its implementation that strongly

suggests that TSS could be a predictive method for establishing sequence-function

relationships in a variety of large sequence-based data sets.

The reliable prediction of peptide binding affinity has already led to ground-

breaking advances in oral health science and will continue to do so in areas requiring a

well-described soft interface between peptides and solid-state inorganic materials

[5,10,36]. Though affinity prediction is not the most descriptive or important

characterization of peptides, understanding the relationship among solid-binding peptides

[10] has led to many technologies such as sensors with high sensitivity, [5] assemblers in

nanotechnology, and tiny enzymes in biomineralization [37].

Materials & Methods

Iterative Alignment (IA) creates a scoring matrix that provides scores correlating

with the positional composition of a peptide when compared to a weak and a strong

binding set. When a sequence of interest has high similarity to these strong binders and

low similarity to the weak binders, the sequence was given a higher TSS_{Seq-S} (TSS of one

sequence to strong binders)and lower TSS_{Seq-W} (TSS of one sequence to weak binders).

Training the similarity matrix was done by increasing the differences in TSS to strong

binders for two binding affinity classes, strong and weak.

First, peptides were sorted by their affinity values shown in Fig 1A. The generated

trend was characterized by the positive correlation TSS_{Seq-S} with binding affinity visualized

in the lower bar chart of Fig 1B. Once training was finished, we calculated the TSS to

strong binders a final time for all peptides in the set. The results from the trained randomly

initialized matrix (RandM) are shown in the scatterplot in Fig 1C. Next, several methods

are used to measure correlation of TSS_{Seq-S} with the experimental affinity including

Pearson and Spearman Rank correlation, Root Mean Square Error and a binary

classification scheme (binder/nonbinder prediction). A sample of these results are

demonstrated in Fig 1D.

Fig 1. Schematic of Iterative Alignment Procedure.

Data Collection

Peptide sequences with affinity for HLA alleles were obtained from the Immune Epitope Database (www.iedb.org), a common source of training and benchmark data for predictive models of peptide function [14]. Quartz binders and the Quartz I matrix were provided by GEMSEC at the MSE Department of the University of Washington [25]. The Amino Acid Index (AAindex) is a large database of amino acid properties that were used to calculate the cluster matrices (A-RMat) [32,33]. Within the site, similarity matrices calculated by various studies are also provided, and it was from here that the SAUSAGE force-field matrix was also chosen [17]. The PMBEC scoring-matrix [27] was included as it was derived directly from binding affinity data from MHC-I. In general, the matrices chosen are a diverse subsection of the types of information used to describe differences between amino acids and therefore were an appropriate selection for yielding conclusions about how the seed matrix would affect the overall result.

Novel Matrix Calculation

To explore the possibility that certain properties, e.g., hydrophobicity, electrical properties, amino acid composition etc., may make better seed matrices, 9 similarity

matrices were calculated based on clusters optimized by Saha *et. al* [38]. After grouping

properties by alpha-helix or beta-sheet propensies, composition, electrical, hydrophobic,

and intrinsic characteristics, residue propensity, and physicochemical properties, we

performed Principal Component Analysis (PCA) on each group and all groups combined.

Using a Python library downloaded from scikit-learn.org [39], the principal components

were calculated which were most representative of the internal variation of property

subset. Because these principal components are orthogonal, Euclidean distance was the

most appropriate for calculating the actual similarity matrix. By calculating the difference

between the principal components of two amino acids, we were able to calculate nine (20

x 20) similarity matrices describing their quantitative physiochemical differences. These

matrices will be referred to for the rest of the work as AMat (Alpha-helix propensity), BMat

(Beta-sheet propensity), CMat (Composition), EMat (Electric), HMat (Hydrophobicity),

IMat (Intrinsic propensity), PMat (Physiochemical), RMat (Residue propensity) and

OCSim [Orthogonal Component Similarity matrix (all properties)].

Code Implementation

The newest version of the algorithm was written in Python, using a gapless scoring

method to calculate TSS scores. The gap calculation was excluded to rectify the issue

created by the changing gap position in each sequence. Per peptide-peptide scoring

operation (300 strong binders x 9000 peptides for *HLA-A*02:01*), per iteration (5000 due

to randomly changing mutabilities) the gap is placed in one position. We suspected the

gap made recognizing the consistent amino acids between iterations difficult. The debut

implementation of the method [25] iteratively aligned less than 20 peptides per strong and

weak binding group. The IEDB dataset being substantially larger (i.e., over 9000 peptides

for the largest set) required the inclusion of more peptides per set in order to capture as

many of the features pertaining to binding affinity as possible.

Designation of Affinity Classes

The peptide sequences were first ordered by $-pIC_{50}$, and then segregated into

groups dependent on their affinity. For example, all peptides within the 3 chosen alleles

(*HLA-A*02:01* [9-length], *HLA-A*02:02* [10-length] and *HLA-A*03:01* [9-length]) with a -

pIC_{50} of 0 were named 'strong' (S) binders, creating 3 sets. The 'weak' (W) binders for

the 9-length and 10-length sets were those with a $-pIC_{50}$ of -5 to -7. From these, 80% of

a strong or weak peptide list was randomly chosen as training sets to obtain cross-

validation. To show the flexibility of the method, we chose several groups with differing

distributions to demonstrate the improvements are still achieved when only partial data is

available.

Matrix Training

To begin, two lists of peptide sequences (at least 6 in each) must be obtained, one

with higher 'internal similarity' and lower 'internal similarity'. Critically, peptides with high

binding affinity for the same material will also higher 'internal similarity' and those with low

affinity will have low 'internal similarity' [25]. Internal similarity refers to the sum of Global

Alignment (GA) scores of each peptide within a list to every other peptide within the same

list. Global Alignment is commonly referred to as the Needleman-Wunsch algorithm or

optimal alignment as it always obtains the optimum number and placement of gaps,

resulting in the most similar domains being recognized and aligned when they are

consensus [20]. It requires a similarity matrix to obtain scores between matches or

mismatches of amino acids, and many of these have been calculated throughout the

literature. For small peptides, it may not be the ideal alignment method considering their

short length makes scoring the entire sequence important.

While guaranteeing the optimal alignment, Global Alignment is computationally

very expensive and therefore impractical to apply to larger groups of sequences than

those used in previous work [25] (10 - 20 sequences per strong and weak group). The

updated method departs from the alignment methodology and scores peptides by their

positional composition only, which is essentially the same score without the gap

calculation. By greatly expanding the number of peptides used in the strong group, the

significance of GA is reduced due to a wider range of domain types and locations being

represented. In general, scoring with more peptides is just as beneficial as scoring a few

with GA. Global Alignment expands the number of sequences a peptide will have

consensus with; in a way making it appear as many peptides in the strong group.

However, the domains being aligned and the values scoring the alignments are different

from one iteration to another, resulting in a lack of consistent scoring between sequence

domains. Therefore, we justify the departure from GA as both a necessity and a benefit

to ensure the method runs within a practical time constraint.

The procedure for one iteration can be described in 6 steps (see Fig 2). After the

affinity classes have been designated (Fig 2, Step 2), a seed similarity matrix is used to

calculate TSS_{S-S} and TSS_{S-W} (same as internal but to separate group of peptides)

similarity for each peptide (Fig 2, Step 3). External similarity is calculated by aligning the

strong binders to each in the low internal similarity group. Within each list, the average is

found and form the cost functions for IA, the Total Similarity Score Strong-Strong (TSS_{S-}

$_{S}$)   and   Total   Similarity   Score   Strong-Weak   (TSS_{S-W}),   respectively.

Mathematically, the expression for general TSS calculation is given by Equation (1) as

$$TSS_{A-B}\left[|A|\,_{xa}^{ya} - |B|\,_{xb}^{yb}\right] = 1/[xa \times (xb - \delta_{AB})] \times \sum_{i=1,j=1}^{xa,xb} PSS_{ij}(1 - \delta_{ij}\delta_{AB})$$

248   (1)

where, TSS_{A-B} is the Total Similarity Score (TSS) between peptide sets A and B, PSS_{ij} is

the pairwise similarity score (PSS) between sequences i and j of sets A and B

respectively, *xa* and *xb* are the total number of sequences in sets A and B, and *δ* is the

Kronecker delta function (δ_{ij} = 1 if δ_{ij} = 0).

After the values of TSS_{S-S} and TSS_{S-W} have been calculated and saved for the first

time, the similarity matrix is perturbed by making random changes (1-20) to the matrix

values by either adding 1 or subtracting 1 (Fig 2, Step 3). Using the new matrix, TSS_{S-S}

and TSS_{S-W} are calculated again and compared with the previous TSS (Fig 2, Step 4). A

change to the matrix is considered beneficial if $TSS_{S-S,NEW}$ is greater than $TSS_{S-S,OLD}$ and

$TSS_{S-W,NEW}$ is less than $TSS_{S-W,OLD}$. Beneficial changes are saved for the next round (Fig

2, Step 5). If the change is not beneficial, then the previous matrix (before mutation) is

perturbed again and the process repeats (Fig 2, Step 5). The algorithm could continue

indefinitely but we considered the matrix converged when over 5,000 iterations occurred

without a beneficial change (Fig 2, Step 6).

Fig 2. Schematics of matrix training procedure.

Benchmark with the Previous Work

To prove the updated methodology was up to par with the original implementation

of the procedure, we obtained the Quartz I matrix and silica binding peptides used by

Oren *et. al* [25] The same procedure was followed by mutating PAM250 and training on

the same strong and weak groups. After training, IA converged on a matrix capable of

predicting binding affinity with similar accuracy to the debut implementation [25]. Using a

Pearson correlation of the external similarity to affinity of any silica binding peptide to the

group of strong binders designated by [25], we calculated a 51% correlation with our

matrix. Previous work obtained a 46% correlation with Quartz I, demonstrating the

equivalent capabilities of the updated method. P-values for these correlations were less

than 0.0005.

Application to MHC Data

To test whether the modified methodology would perform on organic materials, we

needed a set of peptides with affinity for a biological target. The IEDB provides high quality

sequence data including binding affinities for multiple Major-Histocompatibility

Complexes which provided a perfect opportunity to test performance [14]. By designating

peptides with -pIC_{50} (negative logarithm of IC_{50}) of 0 as strong-binders peptides and weak-

binders having -pIC_{50} of -5 to -7 (Fig 2, Step 2) from three alleles (*HLA-A*02:01*, *HLA-*

A*03:01, and *HLA-A*02:02*), we optimized 14 similarity matrices capable of ranking

peptides by their binding affinities via their total similarity to strong binders. Matrices were

optimized by iteratively perturbing a seed similarity matrix and keeping those changes

which ultimately increased the self-similarity of the strong binders and cross-similarity of

the strong with weak binders.

Results/Discussions

Cross-Similarity Analysis. Fig 3 shows the cross-similarity results of 5 subsets

of peptides deemed Strong (S; -pIC_{50}:0), Less Strong (LS; -pIC_{50}:-1 to -2), Medium (M; -

pIC_{50}:-2 to -3), Medium Weak (MW; -pIC_{50}:-3 to -4) and Weak (W; -pIC_{50}:-5 to -7) based

on their binding affinity to alleles MHC-I *HLA-A*02:01* for all matrices before and after

training. Each set of bars per matrix was normalized by the largest value of both before

and after results. In addition, these bars are the results of 5 average TSS subsets (80%

randomly chosen from each affinity class). Previous work showed the TSS of a peptide

with high similarity to the peptides that are strong binders of a solid-state material

indicates that the peptide in question likely also has strong binding capability [25].

Therefore, the average TSS of peptides with an affinity for a protein should decrease with

their experimental affinity. Fig 3 shows that before training (yellow bars) the trend is

somewhat present but not very defined (Strong x Weak is comparable to Strong x Less-

Weak) but after training (blue bars) the trend is very pronounced. For each matrix and

across all three alleles (see S1 and S2 Figs) we observe average TSS when grouped by

affinity class to strong binders correlated with experimental affinity. Most notably, the

randomly initialized matrix RandM despite having no initial correlation was able to show

the trend as definitively as the others after matrix training.

Fig 3. External similarity results for matrices before and after training with *HLA-A 02:01* binders.

Correlations with experimental affinity. In the previous work, binding affinity was predicted by placing peptides into semi-quantitative groups of strong, medium and weak by their total similarity score to the strong binding peptide sequences of quartz [25]. The trend of decreasing TSS_{Seq-S} was correlated with experimental affinity by using TSS_{Seq-S} as a threshold to determine whether a peptide would fall into an affinity class (binary classification) [25]. Though significant predictability (70-80%) was obtained using the semi-quantitative scoring method, it falls short of the trend prediction needed to be comparable with MHCFlurry, NetMHC and DeepMHC [12,13,37]. To enable more direct comparisons the Pearson correlation coefficient (linear, Fig 4C) and Spearman rank

correlation coefficient (nonlinear, Fig 4B) were calculated, which can determine whether

the predicted binding affinity trend (TSS to strong binders) matches the experimental

binding affinity trend. In addition, a classifier scheme is included that can recognize

whether a peptide is a strong or weak binder by the magnitude of its TSS_{Seq-S}. Further, a

root mean square error (RMSE) is calculated from the normalized trend of TSS and RMSE

to get an idea of close the TSS scores are to the experimental affinity (Fig 4A).

Fig 4. RMSE (A), Spearman Rank (B), and Pearson (C) correlations for TSS trends

calculated using trained and untrained matrices.

TSS_{Seq-S} were then correlated with those of the experimental affinity. The values

of TSS_{Seq-S} served as the predicted binding affinity ranking and was correlated with the

experimentally determined binding affinity using Pearson and Spearman Rank functions.

Fig 4 shows the score of each correlation for trained matrices and untrained matrices.

The error bars are one standard deviation from the average of these scores. All p-values

were less than 0.0005, except for in the case of RandM. Considering the substantially

less amount of data used (~350 peptide sequences for *HLA-A*02:01*) compared with

DeepMHC and NetMHC (80% of the full set;~7200 sequences for *HLA-A*02:01*), the

range of 0.5-0.7 is significant and is reflective of mutability information being captured. In

addition, the RMSE scores show that in general one TSS score is insufficient to describe

the exact binding affinity. While it is clear from the improvement in Pearson and Spearman

Rank correlation that these matrices are capturing some similarity information using the

method, no matrix alone can produce a TSS ranking exactly correlating with the rest of

the set. The integration of several TSS rankings into a single score could prove to be a

relevant predictor if they are capturing diverse similarity information unique to their matrix

values.

Binary Classification. Sensitivity and specificity were also recorded as a measure

of binary prediction accuracy, shown in Fig 5A and Fig 5B respectively. A

binder/nonbinder classification was performed via observing peptides conserved as

binders through the magnitude of their TSS_{Seq-S}. The sequences having greater than 500

IC_{50} [12] were considered binders. Therefore, peptides given a predicted ranking above

the TSS_{Seq-S} threshold correlating with the 500 IC_{50} [12] bar were considered predicted

binders. True positives and negatives, and false positive and negatives were calculated

by observing which predicted binders were also in the actual binder group.

Fig 5. Results of classification analysis

Across all the matrices a similar specificity/sensitivity was observed before and

after training. This indicates the cost function did not improve the ability of the

calculated/literature matrices to classify peptides based on TSS values. RandM showed

marked improvement across all the alleles but yields lower accuracies than other

matrices. This demonstrates that information can be integrated into a similarity matrix up

to a limit. In general, the prediction metrics show that the separation of TSS_{S-S} and TSS_{S-W}

W may not be the appropriate cost function to improve a predictive model. However,

TSS_{Seq-S} is a highly relevant predictor of affinity. Though the model was trained on only

the dominant features of the peptide set represented by strong binders, the affinity trend

was generally conserved by TSS_{Seq-S} scoring.

Conclusions and Future Work

The predicted correlation range of 0.5-0.7 determined by Pearson and Spearman

Rank of the similarity matrix methodology demonstrates similarity matrices can predict

functionality (i.e. solid substrate binding specificity) of peptides using the Total Similarity

Score. Previous work provided definitive evidence concluding the average similarity score

(TSS) of a peptide towards strong binding peptides of an inorganic solid material is

positively correlated with the binding affinity of that peptide. Using the Total Similarity

Score, we modified a computational method and applied it to a substantially larger dataset

to demonstrate that across organic and inorganic materials the metric applies. Though

we use substantially lower training data than other methods, similarity matrices were

obtained that recognize the dominant features of the strongest binding peptides, which in

turn describe those of the weaker binders. Therefore, the strongest binders of the full set

can adequately describe the behavior of the remaining peptides Though the training

method is insufficient to produce a trend capable of ranking affinity with comparable

accuracy to other MHC predictors, we postulate that based on the diversity of the matrices

trained that they are capturing different subsections of the total similarity information.

Therefore, integrating the trends of multiple matrices into a single score would produce

comparable accuracy even when trained on substantially less data. In this work, we show

that we can capture similarity information using different matrices and that TSS to strong

binders is a relevant predictor of affinity in both organic and inorganic systems.

To uncover the relationship between $TSS_{Seq\text{-}S}$ and the experimentally measured

affinity, the future work would involve integrating the TSS score with recent statistical

learning techniques. If the matrix cannot be optimized, then the value of $TSS_{Seq\text{-}S}$ may not

be the highest achievable even if the sequence is a strong binder. The sequences with

amino acids in similar positions to the strong binding group will, however, tend to give the

same average score. Therefore, if the goal is to predict the similarity of sequences based

on their positional composition, conserving the common score range will also retain their

sequence information. An additional problem may also arise when considering the

diversity of the strong binding group. If a given peptide is a strong binder having a

completely unique sequence compared to those of the other strong-binding peptides, it

will have a low $TSS_{Seq\text{-}S}$. TSS scoring assumes that weak and medium binders are

mutations of stronger binders. Future methods will capitalize on the information hidden

within weak/medium binders and use it to describe the full strong binding space. The full

results, gapless Iterative Alignment Python program for calculating similarity matrices,

and all the data used to train the matrices are located online on GitHub

(https://github.com/Sarikaya-Lab-GEMSEC/Iterative-Alignment-Gapless).

Acknowledgements

We appreciate the data sets and computational facilities provided GEMSEC labs at the

University of Washington.

We declare there were no conflicts of interest for this work.

References

1. Georgoulia PS, Glykos NM. Molecular simulation of peptides coming of age:

Accurate prediction of folding, dynamics and structures. Archives of Biochemistry

and Biophysics. 2019;664:76-88.

2. Minami S, Sawada K, Chikenji G. MICAN: a protein structure alignment

algorithm that can handle Multiple-chains, Inverse alignments, Cα only models,

Alternative alignments, and Non-sequential alignments. BMC Bioinformatics.

2013;14(1):24.

3. Muthukrishnan S, Puri M. Harnessing the evolutionary information on oxygen

binding proteins through Support Vector Machines based modules. BMC

Research Notes. 2018;11(1).

4. Nakai K, Kidera A, Kanehisa M. Cluster analysis of amino acid indices for

prediction of protein structure and function. "Protein Engineering, Design and

Selection". 1988;2(2):93-100.

5. Khatayevich D, Page T, Gresswell C, Hayamizu Y, Grady W, and Sarikaya M,

Selective Detection of Target Proteins by Peptide-Enabled Graphene Biosensor,

Small, 2014; 10(8): 1505-1513.

6. Hayamizu Y, So CR, Dag S, Page TS, Starkebaum D, Sarikaya M. Bioelectronic interfaces by spontaneously organized peptides on 2D atomic single layer materials. Scientific Reports. 2016 Sep 22;6:33778.

7. Fosgerau K, Hoffmann T. Peptide therapeutics: current status and future directions. Drug Discovery Today. 2015;20(1):122-128.

8. Barbosa AJM, Oliveira AR, Roque ACA. Protein- and Peptide-Based Biosensors in Artificial Olfaction. *Trends Biotechnol.* 2018;36(12):1244–1258. doi:10.1016/j.tibtech.2018.07.004

9. Hughes ZE, Walsh TR. What makes a good graphene-binding peptide? Adsorption of amino acids and peptides at aqueous graphene interfaces. Journal of Materials Chemistry B. 2015;3(16):3211-21.

10. Sarikaya M, Tamerler C, Jen AK-Y, Schulten K, Baneyx F. Molecular biomimetics: nanotechnology through biology. Nature Materials. 2003;2(9):577–85.

11. Jurtz V, Paul S, Andreatta M, Marcatili P, Peters B, Nielsen M. NetMHCpan-4.0: Improved Peptide–MHC Class I Interaction Predictions Integrating Eluted Ligand and Peptide Binding Affinity Data. The Journal of Immunology. 2017;199(9):3360-8.

12. Hu J, Liu Z. DeepMHC: Deep Convolutional Neural Networks for High-performance peptide-MHC Binding Affinity Prediction. Cold Spring Harbor Laboratory; 2017.

13. Odonnell TJ, Rubinsteyn A, Bonsack M, Riemer AB, Laserson U,

Hammerbacher J. MHCflurry: Open-Source Class I MHC Binding Affinity

Prediction. Cell Systems. 2018;7(1).

14. Vita R, Mahajan S, Overton JA, Dhanda SK, Martini S, Cantrell JR, et al. The

Immune Epitope Database (IEDB): 2018 update. Nucleic Acids Research.

2018;47(D1).

15. Wang S, Ma J, Peng J, Xu J. Protein structure alignment beyond spatial

proximity. Scientific Reports. 2013;3(1).

16. Wright ES. DECIPHER: harnessing local sequence context to improve protein

multiple sequence alignment. BMC Bioinformatics. 2015;16(1).

17. Dosztanyi Z, Torda AE. Amino acid similarity matrices based on force fields.

Bioinformatics. 2001;17(8):686-99.

18. Dasetty S, Barrows JK, Sarupria S. Adsorption of Amino Acids on Graphene:

Assessment of Current Force Fields. American Chemical Society (ACS); 2019.

19. Alford RF, Leaver-Fay A, Jeliazkov JR, O'Meara MJ, DiMaio FP, Park H, et al.

The Rosetta all-atom energy function for macromolecular modeling and design. J

Chem Theory Comput. 2017;13(6):3031–48.

20. Needleman SB, Wunsch CD. A general method applicable to the search for

similarities in the amino acid sequence of two proteins. Journal of Molecular

Biology. 1970;48(3):443-53.

21. Jones DT, Taylor WR, Thornton JM. The rapid generation of mutation data

matrices from protein sequences. Bioinformatics. 1992;8(3):275-82.

22. Brown P, Pullan W, Yang Y, Zhou Y. Fast and accurate non-sequential protein

structure alignment using a new asymmetric linear sum assignment heuristic.

Bioinformatics. 2015;32(3):370-7.

23. Deorowicz S, Debudaj-Grabysz A, Gudyś A. FAMSA: Fast and accurate

multiple sequence alignment of huge protein families. Scientific Reports.

2016;6(1).

24. Thompson JD, Higgins DG, Gibson TJ. CLUSTAL W: improving the sensitivity

of progressive multiple sequence alignment through sequence weighting, position-

specific gap penalties and weight matrix choice. Nucleic Acids Research.

1994;22(22):4673–80.

25. Oren EE, Tamerler C, Sahin D, Hnilova M, Seker UOS, Sarikaya M, et al. A

novel knowledge-based approach to design inorganic-binding peptides.

Bioinformatics. 2007;23(21):2816-22.

26. Keul F, Hess M, Goesele M, Hamacher K. PFASUM: a substitution matrix from

Pfam structural alignments. BMC Bioinformatics. 2017;18(1).

27. Kim Y, Sidney J, Pinilla C, Sette A, Peters B. Derivation of an amino acid

similarity matrix for peptide:MHC binding and its application as a Bayesian prior.

BMC Bioinformatics. 2009;10(1):394.

28. Andreatta M, Nielsen M. Gapped sequence alignment using artificial neural

networks: application to the MHC class I system. Bioinformatics. 2015;32(4):511-

7

29. Han Y, Kim D. Deep convolutional neural networks for pan-specific peptide-

MHC class I binding prediction. BMC Bioinformatics. 2017;18(1).

30. Liang G, Yang L, Chen Z, Mei H, Shu M, Li Z. A set of new amino acid

descriptors applied in prediction of MHC class I binding peptides. European

Journal of Medicinal Chemistry. 2009;44(3):1144-54.

31. Hess M, Keul F, Goesele M, Hamacher K. Addressing inaccuracies in

BLOSUM computation improves homology search performance. BMC

Bioinformatics. 2016;17(1).

32. Kawashima S. AAindex: Amino Acid index database. Nucleic Acids Research.

2000;28(1):374-.

33. Kawashima S, Pokarowski P, Pokarowska M, Kolinski A, Katayama T,

Kanehisa M. AAindex: amino acid index database, progress report 2008. Nucleic

Acids Research. 2007;36(Database):D202-D5.

34. Hemmateenejad B, Miri R, Elyasi M. A segmented principal component

analysis—regression approach to QSAR study of peptides. Journal of Theoretical

Biology. 2012;305:37-44.

35. Atchley W, Zhao J, Fernandes A, Druke T. Solving the protein sequence metric

problem. Proceedings of the National Academy of Sciences. 2005;102(18):6395-

6400.

36. Doytchinova IA, Walshe V, Borrow P, Flower DR. Towards the chemometric

dissection of peptide – HLA-A*0201 binding affinity: comparison of local and global

QSAR models. Journal of Computer-Aided Molecular Design. 2005;19(3):203-12.

37. Dogan S, Fong H, Yucesoy DT, Cousin T, Gresswell C, Dag S, Huang G,

Sarikaya M. Biomimetic tooth repair: amelogenin-derived peptide enables in vitro

remineralization of human enamel. ACS Biomaterials Science & Engineering. 2018 Mar 9;4(5):1788-96.

38. Saha I, Maulik U, Bandyopadhyay S, Plewczynski D. Fuzzy clustering of physicochemical and biochemical properties of amino Acids. Amino Acids. 2011;43(2):583-594.

39. Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O et. al. Scikit-learn: Machine learning in Python. Journal of machine learning research. 2011;12(Oct):2825-30.

Figure Legends

Fig 1. Schematic of Iterative Alignment Procedure. The iterative alignment procedure is executed in four separate steps as show in the flow chart, that include: (A) Classification of MHC-I binding peptides from the IEDB and the resultant matrices from AAindex; (B) Training the randomly initialized matrix (RandM) which, before training, was uncapable to demonstrate the trend of decreasing cross-similarity, but after training it becomes prominent indicating the successful integration of the information; (C) Demonstration the total similarity score of the full allele set with respect to the strongest determined binders of *HLA-A*02:01* (TSS $_{HLA-A*02:01-S}$) for trained RandM. Calculations were performed for all matrices before and after training; (D) Showcase correlation and accuracy measurements (see details in the text and figures below).

Fig 2. Schematics of matrix training procedure. Peptides were first downloaded and classified by their affinity. The similarity matrix is perturbed randomly and then TSS scores are calculated. Depending on the outcome, changes to the matrix were either saved or discarded. The matrix was considered 'converged' after 5000 beneficial changes total, or 5000 negative changes in a row, occur.

Fig 3. External similarity results for matrices before and after training with *HLA-A 02:01* binders. Five subsets of peptides were created from the full list from each allele. Blue bars represent after training and yellow before training. The TSS for each group to strong binders (TSS$_{S-LS,M,MW,W}$) was calculated in addition to each group to itself (TSS$_{S-S}$, TSS$_{LS-LS}$, TSS$_{M-M}$, TSS$_{MW-MW}$, TSS$_{W-W}$). The y-axis for each bar chart denotes the matrix, the x-axis is the normalized TSS$_{S-S,LS,M,MW,W}$ values. The results show, especially in RandM's case, that we can improve similarity matrices to predict a trend correlated to binding affinity. This trend is characterized by decreasing TSS$_{S-S,LS,M,MW,W}$ correlating with decreasing binding affinity.

Fig 4. RMSE (A), Spearman Rank (B), and Pearson (C) correlations for TSS trends calculated using trained and untrained matrices. The TSS$_{Seq-S}$ of the *HLA-A*02:01* list was

calculated by aligning each peptide with the top binders of the allele and correlating the list of

values with the list of experimentally determined binding affinities using linear (Pearson, Fig 4C)

and nonlinear (Spearman Rank, Fig 4B) methods. RMSE (Fig 4A) is calculated by obtaining the

root mean square of the difference between the normalized (0-1) -pIC_{50} and TSS_{Seq-S}. Error bars

are 1 standard deviation from the average of each set. The data shows the method can improve

literature and calculated matrices, most significantly that a trained randomly initialized matrix

(RandM) is more reflective of mutability information in the MHC-I context than all literature and

calculated matrices before training.

Fig 5. Results of classification analysis. Sensitivity (A) and specificity (B) measures

calculated from the results of binary classification of binding. In general, these results show the

training function did not improve the predictive ability of any matrix besides RandM, providing

evidence that TSS is a relevant predictor while noting the training operation is an ineffective

application of TSS.

Supporting Information Legends

S1 Fig. Cross-similarity results for the HLA-02:02 allele. Each bar chart shows the

average normalized TSS of the "Strong" affinity class with itself and each other class. The

decreasing trend similarity of "Strong" peptides with those of decreasing affinity

demonstrates the successful optimization of each matrix for the HLA-A*02:02 allele.

S2 Fig. Cross-similarity results for the HLA-03:01 allele. Each bar chart shows the

average normalized TSS of the "Strong" affinity class with itself and each other class. The

decreasing trend similarity of "Strong" peptides with those of decreasing affinity

demonstrates the successful optimization of each matrix for the HLA-A*03:01 allele.

Sensitivity and Specificity

MATRIX	HLA-A*02:01	HLA-A*02:02	HLA-A*03:01

A.
RandM
PMBEC
BLOSUM62
PAM250
Sausage
RMat
PMat
IMat
HMat
EMat
CMat
BMat
AMat
OCSim

B.
RandM
PMBEC
BLOSUM62
PAM250
Sausage
RMat
PMat
IMat
HMat
EMat
CMat
BMat
AMat
OCSim

Rate	0 0.5 1	0 0.5 1	0 0.5 1

■ Before Training   ■ After Training

A. Data Collection

MHC-1 Affinity Class

-pIC$_{50}$ Class

BLOSUM 62; Pam 250

B. Matrix Training

Trendless Matrix

Trendy Matrix

C. Similarity Calculation

Novel Similarity Matrices (14)

TSS Distribution

D. Predictive Functionality

Sensitivity

Cross-Similarity of Affinity Classes for HLA-A 02:01