functionInk: An efficient method to detect functional groups in multidimensional networks reveals the hidden structure of ecological communities

October 28, 2019

Short Title

Community detection in multidimensional ecological networks

Alberto Pascual-García[1, 2,*] and Thomas Bell[1]

(1) Department of Life Sciences. Silwood Park Campus. Imperial College London, Ascot, United Kingdom
(2) Current address: Institute of Integrative Biology. ETH-Zürich, Zürich, Switzerland
(*) Correspondence: alberto.pascual.garcia@gmail.com.

Abstract

1. Complex networks have been useful to link experimental data with mechanistic models, and have become widely used across many scientific disciplines. Recently, the increasing amount and complexity of data, particularly in biology, has prompted the development of multidimensional networks, where dimensions reflect the multiple qualitative properties of nodes, links, or both. As a consequence, traditional quantities computed in single dimensional networks should be adapted to incorporate this new information. A particularly important problem is the detection of communities, namely sets of nodes sharing certain properties, which reduces the complexity of the networks, hence facilitating its interpretation.

2. In this work, we propose an operative definition of "function" for the nodes in multidimensional networks, and we exploit this definition to show that it is possible to detect two types of communities: i) modules, which are communities more densely connected within their members than with nodes belonging to other communities, and ii) guilds, which are sets of nodes connected with the same neighbours, even if they are not connected themselves. We provide two quantities to optimally detect both types of communities, whose relative values reflect their importance in the network.

3. The flexibility of the method allowed us to analyze different ecological examples encompassing mutualistic, trophic and microbial networks. We showed that by considering both metrics we were able to obtain deeper ecological insights about how these different ecological communities were structured. The method mapped pools of species with properties that were known in advance, such as plants and pollinators. Other types of communities found, when contrasted with external data, turned out to be ecologically meaningful, allowing us to identify species with important functional roles or the influence of environmental variables. Furthermore, we found the method was sensitive to community-level topological properties like the nestedness.

4. In ecology there is often a need to identify groupings including trophic levels, guilds, functional groups, or ecotypes.The method is therefore important in providing an objective means of distinguishing modules and guilds. The method we developed, *functionInk* (functional linkage), is computationally efficient at handling large multidimensional networks since it does not require optimization procedures or tests of robustness. The method is available at: HTTPS://GITHUB.COM/APASCUALGARCIA/FUNCTIONINK.

Keywords: Complex networks, community detection, modules, guilds, mutualistic networks, trophic networks, microbial networks

1   Introduction

Networks have played an important role in the development of ideas in ecology, particularly in understanding food webs [1], and flows of energy and matter in ecosystems [2]. However, modern ecological datasets are becoming increasingly complex, notably within microbial ecology, where multiple types of information (taxonomy, behaviour, metabolic capacity, traits) on thousands of taxa can be gathered. A single network might therefore need to integrate different sources of information, leading to connections between nodes representing relationships of different types, and hence with different meanings. Advances in network theory have attempted to develop tools to analyse these more sophisticated networks, encompassing ideas such as multiplex, multilayer, multivariate networks, reviewed in [3]. There could therefore be much value in extending complex networks tools to ecology in order to embrace these new concepts.

Broadly speaking, a network represents how a large set of entities *share* or *transmit* information. This definition is intentionally empty-of-content to illustrate the challenges we face in network analysis. For instance, a network in which information is shared may be built relating genes connected if their sequence similarity is higher than a certain threshold. In that case, we may capture how their similarity diverged after an evolutionary event such as a gene duplication [4]. On the other hand, networks may describe how information is transmitted, as in an ecosystem in which we represent how biomass flows through the trophic levels or how behavioural signals are transmitted among individuals. We aim to illustrate with these examples that, when building networks that consider links of different nature (e.g. shared vs. transmitted information) or different physical units (e.g. biomass vs. bits), it is not straightforward to extrapolate methods from single-dimensional to multidimensional complex networks.

In this paper we aim to address a particularly relevant problem in complex networks theory, namely the detection of "communities"[5] when the network contains different types of links. In addition, we are interested in finding a method with the flexibility to identify different types of communities. This is motivated by the fact that, in ecology, it is recognized that communities may have different topologies [6] and often an intrinsic multilayer structure [7]. We aim to detect two main types of communities. Firstly, the most widely adopted definition of community is the one considering sets of nodes more densely connected within the community than with respect to other communities, often called *modules* [8]. An example in which modules are expected is in networks representing singnificant co-occurrences or segregations between microbial species, when these relationships are driven by environmental conditions. Since large sets of species may simultaneously change their abundances in response to certain environmental variables [9, 10], this results in large groups of all-against-all co-occurring species, and between-groups segregations. Secondly, we are interested in finding nodes sharing a similar connectivity pattern even if they are not connected themselves. An example of this type of communities in ecology comes when networks connecting consumers and their resources are built, and then it is aimed to identify groups of consumers sharing similar resources preferences. This idea is aligned with the classic Eltonian definition of niche, which emphasizes the functions of a species rather than their habitat [11]. We call this second class of communities *guilds*, inspired by the ecological meaning in which species may share similar ways of exploiting resources (i.e. similar links) without necessarily sharing the same niche (not being connected themselves), emphasizing the functional role of the species [12]. Consequently, guilds may be quite different to modules, in which members of the same module are tightly connected by definition. The situation in which guilds are prevalent is known as disassortative mixing [13], and its detection has received comparatively less attention than the "assortative" situation (which results in modules) perhaps with the exception of bipartite networks [14, 15].

There are many different approximations for community detection in networks, summarized in [16]. However, despite numerous advances in recent years, it is difficult to find a method that can efficiently find both modules and guilds in multidimensional networks, and that is able to identify which is the more relevant type of community in the network of interest. This might be because there is no algorithm that can perform optimally for any network [17], and because each type of approximation may be suited for some networks or to address some problems but not for others, as we illustrate below.

Traditional strategies to detect modules explore trade-offs in quantities like the betweeness and the clustering coefficient [8], as in the celebrated Newman-Girvan algorithm [18]. Generalizing the determination of modules to multidimensional networks is challenging. Consider, for instance, that a node A is linked with a node B and this is, in turn, linked with a node C, and both links are of a certain type. If A is then linked with node C with a different type of link, should the triangle ABC be considered in the computation of the clustering coefficient? One solution proposed comes from the consideration of stochastic Laplacian dynamics running in the network [19], where the permanence of the informational fluxes in certain regions of the network reflects the existence of communities. This approximation has been extended to consider multilayer networks [20], even if they are highly

overlapping [21]. A fundamental caveat for these methods is that the links must have a clear interpretation for how their presence affects informational fluxes. Returning to the above example, if the links AB and BC represent mutualistic interactions and the link AC represents a competitive one, can a random walk follow the link AC when this interaction does not describe a flux of biomass between the species but rather a disruption in the flux of biomass of AB and BC?

A related approach searches for modules using an optimization function that looks for a partitioning in a multilayer network that maximizes the difference between the observed model and a null model which considers the absence of modules [14]. This strategy can be applied to multidimensional networks, but raises questions such as which is the appropriate null model, and how to determine the coupling between the different layers defining the different modes of interaction [22]. In addition, since these approximations focus on the detection of modules, they neglect the existence of guilds or other network structures.

The search of guilds has received notable attention in social sciences, where the notion of structural equivalence was developed. Two nodes are said to be structurally equivalent if they have the same connectivity in the network [23]. The connectivity may be defined either analysing if two nodes share the same neighbours, if two nodes are connected with neigbours of the same type even if they are not necessarily the same (following some pre-assigned roles for the nodes, e.g. preys are structurally equivalent because are connected to predators), or a combination of both. Since social agents have often assigned a role, this is the reason why structural equivalence is particularly important in social networks.

An approximation that has exploited the idea of structural equivalence is stochastic blockmodelling [24], which considers generative models with parameters fitted to the observed network. The approach brings greater flexibility because different models can accomodate different types of communities [25]. Therefore, this approximation could be used not only to search guilds but also modules. Indeed, it has also been shown its equivalence to the problem of modularity optimization discussed above [26]. There are, however, also important caveats to the approach, since it is an important challenge to determine whether the underlying assumptions of a particular block model is appropriate for the data being used [27]. Moreover, even when the model brings an analytically closed form, the estimation of the parameters may be computationally intractable [28], hence requiring costly optimality procedures or tests for robustness, whose improvement has attracted much attention in recent years [29].

In this work, we build on the idea of structural equivalence noting that a node belonging to either a guild or a module is, in both cases, approximately structurally equivalent to the other nodes in its community. This observation was acknowledged in social sciences in the definition of $\lambda-$communities [30], which are types of communities encompassing both modules and guilds, whose relevance has been recognized previously in the ecological literature [6, 31]. From this observation, we wondered whether it is possible to find a similarity measure between nodes that quantifies their structural equivalence, even when different types of links are considered. We could then join nodes according to this similarity measure while monitoring whether the communities that are formed are guilds or modules. A similar approach was investigated by Yodzis *et al.* to measure trophic ecological similarity [32], but they did not identify an appropriate threshold for determining community membership (which they call "trophospecies").

We have developed an approach that builds on these results and develops a method to determine objective thresholds for identifying modules and guilds in ecological networks. We show that a modification of the community detection method developed by Ahn et al. [33], leads to the identification of two quantities we call internal and external partition densities. For a set of nodes joined within a community by means of their structural equivalence similarity, the partition densities quantify whether their similarities come from connections linking them with nodes outside the community (external density) or within the community (internal density). Notably, our method generates maximum values for internal and external partition densities along the clustering, allowing us to objectively determine thresholds for the structural equivalence similarities. The notion of structural equivalence therefore opens an avenue to identify and distinguish both guilds and modules. Both types of communities can be understood as different kinds of *functional group* —in the Eltonian sense– and this is the name we adopt here. We reserve the term "community" for a more generic use, since other types of communities beyond functional groups may exist, such as core-periphery structures [34].

We call our method functionInk (functional linkage), emphasizing how the number and types of links of a node determine its functional role in the network. We illustrate its use by considering complex ecological examples, for which we believe the notion of functional role is particularly relevant. We show in the examples that, by combining the external and internal partition densities, we are able to identify the underlying dominant structures of the network (either towards modules or towards guilds). Moreover, selecting the most appropriate community definition in each situation provides results that are comparable to state-of-the-art methods. This versatility in a

single algorithm, together with its low computational cost to handle large networks, makes our method suitable for any type of complex, multidimensional network.

2 Methods

Structural equivalence similarity in multidimensional networks

Our method starts by considering a similarity measure between all pairs of nodes that quantifies the fraction of neighbours connected with links of the same type that they share (Fig. 1). This is a natural definition of structural equivalence for multidimensional networks, which is agnostic on the specific information that the interaction carries. For simplicity, we present a derivation for a network that contains two types of links. We use undirected positive ($+$) interactions (e.g. a mutualism) and negative ($-$) interactions (e.g. competition) to illustrate the method, but these could be replaced by any two link types. Extending the method to an arbitrary number of link types is presented in the Suppl. Methods. We call $\{i\}$ the set of N nodes and $\{e_{ij}\}$ the set of M links in a network. We call $n(i)$ the set of neighbours of i, that can be split into different subsets according to the types of links present in the network.

For two types of links, we split the set of neighbours linked with the node i into those linked through positive relationships, $n_+(i)$, or through negative relationships, $n_-(i)$; we follow a notation similar to the one presented in [33], but note that $n(i)$ there denotes neighbours irrespective of the type of links. Distinguishing link types induces a division in the set of neighbours of a given node into subsets sharing the same link type, shown in Fig. 2A. More specifically, in the absence of link types we define the Jaccard similarity between two nodes i and j as:

$$S^{(\mathrm{J})}(i,j) = \frac{|n(i) \cap n(j)|}{|n(i) \cup n(j)|} \tag{1}$$

where $|\cdot|$ is the cardinality of the set (the number of elements it contains). This metric was shown to be superior to other alternatives [32], and generalizing this expression to multiple attributes is achieved simply differentiating the type of neighbours depending on the types of connections. For two attributes (see Suppl. Methods for an arbitrary number of attributes) this leads to

$$S^{(\mathrm{J})}(i,j) = \frac{|n_+(i) \cap n_+(j)| + |n_-(i) \cap n_-(j)|}{|n_+(i) \cup n_+(j) \cup n_-(i) \cup n_-(j)|}. \tag{2}$$

Accounting for the weight of the links can be made with the generalization of the Jaccard index provided by the Tanimoto coefficient [35], $S^{(\mathrm{T})}(i,j)$, presented in Suppl. Methods.

We note the particular case in which i and j are only connected between them which, with the above definition, means that they do not share any neighbours. This is problematic, because we want to distinguish this situation from the one in which they do not share any nodes, for which we get $S(i,j) = 0$. On the other hand, if they share a connection with respect to a third node, we want to distinguish the situation in which all three nodes are connected (a perfect transitive motif, the archetype of a module) from a situation in which they only share a neighbor but they are not themselves connected (the archetype of a guild). If we consider that a node is always a neighbor of itself, i.e. $\{i\} \in n(i)$, in both situations $S(i,j) = 1$ and we cannot distinguish these cases. Therefore, we take the convention that, for a connection between two nodes $|n(i) \cap n(j)| = 1$ and $|n(i) \cup n(j)| = 2$. In Fig. 1 we illustrate the computation of this similarity with a simple example.

Identification of communities through clustering and similarity cut-offs

Once the similarity between nodes is computed, the next objective is to define and identify communities. We aim to find communities joining nodes that are structural equivalent, and that are able to encapsulate some desirable features. On the one hand, if there are some roles pre-defined for the nodes, we would like that the communities do not mix these roles. This is the idea behind the notion of "regular equivalence" [36], which joins in the same community nodes connecting neighbours with the same role, as in phylogenetic trees where we can recognize that two nodes have as a role being "uncles" even if they belong to different families (so they are connected to different nodes), looking at their relative position in the phylogeny. On the other hand, structural equivalent communities should encode different topological motifs. This is the idea behind finding groups of nodes sharing similar topological roles in the network (e.g. hubs, peripheral, etc) followed in [34] where the authors identified a number of "universal" types of nodes in the network, illustrated in Fig. 1B (top-right network).

Figure 1: **Illustration of the method.** (A) The similarity between nodes i and j is computed considering the neighbours of each node and the types of interactions that link them. In this example, two types of link are shown: positive ($+$) interactions are shown as solid links connecting the sets of neighbours $n_+(i)$ and $n_+(j)$. Negative (-) links are shown as dotted links connecting the sets of neighbours $n_-(i)$ and $n_-(j)$. Following Eq. 2, $|n(i) \cap n(j)| = 2$ and $|n(i) \cup n(j)| = 8$, which yields $S^{(J)}(i,j) = 2/8$. If the link e_{ik} changes from being $-$ to $+$ while e_{jk} remains $-$, these two link types would be different and the node k would no longer belong to the set $n(i) \cap n(j)$, and hence the new similarity would be lower: $S^{(J)}(i,j) = 1/8$. In Ref. [33] the similarity computed in this way would be assigned to the links e_{ik} and e_{jk}. (B) For networks for which we have *a priori* information regarding the roles of the nodes (e.g. that blue and yellow nodes play different functional roles, top-left network), a possible classification consists of two communities (blue and yellow nodes), because every blue node is connected with a yellow one, and hence are structural equivalent. The method of Guimerá and Amaral [34], determines communities through their topological role (top-right network) by identifying central nodes (A and B nodes), peripheral nodes (A1-A3 and B1-B5) and connector nodes (C and D). functionInk (bottom network) defines communities by joining nodes with approximately the same connectivities, and if there are roles for the nodes, these can be incorporated defining link types (one type for each pair of roles connected). All non-zero Jaccard similarities of the example are shown. Nodes connected through a single link, e.g. link CD are counted once in the numerator of $S^{(J)}$, and twice in the denominator, leading to $S^{(J)}(C,D) = 1/4$. Clustering these similarities will lead to different partitions and, stopping at $S^{(J)} = 1/4$, would lead to communities being the intersection of those found in the above networks, highlighting the potential to identify communities considering both the roles and topological features. Figure adapted from [34].

The approximation we developed aims to be compatible with both approximations. First, we can encode different roles using different types of links, one type for each pair of roles connected in the network (see Fig. 1B where, for the top-left network, we *a priori* defined two roles for the nodes, yellow and blue). In the example, all links are of the same type because they always connect nodes of different color (which specify the role) in the top-left network. Second, the similarity metrics we propose will lead to higher values if the nodes have the same neighbours with the same connections, so the nodes in the communities will have similar topological features. We observed (Fig. 1B, bottom network) that clustering nodes with an agglomerative algorithm and stopping at a similarity $S^{(J)} = 1/4$ resulted in communities that are exactly the intersection between the communities that would be found with the previous methods (top networks). Therefore, an agglomerative clustering algorithm allows us to identify communities as in [32]. A critical question, however, is how to objectively determine the threshold to stop the clustering ([37])?

This question is often addressed by iteratively 'partitioning' the network into the distinct communities, and monitoring each partition with a function having a well defined maximum or minimum that determines the threshold of the optimal partition. In [33], the authors proposed to join links of a network according to a similarity measure between the links with an agglomerative clustering, and to monitor the clustering with a quantity called the partition density. The partition density is the weighted average across communities of the number of links within a community out of the total possible number of links (which depends on the number of nodes in the community). It is a metric similar in spirit to the modularity, which determines the optimal clustering threshold, but that allows to work with overlapping communities. Here, we re-considered the method of Ahn et al. [33] which was originally defined over link partitions (see Suppl. Methods), to work over nodes partitions with the similarity measure we propose. We developed two measures that define partition densities across nodes, with two distinct meanings. To develop these measures, we noted that, when joining nodes into a partition, we are concluding that these nodes approximately share the same number and type of connections with respect to the same neighbours, but we actually do not know whether they are connected between themselves. We therefore redefined the partition density so that it distinguishes between the contribution of link density arising from the connections *within* a community from connections shared with with external nodes *between* communities.

Given a node i, we differentiate neighbours that are within the same community ($n^{\text{int}}(i)$, where int stands for "interior") from neighbours that are in different communities ($n^{\text{ext}}(i)$), hence $n(i) = n^{\text{int}}(i) \cup n^{\text{ext}}(i)$ (Fig. 2). For a singleton (a community of size one) $n^{\text{int}}(i) = \{i\}$ and $n^{\text{ext}}(i) = \emptyset$. Similarly, the set of links $m(i)$ connecting the node i with other nodes can also be split into two sets: the set connecting the node with neighbours within its community $m^{\text{int}}(i)$, and those connecting it with external nodes $m^{\text{ext}}(i)$. This distinction was also considered in other context (called the problem of coloring nodes [38]).

Given a partition of nodes into T communities our method identifies, for each community C, the total number of nodes it contains, n_c^{int}, and the total number of links connecting these nodes m_c^{int}. In addition, it computes the total number of nodes in other communities that have connections to the nodes in the community, n_c^{ext}, through a number of links m_c^{ext}. Clearly, to identify n_c^{ext} neighbours, at least n_c^{ext} links are required. Therefore, the number of links in excess, $m_c^{\text{ext}} - n_c^{\text{ext}}$, contributes to the similarity of the nodes in the community through external links (see Suppl. Methods), and a relevant quantity to characterize a community is the fraction of links in excess out of the total possible number $(m_c^{\text{ext}} - n_c^{\text{ext}})/n_c^{\text{ext}} \left(n_c^{\text{int}} - 1\right)$. We note this calculation does not take into account multiple link types. The weighted average of this quantity through all communities leads to the definition of external partition density:

$$D^{\text{ext}} = \frac{1}{M} \sum_c \frac{m_c^{\text{ext}}}{2} \frac{(m_c^{\text{ext}} - n_c^{\text{ext}})}{n_c^{\text{ext}} \left(n_c^{\text{int}} - 1\right)}, \tag{3}$$

where M is the total number of links. We now follow a similar reasoning to consider the contribution to the similarity of the nodes through the internal links (see Suppl. Methods). We acknowledge that in a community created by joining nodes through the similarity measure we propose, it may happen that $n_c^{\text{int}} > 0$ even if $m_c^{\text{int}} = 0$. Therefore, any link is considered a link in excess, leading to the following expression for the internal partition density, which quantifies the fraction of internal links in excess out of the total:

$$D^{\text{int}} = \frac{1}{M} \sum_c m_c^{\text{int}} \frac{2m_c^{\text{int}}}{n_c^{\text{int}}(n_c^{\text{int}} - 1)}. \tag{4}$$

Finally, we define the total partition density as the sum of both internal an external partition densities:

$$D^{\text{total}} = D^{\text{int}} + D^{\text{ext}},$$

Figure 2: **Definition of guilds and modules.** For each set of nodes n_c^{int} belonging to the same community c (nodes within the same shaded area) we consider the number of links within the community (black dashed links, called m_c^{int} in the main text) out of the total number of possible internal links, to compute the internal partition density (see upper curves). We also computed the external partition density, which is the density of links connecting nodes external to the community (m_c^{ext}, solid red lines linking nodes belonging to different communities) out of the total number of possible external links. We call guilds the communities determined at the maximum of the external partition density, and modules those found at the maximum of the internal partition density. The relative value of the external and internal partition densities allow us to estimate which kind of community dominates the network. In the example, guilds dominate the network on the left, and modules dominates the network on the right.

and hence, if all the fractions in D^{int} and D^{ext} are equal to one, i.e. all possible links in excess are realized, D^{total} equals to one. Since at the beginning of the clustering the communities have a low number of members, most of the contribution towards D^{total} comes from D^{ext} while, in the last steps, where the communities become large, D^{int} will dominate. All three quantities will reach a maximum value along the clustering (for the internal it could be at the last step) and, if one of them clearly achieves a higher value, it will be indicative that one type of functional group is dominant in the network. If that is the case, the maximum of D^{total} —which is always larger or equal to $\max(\max(D^{\mathrm{int}}), \max(D^{\mathrm{ext}}))$–, will be at a clustering step close to the step in which the dominating quantity peaks. If neither D^{ext} nor D^{int} clearly dominates, D^{total} will peak at an intermediate step between the two partial partition densities maxima, suggesting that this intermediate step is the best candidate of the optimal partition for the network. Communities determined at this intermediate point where they can be both guilds and modules will be called, generically, functional groups.

3   Results

Plant-pollinator networks

To illustrate the use of the method we start analyzing a synthetic example. In ecological systems, species are often classified into communities according to their ecological interactions, such as in mutualistic networks of flowering plants and their animal pollinators. These networks are characterized by intra and interspecific competition within the pool of plants and within the pool of animals, and by mutualistic relationships between plants and animals, leading to a bipartite network.

To investigate the performance of our method and, in particular, the influence of the topological properties into the partition density measures, we generated a set of artificial mutualistic networks with diverse topological properties, following the method presented in [39]. For the mutualistic interactions, we focused on two properties: the connectance κ_{mut}, which is the fraction of observed interactions out of the total number of possible interactions, and the nestedness ν as defined in [40] (see Methods), which codifies the fraction of interactions that are shared between two species of the same pool, averaged over all pairs of species. We selected these measures for their importance in the stability-complexity debate in mutualistic systems [39], and the similarity between the nestedness (which, in the definition we adopt here, represents the mean ecological overlap between species) and the notion of structural equivalence we considered. For the competition matrices, we considered random matrices with different connectances, κ_{comp}, since it is difficult to estimate direct pairwise competitive interactions experimentally, and they are frequently modeled with a mean field competition matrix.

We verified that in all networks the set of plants and animals are joined in the very last step of the clustering irrespective of the clustering method used, a result that must follow construction. As expected, the curves monitoring the external and internal partition densities depends on the properties of the networks. We illustrate this finding in Fig. 3, where we have selected two networks with contrasting topological properties. One of the networks has high connectance within the pools and low connectance and nestedness between the pools. The internal partition density peaks at the last step minus one (i.e. where the two pools are perfectly separated) consistent with the definition of modules, where the intra-modules link density is higher than the inter-modules link density. On the other hand, the second network has intra-pool connectance equals to zero, and very high connectance and nestedness between the pools (see Fig. 3). We selected a $\kappa_{\mathrm{comp}} = 0$ for simplicity in the network representation, but similar results are obtained for low values of κ_{comp}, see for instance Suppl. Fig. 11. In this second network (see Fig. 3, right panel), only the external partition density peaks and, at the maximum, the communities that we identified clearly reflect the structural equivalence of the nodes members in terms of their connectance with nodes external to the group, as we expect for the definition of guilds. The ecological information retrieved for guilds is clearly distinct from the information retrieved for the modules, the former being related to the topology of the network connecting plants and animals. We observe that guilds identify specialist species clustered together, which are then linked to generalists species of the other pool: a structure typical of networks with high nestedness.

The method identified several interesting guilds and connections between them. For instance, generalists Plant 1, Animal 1 and Animal 2 (and to a lesser extent Plant 2) have a low connectivity between them but, being connected to many specialists, determine a region of high vulnerability, in the sense that a directed perturbation over these species would have consequences for many other species. This is confirmed by the high betweeness of these nodes (proportional to the size of the node in the network). In addition, the algorithm is able to identify more complex partitions of nodes into communities. As an example of this, Animal 16 (turquoise) is split from

Animals 10 and 11 (cyan), which form a second community, and from Animals 15, 18 and 19 (light pink) that are joined into a third community, despite of the subtle connectivity differences between these six nodes. Finally, it also detects communities of three or more species that have complex connectivity patterns which, in this context, may be indicative of functionally redundant species (e.g. red and blue communities).

Examples with other intermediate properties are analyzed in the Suppl. Figs. 9 and 10. Broadly speaking, either the internal or the total partition density maximum peaks at the last step minus one, allowing for detection of the two pools of species. Nevertheless, the method fails to find these pools in situations in which the similarity between members of distinct pools is comparable to the similarity of members belonging to the same pool. This may be the case if the connectances are small (see Suppl. Fig. 11). The relative magnitude of the external vs. internal partition density depends on the connectance between the pools of plants and animals and on the connectance within the pools, respectively (see Suppl. Fig. 9). Interestingly, networks for which the nestedness is increased keeping the remaining properties the same generated an increase in the external partition density (see Suppl. Fig. 10). These examples illustrate how the external partition density is sensitive to complex topological properties, in particular to an increase in the dissasortativity of the network, expected when guilds are dominant.

Figure 3: **Synthetic mutualistic networks**. (Top left) Partition densities for a network with $\kappa_{\text{comp}} = 0.5$, nestedness $\nu = 0.15$ and $\kappa_{\text{mut}} = 0.08$ and (top right) for a network with $\kappa_{\text{comp}} = 0$, nestedness $\nu = 0.6$ and $\kappa_{\text{mut}} = 0.08$. The high density of competitive links in the first network makes the internal partition density dominate, leading to two modules representing the plant-pollinator pools (bottom left network), while reducing the density of competitive links to zero in the second network makes the external partition density to dominate, finding guilds (bottom right, with plants labeled "Pl" and animals labeled "An"). The small increase in the internal partition density for this network at step 59 is due to two specialist species joined at that step (animal 29 and plant 56, shown at the bottom left of the network). Nodes are colored according to their functional group in both networks although, in the network finding guilds (bottom right), specialist species are yellow, single species communities are grey, and the size of the nodes is proportional to their betweeness.

Trophic networks

We tested our method in a comprehensive multidimensional ecological network of 106 species distributed in trophic layers with approximately 4500 interactions, comprising trophic and non-trophic interactions (approximately 1/3 of the interactions are trophic) [41]. This network was analyzed looking for communities extending a stochastic

Figure 4: **Analysis of a trophic network.** Trophic networks with links representing trophic (gray), non-trophic positive (red), and negative (green) interactions. (Left) Nodes are grouped according to the classification found in [41] (reference classification), and colored by the guilds found with functionInk at the maximum of the external partition density. (Right) Nodes are grouped according to the trophic levels and colored by the modules found by functionInk (see Main Text for details). The modules separate the three main trophic levels: predators, herbivores and basal species, further separating some of them into subgroups, such as filter feeders and plankton, which is an orphan module.

blockmodelling method [13] to deal with different types of interactions [41]. The estimation of the parameters of the model through an Expectation-Maximization algorithm requires a heuristic approximation, and hence it is needed to test the robustness of the results found. Here we show that, in this example, our method is comparable with this approximation, and it has the advantage of being deterministic. Moreover, the simplicity of the method allows us to handle large networks with arbitrary number of types of links and to evaluate and interpret the results, as we show in the following.

Our method finds a maximum for the internal density when there are only three communities. Previous descriptions of the network identified three trophic levels in the network (Predators, Herbivores and Basal species). The latter are further subdivided into subgroups like (e.g. Kelps, Filter feeders), and there are some isolated groups like one Omnivore and Plankton. To match these subgroups we observed that the total partition density reaches a maximum close to the maximum of the external partition density (step 69) and maintains this value along a plateau until step 95 (see Suppl. Fig. 12). We analyzed results at both clustering thresholds finding that, at step 95, we obtain modules with a good agreement with the trophic levels, shown in Fig. 4. On the other hand, at step 69 we find a larger number of communities, some of which fit the definition of modules and others the definition of guilds (see Fig. 4).

To shed some light on the information obtained from this second network, we compared the classification obtained by Kefi *et al.* [41] (in the following reference classification) and our method. We computed several similarity metrics comparing the classification we obtained at each step of the agglomerative clustering with functionInk and the reference classification (see Methods). In Fig. 5, we show that the similarity between both classifications is highly significant (Z-score > 2.5) and is maximized when the external partition density is also maximized, i.e. at step 69. This is particularly apparent for the Wallace 01, Wallace 10 and Rand indexes (see Fig. 7 and Suppl. Fig. 13). Notably, communities in the reference classification were also interpreted as functional groups in the same sense proposed here [41].

Nevertheless, there are some discrepancies between both classifications. In particular, although there is a complete correspondence between the two largest communities in both classifications, there are a number of intermediate communities in the reference classification whose members are classified differently in our method. To illustrate these discrepancies, we plotted a heatmap of the Tanimoto coefficients of members of four communities of intermediate sizes containing discrepancies, showing their membership in both the reference and the functionInk classification with different colors (see Fig. 4). The dendrograms cluster rows and columns computing the Euclidean distance between their values. Therefore, these dendrograms are very similar to the method encoded in functionInk, and the communities must be consistent, representing a powerful way to visually inspect results. Indeed, the blocks found in the heatmap are in correspondence with functionInk communities, as expected, but we observe some discrepancies with the reference classification. For instance, the community found by the reference classification containing several *Petrolishtes* species, joins species that have low similarity regarding the number and type of interactions as measured by the Tanimoto coefficients, while functionInk joins together the three species with high similarity, leaving aside the remainder species. Of course, we cannot discard that the method used in the reference classification captures other properties justifying the differences. But it is immediately apparent the advantages provided by the simplicity our method, which permits validation through visual inspection of the consistency of the classification.

Microbial networks

We discuss a last example of increasing importance in current ecological research, which is the inference of interactions among microbes sampled from natural environments. We considered a large matrix with more than 700 samples of 16S rRNA operative taxonomic units (OTUs) collected from rain pools (water-filled tree-holes) in the UK [43, 44] (see Suppl. Methods). We analyzed $\beta-$diversity similarity of the communities contained in the matrix with the Jensen-Shannon divergence metric [45], further classifying the communities automatically, leading to 6 disjoint communities (see Methods). Next, we inferred a network of significant positive (co-occurrences) or negative (segregations) correlations between OTUs using SparCC [46], represented in Fig. 6 (see Methods). Applying functionInk to the network of inferred correlations, we aimed to understand the consistency between the results of functionInk (modules and guilds) and the $\beta-$diversity-classes. The rationale is that, by symmetry, significant co-occurrences and segregations between OTUs should reflect the similarity and dissimilarity between the communities, hence validating the method.

Contrasting with the trophic network analyzed in the previous example, the external partition density achieves a low relative value and brings a poor reduction of the complexity of the network, suggesting optimal clustering after just 22 clustering steps (see Suppl. Fig. 14). The internal partition density achieves a higher value, hence suggesting that modules are more relevant than functional groups in this network. Two large modules are apparent, see Fig. 6, with a large number of intracluster co-occurrences (continuous links) and interclusters segregations (dotted links). Note that this is quite different to what is found in macroscopic trophic networks, where pools of species (e.g. prey) have within module competitive (segregating) interactions, while between-modules interactions can be positive (for predators) or negative (for prey). In addition, the total partition density peaks at a much higher value and it seems to be able to split some of the large modules into smaller motifs, some of which were identified as guilds and have clearly distinctive connectivities, that we analyse in further detail. Since some of these motifs have characteristics closer to those of guilds while others are closer to modules, we refer to them generically as functional groups.

There is reasonable agreement between the functional groups found at the maximum of the total partition density and the $\beta-$diversity-classes shown in Fig. 6. Since it was shown in [43] that the $\beta-$diversity-classes might be related to a process of ecological succession driven by environmental variation, the functional groups are likely driven by environmental preferences rather than by ecological interactions, likely explaining the large number of positive co-occurrences. This speaks against a naive interpretation of correlation networks in microbial samples as ecological interactions, unless environmental preferences are controlled [10, 9]. However, the detection of networks complements the information that $\beta-$diversity-classes provides, since it is possible to individuate the key players of these classes. For instance, only two OTUs from the green functional group have an important number of co-occurrences with members of the red functional group, and only one of them has a significant segregation with respect to a member of the blue functional groups. These two highly abundant segregating OTUs are *Pseudomonas putida* and *Serratia fonticola*, both of which were shown to dominate two of the $\beta-$diversity-classes [43].

Figure 5: **Analysis of guilds.** (Top) Z-score of the Wallace 10 index [42], measuring the similarity between the reference classification and the functionInk method at each clustering step. The similarity with the reference classification (see Main Text) is maximized around the maximum of the external partition density. (Bottom) Comparison of communities 1, 4, 7 and 9 in the reference classification, whose members were classified differently by functionInk. Colors in the names of species in rows (columns) represent community membership in the reference (functionInk) classifications. The heatmap represents the values of the Tanimoto coefficients, and the dendrograms are computed using Euclidean distance and clustered with complete linkage. The heatmap blocks of high similarity are in some cases inconsistent with the reference classification. Given the simplicity of the interpretation of these coefficients, it is difficult to explain the clustering of distant members by the reference classification.

Figure 6: **Comparison of functional groups in the microbial network.** Network of significant co-occurrences (continuous links) and segregations (dotted links) at the species level (nodes). Colors indicate functional group membership, which was determined by the maximum of the external (top), total (middle) and internal partition densities (bottom). Orphan nodes are colored grey in the top figure for clarity. The higher value of the internal partition density (see Suppl. Fig. 14) suggests that a modular structure is the more appropriate to describe the functional groups. This is confirmed by the low number of guilds (top figure) and the good agreement between the global topological structure and the modules (bottom figure). Communities were automatically located close in space according to the partition found with the total partition density (middle) and blue and green communities rearranged manually to make more clear their connections, in particular we separated one node in the green community being the only one with co-occurrences with other communities on the right-hand side.

Figure 7: **Analysis of a microbial network.** Heatmap representing the z-score of the log-transformed abundances of the OTUs (see Methods). Species are colored according to their functional group membership obtained at the maximum of the total partition density. Samples are colored according to one of the six community classes found in [43]. Heatmap blocks show segregation and co-occurrence between modules, further mapping the β−diversity classes.

Discussion

We presented a novel method for the analysis of multidimensional networks, with nodes containing an arbitrary number of link types. We developed the method to work with nodes instead of with links (which was the case for the original method proposed by Ahn et al. [33]), which we find more intuitive, and allows the interpretation of the communities and its analysis with current visualization software (see Suppl. Methods). From an ecological perspective, the definition of a species' function in the network is straightforward for nodes, adopting the definition of structural equivalence used in social networks. This notion underlies both the similarity measure definition and the rationale behind both the clustering and our definition of partition densities. From the point of view of the similarity between nodes, we selected a set-theoretic measure quantifying the number of nodes that are shared with the same type of interaction. We believe this is a natural definition of structural equivalence for multidimensional networks, that has the advantage that it does not make assumptions on how the information flows in the network, typical of approximations based on Laplacian dynamics (see e.g. [19, 20]). This allow us to join nodes simply by their similarity, with no need of assuming any specific underlying network structure, or the introduction of additional parameters such as the coupling between the different modes of interaction (see e.g. [21]). This makes our approximation amenable to handle networks containing any type of interactions (although see some limitations below).

Working with this definition of the similarity we defined two measures of nodes partitioning. While the internal partition density is very similar to the definition provided in [33] (see Suppl. Methods), the external partition density brings a new dimension, being similar in spirit to the search of structural equivalent communities in social networks [23]. This allowed us to propose a clear differentiation between modules (determined by the maximum of the internal partition density) and guilds (determined by the maximum of the external partition density). Although the method might not be able to achieve the generality of other approximations aiming to find any arbitrary structure in the network [13, 25, 29], such approximations require either heuristics to find a solution for the parameters –and hence a unique optimal solution is not guaranteed–, or a computationally costly sampling of the parameter space. Our method relies on a deterministic method whose results are easily inspected, given the simplicity of the similarity metric used and the partition density functions proposed to monitor the optimal clustering.

Beyond these technical advantages, we illustrated the versatility of functionInk using several ecological examples. The relative value between the internal and external partition density immediately yields information on whether the network is dominated by modules, guilds, or intermediate structures. This allows for increasing flexibility in the analysis of the networks, and for a more nuanced interpretation of network structure and species' roles in the ecosystem. For both mutualistic and trophic networks, the internal partition density correctly finds the trophic layers, justifying the success of the original method [33]. Our extension recovered the functional groups as determined by Kefi et al. [41] through the external partition density, and the visual inspection reflects a good consistency with the definition we proposed for functional groups in terms of structural equivalence. Moreover, in the mutualistic networks, we showed that the functional groups discovered in this way was sensitive to changes to high-order topological properties such as the nestedness.

The analysis of the microbial network was dominated by modules rather than guilds. Interestingly, these modules had intra-cluster positive correlations, contrary to what would be expected in a macroscopic trophic network, where competitive interactions would be dominant between members of the same trophic layer. We selected in this example for further exploration the functional communities found at the maximum of the total partition density, with some groups having properties closer to those of guilds and others closer to modules. The communities that we identified were in good agreement with the functional communities found using $\beta-$diversity similarity [43], supporting the consistency of the method. Interestingly, it was found in [43] that similar $\beta-$diversity-classes were driven by environmental conditions. Although co-occurring more often in the same environment may be indicative of a higher probability of interaction [47], the most economical hypothesis is that they co-occur because they share similar environmental preferences, and hence it cannot be disentangled the type of interaction (if any) unless the environmental variables are under control [10, 9].

Our method may have problems if the communities are highly overlapping [21, 33]. In these cases, it would be convenient to inspect the partition at the three classifications given by the partition densities, since it is likely that overlapping communites are split in an earlier classification and then joined at later steps of the clustering. Another possibility is to combine it with the approximation proposed in Ref. [33], that has both very compatible and, at the same time, complementary results (see Suppl. Results). Our approximation does not consider yet the case in which there are multiedges in the network, although real networks are typically very sparse and the

probability of finding multiedges is small [27]. We do not address either the challenge of temporal networks, but we believe that the framework can be expanded to consider these cases.

Finally, we remark that functionInk requires the computation of Jaccard or Tanimoto coefficients, whose computational cost scales as N^2, being N the number of nodes. However, the similarity coefficients only need to be computed once, and then the clustering with different methods and posterior analysis are at most order N, making the method suitable for large networks. Notably, since the method is deterministic, it does not require computationally costly optimization methods (some of which are extensively discussed in [5]) and, given the intuitive definition of similarity used, it brings the possibility of easily evaluating the results found. The method is freely available in the address (HTTPS://GITHUB.COM/APASCUALGARCIA/FUNCTIONINK) and, importantly, although we developed it with ecological networks in mind, it can be applied to any kind of network.

Acknowledgments

We thank Michael Schaub for critical comments on an earlier version of the manuscript, and to Sebastian Bonhoeffer for his support. We also thank to two anonymous referees whose comments help us to improve the manuscript. The research was funded by a European Research Council starting grant (311399-Redundancy) awarded to T.B. T.B. was also funded by a Royal Society University Research Fellowship. APG was also funded by the Simons Collaboration: Principles of Microbial Ecosystems (PriME), award number 542381.

Supplementary Methods

Generalization of the Jaccard and Tanimoto coefficients to an arbitrary number of link types

Consider a network with a set $\{i\}$ of N nodes and a set $\{e_{ij}\}$ of M links. These links are classified into Ω types labeled with the index $\alpha = (1, ..., \Omega)$. These types would typically account for differential qualitative responses of the nodes properties due to the interactions. For example, if we consider that the nodes are species and the property of interest is the species abundances, the effect of cooperative or competitive interactions on the abundances can be codified using two different types of links: positive and negative. If these relations are inferred through correlations between abundances, we could use a quantitative threshold (for instance a correlation equal to zero) to split the links into positive and negative correlations. In general, we may use a number of qualitative attributes or quantitative thresholds in the weights of the links to determine different types of links.

We call $n(i)$ the set of neighbours of i, and we split these neighbours into (at most) Ω different subsets according to the types of links present in the network. The Jaccard coefficient defined in Eq. 2 can be extended, considering similarities between nodes, as:

$$S^{(\mathrm{J})}(n_i, n_j) = \frac{\sum_{\alpha=1}^{\Omega} |n_\alpha(i) \cap n_\alpha(j)|}{|\bigcup_{\alpha=1}^{\Omega} n_\alpha(i) \cup n_\alpha(j)|}. \tag{5}$$

Accounting for the weight of the links can be made with the generalization of the Jaccard index provided by the Tanimoto coefficient [35]. We first introduce the method without differentiating between different types of neighbours. Consider the vector $\boldsymbol{a}_i = \left(\tilde{A}_{i1}, \ldots, \tilde{A}_{iN} \right)$ with

$$\tilde{A}_{ij} = \frac{1}{k_i} \sum_{i' \in n(i)} w_{ii'} \delta_{ij} + w_{ij} \tag{6}$$

where w_{ij} is the weight of the link connecting the nodes i and j, $k_i = |n(i)|$ and δ_{ij} is the Kronecker's delta ($\delta_{ij} = 1$ if $i = j$ and zero otherwise). Determining the quantity $W_{ij} = \boldsymbol{a}_i \boldsymbol{a}_j = \sum_k \tilde{A}_{ik} \tilde{A}_{kj}$, the Tanimoto similarity is defined as

$$S^{(\mathrm{T})}(e_{ik}, e_{jk}) = \frac{W_{ij}}{W_{ii} + W_{jj} - W_{ij}}. \tag{7}$$

Working with link types requires a generalization of the above expression. Consider for the moment two types related with a positive $w_{ij} > 0$ or a negative $w_{ij} < 0$ weight of the links. The term $\tilde{A}_{ii} = 1/k_i \sum_{i'} w_{ii'}$ is the average of the strengths of the links connected with node i, and it is desirable to keep this meaning when considering two types to properly normalize the Tanimoto similarity. This is simply achieved redefining $\tilde{A}_{ij}$ as

$$\tilde{A}_{ij} = \frac{1}{k_i} \sum_{i' \in n(i)} \mathrm{abs}(w_{ii'}) \delta_{ij} + w_{ij}. \tag{8}$$

On the other hand, the similarity is essentially codified in the term W_{ij} that we now want to redefine to account for two types of interactions in such a way that only products $\tilde{A}_{ik} \tilde{A}_{kj}$ between terms with the same sign contribute to the similarity. This is achieved with the following definition, which generalizes the Tanimoto coefficient

$$W_{ij} = \sum_k \tilde{A}_{ik} \tilde{A}_{kj} \delta(\mathrm{sgn}(\tilde{A}_{ik}) - \mathrm{sgn}(\tilde{A}_{kj})) \tag{9}$$

where $\mathrm{sgn}(\cdot)$ is the sign function and $\delta(a - b)$ is the Dirac delta function ($\delta(a - b) = 0$ if $a \neq b$). Generalizing to an arbitrary number of types can be achieved by defining a variable μ_{ij} that returns the type of the link, i.e. $\mu_{ij} = \alpha$ with α being a factor variable which, for the example of positive and negative links, is codified by the sign of the links' weight. We generalize the expression in Eq. 9 as follows

$$W_{ij} = \sum_k \tilde{A}_{ik} \tilde{A}_{kj} \delta(\mu_{ik} - \mu_{kj}). \tag{10}$$

Finally, the generalization of the external and internal partition densities to consider multiple types of links simply requires us to correctly classify the neighbours of each node accounting for the different types $n(i) = \bigcup_{\alpha=1}^{\Omega} n_{\alpha}^{\text{int}}(i) \cup n_{\alpha}^{\text{ext}}(i)$. Similarly, the set of links $m(i)$ connecting the node i with other nodes must be also split into sets according to the different types $m(i) = \bigcup_{\alpha=1}^{\Omega} m_{\alpha}^{\text{int}}(i) \cup m_{\alpha}^{\text{ext}}(i)$. The expressions for the internal and external partition densities remain otherwise the same.

Additional notes on the relation between the Jaccard similarity and the partition densities

In this section we aim to provide a more explicit relation between the Jaccard similarity and the partition density and, in particular, the notion of links in excess. Consider that the network has a single type of link (and we will make some precision below for the general case in which there are different types of links). In the computation of the partition densities, we inspect each community and we average across communities. Therefore, let us start considering a generic community c, and note that the neighbours of a node i are partitioned into those belonging to the same community, $n^{\text{int}}(i)$, and those belonging to other communities, $n^{\text{ext}}(i)$. Therefore, the Jaccard similarity of two nodes within the same community can be expressed as

$$S_c^{(\text{J})}(i,j) = \frac{|n^{\text{int}}(i) \cap n^{\text{int}}(j)| + |n^{\text{ext}}(i) \cap^{\text{ext}} n(j)|}{|n^{\text{int}}(i) \cup n^{\text{int}}(j) \cup n^{\text{ext}}(i) \cup n^{\text{ext}}(j)|} = S_c^{(\text{J}),\text{int}}(i,j) + S_c^{(\text{J}),\text{ext}}(i,j), \tag{11}$$

where we used a subindex c to stress the fact that $i,j \in c$. Hence, the mean similarity of the nodes in the community can also be split in two components

$$\overline{S_c^{(\text{J})}(i,j)} = \frac{2}{n^{\text{int}}(n^{\text{int}} - 1)} \left(\sum_{i<j} S_c^{(\text{J}),\text{int}}(i,j) + S_c^{(\text{J}),\text{ext}}(i,j) \right) = \overline{S_c^{(\text{J}),\text{int}}(i,j)} + \overline{S_c^{(\text{J}),\text{ext}}(i,j)}.$$

Therefore, the sums $\hat{s}_c^{\text{int}} = \sum_{i<j} |n^{\text{int}}(i) \cap n^{\text{int}}(j)|$ and $\hat{s}_c^{\text{ext}} = \sum_{i<j} |n^{\text{ext}}(i) \cap n^{\text{ext}}(j)|$ (where $i,j \in c$) encode the contributions to the mean similarity of the community given by external and internal nodes, respectively. We aim to relate these terms to the links in excess used to compute the partition densities.

To establish this relation, we note that the degree of any node in the network, $|n(i)|$, can also be partitioned between the links connecting to other nodes in the community it belongs to, $|n^{\text{int}}(i)|$, and the links connecting to nodes from other communities, $|n^{\text{ext}}(i)|$. Again, we will add a subindex, e.g. $|n_c(i)|$, if there is any possible ambiguity about the identity of the community to which i belongs. In addition, we would like to specifically identify how the degree $|n^{\text{ext}}(i)|$ is partitioned with respect to each of the communities the node i is connected to, i.e. $|n_c^{\text{ext}}(i)| = \sum_{c'} |n_c^{\text{ext}}(i|c')|$, where $n_c^{\text{ext}}(i|c')$ stands for the set neighbours of $i \in c$ belonging to the communities $c' \neq c$. Following these considerations we observe that each comparison between two nodes in the community contributing to $\hat{s}_c^{\text{ext}}$, requires that an external node $k \in c' \neq c$ has at least degree two with respect to c, and therefore

$$\hat{s}_c^{\text{ext}} = \sum_{i<j} |n_c^{\text{ext}}(i) \cap n_c^{\text{ext}}(j)| = \sum_{\substack{c' \neq c \\ k \in c'}} \frac{|n_{c'}^{\text{ext}}(k|c)|(|n_{c'}^{\text{ext}}(k|c)| - 1)}{2},$$

where the summatory runs for every element $k \in c'$ and every community $c' \neq c$. Clearly, if all $|n^{\text{ext}}(k|c)| \leq 1$ there is no contribution to the similarity of the nodes in c and we require at least having a degree equal 2 to have one contribution (a degree equal N to have $N(N-1)/2$ contributions). Therefore, given an external node k with degree N with respect to the community c, we have $N-1$ links in excess generating contributions to the similarities in c, and we can compute the number of these links in the community as

$$\hat{s}_c^{\text{ext}} - \sum_k \frac{(|n_{c'}^{\text{ext}}(k|c)| - 1)(|n_{c'}^{\text{ext}}(k|c)| - 2)}{2} = \sum_k (|n_{c'}^{\text{ext}}(k|c)| - 1) = m_c^{\text{ext}} - n_c^{\text{ext}},$$

which is the main argument in the external partition density function used. A similar reasoning can be followed for the internal partition density, although now we should note that all links contribute to the similarity because we followed a convention in which $|n^{\text{int}}(i) \cap n^{\text{int}}(j)| = 1$ if i and j are linked, what leads to

$$\hat{s}_c^{\text{int}} - \sum_i \frac{|n^{\text{int}}(i)|(|n^{\text{int}}(i)| - 1)}{2} = m^{\text{int}}.$$

A weakness of our approximation is that the links in excess do not generate all the possible contributions to the similarity of the community if there exist different types of links. This would, however, require reinspecting along the clustering procedure the types of connections for each neighbor and developing a procedure to solve ambigüities if the types are different. This is not required in the current implementation, in which the method is separated in two distinct problems, namely the computation of the similarities (where there is inspection of the neighbours and the types of connections) and the clustering, hence improving the computational efficiency. Since the clustering is performed using the N highest similarities (out of $N(N-1)/2$ possible similarities, being N the number of nodes in the network), our choice is designed in a way in which nodes joined in a community are connected in a large extent to the same neighbours through the same type of links (otherwise the similarities should be low and the nodes will not be joined), which we confirmed in the examples shown is the article. Hence, a more accurate partition density will likely not change the qualitative behaviour of the current functions, which have the advantage of being computationally very efficient.

Original definition of partition density and relation with functionInk

For completeness, we present the definition of partition density presented in [33] and a comparison with the new method. In short, Ahn *et al.* method starts building a similarity measure between any pair of links sharing one node in common. Two links will be similar if the nodes that these two links do not share have, in turn, similar relationships with any other node, shown in Fig. 1. From this similarity measure, links are clustered and an optimal cut-off for the clustering is found monitoring a measure called *partition density* (which in this paper relates to the *internal partition density*). The optimal classification found at the cut-off, determines groups of links that are similar because they connect nodes that are themselves similar in terms of their connectivity. Therefore, the nodes are classified indirectly, according to the groups that their respective links belong, and a node may not belong to a single community but to several communities if its links belong to different clusters. This is claimed to be an advantage with respect to other methods (in particular for high density networks) as membership to a single cluster is not enforced. At every step of the clustering it is obtained a partition $P = P_1, ..., P_C$ of the links into C subsets. For every subset, the number of links is $m_c = |P_c|$ and the number of nodes that these links are connecting is $n_c = | \cup_{e_{ij} \in P_c} \{i, j\}|$. The density of links for the cluster C is then

$$D_c = \frac{m_c - (n_c - 1)}{n_c(n_c - 1)/2 - (n_c - 1)} \tag{12}$$

where the normalization considers the minimum $(n_c - 1)$ and maximum $(n_c(n_c - 1)/2)$ number of links that can be found in the partition. The difference with respect to Eq. 4, is that a term $(n_c^{int} - 1)$ is now subtracted. The reason is that, in Ahn *et al.* method, clustering with links implies that two nodes in the same cluster must share links. But, according to our definition of function, two nodes may be structurally equivalent even if there is no interaction between them.

The partition density D is then given by the average of the density of links for all the partitions, weighted by the number of links

$$D = \frac{2}{M} \sum_c m_c \frac{m_c - (n_c - 1)}{(n_c - 2)(n_c - 1)} \tag{13}$$

where M is the total number of links. It was shown that when using agglomerative clustering, this function achieves a maximum which determines the optimal partition [33].

functionInk shifts the attention from links back to nodes (see Fig. 1A). There are a number of reasons justifying this shift:

- Working with nodes is more natural, thus favoring the interpretation of the communities. From a biological perspective, we are interested in the function of nodes. For instance, the definition of "niche" is straightforward for nodes, justifying both the similarity measure definition and the rational behind both the clustering and the definition of partition densities we proposed. In particular, focusing on nodes allowed us to identify both modules and guilds.

- Inspecting and interpreting results is more convenient working with node partitions. For instance, most of the network visualization programs can easily separate communities defined over nodes partitions but not over links partitions.

- Monitoring changes in communities defined over node partitions becomes easier (even more if there are changes in the network such as addition/removal of nodes or links), because the number of links scales as N^2 while the number of nodes scales N (being N the number of nodes), so it may be expected a more profound change in the links partitioning when adding/removing nodes.

Nevertheless, there are some types of networks for which a sharp classification of nodes into communities may be elusive, such as when communities overlap (see section 11 in [5]), a situation motivating the development of the method of Ahn *et al.* [33]. To illustrate this point we perform an explicit comparison between the method of Ahn *et al.* and functioInk with a specific example. The open question to compare both methods is how to determine partitions over sets of nodes from partitions over sets of links. A possibility comes from the identification of sets of nodes whose links belong to the same set of link partition(s), since this is the idea behind the development of functionInk. Therefore, we should find similar communities (clusters in the nodes' partition) if we use the method of Ahn *et al.* to identify a partition of links and i) we then identify communities as those nodes sharing links classified in the same clusters in the partition of links or ii) we find these communities directly with functionInk.

To explore this question, we re-analyze the microbial network shown in Fig. 6 with functionInk considering a single type of link and the communities found at the maximum of the total partition density, together with the partition in links determined with the method of Ahn *et al.*, using average linkage as a clustering algorithm in both cases. In Fig. 8 we show the network in which, for clarity, we removed communities with less than three members (although we kept some nodes with a high density of links).

Partitions defined by Ahn *et al.* method are identified by different colors for the links, and those defined by functionInk by different colors for the nodes (which are further located close in space). It is immediately apparent the good match between both methods, as expected since functionInk departs from the method of Ahn *et al.* For instance, the community labeled G can be defined as the one having cyan, olive, red and blue links. We also observe, however, some differences. Communities B and C are those having only blue links. functionInk splits these nodes in two communities because all three members of community B are linked to the same member in community G, but this is a connection that none of the C-members have, and similarly with respect to two members of community A (although, in this case, one member of C has one such connection). The same applies for communities D and E, which could be defined as those preferentially having red links, but community E is split from D because it has connections with other nodes, in particular with community F. Nevertheless, functionInk is not able to split community H into sub-communities, which is suggested for instance by subsets of nodes having links to several link partitions, e.g. pink and orange links. Even if these communities would be split stopping at an earlier step (for instance at the maximum of the external partition density) thanks to the flexibility provided by the availability of several partition function definitions, it is also clear that functionInk may have difficulties with highly overlapping communities, a situation in which it may be useful to combine both methods.

Clustering algorithm

After computing the similarity between nodes with the method presented in the Results, the algorithm clusters nodes using one of three hierarchical clustering algorithms: average linkage [48], single linkage and complete linkage. Starting from each node being a separate cluster, at each step t all algorithms join the two most similar clusters A and B, and compute the similarity between the new combined cluster and all other clusters C in a way that depends on the clustering algorithm.

Single linkage is the most permissive algorithm, because the similarity it assigns to the new cluster is the maximum similarity between the two clusters joined and clusters C:

$$S^{t+1}(AB, C) = \max\left(S(A, C), S(B, C)\right).$$

where t labels the step of the algorithm, A and B are the clusters that are joined, AB denotes the new composite cluster, and C is any other cluster. On the other hand, complete linkage is the most restrictive, assigning the minimum similarity

$$S^{t+1}(AB, C) = \min\left(S(A, C), S(B, C)\right).$$

Figure 8: **Comparison between functionInk and Ahn *et al.* method** [33]. Microbial network analyzed in Fig. 6 now comparing the partition over the set of nodes found with the total partition density with functionInk (leading to communities of nodes sharing the same color and close in space) and the partition over the set of links found with Ahn *et al.* method (leading to groups of links sharing the same color and connecting similar community nodes). The network is reduced in size and rearranged for the sake of a more clear comparison. Analysis of the communities labeled A-G is found in the text. Note that there is not full correspondence with the communities found in Fig. 6, since we do not use the information from the types of links here.

ν	κ_{mut}	κ_{comp}
0.15	0.08	0
0.35	0.16	0.15
0.6	0.28	0.5

Table 1: **Topological properties of the bipartite networks analyzed.** Different combinations of nestedness (ν), intra-pools connectance κ_{comp} and inter-pools connectance κ_{mut} were analyzed.

Finally, average linkage assigns an intermediate value computed as the weighted average similarity with the two joined clusters

$$S^{t+1}(AB, C) = \frac{n_A S^t(A, C) + n_B S^t(B, C)}{n_A + n_B}$$

being n_A and n_B the number of elements that A and B contain, respectively. Identification of the two pools of plants and animals is independent of the clustering method used, but the maximum of the external partition density is achieved earlier for single linkage and later for complete linkage; we found a good compromise between the number and the size of the clusters working with average linkage, in agreement with previously reported results [32], but the clustering method could be selected according to information known from the links. In our experience, single linkage is easily dominated by the giant cluster in high density networks in which modules are prevalent (rather than for guilds). The appropriate clustering method should be guided by the research question. For instance, if gene homology is explored, it is probably more appropriate to use single linkage (as a relative of one gene's relative is also its relative, i.e. transitivity is automatically fulfilled [4]). On the other hand, if we analyse well-differentiated functional similarity, it might be more appropriate to be conservative and use complete linkage.

Plant-pollinator networks and topological properties

We selected six plant-pollinator networks artificially generated in [39] with known topological properties, summarized in Table. We consider as topological properties the connectance (fraction of links) of the mutualistic matrix, the connectance of the competition matrices, and the definition of nestedness provided in [40]. Given a mutualistic matrix $A_{ik}^{(\mathrm{P})}$ representing presence-absence of interaction between the set of plants, indexed by i, and the set of animal species, indexed by k, we compute the degree of a species as $n_i^{(\mathrm{P})} = \sum_k A_{ik}^{(\mathrm{P})}$ (see Ref. [40] in Supplementary Material). A similar definition would apply for animals $n_k^{(\mathrm{A})} = \sum_i A_{ik}^{(\mathrm{P})}$. Next we define the ecological overlap between two species of plants i and j as the number of insects that pollinate both plants:

$$n_{ij}^{(\mathrm{P})} = \sum_k A_{ik}^{(\mathrm{P})} A_{jk}^{(\mathrm{P})},$$

a definition that is equivalent to the Jaccard similarity used in this work. Summing over every pair of plants and normalizing leads to the definition of nestedness:

$$\nu^{(\mathrm{P})} = \frac{\sum_{i<j} n_{ij}^{(\mathrm{P})}}{\sum_{i<j} \min(n_i^{(\mathrm{P})}, n_j^{(\mathrm{P})})}.$$

A symmetric definition applies for animals, so we take as final definition of nestedness $\nu = \max(\nu^{(\mathrm{P})}, \nu^{(\mathrm{A})})$.

Trophic networks

We downloaded the network and metadata provided in [41] and compared the clusters found with those obtained by functionInk. After computing the Tanimoto coefficients as explained above, we cluster the nodes and retrieve the classification found at each step. We then computed five indexes (Rand, Fowlkes and Mallows, Wallace 10, Wallace 01 and Jaccard), implemented in the R PCI function of the PROFDPM package [42]. In order to assign a significance value for the different indexes we obtained, for each index x, a bootstrapped distribution with mean $\bar{x}_{(\mathrm{B})}$ and standard deviation $\sigma_{(\mathrm{B})}$, resampling with replacement the samples and recomputing the indexes 10^3 times. Next we computed 10^3 completely random classifications, obtained by shuffling the identifiers relating each

sample with one of the classifications, and retrieving the maximum $x_{(R)}$. We finally verified that the random value was significantly different from the bootstrapped distribution by computing the z-scores:

$$z = \frac{\text{abs}(x_{(R)} - \bar{x}_{(B)})}{\sigma_{(B)}},$$

which we considered significant if it was higher than 2.5. Heatmaps were generated with the HEATMAP.2 function in R package GPLOTS.

Bacterial networks

We considered a public dataset of 753 bacterial communities sampled from rainwater-filled beech tree-holes (Fagus spp.) [44], leading to 2874 Operative Taxonomic Units (OTUs) at the 97% of 16 rRNA sequence similarity. These communities were compared with Jensen-Shannon divergence [45], and automatically clustered following the method proposed in Ref. [49] to identify enterotypes. The clusters found with this method in [43] were used to color the community labels in Fig. 6.

The inference of the OTU network started quantifying correlations between OTUs abundances with SparCC [46]. To perform this computation, from the original OTUs we reduced the data set removing rare taxa with less than 100 reads or occurring in less than 10 samples, leading to 619 OTUs. Then, the significance of the correlations was evaluated bootstrapping the samples 100 times the data and estimating pseudo p-values for each of the $N(N-1)/2$ pairs. A relationship between two OTUs was considered significant and represented as a link in the network if the correlation was larger than 0.2 in absolute value and the pseudo p-value lower than 0.01. The network obtained in this way was analyzed using Cytoscape [50].

Supplementary Figures

Figure 9: **Partition densities of synthetic mutualistic networks.** Networks with nestedness $\nu = 0.15$, $\kappa_{\mathrm{mut}} = 0.08$, and $\kappa_{\mathrm{comp}} = 0.5$ (left) or $\kappa_{\mathrm{comp}} = 0.15$ (right). Changing the connectance change the relative value between the external and internal partition densities.

Figure 10: **Partition densities for synthetic mutualistic networks.** Networks with $\kappa_{\mathrm{comp}} = 0.5$, $\kappa_{\mathrm{mut}} = 0.28$ and $\nu = 0.35$ (left) or $\nu = 0.6$ (right). The high connectance of both networks make the internal partition density dominant, and two pools are detected through the total partition density. Nevertheless, the increase of the nestedness is detected through an increase in the external partition density, which makes the second network more disassortative.

Figure 11: **Partition densities of synthetic mutualistic networks.** Network with nestedness $\nu = 0.05$, $\kappa_{\mathrm{mut}} = 0.065$ and $\kappa_{\mathrm{comp}} = 0.15$. The low connectance hinders the detection of the two pools of plants and pollinators.

Figure 12: **Partition density of the trophic network.** The internal partition density peaks when there are three clusters, consistent with the existence of three trophic layers. The external partition density has a maximum at step 69, which is analyzed in detail with respect to the reference classification found in [41].

Figure 13: **Comparison between classifications of the trophic network.** Similarity between the reference classification found in [41] and the one found with functionInk is performed with the Z-score of a different indexes: Wallace 01 (Top left), Fowlkes and Mallows (Top right), Jaccard (Bottom left) and Rand (Bottom right). All indexes bring significant values and the maximum similarity is close to the maximum of the external partition density.

Figure 14: **Partition density of the microbial network.** The external partition density brings a poor reduction in the complexity of the network, with only 22 elements joined, while the internal partition density achieves a higher value and still a good number of clusters. Results suggest that modules are more relevant in this network given the high number of intra-cluster co-occurrences, later confirmed by visual inspection in the Main Text.

References

[1] J. E. Cohen and D. W. Stephens, *Food webs and niche space.* No. 11, Princeton University Press, 1978.

[2] R. MacArthur, "Fluctuations of animal populations and a measure of community stability," *Ecology*, vol. 36, p. 533, July 1955.

[3] M. Kivelä, A. Arenas, M. Barthelemy, J. P. Gleeson, Y. Moreno, and M. A. Porter, "Multilayer networks," *Journal of Complex Networks*, vol. 2, no. 3, pp. 203–271, 2014.

[4] A. Pascual-García, D. Abia, Á. R. Ortiz, and U. Bastolla, "Cross-over between discrete and continuous protein structure space: insights into automatic classification and networks of protein structures," *PLoS Computational Biology*, vol. 5, no. 3, p. e1000331, 2009.

[5] S. Fortunato, "Community detection in graphs," *Physics Reports*, vol. 486, no. 3-5, pp. 75–174, 2010.

[6] S. Allesina and M. Pascual, "Food web models: a plea for groups," *Ecology Letters*, vol. 12, no. 7, pp. 652–662, 2009.

[7] S. Pilosof, M. A. Porter, M. Pascual, and S. Kéfi, "The multilayer nature of ecological networks," *Nature Ecology & Evolution*, vol. 1, no. 4, p. 0101, 2017.

[8] S. Boccaletti, V. Latora, Y. Moreno, M. Chavez, and D.-U. Hwang, "Complex networks: Structure and dynamics," *Physics reports*, vol. 424, no. 4, pp. 175–308, 2006.

[9] A. Carr, C. Diener, N. S. Baliga, and S. M. Gibbons, "Use and abuse of correlation analyses in microbial ecology," *The ISME journal*, p. 1, 2019.

[10] A. Pascual-García, J. Tamames, and U. Bastolla, "Bacteria dialog with santa rosalia: Are aggregations of cosmopolitan bacteria mainly explained by habitat filtering or by ecological interactions?," *BMC Microbiology*, vol. 14, no. 1, p. 284, 2014.

[11] C. S. Elton, *Animal ecology.* New York: The Macmillan Company, 1927.

[12] D. Simberloff and T. Dayan, "The guild concept and the structure of ecological communities," *Annual Review of Ecology and Systematics*, vol. 22, no. 1, pp. 115–143, 1991.

[13] M. E. Newman and E. A. Leicht, "Mixture models and exploratory analysis in networks," *Proceedings of the National Academy of Sciences*, vol. 104, no. 23, pp. 9564–9569, 2007.

[14] M. E. Newman, "Finding community structure in networks using the eigenvectors of matrices," *Physical Review E*, vol. 74, no. 3, p. 036104, 2006.

[15] E. Estrada and J. A. Rodríguez-Velázquez, "Spectral measures of bipartivity in complex networks," *Physical Review E*, vol. 72, no. 4, p. 046105, 2005.

[16] M. T. Schaub, J.-C. Delvenne, M. Rosvall, and R. Lambiotte, "The many facets of community detection in complex networks," *Applied Network Science*, vol. 2, no. 1, p. 4, 2017.

[17] L. Peel, D. B. Larremore, and A. Clauset, "The ground truth about metadata and community detection in networks," *Science advances*, vol. 3, no. 5, p. e1602548, 2017.

[18] M. Girvan and M. E. Newman, "Community structure in social and biological networks," *Proceedings of the National Academy of Sciences*, vol. 99, no. 12, pp. 7821–7826, 2002.

[19] R. Lambiotte, J.-C. Delvenne, and M. Barahona, "Laplacian dynamics and multiscale modular structure in networks," *arXiv preprint arXiv:0812.1770*, 2008.

[20] P. J. Mucha, T. Richardson, K. Macon, M. A. Porter, and J.-P. Onnela, "Community structure in time-dependent, multiscale, and multiplex networks," *Science*, vol. 328, no. 5980, pp. 876–878, 2010.

[21] M. De Domenico, A. Lancichinetti, A. Arenas, and M. Rosvall, "Identifying modular flows on multilayer networks reveals highly overlapping organization in interconnected systems," *Physical Review X*, vol. 5, no. 1, p. 011027, 2015.

[22] M. Bazzi, M. A. Porter, S. Williams, M. McDonald, D. J. Fenn, and S. D. Howison, "Community detection in temporal multilayer networks, with an application to correlation networks," *Multiscale Modeling & Simulation*, vol. 14, no. 1, pp. 1–41, 2016.

[23] S. Wasserman and K. Faust, *Social network analysis: Methods and applications*, vol. 8. Cambridge university press, 1994.

[24] P. W. Holland, K. B. Laskey, and S. Leinhardt, "Stochastic blockmodels: First steps," *Social networks*, vol. 5, no. 2, pp. 109–137, 1983.

[25] C. De Bacco, E. A. Power, D. B. Larremore, and C. Moore, "Community detection, link prediction, and layer interdependence in multilayer networks," *Physical Review E*, vol. 95, no. 4, p. 042317, 2017.

[26] M. E. Newman, "Equivalence between modularity optimization and maximum likelihood methods for community detection," *Physical Review E*, vol. 94, no. 5, p. 052315, 2016.

[27] B. Karrer and M. E. Newman, "Stochastic blockmodels and community structure in networks," *Physical Review E*, vol. 83, no. 1, p. 016107, 2011.

[28] T. Valles-Catala, F. A. Massucci, R. Guimera, and M. Sales-Pardo, "Multilayer stochastic block models reveal the multilayer structure of complex networks," *Physical Review X*, vol. 6, no. 1, p. 011036, 2016.

[29] M. Ganji, J. Chan, P. J. Stuckey, J. Bailey, C. Leckie, K. Ramamohanarao, and I. Davidson, "Image constrained blockmodelling: a constraint programming approach," in *Proceedings of the 2018 SIAM International Conference on Data Mining*, pp. 19–27, SIAM, 2018.

[30] S. P. Borgatti, M. G. Everett, and P. R. Shirey, "LS sets, lambda sets and other cohesive subsets," *Social networks*, vol. 12, no. 4, pp. 337–357, 1990.

[31] J. J. Luczkovich, S. P. Borgatti, J. C. Johnson, and M. G. Everett, "Defining and measuring trophic role similarity in food webs using regular equivalence," *Journal of Theoretical Biology*, vol. 220, no. 3, pp. 303–321, 2003.

[32] P. Yodzis and K. O. Winemiller, "In search of operational trophospecies in a tropical aquatic food web," *Oikos*, pp. 327–340, 1999.

[33] Y.-Y. Ahn, J. P. Bagrow, and S. Lehmann, "Link communities reveal multiscale complexity in networks," *Nature*, vol. 466, no. 7307, pp. 761–764, 2010.

[34] R. Guimera and L. A. N. Amaral, "Cartography of complex networks: modules and universal roles," *Journal of Statistical Mechanics: Theory and Experiment*, vol. 2005, no. 02, p. P02001, 2005.

[35] T. T. Tanimoto, "elementary mathematical theory of classification and prediction," 1958.

[36] S. P. Borgatti and M. G. Everett, "The class of all regular equivalences: Algebraic structure and computation," *Social networks*, vol. 11, no. 1, pp. 65–88, 1989.

[37] A. Harrer and A. Schmidt, "Blockmodelling and role analysis in multi-relational networks," *Social Network Analysis and Mining*, vol. 3, no. 3, pp. 701–719, 2013.

[38] M. G. Everett and S. P. Borgatti, "Exact colorations of graphs and digraphs," *Social networks*, vol. 18, no. 4, pp. 319–331, 1996.

[39] A. Pascual-García and U. Bastolla, "Mutualism supports biodiversity when the direct competition is weak," *Nature Communications*, vol. 8, p. 14326, Feb. 2017.

[40] U. Bastolla, M. A. Fortuna, A. Pascual-García, A. Ferrera, B. Luque, and J. Bascompte, "The architecture of mutualistic networks minimizes competition and increases biodiversity," *Nature*, vol. 458, pp. 1018–1020, Apr. 2009.

[41] S. Kéfi, V. Miele, E. A. Wieters, S. A. Navarrete, and E. L. Berlow, "How structured is the entangled bank? the surprisingly simple organization of multiplex ecological networks leads to increased persistence and resilience," *PLoS Biology*, vol. 14, no. 8, p. e1002527, 2016.

[42] M. S. Shotwell *et al.*, "profdpm: An r package for map estimation in a class of conjugate product partition models," *J Stat Softw*, vol. 53, no. 8, pp. 1–18, 2013.

[43] A. Pascual-García and T. Bell, "Community-level signatures of ecological succession in natural bacterial communities," *bioRxiv*, p. 636233, 2019.

[44] D. W. Rivett and T. Bell, "Abundance determines the functional role of bacterial phylotypes in complex communities," *Nature microbiology*, p. 1, 2018.

[45] D. M. Endres and J. E. Schindelin, "A new metric for probability distributions," *IEEE Transactions on Information Theory*, vol. 49, pp. 1858–1860, July 2003.

[46] J. Friedman and E. J. Alm, "Inferring correlation networks from genomic survey data," *PLoS Computational Biology*, vol. 8, no. 9, p. e1002687, 2012.

[47] M. T. Agler, J. Ruhe, S. Kroll, C. Morhenn, S.-T. Kim, D. Weigel, and E. M. Kemen, "Microbial hub taxa link host and abiotic factors to plant microbiome variation," *PLoS Biology*, vol. 14, no. 1, p. e1002352, 2016.

[48] R. R. Sokal, "A statistical method for evaluating systematic relationships," *Univ Kans Sci Bull*, vol. 38, pp. 1409–1438, 1958.

[49] M. Arumugam, J. Raes, E. Pelletier, D. Le Paslier, T. Yamada, D. R. Mende, G. R. Fernandes, J. Tap, T. Bruls, J.-M. Batto, *et al.*, "Enterotypes of the human gut microbiome," *Nature*, vol. 473, no. 7346, pp. 174–180, 2011.

[50] P. Shannon, A. Markiel, O. Ozier, N. S. Baliga, J. T. Wang, D. Ramage, N. Amin, B. Schwikowski, and T. Ideker, "Cytoscape: a software environment for integrated models of biomolecular interaction networks," *Genome research*, vol. 13, no. 11, pp. 2498–2504, 2003.