Title

Deep-learning-based cell composition analysis from tissue expression profiles.

Kevin Menden[$], Mohamed Marouf, Sergio Oller, Anupriya Dalmia, Karin Kloiber, Peter Heutink, Stefan Bonn[$]

[$] Correspondence to sbonn@uke.de & Kevin.Menden@dzne.de

Abstract

We present Scaden, a deep neural network for cell deconvolution that uses gene expression information to infer the cellular composition of tissues. Scaden is trained on single cell RNA-seq data to engineer discriminative features that confer robustness to bias and noise, making complex data preprocessing and feature selection unnecessary. We demonstrate that Scaden outperforms existing deconvolution algorithms in both precision and robustness. A single trained network reliably deconvolves bulk RNA-seq and microarray, human and mouse tissue expression data and leverages the combined information of multiple data sets. Due to this stability and flexibility, we surmise that deep learning will become an algorithmic mainstay for cell deconvolution of various data types. Scaden's comprehensive software package is easy to use on novel as well as diverse existing expression datasets available in public resources, deepening the molecular and cellular understanding of developmental and disease processes.

Keywords

Cell Deconvolution, Deep Learning, Machine Learning, single cell RNA sequencing, RNA sequencing, Deep Sequencing, Source Separation.

Introduction

The analysis of tissue-specific gene expression using Next Generation Sequencing (RNA-seq) is a centerpiece of the molecular characterization of biological and medical processes *(1)*. A well-known limitation of tissue-based RNA-seq is that it typically measures average gene expression across many molecularly diverse cell types that can have distinct cellular states *(2)*. A change in gene expression between two conditions can therefore be attributed to a change in the cellular composition of the tissue or a change in gene expression in a specific cell population, or a mixture of the two. To deconvolve the cell type composition from a change in gene expression is especially important in systems with cellular proliferation (e.g. cancer) or cellular death (e.g. neuronal loss in Neurodegenerative Diseases) due to systematic cell population differences between experimental groups *(3)*.

To account for this problem, several computational cell deconvolution methods have been proposed during the last years *(4, 5)*. These algorithms utilize gene expression profiles (GEPs) of cell type-specifically expressed genes to estimate cellular fractions using linear regression in order to detect, interpret, and possibly correct for systematic differences in cellular abundance between samples *(4)*. While the best performing linear regression algorithms for deconvolution seem to be variations of Support Vector Regression (SVR) *(6–10)*, the selection of an optimal GEP is a field of active research *(10, 11)*. Indeed, it has been recently shown that the design of the GEP is the most important factor in most deconvolution methods, as results from different algorithms strongly correlate given the same GEP *(11)*.

In theory, an optimal GEP should contain a set of genes that are predominantly expressed within each cell population of a complex sample *(12)*. They should be stably expressed across experimental conditions, for example across health and disease,

and resilient to experimental noise and bias. However, bias is typically inherent to

biomedical data and is imparted, for instance, by intersubject variability, variations

across species, different data acquisition methods, different experimenters, or different

data types. The negative impact of bias on deconvolution performance can be partly

improved by using large, heterogeneous GEP matrices *(11)*. It is therefore not

surprising that recent advancement in cell deconvolution relied almost exclusively on

sophisticated algorithms to normalize the data and engineer optimal GEPs *(10)*.

While GEP-based approaches lay the foundational basis of modern cell deconvolution

algorithms, we hypothesize that Deep Neural Networks (DNNs) could create optimal

features for cell deconvolution, without relying on the complex generation of GEPs.

DNNs such as multilayer perceptrons are universal function approximators that

achieve state-of-the-art performance on classification and regression tasks. Whereas

this feature is of little importance for strictly linear input data, it makes DNNs superior

to linear regression algorithms as soon as data deviates from ideal linearity. This

means, for instance, that as soon as data is noisy or biased and classical linear

regression algorithms may falter, the hidden layer nodes of the DNN learn to represent

higher-order latent representations of cell types that do not depend on input noise and

bias. We theorize, therefore, that by using gene expression information as network

input, hidden layer nodes of the DNN would represent higher-order latent

representations of cell types that are robust to input noise and technical bias.

An obvious limitation of DNNs is the requirement for large training data to avoid

overfitting of the machine learning model. While ground truth information on tissue

RNA-seq cell composition is scarce, one can use single cell RNA-seq (scRNA-seq)

data to obtain virtually unlimited *in silico* tissue datasets of predefined cell composition

(7–9, 13–15). We do this by sub-sampling and subsequently merging cells from

scRNA-seq datasets, this approach being limited only by the availability of tissue-

specific scRNA-seq data. It is to be noted that scRNA-seq data suffers from biases,

such as drop-out, that RNA-seq data is not subject to *(16)*. While this complicates the

use of scRNA-seq data for GEP design *(8)*, we surmise that latent network nodes

could represent features that are robust to such biases.

Based on these assumptions we developed a single-cell-assisted deconvolutional

DNN (Scaden) that uses simulated bulk RNA-seq samples for training and predicts

cell type proportions for input expression samples of cell mixtures. Scaden is trained

on publicly available scRNA- and RNA-seq data, does not rely on specific GEP

matrices, and automatically infers informative features. Finally, we show that Scaden

deconvolves expression data into cell types with higher precision and robustness than

existing methods that rely on GEP matrices.

Results

Scaden Overview, Model Selection, and Training

In this part we focus on the design and optimization of Scaden by training, validation,

and testing on *in silico* data. Note that the generation of in silico data is a strictly linear

mathematical operation. Our aim in this context, in order to corroborate Scaden's basic

functionality, is to show that Scaden's performance compares with (but not necessarily

exceeds) that of state-of-the-art algorithms.

The basic architecture of Scaden is a DNN that takes gene counts of RNA-seq data

as input and outputs predicted cell fractions (Fig. 1). To optimize the performance of

the DNN, it is trained on data that contains both the gene expression and the real cell

type fraction information (Fig. 1B). The network then adjusts its weights to minimize

the error between the predicted cell fractions and the real cell fractions (Fig. 1C).

For the model selection and training we made use of the virtually unlimited amount of

artificial bulk RNA-seq datasets with defined composition that can be generated *in*

silico from published scRNA-seq and RNA-seq datasets (simulated tissues) (Fig. 1A,

Tables S1 & S2). The only constraint is that the scRNA-seq and RNA-seq data must

come from the same tissue as the bulk data subject to deconvolution.

To find the optimal DNN architecture for cell deconvolution, we generated bulk PBMC

(peripheral blood mononuclear cells) RNA-seq data from four publicly available

scRNA-seq data sets (Tables S1 & S3). We performed leave-one-dataset-out cross

validation, training Scaden on mixtures of synthetic datasets from three scRNA-seq

datasets and evaluating the performance on simulated tissue from a fourth scRNA-

seq dataset.

We used the root mean square error (RMSE), Pearson's correlation coefficient (r), the

slope and intercept of the regression fitted for ground truth and predicted cell fractions,

and Lin's concordance correlation coefficient (CCC) *(17)* to assess algorithmic

performance. The CCC is a measure sensitive not only to scatter but also to deviations

from linearity (slope and intercept). Within the main text, we report on CCC and RMSE

values only, other metrics can be found in the supplements.

The final Scaden model is an ensemble of the three best performing models (Table

S4) and the final cell type composition estimates are the averaged predictions of all

three ensemble models (Fig. 1 & S1). Using an ensemble of models increased the

deconvolution performance as compared to single best models (Table S6). Details of

the model and hyper-parameters are given in Table S5. We also evaluated the effect

of the size of the training data set on Scaden deconvolution performance, repeating

leave-one-dataset-out cross validation on PBMC data with training dataset sizes from

150 up to 15,000 samples (Fig. S2). The increase in CCC value starts to level off from

about 1,500 simulated samples for this data set but continues to increase slowly with

sample size. We specifically addressed the question to what degree the DNN, trained

on simulated samples, tends to overfit, failing to generalize to real bulk RNA-seq data.

To understand after how many steps a model trained on *in silico* data overfits on real

RNA-seq data, we trained Scaden on simulated data from an ascites scRNA-seq

dataset (Table S1, 6,000 samples) and evaluated the loss function on a corresponding

annotated RNA-seq dataset *(18)* (Table S2, 3 samples) as a function of the number of

steps (Fig. S3). All models converged after approximately 5,000 steps, and slightly

overfit when trained for longer. Based on this result, we opted for an early-stop

approach after 5,000 steps for evaluation on real bulk RNA-seq data.

Figure 1 *Overview of training data generation and cell type deconvolution with Scaden*. A:
Artificial bulk samples are generated by subsampling random cells from a scRNA-seq datasets
and merging their expression profiles. B: Model training and parameter optimization on
simulated tissue RNA-seq data by comparing cell fraction predictions to ground-truth cell
composition. C: Cell deconvolution of real tissue RNA-seq data using Scaden.

We then compared Scaden to four state-of-the-art GEP-based cell deconvolution

algorithms, CIBERSORT (CS) *(6)*, CIBERSORTx (CSx) *(7)*, MuSiC *(8)*, and Cell

Population Mapping (CPM) *(9)*. While CS relies on hand-curated GEP matrices, CSx,

MuSiC, and CPM can generate GEPs using scRNA-seq data as input.

To get an initial estimate of Scaden's deconvolution fidelity we trained the model on

24,000 simulated PBMC RNA-seq samples from three datasets and tested its

performance in comparison to CS, CSx, MuSiC and CPM on a fourth dataset of 500

samples each (e.g. training on data6k, data8k, donorA and evaluation on donorC). We

used corresponding scRNA-seq data sets for the construction of GEPs as input for

CSx and MuSiC, and CPM. For CS we used the PBMC-optimized LM22 GEP

matrix*(6)*, which was developed by the CS authors for the deconvolution of human

PBMC data.

Figure 2 *Deconvolution performance on simulated tissue data* A: Boxplots of the cell type prediction concordance correlation coefficient (CCC) and RMSE for four simulated PBMC datasets. Tables S14 and S16 contain information on the five (six for CS) cell types used. B: Scatterplots for four pancreas cell types of ground truth (x-axis) and predicted values (y-axis) for Scaden, CSx, and MuSiC on artificial pancreas data*(19)*. Numbers inside the plotting area signify CCC values.

For two of four test datasets (donorA, donorC), Scaden obtained the highest CCC and

lowest RMSE, followed by CSx, MuSiC, CS, and CPM (Fig. S4, Table S7). CSx and

MuSiC obtained the highest CCC values for the data8k and data6k datasets,

respectively. Scaden obtained the highest average CCC and lowest RMSE (0.88,

0.08, respectively), followed by MuSiC (0.85, 0.10), CSx (0.83, 0.11), CS (0.63 0.15),

and CPM (0, 0.20) (Fig. S4). As expected, all algorithms that use scRNA-seq data as

reference performed well, with the notable exception of CPM. We want to mention that

CPM focuses on the reconstruction of continuous spectra of cellular states, while it

incorporates cell deconvolution as an additional feature. We therefore report CPM's

deconvolution performance in the supplementary material from here on. On average,

Scaden also obtained the highest correlation and the best intercept and slope values

on simulated PBMC data (Table S7). A closer inspection on a per cell type bases (Fig.

2A) revealed that Scaden yields consistently higher CCC values and lower RMSEs

when compared to the other algorithms.

A specific feature of the MuSiC algorithm is that it preferentially weighs genes

according to low inter-subject and intra-cell cluster variability for its GEP, which

increases deconvolution robustness when high expression heterogeneity is observed

between human subjects, for example *(8)*. To understand if Scaden can utilize multi-

subject information to increase its deconvolution performance, we trained Scaden,

CSx, and MuSiC on scRNA-seq pancreas data from several subjects *(20)* and

assessed the performance on a separate simulated pancreas RNA-seq dataset *(19)*.

To allow for direct comparison, we chose the same pancreas training and test datasets

that were used in the original MuSiC publication (Table S1). To enable Scaden to

leverage the heterogeneity of multi-subject data, training data was generated

separately for every subject in the dataset (see Methods). CSx cannot profit from multi-

subject data but performed well on the artificial PBMC datasets and was therefore

included in the comparison. The best average performance (across cell types) is

achieved by Scaden (CCC = 0.98), closely followed by MuSiC (CCC = 0.93), while

CSx does not perform as well (CCC = 0.75) (Fig. 2B, Table S8). On a per cell-type

basis, Scaden's predictions are clearly superior to the other two algorithms for all cell

types. This provides strong evidence that Scaden, by separating training data

generation for each subject, can learn inter-subject heterogeneity and outperform

specialized multi-subject algorithms such as MuSiC on the cell-type deconvolution

task.

Additionally, we wanted to test how the best performing deconvolution algorithms

Scaden, MuSiC, and CSx behave when unknown cell content is part of the mixture.

To test this, all cells falling into the 'Unknown' category were removed from the training

or reference PBMC datasets but added to the simulated mixture samples at fixed

percentages (5%, 10%, 20%, 30%) (see Methods). Scaden obtains the highest CCC

for all tested percentages of unknown cell content (Fig. S5, Table S9). The general

deconvolution performance declines linearly with increasing percentage of unknown

content for all tested algorithms, indicating that Scaden, MuSiC, and CSx have a

similar robustness against unknown mixture content.

Robust deconvolution of bulk expression data

The true use case of cell deconvolution algorithms is the cell fraction estimation of

tissue RNA-seq data. Especially for noisy and biased bulk RNA-seq data we

hypothesize that Scaden's latent feature representations might help it to more robustly

predict cell fractions as compared to GEP-based algorithms.

We therefore assessed the performance of Scaden, CS, CSx, and MuSiC to

deconvolve two publicly available human PBMC bulk RNA-seq datasets, for which

curated GEP matrices as well as RNA-seq data with associated ground truth cell type

compositions from flow cytometry are available. We will refer to these datasets that

consists of 12 samples each as PBMC1 *(21)* and PBMC2 *(10)* (Table S2).

Deconvolution for all methods was performed as described in the previous section,

with the difference that data from all four PBMC scRNA-seq datasets was now

deployed for Scaden training. Results are given in Fig. 3A, B & C and Tables S10 &

S11.

Figure 3 *Deconvolution of real tissue RNA-seq data* A: Per-cell-type scatterplots of ground

truth (x-axis) and predicted values (y-axis) for Scaden, CS, CSx and MuSiC on real PBMC1

and PBMC2 cell fractions. Numbers inside the plotting area signify CCC values. For Scaden,

the CCC using only scRNA-seq training data (in parenthesis) and the CCC using mixed

scRNA-seq and RNA-seq training data is shown. B: Boxplots of CCC values for real PBMC1

(first column) and PBMC2 (second column) data. C: RMSE values for real PBMC1 (first

column) and PBMC2 (second column) data. D: Prediction of human brain cell fractions of the

ROSMAP dataset using the Darmanis data set as reference: Scatterplots of ground truth (x-

axis) and predicted values (y-axis) for Scaden, CSx, MuSiC, of data. CCC values are shown

as inserts. E: Per cell type CCC values for ROSMAP using the Darmanis data as reference.

F: Neuronal content determined by Scaden trained on mouse brain data and evaluated on the

Braak stage of the ROSMAP study.

On the PBMC1 dataset and using all cell types, Scaden obtained the highest CCC and

lowest RMSE (0.56, 0.13), while CSx (0.55, 0.16) and CS (0.43, 0.15) performed well

yet significantly worse than Scaden (Fig. 3A, Tables S10 & S11). CPM (0, 0.18) and

MuSiC (-0.19, 0.32) both failed to deconvolve the cell fractions of the PBMC1 data.

Scaden also obtained the best CCC and RMSE (0.68, 0.08) on the PBMC2 dataset,

while CS (0.58, 0.10) and CSx (0.42, 0.13) obtained good deconvolution results.

Similar to the PBMC1 data deconvolution results, CPM (-0.16, 0.11) as well as MuSiC

(-0.13, 0.30) did not perform well on the PBMC2 deconvolution task. In addition to

CCC and RMSE metrics, Scaden achieves the best correlation, intercept and slope

on both PBMC datasets (Tables S10 & S11).

In particular, Scaden outperforms classical algorithms on a per cell-type basis (Fig. 3B

& C). These results show weaker correlations and a strong dependence on the cell

type. A closer examination of the metrics in Table S11 and Figure S6 shows that the

largest variations are found in the slope and intercept.

An additional algorithmic feature of Scaden is that it seamlessly integrates increasing

amounts of training data, which can be of different types, such as a combination of

simulated tissue and real tissue data with cell fraction information. In theory, even

limited real tissue training data could make Scaden robust to data type bias and

consequently improve Scaden's deconvolution performance on real tissue data. We

therefore trained Scaden on a mix of simulated PBMC and real PBMC2 (12 samples)

data and evaluated its performance on real PBMC1 data (Fig. 3A & B, S6, Tables 10

& S11). While the training contained very little (~2%) real data, Scaden's CCC

increased from 0.56 to 0.72 and the RMSE decreased from 0.13 to 0.10. We observed

similar performance increases when Scaden was trained on simulated PBMC and real

PBMC1 data and evaluated on real PBMC2 data (Fig. 3A & B, S6, Tables 10 & S11).

This further validates that Scaden reliably deconvolves tissue RNA-seq data into the

constituent cell fractions and that very accurate deconvolution results can be obtained

if reference and target datasets are from the same experiment.

We next wanted to test how the algorithm performs on post-mortem human brain

tissue of a subsample from the ROSMAP study *(22)*, for which ground truth cell

composition information was recently measured by immunohistochemistry (41

samples with all cell types given) *(23)*. The data provided by this study consists of bulk

RNA-seq data from the dorsolateral prefrontal cortex (DLPFC) and poses a special

challenge due to the complexity of its cell type composition, which is further

complicated by the fact that data originates from brains of healthy individuals as well

as AD (Alzheimer Disease) patients at various stages of neuronal loss. As reference

datasets, we used the scRNA-seq dataset provided by Darmanis *et al. (24)* from the

anterior temporal lobe of living patients and the Lake dataset that isolates nuclei of

neurons from two (visual and frontal) cortical regions from a postmortem brain and

subjects them to RNA sequencing *(25)*. From these, we generated 2000 training

samples (Darmanis) and 4000 samples (two regions from the Lake dataset).

Fig. 3D shows the deconvolution results for all three algorithms with the Darmanis

(scRNA-seq) reference dataset. Scaden achieves the highest CCC value (0.92)

followed by MuSiC (0.87) and CSx (0.81) (Table S12). Compared to Scaden, MuSiC

and CSx overestimate neural percentages, leading to higher RMSE values of 0.09 and

0.12, respectively (Scaden: 0.06). Notably, all methods showed a lower concordance

correlation coefficient on the per cell type level (Fig. 3E), demonstrating that some per-

cell-type correlations are poor, either in slope, intercept, variance, or a combination of

them. This emphasizes the need for a cell type-specific inspection of results and

highlights that, depending on the dataset, cell type-specific deconvolution results can

be far from perfect.

In addition to comparing the predictive power of Scaden, CSx and MuSiC on human

brain tissue with different reference datasets, we also tested how the choice of

reference datasets affected Scaden's deconvolution results. Notably, all methods

significantly drop in performance when the Lake snRNA-seq dataset is used as

reference as we had presumed (Figure S7A). We want to emphasize that Scaden, in

contrast to CSx and MuSiC, has the possibility to simultaneously use both datasets as

reference, whereas for CSx and MuSiC, the user has to choose one of the two,

unaware which will give the correct results.

Indeed, we found that the performance of Scaden was almost unaffected when the

Lake dataset was added to the training samples (CCC=0.90, RMSE=0.06) (Figure

S7A, Table S12). Finally, when calculating the CCC values on a per-sample basis,

Scaden achieves the best scores for most samples (Figure S7B).

In a next step, we wanted to assess whether Scaden's deconvolution performance

was robust across species by trying to predict the cell fractions of the ROSMAP study

(22) with a Scaden model trained on *in silico* data from five mouse brain scRNA-seq

datasets (Table S1). Intriguingly, Scaden was able to achieve a CCC value of 0.83

and an RMSE of 0.079 (Figure 3D, left panel), showing that Scaden can reliably

deconvolve RNA-seq data across related species.

The ROSMAP study also contains information on the Braak stages *(26)* corresponding

to 390 human post-mortem prefrontal cortex samples, which correlate with the severity

and progression stage of AD and the degree of neuronal loss. We used the Scaden

model trained on artificial data generated from five mouse brain scRNA-seq datasets

to predict neuronal cell fractions of this larger human dataset. Overall, Scaden's cell

fraction predictions capture the increased neuronal loss with increasing Braak stage

(Fig. 3F). Interestingly, the largest drop in neural percentage is observed at stage 5,

when the neurodegeneration typically reaches the prefrontal cortex of the brain.

Given the robustness with which Scaden predicts tissue RNA-seq cell fractions using

scRNA-seq training data, even across species, we next wanted to investigate if a

scRNA-seq-trained Scaden model can also deconvolve other data types. To this end,

we measured the deconvolution performance on a bulk PBMC microarray dataset (20

samples)*(6)* of a Scaden model trained on scRNA-seq and RNA-seq PBMC data (see

above). We compared Scaden to CS using the microarray-derived LM22 matrix. CS

achieved a slightly higher CCC and slightly lower total RMSE (0.72, 0.11) than Scaden

(0.71, 0.13), while Scaden obtained the highest average CCC (0.50) compared to CS

(0.39) (Fig. S8, Table S13). Notably in this scenario, Scaden was trained entirely on

simulated scRNA-seq and RNA-seq data, while CS's LM22 GEP was optimized on

PBMC microarray data.

Overall, we provide strong evidence that Scaden robustly deconvolves tissue data

across tissues, species, and even data types.

Discussion

Scaden is a novel deep learning-based cell deconvolution algorithm that in many instances compares favorably in both prediction robustness and accuracy to existing deconvolution algorithms that rely on GEP design and linear regression. We believe that Scaden's performance relies to a large degree on the inherent feature engineering of the DNN. The network does not only select features (genes) for regression, it also creates novel features that are optimal for the regression task in the nodes of the hidden layers. These hidden features are non-linear combinations of the input features (gene expression), which makes it notoriously difficult to explain how a DNN works *(27)*. It is important to highlight that this feature creation is fundamentally different from all other existing cell deconvolution algorithms, which rely on heuristics that select a defined subset of genes as features for linear regression.

Another advantage of this inherent feature engineering is that Scaden can be trained to be robust to input noise and bias (e.g. batch effects). Noise and bias are all prevalent in experimental data, due to different sample quality, sample processing, experimenters, and instrumentation, for example. If the network is trained on different datasets of the same tissue, however, it learns to create hidden features that are robust to noise and bias, such as batch effects. This robustness is pivotal in real world cell deconvolution use cases, where the bulk RNA data for deconvolution and the training data (and therefore the network and GEP) contain different noise and biases. While especially recent cell deconvolution algorithms include batch correction heuristics prior to GEP construction, Scaden optimizes its hidden features automatically when trained on data from various batches.

The robustness to noise and bias, which might be due to hidden feature generation, is especially evident in Scaden's ability to deconvolve across data types. A network

trained on *in silico* bulk RNA-seq data can seamlessly deconvolve microarray data of

the same tissue. This is quite noteworthy, as microarray data is known to have a

reduced dynamic range and several hybridization-based biases compared to RNA-

seq data. In other words, Scaden can deconvolve bulk data of types it has never been

trained on, even in the face of strong data type bias. This raises the possibility that

Scaden trained on scRNA-seq data might reliably deconvolve other bulk omics data

as well, such as proteomic and metabolomic data. This assumption is strengthened

by the fact that Scaden, trained on scRNA-seq data, attains state-of-the-art

performance on the deconvolution of bulk RNA-seq data, two data types with very

distinct biases *(16)*.

As highlighted in the introduction, a drawback for many DNNs is the large amount of

training data required to obtain robust performance. Here, we used scRNA-seq data

to create virtually unlimited amounts of *in silico* bulk RNA-seq data of predefined type

(target tissue) with known composition, across datasets. This immediately highlights

Scaden's biggest limitation, the dependency on scRNA-seq data of the target tissue.

In this study we have shown that Scaden, trained solely on simulated data from

scRNA-seq datasets, can outperform GEP-based deconvolution algorithms. We did

observe, however, that the addition of labeled RNA-seq samples to the training data

did significantly improve deconvolution performance in the case of PBMC data. We

therefore believe that efforts to increase the similarity between simulated training data

and the target bulk RNA-seq data could increase Scaden's performance further.

Mixtures of *in silico* bulk RNA-seq data and publically available RNA-seq data, of

purified cell types for example, could further increase the deconvolution performance

of Scaden. Furthermore, domain adaptation methods can be used to improve

performance of models that are trained on data (here, scRNA-seq data) that is similar

to the target data (here, RNA-seq data) *(28)*. In future versions, Scaden's simple

multilayer perceptron architecture could leverage domain adaptation to further

stabilize and improve its cell deconvolution performance.

Recent cell deconvolution algorithms have used cell fraction estimates to infer cell

type-specific gene expression from bulk RNA-seq data. It is straightforward to use

Scaden's cell fraction estimates to infer per group *(3)* and per sample *(7)* cell type-

specific gene expression using simple regression or non-negative matrix factorization,

respectively. We would like to add a note of caution, however, as the error of cell

fraction estimates, which can be quite significant, is propagated into the gene

expression calculations and will affect any downstream statistical analysis.

In summary, the deconvolution performance, robustness to noise and bias, the

flexibility to learn from large numbers of *in silico* datasets, across data types (scRNA-

seq and RNA-seq mixtures), and potentially even tissues makes us believe that DNN-

based architectures will become an algorithmic mainstay of cell type deconvolution.

Methods

Datasets and pre-processing

scRNA-seq datasets

The following human PBMC scRNA-seq datasets were downloaded from the 10X Genomics data download page: 6k PBMCs from a Healthy Donor, 8k PBMCs from a Healthy Donor, Frozen PBMCs (Donor A), Frozen PBMCs (Donor C) *(29)*. Throughout this paper, these datasets are referred to with the handles data6k, data8k, donorA and donorC, respectively. It was not intended to incorporate as many datasets as possible. Instead, these four datasets were chosen with the goal to dispose of a set of samples with consistent cell types and gene expression. This limited our choice to datasets that displayed clearly identifiable cell types for the majority of cells. The Ascites scRNA-seq dataset was downloaded from https://figshare.com as provided by Schelker *(18)*. Pancreas and mouse brain datasets were downloaded from the scRNA-seq dataset collection of the Hemberg lab (https://hemberg-lab.github.io/scRNA.seq.datasets/). The human brain datasets from Darmanis *et al.* and Lake *et al.* where downloaded from GEO with accession numbers GSE67835 and GSE97930, respectively. A table listing all datasets including references to the original publications can be found in Table S1.

scRNA-seq preprocessing and analysis

All datasets were processed using the Python package Scanpy (v. 1.2.2) *(30)* following the Scanpy's reimplementation of the popular Seurat's clustering workflow. First, the corresponding cell-gene matrices were filtered for cells with less than 500 detected genes, and genes expressed in less than 5 cells. The resulting count matrix for each

dataset was filtered for outliers with high or low numbers of counts. Gene expression

was normalized to library size using the Scanpy function 'normalize_per_cell'. The

normalized matrix of all filtered cells and genes was saved for the subsequent data

generation step.

The following processing and analysis steps had the sole purpose of assigning cell

type labels to every cell. All cells were clustered using the louvain clustering

implementation of the Scanpy package. The louvain clustering resolution was chosen

for each dataset, using the lowest possible resolution value (low resolution values lead

to less clusters) for which the calculated clusters separated the cell types

appropriately. The top 1000 highly variable genes were used for clustering, which were

calculated using Scanpy's 'filter_genes_dispersion' function with parameters

min_mean=0.0125, max_mean=3 and min_disp=0.5. Principal Component Analysis

(PCA) was used for dimensionality reduction.

To identify cell types, marker genes were investigated for all cell types in question. For

PBMC datasets, useful marker genes were adopted from public resources such as the

Seurat tutorial for 2700 PBMCs*(31)*. Briefly, IL7R was taken as marker for CD4 T-cells,

LYZ for Monocytes, MS4A1 for B-cells, GNLY for Natural Killer cells, FCER1A for

Dendritic cells and CD8A and CCL5 as markers for CD8 T-cells. For all other scRNA-

seq datasets, marker genes and expected cell types were inferred from the original

publication of the dataset. For instance, to annotate cell types of the mouse brain

dataset from Zeisel *et al. (32)*, we used the same marker genes as Zeisel and

colleagues. We did not use the same cell type labels from the original publications

because a main objective was to assure that cell type labeling is consistent between

all datasets of a certain tissue.

Cell type annotation was performed manually across all the clusters for each dataset,

such that all cells belonging to the same cluster were labeled with the same cell type.

The cell type identity of each cluster was chosen by crossing the cluster's highly

differentially expressed genes with the curated cell type's marker genes. Clusters that

could not be clearly identified with a cell type were grouped into the 'Unknown'

category.

Tissue Datasets for Benchmarking

To assess the deconvolution performance on real tissue expression data, we used

datasets for which the corresponding cell fractions were measured and published. The

first dataset is the PBMC1 dataset which was obtained from Zimmermann *et al.(21)*.

The second dataset, PBMC2, was downloaded from GEO with accession code

GSE107011*(10)*. This dataset contains both RNA-seq profiles of immune cells (S4

cohort) and from bulk individuals (S13 cohort). As we were interested in the bulk

profiles, we only used 12 samples from the S13 cohort from this data. Flow cytometry

fractions were collected from the Monaco *et al.* publication.

In addition to the above mentioned two PBMC datasets, we used Ascites RNA-seq

data. This dataset was kindly provided by the authors and cell type fractions for this

dataset were taken from the supplementary materials of the publication *(18)*.

For the evaluation on pancreas data, artificial bulk RNA-seq samples created from the

scRNA-seq dataset of Xin *et al. (19)* were used. This dataset was downloaded from

the resources of the MuSiC publication*(8)*. The artificial bulk RNA-seq samples used

for evaluation were then created using the 'bulk_construct' function of the MuSiC tool.

To assess how Scaden and the GEP algorithms deal with the presence of unknown

cell types, we generated PBMC bulk RNA samples from the four scRNA-seq datasets

(6000 each). The undefined amount of unknown cells that was generated by this

approach was removed to be replaced by defined amounts of 5%, 10%, 20%, 30% of

unknown cells, respectively. Cell fractions of all four samples were predicted with

Scaden trained on the other three.

Performance on these samples was then assessed to test robustness against unseen

cell types in the bulk mixture. Scaden was trained on samples from all datasets but

the test dataset, while CSx and MuSiC used data8k as a reference.

The microarray dataset GSE65133 was downloaded from GEO, and cell type fractions

taken from the original CS publication *(6)*.

Finally, we wanted to get insights into neurodegenerative cell fraction changes in the

brain. While it is known that neurodegenerative diseases like Alzheimer's Disease are

accompanied by a gradual loss of brain neurons, stage-specific cell type shifts are still

hard to come by. Here we use the ROSMAP (Religious Orders Study and Memory and

Aging Project Study) cortical RNA-seq dataset along with the corresponding clinical

metadata, to infer cell type composition over six clinically relevant stages of

neurodegeneration *(22)*. Furthermore, to assess deconvolution accuracy on post-

mortem human brain tissue, we used 41 samples from the ROSMAP (Religious Orders

Study and Memory and Aging Project), for which cell composition information from

immunohistochemistry *(23)* was recently released and for which fractions for all cell

types were reported. The ROSMAP RNA-seq data was downloaded from

https://www.synapse.org/. The cell composition values were kindly provided by the

authors of the study *(23)*.

RNA-seq preprocessing and analysis

For the RNA-seq datasets analyzed in this study, we did not apply any additional

processing steps, but used the obtained count or expression tables directly as

downloaded for all dataset except the ROSMAP dataset. For the latter, we generated

count tables from raw FastQ-files using Salmon *(33)* and the GRCh38 reference

genome. FastQ-files from the ROSMAP study were downloaded from Synapse

(www.synapse.org).

Simulation of bulk RNA-seq samples from scRNA-seq data

Scaden's deep neural network requires large amounts of training RNA-seq samples

with known cell fractions. This explains why the generation of artificial bulk RNA-seq

data is one of the key elements of the Scaden workflow.

In order to generate the training data, preprocessed scRNA-seq datasets were used

(see section 'Data Collection and Processing'), comprising the gene expression matrix

and the cell type labels. Artificial RNA-seq samples were simulated by sub-sampling

cells from individual scRNA-seq datasets - cells from different datasets were not

merged into samples to preserve within-subject relationships. Datasets generated

from multiple subjects were split according to subject and each sub-sampling was

constrained to cells from one subject in order to capture the cross-subject

heterogeneity and keep subject-specific gene dependencies.

The exact sub-sampling procedure is described in the following. First, for every

simulated sample, random fractions were created for all different cell types within each

scRNA-seq dataset using the random module of the Python package NumPy. Briefly,

a random number was chosen from a uniform distribution between 0 and 1 using the

NumPy function 'random.rand()' for each cell type, and then this number was divided

by the sum of all random numbers created to ensure the constraint of all fractions

adding up to 1:

506
$$f_c = \frac{r_c}{\sum_{C_{all}} r_c}$$

507　where r_c is the random number created for cell type c, and C_{all} is the set of all cell

508　types. Here, f_c is the calculated random fraction for cell type c. Then, each fraction

509　was multiplied with the total number of cells selected for each sample, yielding the

510　number of cells to choose for a specific cell type:

512
$$N_c = f_c * N_{total}$$

where N_c is the number of cells to select for the cell type c, and N_{total} is the total

number of cells contributing to one simulated RNA-seq sample (500, in this study).

Next, N_c cells were randomly sampled from the scRNA-seq gene expression matrix

for each cell type c. Afterwards, the randomly selected single-cell expression profiles

for every cell type are then aggregated by summing their expression values, to yield

the artificial bulk expression profile for this sample.

Using the above described approach, cell compositions that are strongly biased

toward a certain cell type or are missing specific cell types are rare among the

generated training samples. To account for this and to simulate cell compositions with

a heavy bias to and the absence of certain cell types, a variation of the sub-sampling

procedure was used to generate samples with sparse compositions, which we refer to

as sparse samples. Before generating the random fractions for all cell types, a random

number of cell types was selected to be absent from the sample, with the requirement

of at least one cell type constituting the sample. After these leave-out cell types were

chosen, random fractions were created and samples generated as described above.

Using this procedure, we generated 32,000 samples for the human PBMC training

dataset, 14,000 samples for the human pancreas training dataset, 6000 samples for

human brain, and 30,000 samples for the mouse brain training dataset (Table S3).

Artificial bulk RNA-seq datasets were stored in 'h5ad' format using the Anndata

package*(30)*, which allows to store the samples together with their corresponding cell

type ratios, while also keeping information about the scRNA-seq dataset of origin for

each sample. This allowed to access samples from specific datasets, which is useful

for cross validation.

Scaden Overview

538 The following section contains an overview of the input data preprocessing, the

539 Scaden model, model selection, and how Scaden predictions are generated.

Input Data Preprocessing

The data preprocessing step is aimed to make the input data more suitable for

machine learning algorithms. To achieve this, an optimal preprocessing procedure

should transform any input data from the simulated samples or from the bulk RNA-seq

to the same feature scale. Before any scaling procedure can be applied, it must be

ensured that both the training data and the bulk RNA-seq data subject to prediction

share the same features. Therefore, before scaling, both datasets are limited to

contain features (genes) that are available in both datasets. The two-step processing

procedure used for Scaden is described in the following:

First, to account for heteroscedasticity, a feature inherent to RNA-seq data, the data

was transformed into logarithmic space by adding a pseudocount of 1 and then taking

the Logarithm (base 2).

Second, every sample was scaled to the range [0,1] using the MinMaxScaler() class

from the Sklearn preprocessing module. Per sample scaling, unlike per feature scaling

that is more common in machine learning, assures that inter-gene relative expression

patterns in every sample are preserved. This is important, as our hypothesis was that

a neural network could learn the deconvolution from these inter-gene expression

patterns.

$$x_{scaled,i} = (x_i - min(\boldsymbol{X_i})) / (max(X_i) - min(X_i))$$

where $x_{scaled,i}$ is the log2 expression value of gene x in sample i, X_i is the vector of log2 expression values for all genes of sample i, $min(\boldsymbol{X_i})$ is the minimum gene expression of vector X_i, and $max(X_i)$ the maximum gene expression of vector X_i. Note that all training datasets are stored as expression values and are only processed as described above. In the deployment use-case the simulated training data should contain the same features as in the bulk RNA-seq sample that shall be deconvolved.

Model Selection

The goal of model selection was to find an architecture and hyperparameters that robustly deconvolve simulated tissue RNA-seq data and, more importantly, real bulk RNA-seq data. Due to the very limited availability of bulk RNA-seq datasets with known cell fractions, model selection was mainly optimized on the simulated PBMC datasets. To capture inter-experimental variation, we used leave-one-dataset-out cross validation for model optimization: a model was trained on simulated data from all but one dataset, and performance was tested on simulated samples from the left-out dataset. This allows to simulate batch effects between datasets and helps to test the generalizability of the model. In the process of model selection and (hyper-) parameter optimization, performed on PBMC and Ascites datasets, we found three models with different architectures and dropout rates but comparable performance. In order to address overfitting in individual models, we decided to use a combination of models, expecting this to serve as another means of regularization. We did not test multiple combinations, but rather used an informed choice with varying layer sizes and dropout regularization, with the goal to increase model diversity. We observed that the average

of an ensemble of models generalized better to the test sets than individual models.

Model training and prediction is done separately for each model, with the prediction

averaging step combining all model predictions (Fig. S1, Tables S4 & S6). We provide

a list of all tested parameters in the supplementary materials (Table S5).

Final Scaden Model

The Scaden model learns cell type deconvolution through supervised training on

datasets of simulated bulk RNA-seq samples simulated with scRNA-seq data. To

account for model biases and to improve performance, Scaden consists of an

ensemble of three deep neural networks with varying architectures and degrees of

dropout regularization. All models of the ensemble use four layers of varying sizes

between 32 and 1024 nodes, with dropout-regularization implemented in two of the

three ensemble models. The exact layer sizes and dropout rates are listed in Table

S4. The Rectified Linear Unit (ReLU) is used as activation function in every internal

layer. We used a Softmax function to predict cell fractions, as we did not see any

improvements in using a linear output function with consecutive non-negativity

correction and sum-to-one scaling. Python (v. 3.6.6) and the TensorFlow library (v.

1.10.0) were used for implementation of Scaden. A complete list of all software used

for the implementation of Scaden is provided in Table S15.

Training and Prediction

After the preprocessing of the data a Scaden ensemble can be trained on simulated

tissue RNA-seq data or mixtures of simulated and real tissue RNA-seq data.

Parameters are optimized using Adam with a learning rate of 0.0001 and a batch size

of 128. We used an L1 loss as optimization objective:

$$L1(y_i, \hat{y}_i) = |y_i - \hat{y}_i|$$

where y_i is the vector of ground truth fractions of sample i and $\hat{y}_i$ is the vector of

predicted fractions of sample i. Each of the three ensemble models is trained

independently for 5,000 steps. This 'early stopping' serves to avoid domain overfitting

on the simulated tissue data, which would decrease the model performance on the

real tissue RNA-seq data. We observed that training for more steps lead to an average

performance decrease on real tissue RNA-seq data. To perform deconvolution with

Scaden, a bulk RNA-seq sample is fed into a trained Scaden ensemble and three

independent predictions for the cell type fractions of this sample are generated by the

trained deep neural networks. These three predictions are then averaged per cell type

to yield the final cell type composition for the input bulk RNA-seq sample:

$$\widehat{y_c} = \frac{\widehat{y_c^1} + \widehat{y_c^2} + \widehat{y_c^3}}{3}$$

where $\widehat{y_c}$ is the final predicted fraction for cell type c and $\widehat{y_c^i}$ is the predicted fraction for

cell type c of model i.

Scaden requirements

Currently, a disadvantage of the Scaden algorithm is the necessity to train a new

model for deconvolution if no perfect overlap in the feature space exists. This

constraint limits the usefulness of pre-trained models. Once trained, however, the

prediction runtime scales linearly with sample numbers and is usually in the order of

seconds, making Scaden a useful tool if deconvolution is to be performed on very large

datasets. While the requirements are dataset dependent, the Scaden demo was

profiled to require a peak of 3.2GB of RAM during the DNN training process, so a

computer with 8GB of RAM should be able to run it smoothly. In our tests with an

Intel(R) Xeon(R) CPU E5-1630 workstation the demo could run in 22 minutes,

spending most of the CPU time in the DNN training process. The most prominent and

obvious issue of Scaden is the difference between simulated scRNA-seq data used

for training and the bulk RNA-seq data subject to inference. While Scaden is able to

transfer the learned deconvolution between the two data types and achieves state-of-

the-art performance, we hypothesize that efforts to improve this translatability could

improve Scaden's prediction accuracy even further. Algorithmic improvements are

therefore likely to address this issue and are planned for future releases

640 Algorithm Comparison

We used several performance measures to compare Scaden to four existing cell

deconvolution algorithms, CIBERSORT with LM22 GEP (CS), CIBERSORTx (CSx),

MuSiC and CPM. To compare the performance of the five deconvolution algorithms

we measured the root mean squared error (RMSE), Lin's concordance correlation

coefficient CCC, Pearson product moment correlation coefficient r, and R^2 values

comparing real and predicted cell fractions estimates. Additionally, to identify

systematic prediction errors and biases, slope and intercept for the regression lines

were calculated. These metrics are defined as follows:

649
$$RMSE(y, \hat{y}) = \sqrt{avg(y - \hat{y})^2}$$

650
$$r(y, \hat{y}) = \frac{cov(y, \hat{y})}{\sigma_y \sigma_{\hat{y}}}$$

651
$$R^2(y, \hat{y}) = r(y, \hat{y})^2$$

652
$$slope(y, \hat{y}) = \frac{\Delta y}{\Delta \hat{y}}$$

$$CCC(y, \hat{y}) = \frac{2r\sigma_y\sigma_{\hat{y}}}{\sigma_y{}^2 + \sigma_{\hat{y}}{}^2 + (\mu_x - \mu_{\hat{y}})}$$

where y are the ground truth fractions, $\hat{y}$ are the prediction fractions, σ_x is the standard

deviation of x, $cov(y, \hat{y})$ is the covariance of y and $\hat{y}$, and $\mu_y, \mu_{\hat{y}}$ are the mean of the

predicted and ground truth fractions, respectively.

All metrics were calculated for all data points of a dataset, and separately for all data

points of a specific cell type. For the latter approach, we then averaged the resulting

values to recover single values. While the metrics calculated on all data points might

be sufficient, we deem that the cell type-specific deconvolution might in many

instances be of even greater interest. It is noteworthy in this context that cell type-

specific deconvolution performance can be quite weak, depending on the dataset. This

is true for all tested deconvolution algorithms, while Scaden achieves best

performance.

CIBERSORT (CS)

CS is a cell convolution algorithm based on specialized GEPs and support vector

regression. Cell composition estimations were obtained using the CS web application

(https://cibersort.stanford.edu/). For all deconvolutions with CS, we used the LM22

GEP, which was generated by the CS authors from 22 leukocyte subsets profiled on

the HGU133A microarray platform.

Because the LM22 GEP matrix contains cell types at a finer granularity than what was

used for this study, predicted fractions of sub-cell types were added together. For cell

grouping, we used the mapping of sub-cell types to broader types given by Figure 6

from Monaco *et al. (10)*. We provide a table with the exact mappings used here in the

supplementary material (Table S13). The deconvolution was performed using 500

permutations with quantile normalization disabled for all datasets but GSE65133

(Microarray), as is recommended for RNA-seq data. We used default settings for all

other CS parameters.

CIBERSORTx (CSx)

CSx is a recent variant of CS that can generate GEP matrices from scRNA-seq data

and use these for deconvolution. For additional deconvolution robustness, it applies

batch normalization to the data. All signature matrices were created by uploading the

labeled scRNA-seq expression matrices and using the default options. Quantile

normalization was disabled. For deconvolution on simulated data, no batch

normalization was used. For all bulk RNA-seq datasets, the S-Mode batch

normalization was chosen. All PBMC datasets were deconvolved using a GEP matrix

generated from the data6k dataset (for simulated samples from data6k, a donorA GEP

matrix was chosen).

MuSiC

MuSiC is a deconvolution algorithm that uses multi-subject scRNA-seq datasets as

GEP matrices in an attempt to include heterogeneity in the matrices to improve

generalization. While MuSiC tries to address similar issues of previous deconvolution

algorithms by using scRNA-seq data, the approach is very different. For

deconvolution, MuSiC applies a sophisticated GEP-based deconvolution algorithm

that uses weighted non-negative least squares regression with an iterative estimation

procedure that imposes more weight on informative genes and less weight on non-

informative genes.

The MuSiC R package contains functionality to generate the necessary GEP matrix

given a scRNA-seq dataset and cell type labels. To generate MuSiC deconvolution

predictions on PBMC datasets, we used the data8k scRNA-seq dataset as reference

data for MuSiC and follow the tutorial provided by the authors to perform the

deconvolution. For deconvolution of artificial samples generated from the data8k

dataset, we provided MuSiC with the data6k dataset as reference instead.

MuSiC was developed with a focus on multi-subject scRNA-seq datasets, in which the

algorithm tries to take advantage from the added heterogeneity that these datasets

contain, by calculating a measure of cross-subject consistency for marker genes. To

assess how Scaden performs on multi-subject datasets compared to MuSiC, we

evaluated both methods on artificial bulk RNA-seq samples from human pancreas. We

used the 'bulk_construct' function from MuSiC to combine the cells from all 18 subjects

contained in the scRNA-seq dataset from Xin *et al.* to generate artificial bulk samples

for evaluation. Next, as a multi-subject reference dataset, we used the pancreas

scRNA-seq dataset from Segerstolpe *et al. (20)*, which contains single-cell expression

data from 10 different subjects, 4 of which with type-2 Diabetes. For Scaden, the

Segerstolpe scRNA-seq dataset was split by subjects, and training datasets were

generated for each subject, yielding in total 10,000 samples. For MuSiC, a processed

version of this dataset was downloaded from the resources provided by the MuSiC

authors*(8)* and used as input reference dataset for the MuSiC deconvolution.

Deconvolution was then performed according to the MuSiC tutorial, and performance

compared according to the above-defined metrics.

Cell Population Mapping (CPM)

CPM is a deconvolution algorithm that uses single-cell expression profiles to identify

a so-called 'cell population map' from bulk RNA-seq data*(9)*. In CPM, the cell

population map is defined as composition of cells over a cell-state space, where a cell-

state is defined as a current phenotype of a single cell. Contrary to other deconvolution

methods, CPM tries to estimate the abundance of all cell-states and types for a given

bulk mixture, instead of only deconvolving the cell types. As input, CPM requires a

scRNA-seq dataset and a low-dimensional embedding of all cells in this dataset, which

represents the cell-state map. As CPM estimates abundances of both cell-states and

types, it can be used for cell type deconvolution by summing up all estimated fractions

for all cell-states of a given cell type - a method that is implemented in the scBio R

package, which contains the CPM method. To perform deconvolution with CPM, we

used the data6k PBMC scRNA-seq dataset as input reference for all PBMC samples.

For samples simulated from the data6k dataset, we used the data8k dataset as

reference. According to the CPM paper, a dimension reduction method can be used

to obtain the cell-state space. We therefore used UMAP, a dimension reduction

method widely used for scRNA-seq data, to generate the cell-state space mapping for

the input scRNA-seq data. Deconvolution was then performed using the CPM function

of the scBio package with a scRNA-seq and accompanying UMAP embedding as

input.

Data Availability

Only publicly available datasets were used during this study. The scRNA-seq PBMC datasetse donorA, donorC, data6k and data8k were all downloaded from 10X Genomics (https://support.10xgenomics.com/single-cell-gene-expression/datasets), were they are listed as 'Frozen PBMCs (Donor A)', 'Frozen PBMCs (Donor C)', '6k PBMCs from a Healthy Donor' and '8k PBMCs from a Healthy Donor', respectively. The Segerstolpe *et al.* scRNA-seq pancreas dataset was downloaded from ArrayExpress with accession code E-MTAB-5061. The scRNA-seq datasets from Baron *et al.* (pancreas), Tasic *et al.*, Zeisel *et al.*, Romanov *et al.*, Campbell *et al.* and Chen *et al.* (all mouse brain) were all downloaded from https://hemberg-lab.github.io/scRNA.seq.datasets/. The ascites scRNA-seq dataset was downloaded from https://figshare.com/s/711d3fb2bd3288c8483a. The bulk RNA-seq dataset PBMC1 is accessible from ImmPort with accession code SDY67. The PBMC2 dataset was downloaded from GEO with accession code GSE107011. The ROSMAP human brain RNA-seq dataset was downloaded from Synapse (ID: syn3219045). The bulk RNA-seq data from ascites was kindly provided by Schelker *et al.* The pancreas scRNA-seq dataset from Xin *et al.* was accessed from the MuSiC tutorial site (https://xuranw.github.io/MuSiC/articles/pages/data.html).

Code Availability

760   The source code for Scaden is available at https://github.com/KevinMenden/scaden.

762   Documentation is published at https://scaden.readthedocs.io. Code to generate the

763   figures along with the training datasets used in this study is published at figshare:

764   https://figshare.com/projects/Scaden/62834.

List of abbreviations

RNA-seq : Next Generation RNA Sequencing

GEP : gene expression profile matrix

SVR : Support Vector Regression

DNN : Deep Neural Network

scRNA-seq : single cell RNA-seq

simulated tissue : training data generated by mixing proportions of scRNA-seq data

PBMC : peripheral blood mononuclear cells

CCC : concordance correlation coefficient

r : Pearson's correlation coefficient

CS : CIBERSORT

CSx : CIBERSORTx

CPM : Cell Population Mapping

Author information

Affiliations

German Center for Neurodegenerative Diseases Tuebingen, Germany

Kevin Menden, Anupriya Dalmia, Peter Heutink, Stefan Bonn

Institute of Medical Systems Biology, University Medical Center Hamburg-Eppendorf, Germany

Mohamed Marouf, Sergio Oller, Karin Kloiber, Stefan Bonn

Contributions

KM and SB initiated the project. KM, PH, and SB designed the study, deep learning models, and analysis. KM, MM, and SO built the deep learning models. KM, MM, KK, and AD analyzed the data. KM, KK, and SB wrote and MM, AD, and PH contributed to the manuscript writing.

Competing interests

The authors have no competing interests.

Acknowledgements

We would like to thank the people of the Genome Biology of Neurodegenerative Diseases group and Institute of Medical Systems Biology for helpful discussions and suggestions.

Funding

This study was supported in part by RiMod-FTD an EU Joint Programme - Neurodegenerative Disease Research (JPND) to PH, KM and SFB 1286/Z2, BMBF

801   Integrative Data Semantics for Neurodegenerative research (IDSN), and KFO 306 P8

802   to MM, SO, and KK.

803   **Corresponding author**

804   Correspondence to Stefan Bonn (sbonn@uke.de) and Kevin Menden

805   (kevin.menden@dzne.de).

References

1. R. Hrdlickova, M. Toloue, B. Tian, RNA-Seq methods for transcriptome analysis, *Wiley Interdiscip. Rev. RNA* **8** (2017).

2. M. Egeblad, E. S. Nakasone, Z. Werb, Tumors as organs: Complex tissues that interface with the entire organism, *Dev. Cell* **18**, 884–901 (2010).

3. A. Kuhn, D. Thu, H. J. Waldvogel, R. L. M. Faull, R. Luthi-Carter, Population-specific expression analysis (PSEA) reveals molecular changes in diseased brain, *Nat. Methods* **8**, 945–947 (2011).

4. F. Avila Cobos, J. Vandesompele, P. Mestdagh, K. De Preter, Computational deconvolution of transcriptomics data from mixed cell populations*Bioinformatics* **34**, 1969–1979 (2018).

5. S. Mohammadi, N. Zuckerman, A. Goldsmith, A. Grama, A Critical Survey of Deconvolution Methods for Separating Cell Types in Complex Tissues, *Proc. IEEE* **105**, 340–366 (2017).

6. A. M. Newman, C. L. Liu, M. R. Green, A. J. Gentles, W. Feng, Y. Xu, C. D. Hoang, M. Diehn, A. A. Alizadeh, Robust enumeration of cell subsets from tissue expression profiles, *Nat. Methods* **12**, 453–457 (2015).

7. A. M. Newman, C. B. Steen, C. L. Liu, A. J. Gentles, A. A. Chaudhuri, F. Scherer, M. S. Khodadoust, M. S. Esfahani, B. A. Luca, D. Steiner, M. Diehn, A. A. Alizadeh, Determining cell type abundance and expression from bulk tissues with digital cytometry, *Nat. Biotechnol.* (2019).

8. X. Wang, J. Park, K. Susztak, N. R. Zhang, M. Li, Bulk tissue cell type deconvolution with multi-subject single-cell expression reference, *Nat. Commun.* **10**, 380 (2019).

9. A. Frishberg, N. Peshes-Yaloz, O. Cohn, D. Rosentul, Y. Steuerman, L.

Valadarsky, G. Yankovitz, M. Mandelboim, F. A. Iraqi, I. Amit, L. Mayo, E. Bacharach, I. Gat-Viks, Cell composition analysis of bulk genomics using single-cell data, *Nat. Methods* **16** (2019).

10. G. Monaco, B. Lee, W. Xu, S. Mustafah, Y. Y. Hwang, C. Carré, N. Burdin, L. Visan, M. Ceccarelli, M. Poidinger, A. Zippelius, J. Pedro de Magalhães, A. Larbi, RNA-Seq Signatures Normalized by mRNA Abundance Allow Absolute Deconvolution of Human Immune Cell Types, *Cell Rep.* **26**, 1627–1640.e7 (2019).

11. F. Vallania, A. Tam, S. Lofgren, S. Schaffert, T. D. Azad, E. Bongen, W. Haynes, M. Alsup, M. Alonso, M. Davis, E. Engleman, P. Khatri, Leveraging heterogeneity across multiple datasets increases cell-mixture deconvolution accuracy and reduces biological and technical biases, *Nat. Commun.* **9** (2018).

12. D. Venet, F. Pecasse, C. Maenhaut, H. Bersini, Separation of samples into their constituents using gene expression data, *Bioinformatics* **17**, 279–287 (2001).

13. E. Shapiro, T. Biezuner, S. Linnarsson, Single-cell sequencing-based technologies will revolutionize whole-organism science, *Nat. Rev. Genet.* **14**, 618–630 (2013).

14. N. Schaum, J. Karkanias, N. F. Neff, B. M. Wang, K. Weinberg, I. L. Weissman, S. M. Wu, S. R. Quake, T. Wyss-Coray, Single-cell transcriptomics of 20 mouse organs creates a Tabula Muris, *Nature* **562**, 367–372 (2018).

15. K. W. Kelley, H. Nakao-Inoue, A. V. Molofsky, M. C. Oldham, Variation among intact tissue samples reveals the core transcriptional features of human CNS cell classes, *Nat. Neurosci.* **21**, 1171–1184 (2018).

16. S. C. Hicks, F. W. Townes, M. Teng, R. A. Irizarry, Missing data and technical variability in single-cell RNA-sequencing experiments, *Biostatistics* **19**, 562–578 (2018).

17. L. I. Lin, A Concordance Correlation Coefficient to Evaluate Reproducibility,

Biomatrics **45**, 255–268 (1989).

18. M. Schelker, S. Feau, J. Du, N. Ranu, E. Klipp, G. MacBeath, B. Schoeberl, A.

Raue, Estimation of immune cell content in tumour tissue using single-cell RNA-seq

data, *Nat. Commun.* **8**, 2032 (2017).

19. Y. Xin, J. Kim, H. Okamoto, M. Ni, Y. Wei, C. Adler, A. J. Murphy, G. D.

Yancopoulos, C. Lin, J. Gromada, RNA Sequencing of Single Human Islet Cells

Reveals Type 2 Diabetes Genes, *Cell Metab.* **24**, 608–615 (2016).

20. Å. Segerstolpe, A. Palasantza, P. Eliasson, E. M. Andersson, A. C. Andréasson,

X. Sun, S. Picelli, A. Sabirsh, M. Clausen, M. K. Bjursell, D. M. Smith, M. Kasper, C.

Ämmälä, R. Sandberg, Single-Cell Transcriptome Profiling of Human Pancreatic

Islets in Health and Type 2 Diabetes, *Cell Metab.* **24**, 593–607 (2016).

21. M. T. Zimmermann, A. L. Oberg, D. E. Grill, I. G. Ovsyannikova, I. H.

Haralambieva, R. B. Kennedy, G. A. Poland, System-wide associations between

DNA-methylation, gene expression, and humoral immune response to influenza

vaccination, *PLoS One* **11**, 1–21 (2016).

22. D. A. Bennett, A. S. Buchman, P. A. Boyle, L. L. Barnes, R. S. Wilson, J. A.

Schneider, Religious Orders Study and Rush Memory and Aging Project, *J.*

Alzheimer's Dis. **64**, S161–S189 (2018).

23. E. Patrick, M. Taga, A. Ergun, B. Ng, W. Casazza, M. Cimpean, C. Yung, J. A.

Schneider, D. A. Bennett, C. Gaiteri, P. L. De Jager, E. M. Bradshaw, S. Mostafavi,

Deconvolving the contributions of cell-type heterogeneity on cortical gene

expression, *bioRxiv* , 566307 (2019).

24. S. Darmanis, S. a. Sloan, Y. Zhang, M. Enge, C. Caneda, L. M. Shuer, M. G.

Hayden Gephart, B. a. Barres, S. R. Quake, A survey of human brain transcriptome

diversity at the single cell level, *Proc. Natl. Acad. Sci.* **112**, 7285–7290 (2015).

25. B. B. Lake, R. Ai, G. E. Kaeser, N. S. Salathia, Y. C. Yung, R. Liu, A. Wildberg,

D. Gao, H. L. Fung, S. Chen, R. Vijayaraghavan, J. Wong, A. Chen, X. Sheng, F.

Kaper, R. Shen, M. Ronaghi, J. B. Fan, W. Wang, J. Chun, K. Zhang, Neuronal

subtypes and diversity revealed by single-nucleus RNA sequencing of the human

brain, *Science (80-.).* **352**, 1586–1590 (2016).

26. H. Braak, E. Braak, Neuropathological stageing of Alzheimer-related changes.,

Acta Neuropathol. **82**, 239–59 (1991).

27. J. Yosinski, J. Clune, A. Nguyen, T. Fuchs, H. Lipson, Understanding Neural

Networks Through Deep Visualization, (2015) (available at

http://arxiv.org/abs/1506.06579).

28. B. Athiwaratkun, M. Finzi, P. Izmailov, A. G. Wilson, Improving Consistency-

Based Semi-Supervised Learning with Weight Averaging, *Jmlr* **17**, 1–35 (2018).

29. M. Zhang, K. T. Ma, J. H. Lim, Q. Zhao, J. Feng, Deep Future Gaze : Gaze

Anticipation on Egocentric Videos Using Adversarial Networks, *Cvpr2017* , 4372–

4381 (2017).

30. F. A. Wolf, P. Angerer, F. J. Theis, SCANPY: Large-scale single-cell gene

expression data analysis, *Genome Biol.* **19**, 1–5 (2018).

31. R. Satija, J. A. Farrell, D. Gennert, A. F. Schier, A. Regev, Spatial reconstruction

of single-cell gene expression data, *Nat. Biotechnol.* **33**, 495–502 (2015).

32. A. Zeisel, H. Hochgerner, P. Lönnerberg, A. Johnsson, F. Memic, J. van der

Zwan, M. Häring, E. Braun, L. E. Borm, G. La Manno, S. Codeluppi, A. Furlan, K.

Lee, N. Skene, K. D. Harris, J. Hjerling-Leffler, E. Arenas, P. Ernfors, U. Marklund, S.

Linnarsson, Molecular Architecture of the Mouse Nervous System., *Cell* **174**, 999–

1014.e22 (2018).

33. M. I. Love, C. Soneson, R. Patro, K. Vitting-seerup, A. Oshlack, Swimming

downstream : statistical analysis of differential transcript usage following Salmon

quantification, *F1000 Research*, 1–50 (2019).

Supplementary Figures & Tables

Supplementary Table S1: scRNA-seq datasets used for the generation of simulated tissues for Scaden training.

Tissue	Name	# cells	# Subjects	Source
PBMC	data6k	5,419	1	10X Genomics
PBMC	data8k	8,381	1	10X Genomics
PBMC	donorA	2,900	1	10X Genomics
PBMC	donorC	9,519	1	10X Genomics
Mouse Brain	Tasic	1,679	1	Tasic et al., Nat. Neurosci., 2016
Mouse Brain	Zeisel	3,005	1	Zeisel et al., Science, 2015
Mouse Brain	Romanov	2,881	1	Romanov et al., Nat. Neurosci., 2018
Mouse Brain	Campbell	21,086	1	Campbell et al, Nat. Neurosci., 2017
Mouse Brain	Chen	14,437	1	Chen et al., Cell Rep., 2017
Pancreas	Segerstolpe	3,514	10	Segerstolpe et al., Cell Metab., 2016
Pancreas	Baron	8,569	4	Baron et al., Cell Syst., 2016
Ascites	Ascites	3,114	3	Schelker et al, Nat. Comm., 2018
Human Brain	Darmanis	465	1	Darmanis et al., PNAS, 2015
Human Brain	Lake	27,416	1	Lake et al., Science, 2016

Supplementary Table S2: Bulk tissue RNA-seq datasets used for performance evaluation

Tissue	Name	# Samples	Reference
PBMC	PBMC1	12	Zimmermann et al., PLOS one, 2016
PBMC	PBMC2	12	Monaco et al., Cell Reports, 2019
Pancreas	Xin	18	Xin et al., Cell Metab., 2016
Human Brain	ROSMAP	390	Bennett et al., Curr Alzheimer Res., 2012
Ascites	Ascites	3	Schelker at al., Nat. Comm. 2018

924
925 **Supplementary Figure S1:** Overview of Scaden neural network ensemble model. A
926 bulk RNA-seq sample is the input to three separate deep neural networks with varying
927 layer sizes and dropout regularization. The predictions of all three models are
928 subsequently averaged to obtain the final Scaden predictions. During training,
929 predictions are not averaged and each model is trained separately.
930

932 **Supplementary Table S3:** Number of samples, datasets and size of the simulated
933 training data.

Tissue	# Samples	# Datasets	Size
PBMC	32,000	4	1.2 GB
Pancreas	14,000	2	0.6 GB
Human Brain	6,000	2	0.32 GB
Ascites	6,000	1	0.38 GB
Mouse Brain	30,000	5	1.5 GB

934
935
936 **Supplementary Table S4:** Architectures of deep neural network models used in
937 Scaden ensemble. All models use an L1 as a loss function, ReLU activation for all
938 layers but the last, and softmax activation for the last layer.

Model	# Layers	Layer sizes	Dropout rates
M256	4	256, 128, 64, 32	0, 0, 0, 0
M512	4	512, 256, 128, 64	0, 0.3, 0.2., 0.1
M1024	4	1024, 512, 256, 128	0, 0.6, 0.3, 0.1

939
940
941 **Supplementary Table S5:** Hyperparameters used for model optimization

Parameter	Values tested
Batch size	32, 64, 128, 256, 512
# Layers	2, 3, 4
Layer sizes	2048, 1024, 512, 256, 128, 64, 32, 16
Dropout rate	[0, 0.8]
Loss function	L1, L2

942
943
944 **Supplementary Table S6**: Comparison of Scaden models and the Scaden ensemble
945 on four PBMC scRNA-seq datasets. Concordance correlation coefficient was
946 calculated on all datasets separately and then averaged.

	Scaden Ensemble	M256	M512	M1024
CCC	0.914	0.898	0.909	0.907

947
948

950 **Supplementary Figure S2:** Assessment of the effect of training data size on the CCC.
951 We used four publicly available PBMC scRNA-seq datasets (see also Table S1) to
952 train Scaden on different sample sizes between 150 and 15,000. Each simulated RNA-
953 seq training dataset was generated from three scRNA-seq datasets. Simulated testing
954 datasets were generated from a separate scRNA-seq dataset.

956
957 **Supplementary Figure S3:** Assessment of overfitting. We trained Scaden on
958 simulated data from ascites scRNA-seq datasets (6000 samples, see Table S1) and
959 evaluated the loss function on annotated bulk RNA-seq datasets (see also Table S2)
960 (3 samples) as a function of training steps. The results led us to an early-stop approach
961 after 5,000 steps for evaluation on real bulk RNA-seq data.
962

963 **Supplementary Table S7:** Deconvolution evaluation on simulated PBMC data.

Method	DS	RMSE	Slope	Correlation	Intercept	CCC
CPM	data6k	0.192	0.03	0.082	0.162	0.053
CPM	data8k	0.185	0.048	0.263	0.159	0.093
CPM	donorA	0.239	-0.081	-0.259	0.18	-0.147
CPM	donorC	0.189	0.038	0.102	0.16	0.066
CS	data6k	0.163	0.508	0.57	0.082	0.566
CS	data8k	0.136	0.551	0.708	0.075	0.687
CS	donorA	0.137	0.605	0.767	0.066	0.746
CS	donorC	0.168	0.45	0.522	0.092	0.517
CSx	data6k	0.106	0.756	0.824	0.041	0.821
CSx	data8k	0.097	0.744	0.863	0.043	0.854
CSx	donorA	0.125	0.696	0.81	0.051	0.801
CSx	donorC	0.094	0.829	0.865	0.029	0.864
MuSiC	data6k	0.086	0.848	0.887	0.025	0.886
MuSiC	data8k	0.136	0.663	0.728	0.056	0.725
MuSiC	donorA	0.1	0.811	0.883	0.031	0.88
MuSiC	donorC	0.084	0.897	0.896	0.017	0.896
Scaden	data6k	0.104	0.747	0.83	0.042	0.825
Scaden	data8k	0.133	0.625	0.73	0.063	0.722
Scaden	donorA	0.035	0.92	0.988	0.013	0.985
Scaden	donorC	0.046	0.849	0.973	0.025	0.964

Supplementary Figure S4: Scatter plots of predicted (y-axis) vs ground truth values (x-axis) for four simulated PBMC RNA-seq datasets (data6k, data8k, donorA, donorC) for all tested algorithms (Scden, CS, CSx, MuSiC, CPM). CCCs are given as insets in each plot.

973   **Supplementary Table S8:** Deconvolution performance on simulated pancreas data
974   from Xin et al. on a per cell-type level.

Method	Celltype	RMSE	Correlation	Slope	Intercept	CCC
CSx	ALPHA	0.282	0.816	0.691	0.431	0.375
CSx	Average	0.171	0.845	0.891	0.1	0.499
CSx	BETA	0.309	0.833	0.175	-0.017	0.078
CSx	DELTA	0.04	0.812	1.567	-0.013	0.647
CSx	GAMMA	0.052	0.921	1.131	0.0	0.897
CSx	Total	0.212	0.79	1.113	-0.028	0.746
MuSiC	ALPHA	0.11	0.887	1.108	-0.042	0.863
MuSiC	Average	0.087	0.835	0.861	-0.008	0.744
MuSiC	BETA	0.148	0.752	1.067	0.017	0.694
MuSiC	DELTA	0.023	0.817	0.716	-0.003	0.707
MuSiC	GAMMA	0.068	0.881	0.552	-0.003	0.711
MuSiC	Total	0.099	0.938	1.078	-0.019	0.929
Scaden	ALPHA	0.067	0.949	1.071	-0.034	0.942
Scaden	Average	0.051	0.902	1.031	-0.02	0.881
Scaden	BETA	0.07	0.936	1.152	-0.045	0.916
Scaden	DELTA	0.024	0.807	1.012	0.008	0.764
Scaden	GAMMA	0.045	0.914	0.89	-0.008	0.901
Scaden	Total	0.055	0.978	1.033	-0.008	0.976

975
976
977

978
Supplementary Figure S5 Deconvolution performance on simulated PBMC datasets
with added unknown mixture contents. Cell types from 24,000 *in silico* PBMC samples
(Table S1) were replaced by a defined percentage of unkown cells (5, 10, 20, 30 %),
which were removed from the data prior to sample simulation. The shaded areas mark
the 95% confidence interval. One dataset was evaluated by Scaden trained on *in silico*
data from the remaining three. For CSx and MuSiC, a different dataset was used as
reference.
986
987
988

Supplementary Table S9: Deconvolution performance on datasets with added
unknown mixture contents.

Method	Content	CCC	RMSE	Correlation	Intercept	Slope
CSx	0.02	0.731	0.097	0.738	0.032	0.841
CSx	0.05	0.751	0.092	0.754	0.035	0.823
CSx	0.1	0.715	0.092	0.719	0.041	0.797
CSx	0.2	0.694	0.091	0.703	0.039	0.807
CSx	0.3	0.632	0.099	0.637	0.057	0.714
MuSiC	0.02	0.793	0.084	0.803	0.016	0.921
MuSiC	0.05	0.799	0.083	0.805	0.018	0.908
MuSiC	0.1	0.739	0.089	0.745	0.032	0.841
MuSiC	0.2	0.669	0.095	0.679	0.04	0.8
MuSiC	0.3	0.665	0.101	0.687	0.028	0.861
Scaden	0.02	0.934	0.041	0.944	0.033	0.837
Scaden	0.05	0.925	0.044	0.936	0.035	0.825
Scaden	0.1	0.902	0.046	0.915	0.042	0.792
Scaden	0.2	0.846	0.054	0.859	0.051	0.747
Scaden	0.3	0.798	0.063	0.816	0.063	0.686

 Supplementary Table S10: Deconvolution performance on real PBMC RNA-seq
996 datasets PBMC1 and PBMC2. Scaden was trained on a mixture of *in silico* and real
997 bulk RNA-seq data, the remaining tools used either scRNA-seq datasets as reference
998 (CPM, MuSiC, CSx) or a in-built reference (CS).
999

Method	Dataset	RMSE	Correlation	Slope	Intercept	CCC
CPM	PBMC1	0.18	-0.003	-0.003	0.167	-0.003
CPM	PBMC2	0.114	-0.203	-0.094	0.182	-0.155
CS	PBMC1	0.147	0.437	0.491	0.085	0.434
CS	PBMC2	0.101	0.594	0.754	0.041	0.577
CSx	PBMC1	0.16	0.603	0.925	0.012	0.552
CSx	PBMC2	0.13	0.456	0.67	0.055	0.424
MuSiC	PBMC1	0.316	-0.235	-0.468	0.245	-0.189
MuSiC	PBMC2	0.299	-0.197	-0.542	0.257	-0.127
Scaden	PBMC1	0.104	0.722	0.805	0.032	0.717
Scaden	PBMC2	0.052	0.855	0.848	0.025	0.855

1002 **Supplementary Table S11:** Deconvolution performance on real PBMC RNA-seq
1003 data for Scaden models trained only on scRNA-seq simulated tissues (Scaden_SC)
1004 or on a mix of simulated and real tissue (Scaden_all).
1005

Method	Dataset	Celltype	RMSE	Corr.	Slope	Intercept	CCC
Scaden_SC	PBMC1	Total	0.131	0.564	0.644	0.059	0.559
Scaden_SC	PBMC2	Total	0.077	0.684	0.689	0.052	0.684
Scaden_all	PBMC1	Total	0.104	0.722	0.805	0.032	0.717
Scaden_all	PBMC2	Total	0.052	0.855	0.848	0.025	0.855
Scaden_SC	PBMC1	Bcells	0.033	0.648	0.172	0.006	0.083
Scaden_SC	PBMC1	CD4Tcells	0.228	0.633	0.492	-0.055	0.149
Scaden_SC	PBMC1	CD8Tcells	0.101	0.603	0.761	0.108	0.562
Scaden_SC	PBMC1	Monocytes	0.178	0.556	0.885	0.173	0.186
Scaden_SC	PBMC1	NK	0.087	0.81	0.531	0.137	0.312
Scaden_SC	PBMC1	Unknown	0.029	0.577	0.361	0.009	0.287
Scaden_SC	PBMC2	Bcells	0.012	0.936	0.977	0.002	0.935
Scaden_SC	PBMC2	CD4Tcells	0.145	0.767	0.682	-0.057	0.119
Scaden_SC	PBMC2	CD8Tcells	0.049	0.67	0.403	0.129	0.587
Scaden_SC	PBMC2	Monocytes	0.078	0.865	0.994	0.071	0.558
Scaden_SC	PBMC2	NK	0.071	0.629	0.314	0.14	0.276
Scaden_SC	PBMC2	Unknown	0.025	0.247	0.217	0.044	0.209
Scaden_all	PBMC1	Bcells	0.031	0.668	0.188	0.007	0.1
Scaden_all	PBMC1	CD4Tcells	0.151	0.638	0.652	-0.017	0.345
Scaden_all	PBMC1	CD8Tcells	0.096	0.6	0.704	0.123	0.569
Scaden_all	PBMC1	Monocytes	0.172	0.518	0.777	0.184	0.177
Scaden_all	PBMC1	NK	0.036	0.804	0.488	0.058	0.71
Scaden_all	PBMC1	Unknown	0.026	0.64	0.41	0.01	0.365
Scaden_all	PBMC2	Bcells	0.013	0.936	0.94	0.0	0.917
Scaden_all	PBMC2	CD4Tcells	0.074	0.772	0.769	-0.005	0.373
Scaden_all	PBMC2	CD8Tcells	0.051	0.672	0.398	0.106	0.562
Scaden_all	PBMC2	Monocytes	0.072	0.895	1.058	0.049	0.614
Scaden_all	PBMC2	NK	0.045	0.69	0.301	0.103	0.467
Scaden_all	PBMC2	Unknown	0.023	0.241	0.178	0.043	0.203

1006
1007

Supplementary Figure S6: Comparison of Scaden deconvolution results on PBMC1 and PBMC2 datasets with and without (Scaden_all, Scaden_SC, respectively) bulk RNA-seq samples included in training data. Results are given on a per-cell type basis, predicted values are shown on the y-axis, ground truth is given on the x-axis.

Supplementary Table S12: Deconvolution performance on bulk RNA-seq data from post-mortem human brain tissue (ROSMAP). Metrics are reported for deconvolution with different reference datasets (Darmanis and Lake) and additionally with both reference datasets for Scaden (Darmanis and Lake).

Method	Reference	CCC	RMSE	Correlation	Slope	Intercept
Scaden	Darmanis	0.922	0.056	0.924	0.992	0.028
Scaden	Lake	0.76	0.144	0.918	1.730	0.103
Scaden	Darmanis& Lake	0.898	0.064	0.899	0.948	0.029
MuSiC	Darmanis	0.873	0.089	0.951	1.445	0.075
MuSiC	Lake	0.65	0.119	0.652	0.696	0.078
CSx	Darmanis	0.805	0.123	0.94	1.663	0.094
CSx	Lake	0.706	0.183	0.95	2.130	0.115

1028

1029
1030

Supplementary Figure S7: Top panel: CCC values for prediction of post-mortem human brain (ROSMAP) cell fractions for Scaden , CSx, and MuSiC on the reference data sets Darmanis (lightblue, leftmost bars) and Lake (medium-shaded blue), as well as both (for Scaden only, dark blue). Note that the Lake dataset contains only neurons, such that we fit only a subset of cell types (excitatory and inhibitory neurons, respectively). Interestingly, addition of the Lake dataset into training data affected Scaden performance only slightly. Bottom panel: Per sample results for prediction of post-morten human brain (ROSMAP) cell fractions on the Darmanis reference datasets using Scaden, CSx, and MuSiC.

 Supplementary Table S13: Deconvolution performance comparison of CS (LM22)
1042 and Scaden on the GSE65133 Microarray dataset. Please note that the LM22 GEP
1043 used for CS was created using PBMC microarray data, while Scaden was trained on
1044 simulated scRNA-seq PBMC datasets.

Method	Celltype	CCC	Correlation	Intercept	R2	RMSE	Slope
CIBERSORT	Average	0.391	0.612	0.087	0.396	0.103	0.516
CIBERSORT	Bcells	0.122	0.33	0.029	0.109	0.068	0.109
CIBERSORT	CD4Tcells	0.629	0.658	0.199	0.433	0.095	0.537
CIBERSORT	CD8Tcells	0.285	0.635	0.018	0.404	0.12	0.375
CIBERSORT	Monocytes	0.295	0.741	0.19	0.548	0.17	0.779
CIBERSORT	NK	0.623	0.698	-0.003	0.487	0.059	0.78
CIBERSORT	Total	0.717	0.728	0.026	0.53	0.11	0.869
Scaden	Average	0.498	0.726	-0.032	0.536	0.115	1.006
Scaden	Bcells	0.431	0.728	0.012	0.53	0.055	0.388
Scaden	CD4Tcells	0.64	0.778	-0.195	0.606	0.153	1.474
Scaden	CD8Tcells	0.474	0.543	0.02	0.294	0.104	0.635
Scaden	Monocytes	0.43	0.838	0.033	0.702	0.191	1.764
Scaden	NK	0.516	0.741	-0.029	0.549	0.074	0.77
Scaden	Total	0.705	0.749	-0.015	0.561	0.126	1.067

1045
1046

Supplementary Figure S8: Scatterplots showing the deconvolution performance of CS (LM22) and Scaden on the GSE65133 Microarray dataset. Please note that the LM22 GEP used for CS was created using PBMC microarray data, while Scaden was trained on simulated scRNA-seq PBMC datasets.

1055 **Supplementary Table S14:** Marker genes used to define cell type populations

Tissue	Cell Type	Marker Genes
PBMC	Monocytes	LYZ, FCGR3A
	CD8Tcells	CD8A
	CD4Tcells	IL7R
	Natural Killer (NK)	GNLY
	Bcells	MS4A1
Pancreas	Alpha	GCG, TTR, SSR4
	Beta	INS, SCGN, IAPP
	Gamma	PPY2, PPY
	Delta	SST, BCHE
	Acinar	REG1A, SPINK1
	Ductal	AQP1, SLC3A1
	Endothelial	IDO1
Ascites	Monocytes	FCGR3A, CD14
	CD8Tcells	CD8A
	CD4Tcells	CD3D
	Dendritic	CST3
	Fibroblast	COL1A1
	Carcinoma	EPCAM
Brain	Oligodendrocytes	MOBP
	Excitatory Neurons	SLC17A7
	Inhibitory Neurons	GAD1
	Astrocytes	AGT, SLC1A2
	Endothelial	FL1, DUSP1
	Oligodendrocytes Precursors (OPC)	PCDH15
	Microglia	APBB1IP

1056
1057

1058

1059

1060 **Supplementary Table S15:** Software packages and versions used.

Software	Version
pandas	0.23.4
Python	3.6.8
Tensorflow	1.10.0
matplotlib	2.2.3
nb_conda	2.2.1
numpy	1.15.0
scipy	1.1.0
seaborn	0.9.0
anndata	0.6.9
scanpy	1.2.2
scikit-learn	0.20.0
ipython	6.5.0
python-igraph	0.7.1.post6
louvain	0.6.1
tqdm	4.7.2
igraph	0.7.1

1061

1062

1063 **Supplementary Table S16:** Mapping of the LM22 GEP to cell types.

Target Cell Type	LM22 Cell Types
B cells	B cells naive, B cells memory
CD8 T cells	T cells CD8, T cells follicular helper, T cells gamma delta
CD4 T cells	T cells CD4 naive, T cells regulatory (Tregs), T cells CD4 memory resting, T cells CD4 memory activated
NK	NK cells resting, NK cells activated
Monocytes	Monocytes, Macrophages M0, Macrophages M1, Macrophages M2
Unknown	Mast cells resting, Mast cells activated, Eosinophils, T cells follicular helper, T cells gamma delta, Plasma cells, Neutrophils, Dendritic cells resting, Dendritic cells activated