ModEx: A text mining system for extracting mode of regulation of Transcription Factor-gene regulatory interaction

Saman Farahmand[1,2], Todd Riley[1,2] and Kourosh Zarringhalam[1,3]*

[1] Computational Sciences PhD program, University of Massachusetts Boston, Boston, USA

[2] Department of Biology, University of Massachusetts Boston, Boston, USA;

[3] Department of Mathematics, University of Massachusetts Boston, Boston, USA

* Correspondence: kourosh.zarringhalam@umb.edu, Department of Mathematics, University of Massachusetts Boston, 100 Morrissey Boulevard, 02125 Boston, USA

Abstract— Transcription factors (TFs) are proteins that are fundamental to transcription and regulation of gene expression. Each TF may regulate multiple genes and each gene may be regulated by multiple TFs. TFs can act as either activator or repressor of gene expression. This complex network of interactions between TFs and genes underlies many developmental and biological processes and is implicated in several human diseases such as cancer. Hence deciphering the network of TF-gene interactions with information on mode of regulation (activation vs. repression) is an important step toward understanding the regulatory pathways that underlie complex traits. There are many experimental, computational, and manually curated databases of TF-gene interactions. In particular, high-throughput ChIP-seq datasets provide a large-scale map or transcriptional regulatory interactions. However, these interactions are not annotated with information on context and mode of regulation. Such information is crucial to gain a global picture of gene regulatory mechanisms and can aid in developing machine learning models for applications such as biomarker discovery, prediction of response to therapy, and precision medicine. In this work, we introduce a text-mining system to annotate ChIP-seq derived interaction with such meta data through mining PubMed articles. We evaluate the performance of our system using the gold standard small scale manually curated TRUSST database. Our results show that the method is able to accurately extract mode of regulation with

F-score 0.77 on TRRUST curated interaction and F-score 0.96 on intersection of TRUSST and ChIP-
network. We provide a HTTP REST API for our code to facilitate usage.

Availability: Source code and datasets are available for download on GitHub:

https://github.com/samanfrm/modex

HTTP REST API: https://watson.math.umb.edu/modex/

Index Terms— Text mining, information extraction, name entity recognition, biological NLP, biomedical
literature, gene regulatory network, mode of regulation.

1. INTRODUCTION

Gene regulatory networks are essential in many cellular processes, including metabolism, signal
transduction, development, and cell fate [1]. At the transcriptional level, regulations of genes are
orchestrated by concerted action between Transcription Factors (TFs), histone modifies, and distal *cis*-
regulatory elements to finely tune and modulate expression of genes. Sequence-specific Transcription
Factors play a key role in regulating gene transcription at the transcriptional level. They bind specific DNA
motifs to regulate promoter activity and either enhance (activate) or repress (inhibit) expression of the
genes. Deciphering transcriptional regulatory networks is crucial for understanding cellular mechanisms
and response at a molecular level and can shed light on molecular basis of complex human diseases [2–5].
Moreover, knowledge on interactions between genes and biomolecules is an essential building block in
several pathway inference and gene enrichment analysis methods that aim to annotate an altered set of
transcripts with biological function [6,7]. There are several sources of publicly available biomolecular
interactions, including, signaling pathways, metabolic pathways, and protein-protein interactions [8–10].
Databases of transcriptional regulatory network include JASPAR [11], the Open Regulatory Annotation
database (ORegAnno) [12] , Swissregulon [13], the Transcriptional Regulatory Element Database (TRED)
[14], the Transcription Regulatory Regions Database (TRRD) [15], TFactS [16], TRRUST [17], and the
Human Transcriptional Regulation Interactions database (HTRIdb) [17]. These databases include
biologically validated and computationally inferred gene regulatory interactions and have been assembled
with a variety of approaches, including reverse engineering approaches based on high-throughput gene
expression experiments [18–20], text mining approaches [21], and manual curation [22]. These databases
are a valuable source of gene regulatory information, however, there are several constraints that limit their
usability. For example, databases of computationally predicted and expression-driven interactions are

typically very noisy. Importantly, the majority of the databases do not report the direction of regulation (up

or down) - which is crucial to understanding the functional behavior of the cell.

A high-throughput experimental approach for identifying regulatory interaction is chromatin

immunoprecipitation followed by sequencing (ChIP-seq). In ChIP-seq methodologies, antibodies that

recognizes a specific TF are used to pull down attached DNA for sequencing. The ENCODE (Encyclopedia

of DNA Elements) consortium [23] has produced vast amount of publicly available high-throughput ChIP-

seq experiments that are processed and deposited into databases such as GTRD [24] and ChIP-Atlas [25]

(>35,000 experiments). These databases can be utilized to construct a high coverage transcriptional

regulatory network. Although these interactions are experimentally derived, they are still very noisy as the

experiments are performed under different conditions and in different cell lines. Moreover, ChIP-seq does

not provide direct information on mode of regulation.

The most reliable source of regulatory information is obtained by manual curation of peer-reviewed

biomedical literature by domain experts and can be considered as the gold standard. Commercial vendors

such as Ingenuity (www.ingenuity.com) offer pathway inference analysis algorithms on such manually

curated networks of regulatory interactions. There are also public sources of curated causal gene regulatory

interactions, such as TRRD, TRED, TFactS, and TRRUST. However, these databases are very small in

their scope, covering only a fraction of TF-gene interactions. Overall, manual curation of biomedical

literature is very time consuming, requires extensive resources, and does not scale to the pace at which

biomedical literature is expanding [26]. For this reason, biomedical text mining has been extensively used

to automate the process of biomolecular relation extraction from the literature. As literature lacks

standardized representation of text, automatic routines for information extraction from textual context is

very challenging [27].

There is a vast amount of literature on text-mining for various application [27]. Essential text mining steps

for biomedical relation extraction can be divided into 3 steps: (1) information retrieval (IR), (2) entity

recognition (ER), and (3) information extraction (IE). Together, they can be utilized to identify and extract

specific biological knowledge from literature [28,29].

IR tools retrieve relevant text information from articles, abstracts, paragraphs, and sentences corresponding

to subject of interest. A popular IR approach for biomedical application is the use of Boolean model logic

(AND/OR) for extracting relevant information containing specific biological terms [27]. Prominent IR tools

that use the Boolean logic model are iHOP [30] and PubMed. PubMed utilizes human-indexed MeSH terms

to reduce the search space and retrieve relevant abstracts containing user specified keywords. iHOP builds

on PubMed and is able to detect co-occurrence of terms. A limitation of iHOP is that the terms must occur

in the same sentence.

After the IR step, ER must be used to identify relation between biological entities. This is a challenging
step as entity names are not unique. Therefore, ER tools must take textual context into consideration to
accurately detect entities. For example, gene names may have different variations in ortho-graphical
structure (e.g. ABL1, Abl1, Abl-1) or multiple synonyms (e.g. ABL1, ABL, CHDSKM, Abelson tyrosine-
protein kinase 1). ER methods, typically divide the task into two steps, (1) identify the entities and their
location in the context, and (2) assign unique identifiers to the entities [27]. Fortunately, multiple
terminological databases, such as Gene Ontology [31], UMBLS [32], BioLexicon [32], and Biothesaurus
[32] provide information on biological entities and name variations and can be used to detect biological
entities such as genes or proteins [33–35].

Lastly, Relation Extraction (RE) is an IR tasks for extracting pre-defined facts relating to an entity or entities
in the text [36]. In biomedical domain, multiple RE methods have been developed to extract information
relating to genes [17], such as Mutation-Disease associations, protein-protein interaction [37,38], pathway
curation [39], gene methylation and cancer relation [40], biomolecular events [41], metabolic reactions [42]
and gene-gene interactions [43]. For gene regulatory networks, which is the focus of this paper, the RE
system must detect and extract a *causal* relation between a protein and a gene (e.g., A regulated B). This
task is very complex, even for human experts [44]. To illustrate, consider the causal relation "aatf
upregulates c-myc" that should be deduced from the following sentence: "down-regulation of c-myc gene
was accompanied by decreased expressions of c-myc effector genes coding for htert, bcl-2, and aatf" [45].
Extracting a positive regulatory interaction between aatf and c-myc is quite challenging using simple RE
methods. For example, the RE method, may naively annotated the interaction as negative because of the
keyword "decreased". However, by taking "down-regulation" into account, the RE method would able to
correctly extract a positive regulation from this sentence.

Construction of a causal transcriptional regulatory network by traditional means of text mining is hampered
by these challenges and as a result, fully automated text-mining based models are limited in their scope and
accuracy [27]. Combining experimentally-derived regulatory interactions from high-throughput sources
with text-mining approaches can bridge the gap between the two approaches and address their
shortcomings.

In this work, we present a hybrid model ModEx, to mine the biomedical literature to extract and annotate
causal transcriptional regulatory interactions derived from high-throughput ChIP-seq datasets. Specifically,
we applied our text-mining method to extract experimental TF-gene relations reported in ChIP-Atlas
(assembled from all publicly available ChIP-seq experiments) from biomedical literature and annotated the
retrieved interaction with meta-data, such as full supporting sentences, PubMed ID, and importantly mode
of regulation, which is missing from ChIP-seq data. It is important to note that our approach bypasses

several of the challenges of fully automated text-mining methods, including query translation for a
particular interaction, relevant citation retrieval, entities recognition and regulatory annotation. We
evaluated the performance of our model using the TRRUST network [22], which contains 9,396 manually
curated regulatory interactions. Our model was able to achieve an F-score 0.77 in retrieving and annotating
the TRUSST network. When applied to TRRUST reported interaction that are also present in ChIP-seq
data, the method achieved an F-score of 0.96.

2. MATERIALS AND METHODS

We begin by a brief overview of our text mining approach for extracting and annotating ChIP-seq derived
TF-gene interactions with meta-data. We acquired all citations from PubMed abstracts by submitting
quarries to the database with appropriate Boolean logic regarding entities and their synonyms. State-of-the-
art external ER systems such as PubTator [46] and beCAS [47] along with our ER system were utilized to
obtain a list of biological entities in the abstract. We then used the Stanford dependency parser [48] to
extract dependencies on different sentences and merge the parse trees into a parse graph. The major
advantage of this parse graph is its potential to identify long-range dependency relations across sentence
boundaries. Candidate relations were created by extracting subtrees connecting pairs of entities from the
dependency graph. Finally, we extracted the mode of regulation based on two sets of manually-annotated
positive and negative causal categories (consisting > 100 verbs and their inflections). In the subsequent
sections we describe the details of our text-mining system.

2.1 Data sets

PubMed database was used to query the entities relating to interaction in ChIP-Atlas. PubMed provides
more than 25 million biomedical and life sciences journal articles. TRRUST regulatory network [49] was
utilized as gold standard to evaluate the performance of ModEx. TRRUST is a manually-curated database
of human transcriptional regulatory network with partial information on mode of regulation. It contains
9,396 regulatory interactions of 800 human transcription factors, 5,066 of which are annotated with
information on mode of regulation (3,148 repression and 1,918 activation). We also obtained TF-gene
interaction data from ChIP-seq experiments, deposited on the ChIP-Atlas database [25]. This database
contains all publicly available high-throughput ChIP-seq experiments. We assembled regulatory networks
from these interactions using various cutoff criteria for ChIP-seq peak signal score and distance to the TSS.
The least stringent criterion results in a network with 4 million interactions between 758 TFs and 18,874
target genes. There is no reported mode of regulation in this database.

2.2 Extraction of relevant citations

For each regulatory interaction in our assembled ChIP-derived network, we developed an IR system to retrieve the information from the literature. Figure 1 illustrates the overall workflow of our IR component to fetch relevant citations associated with the regulatory interaction. We built a query based on the entities participated in the interactions to retrieve abstracts from PubMed database.

Fig. 1. The Information Retrieval framework. The steps are as follows: first, a Boolean query is built according to the associated entities in the regulatory interaction. It uses several external databases to complement the query with more synonyms and aliases. Then, the query is submitted to the PubMed databased and abstracts are retrieved for processing. Abstracts with no regulatory events are excluded for further analysis.

Each query was supplemented with synonyms acquired from several external resources, including HGNC, Entrez, and UniprotKB to fetch more relevant abstracts. All related citations were acquired by submitting a query with appropriate Boolean logic (AND/OR) on entities and their synonyms. A MeSH descriptor term

(e.g. Humans) was also incorporated in the query to reduce the search space. For examples the query for

AATF and MYC regulatory interaction is, "humans[mesh terms] AND (AATF[sym] OR BFR2[sym] OR

CHE-1[sym] OR CHE1[sym] OR DED[sym]) AND (MYC[sym] OR MRTL[sym] OR MYCC[sym] OR

BHLHE39[sym] OR C-MYC[sym])".

The queries were submitted via the PubMed engine, a search engine that provides access to the MEDLINE

database of references and abstracts on life sciences and biomedical articles. In our implementation we

utilized Biopython [50] to run the queries through PubMed engine. We applied a filter on retrieved abstracts

and retained only those containing expert-generated "regulatory events" as presented in Table 1. Each

category contains more than 50 verbs and their inflections. For example, the ATTF-MYC query outlined

above, resulted in 4 relevant abstracts (PMIDs: 20549547, 17006618, 17006618, 20924650).

TABLE 1. Regulatory events categories

Category	NO. Events	Examples
Positive	500	increase, induce, activate, enhance, up-regulate, …
Negative	511	reduce, decrease, suppress, block, down-regulate, decrease, …

2.3 Gene and regulatory event recognition

The next step in the pipeline is to identify biological entities within the abstracts. Figure 2 shows the NER

component of our system. Two external state-of-the-art NER systems were utilized to annotate the retrieved

abstracts with an accurate and complete list of biological entities. The first system is PubTator [51], a web-

based system for assisting biocuration. PubTator utilizes a HTTP REST interface, equipped with multiple

state-of-the-art text mining algorithms to run queries. Using this system, we queried the retrieved PMIDs

and obtained entity annotations in a JSON encoded text. Additionally, we utilized BeCAS [51] (another

online NER tool) to improve the coverage of the entities. BeCAS, like PubTator, provides a RESTful API

for biomedical name identification. It can run queries directly on provided text or PMIDs and returns

associated annotations as an XML document.

Fig. 2. The Gene and regulatory event recognition workflow. Each PubMed ID retrieved by IR component are submitted to the external NER tools (PubTator and BeCAS) for annotating genes in the abstracts. It follows complementary annotations using our internal NER component including a lookup table for covering acronyms, and a similarity search to identify lexical variations for gene names.

To further enhance the NER system, we implemented and added an additional NER component as follows. Abstracts were normalized to uppercase format and searched for gene acronyms using a manually-curated lookup table [52]. This table includes long term / short term pair association to recognize entities, which were missed by the external NER tools. For instance, AR is a short term for "Androgen Receptor" and was only detected as an entity (transcription factor) using this lookup table. Furthermore, we utilized a name similarity metric to identify strings with lexical variations such as whitespace and punctuations. For instance, "IL-12" and "IL12" are two lexical variations of "Interleukin 12". The former version was not identified by the External NER systems. In our implementation, we set the entity detection threshold based on Jaro similarity [53] of 0.9 or larger between the query entity and the string in the abstract.

Next, we normalized the annotated word or a group of words corresponding to a gene to their HGNC symbol for simplification of downstream analysis. Regulatory events were also annotated using our expert-generated categories (Table 1). Figure 3 illustrates the normalization of gene names and annotation of regulatory events. Sentences that contained no regulatory event were excluded from further analysis.

2.4. Extracting mode of regulation

For each causal interaction, its associated annotated sentences within relevant abstracts were submitted to the Stanford dependency parser [48] and a dependency parse tree was generated. Dependency trees extracted from different sentences were merged into a single large graph. The merging process is straightforward; Each dependency relation includes one head word/node and one dependent word/node. Nodes from different dependency relations representing the same word were. PMID was recorded for each edge in the parse tree to indicate its source. Each edge in the parse tree was assigned a weight based on the number of occurrences of dependency relations. The rational for using this weighted parse tree is that it can be used to identify long-range dependency relations across sentence boundaries that would otherwise be missed. Figure 4 shows the relation extraction workflow of our method. Absolute frequency of a dependency relation obtained from the merging step can somewhat reflect the semantic relation of the head word and the dependent word.

Fig. 4. Regulatory sign extraction workflow. A long-range dependency graph is constructed by merging all of dependency trees corresponding to the evidence sentences. The weights of the graph are the number of occurrences of dependency relations. Candidate regulatory signs are identified using common subtrees with at least one regulatory event in the graph. Finally, a sign of regulation is assigned to the query interaction through the ranking task.

Our system, ModEx, creates candidate relations by extracting subtrees with common ancestors connecting the pair of query genes as leaves. These subtrees must contain at least one causal event describing the candidate relation between the given pair of genes. Subtrees were extracted by applying a Depth First Search along with a boolean visited array to avoid possible loops. Nodes with two paths to the entities were considered as a root of the subtree. Next, we utilized a rule based approach to describe relations using three commonly used language constructs [36]. The first rule is effector-relation-effectee (e.g. A activates B). The second rule is relation-of-effectee-by-effector (e.g. Activation of A by B). These rules were applied to both paths from root to query entities to identify their regulatory dependency. Figure 5a illustrates the regulatory relation extraction using these rules. Some sentences in the literature have complex structures,

which cannot be captured by these language constructs. To address this, we also incorporated a negation

rule to increase the performance of the RE system. For example, consider the following sentence: "LMP1

suppresses the transcriptional repressor ATF3, possibly leading to the TGFβ-induced ID1 upregulation"

[54]. In the first pass the system assigns a positive mode to the interaction between ATF3 and ID1.

However, there is a negative interaction between the TF and target gene. The negation rule considers the

negative event "suppresses" related to ATF3 and switch the positive mode to negative. Figure 5b shows a

subtree reflecting the negation rule.

Fig. 5. Examples to illustrate the rules for finding the regulatory sign. panel (a) shows an example for simple rule

(effector-relation-effectee) in which the RE system can assign a positive sign to this candidate pattern. In panel (b),

we can see the impact of the negation rule to extract accurate sign to this pattern. Two paths from root to query entities

contain negative regulatory events which carries an activation/positive sign for the pattern.

We then ranked each subtree based on the sign of regulatory interaction between the query genes. The

weights of the graph encode repetition of regulatory relations across sentences and abstracts. we considered

the weights when there were more than one regulatory event associated with the target gene. In this case,

an event with higher weight was selected for ranking the subtree. We also considered distance of events to

the target gene when the weights in the subtree were equal. The closest event to the target entity will take

the highest priority for determining the interaction sign. Finally, we investigated signs in every candidate

subtree and assigned a total sign of regulation to the interaction using a voting scheme.

2.5.   ModEx HTTP Interface

We implemented an HTTP REST server for users to programmatically annotate gene regulatory networks

using ModEx. Clients should make HTTP requests to the server with a particular format, specifying the

query entities and optional MeSH term to annotate. The query has to be requested in the following format:

TFEntrezID_TargetEntrezID_MeSHterm[optional]. For instance, a query to the server for AATF-MYC

should be formatted as "*/signex/26574_4609_humans*". The server returns extracted annotation along with

associated citations and sentences from PubMed database if any evidence exist. The server can be accessed

at: https://watson.math.umb.edu/modex/

3   RESULTS

3.1   Classification Performance

We evaluated the performance of our method using the TRRUST database, a manually-curated network or

regulatory interaction with partial information on mode of regulation. TRRUST is a high-quality database

and can be considered as gold standard for our benchmark. We applied our method to 5,066 regulatory

interactions in TRRUST for which information on mode of regulation was available. Table 2 shows the

summary statistic of the results.

TABLE 2. Summary statistics of performing ModEx on TRRUST

System	Without evidence	With evidence	Detected with sign	
			4225	
			Positive	Negative
modEx	182	4884	2659	1566

Our method did not detect any PubMed abstracts for 182 of interactions. ModEx detected 4,225 signs

corresponding to 4,225 regulatory interactions including 2,659 positive and 1,566 negative interactions. We

compare the identified signs by ModEx with reported signs in the TRRUST database. Our system correctly

extracted 2,216 positive and 1,024 negative signs with overall accuracy of 0.76. Figure 6 shows the

classification result of ModEx on the TRRUST database using various metrics (Precision, Recall and F-

score).

Fig. 6. Classification results of ModEx on TRRUST

We also compared the citations of the 4,884 retrieved by our system with the citations reported in the

TRRUST database. All citations match, with accuracy of 1.0. This validation using the gold standard

demonstrates the ability of our system to correctly identify relevant citations, extract causal interactions

between TF and gene, and detect mode of regulation. We used our system to annotate the remining

interactions in the TRUSST database for which no mode of regulation is reported.

3.2   ChIP-Atlas Analysis

We next sought to extract and annotate ChIP-seq derived TF-gene causal regulatory interactions from

literature using our system. Such meta-data and evidence from literature can increase the confidence in the

TF-gene interactions identified by ChIP-seq experiments and further shed light on the mechanism of

interaction. Information on mode of regulation in particular can be helpful to enhance the accuracy of

enrichment algorithms for regulatory pathway inference [55].

We applied ModEx to ChIP-seq interactions, with moderately stringency criteria, i.e., binding distance

within 1k of the TSS and ChIP peak score > 950, resulting in 43,444 interactions. The system was able to

detect and annotate 1,592 of interactions in PubMed database. Table 3 outlines the results.

TABLE 3. Summary statistics of performing ModEx on ChIP-Atlas

System	Overall	With evidence	Detected with sign	
			1,592	
ModEx	43,444	5,133	Positive	Negative
			1,421	171

Some of the retrieved annotated ChIP-seq interactions also appear in the TRRUST database (69 total). We

compared the identified mode of regulations of ChIP-seq interactions with the reported signs in the

TRRUST database. Figure 7 summarizes the classification results. As can be seen the agreement is very

high, indicating that our method can reliably identify and annotate ChIP interaction when they are reported

in literature. Additionally, we compared our acquired evidence (PMIDs) by ModEx with citations reported

in TRRUST. Our IR module was able to fetch the relevant evidence from PubMed database with accuracy

0.88.

329   **Fig. 7.** Classification results of ModEx on intersctio on TRRUST and ChIP-Atlas

3.3   Directional enrichment analysis

To demonstrate the utility of our annotated network, we used our network in conjunction with a directional enrichment analysis algorithm [55] to identify drivers of differential expressed genes. We utilized quaternaryProd, a gene set enrichment algorithm that can take advantage of direction of regulation on causal biological interaction graphs to identify regulators of differential gene expression. The algorithm can take a signed transcriptional regulatory network, such as TRRUST or our annotated ChIP-network along with a differential expression profile as input and outputs a set of candidate active regulators. The ability of the algorithm to identify regulators of differential gene expression relies heavily on the quality and the coverage of the regulatory network on which the queries are performed. To test the utility of our network, we used this algorithm along with differential expression profiles from controlled over-expression experiments used in the original study. The over-expression experiments consist of differential gene expression profile from a controlled in vitro E2F3 over expression [56] and c-Myc [56]. We inputted three networks into the algorithm (1) the original TRUSST network, (2) annotated TRUSST network, and (3) annotated TRRUST augmented with annotated ChIP-Atlas. By annotated TRRUST, we refer to the TRRUST network where interaction with no reported mode of regulation were annotated using our system. Differential gene expression analysis of these data sets resulted in 272, and 220 differentially expressed genes respectively. Table 4 outlines the top 5 regulators predicted by the algorithm on E2F3 experiment sorted by the FDR corrected *p-values* of the scoring scheme. For the E2F3 experiment, E2F1 is returned as the top hypothesis regulator by the algorithm incorporating our annotated networks. E2F1 and E2F3 are close family members and have a very similar role as transcription factors that function to control the cell cycle and are similarly implicated in cancer [57]. It is interesting to note that original TRRUST database does not include enough information for algorithm to recover E2F1, however the signal strengthens when TRUSST is annotated with our system and a much more significant p-value is obtained when TRRUST is augmented with annotated ChIP-Atlas. This shows that annotating ChIP-seq data provides significant additional power to identify upstream regulators in conjunction with freely available causal networks.

TABLE 4. Directional enrichment analysis results on E2F1 expression signatures

TRRUST			Annotated TRRUST			Annotated TRRUST with ChIP-Atlas		
Name	Regulation	Adj. P-Val	Name	Regulation	Adj. P-Val	Name	Regulation	Adj. P-Val
REL	Down	1.5e-3	**E2F1**	**Up**	**1.2e-5**	**E2F1**	**Up**	**1.2e-7**
PROX1	Up	2.9e-3	PROX1	Up	2.1e-3	PROX1	Up	2.1e-3
SUGP1	Down	3.2e-3	SUGP1	Down	2.4e-3	SUGP1	Down	2.4e-3

NFIL3	Up	6.3e-3	RELA	Down	3.5e-3	RELA	Down	3.5e-3
TFDP1	Up	7e-3	TFDP1	Up	3.9e-3	TFDP1	Up	3.9e-3

Application of the method to c-Myc differential expression profile shows the same pattern. The annotated TRRUST with ChIP-Atlas recovered MAX as one of the top 20 regulators with low p-value compared to TRRUST. It has been demonstrated that oncogenic activity of c-Myc requires dimerization with MAX [58].

TABLE 5. Directional enrichment analysis results on c-Myc expression signatures

TRRUST			Annotated TRRUST			Annotated TRRUST with ChIP-Atlas		
Name	Regulation	Adj. P-Val	Name	Regulation	Adj. P-Val	Name	Regulation	Adj. P-Val
MYBL2	Up	3.6e-3	MAFA	Down	1.3e-2	USF2	Up	8.8e-3
MXI1	Down	4.0e-3	MKL1	Down	1.3e-2	MAFA	Down	1.3e-2
AATF	Up	4.0e-3	GLI3	Down	1.7e-2	MKL1	Down	1.3e-2
ENO1	Down	4.0e-3	KAT2B	Up	1.9e-2	GLI3	Down	1.7e-2
NR1D1	Up	6.4e-3	SOX6	Down	1.9e-2	KAT2B	Up	1.9e-2
TLE3	Up	6.4e-3	HDAC1	Down	2.5e-2	SOX6	Down	1.9e-2
TOP2B	Down	6.4e-3	MYBL2	Down	2.6e-2	HDAC1	Down	2.5e-2
L3MBTL1	Up	6.4e-3	HDAC7	Up	3.0e-2	MYBL2	Down	2.6e-2
MAFA	Down	6.4e-3	ILF3	Down	3.0e-2	HDAC7	Up	3.0e-3
TLX1	Up	7.9e-3	ELK1	Up	3.6e-2	ILF3	Down	3.0e-2
HLF	Up	1.0e-2	GATA6	Up	3.9e-2	ELK1	Up	3.6e-2
DLX5	Up	1.1e-2	PPARG	Down	4.3e-2	GATA6	Up	3.9e-2
HOXA1	Up	1.1e-2	SATB1	Up	4.4e-2	PLAG1	Up	4.0e-2
MKL1	Down	1.2e-2	ARNT	Up	4.8e-2	CREB1	Up	4.1e-2
IFI16	Down	1.4e-2	RXRA	Up	5.3e-2	PPARG	Down	4.3e-2
PRDM1	Down	1.5e-2	ZEB1	Down	5.5e-2	SATB1	Up	4.4e-2
CEBPE	Down	1.6e-2	E2F4	Down	5.5e-2	ZNF143	Up	4.6e-2
HDAC1	Down	1.6e-2	PPARD	Down	5.6e-2	ARNT	UP	4.8e-2
GLI3	Down	1.6e-2	XBP1	Up	6.5e-2	**MAX**	**Up**	**5.3e-2**
STAT4	Up	1.8e-2	DDIT3	Down	6.5e-2	RXRA	Up	5.4e-2

Conclusion

In this work we presented a fully automated text-mining system to extract and annotate causal regulatory interaction between transcription factors and genes from the biomedical literature. As a starting point, our method uses putative TF-gene interactions derived from high-throughput ChIP-seq or other experiments and seeks to collect evidence and meta-data in the biomedical literature to support the interaction. It should be noted that annotating a priori known interactions differs significantly in scope and complexity from general text-mining approaches for biomedical relation extraction. The later attempts to extract the causal relation from biomedical text directly, without prior knowledge of the entities and the interaction, whereas in our method the relation is know from biological experiments and curated databases a priori, thereby reducing the complexity significantly. This approach bridges the gap between data-driven methods and text-mining methods for constructing causal transcriptional gene regulatory networks and overcomes some of the drawbacks of either approach. With the rapid increase in high-throughput experiments and biomedical literature, hybrid method such as the one proposed can make a significant impact in biological knowledge retrieval.

We used a gold-standard manually curated dataset and demonstrated that our approach can reliably identify the relevant literature and extract the correct interaction and meta-data. We applied our method to high-throughput ChIP-seq data and provided literature support for ~1,500 interactions. Our annotated ChIP-derived transcriptional regulatory interaction can be used in conjunction with directional enrichment methods that aim to identify regulators of differential gene expression. Moreover, we use our system to annotate the interactions in the TRRUST database for which more of regulation is not reported. Our system can also be used as a tool to mine the literature for investigate interactions in newly performed ChIP-seq experiments, where researchers are interested to investigate a specific interaction between a protein and a gene. To facilitate usage, we implemented an HTTP REST server for users to programmatically annotate gene regulatory networks using ModEx available to download at: https://watson.math.umb.edu/modex/. The annotated ChIP-network as well as annotated TRRUST can be obtained from: https://doi.org/10.6084/m9.figshare.8251502.v1

ACKNOWLEDGMENT

The authors are grateful to Dr. Nurit Haspel for helpful discussions and comments.

REFERENCES

[1]   H. de Jong, Modeling and Simulation of Genetic Regulatory Systems: A Literature Review, J. Comput. Biol. 9 (2002) 67–103. doi:10.1089/10665270252833208.

[2]   G. Karlebach, R. Shamir, Modelling and analysis of gene regulatory networks, Nat. Rev.
Mol. Cell Biol. 9 (2008) 770–780. doi:10.1038/nrm2503.

[3]   S. Farahmand, S. Goliaei, N. Ansari-Pour, Z. Razaghi-Moghadam, GTA: a game theoretic
approach to identifying cancer subnetwork markers, Mol. Biosyst. 12 (2016) 818–825.
doi:10.1039/C5MB00684H.

[4]   S. Farahmand, M.H. Foroughmand-Araabi, S. Goliaei, Z. Razaghi-Moghadam, CytoGTA: A
cytoscape plugin for identifying discriminative subnetwork markers using a game theoretic
approach, PLoS One. 12 (2017) e0185016. doi:10.1371/journal.pone.0185016.

[5]   Z. Razaghi-Moghadam, A. Namipashaki, S. Farahmand, N. Ansari-Pour, Systems genetics of
nonsyndromic orofacial clefting provides insights into its complex aetiology, Eur. J. Hum.
Genet. 27 (2019) 226–234. doi:10.1038/s41431-018-0263-7.

[6]   M. Miwa, T. Ohta, R. Rak, A. Rowley, D.B. Kell, S. Pyysalo, S. Ananiadou, A method for
integrating and ranking the evidence for biochemical pathways by mining reactions from
text, Bioinformatics. 29 (2013) i44–i52. doi:10.1093/bioinformatics/btt227.

[7]   S. Bagewadi, T. Bobić, M. Hofmann-Apitius, J. Fluck, R. Klinger, Detecting miRNA Mentions
and Relations in Biomedical Literature, F1000Research. 3 (2015) 205.
doi:10.12688/f1000research.4591.3.

[8]   D. Szklarczyk, A. Franceschini, S. Wyder, K. Forslund, D. Heller, J. Huerta-Cepas, M.
Simonovic, A. Roth, A. Santos, K.P. Tsafou, M. Kuhn, P. Bork, L.J. Jensen, C. von Mering,
STRING v10: protein–protein interaction networks, integrated over the tree of life, Nucleic
Acids Res. 43 (2015) D447–D452. doi:10.1093/nar/gku1003.

[9]   M. Kanehisa, S. Goto, KEGG: Kyoto Encyclopedia of Genes and Genomes, Nucleic Acids Res.
28 (2000) 27–30. doi:10.1093/nar/28.1.27.

[10]   E.G. Cerami, B.E. Gross, E. Demir, I. Rodchenkov, O. Babur, N. Anwar, N. Schultz, G.D.
Bader, C. Sander, Pathway Commons, a web resource for biological pathway data, Nucleic
Acids Res. 39 (2011) D685–D690. doi:10.1093/nar/gkq1039.

[11]   A. Sandelin, W. Alkema, P. Engström, W.W. Wasserman, B. Lenhard, JASPAR: an open-
access database for eukaryotic transcription factor binding profiles, Nucleic Acids Res. 32
(2004) 91D − 94. doi:10.1093/nar/gkh012.

[12]   O.L. Griffith, S.B. Montgomery, B. Bernier, B. Chu, K. Kasaian, S. Aerts, S. Mahony, M.C.
Sleumer, M. Bilenky, M. Haeussler, M. Griffith, S.M. Gallo, B. Giardine, B. Hooghe, P. Van
Loo, E. Blanco, A. Ticoll, S. Lithwick, E. Portales-Casamar, I.J. Donaldson, G. Robertson, C.
Wadelius, P. De Bleser, D. Vlieghe, M.S. Halfon, W. Wasserman, R. Hardison, C.M.
Bergman, S.J.M. Jones, ORegAnno: an open-access community-driven resource for
regulatory annotation, Nucleic Acids Res. 36 (2007) D107–D113. doi:10.1093/nar/gkm967.

[13]   M. Pachkov, I. Erb, N. Molina, E. van Nimwegen, SwissRegulon: a database of genome-
wide annotations of regulatory sites, Nucleic Acids Res. 35 (2007) D127–D131.
doi:10.1093/nar/gkl857.

[14]   C. Jiang, Z. Xuan, F. Zhao, M.Q. Zhang, TRED: a transcriptional regulatory element
database, new entries and other development, Nucleic Acids Res. 35 (2007) D137–D140.
doi:10.1093/nar/gkl1041.

[15]   N.A. Kolchanov, O.A. Podkolodnaya, E.A. Ananko, E. V. Ignatieva, I.L. Stepanenko, O. V. Kel-
Margoulis, A.E. Kel, T.I. Merkulova, T.N. Goryachkovskaya, T. V. Busygina, F.A. Kolpakov,
N.L. Podkolodny, A.N. Naumochkin, I.M. Korostishevskaya, A.G. Romashchenko, G.C.

Overton, Transcription Regulatory Regions Database (TRRD): its status in 2000, Nucleic
Acids Res. 28 (2000) 298–301. doi:10.1093/nar/28.1.298.

[16]   A. Essaghir, F. Toffalini, L. Knoops, A. Kallin, J. van Helden, J.-B. Demoulin, Transcription
factor regulation can be accurately predicted from the presence of target gene signatures
in microarray gene expression data, Nucleic Acids Res. 38 (2010) e120–e120.
doi:10.1093/nar/gkq149.

[17]   H. Han, H. Shim, D. Shin, J.E. Shim, Y. Ko, J. Shin, H. Kim, A. Cho, E. Kim, T. Lee, H. Kim, K.
Kim, S. Yang, D. Bae, A. Yun, S. Kim, C.Y. Kim, H.J. Cho, B. Kang, S. Shin, I. Lee, TRRUST: a
reference database of human transcriptional regulatory interactions, Sci. Rep. 5 (2015)
11432. doi:10.1038/srep11432.

[18]   E. Segal, M. Shapira, A. Regev, D. Pe'er, D. Botstein, D. Koller, N. Friedman, Module
networks: identifying regulatory modules and their condition-specific regulators from
gene expression data, Nat. Genet. 34 (2003) 166–176. doi:10.1038/ng1165.

[19]   S. Farahmand, S. Goliaei, Z.R.M. Kashani, S. Farahmand, Identifying Cancer Subnetwork
Markers Using Game Theory Method, in: Springer, Singapore, 2019: pp. 105–109.
doi:10.1007/978-981-10-4505-9_17.

[20]   A. Vajdi, N. Haspel, H. Banaee, A new DP algorithm for comparing gene expression data
using geometric similarity, in: 2015 IEEE Int. Conf. Bioinforma. Biomed., IEEE, 2015: pp.
1157–1161. doi:10.1109/BIBM.2015.7359846.

[21]   M. Krallinger, A. Valencia, Text-mining and information-retrieval services for molecular
biology, Genome Biol. 6 (2005) 224. doi:10.1186/gb-2005-6-7-224.

[22]   H. Han, J.-W. Cho, S. Lee, A. Yun, H. Kim, D. Bae, S. Yang, C.Y. Kim, M. Lee, E. Kim, S. Lee, B.
Kang, D. Jeong, Y. Kim, H.-N. Jeon, H. Jung, S. Nam, M. Chung, J.-H. Kim, I. Lee, TRRUST v2:
an expanded reference database of human and mouse transcriptional regulatory
interactions, Nucleic Acids Res. 46 (2018) D380–D386. doi:10.1093/nar/gkx1013.

[23]   T.E.P. ENCODE Project Consortium, The ENCODE (ENCyclopedia Of DNA Elements) Project.,
Science. 306 (2004) 636–40. doi:10.1126/science.1105136.

[24]   I. Yevshin, R. Sharipov, T. Valeev, A. Kel, F. Kolpakov, GTRD: a database of transcription
factor binding sites identified by ChIP-seq experiments, Nucleic Acids Res. 45 (2017) D61–
D67. doi:10.1093/nar/gkw951.

[25]   S. Oki, T. Ohta, G. Shioi, H. Hatanaka, O. Ogasawara, Y. Okuda, H. Kawaji, R. Nakaki, J. Sese,
C. Meno, ChIP-Atlas: a data-mining suite powered by full integration of public ChIP-seq
data, EMBO Rep. 19 (2018) e46255. doi:10.15252/embr.201846255.

[26]   S. Gebel, R.B. Lichtner, B. Frushour, W.K. Schlage, V. Hoang, M. Talikka, A. Hengstermann,
C. Mathis, E. Veljkovic, M. Peck, M.C. Peitsch, R. Deehan, J. Hoeng, J.W. Westra,
Construction of a computable network model for DNA damage, autophagy, cell death, and
senescence., Bioinform. Biol. Insights. 7 (2013) 97–117. doi:10.4137/BBI.S11154.

[27]   L.J. Jensen, J. Saric, P. Bork, Literature mining for the biologist: from information retrieval
to biological discovery, Nat. Rev. Genet. 7 (2006) 119–129. doi:10.1038/nrg1768.

[28]   A.M. Cohen, W.R. Hersh, A survey of current work in biomedical text mining, Brief.
Bioinform. 6 (2005) 57–71. doi:10.1093/bib/6.1.57.

[29]   P. Zweigenbaum, D. Demner-Fushman, H. Yu, K.B. Cohen, Frontiers of biomedical text
mining: current progress, Brief. Bioinform. 8 (2007) 358–375. doi:10.1093/bib/bbm045.

[30]   R. Hoffmann, A. Valencia, Implementing the iHOP concept for navigation of biomedical

literature, Bioinformatics. 21 (2005) ii252–ii258. doi:10.1093/bioinformatics/bti1142.

[31]   M. Ashburner, C.A. Ball, J.A. Blake, D. Botstein, H. Butler, J.M. Cherry, A.P. Davis, K.
Dolinski, S.S. Dwight, J.T. Eppig, M.A. Harris, D.P. Hill, L. Issel-Tarver, A. Kasarskis, S. Lewis,
J.C. Matese, J.E. Richardson, M. Ringwald, G.M. Rubin, G. Sherlock, Gene Ontology: tool
for the unification of biology, Nat. Genet. 2000 251. (2000).

[32]   O. Bodenreider, The Unified Medical Language System (UMLS): integrating biomedical
terminology., Nucleic Acids Res. 32 (2004) D267-70. doi:10.1093/nar/gkh061.

[33]   A. Yeh, A. Morgan, M. Colosimo, L. Hirschman, BioCreAtIvE Task 1A: gene mention finding
evaluation, BMC Bioinformatics. 6 (2005) S2. doi:10.1186/1471-2105-6-S1-S2.

[34]   Y. Mao, K. Van Auken, D. Li, C.N. Arighi, P. McQuilton, G.T. Hayman, S. Tweedie, M.L.
Schaeffer, S.J.F. Laulederkind, S.-J. Wang, J. Gobeill, P. Ruch, A.T. Luu, J. -j. Kim, J.-H. Chiang,
Y.-D. Chen, C.-J. Yang, H. Liu, D. Zhu, Y. Li, H. Yu, E. Emadzadeh, G. Gonzalez, J.-M. Chen,
H.-J. Dai, Z. Lu, Overview of the gene ontology task at BioCreative IV, Database. 2014
(2014) bau086–bau086. doi:10.1093/database/bau086.

[35]   A.A. Morgan, Z. Lu, X. Wang, A.M. Cohen, J. Fluck, P. Ruch, A. Divoli, K. Fundel, R. Leaman,
J. Hakenberg, C. Sun, H. Liu, R. Torres, M. Krauthammer, W.W. Lau, H. Liu, C.-N. Hsu, M.
Schuemie, K.B. Cohen, L. Hirschman, Overview of BioCreative II gene normalization.,
Genome Biol. 9 Suppl 2 (2008) S3. doi:10.1186/gb-2008-9-s2-s3.

[36]   K. Fundel, R. Kuffner, R. Zimmer, RelEx--Relation extraction using dependency parse trees,
Bioinformatics. 23 (2007) 365–371. doi:10.1093/bioinformatics/btl616.

[37]   L. Qian, G. Zhou, Tree kernel-based protein–protein interaction extraction from biomedical
literature, J. Biomed. Inform. 45 (2012) 535–543. doi:10.1016/J.JBI.2012.02.004.

[38]   A. Vajdi, K. Zarringhalam, N. Haspel, Patch-DCA: Improved Protein Interface Prediction by
utilizing Structural Information and Clustering DCA scores, BioRxiv. (2019) 656074.
doi:10.1101/656074.

[39]   K.E. Ravikumar, K.B. Wagholikar, D. Li, J.-P. Kocher, H. Liu, Text mining facilitates database
curation - extraction of mutation-disease associations from Bio-medical literature, BMC
Bioinformatics. 16 (2015) 185. doi:10.1186/s12859-015-0609-x.

[40]   Y.-C. Fang, P.-T. Lai, H.-J. Dai, W.-L. Hsu, MeInfoText 2.0: gene methylation and cancer
relation extraction from biomedical literature, BMC Bioinformatics. 12 (2011) 471.
doi:10.1186/1471-2105-12-471.

[41]   M. Gerner, F. Sarafraz, C.M. Bergman, G. Nenadic, BioContext: an integrated text mining
system for large-scale extraction and contextualization of biomolecular events,
Bioinformatics. 28 (2012) 2154–2161. doi:10.1093/bioinformatics/bts332.

[42]   J. Czarnecki, I. Nobeli, A.M. Smith, A.J. Shepherd, A text-mining system for extracting
metabolic reactions from full-text articles, BMC Bioinformatics. 13 (2012) 172.
doi:10.1186/1471-2105-13-172.

[43]   E.K. Mallory, C. Zhang, C. Ré, R.B. Altman, Large-scale extraction of gene interactions from
full-text literature using DeepDive, Bioinformatics. 32 (2015) btv476.
doi:10.1093/bioinformatics/btv476.

[44]   R.J. Mooney, R. Bunescu, Mining knowledge from text using information extraction, ACM
SIGKDD Explor. Newsl. 7 (2005) 3–10. doi:10.1145/1089815.1089817.

[45]   S. Bhatia, D. Kaul, N. Varma, Potential tumor suppressive function of miR-196b in B-cell
lineage acute lymphoblastic leukemia, Mol. Cell. Biochem. 340 (2010) 97–106.

doi:10.1007/s11010-010-0406-9.

[46] C.-H. Wei, H.-Y. Kao, Z. Lu, PubTator: a web-based text mining tool for assisting biocuration,
Nucleic Acids Res. 41 (2013) W518–W522. doi:10.1093/nar/gkt441.

[47] T. Nunes, D. Campos, S. Matos, J.L. Oliveira, BeCAS: biomedical concept recognition
services and visualization, Bioinformatics. 29 (2013) 1915–1916.
doi:10.1093/bioinformatics/btt317.

[48] D. Klein, C.D. Manning, Fast Exact Inference with a Factored Model for Natural Language
Parsing, in: S. Becker, S. Thrun, K. Obermayer (Eds.), Adv. Neural Inf. Process. Syst. 15, MIT
Press, 2003: pp. 3–10. http://papers.nips.cc/paper/2325-fast-exact-inference-with-a-
factored-model-for-natural-language-parsing.pdf.

[49] H. Han, J.-W. Cho, S. Lee, A. Yun, H. Kim, D. Bae, S. Yang, C.Y. Kim, M. Lee, E. Kim, S. Lee, B.
Kang, D. Jeong, Y. Kim, H.-N. Jeon, H. Jung, S. Nam, M. Chung, J.-H. Kim, I. Lee, TRRUST v2:
an expanded reference database of human and mouse transcriptional regulatory
interactions, Nucleic Acids Res. 46 (2018) D380–D386. doi:10.1093/nar/gkx1013.

[50] P.J.A. Cock, T. Antao, J.T. Chang, B.A. Chapman, C.J. Cox, A. Dalke, I. Friedberg, T.
Hamelryck, F. Kauff, B. Wilczynski, M.J.L. de Hoon, Biopython: freely available Python tools
for computational molecular biology and bioinformatics, Bioinformatics. 25 (2009) 1422–
1423. doi:10.1093/bioinformatics/btp163.

[51] C.-H. Wei, H.-Y. Kao, Z. Lu, PubTator: a web-based text mining tool for assisting biocuration,
Nucleic Acids Res. 41 (2013) W518–W522. doi:10.1093/nar/gkt441.

[52] K.E. Ravikumar, M. Rastegar-Mojarad, H. Liu, BELMiner: adapting a rule-based relation
extraction system to extract biological expression language statements from bio-medical
literature evidence sentences, Database. 2017 (2017). doi:10.1093/database/baw156.

[53] M.A. Jaro, Advances in Record-Linkage Methodology as Applied to Matching the 1985
Census of Tampa, Florida, J. Am. Stat. Assoc. 84 (1989) 414. doi:10.2307/2289924.

[54] A.K. Lo, C.W. Dawson, K.W. Lo, Y. Yu, L.S. Young, Upregulation of Id1 by Epstein-Barr Virus-
encoded LMP1 confers resistance to TGFβ-mediated growth inhibition, Mol. Cancer. 9
(2010) 155. doi:10.1186/1476-4598-9-155.

[55] C.T. Fakhry, P. Choudhary, A. Gutteridge, B. Sidders, P. Chen, D. Ziemek, K. Zarringhalam,
Interpreting transcriptional changes using causal graphs: new methods and their practical
utility on public networks, BMC Bioinformatics. 17 (2016) 318. doi:10.1186/s12859-016-
1181-8.

[56] A.H. Bild, G. Yao, J.T. Chang, Q. Wang, A. Potti, D. Chasse, M.-B. Joshi, D. Harpole, J.M.
Lancaster, A. Berchuck, J.A. Olson, J.R. Marks, H.K. Dressman, M. West, J.R. Nevins,
Oncogenic pathway signatures in human cancers as a guide to targeted therapies, Nature.
439 (2006) 353–357. doi:10.1038/nature04296.

[57] H.-Z. Chen, S.-Y. Tsai, G. Leone, Emerging roles of E2Fs in cancer: an exit from cell cycle
control, Nat. Rev. Cancer. 9 (2009) 785–797. doi:10.1038/nrc2696.

[58] B. Amati, M.W. Brooks, N. Levy, T.D. Littlewood, G.I. Evan, H. Land, Oncogenic activity of
the c-Myc protein requires dimerization with Max, Cell. 72 (1993) 233–245.
doi:10.1016/0092-8674(93)90663-B.