SAPdb: A database of nanostructures formed by self-assembly of short peptides

Deepika Mathur[#, 1]**,** Harpreet Kaur[#, 1], Anjali Dhall[2], Neelam Sharma[2], Gajendra P. S. Raghava*[,2]

1. Bioinformatics Centre, CSIR-Institute of Microbial Technology, Chandigarh-160036, India.

2. Department of Computational Biology, Indraprastha Institute of Information Technology, New Delhi-110020, India.

Emails of Authors:

Deepika Mathur: matdeepika@gmail.com

Harpreet Kaur: harpreet5aug@imtech.res.in; hks04180@gmail.com

Anjali Dhall: anjalid@iiitd.ac.in

Neelam Sharma: neelams@iiitd.ac.in

GPS Raghava: raghava@iiitd.ac.in

#These authors contributed equally to this work.

* Corresponding author

G. P. S. Raghava: Professor, Centre for Computational Biology, Indraprastha Institute of Information Technology

Okhla Industrial Estate, Phase III, New Delhi 110020,

India. Tel.: +91 011 26907444

E-mail address: raghava@iiitd.ac.in

Abstract

Background: Nanostructures generated by self-assembly of peptides yield nanomaterial that has

many therapeutic applications, including drug delivery and biomedical engineering, due to their

low cytotoxicity and higher uptake by targeted cells owing to their high affinity and specificity

towards cell surface receptors. Despite the promising implications of this rapidly expanding field,

there is no dedicated resource to study peptide nanostructures.

Result: This study endeavours to create a dedicated repository of short peptides, which may prove

to be the best models to study ordered nanostructures formed by peptide self-assembly. SAPdb has

a repertoire of 1,049 entries of experimentally validated nanostructures formed by the self-

assembling of small peptides. It includes 701 entries are of dipeptides, 328 entries belong to

tripeptides, and 20 entries of single amino acid with some conjugated partners. Each entry

encompasses comprehensive information about the peptide such as chemical modifications in the

peptide sequences, the type of nanostructure formed, and experimental conditions like pH,

temperature, and solvent required for the self-assembly of the peptide, etc. Further, our analysis

has shown that the occurrence of aromatic amino acids favours the formation of self-assembling

nanostructures, as indicated by a large number of entries in SAPdb contain aromatics amino acids.

Besides, we have observed that these peptides form different nanostructures under different

experimental conditions. SAPdb provides this comprehensive information in a hassle-free

tabulated manner at a glance. User-friendly browsing, searching, and analysis modules are

integrated for easy retrieval and comparison of data and examination of properties. We anticipate

SAPdb to be a valuable repository for researchers engaged in the burgeoning arena of

nanobiotechnology.

Availability: The database can be accessed on the web at https://webs.iiitd.edu.in/raghava/sapdb.

Keywords: Nanostructure; Dipeptide; Tripeptide; Self-assembly; Resource

Introduction

Peptides have been reported as key players in diverse fields like immunotherapeutic [1–7], disease

biomarkers [8–10], antibacterial [11–15], antiviral [16–20], anticancer [21–25], antiparasitic [26–

30], antihypertensive [31–33] drugs owing to their properties such as cell-penetration [34],

stability [35–37] and low toxicity [38, 39]. Besides these areas, peptides are rapidly gaining the

attention of researchers in the field of nanobiotechnology [40–43] by virtue of their property to

self-assembly into well-defined nanostructures. Advantages of self-assembled short peptides for

use as nanomaterial relative to conventional materials include simple structure, fast and low-cost

synthesis, better chemical and physical stability, diversity in morphology, ease of synthesis in large

quantities. In addition, biocompatibility, biodegradability, low cytotoxicity, and higher uptake by

targeted cells of SAPs (self-assembling peptides) play a significant role in their therapeutic

applications [44, 45]. Owing to these attractive properties, bioactive peptides with the ability to

undergo self-assembly are being explored to serve as building blocks of hydrogels and scaffolds

in cell culture [46] and tissue engineering [47, 48], controlled drug delivery in response to changes

in pH [49, 50] for diagnostics and biosensors [51], as well as in the field of bioelectronics [52] and

material sciences [52].

Self-assembly of peptides can lead to the formation of well-defined nanostructures like nanofibers,

nanorods, nanoparticles, hydrogels, nanotubes, etc. [53–61]. The assembly of these nanostructures

depends on weak non-covalent interactions like Van der Waals force, hydrophobic interactions,

hydrogen bonds, and π-π stacking [62–65]. The lack of a comprehensive understanding of the

properties and mechanisms of the self-assembly of peptide nanostructure formation affects their

configuration and utility. Thus, it is a challenge to control the shape, size, and stability of these

nanostructures during synthesis for successful integration and translation into biosensors and

controlled release devices for drug delivery.

Though various studies have been carried out to design peptide-based nanoparticles, to the best of

the authors' knowledge, there is no dedicated platform that maintains comprehensive information

about nanoparticles formed by the self-assembly of peptides. A systematic collection and

compilation of experimental data is needed to examine the mechanisms and interactions governing

the self-assembly of peptides into nanostructures for facilitating the rational designing of

morphologies and the size of peptide assemblies. The present report is the first attempt to develop

a repository of short peptides that undergo self-assembly to form nanostructures. Dipeptides and

tripeptides are the smallest of known peptide self-assemblers, which show fascinating

morphologies and functionalities besides being cost-efficient and fast to synthesize. "SAPdb"

database of such short peptides will be very beneficial to study how experimental conditions and

chemical modifications in the amino acid sequence of peptides affect the bottom-up process of

self-assembly to form well-defined ordered nanostructures.

Methods

Data Collection

To collate the relevant information for di- and tri-peptides that self-assemble to form discrete and

ordered nanostructure, PubMed was queried to obtain the research articles. Keywords like

"(tripeptide AND self-assembly)", "(tripeptide AND nanostructure)", "(tripeptide AND

nanotube)", "(tripeptide AND nanofiber)", "(tripeptide AND nanorod)", "(tripeptide AND

hydrogel)", "(tripeptide AND nanosphere)" and "(tripeptide AND nanoparticle)" for self-

assembling tripeptides, while to collect research articles relevant to self-assembling dipeptides

keywords "(dipeptide AND self-assembly)", "(dipeptide AND nanotube)", "(dipeptide AND

nanostructure)", "(dipeptide AND nanorod)", "(dipeptide AND nanosphere)", "(dipeptide AND

nanofiber)", "(dipeptide AND hydrogel)", "(dipeptide AND nanoparticle)" were used collected

around ~1500 publications till July 2019. We screened the articles obtained and included only

those for further data curation, where information about peptides forming self-assembled

nanostructures was available. These self-assembling peptides form various nanostructures, i.e.,

nanosphere, nanotube, hydrogel, nanovesicle, nanofibers, etc. as represented in Figure 1.

Figure 1: Description of the formation of different nanostructures from the self-assembly of
peptides.

After the thorough screening, relevant information extracted from selected articles concerning the

sequence of peptides, N-terminal modifications, C-terminal modification, a technique to analyze

self-assembled structure, method, type of self-assembly, size of the self-assembled structure, and

the conditions under which peptide formed the self-assembled structure such as solvent,

concentration, temperature, pH and incubation time, etc. To provide information regarding the

effect of experimental conditions on the self-assembly of peptides like concentration, solvent, pH,

incubation time, etc. on the self-assembly of peptides, we made multiple entries of the same peptide

if it was reported under different experimental conditions. This extensive information is

systematically cataloged in a tabulated manner. Consequently, 1,049 entries were collated in the

SAPdb database from 301 research articles.

Architecture and web - interface of the Database

SAPdb was designed using Apache HTTP Server (version 2.2.17) on the Linux system following

the collection and compilation of significant information. SAPdb is based on MySQL at the back

end that was implemented to maintain the information and HTML5, PHP, and JavaScript. They

were deployed to execute the front end in order to build a mobile, tablet, and desktop compatible

web-resource. Different modules were integrated into SAPdb for data compilation, retrieval, and

exploration. The complete architecture depicting information and tools embedded into SAPdb

represented in Figure 2.

Figure 2: Architecture depicting the information and tools integrated in SAPdb.

Organization of Database

In SAPdb, collated information was classified into primary and secondary information. The

primary information includes fields like (i) PubMed ID, (ii) peptide sequence, (iii) N-terminal

modification, (iv) C-terminal modification, (v) non-terminal modification, (vi) technique, (vii)

method, (viii) solvent, (ix) concentration of peptide, (x) pH, (xi) temperature, (xii) incubation time,

(xiii) type of self-assembly, (xiv) size of self-assembled structure and (xv) stability of self-

assembled structure. While in secondary information (xvi) SMILES and (xvii) tertiary structure of

peptides were included.

Results

Statistical analysis of data of SAPdb

SAPdb is a collection of 1,049 entries of experimentally validated short peptides that undergo self-

assembly to form ordered nanostructures manually curated and compiled from 301 research

articles published in the recent past with the rise of interest in nanobiotechnology (Figure 3C). Of

these 1,049 entries, 701 entries are of dipeptides, 328 entries belong to tripeptides, and 20 entries

belong to single amino acid with their conjugate partners. 48 of the peptides were cyclic, while the

rest were linear. These model short peptides form 13 major types of nanostructures, as shown in

Figure 3A. Hydrogel (297 entries) is the most common type of structure followed by nanofibers

(127 entries), nanotubes (67 entries), nanospheres (50 entries), nanoparticles (47), and hundreds

of entries of mix nanostructures. Different techniques have been described in the literature to study

the phenomenon of self-assembly of peptides. The most common techniques were scanning

electron microscopy, transmission electron microscopy, atomic force microscopy, Fourier

transform infrared spectroscopy (Figure 3D).

To give different functionality, stability, and shape to nanostructure, some peptides have been

cyclized. In contrast, various terminal modifications and non-natural amino acids have been

incorporated in various other peptide sequences (Figure 3B). Thereis a total of 382 entries in

SAPdb encompass modifications at the N-terminal. Most commonly reported N-terminal

modifications include Fmoc (fluorenylmethoxycarbonyl; 160 entries), Boc (N-t-Butoxycarbonyl;

113 entries) and acetylation (46 entries); while, methoxylation (73), amidation (49 entries),

benzylation (33 entries), were reported as primary modifications at C-terminal. Besides this, 54

reported entries had non-natural amino acids like dehydrophenylalanine (ΔPhe) (30 entries), beta-

alanine (β-Ala) (16 entries), amino benzoic acid (ABA) (9 entries), amino isobutyric acid (Aib) (9

entries), *etc*. in their sequences.

Figure 3: Statistics of distribution of entries in the SAPdb: (A) Types of nanostructures, (B) Year-wise distribution, (C) Based on Peptide, and (D) terminal modification.

Implementation of Web Tools

Various modules, i.e., search tools, browse tools, and analysis tools, were integrated into the database for users to explore SAPdb.

Search Tools

Two distinctive modules are implemented in SAPdb, i.e., Simple search, Advance search under search tool to assist the user for amiable data retrieval.

Simple search: This module offers the fundamental facility for data retrieval from the database. Here one can perform a keyword query by selecting any required field of SAPdb such as the type

of self-assembly, technique, peptide sequence, etc. Besides, this module also permits the users to

select anticipated fields to be displayed in the result.

Advance search: To retrieve relevant information from SAPdb, the advance search module

presents the facility for the user to implement multiple query system. By default, it executes four

queries simultaneously, but the user can select the desired keyword search from any selected field.

Moreover, this module allows the implementation of standard logical operators (=, >, <, and

LIKE). Besides this, advance search permits the user to integrate the output of different queries by

employing operators like 'AND and OR'. Further, the user can also add or remove the queries to

be executed.

Browsing Tools

The browsing facility has been integrated to facilitate the user for data mining in systematic mode

from SAPdb. In this module, the user can fetch information on peptides by browsing six different

classes (i) Chemical modification, (ii) Type of Nanostructure, (iii) Size of Nanostructure, (iv)

Technique, (v) Publication year, (vi) Dipeptides and (vii) Tripeptides.

The chemical modification field assists the user in retrieving data on peptides that have different

chemical modifications at the N or C termini. For instance, Fmoc (fluorenylmethoxycarbonyl; 160

entries), Boc (N-t-Butoxycarbonyl; 113 entries), and acetylation (47 entries) are major

modification at N-terminal; while methoxy (73), amidation (49 entries), benzylation (33 entries),

were reported as primary modifications at C-terminal. Type of nanostructure category offers the

user to fetch detailed information on peptides that form a particular nanostructure such as

nanotube, nanosphere, nanofibers, hydrogel, etc. The size of the nanostructure category allows

users to browse entries based on the size of the nanostructure reported. Further technique category

permits the user to extract information regarding peptides whose nanostructure was studied using

a particular technique such like Transmission Electron Microscopy (TEM), Scanning Electron

Microscopy (SEM), and Atomic Force Microscopy (AFM), and Fourier Transform Infrared

(FTIR), etc. Additionally, users can also retrieve information of the peptides by the year of

publication. Different entries of dipeptide and tripeptide sequences can be explored under the

dipeptide and tripeptide modules of the browse facility.

Analysis Tools

This module enables the users to execute several examinations, such as sequence similarity,

peptide mapping, and physicochemical properties of peptides.

GGSearch: This tool allows the user to perform an efficient similarity-based search against the

short peptides in SAPdb. It is based on Needleman-Wunsch alignment [66].

Smith–Waterman Algorithm: This algorithm [66] permits the user to search peptides in the

SAPdb database similar to their query peptides. Under this option, the user can submit concurrently

multiple peptide sequences in FASTA format.

Peptide Mapping: This tool offers the facility to map SAPdb peptides over the query protein

sequence. It will be useful for identifying motifs within proteins that tend to undergo self-

assembly.

Physicochemical Properties: This module facilitates users to examine properties like charge,

polarity, volume, hydrophobicity, etc. of the desired peptide sequences.

Effect of Experimental Conditions

Previous studies have shown that the variation in experimental conditions like the type of solvent,

change in concentration of peptide, temperature, incubation time, pH, etc. can lead to the formation

of different nanostructures by the same peptide [67]. Further, our analysis shows that the

concentration of peptide is also an important factor for controlling the shape and size of the

nanostructure. For example, KFG tripeptide forms vesicles at a low concentration of 0.5mg/ml

while at higher concentration of 5mg/ml forms nanotubes [67]. Furthermore, the role of solvent in

directing the type of nanostructure formation is also revealed through this analysis. Most of the

nanostructures are formed using water as a solvent, followed by phosphate buffer and organic

solvents like methanol, ethanol, hexafluoropropanol, chloroform, and acetone. FF is reported to

form nanovesicles in acetone, while in water, it forms nanotubes [68]. This analysis also shows

some specific experimental conditions favor the formation of nanostructure as evidenced by the

observation that the majority of the nanostructures are reported to be formed by self-assembly

under room temperature or 25 °C (499 entries) and in the range of neutral pH of 7 to physiological

pH of 7.4 (178 entries) followed by acidic pH of less than 6 (118). Besides, we have observed that

there 258 entries (see Table 1), where, peptides form different nanostructures without any chemical

modifications or conjugate partners. Out of 258 entries, 180 (70%) entries contain any of aromatics

amino acids. This indicates presence of aromatics amino acids favored the self-assembly

formation.

Case Study

Our analysis also shown that the different experimental condition changes the nature of self-

assemblies. In order to understand the effect of conditions, we have considered an example of

diphenylalanine (FF). FF forms hydrogels at different experimental condition such as temperature

= 55°C, pH= ~3-4, 7.2 and 8, incubation time >24 hours etc. On the other side, it forms

nanostructure like nanosphere, nanotubes, and nanofibers at various conditions like pH, N-terminal

modification, temperature, and incubation time, as represented in **Figure 4.**

Figure 4: The demonstration of the effect of experimental conditions (pH, temperature, incubation

time, and N-terminal modification) in the formation of different self-assembled structures like

nanosphere, hydrogel, nanofiber, and nanotube.

In the absence of any user-friendly web-platform, the user needs to go through widely spread

literature in the form of the bulky text publications. SAPdb allows easy access to such information

in tabulated form, which leads to a better understanding of the 3D shape of nanostructures formed

by altering experimental conditions.

Working of SAPdb database

To understand how a user can be queried and retrieve data from the SAPdb database, we have

demonstrated (Figure 5) with an example of a dipeptide, i.e., dipleneyalanine (FF). Figure 5

representing the step by step information on how users can query/search SAPdb using a simple

search module by a keyword like PMID, Peptide sequence, Peptide name, year of publication,

etc. For instance, here, we queried the search module with peptide sequence, i.e., FF in the given

search space (Figure 5A) of the database. User can further select various display fields that are

given on a simple search page. On submitting the desired query (e.g., FF) using the "Submit"

button, the next page will display all the entries related to the query; for instance, here we retrieved

362 entries of FF, as shown in Figure 5B. Each entry has a unique SAPdb ID, and the user can get

the detailed information regarding peptide by further clicking on the SAPdb ID. The next page

provides complete information about the selected SAPdb ID, as represented in Figure 5C. It gives

the peptide's primary information (SAPdb ID, PMID, Year, Name, Sequence, N-terminal

modification, C-terminal modification, non-terminal modification, peptide/conjugate/Mixture,

conjugate partner, Technique, solvent, Method, concentration, pH, Temperature, etc. The

secondary information provides Physiochemical properties, Structure, and SMILS of the given

peptide. Users can further explore these properties, as shown in Figure 5D.

Figure 5: Demonstration of querying and retrieval of information from SAPdb using the

Simple Search module.

Discussion

With the rising interest in nanobiotechnology, it is important to understand the properties

governing the self-assembly of peptides into nanostructures. Previously databases like AmyLoad

[69], CPAD [70] and AMYPdb [71] have curated protein and peptide aggregation. Since there was

no repository of experimentally validated and well-ordered self-assembling peptide

nanostructures, we have developed SAPdb, a platform with comprehensive information about

nanostructure formed by short peptides. Dipeptides and tripeptides are the shortest peptides that

can assemble into higher-order structures. They are the model candidates to understand the process

of self-assembly. SAPdb holds information of 167 unique dipeptides and 96 unique tripeptides that

have been experimentally validated for undergoing ordered nanostructure formation by self-

assembly.

Comprehensive analysis of SAPdb data have shown that different environmental conditions like

temperature, pH, solvent, concentration, etc. direct the shape or type of nanostructures formation.

Further, the specific conditions, i.e., room temperature, acidic pH, favors the formation of

nanostructure of self-assembling peptides. Besides, amino acid composition analysis of peptides

of SAPdb revealed that self-assembling peptides are rich in valine, tryptophan, leucine, and

alanine. At the same time, they are depleted in isoleucine, aspartic acid, and histidine compared to

non-self-assembling peptides. Further, aromatic residues like phenylalanine and tyrosine are

favored at the second and third positions in tripeptides undergoing self-assembly. Besides,

negatively charged residues are preferred at the C-terminal and while positively charged residue

are at the N-terminal.

Utilization of SAPdb

SAPdb maintains nanostructure-forming small peptides, which have numerous applications in

diverse areas as illustrated by the following examples:

The drug, gene, and other biomolecules delivery vehicles

One of the major applications of SAPs lies in the delivery of drugs and biomolecules. This is

attributed to their biocompatible nature, the small size of self-assembling dipeptides and tripeptides

[72–76]. For instance, EΔF dipeptide based nanovesicles employed to deliver vitamin B-12 in the

HeLa cells [77], while MΔF, IΔF, and LΔF were used for the invitro delivery of curcumin in L-

929 cells and in vivo delivery in mouse [78].

Cell culture scaffold biomaterial for tissue engineering

Another major application of the peptide based self-assembled hydrogels is their efficiency for

3D-cell culture (Jayawarna). It has been observed that dipeptide FΔF based hydrogel sustained

3D cell growth of HeLa cells and L929 (mouse fibroblast) cells for more than 14 days, with

substantial multiplication rate and cell viability [79].

Models for nanofabrication and biomineralization

In the past, self-assembling peptides were explored as templates for nanofabrication like

nanowires, biomineralization, nanocircuits owing to their potential of self-assembly [80, 81]. For

example, Phe–Phe tagged with ferrocence forms uniform nanowires having a diameter of 100 nm

with a length 5–10 mm. After adsorbing gold nanoparticles and antibody molecules onto these Fc-

tagged nanowires surface, these nanowires were employed as a detection probe for sensitive

electrochemical immunosensing [82].

We have incorporated peptides with such far-reaching applications in SAPdb so that the users can

easily retrieve the SAPs of their interest. Using different modules, one can examine how the

substitution of D-amino acids or non-natural amino acids in the peptide sequence and the

experimental conditions like a solvent, concentration, pH, etc. influence the self-assembling

property of the peptides. Moreover, to facilitate the users, we have integrated a chemical

modification browsing tool to highlight the impact of different modifications on the type of

nanostructure formed by the same peptide sequence. The users can easily analyze sequence

similarity of their query peptide with different SAPs at a single platform, i.e., SAPdb, which are

otherwise scattered in the literature and difficult to access.

Future Developments

289 As the scientific community is actively publishing articles pertaining to this emerging field, in the

290 future, our first concern will be to update data available about short model peptides as well as to

291 expand the database further to include longer peptides which form ordered nanostructures on self-

292 assembly.

Acknowledgments

294 The authors are thankful to the Department of Science Technology, India (JC Bose National

295 Fellowship) for financial support. D.M. and H.K. are grateful to the Council of Scientific and

296 Industrial Research (CSIR), India, and A.D. and N.S. are thankful to the Department of Science

297 Technology (DST), India, for providing fellowships.

Author contributions

299 D.M., H.K., A.D., and N.S., collected and compiled the data. D.M., H.K., developed the website

300 and penned the manuscript. G.P.S.R. conceived the idea and coordinated the project.

Competing interests

302 The authors declare no competing financial and non-financial interests.

References

1.   Nagpal, G., Usmani, S.S., Dhanda, S.K., Kaur, H., Singh, S., Sharma, M., Raghava,

G.P.S.: Computer-aided designing of immunosuppressive peptides based on IL-10

inducing potential. Sci. Rep. 7, 42851 (2017). https://doi.org/10.1038/srep42851

2.   Dhanda, S.K., Usmani, S.S., Agrawal, P., Nagpal, G., Gautam, A., Raghava, G.P.S.:

Novel in silico tools for designing peptide-based subunit vaccines and

immunotherapeutics. Brief. Bioinform. 18, 467–478 (2017).

https://doi.org/10.1093/bib/bbw025

3.   Miller, M.J., Foy, K.C., Kaumaya, P.T.P.: Cancer immunotherapy: present status, future

perspective, and a new paradigm of peptide immunotherapeutics. Discov. Med. 15, 166–

76 (2013)

4.   Reche, P., Flower, D.R., Fridkis-Hareli, M., Hoshino, Y.: Peptide-Based

Immunotherapeutics and Vaccines 2015. J. Immunol. Res. 2015, 349049 (2015).

https://doi.org/10.1155/2015/349049

5.   Dhanda, S.K., Usmani, S.S., Agrawal, P., Nagpal, G., Gautam, A., Raghava, G.P.S.:

Novel *in silico* tools for designing peptide-based subunit vaccines and

immunotherapeutics. Brief. Bioinform. bbw025 (2016).

https://doi.org/10.1093/bib/bbw025

6.   Zhan, X., Li, C., Jiang, Y., Li, N.: EPITOPE-BASED VACCINE FOR THE

TREATMENT OF DER F 3 ALLERGY. Nutr. Hosp. 32, 2763–70 (2015).

https://doi.org/10.3305/nh.2015.32.6.9878

7.   Kobayashi, H., Kennedy, R., Lu, J., Davila, E., Celis, E.: MHC-binding peptides as

immunotherapeutics for cancer. Immunol. Invest. 29, 105–10 (2000)

8.   Bhalla, S., Verma, R., Kaur, H., Kumar, R., Usmani, S.S., Sharma, S., Raghava, G.P.S.:

CancerPDF: A repository of cancer-associated peptidome found in human biofluids. Sci.

Rep. 7, 1511 (2017). https://doi.org/10.1038/s41598-017-01633-3

9.   Stalmach, A., Johnsson, H., McInnes, I.B., Husi, H., Klein, J., Dakna, M., Mullen, W.,

Mischak, H., Porter, D.: Identification of urinary peptide biomarkers associated with

rheumatoid arthritis. PLoS One. 9, e104625 (2014).

https://doi.org/10.1371/journal.pone.0104625

10.   Salamanca, D., Gómez-Chaparro, J.L., Hidalgo, A., Labella, F.: Expresión diferencial del

proteoma en humor acuoso de pacientes con y sin glaucoma. Arch. Soc. Esp. Oftalmol.

93, 160–168 (2018). https://doi.org/10.1016/j.oftal.2017.12.019

11.   Waghu, F.H., Gopi, L., Barai, R.S., Ramteke, P., Nizami, B., Idicula-Thomas, S.: CAMP:

Collection of sequences and structures of antimicrobial peptides. Nucleic Acids Res. 42,

D1154–D1158 (2014). https://doi.org/10.1093/nar/gkt1157

12.   Piotto, S.P., Sessa, L., Concilio, S., Iannelli, P.: YADAMP: yet another database of

antimicrobial peptides. Int. J. Antimicrob. Agents. 39, 346–51 (2012).

https://doi.org/10.1016/j.ijantimicag.2011.12.003

13.   Marr, A.K., Gooderham, W.J., Hancock, R.E.: Antibacterial peptides for therapeutic use:

obstacles and realistic outlook. Curr. Opin. Pharmacol. 6, 468–72 (2006).

https://doi.org/10.1016/j.coph.2006.04.006

14.   Jenssen, H., Hamill, P., Hancock, R.E.W.: Peptide Antimicrobial Agents. Clin. Microbiol.

Rev. 19, 491–511 (2006). https://doi.org/10.1128/CMR.00056-05

15.   Berges, D.A., DeWolf, W.E., Dunn, G.L., Grappel, S.F., Newman, D.J., Taggart, J.J.,

Gilvarg, C.: Peptides of 2-aminopimelic acid: antibacterial agents that inhibit diaminopimelic acid biosynthesis. J. Med. Chem. 29, 89–95 (1986)

16. da Mata, É.C.G., Mourão, C.B.F., Rangel, M., Schwartz, E.F.: Antiviral activity of animal venom peptides and related compounds. J. Venom. Anim. Toxins Incl. Trop. Dis. 23, 3 (2017). https://doi.org/10.1186/s40409-016-0089-0

17. Zhao, H., Zhou, J., Zhang, K., Chu, H., Liu, D., Poon, V.K.-M., Chan, C.C.-S., Leung, H.-C., Fai, N., Lin, Y.-P., Zhang, A.J.-X., Jin, D.-Y., Yuen, K.-Y., Zheng, B.-J.: A novel peptide with potent and broad-spectrum antiviral activities against multiple respiratory viruses. Sci. Rep. 6, 22008 (2016). https://doi.org/10.1038/srep22008

18. Qureshi, A., Thakur, N., Tandon, H., Kumar, M.: AVPdb: a database of experimentally validated antiviral peptides targeting medically important viruses. Nucleic Acids Res. 42, D1147–D1153 (2014). https://doi.org/10.1093/nar/gkt1191

19. Mohan, K.V.K., Rao, S.S., Atreya, C.D.: Antiviral activity of selected antimicrobial peptides against vaccinia virus. Antiviral Res. 86, 306–11 (2010). https://doi.org/10.1016/j.antiviral.2010.03.012

20. Carriel-Gomes, M.C., Kratz, J.M., Barracco, M.A., Bachére, E., Barardi, C.R.M., Simões, C.M.O.: In vitro antiviral activity of antimicrobial peptides against herpes simplex virus 1, adenovirus, and rotavirus. Mem. Inst. Oswaldo Cruz. 102, 469–472 (2007). https://doi.org/10.1590/S0074-02762007005000028

21. Felício, M.R., Silva, O.N., Gonçalves, S., Santos, N.C., Franco, O.L.: Peptides with Dual Antimicrobial and Anticancer Activities. Front. Chem. 5, 5 (2017).

https://doi.org/10.3389/fchem.2017.00005

22. Akrami, M., Balalaie, S., Hosseinkhani, S., Alipour, M., Salehi, F., Bahador, A., Haririan,

I.: Tuning the anticancer activity of a novel pro-apoptotic peptide using gold nanoparticle

platforms. Sci. Rep. 6, 31030 (2016). https://doi.org/10.1038/srep31030

23. Chu, H.-L., Yip, B.-S., Chen, K.-H., Yu, H.-Y., Chih, Y.-H., Cheng, H.-T., Chou, Y.-T.,

Cheng, J.-W.: Novel antimicrobial peptides with high anticancer activity and selectivity.

PLoS One. 10, e0126390 (2015). https://doi.org/10.1371/journal.pone.0126390

24. Tyagi, A., Tuknait, A., Anand, P., Gupta, S., Sharma, M., Mathur, D., Joshi, A., Singh, S.,

Gautam, A., Raghava, G.P.S.: CancerPPD: a database of anticancer peptides and proteins.

Nucleic Acids Res. 43, D837-43 (2015). https://doi.org/10.1093/nar/gku892

25. Schweizer, F.: Cationic amphiphilic peptides with cancer-selective toxicity. Eur. J.

Pharmacol. 625, 190–4 (2009). https://doi.org/10.1016/j.ejphar.2009.08.043

26. Lacerda, A.F., Pelegrini, P.B., de Oliveira, D.M., Vasconcelos, É.A.R., Grossi-de-Sá,

M.F.: Anti-parasitic Peptides from Arthropods and their Application in Drug Therapy.

Front. Microbiol. 7, 91 (2016). https://doi.org/10.3389/fmicb.2016.00091

27. Mehta, D., Anand, P., Kumar, V., Joshi, A., Mathur, D., Singh, S., Tuknait, A.,

Chaudhary, K., Gautam, S.K., Gautam, A., Varshney, G.C., Raghava, G.P.S.: ParaPep: a

web resource for experimentally validated antiparasitic peptide sequences and their

structures. Database (Oxford). 2014, bau051–bau051 (2014).

https://doi.org/10.1093/database/bau051

28. Pretzel, J., Mohring, F., Rahlfs, S., Becker, K.: Antiparasitic peptides. Adv. Biochem.

Eng. Biotechnol. 135, 157–92 (2013). https://doi.org/10.1007/10_2013_191

29.   Mor, A.: Multifunctional host defense peptides: antiparasitic activities. FEBS J. 276,

6474–82 (2009). https://doi.org/10.1111/j.1742-4658.2009.07358.x

30.   Boulanger, N., Munks, R.J.L., Hamilton, J. V, Vovelle, F., Brun, R., Lehane, M.J., Bulet,

P.: Epithelial innate immunity. A novel antimicrobial peptide with antiparasitic activity in

the blood-sucking insect Stomoxys calcitrans. J. Biol. Chem. 277, 49921–6 (2002).

https://doi.org/10.1074/jbc.M206296200

31.   Kumar, R., Chaudhary, K., Sharma, M., Nagpal, G., Chauhan, J.S., Singh, S., Gautam, A.,

Raghava, G.P.S.: AHTPDB: a comprehensive platform for analysis and presentation of

antihypertensive peptides. Nucleic Acids Res. 43, D956-62 (2015).

https://doi.org/10.1093/nar/gku1141

32.   Puchalska, P., Marina Alegre, M.L., García López, M.C.: Isolation and characterization of

peptides with antihypertensive activity in foodstuffs. Crit. Rev. Food Sci. Nutr. 55, 521–

51 (2015). https://doi.org/10.1080/10408398.2012.664829

33.   Aleixandre, A., Miguel, M., Muguerza, B.: [Peptides with antihypertensive activity from

milk and egg proteins]. Nutr. Hosp. 23, 313–8

34.   Agrawal, P., Bhalla, S., Usmani, S.S., Singh, S., Chaudhary, K., Raghava, G.P.S.,

Gautam, A.: CPPsite 2.0: a repository of experimentally validated cell-penetrating

peptides. Nucleic Acids Res. 44, D1098-103 (2016). https://doi.org/10.1093/nar/gkv1266

35.   Mathur, D., Prakash, S., Anand, P., Kaur, H., Agrawal, P., Mehta, A., Kumar, R., Singh,

S., Raghava, G.P.S.: PEPlife: A Repository of the Half-life of Peptides. Sci. Rep. 6, 36617

(2016). https://doi.org/10.1038/srep36617

36.   Penchala, S.C., Miller, M.R., Pal, A., Dong, J., Madadi, N.R., Xie, J., Joo, H., Tsai, J.,

Batoon, P., Samoshin, V., Franz, A., Cox, T., Miles, J., Chan, W.K., Park, M.S.,

Alhamadsheh, M.M.: A biomimetic approach for enhancing the in vivo half-life of

peptides. Nat. Chem. Biol. 11, 793–8 (2015). https://doi.org/10.1038/nchembio.1907

37.   Werle, M., Bernkop-Schnürch, A.: Strategies to improve plasma half life time of peptide

and protein drugs. Amino Acids. 30, 351–67 (2006). https://doi.org/10.1007/s00726-005-

0289-3

38.   Gautam, A., Chaudhary, K., Singh, S., Joshi, A., Anand, P., Tuknait, A., Mathur, D.,

Varshney, G.C., Raghava, G.P.S.: Hemolytik: a database of experimentally determined

hemolytic and non-hemolytic peptides. Nucleic Acids Res. 42, D444-9 (2014).

https://doi.org/10.1093/nar/gkt1008

39.   Chaudhary, K., Kumar, R., Singh, S., Tuknait, A., Gautam, A., Mathur, D., Anand, P.,

Varshney, G.C., Raghava, G.P.S.: A Web Server and Mobile App for Computing

Hemolytic Potency of Peptides. Sci. Rep. 6, 22843 (2016).

https://doi.org/10.1038/srep22843

40.   Yu, C.-Y., Huang, W., Li, Z.-P., Lei, X.-Y., He, D.-X., Sun, L.: Progress in Self-

assembling Peptide-based Nanomaterials for Biomedical Applications. Curr. Top. Med.

Chem. 16, 281–90 (2016)

41.   Luo, Z., Yue, Y., Zhang, Y., Yuan, X., Gong, J., Wang, L., He, B., Liu, Z., Sun, Y., Liu,

J., Hu, M., Zheng, J.: Designer D-form self-assembling peptide nanofiber scaffolds for 3-

dimensional cell cultures. Biomaterials. 34, 4902–13 (2013).

https://doi.org/10.1016/j.biomaterials.2013.03.081

42.   de la Rica, R., Matsui, H.: Applications of peptide and protein-based materials in

bionanotechnology. Chem. Soc. Rev. 39, 3499–509 (2010).

https://doi.org/10.1039/b917574c

43.   Zhao, X., Pan, F., Xu, H., Yaseen, M., Shan, H., Hauser, C.A.E., Zhang, S., Lu, J.R.:

Molecular self-assembly and applications of designer peptide amphiphiles. Chem. Soc.

Rev. 39, 3480 (2010). https://doi.org/10.1039/b915923c

44.   Habibi, N., Kamaly, N., Memic, A., Shafiee, H.: Self-assembled peptide-based

nanostructures: Smart nanomaterials toward targeted drug delivery. Nano Today. 11, 41–

60 (2016). https://doi.org/10.1016/j.nantod.2016.02.004

45.   Elzoghby, A.O., Elgohary, M.M., Kamel, N.M.: Implications of protein- and Peptide-

based nanoparticles as potential vehicles for anticancer drugs. Adv. Protein Chem. Struct.

Biol. 98, 169–221 (2015). https://doi.org/10.1016/bs.apcsb.2014.12.002

46.   Liyanage, W., Vats, K., Rajbhandary, A., Benoit, D.S.W., Nilsson, B.L.: Multicomponent

dipeptide hydrogels as extracellular matrix-mimetic scaffolds for cell culture applications.

Chem. Commun. 51, 11260–11263 (2015). https://doi.org/10.1039/C5CC03162A

47.   Koutsopoulos, S.: Self-assembling peptide nanofiber hydrogels in tissue engineering and

regenerative medicine: Progress, design guidelines, and applications. J. Biomed. Mater.

Res. A. 104, 1002–16 (2016). https://doi.org/10.1002/jbm.a.35638

48.   Liu, J., Song, H., Zhang, L., Xu, H., Zhao, X.: Self-assembly-peptide hydrogels as tissue-

453   engineering scaffolds for three-dimensional culture of chondrocytes in vitro. Macromol.

454   Biosci. 10, 1164–70 (2010). https://doi.org/10.1002/mabi.200900450

455 49.   Chen, B., He, X.-Y., Yi, X.-Q., Zhuo, R.-X., Cheng, S.-X.: Dual-peptide-functionalized

456   albumin-based nanoparticles with ph-dependent self-assembly behavior for drug delivery.

457   ACS Appl. Mater. Interfaces. 7, 15148–53 (2015).

458   https://doi.org/10.1021/acsami.5b03866

459 50.   Seib, F.P., Jones, G.T., Rnjak-Kovacina, J., Lin, Y., Kaplan, D.L.: pH-Dependent

460   Anticancer Drug Release from Silk Nanoparticles. Adv. Healthc. Mater. 2, 1606–1611

461   (2013). https://doi.org/10.1002/adhm.201300034

462 51.   Sasso, L., Vedarethinam, I., Emnéus, J., Svendsen, W.E., Castillo-León, J.: Self-

463   assembled diphenylalanine nanowires for cellular studies and sensor applications. J.

464   Nanosci. Nanotechnol. 12, 3077–83 (2012)

465 52.   Scheibel, T., Parthasarathy, R., Sawicki, G., Lin, X.-M., Jaeger, H., Lindquist, S.L.:

466   Conducting nanowires built by controlled self-assembly of amyloid fibers and selective

467   metal deposition. Proc. Natl. Acad. Sci. 100, 4527–4532 (2003).

468   https://doi.org/10.1073/pnas.0431081100

469 53.   Emerging biological materials through molecular self-assembly. - PubMed - NCBI,

470   https://www.ncbi.nlm.nih.gov/pubmed/?term=Emerging+biological+materials+through+

471   molecular+self-assembly.+Biotechnol+Adv

472 54.   Zhang, S.: Emerging biological materials through molecular self-assembly. Biotechnol.

473   Adv. 20, 321–339 (2002). https://doi.org/10.1016/S0734-9750(02)00026-5

55.   Hatip Koc, M., Cinar Ciftci, G., Baday, S., Castelletto, V., Hamley, I.W., Guler, M.O.:

Hierarchical Self-Assembly of Histidine-Functionalized Peptide Amphiphiles into

Supramolecular Chiral Nanostructures. Langmuir. 33, 7947–7956 (2017).

https://doi.org/10.1021/acs.langmuir.7b01266

56.   Rodríguez-Vázquez, N., Amorín, M., Granja, J.R.: Recent advances in controlling the

internal and external properties of self-assembling cyclic peptide nanotubes and dimers.

Org. Biomol. Chem. 15, 4490–4505 (2017). https://doi.org/10.1039/C7OB00351J

57.   Fuertes, A., Ozores, H.L., Amorín, M., Granja, J.R.: Self-assembling Venturi-like peptide

nanotubes. Nanoscale. 9, 748–753 (2017). https://doi.org/10.1039/C6NR08174F

58.   Tamamis, P., Kasotakis, E., Archontis, G., Mitraki, A.: Combination of theoretical and

experimental approaches for the design and study of fibril-forming peptides. Methods

Mol. Biol. 1216, 53–70 (2014). https://doi.org/10.1007/978-1-4939-1486-9_3

59.   Lee, H.-K., Soukasene, S., Jiang, H., Zhang, S., Feng, W., Stupp, S.I.: Light-induced self-

assembly of nanofibers inside liposomes. Soft Matter. 4, 962–964 (2008).

https://doi.org/10.1039/b719486b

60.   Cui, H., Muraoka, T., Cheetham, A.G., Stupp, S.I.: Self-assembly of giant peptide

nanobelts. Nano Lett. 9, 945–51 (2009). https://doi.org/10.1021/nl802813f

61.   Khoe, U., Yang, Y., Zhang, S.: Self-assembly of nanodonut structure from a cone-shaped

designer lipid-like peptide surfactant. Langmuir. 25, 4111–4 (2009).

https://doi.org/10.1021/la8025232

62.   Mandal, D., Nasrolahi Shirazi, A., Parang, K.: Self-assembly of peptides to

nanostructures. Org. Biomol. Chem. 12, 3544–61 (2014).

https://doi.org/10.1039/c4ob00447g

63. Hamley, I.W., Dehsorkhi, A., Castelletto, V.: Coassembly in binary mixtures of peptide

amphiphiles containing oppositely charged residues. Langmuir. 29, 5050–9 (2013).

https://doi.org/10.1021/la400163q

64. Ulijn, R. V, Smith, A.M.: Designing peptide based nanomaterials. Chem. Soc. Rev. 37,

664–75 (2008). https://doi.org/10.1039/b609047h

65. Whitesides, G.M., Mathias, J.P., Seto, C.T.: Molecular self-assembly and nanochemistry:

a chemical strategy for the synthesis of nanostructures. Science. 254, 1312–9 (1991).

https://doi.org/10.1126/science.1962191

66. Needleman, S.B., Wunsch, C.D.: A general method applicable to the search for

similarities in the amino acid sequence of two proteins. J. Mol. Biol. 48, 443–53 (1970)

67. Ozkan, A.D., Tekinay, A.B., Guler, M.O., Tekin, E.D.: Effects of temperature, pH and

counterions on the stability of peptide amphiphile nanofiber structures. RSC Adv. 6,

104201–104214 (2016). https://doi.org/10.1039/C6RA21261A

68. Demirel, G., Malvadkar, N., Demirel, M.C.: Control of protein adsorption onto core-shell

tubular and vesicular structures of diphenylalanine/parylene. Langmuir. 26, 1460–3

(2010). https://doi.org/10.1021/la903571y

69. Wozniak, P.P., Kotulska, M.: AmyLoad: website dedicated to amyloidogenic protein

fragments. Bioinformatics. 31, 3395–7 (2015).

https://doi.org/10.1093/bioinformatics/btv375

70. Thangakani, A.M., Nagarajan, R., Kumar, S., Sakthivel, R., Velmurugan, D., Gromiha,

M.M.: CPAD, Curated Protein Aggregation Database: A Repository of Manually Curated

Experimental Data on Protein and Peptide Aggregation. PLoS One. 11, e0152949 (2016).

https://doi.org/10.1371/journal.pone.0152949

71. Pawlicki, S., Le Béchec, A., Delamarche, C.: AMYPdb: A database dedicated to amyloid

precursor proteins. BMC Bioinformatics. 9, 273 (2008). https://doi.org/10.1186/1471-

2105-9-273

72. Panda, J.J., Varshney, A., Chauhan, V.S.: Self-assembled nanoparticles based on modified

cationic dipeptides and DNA: novel systems for gene delivery. J. Nanobiotechnology. 11,

18 (2013). https://doi.org/10.1186/1477-3155-11-18

73. Ischakov, R., Adler-Abramovich, L., Buzhansky, L., Shekhter, T., Gazit, E.: Peptide-

based hydrogel nanoparticles as effective drug delivery agents. Bioorg. Med. Chem. 21,

3517–22 (2013). https://doi.org/10.1016/j.bmc.2013.03.012

74. Panda, J.J., Kaul, A., Alam, S., Babbar, A.K., Mishra, A.K., Chauhan, V.S.: Designed

peptides as model self-assembling nanosystems: characterization and potential biomedical

applications. Ther. Deliv. 2, 193–204 (2011)

75. Liang, G., Yang, Z., Zhang, R., Li, L., Fan, Y., Kuang, Y., Gao, Y., Wang, T., Lu, W.W.,

Xu, B.: Supramolecular hydrogel of a D-amino acid dipeptide for controlled drug release

in vivo. Langmuir. 25, 8419–22 (2009)

76. Panda, J.J., Mishra, A., Basu, A., Chauhan, V.S.: Stimuli responsive self-assembled

hydrogel of a low molecular weight free dipeptide with potential for tunable drug delivery.

Biomacromolecules. 9, 2244–50 (2008). https://doi.org/10.1021/bm800404z

77.   Mishra, A., Panda, J.J., Basu, A., Chauhan, V.S.: Nanovesicles based on self-assembly of

conformationally constrained aromatic residue containing amphiphilic dipeptides.

Langmuir. 24, 4571–6 (2008). https://doi.org/10.1021/la7034533

78.   Alam, S., Panda, J.J., Chauhan, V.S.: Novel dipeptide nanoparticles for effective curcumin

delivery. Int. J. Nanomedicine. 7, 4207–22 (2012). https://doi.org/10.2147/IJN.S33015

79.   Jayawarna, V., Ali, M., Jowitt, T.A., Miller, A.F., Saiani, A., Gough, J.E., Ulijn, R.V.:

Nanostructured Hydrogels for Three-Dimensional Cell Culture Through Self-Assembly of

Fluorenylmethoxycarbonyl–Dipeptides. Adv. Mater. 18, 611–614 (2006).

https://doi.org/10.1002/adma.200501522

80.   Panda, J.J., Dua, R., Mishra, A., Mittra, B., Chauhan, V.S.: 3D cell growth and

proliferation on a RGD functionalized nanofibrillar hydrogel based on a conformationally

restricted residue containing dipeptide. ACS Appl. Mater. Interfaces. 2, 2839–48 (2010).

https://doi.org/10.1021/am1005173

81.   Panda, J.J., Dua, R., Mishra, A., Mittra, B., Chauhan, V.S.: 3D Cell Growth and

Proliferation on a RGD Functionalized Nanofibrillar Hydrogel Based on a

Conformationally Restricted Residue Containing Dipeptide. ACS Appl. Mater. Interfaces.

2, 2839–2848 (2010). https://doi.org/10.1021/am1005173

82.   Hartgerink, J.D., Beniash, E., Stupp, S.I.: Self-Assembly and Mineralization of Peptide-

Amphiphile Nanofibers. Science (80-.). 294, 1684–1688 (2001).

https://doi.org/10.1126/science.1063187