CNN explains tuning properties of anterior, but not middle, face-processing areas in macaque IT

Rajani Raman*, Haruo Hosoya*

Cognitive Mechanisms Laboratories, ATR International, Kyoto, Japan 619-0288

(*) corresponding authors

Abstract

A number of recent computational studies have emphasized quantitative similarity between convolutional neural networks (CNNs) and the visual ventral stream up to the inferotemporal (IT) cortex in the primate. However, whether such similarity holds for the face-selective areas, a subsystem of IT, is not clear. To address this question, we extensively investigate whether CNNs show facial tuning properties previously reported by four experimental studies on different macaque face areas. More specifically, while simulating the four experiments on a variety of CNN models optimized for classification, we attempted to make a correspondence between the model layers and the macaque face areas by quantitatively matching the tuning properties. As a result, we found that higher model layers explained well all properties of anterior areas, while no layer simultaneously explained multiple properties of middle areas. This observation was consistent across the different model instances with varied architecture and dataset settings. Thus, our results indicate that, although the near-goal representation of face-classifying CNNs has some similarity with the primate face processing system, the intermediate computational process might be rather different, thus calling for a more comprehensive model for better understanding of this system.

Introduction

Recently, the neuroscience community has witnessed the rise of the deep convolution neural network (CNN) (LeCun et al., 2015), a family of feedforward artificial neural

networks, in computational modeling of the primate visual system. CNN models trained for behavioral goals have exhibited a remarkable similarity to ventral visual areas in terms of stimulus-response relationship despite that the network itself was not directly optimized to fit neural data. For example, CNN models optimized for image classification were highly predictive of single-site and population-level neural responses in the inferotemporal (IT) cortex (Cadieu et al., 2014; Yamins et al., 2014). In some studies, parallels along the hierarchy have been discovered between layers of a CNN model and the intermediate (Khaligh-Razavi and Kriegeskorte, 2014; Yamins et al., 2014; Güçlü and van Gerven, 2015) or lower visual areas (Cadena et al., 2019); analogous parallels have been observed also in an fMRI study (Horikawa and Kamitani, 2017). Such predictive CNN model has further been used to generate "optimal" stimuli to validate the model (Bashivan et al., 2019). A natural question arises here: if CNN explains overall responses in IT, then does it also explain responses in a subsystem of IT?

Among various subsystems of IT (Downing et al., 2005; Lafer-Sousa and Conway, 2013; Sato et al., 2013), the most well-studied is the macaque face-processing system (Tsao et al., 2003; 2006). The subsystem forms a network consisting of multiple face-selective patches with anatomically tight inter-connections (Moeller et al., 2008). The network putatively has a functional hierarchy from the middle to the anterior patch areas with a progressive increase of selectivity to facial identities and invariance in viewing angles (Freiwald and Tsao, 2010). For each patch area, a number of tuning properties to specific facial features have been reported in a clear and detailed manner (Freiwald et al., 2009; Freiwald and Tsao, 2010; Ohayon et al., 2012; Chang and Tsao, 2017). Given these experimental facts, the macaque face processing system emerges as an ideal testbed to examine our question regarding the generality of CNN as a model of higher visual processing. However, previous studies have only touched on this direction in restricted cases involving one experiment, one face-processing patch, or one CNN model (Chang and Tsao, 2017; Yildirim et al., 2018).

Thus, in this study, we have undertaken a more thorough investigation on whether CNN explains previously reported tuning properties of face neurons in macaque IT (Figure 1). More specifically, we explored a variety of CNN models that were trained for classification with different architecture and dataset settings. We incorporated four major physiological experiments that had been conducted on the middle lateral (ML), anterior lateral (AL), and

anterior medial (AM) patches: (1) view-identity tuning (Freiwald and Tsao, 2010), (2) shape-appearance tuning (Chang and Tsao, 2017), (3) facial geometry tuning (Freiwald et al., 2009), and (4) contrast polarity tuning (Ohayon et al., 2012). While simulating these experiments on each model, we attempted to make a correspondence between the model layers and the macaque face patches by matching the population-level tuning properties. As presented below, we discovered that higher layers tended to explain well all known properties of anterior patches, while no layer explained multiple properties of middle patches at the same time. This observation was largely consistent across the explored CNN models. Thus, although the near-goal representation in face processing might be similar between CNN and macaque, the intermediate computational process might be rather different, thus calling for a more comprehensive model to understand the computation in the primate face processing system.

Figure 1: Schema of our investigation to compare the macaque face-processing network and a CNN model. We simulate previous four experiments (left image sets; top left face was obscured due to bioRxiv policy on the inclusion of human faces/identifiable information within research manuscripts) on a CNN model (bottom middle) to identify tuning properties (bottom right). We quantitatively compare the tuning properties between each macaque face patch (from the past experiment) and each CNN layer (from the present simulation) to find out their correspondence.

Results

To investigate whether CNN can explain known tuning properties of the macaque face-processing network, we started with a representative CNN model optimized for classification of face images. Our model adopted an architecture similar to AlexNet (Krizhevsky et al., 2012), following recent studies relating CNNs with the ventral stream

(Cadieu et al., 2014; Khaligh-Razavi and Kriegeskorte, 2014; Horikawa and Kamitani, 2017). The AlexNet architecture had seven layers in total. The first five layers were called 'convolutional' and performed multi-channeled local linear filters that were replicated across the visual field. Repetition of such layers progressively increased the size of visual receptive fields, mimicking the general structure of the visual cortex. Then, two layers followed, which were called 'fully connected' and covered the entire visual field. (The network ended with a special layer representing the class, which is ignored throughout our analysis here.) We trained our CNN model on a large number of natural face images for classifying facial identities (using the VGG-Face dataset; see Methods). From here on, we refer to this network as 'AlexNet-Face.'

For our AlexNet-Face model thus constructed, we first identified a population of face-selective units in each layer (Methods); we call face-selective population simply 'population' and face-selective unit simply 'unit' from here on. We then proceeded to simulation of previous four monkey experiments (Freiwald et al., 2009; Freiwald and Tsao, 2010; Ohayon et al., 2012; Chang and Tsao, 2017) on our model to see how each model layer corresponded to each macaque face-processing patch (Figure 1).

View-Identity Tuning

In the first study that we consider (Freiwald and Tsao, 2010), it has been reported that different macaque face patch areas (ML, AL, and AM) have different joint tuning properties to the facial view and identity. Accordingly, we incorporated the same set of face images as used experimentally, which consisted of 25 identities and 8 views (frontal, left and right half-profiles, left and right profiles, up, down, and back). For each layer of our CNN model, we first recorded the responses of all model units to those images. We then calculated the correlation between the population responses to each pair of face images and constructed a population response similarity matrix (RSM) of such correlations (Methods). Figure 2 shows RSMs for layers 1, 3, 5, and 7, where the face numbers are grouped according to the view (forming sub-matrices of size 25×25) and sorted by identity in the same way within each group. (For succinctness, we present, here and hereafter, comparison results only for the odd-numbered layers since the remaining layers generally give more or less interpolated results of the presented layers.) In the intermediate layers (layers 3 to 5), the RSMs had strong block-diagonal patterns, which indicated that most units had selectivity to a specific

view, similarly to ML (Freiwald and Tsao, 2010). In the top layer (layer 7), such block-diagonal structure disappeared, but para-diagonal lines instead became prominent, which indicated that most units had selectivity to facial identity with some degree of view invariance, similarly to AM (Freiwald and Tsao, 2010). In addition, a mirror-symmetric pattern in view can be seen from layers 3 to 7, somewhat similarly to AL (Freiwald and Tsao, 2010), though high correlations were observed only between the left and right profile views, not the half-profile views. In sum, the intermediate-to-top layers gradually shifted from view-specific to view-invariant and identity-selective, which is reasonably consistent with the idea of functional hierarchy in the macaque face patches (Freiwald and Tsao, 2010).

Figure 2. View-identity tuning. Each plot shows the population response similarity matrix for each layer. The pixel values of the matrix indicate the pairwise correlation coefficients (legend) for the population responses to face images. The elements of the matrix are grouped according to the view (indicated by the images along the axes; images were obscured due to bioRxiv policy) with the same order of identities in each group.

The same experimental study has also reported invariance property in stimulus size (Freiwald and Tsao, 2010). To examine such property in our model, we recorded the model unit responses to a set of face and non-face object images of various sizes (illustrated in Figure 3A). We then calculated, for each layer, the average response, $\bar{R}_{\text{face}}^{\text{size}}$ or $\bar{R}_{\text{object}}^{\text{size}}$, across the population and the stimulus set, separately for face or object images and for each image size. We quantified the degree of invariance by size-invariance index (SII), which is defined as the minimal fraction of image sizes at which the average population response to faces is reasonably larger than the one to objects ($\bar{R}_{\text{face}}^{\text{size}} > 1.4\bar{R}_{\text{object}}^{\text{size}}$); thus, a lower SI-index indicates a stronger size invariance (Methods). Not surprisingly, size invariance in our CNN model strengthened along with its depth (Figure 3B). In particular, the top layer (layer 7)

had the strongest size invariance (SII equal to 1/4), where the average population response to faces (red) was always larger than the one to objects (blue) for all tested sizes. In comparison to the macaque, the top layer quantitatively came closest, of all layers, to the face patches (ML/AL/AM), which all give SII around 1/8 (Freiwald and Tsao, 2010). (The experimental study also investigated position invariance, but we did not incorporate this since position-shifted images extruded the image frame in our setting.)

Figure 3: Size invariance. (A) Examples of face (faces were obscured due to bioRxiv policy) and non-face object stimuli of various sizes (the numbers beneath). (B) The average responses to the face images (red) and to the object images (blue) for each image size (x-axis) in each model layer. The 'bline' stands for the average baseline response to the blank image.

Shape-Appearance Tuning

In the second experimental study (Chang and Tsao, 2017), coding of facial shapes and appearances in the macaque face patch areas (ML and AM) has been investigated. Similarly to their experimental method, we constructed a face space based on the active appearance model (Cootes and Edwards, 2001). The face space was described by 50-dimensional feature vectors, consisting of 25 shape and 25 appearance dimensions, defined as follows. Using a set of natural frontal face images with coordinates annotated on pre-defined facial landmarks, the shape dimensions are the first 25 principal components (PC) of the landmark coordinates and the appearance dimensions are the first 25 PCs of the original face images

that were morphed so that the landmarks matched to their mean coordinates (Methods). Figure 4A illustrates the first shape and first appearance dimensions by showing how varying these dimensions changes the image. We then randomly sampled a set of face images from this space and used this set for all the subsequent analyses.

Shape-appearance preference. Following the experimental study (Chang and Tsao, 2017), we examined whether and how much each model unit preferred shape or appearance. For this, we first recorded the responses to the face images and estimated the 50-dimensional vector of spike-triggered average (STA), that is, the average of feature vectors of the face images weighted by the responses. We then computed the shape preference index (SPI), $(S - A)/(S + A)$, where S is the vector length of the shape dimensions and A is the vector length of the appearance dimensions of the STA; a unit is considered to prefer shape when SPI is positive and prefer appearance when SPI is negative (Methods). Figure 4B shows the distribution of SPIs for each layer (blue). In the intermediate-to-higher layers (layers 5 to 7), most units had appearance preference, with a similar distribution to the corresponding experimental data on AM (pink). However, the lower layers (layers 1 to 3) broadly mixed both shape-preferring and appearance-preferring units, thus not particularly similar to either AM (pink) or ML (gray). We also examined shape-appearance preference by counting the number of significantly tuned units to each feature dimension; the tendency was similar (Figure S1A).

Decoding performance. Following the experimental study (Chang and Tsao, 2017), we investigated how much information each layer contained on the face space. For this, we first decoded feature vectors from the population responses to each face image by linear regression with leave-one-out. We then measured the performance of the decoding by the ratio of explained variance in the actual feature values by the predicted feature values for each feature dimension (Figure 4C, blue). The results for the top layer (layer 7) had a good match with the data from AM (red). However, all lower-top-intermediate layers (layers 1 to 5) gave results far from both AM (red) and ML (gray). In particular, no layer showed higher performance for shape dimensions and lower performance for appearance dimensions like ML (opposite to AM). We also measured the decoding performance in terms of accuracy of nearest-neighbor classification in the feature space; we observed a similar tendency (Figure S1B). Thus, in contrast to the comparison regarding the view-identity tuning experiment

(Freiwald and Tsao, 2010), the results here reveal the lacking of ML-like properties in the CNN model.

It is somewhat unintuitive, in Figure 4C, that lower layers yielded higher decoding performance despite the fact that they would have less face-related representations. In addition, we also found that, in all layers, most units showed ramp-shaped tuning curves along the STA and flat tuning curves along orthogonal axes to the STA (Figure S2), like in both ML and AM (Chang and Tsao, 2017). We continue to discuss these points in Discussions.

Figure 4: Shape-appearance preference. (A) Illustration of the first shape and first appearance dimensions for frontal faces. The images correspond to the feature vectors with all zero except the indicated dimension is set to -3, 0, or 3. (B) The distribution of shape-preference indices for each model layer (blue), in comparison to the corresponding distributions for ML (gray) and AM (pink) replotted from Figure 1F of the experimental study (Chang and Tsao, 2017). (C) Decoding performance measured by the ratio of explained variance in the actual feature values by the decoded feature values for each feature

dimension. Each plot compares the results from a model layer (blue) with those from AM (pink) and ML (gray), replotted from Figure 2C of the experimental study (Chang and Tsao, 2017).

View tolerance. The same experimental study also investigated view tolerance in the face space representation in patch AM (Chang and Tsao, 2017). Accordingly, we first constructed the feature representation for profile faces in a way compatible with frontal faces. Namely, we built another shape-appearance face space from left profile face images, similarly to frontal faces, and established a mapping between the frontal and profile face spaces via linear regression; we hereafter always used feature vectors for profile faces that were mapped to the front face space, which allowed us to use the same feature vectors for both views of the same identity (Methods). Figure 5A illustrates the first shape and appearance dimensions for profile faces; note the compatibility of the shown profile images with the frontal faces in Figure 4A. For each unit, we estimated the STA from profile faces, similarly to frontal faces, and calculated the correlation between the frontal and the profile STAs at each feature dimension across all units in each layer (Figure 5B, red and blue). We can see that, from lower to higher layers, the STA correlations of the first half of the appearance dimensions (blue) increased, which indicated a gradual progression of view tolerance along with the depth. In particular, the correlations in the top layer (layer 7) came closest, of all layers, to the corresponding data on AM (black). Note that this result is compatible with the view-identity tuning in the top layer shown in Figure 2. We also conducted a decoding analysis using a mixed set of frontal and profile faces; only in the top layer, decoding performance was similar between both views (Figure S3), consistently with AM (Chang and Tsao, 2017).

To gain further insight, we repeated the above analysis for all available 10 non-frontal views including right profile and half-profile views. The result for a left half-profile view (Figure 5C) shows a similar tendency to the full left profile, but the overall STA correlations were slightly higher, indicating stronger tolerance for the half-profile view than the profile view. This result is again consistent with Figure 2, where a closer look at the RSM of layer 7 reveals that the correlations between the half-profile and frontal views are slightly stronger than those between the profile and frontal views. This property likely arose from our training image set that included less images in profile views than half-profile views. Finally,

Figure 5D plots the mean STA correlation between the frontal and the non-frontal STAs (averaged over the feature dimensions) for each non-frontal view and for each layer. The mean STA correlation increased, thus view-tolerance became stronger, in a higher layer and in a view closer to the frontal view.

Figure 5: View tolerance. (A) Illustration of the first shape and first appearance dimensions for profile faces. The images correspond to the feature vectors with all zero except the indicated dimension is set to -3, 0, or 3. (B) The correlation between the frontal and the profile STAs across units for each dimension (x-axis; 1–25: shape, 26–50: appearance). Each plot compares the result from a model layer (red and blue) and AM (black) replotted from Figure 6D of the experimental study (Chang and Tsao, 2017). The shaded region indicates the 99% confidence interval of randomly shuffled data from the model. (C) Analogous result for the left half-profile view. (D) The mean STA correlation (averaged over the feature

dimensions) for each non-frontal view (x-axis) against frontal view, for each layer (color; see legend).

Facial Geometry Tuning

In the third experimental study (Freiwald et al., 2009), tuning of ML neurons to local and global features in cartoon face stimuli has been documented. Thus, we incorporated their stimulus design of cartoon face images, which were parametrized by 19 different facial features, each ranging from -5 to $+5$ with ±5 corresponding to the extreme features and 0 corresponding to the mean features (Figure 6A). We randomly generated a set of cartoon face images. From the responses of each unit to those cartoon face images, we estimated a tuning curve for each feature parameter and determined its statistical significance (Methods).

Figure 6B (blue) shows how many features each unit was significantly tuned to (features-per-unit) in each model layer. Analogously, Figure 6C (blue) shows how many units in each layer were significantly tuned to each feature (units-per-feature). In both plots, the intermediate-to-top layers (layers 5 to 7) showed very different distributions from ML (gray), accommodating more units tuned to larger numbers of features and to more remaining features absent in ML. Curiously, the lower layers (layers 1 to 3) gave results somewhat closer to ML: most units were tuned to a small number of features, which were mostly geometrically larger features (i.e., face aspect ratio, face direction, feature assembly height, and inter-eye distance) rather than smaller features (related to mouth and nose). In addition, we observed that, in all layers, the units had tuning curves mostly ramp-shaped with peaks and troughs mostly at the extreme values (Figure S4), similarly to ML (Freiwald et al., 2009). We come back to these points in Discussions.

Figure 6: Facial geometry tuning. (A) Examples of cartoon face images varying a feature parameter (inter-eye distance in this case). (B) The distribution of the number of features that each unit is significantly tuned to. (C) The distribution of the number of units significantly tuned to each feature. Each plot compares the result from a model layer (blue) with ML (gray) replotted from Figure 3 of the experimental study (Freiwald et al., 2009).

Contrast Polarity Tuning

The last experimental study (Ohayon et al., 2012) has reported that ML units had preference for contrast polarities between face parts in mosaic-like cartoon face stimuli (Ohayon et al., 2012). Thus, we again used their stimulus design of cartoon face images, which consisted of 11 distinct face parts that were each assigned a unique intensity value varying from dark to light (Figure 7A). We randomly generated a set of mosaic-like cartoon faces and analyzed the responses of each unit to identify its contrast polarity tuning. That is, for each pair of face parts, A and B, out of 55 pairs in total, we determined whether the unit prefers part A

lighter than part B (part A > part B) or the opposite (part A < part B); see Methods. As summarized in Figure 7B (blue), in all layers, most of the units had preferences for contrast polarities mainly related to the forehead, the largest geometrical area in the mosaic face. This result is inconsistent with the experimental finding in ML (gray), where most neurons were tuned to eye- or nose-related contrast polarities and the polarity directions were consistent across the neurons.

Figure 7: Contrast polarity tuning. (A) Examples of mosaic-like cartoon face images with various intensity assignment to each face part. The first three have a larger intensity on the forehead than the left eye; the last three have the opposite. (B) The distribution of contrast polarity preferences in each model layer (blue and red) in comparison to ML (gray) replotted from Figure 3A of the experimental study (Ohayon et al., 2012). In each plot, the upper half gives the positive polarities, i.e., the units that significantly preferred part A compared to

part B, while the lower half gives the negative polarities, i.e., the number of units that significantly preferred part A compared to part B. The binary table at the bottom indicate the 55 part-pairs; for each pair, the upper black block denotes A and the lower block denotes B.

Summary of Correspondence

To see more clearly which model layer corresponds to each macaque face patch, we next quantify the similarities of tuning properties; Figure 8 summarizes the results for our AlexNet-Face model. For each tuning property, we use a different metric to quantify similarity between the results from the model and the experiment. For view-identity tuning (Figure 8A), we use the correlation between the response similarity matrices from each layer (Figure 2) and each face patch (Freiwald and Tsao, 2010). For size invariance (Figure 8B), we compare the size invariance indices obtained from each layer (Figure 3B) and each face patch (Freiwald and Tsao, 2010). For shape-appearance preference (Figure 8C) or view tolerance (Figure 8D), we compare the averages of shape-preference indices (Figure 4B) or mean STA-correlations (Figure 5B) from each layer and the corresponding experimental data (Chang and Tsao, 2017). For facial geometry tuning (Figure 8E) and contrast polarity tuning (Figure 8F), we use the cosine similarity between the distributions from each layer (Figure 6 and Figure 7, respectively) and each face patch (Freiwald et al., 2009; Ohayon et al., 2012).

Comparing between layers, AM data favor higher model layers consistently across different tuning properties (Figure 8A–D). However, ML data favor different layers depending on each tuning property: intermediate layers in view-identity tuning (Figure 8A), higher layers in size invariance (Figure 8B), and lower layers in other tunings (Figure 8C, E–F). Comparing between face patches, higher model layers also generally favor AM (Figure 8A, C). However, intermediate layers are somewhat inclined to ML in view-identity tuning (Figure 8A) but to AM in shape-appearance preference (Figure 8C). In sum, AM clearly has the best match with higher layers, while ML has no such clear correspondence since no layer is simultaneously compatible with all the investigated experimental data on ML.

Model variation

How much robust are the results so far against the training condition? To address this question, we investigated various model instances while varying the architecture and the dataset.

First, we examined three publicly available pre-trained networks: (1) VGG-Face network (Parkhi et al., 2015), a very deep 16-layer CNN model trained on face images, (2) AlexNet (Krizhevsky et al., 2012), trained on general natural images, and (3) Oxford-102 network, an AlexNet-type model trained on flower images (Methods). Figure 9 summarizes the layer-patch comparisons for all three models (shown in different line styles), overlaid with the plots for AlexNet-Face already given in Figure 8. Generally, the results for all four models are similar: AM data tend to match with higher layers, while ML data do not match with any particular layer simultaneously for all the tuning properties. It is rather surprising that consistency can be found even in the cases of non-face training images like flowers, though the tendency is overall weaker, in particular, view tolerance in Figure 9D. The weaker size invariance in VGG-Face model is probably because it was trained without data augmentation for size variation, unlike our AlexNet-Face model.

Second, to further explore the architecture space, we modified the AlexNet architecture to construct six additional networks, where four had five, six, eight, or nine layers and two changed the number of convolution filters in every layer to either half or double (Table S1). We trained each model on the same face image dataset (Methods). Figure 10 summarizes the results from these six models in addition to AlexNet-Face, where the layer numbers are normalized. Again, the general tendency is similar across the architectures: AM corresponds to higher layers but ML has no corresponding layer. The weak view tolerance for the model with five layers or with half numbers of filters (Figure 10D) is probably because the depth or the filter variety was not sufficient for gaining strong invariance.

Figure 8. Summary of comparison between layers of AlexNet-Face and face-patches. (A) The correlation between the response similarity matrices from each layer (Figure 2) and each face patch (AM/AL/ML) in Figure 4D–F of the corresponding experimental study (Freiwald and Tsao, 2010). (B) The size invariance index for each layer (Figure 3B) and for face patches (equal for AM/AL/ML) from Figure S10C of the corresponding experimental study (Freiwald and Tsao, 2010). (C) The mean shape-preference index for each layer (Figure 4B) with the mean indices for AM and ML from Figure 1F of the corresponding experimental study (Chang and Tsao, 2017). (D) The mean STA correlation for each layer (Figure 5B) and AM from Figure 6D of the corresponding experimental study (Chang and Tsao, 2017). (E) The cosine similarity between the distributions of the number of tuned units per feature or the number of tuned features per unit from each layer (Figure 6) and ML from Figure 3 of the corresponding experimental study (Freiwald et al., 2009). (F) The cosine similarity between the distributions of contrast polarity preferences from each layer (Figure 7B) and ML from Figure 3A of the corresponding experimental study (Ohayon et al., 2012).

Figure 9. Summary of layer-patch comparisons for pre-trained networks in addition to AlexNet-Face (in different line styles; see the legend at the bottom). The format of each plot is analogous to Figure 8. In the view-identity tuning plot (A), we omit comparison with AL data for visibility. In the size invariance plot (B), we slightly shift each curve vertically for visibility. Since VGG-Face model was too large to fully analyze, we show results from five chosen intermediate-to-top layers.

Figure 10. Summary of layer-patch comparisons for different architectures changing the depth or the number of convolution filters, indicated by different colors or line styles; AF-5 to 9 varied the depth; AF-h halved and AF-d doubled the number of filters in each layer; see the legend at the bottom. The format of each plot is similar to Figure 8, except that x-axis shows the normalized depth (0 corresponds to the lowest layer and 1 to the highest layer).

Discussions

In this study, we have investigated whether CNN can serve as a model of the macaque face-processing network. While simulating four previous physiological experiments (Freiwald et al., 2009; Freiwald and Tsao, 2010; Ohayon et al., 2012; Chang and Tsao, 2017) on a variety of CNNs trained for classification, we examined whether the results quantitatively match between each model layer and each face patch. We found that higher model layers tended to explain well properties of the anterior patch, while none of the layers simultaneously captured those of the middle patch. This observation was largely consistent across the different model instances. Thus, despite the prevailing view linking CNNs and IT, our results indicate that the intermediate computational process in the macaque face processing system might be rather different from CNN and therefore requires a more refined model to clarify the underlying computational principle.

Some previous studies have addressed a similar question but in a smaller scale. In one study (Yildirim et al., 2018), the authors tested view-identity tuning on a CNN model in comparison to physiology (Freiwald and Tsao, 2010) and gave a similar result to ours (Figure 2). However, they considered no other physiological experiment. In another study (Chang and Tsao, 2017), the authors trained a smallish face-classifying CNN model and tested shape-appearance tuning. They showed that the top layer exhibited appearance preference and ramp-flat tuning consistent with their experimental result on AM (Chang and Tsao, 2017) and with our results (Figure 4B and Figure S2, layer 7). However, they did not consider any other part of the same experiment (decoding performance and view tolerance) or any other layer than the top, or any comparison with ML, not to say about different experiments or model instances. Thus, the comparisons undertaken in our study here are far more thorough and extensive than those previous studies.

What insight did we gain from our results? First, later stages in both CNNs and the macaque face-processing system have similarity in terms of strong invariance properties in size and view (Figure 2, Figure 3B, and Figure 5B). Although invariance properties in CNN are generally well-known, such fine-grained similarity to physiology in the view-tolerant appearance code would be somewhat beyond expectation (Figure 5B). Second, later stages in both systems are also similar in terms of dominant appearance representation (Figure 4).

However, shape representation, in contrast, is dominant in intermediate stages in macaque but conspicuously lacking in intermediate-to-higher stages in CNN (Figure 4 and Figure 6). This may be because shapes turn out to be relatively unimportant features for classification and thus neglected during the model training (Baker et al., 2018). This implies that the goal of the face-processing system may not be merely classification. On the other hand, we have found several somewhat unintuitive results in lower layers: (1) facial shape tuning (Figure 4B and Figure 6), (2) higher decoding performance than higher layers (Figure 4C), and (3) ramp-shape tuning along STA axis and flat tuning along the orthogonal axis (Figure S2 and Figure S4). We speculate that these are partly because lower-layer units, although simple, localized feature detectors (e.g., Gabor filters), can in fact easily interact with stimulus parameters controlling shape feature dimensions or local facial geometry. In addition, lower layers have much weaker nonlinearity so that linear decoding would become easier. Nonetheless, we consider that such low-level units should not be qualified as face-selective from the first place, but might have been misjudged so by the standard criterion due to the specific image statistics of face images (e.g., emphasis on eyes); future studies might therefore need to consider revision of the criterion itself.

In general, relationship between artificial and biological neural networks has been a recurring question. Since the brain has a number of sub-networks with a hierarchical structure, it is tempting to hypothesize that such sub-network is optimized for some behavioral goal. Indeed, in a classical study (Zipser and Andersen, 1988), it has been shown that a neural network trained for a coordinate transformation task exhibits, in the intermediate layer, properties related to spatial location similar to primate parietal area 7a. More recently, as already discussed in the introduction, numerous studies have argued that CNNs trained for image classification have layers similar to higher (Cadieu et al., 2014; Khaligh-Razavi and Kriegeskorte, 2014; Yamins et al., 2014; Horikawa and Kamitani, 2017), intermediate (Khaligh-Razavi and Kriegeskorte, 2014; Yamins et al., 2014; Güçlü and van Gerven, 2015), or lower (Cadena et al., 2019) areas in the monkey or human visual ventral stream. Analogously, some studies have discovered layer-wise correspondence between CNNs trained for audio classification and the human auditory cortex (Kell et al., 2018) or the monkey peripheral auditory network (Koumura et al., 2019). Note that all these studies have offered positive answers to the correspondence question, which stresses the

generality of explanatory capabilities of goal-optimized neural networks. However, the same story might not go all the way through. For the macaque face-processing network, our study here could not find a CNN layer corresponding to the intermediate stage (ML). In addition, some recent studies have pointed out potential representational discrepancies between CNN and the ventral stream from behavioral consideration (Baker et al., 2018; Groen et al., 2018; O'Toole et al., 2018; Rajalingham et al., 2018). (See also the related discussion on the 'computational gap' below.)

One should note that there are, in general, two fundamentally different approaches for comparing a model with the neural system. In one approach, which is more traditional and taken in our study here, a given model is tested whether it exhibits tuning properties compatible with prior experimental observations ('tuning approach'). In the other approach, which is recently more popular (Cadieu et al., 2014; Yamins et al., 2014; Kell et al., 2018), a given model is used as a basis function and a linear regression fitting is conducted from model responses to actual neural responses for predicting new neural responses ('prediction approach'). In the tuning approach, although the comparison is arguably more direct in the sense of involving no fitting, tuning experiments have often been criticized for biased and subjective stimulus design and for use of degenerate summary statistics. Therefore showing consistency with experimentally observed tuning may not be sufficiently supportive evidence for the model. Note that, nevertheless, showing clear inconsistency is strongly falsifying evidence, from the logical contraposition of 'if the model behaves similarly to the neural system, then it should reproduce the tuning.' Our comparison with ML is one such example. In the prediction approach, on the other hand, since a model can be tested with an arbitrary (randomly selected) set of stimulus, the aforementioned criticism would not occur. However, because of the necessity of linear fitting, the comparison becomes somewhat more indirect: the correspondence is made between an actual neuron and a 'synthetic neuron,' i.e., the output of a linear model after fitting (Cadieu et al., 2014; Khaligh-Razavi and Kriegeskorte, 2014; Yamins et al., 2014; Eickenberg et al., 2017). Indeed, one example of computational gap between CNN and IT neural responses has been raised in Fig. 7 of the study by Cadieu et al. (Cadieu et al., 2014), where the population similarity matrices from IT and the CNN top layer were strikingly different without fitting, although very similar with fitting; one might therefore argue that it is a CNN

plus a linear regression, not a CNN itself, that has predicted neural responses. However, neither of the two approaches, tuning or prediction, seems to be better than the other. Rather, both are looking at different aspects of the visual representations and therefore should probably continue to be used for further deepening our understanding.

If CNN does not fully explain all the facial tuning properties, then what are other possible models? Some hints can be found in prior theoretical studies. First, unsupervised learning can give rise to feature representations from the statistics of input images. Although such theory has more traditionally been used for early vision (Olshausen and Field, 1996; Hyvärinen and Hoyer, 2001; Schwartz and Simoncelli, 2001; Hosoya and Hyvärinen, 2015), recent studies have reported its possible contributions in facial tuning properties. For example, sparse coding of facial images can produce facial-part-like feature representations and explain the facial geometry tuning in ML (Hosoya and Hyvärinen, 2017); PCA-based learning can produce global facial feature representations and explain mirror-symmetric tuning like in AL (Leibo et al., 2017). Second, feedback processing is ubiquitous in the visual system and therefore likely important, but crucially missing in CNN. One standard theoretical approach to incorporating feedbacks is to use a generative model. Such theory has also been typical for modeling early vision (Olshausen and Field, 1997; Rao and Ballard, 1999; Hosoya, 2012), some recent studies have raised potential importance in higher vision. For example, a particular generative model, called mixture of sparse coding models, has been employed to represent an organization of multiple modules of model units with competitive interaction (Hosoya and Hyvärinen, 2017), which has endowed the units with a global face detection capability similar to the neural face selectivity. In a completely different approach, an inverse-graphics-based generative model has been investigated, where a feedforward network employed to infer facial parameters has exhibited view-identity tuning properties similar to ML, AL, and AM in different layers (Yildirim et al., 2018). Third, although invariance properties can emerge from supervised learning as in CNN, other approaches exist. Some theories have used spatial image statistics to explain position or phase invariance in early vision (Hyvärinen and Hoyer, 2001; Karklin and Lewicki, 2008; Hosoya and Hyvärinen, 2016). However, for explaining more complex invariance properties in higher vision, the temporal coherence principle (Földiák, 1991), which learns the most slowly changing features, has been more commonly used (Einhäuser et al., 2005; Farzmahdi

et al., 2016; Leibo et al., 2017) and experimentally tested (Cox et al., 2005). Lastly, although combining invariance learning into a generative model is theoretically not so obvious, one recent development has achieved it (Hosoya, 2019). In sum, for clarifying the computational principle underlying the primate face-processing system, it seems crucial to view this system as not merely a classifier but having a richer repertoire of visual processing. We hope that investigation in this direction, together with the results in the present work, will eventually guide us to better understanding of general visual object processing.

Methods

Convolutional Neural Network (CNN)

CNN is a family of feedforward, multi-layered computational models (LeCun et al., 1998), which has originally been inspired by the mammalian visual system. CNN allows for a variety of architecture design, stacking an arbitrary number of layers with different structural parameters. Each layer in CNN undergoes several operations. The layer typically starts with convolutional filtering, which applies an identical multi-channel linear filter to every local subregion throughout the visual field. Then, the results are given to a nonlinear function, $\mathrm{ReLU}(x) = \max(0, x)$, at each dimension, for ensuring non-negative outputs. The layer is optionally preceded by pooling and normalization. Pooling gathers the incoming inputs within a local spatial region by taking the maximum. Normalization normalizes the outputs by dividing the incoming inputs by their squared norm. Generally, a CNN architecture consists of multiple such layers, by which it progressively increases the effective receptive field sizes and eventually achieves a non-linear transform of the input from the whole image space to a space of interest (i.e., class). Often, the last several layers of a CNN architecture have convolutional filters covering the entire visual field, thus called fully-connected layers.

Each layer operation is closely related to some neural computation discovered in neurophysiology. Convolutional filtering mimics V1 simple cells, which replicate their receptive field structures across the visual field (Hubel and Wiesel, 1962). The nonlinear function proxies for neural thresholding giving rise to non-negative values of firing rates. Pooling comes from the classical notion that V1 complex cells gather the outputs from V1

simple cells to achieve position or phase invariance (Hubel and Wiesel, 1962; Alonso and Martinez, 1998). Normalization stems from a gain-controlling phenomenon that is widely observed in the cortex and often explained by the well-known divisive normalization theory (Heeger, 1992). Further, the repetition of layers of similar processes is inspired by the hierarchy of the visual cortex, for which the gradual increase of receptive field sizes and the congruent micro-circuit structures are well known (Felleman and Van Essen, 1991). To dive deep in CNN, see introductory materials (Goodfellow et al., 2016; Rawat and Wang, 2017).

Trained CNN Models

We show, most in detail, the results from a representative CNN model called 'AlexNet-Face.' This CNN model has the same architecture as AlexNet (Krizhevsky et al., 2012) with five convolutional layers followed by two fully connected layers. (The network ends with a special layer for representing classes, but we ignore it in our analysis.) The architecture parameters are given in Table S1. We trained it for the classification task using the VGG-Face dataset (Parkhi et al., 2015), which contains millions of face images of 2622 identities. We augmented the dataset with size variation, allowing four-times downsizing. We performed the training by minimizing the cross-entropy loss function, a commonly used probabilistic approach to measure the error between the computed and given outputs (Goodfellow et al., 2016); we used the stochastic gradient descent method with momentum (SGDM) as optimizer. The resulting CNN model gave classification accuracy 72.78% for held-out test data. (This score is somewhat lower than state-of-art face recognizing deep nets, which typically go over 90% of accuracy. This is likely because our size-varied data augmentation yielded very small images that would be difficult to classify, e.g., Figure 3A).

To test robustness of our results against structural change to the model, we incorporated a set of six additional model instances modifying the architecture of AlexNet. Four of them changed the number of layers to five, six, eight, and nine.   We designed the specific architectures for these by changing only the convolutional layers, keeping the overall structure of increasing receptive field sizes. The remaining two models changed the number of filters in every layer, one halved and one doubled. The architecture parameters of the additional models as well as their classification accuracies are given in Table S1.

For all implementation, we used Matlab with Deep Learning Toolbox (https://www.mathworks.com/products/deep-learning.html) as well as Gramm plotting tool (Morel, 2018) for visualization.

Pre-trained CNN Models

To further test robustness, we included three publicly available pre-trained CNN models using very different architecture or dataset, namely, VGG-Face network (Parkhi et al., 2015), AlexNet (Krizhevsky et al., 2012), and Oxford-102 network. The VGG-Face network is a very deep 16-layer CNN model that has been trained on VGG-Face database for face classification (with no data augmentation for size variation). AlexNet is the original network trained on ImageNet database (Deng et al., 2010) for natural image classification. Oxford102 is an AlexNet network that has been 'fine-tuned' for the classification of flower images in Oxford-102 dataset (Nilsback and Zisserman, 2008). We imported these three network models from a public repository (https://github.com/BVLC/caffe/wiki/Model-Zoo).

Experiments

On each CNN model, we first identified face-selective units and then proceeded to simulation of four macaque experiments on these face-selective units. The specific procedures are summarized as follows.

Face-Selective Population Estimation

We determined the face-selectivity of a unit by following the general approach used in experiments on IT (Freiwald et al., 2009; Freiwald and Tsao, 2010). That is, we first recorded the responses of the unit to a set of 50 natural frontal faces from the FEI image database (http://fei.edu.br/~cet/facedatabase.html) and to a set of 50 non-face object images obtained from the Web. Then, from the average responses to the faces, $\overline{R}_{\text{face}}$, and non-face object images, $\overline{R}_{\text{object}}$, above the baseline response to the blank image (all zero pixel-values), we estimated the Face Selective Index, $\text{FSI} = \left(\overline{R}_{\text{face}} - \overline{R}_{\text{object}} \right)/\left(\overline{R}_{\text{face}} + \overline{R}_{\text{object}} \right)$. FSI was set to 1 when $\overline{R}_{\text{face}} > 0$ and $\overline{R}_{\text{object}} < 0$, and to -1 when $\overline{R}_{\text{face}} < 0$ and $\overline{R}_{\text{object}} > 0$. We judged a unit as face-selective if $\text{FSI} > \frac{1}{3}$, that is, the unit responded to face images, on average, twice as strongly as to non-face object images. (Zero FSI, for instance, implies an equal average response to face and non-face images.) For the simulation of shape-

appearance tuning experiment described below, we used profile faces in addition to frontal faces for selectivity determination. Below, 'unit' or 'population' always refer to the face-selective ones.

View-Identity Tuning Experiment

To simulate the experiment on view-identity tuning (Freiwald and Tsao, 2010), we used the same set of 'face-view' (FV) images as in the experimental study, which consisted of 200 images of 25 identities and 8 views (left full profile, left half profile, straight, right half profile, right full profile, up, down, and back; see the images along the axes in Figure 2). To determine the view-identity tuning, we first recorded the responses of the units to these images and calculated the correlation between the population responses to each pair of FV images; we then constructed a population response similarity matrix (RSM) from those values. The authors of the experiment provided us the FV image set and the RSMs obtained from the experiment (except that the data corresponding to the back view was missing).

Size-Invariance Experiment

To simulate the experiment on size invariance (Freiwald and Tsao, 2010), we took frontal as well as right and left profile face images of 8 individuals (24 face images in total) from FEI face database, and 16 non-face object images obtained from the Web. We then resized these images from the original size 224×224 pixels down to 196×196, 168×168, 140×140, 112×112, 84×84, and 56×56 pixels (see Figure 3A), forming a set of 280 images in total. For each layer, we recorded the responses of the units to those images and calculated the average across the population and the image set, $\bar{R}_{\text{face}}^{\text{size}}$ or $\bar{R}_{\text{object}}^{\text{size}}$, separately for faces or objects, and separately for each size. To quantify the degree of size-invariance, we define size-invariance index (SII) as the minimal fraction of sizes at which the mean population response to faces is reasonably larger than objects: ($\bar{R}_{\text{face}}^{\text{size}} > 1.4 \bar{R}_{\text{object}}^{\text{size}}$).

Shape-Appearance Tuning Experiment

To simulate the experiment on shape-appearance tuning (Chang and Tsao, 2017), we followed their approach to create a face space based on the active appearance model (Cootes and Edwards, 2001). For this, we employed 200 frontal face images from FEI face dataset, on which we annotated the coordinates of pre-defined 95 facial landmarks. We here used the Face++ tool (https://www.faceplusplus.com) to automatically annotate the

landmarks supported by this tool and resorted to manual annotation for the other landmarks. Our set of landmarks were in fact a superset of the ones used experimentally (58 landmarks) since the automatic tool happened to provide richer annotations, which would not (at least) impoverish our result.

From the above annotated image dataset, we constructed a 50-dimensional face space as follows. We first performed principle component analysis (PCA) on the landmark coordinates of the 200 images, of which the first 25 principal components provided the first 25 dimensions of the face space, called shape dimensions or features. Thereafter, we normalized each image by morphing the original image so that the warped landmark coordinates match the mean landmark coordinates (across all images). We again performed PCA on the resulting normalized images, of which the first 25 principal components provided the last 25 dimensions of the face space, called appearance dimensions or features. We then generated a set of 2000 face images by randomly sampling feature vectors from the 50-dimensional isotropic Gaussian distribution and reconstructing images by reversely following the above process. Figure 4A shows examples of generated frontal face images by varying the first shape and appearance dimensions.

To identify shape-appearance preference of each unit, we first recorded the responses to the generated 2000 face images and calculated the spike-triggered average (STA) as the average of the 50-dimenisonal feature vectors of those images weighted by the corresponding responses. To quantify the preference to shape or appearance, we defined shape preference index (SPI):

$$\mathrm{SPI} = \frac{(S - A)}{(S + A)}$$

where S is the vector length of the 25 shape dimensions and A is the vector length of the appearance dimensions of the STA (Chang and Tsao, 2017).

We conducted the same decoding study as in the experimental study (Chang and Tsao, 2017). Since the size of unit population affects the performance of decoding, we randomly selected a subpopulation of 100 units from each layer, which is comparable to the size in the experiment. To decode a feature vector from the population responses for a chosen face image, we trained a linear regression model from the population responses to the remaining 1999 face images and predicted the feature vector for the chosen image. Using

the leave-one-out approach, we continued this process for each of the 2000 images to decode the feature vectors for all images. We evaluated the performance of decoding in terms of ratios of explained variance in the actual feature vectors by the decoded feature vectors for each feature dimension.

To further investigate view tolerance, we repeated the aforementioned face space generation process for the profile view. That is, we created a profile face space from 200 profile face images from FEI database with manually annotated landmark coordinates and randomly generated 2000 profile face images. We established a mapping between the frontal and profile face spaces by linear regression between the frontal and profile feature vectors of the same identities. From then on, we always used the profile feature vectors mapped to the frontal face space. Figure 5A shows examples of generated left profile face images by varying the first shape and appearance dimensions. We thereafter calculated the STA and performed decoding for profile face images in similar ways to frontal face images. We also repeated the same process for all remaining non-frontal views (10 views in total). See the original experimental study (Chang and Tsao, 2017) for details.

Facial Geometry Tuning Experiment

To simulate the experiment using cartoon face stimuli (Freiwald et al., 2009), we used the same cartoon face design, where each face image had seven elementary parts (hair, face outline, eyes, irises, eyebrows, mouth, and nose) and the geometry of the parts were parameterized by 19 feature parameters (face aspect ratio, face direction, height of assembly, hair length, hair thickness, eyebrow slant, eyebrow width, eyebrow height, inter-eye distance, eye eccentricity, eye size, iris size, gaze direction, nose base, nose altitude, mouth-nose distance, mouth size, mouth top, and mouth bottom). Each of these parameters held values between -5 to $+5$ (11 values), where zero corresponded to the average features (e.g., normal inter-eye distance) and ± 5 corresponded to the extreme features (e.g., large or no inter-eye distance). Figure 6A shows example cartoon face images that vary the inter-eye distance parameter over 11 different values.

Using the same method as in the experimental study (Freiwald et al., 2009), we estimated a tuning curve for each unit and for each feature. For this, we first generated a set of 5000 cartoon face images with random values for the 19 parameters. From the responses to those images, we estimated a tuning curve for each feature parameter by taking the

average of the responses corresponding to each value that the feature parameter takes, regardless of the values of the remaining features; we smoothed the curve by a Gaussian kernel of unit variance. We then determined the statistical significance of the tuning curve using the same criterion as in the experimental study (Freiwald et al., 2009).

Contrast Polarity Tuning Experiment

To simulate the experiment using mosaic-like parameterized cartoon faces images (Ohayon et al., 2012), we used the same stimulus design, where each face image consisted of 11 face parts (forehead, left eye, right eye, nose, upper lip, left cheek, right-cheek, lower-left cheek, lower-right cheek, mouth, chin) based on a manual fragmentation of a mean face. Following the experimental procedure (Ohayon et al., 2012), we generated a set of 432 faces images by randomly giving a unique intensity value to each part ranging between dark and bright (11 values), while ensuring that, for every possible part-pair (55 part-pairs in total, e.g. forehead and left-eye, forehead and right-eye) and every possible intensity level, the set included at least one exemplar in which that part-pair had that intensity level. Figure 7A shows some examples of generated mosaic-like cartoon face images in the case of forehead lighter than left eye or the opposite.

Following the experimental method (Ohayon et al., 2012), we used the responses of each unit to the above set of images to determine preference on the contrast polarity for each of the 55 part-pairs. More specifically, for each part-pair (A and B), we compared the average response between the condition where intensity of part A was greater than part B (part A > part B) and the condition where intensity of part A was lesser than part B (part A < part B) irrespective of what intensity value the remaining 9 parts held. We then determined the significance of the contrast polarity preference for each part-pair using the same criterion as in the experimental study (Ohayon et al., 2012).

Acknowledgments

This work has been supported by the Commissioned Research of National Institute of Information and Communications Technology (1940201), the New Energy and Industrial Technology Development Organization (P15009), and Grants-in-Aid for Scientific Research (18H05021, 18K11517, and 19H04999).

Author Contributions

H.H. designed the study. R.R. and H.H. created software required for the study. R.R. performed simulation and analysis. R.R. and H.H. wrote the manuscript.

Competing interests

The authors declare no competing financial interests.

Corresponding authors

Correspondence to Rajani Raman and Haruo Hosoya.

Data availability

The authors declare that all data supporting the findings of this study are available within the paper and its supplementary information files.

References

Alonso JM, Martinez LM (1998) Functional connectivity between simple cells and complex cells in cat striate cortex. Nature neuroscience 1:395–403.

Baker N, Lu H, Erlikhman G, Kellman PJ (2018) Deep convolutional networks do not classify based on global object shape. PLoS Comp Biol 14:e1006613.

Bashivan P, Kar K, DiCarlo JJ (2019) Neural population control via deep image synthesis. Science 364:eaav9436.

Cadena SA, Denfield GH, Walker EY, Gatys LA, Tolias AS, Bethge M, Ecker AS (2019) Deep convolutional models improve predictions of macaque V1 responses to natural images. PLoS Comp Biol 15:e1006897.

Cadieu CF, Hong H, Yamins DLK, Pinto N, Ardila D, Solomon EA, Majaj NJ, DiCarlo JJ (2014) Deep Neural Networks Rival the Representation of Primate IT Cortex for Core Visual Object Recognition. PLoS Comp Biol 10:e1003963.

Chang L, Tsao DY (2017) The Code for Facial Identity in the Primate Brain. Cell 169:1013–1020.e1014.

Cootes TF, Edwards GJ (2001) Active Appearance Models. IEEE Trans Pattern Anal Mach Intell 23:681–685.

Cox DD, Meier P, Oertelt N, DiCarlo JJ (2005) "Breaking" position-invariant object recognition. Nature neuroscience 8:1145–1147.

Deng J, Berg AC, Li K, Fei-Fei L (2010) What does classifying more than 10,000 image categories tell us? Computer Vision–ECCV 2010:71–84.

Downing PE, Chan AWY, Peelen MV, Dodds CM, Kanwisher N (2005) Domain Specificity in Visual Cortex. Cereb Cortex 16:1453–1461.

Eickenberg M, Gramfort A, Varoquaux G, Thirion B (2017) Seeing it all: Convolutional network layers map the function of the human visual system. NeuroImage 152:184–194.

Einhäuser W, Hipp J, Eggert J, Körner E, König P (2005) Learning viewpoint invariant object representations using a temporal coherence principle. Biological Cybernetics 93:79–90.

Farzmahdi A, Rajaei K, Ghodrati M, Ebrahimpour R, Khaligh-Razavi S-M (2016) A specialized face-processing model inspired by the organization of monkey face patches explains several face-specific phenomena observed in humans. Sci Rep 6:25025.

Felleman DJ, Van Essen DC (1991) Distributed hierarchical processing in the primate cerebral cortex. Cereb Cortex 1:1–47.

Földiák P (1991) Learning invariance from transformation sequences. Neural Computation 3:194–200.

Freiwald WA, Tsao DY (2010) Functional compartmentalization and viewpoint generalization within the macaque face-processing system. Science 330:845–851.

Freiwald WA, Tsao DY, Livingstone MS (2009) A face feature space in the macaque temporal lobe. Nature neuroscience 12:1187–1196.

Goodfellow I, Bengio Y, Courville A (2016) Deep Learning. MIT Press.

Groen I, Greene MR, Baldassano C, Fei-Fei L (2018) Distinct contributions of functional and deep neural network features to representational similarity of scenes in human brain and behavior. eLife 7:e32962.

Güçlü U, van Gerven MAJ (2015) Deep Neural Networks Reveal a Gradient in the Complexity of Neural Representations across the Ventral Stream. Journal of Neuroscience 35:10005–10014.

Heeger DJ (1992) Normalization of cell responses in cat striate cortex. Visual Neuroscience 9:181–197.

Horikawa T, Kamitani Y (2017) Generic decoding of seen and imagined objects using hierarchical visual features. Nature Communications 8:1–15.

Hosoya H (2019) Group-based learning of disentangled representations with generalizability for novel contents. International Joint Conference on Artificial Intelligence.

Hosoya H, Hyvärinen A (2015) A Hierarchical Statistical Model of Natural Images Explains Tuning Properties in V2. Journal of Neuroscience 35:10412–10428.

Hosoya H, Hyvärinen A (2016) Learning Visual Spatial Pooling by Strong PCA Dimension Reduction. Neural Computation 28:1249–1263.

Hosoya H, Hyvärinen A (2017) A mixture of sparse coding models explaining properties of face neurons related to holistic and parts-based processing. PLoS Comp Biol 13:e1005667.

Hubel DH, Wiesel TN (1962) Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. The Journal of Physiology 160:106–154.

Hyvärinen A, Hoyer PO (2001) A two-layer sparse coding model learns simple and complex cell receptive fields and topography from natural images. Vision Research 41:2413–2423.

Karklin Y, Lewicki MS (2008) Emergence of complex cell properties by learning to generalize in natural scenes. Nature 457:83–86.

Kell AJE, Yamins DLK, Shook EN, Norman-Haignere SV, McDermott JH (2018) A Task-Optimized Neural Network Replicates Human Auditory Behavior, Predicts Brain Responses, and Reveals a Cortical Processing Hierarchy. Neuron 98:1–32.

Khaligh-Razavi S-M, Kriegeskorte N (2014) Deep Supervised, but Not Unsupervised, Models May Explain IT Cortical Representation. PLoS Comp Biol 10:e1003915.

Koumura T, Terashima H, Furukawa S (2019) Cascaded Tuning to Amplitude Modulation for Natural Sound Recognition. The Journal of neuroscience 2914-18.

Krizhevsky A, Sutskever I, Hinton GE (2012) ImageNet classification with deep convolutional neural networks. Advances in neural information processing systems:1097–1105.

Lafer-Sousa R, Conway BR (2013) Parallel, multi-stage processing of colors, faces and shapes in macaque inferior temporal cortex. Nature neuroscience 16:1870–1878.

LeCun Y, Bengio Y, Hinton G (2015) Deep learning. Nature 521:436–444.

LeCun Y, Bottou L, Bengio Y (1998) Gradient-based learning applied to document recognition. Proceedings of the IEEE 86:2278–2324.

Leibo JZ, Liao Q, Anselmi F, Freiwald WA, Poggio T (2017) View-Tolerant Face Recognition and Hebbian Learning Imply Mirror-Symmetric Neural Tuning to Head Orientation. Curr Biol 27:62–67.

Moeller S, Freiwald WA, Tsao DY (2008) Patches with Links: A Unified System for Processing Faces in the Macaque Temporal Lobe. Science 320:1355–1359.

Morel P (2018) Gramm: grammar of graphics plotting in Matlab. JOSS 3:568.

Nilsback M-E, Zisserman A (2008) Automated Flower Classification over a Large Number of Classes. Indian Conference of Computer Vision and Graphic Image Processing:722–729.

Ohayon S, Freiwald WA, Tsao DY (2012) What Makes a Cell Face Selective? The Importance of Contrast. Neuron 74:567–581.

Olshausen BA, Field DJ (1996) Emergence of simple-cell receptive field properties by learning a sparse code for natural images. Nature 381:607–609.

O'Toole AJ, Castillo CD, Parde CJ, Hill MQ, Chellappa R (2018) Face Space Representations in Deep Convolutional Neural Networks. Trends in cognitive Sciences 22:794–809.

Parkhi OM, Vedaldi A, Zisserman A (2015) Deep Face Recognition. British Machine Vision Conference:41.1–41.12.

Rajalingham R, Issa EB, Bashivan P, Kar K, Schmidt K, DiCarlo JJ (2018) Large-Scale, High-Resolution Comparison of the Core Visual Object Recognition Behavior of Humans, Monkeys, and State-of-the-Art Deep Artificial Neural Networks. The Journal of neuroscience 38:7255–7269.

Rawat W, Wang Z (2017) Deep Convolutional Neural Networks for Image Classification: A Comprehensive Review. Neural Computation 29:2352–2449.

Sato T, Uchida G, Lescroart MD, Kitazono J, Okada M, Tanifuji M (2013) Object representation in inferior temporal cortex is organized hierarchically in a mosaic-like structure. Journal of Neuroscience 33:16642–16656.

Schwartz O, Simoncelli EP (2001) Natural signal statistics and sensory gain control. Nature neuroscience 4:819–825.

Tsao DY, Freiwald WA, Knutsen TA, Mandeville JB, Tootell RBH (2003) Faces and objects in macaque cerebral cortex. Nature neuroscience 6:989–995.

Tsao DY, Freiwald WA, Tootell R, Livingstone MS (2006) A cortical region consisting entirely of face-selective cells. Science 311:670–674.

Yamins DLK, Hong H, Cadieu CF, Solomon EA, Seibert D, DiCarlo JJ (2014) Performance-optimized hierarchical models predict neural responses in higher visual cortex. Proceedings of the National Academy of Sciences 111:8619–8624.

Yildirim I, Belledonne M, Freiwald W, Tenenbaum JB (2018) Efficient inverse graphics in biological face processing. bioRxiv http://dx.doi.org/10.1101/282798.

Zipser D, Andersen RA (1988) A back-propagation programmed network that simulates response properties of a subset of posterior parietal neurons. Nature 331:679–684.