Lake overturn as a key driver for methane oxidation

M. Zimmermann[1,2]*, M. J. Mayr[1,2], D. Bouffard[1], W. Eugster[2], T. Steinsberger[1], B. Wehrli[1,2], A.

Brand[1,†] and H. Bürgmann[1]

[1]Eawag, Swiss Federal Institute of Aquatic Science and Technology, Surface Waters

- Research and Management, Kastanienbaum, Switzerland.

[2]Departement of Environmental Systems Science, ETH Zürich, Switzerland.

Corresponding author: Matthias Zimmermann (matthias.zimmermann@eawag.ch)

†Current address: Andreas Brand, Furkastrasse 75, 3904 Naters, Switzerland

Abstract

Many seasonally stratified lakes accumulate substantial amounts of the greenhouse gas methane

in the anoxic zone. Methane oxidizing bacteria in the water column act as a converter, oxidizing

methane into carbon dioxide and biomass before it reaches the atmosphere. Current observations

and estimates of this methane oxidation efficiency are diverging, especially for the lake overturn

period. Here we combine a model of turbulent mixing, gas exchange and microbial growth with

a comprehensive data set for autumn mixing to quantify the relevant physical and microbial

processes. We show that the microbial methane converter is effectively transforming the

increased methane flux during the overturn period. Only rare events of pronounced surface

cooling in combination with persistently strong wind can trigger substantial outgassing. In the

context of climate change, these results suggest that changes in the frequency of storms may be

even more important for methane emissions from temperate lakes than gradual warming.

Main

Lakes and reservoirs are increasingly recognized as significant players in the global carbon cycle

because they store, convert and release substantial amounts of greenhouse gases[1]. According to

recent estimates, lacustrine methane emissions are responsible for about 75% of the climate

impact of lacustrine systems[2] and might even offset the continental carbon sink[3]. In lakes, most

methane is produced in the anaerobic sediment as one of the final products of anaerobic carbon

mineralization[4]. Ultimately, this methane is either released to the atmosphere or is oxidized by

aerobic methane oxidizing bacteria (MOB), which have the unique ability to use methane as their

sole carbon and energy source[5]. Here we provide evidence that this microbial methane converter

is efficient and robust even at high rates of vertical mixing and prevents a major fraction of

methane from reaching the atmosphere.

This microbial methane sink has important implications for lakes with seasonal thermal

stratification that accumulate large amounts of methane in the anoxic hypolimnion, hereafter

referred to as 'stored methane'. During stratification, MOB at the oxic-anoxic interface form an

effective barrier against diffusive methane outgassing, which is only bypassed by ebullition, i.e.

methane bubbles released from the sediment[6]. In contrast, strong vertical mixing during the

autumn overturn may lead to a rapid transport of stored methane to the surface. So far, estimates

of global methane emissions from lakes have therefore assumed that most of this methane is

ultimately released to the atmosphere[7]. However, the supply of methane to the oxygen-rich

surface water creates favourable conditions for the growth of aerobic MOB. If the community of

MOB grows fast enough, it could significantly reduce methane emissions even under conditions

of rapid lake mixing.

Published field measurements of the percentage of stored methane that is oxidized range from 54

to 94%[8–11]. These previous studies focused either on time-resolved flux measurements[7,10] or on

microbial rate observations[8,9]. Here we closely integrate the two approaches in order to improve

our understanding of the underlying processes during lake mixing. Based on a detailed field

campaign we further developed and validated a dynamic model of turbulent mixing, gas

exchange and Monod-type growth of MOB. We used this model to derive bulk kinetic properties

of the MOB community and to quantify the efficiency and robustness of the microbial methane

converter during the autumn overturn in a small temperate lake.

Fate of methane during the autumn overturn

We determined the fate of methane in a small temperate lake during the autumn overturn (Figure

1). From October to December 2016 only 9% of the stored methane that was transported to the

surface was emitted to the atmosphere. Methane emissions measured by eddy covariance flux

measurement were on average 0.26 µg CH_4 m^{-2} s^{-1} and summed to a total of 0.36 Mg C that

were emitted from the whole lake (Figure 1a). During this period, cooling of the surface water as

well as wind (Figure 1a) increased the mixed-layer depth from 7.6 to 13 m (Figure 1b). This

physical process gradually depleted the pool of stored methane in the hypolimnion and

transferred a total of 4.2 Mg C of methane to the mixed layer. After subtraction of the emissions,

the remaining 3.8 Mg C either were oxidized by MOB or remained in the mixed layer. However,

we only measured mixed layer methane concentrations of 0.5 ± 0.4 µM (SD) or a maximum total

methane inventory of 0.039 ± 0.026 Mg C (SD), suggesting that MOB oxidized about 91% of the

stored methane. In parallel, the cumulative biomass of MOB in the oxic mixed layer increased by

a factor of 14 from 0.047 Mg C to 0.67 Mg C (Figure 1c). Despite this rapid growth, the 0.62 Mg

C of newly formed biomass represented a small fraction of the 3.8 Mg C that were supplied to

the mixed layer suggesting a carbon conversion efficiency of MOB of only 0.16. With the

increase of MOB biomass we also observed a change in the community composition which is

documented in detail in a parallel study[12].

Figure 1: Field observations during the overturn period 2016 in Lake Rotsee. The horizontal time axis for all panels is plotted on top. Major ticks indicate the start of the month and minor ticks refer to the dates. **(a)** The daily average difference between air temperature and surface water temperature is plotted as a proxy for the progressing cooling during the overturn period. The daily maximum and minimum difference are indicated by the shaded area around the daily average. Wind-speeds are plotted as hourly averages and were corrected for Lake Rotsee (Supplementary Figure 1). Time series of the daily average air temperatures and wind-speeds were obtained from the closest automated weather station of MeteoSwiss (www.meteoswiss.ch). Methane emissions are plotted as Gaussian filtered flux of the measured 30 min average fluxes. **(b)** Methane stored in the water column multiplied by the cross-section area is plotted as a heatmap interpolated from individual measurements that are indicated by gray dots. Methane concentrations in the mixed layer were 0.5 ± 0.4 µM (SD) but reached levels of up to 3.7 mM at the sediment-water interface (Supplementary Figure 2), which corresponds to a partial pressure of about 65% at this depth. The depth of the thermocline was interpolated from the continuous thermistor string data and was verified by individual CTD profiles. **(d)** Biomass of MOB multiplied by the cross-section area is plotted as a heatmap interpolated from individual measurements that are indicated by gray dots.

Modelling the key processes

Based on these field observations we validated a minimal model of the key processes (Figure 2)

that determine the fate of stored methane and control the efficiency and robustness of the

microbial methane converter during the autumn overturn. Despite its simplicity, the turbulent

mixing model was able to reproduce the evolution of the measured mixed-layer depth (Figure 2a)

with a root mean square error (RMSE) of only 0.27 m. The resulting flux of stored methane to

the mixed layer was therefore in good agreement with the measurements (Figure 2b). The

Monod-type growth model reproduced the evolution of MOB biomass to a maximum of

0.68 Mg C with a RMSE of 0.061 Mg C (Figure 2c). The box model approach neglected a

potential gradual crossover of methane and oxygen within the thermocline. However, the

biomass profiles did not give any indication that such a transition zone was of particular

importance for methane oxidation during the overturn period (Figure 1c).

The ratio of modelled methane emission to the total transport of stored methane to the mixed

layer suggests that about 98% of this methane was oxidized by MOB. The measured cumulative

methane flux the atmosphere was about three times larger than the modelled flux (Figure 2d). A

likely explanation for the discrepancy is the contribution of methane ebullition to the emissions

during the overturn period, which was not included in the model. That bubble emission is a

major pathway during the autumn overturn in Lake Rotsee has been shown in a study by

Schubert et al. [8] who estimated cumulative contributions of ebullition to total atmospheric

emissions between 88 and 97%.

Figure 2: Model combining the key processes that determine the fate of stored methane during the autumn overturn. **(a)** The deepening of the thermocline was modeled using a turbulent mixing model that considers wind-driven and thermal convection. Modelled and measured depth of the thermocline fit very well. The inset shows the histogram of the dissipation rate of convective and wind-driven turbulent kinetic energy at the mixed-layer depth over the simulation period. **(b)** Modelled and measured cumulative amount of stored methane transported to the mixed layer. **(c)** Modelled and measured MOB biomass. The error bars for the measured biomasses represent 95% confidence intervals for the biomass, based on the uncertainty in the cellular carbon content. **(d)** Modelled and measured emissions of methane to the atmosphere. Emissions measured by eddy covariance also include ebullition, whereas the model does not include this emission pathway.

Even though the model does not take into account the observed diversity of the MOB

community[12], the fitted bulk kinetic parameter are well in line with expected properties for the

methane limiting conditions in the mixed layer. The half saturation constant for methane

oxidation (K_{M,CH_4}) of 1.7 µM is in the lower range of published values (1 and 10 µM)[5,13]. It is

known that the affinity for methane can even be in the nM range for growth under atmospheric

methane concentrations[14,15]. The fitted half saturation in the lower µM range therefore reflects an

adaptation to the low methane concentrations in the mixed layer. The best fit estimated for the

carbon conversion efficiency of the Monod-type growth model (y) is 0.13 which is in good

agreement with the 0.16 estimated from the measurements. Published values for the carbon

conversion efficiency (CCE) of MOB vary widely from 0.19 to 0.7 and likely also depend on

growth conditions[16,17]. The low CCE reflects the methane limiting conditions, where

maintenance energy accounts for a higher proportion of methane oxidation. That a high

respiratory demand decreases the growth efficiency has been shown for various bacteria in

lakes[18]. According to the growth model, the MOB community indeed grew on average with only

26 ± 19 % (SD) of the maximum growth rate. In addition, the potentially higher metabolic costs

of the elevated methane affinity required to thrive at low concentrations might also have reduced

the CCE[13]. The best fit estimate for the maximum specific methane oxidation rate (r_{mox}^{max}) is 1.2

d^{-1} and lies well within the range of measured specific methane oxidation rates of 0.08 – 2.3 d^{-1}

(ref. [12]). Combined with the carbon conversion efficiency the maximum specific methane

oxidation rate translates to a growth rate of 0.16 d^{-1} or a doubling time of ~4 days. Doubling

times reported for pure cultures are typically in the range of a few hours[13,14,19], but these values

represent growth under optimal conditions. Doubling times in environmental settings are likely

to be slower and reported values for freshwater samples are in the range of 2 – 3 days[20–22].

Robustness of the microbial methane converter

The velocity of thermocline deepening and the piston velocity of gas exchange with the atmosphere, are important factors influencing the efficiency of the microbial methane converter (i.e. the amount of stored methane that is oxidized by MOB before it escapes to the atmosphere). During the autumn overturn in Lake Rotsee, wind and thermal convection played different roles in this respect. Our model calculations show that wind contributed 77 ± 13 % (SD) to the gas transfer coefficient and that wind was therefore the main driver for the transport of methane from the surface water to the atmosphere. In contrast, wind on average only contributed to 5% to the dissipation rate of turbulent kinetic energy at the mixed-layer depth (Figure 2a, inset) and the Monin-Obukhov length scale was smaller than the mixed layer depth (Supplementary Figure 5) for most of the time. Thermal convection was therefore the dominant driver for the deepening of the thermocline and thus for the supply of stored methane to the mixed layer. Model simulations of the autumn overturn in Lake Rotsee based on meteorological data from 1990 to 2016 showed that this convective regime dominated throughout the years. The annual variability of stored methane that is oxidized by MOB stayed in a fairly narrow range of 95% to 98%.

This high efficiency of the methane converter was a result of the convective mixing regime, with a gradual deepening of the thermocline that kept methane fluxes well below the methane oxidation capacity, defined here as the maximum methane oxidation rate at a given concentration of biomass (Figure 3a). The average of the daily maximum methane fluxes to the mixed layer reached only 27 % of the methane oxidation capacity even when deeper water layers with higher methane concentrations were involved. This robustness of the methane converter during the

overturn is due to two effects. First, the increasing flux of stored methane to the mixed layer was

diluted in an ever-larger volume of the mixed layer. The dilution of stored methane entering the

epilimnion was three times larger at the end of the overturn compared to the initial situation.

Second, the supply of methane led to an increase of MOB biomass, which in turn increased the

methane oxidation capacity itself. In summary, both the progressing dilution of the methane

supply as well as the growing methane oxidation capacity counteract the increasing flux of

methane supplied to the mixed layer.

Because Lake Rotsee is wind-sheltered, we used a scenario analysis to explore the robustness of

the microbial methane converter to events of high wind-speeds (Figure 3b). The scenario

analysis revealed three important patterns. First, the fraction of stored methane that is emitted to

the atmosphere by the end of the overturn period is negligible for wind-speeds of up to about 20

km/h (Figure 3b, line A). For these wind-speeds, convection still dominates the deepening of the

thermocline. Second, for a 12 hour wind event, the fraction of emitted methane stayed below

20% even for wind-speeds of up to 70 km/h (Figure 3b, line B). To increase this fraction to 60%,

3 days of consecutive wind-speeds of 70 km/h were necessary. Third, the timing of the wind-

event matters. The fraction of emitted methane was highest when the wind-event occurred at

intermediate mixed-layer depths (Figure 3b, line C) but was significantly lower if it occurred at

the beginning or the end of the mixing period.

Figure 3: Robustness of the microbial methane converter. **(a)** Typical methane fluxes to the mixed layer for the convective regime. The methane fluxes were normalized to the minimum non-zero flux and are plotted per cross-section area at the mixed layer interface and per volume of the mixed layer. The flux of stored methane per volume can be compared to the methane oxidation capacity, the maximum rate of methane oxidation of the MOB biomass. **(b)** Scenario analysis for events of elevated wind-speeds. The two surfaces represent the fraction of stored methane that is emitted at the end of the overturn period if a 3 day or a 0.5 day wind-event is artificially generated during the overturn period. The two surfaces are colored according to whether wind or convection was the dominant driver for the thermocline deepening. Wind-events started at different mixed-layer depths and consisted of constant wind-speeds for the whole duration of the event.

Accordingly, we suggest that global estimates of methane emissions from lakes should consider

robust and effective methane oxidation even during overturn as the norm rather than as an

exception. Wind has often been perceived as the strongest forcing for turbulent mixing[23]. In lakes

however, convective processes are usually the dominant drivers for mixing and stratification

because unlike wind-shear, they remain constant with decreasing surface area. Convective forces

are therefore increasingly becoming recognized as important drivers for various biogeochemical

processes in inland waters[23].

We expect that future emissions of stored methane from temperate lakes remain low. Climate

change will increasingly strengthen lake stratification and make partial mixing more common[24].

Even though more extensive anoxic conditions will allow more methane to accumulate, the

slower mixing process resulting from strong stratification in turn facilitates its oxidation. In

contrast, we expect that the relative importance of ebullition increases, especially when

prolonged hypoxia increase the sediment methane concentration. Elevated methane emissions

during autumn overturn are linked to exceptional meteorological events with persistently strong

wind for several days or a combination of rapid cooling with strong winds. Estimates of the

frequency of extreme wind and cooling events during the autumn overturn might therefore be

particularly important to estimate current and future emissions of stored methane, since such

events could have larger effects than the average warming trend[25] itself.

Methods

Study site

Lake Rotsee is a small eutrophic subalpine lake in Switzerland that is 2.5 km long, 200 m wide and has a maximum depth of 16 m. The lake is oligomictic and exhibits a stable stratification from approximately May to September[26,27]. The fate of methane was determined during 7 field campaigns over the course of the autumn overturn from October to December 2016. Water samples were taken at the deepest point of Lake Rotsee at 47.0705° N and 8.3157° E.

Methane concentrations

We measured methane concentrations in the water column using the headspace equilibration method. 20 mL water samples were filled into 40 mL serum vials. The serum vials had previously been prepared by addition of 4 g sodium hydroxide pellets, repeated flushing with nitrogen (N_2) and evacuation to a final pressure of 600 mbar. We measured methane concentrations in the headspaces with a gas chromatograph (Agilent 6890N, USA) equipped with a Carboxen 1010 column (Supelco 10 m × 0.53 mm, USA) and flame ionisation detector. Samples that exceeded the calibration range were diluted with N_2 and measured again. Dissolved methane concentrations were calculated according to Wiesenburg & Guinasso[28]. Control experiments showed that 4 g of solid NaOH produced 32.6 nmol methane on average, which was accounted for when calculating methane concentrations.

Methane concentrations in the sediment were determined in two duplicate sediment cores. Sediment cores were retrieved from the deepest part of Lake Rotsee with a UWITEC gravity corer (UWITEC, Mondsee, Austria). For methane sampling, predrilled PVC tubes of 6.3 cm

diameter and 60 cm length with holes of 1.2 cm diameter spaced at 1 cm were used. 2 cm^3

aliquots of sediment were taken for methane analysis with syringes with cut-off tips by pushing

the syringe through the taped holes. The sediment aliquots were directly injected into 113.7 ml

flasks pre-filled with 7 M NaOH, capped and stored in the dark at 4°C. Methane was determined

by headspace analysis using an Agilent gas chromatograph (Agilent Technologies AG, Basel,

Switzerland) equipped with a Supelco Carboxene®-1010 column (Sigma-Aldrich, Steinheim,

Germany).

Biomass of methane oxidizing bacteria

We determined MOB cell numbers using CARD FISH and epifluorescence microscopy. Water

samples of 5 mL were fixed with 300 µl sterile filtered (0.2 µm) formaldehyde (2.22% [v/v] final

concentration) for 3 – 6 h on ice. Samples were then filtered onto 0.2 µm nuclepore track-etched

polycarbonate membrane filters (Whatman, UK), dried, and stored at –20°C until further

analyses. Cells were permeabilized with lysozyme (10 mg mL^{-1}) at 37 °C for 70 min, followed

by inactivation of endogenous peroxidases with 0.1 M hydrogen chloride for 10 min at room

temperature. Filters were hybridised with hybridisation buffer containing HRP-labelled probes at

46 °C for 2.5 h. The buffer contained either a 1:1:1 mix of Mg84, Mg705, and Mg669 probes

targeting methanotrophic gammaproteobacteria or a Ma450 probe targeting methanotrophic

alphaproteobacteria[29]. Fluorescent signals were amplified with the green-fluorescent Oregon

Green 488 tyramide (OG) fluorochrome (1 µl mL^{-1}) at 37 °C for 30 min. Hybridised cells were

counterstained with DAPI (20 µl of 1 µg mL^{-1} per filter) for 5 minutes. We used a 4:1 mix of

Citifluor and Vectashield to mount filter pieces for fluorescence microscopy. We quantified

MOB cell numbers using an inverted light microscope (Leica DMI6000 B, Germany) at a 1000-

fold magnification. For each sample, 22 image pairs (DAPI and OG) of randomly selected fields

of view (FOVs) were taken for each filter piece. Cells were detected and counted using Daime

2.0 for computer digital image processing (CDIP)[30]. We converted the cell numbers to biomass

using an average cellular carbon content of 0.42 pg cell^{-1} based on literature values[21,31,32].

Methane emissions

Methane emissions during the overturn period in 2016 were quantified with eddy-covariance flux

measurements using an FGGA-100 fast methane and CO_2 gas analyzer (Los Gatos Reseach Inc.,

Mountain View, CA, USA) combined with a Solent R2A ultrasonic anemometer (Gill

Instruments, Solent, UK) as described in Sollberger et al.[33] and Eugster & Plüss[34]. The

measurement setup was deployed at the same location as the one described in Schubert et al.[8]:

The sonic anemometer was mounted on a moored buoy 70 m from the lake shore, and air was

pulled 1. 47 m (center of ultrasonic anemometer head) above the lake surface and guided to the

gas analyser using a Synflex 1300 tube at a flow rate of 26.3 L min^{-1}. The footprint area of the

eddy covariance measurements is shown in the Supplementary Figure 3.

Meteorological conditions and water temperature

We continuously measured the evolution of the water temperature with a temporal resolution of

5 s and a spatial resolution of 1 m (RBRconcerto T24 thermistor string, RBR). To be able to

cover a long period, air temperature, wind speed, vapour pressure, shortwave incoming radiation

and cloud cover were obtained from MeteoSchweiz (SwissMetNet station LUZ). We adjusted

wind-speeds to the local conditions using sporadically available wind speed measurements

directly at Lake Rotsee obtained with an automated weather station by AANDERAA (<mark>Figure</mark>

<mark>S1</mark>).

Biogeochemical model

256   The mixed layer was approximated as a single, homogeneously mixed box, which gets larger as

257   the thermocline deepens. The system of ordinary differential equations (ODE) describing the

258   temporal evolution of the mixed-layer depth (h_{mix}) and volume (V_{mix}), temperature (T_{mix}),

259   methane concentration (C_{mix}) and MOB biomass (B_{mix}) is:

$$\frac{dh_{mix}}{dt} = v_{mix} \tag{1}$$

$$\frac{dV_{mix}}{dt} = v_{mix} \cdot A(h_{mix}) \tag{2}$$

$$\frac{dC_{mix}}{dt} = \frac{1}{V_{mix}}\frac{dV_{mix}}{dt}\left(C_{hypo}(h_{mix}) - C_{mix}\right) - F_{atm} - r_{mox} \cdot B_{mix} \tag{3}$$

$$\frac{dB_{mix}}{dt} = -\frac{1}{V_{mix}}\frac{dV_{mix}}{dt}B_{mix} + \mu B_{mix} \tag{4}$$

$$\frac{dT_{mix}}{dt} = \frac{1}{V_{mix}}\frac{dV_{mix}}{dt}\left(T_{hypo}(h_{mix}) - T_{mix}\right) + H \tag{5}$$

where v_{mix} is the velocity of the thermocline deepening, $A(h_{mix})$ is the cross-section area of the

lake at the mixed-layer depth h_{mix}, F_{atm} is the flux of methane to the atmosphere, r_{mox} is the

specific rate of microbial methane oxidation, μ is the growth rate of MOB, H is the heat flux into

(positive) the lake, and $C_{hypo}(h_{mix})$ and $T_{hypo}(h_{mix})$ are the methane concentration and

temperature in the hypolimnion at the mixed-layer depth.

The initial temperature profile at the onset of the overturn period was obtained from field data

and was assumed to remain constant in the hypolimnion. In contrast, the measured methane

profiles do not remain constant due to the ongoing accumulation of methane at the bottom of the

lake. To keep the model simple, instead of modelling the accumulation we compiled a profile of

maximum concentrations (Supplementary Figure 2) that was used as the initial methane profile.

In the above system of ODEs, C_{hypo} and T_{hypo} are only depth dependent and correspond to the

temperature and methane concentration given by the initial profile at the mixed-layer depth.

We calculated methane emissions with the boundary layer model of Liss and Slater [35]:

$$F_{atm} = k(C_{mix} - C_{eq}) \tag{6}$$

273 where C_{eq} is the water saturation concentration calculated according to ref. [36] and k is the

274 transfer velocity. To explicitly take into account buoyancy and wind driven components of

275 turbulence at the air-water interface, we calculated the transfer velocity using the surface-

276 renewal model[37–39]:

$$k = \eta(\varepsilon v)^{1/4} Sc^{-n} \tag{7}$$

where ε is the rate of dissipation of turbulent kinetic energy near the air-water interface, v is the

kinematic viscosity and η is an empirically derived, depth dependent scaling coefficient. For the

purpose of this conceptual model, η was set to $1/(2\pi)$ based on theoretical considerations[40]. We

determined the Schmidt number Sc for methane with an exponent $n = -1/2$ (ref. [36]).

The dissipation rate ε was explicitly partitioned into the wind shear and the buoyancy

components:

$$\varepsilon = A_L \frac{u_*^3}{\kappa z} + B_L J_{B0} \tag{8}$$

283 where κ is the von Kármán constant, u_* is the water-side friction velocity and A_L as well as B_L

284 are empirically derived coefficients set to 1 as in ref. [39]. The wind-shear component of the

285 dissipation was calculated at the depth of the viscous boundary layer $z = \delta v$ (ref. [40]):

$$\delta v = \eta \frac{\nu}{U_{10}} \tag{9}$$

286 We calculated the friction velocity u_* as a function of the 10-m wind speed U_{10} as described in

287 ref. [41]:

$$u_* = (\tau/\rho_w)^{1/2} \tag{10}$$

$$\tau = \rho_{air} C_D U_{10}^2 \tag{11}$$

$$C_D = \begin{cases} 0.06215, & U_{10} \leq 0.1 \\ 0.0044 \cdot U_{10}^{-1.15}, & U_{10} \leq 3.85 \\ otherwise: \\ -712 \times 10^{-8} \cdot U_{10}^2 + 73.87 \times 10^{-6} \cdot U_{10} + 6.605 \times 10^{-4} \end{cases} \tag{12}$$

The buoyancy flux is defined as: $J_{B0} = g\alpha H/(\rho_w C_p)$ with the gravitational constant g, the

thermal expansion coefficient α, the heat flux H, the density of water ρ_w and the isobaric heat

capacity C_p. Finally, the parameterization of the heat flux (H) includes the shortwave absorption,

the longwave absorption, the longwave emission, the heat flux by evaporation and the heat

convection[42].

The deepening of the mixed layer was parameterized as a function of convective and wind-

driven forcing[43,44]:

$$\frac{dh_{mix}}{dt} = v_{mix} = \frac{(1 + 2A)w_*^3 + Bu_*^3}{N^2 h_{mix}} \tag{13}$$

where A and B are respectively entrainment coefficients for the convective, $w_* = (J_{B0}h_{mix})^{1/3}$,

and sheared u_* velocities and N^2 is the Brunt-Väisälä frequency at the mixed-layer interface[45].

We set $A = 0.2$ (ref. [46]) and $B = 2.5$ (ref. [47]).

In the mixed layer, we assume that methane is the limiting nutrient and we formulate the growth

rate of MOB with a Monod-type methane oxidation kinetics where the growth rate (μ) is

approximated based on the maximum specific methane oxidation rate (r_{mox}) and a carbon

conversion efficiency (y):

$$r_{mox} = r_{mox}^{max} \frac{[CH_4]}{K_{M,CH_4} + [CH_4]} \tag{14}$$

$$\mu = y \cdot r_{mox} \tag{15}$$

We obtained the kinetic parameters (y, r_{mox}^{max}, K_{M,CH_4}) based on the measured biomass evolution.

First, we performed a global parameter estimation using the CRS algorithm[48]. Based on the

result, a local parameter estimation was performed using the COBYLA algorithm[49].

The system of ODEs was implemented with Julia 1.0.1[50] and solved numerically with adaptive

time stepping and a maximum time step of 1 hour using an order 2/3 L-Stable Rosenbrock-W

method – which is good for very stiff equations with oscillations at low tolerances – provided in

the *DifferentialEquations.jl* package[51]. Parameter estimation was performed using the Julia

package *NLopt.jl*[52].

Fate of Methane

We calculated the methane budget neglecting potential horizontal variability. Amounts of

methane and biomass in the water column are given as volume integrated mass of carbon. We

obtained profiles of methane and biomass storage in units of $\mathrm{Mg\ m^{-1}}$ by multiplying the

measured concentrations with the cross-section area of the lake at the respective depth of

measurement. Methane emissions were extrapolated to the whole lake surface area and are given

as cumulative amounts.

The statistical interpretation of number ranges is given in brackets. We used the standard

deviation (SD) when the variability of the sample was of interest. The standard error of the mean

(SEM) or the 95% confidence interval (CI) was used in cases where the uncertainty of the mean

was of interest. The confidence intervals were corrected for the sample size using the t statistic.

Robustness of the microbial methane converter

The contribution of wind to the gas transfer coefficient was expressed as:

$$f_P = \frac{k_P}{k_P + k_B} \qquad (16)$$

where k_P is the transfer coefficient based on wind and k_B is the transfer coefficient based on

convection.

Because Lake Rotsee is wind-shelterd, we explored the effect of various wind regimes on

methane emissions by a model scenario analysis. We set wind-speeds to a constant level for 12

hours or 3 days. Each scenario consisted of a single wind-event that started at a specific mixed-

layer depths. To avoid artefacts from other meteorological conditions during the wind-event, we

neglected the heat balance during this period and calculated the forced convection based on an

empirical regression between the friction velocity and the buoyancy flux at the surface

(Supplementary Figure 4).

Code availability

334   The source code of the generic model is available as a Julia package on GitHub:

335   https://github.com/zimmermm/ConvectionBoxmodel.jl. The actual implementation for Lake

336   Rotsee is attached to the data package on the ETH Research Collection (10.3929/ethz-b-

337   000350091).

Data availability

339   All measurement data used for this publication are available on the ETH Research Collection

340   (10.3929/ethz-b-000350091).

341   Meteorological data was obtained from MeteoSwiss (www.meteoswiss.admin.ch)

Acknowledgments

343   This research was supported by SNF (grant CR23I3_156759) and ETH Zurich (scientific

344   equipment grants 0-43350-07, 0-23138-09 and 0-43683-11). We thank Karin Beck, Michael

345   Plüss, Michael Schurter and Christian Dinkel for the technical support during the field

346   campaigns and Jason Dey for CARD-FISH and image analysis.

References

1. Tranvik, L. J., Cole, J. J. & Prairie, Y. T. The study of carbon in inland waters-from isolated ecosystems to players in the global carbon cycle. *Limnol. Oceanogr. Lett.* **3**, 41–48 (2018).

2. DelSontro, T., Beaulieu, J. J. & Downing, J. A. Greenhouse gas emissions from lakes and impoundments: Upscaling in the face of global change. *Limnol. Oceanogr. Lett.* **3**, 64–75 (2018).

3. Bastviken, D., Tranvik, L. J., Downing, J. A., Crill, P. M. & Enrich-Prast, A. Freshwater Methane Emissions Offset the Continental Carbon Sink. *Science.* **331**, 50 (2011).

4. Bastviken, D., Cole, J. J., Pace, M. L. & Van de-Bogert, M. C. Fates of methane from different lake habitats: Connecting whole-lake budgets and CH_4 emissions. *J. Geophys. Res. Biogeosciences* **113**, 1–13 (2008).

5. Hanson, R. S. & Hanson, T. E. Methanotrophic bacteria. *Microbiol. Rev.* **60**, 439–471 (1996).

6. DelSontro, T., McGinnis, D. F., Wehrli, B. & Ostrovsky, I. Size Does Matter: Importance of Large Bubbles and Small-Scale Hot Spots for Methane Transport. *Environ. Sci. Technol.* **49**, 1268–1276 (2015).

7. Bastviken, D., Cole, J., Pace, M. & Tranvik, L. Methane emissions from lakes: Dependence of lake characteristics, two regional assessments, and a global estimate. *Global Biogeochem. Cycles* **18**, 1–12 (2004).

8. Schubert, C. J., Diem, T. & Eugster, W. Methane emissions from a small wind shielded

lake determined by eddy covariance, flux chambers, anchored funnels, and boundary

model calculations: A comparison. *Environ. Sci. Technol.* **46**, 4515–4522 (2012).

9. Kankaala, P., Taipale, S., Nykänen, H. & Jones, R. I. Oxidation, efflux, and isotopic

fractionation of methane during autumnal turnover in a polyhumic, boreal lake. *J.*

Geophys. Res. Biogeosciences **112**, 1–7 (2007).

10. Utsumi, M. *et al.* Dynamics of dissolved methane and methane oxidation in dimictic Lake

Nojiri during winter. *Limnol. Oceanogr.* **43**, 10–17 (1998).

11. Encinas Fernández, J., Peeters, F. & Hofmann, H. Importance of the autumn overturn and

anoxic conditions in the hypolimnion for the annual methane emissions from a temperate

lake. *Environ. Sci. Technol.* **48**, 7297–7304 (2014).

12. Mayr, M. J., Zimmermann, M., Dey, J., Brand, A. & Bürgmann, H. Growth and rapid

succession of methanotrophs effectively limit methane release during lake overturn.

bioRxiv (2019). doi:10.1101/707836

13. Knief, C. & Dunfield, P. F. Response and adaptation of different methanotrophic bacteria

to low methane mixing ratios. *Environ. Microbiol.* **7**, 1307–1317 (2005).

14. Baani, M. & Liesack, W. Two isozymes of particulate methane monooxygenase with

different methane oxidation kinetics are found in Methylocystis sp. strain SC2. *Proc. Natl.*

Acad. Sci. U. S. A. **105**, 10203–10208 (2008).

15. Dunfield, P. F. & Conrad, R. Starvation alters the apparent half-saturation constant for

methane in the type II methanotroph Methylocystis strain LR1. *Appl. Environ. Microbiol.*

66, 4136–4138 (2000).

390 16. Leak, D. J. & Dalton, H. Growth yields of methanotrophs - 1. Effect of copper on the

391   energetics of methane oxidation. *Appl. Microbiol. Biotechnol.* **23**, 470–476 (1986).

392 17. Leak, D. J. & Dalton, H. Growth yields of methanotrophs - 2. A theoretical analysis. *Appl.*

393   *Microbiol. Biotechnol.* **23**, 477–481 (1986).

394 18. Smith, E. M., Prairie, Y. T. & Carolina, S. Bacterial metabolism and growth efficiency in

395   lakes : The importance of availability phosphorus. *Limnology* **49**, 137–147 (2009).

396 19. Joergensen, L. & Degn, H. Growth rate and methane affinity of a turbidostatic and

397   oxystatic continuous culture of Methylococcus capsulatus (Bath). *Biotechnol. Lett.* **9**, 71–

398   76 (1987).

399 20. Oswald, K. *et al.* Aerobic gammaproteobacterial methanotrophs mitigate methane

400   emissions from oxic and anoxic lake waters. *Limnol. Oceanogr.* **61**, S101–S118 (2016).

401 21. Oswald, K. *et al.* Light-Dependent Aerobic Methane Oxidation Reduces Methane

402   Emissions from Seasonally Stratified Lakes. *PLoS One* **10**, (2015).

403 22. Milucka, J. *et al.* Methane oxidation coupled to oxygenic photosynthesis in anoxic waters.

404   *ISME J.* **9**, 1991–2002 (2015).

405 23. Bouffard, D. & Wüest, A. Convection in Lakes. *Annu. Rev. Fluid Mech.* **51**, annurev-

406   fluid-010518-040506 (2019).

407 24. Woolway, R. I. & Merchant, C. J. Worldwide alteration of lake mixing regimes in

408   response to climate change. *Nat. Geosci.* **12**, 271–276 (2019).

409 25. Woolway, R. I. *et al.* Substantial increase in minimum lake surface temperatures under

410   climate change. *Clim. Change* **155**, 81–94 (2019).

411   26.   Schubert, C. J. *et al.* Oxidation and emission of methane in a monomictic lake (Rotsee,

412   Switzerland). *Aquat. Sci.* **72**, 455–466 (2010).

413   27.   Brand, A. *et al.* Oxygenic primary production below the oxycline and its importance for

414   redox dynamics. *Aquat. Sci.* **78**, 727–741 (2016).

415   28.   Wiesenburg, D. A. & Guinasso, N. L. Equilibrium Solubilities of Methane, Carbon

416   Monoxide, and Hydrogen in Water and Sea Water. *J. Chem. Eng. Data* **24**, 356–360

417   (1979).

418   29.   Eller, G., Stubner, S. & Frenzel, P. Group-specific 16S rRNA targeted probes for the

419   detection of type I and type II methanotrophs by fluorescence in situ hybridisation. **198**,

420   91–97 (2001).

421   30.   Daims, H., Lücker, S. & Wagner, M. *daime*, a novel image analysis program for microbial

422   ecology and biofilm research. *Environ. Microbiol.* **8**, 200–213 (2006).

423   31.   Romanova, N. D. & Sazhin, A. F. Relationships between the cell volume and the carbon

424   content of bacteria. *Oceanology* **50**, 522–530 (2010).

425   32.   Posch, T. *et al.* Precision of bacterioplankton biomass determination: a comparison of two

426   fluorescent dyes, and of allometric and linear volume-to-carbon conversion factors. *Aquat.*

427   *Microb. Ecol.* **25**, 55–63 (2001).

428   33.   Sollberger, S., Wehrli, B., Schubert, C. J., DelSontro, T. & Eugster, W. Minor methane

429   emissions from an Alpine hydropower reservoir based on monitoring of diel and seasonal

430   variability. *Environ. Sci. Process. Impacts* **19**, 1278–1291 (2017).

34.   Eugster, W. & Plüss, P. A fault-tolerant eddy covariance system for measuring CH_4

fluxes. *Agric. For. Meteorol.* **150**, (2010).

35.   Liss, P. S. & Slater, P. G. Flux of Gases across the Air-Sea Interface. *Nature* **247**, 181–

184 (1974).

36.   Wanninkhof, R. Relationship between wind speed and gas exchange over the ocean

revisited. *Limnol. Oceanogr. Methods* **12**, 351–362 (2014).

37.   Zappa, C. J. *et al.* Environmental turbulent mixing controls on air-water gas exchange in

marine and aquatic systems. *Geophys. Res. Lett.* **34**, 1–6 (2007).

38.   MacIntyre, S. *et al.* Buoyancy flux, turbulence, and the gas transfer coefficient in a

stratified lake. *Geophys. Res. Lett.* **37**, 2–6 (2010).

39.   Read, J. S. *et al.* Lake-size dependency of wind shear and convection as controls on gas

exchange. *Geophys. Res. Lett.* **39**, 1–5 (2012).

40.   Soloviev, A., Donelan, M., Graber, H., Haus, B. & Schlüssel, P. An approach to

estimation of near-surface turbulence and CO_2 transfer velocity from remote sensing data.

66, 182–194 (2007).

41.   Wüest, A. & Lorke, A. Small-scale hydrodynamics in lakes. *Annu. Rev. Fluid Mech.* **35**,

373–412 (2003).

42.   Goudsmit, G.-H. Application of k-ε turbulence models to enclosed basins: The role of

internal seiches. *J. Geophys. Res.* **107**, 3230 (2002).

43.   Driedonks, A. G. M. Models and observations of the growth of the atmospheric boundary

layer. *Boundary-Layer Meteorol.* **23**, 283–306 (1982).

44.   Batchvarova, E. & Gryning, S.-E. Applied model for the growth of the daytime mixed

layer. *Boundary-Layer Meteorol.* **56**, 261–274 (1991).

45.   Zilitinkevich, S. & Mironov, D. V. A multi-limit formulation for the equilibrium depth of

a stably stratified boundary layer. *Boundary-Layer Meteorol.* **81**, 325–351 (1996).

46.   Zilitinkevich, S. S. *Turbulent Penetrative Convection*. (Avebury Technical, 1991).

47.   Gryning, S.-E. & Batchvarova, E. Analytical model for the growth of the coastal internal

boundary layer during onshore flow. *Q. J. R. Meteorol. Soc.* **116**, 187–203 (1990).

48.   Kaelo, P. & Ali, M. M. Some variants of the controlled random search algorithm for

global optimization. *J. Optim. Theory Appl.* **130**, 253–264 (2006).

49.   Powell, M. J. D. A direct search optimization method that models the objective and

constraint functions by linear interpolation. in *Advances in Optimization and Numerical*

Analysis 51–67 (1994).

50.   Bezanson, J., Edelman, A., Karpinski, S. & Shah, V. B. Julia: A Fresh Approach to

Numerical Computing. *SIAM Rev.* (2014).

51.   Rackauckas, C. & Nie, Q. DifferentialEquations.jl – A Performant and Feature-Rich

Ecosystem for Solving Differential Equations in Julia. *J. Open Res. Softw.* **5**, 15 (2017).

52.   Johanson, S. G. The NLopt nonlinear-optimization package. (2018). Available at:

http://ab-initio.mit.edu/nlopt. (Accessed: 11th December 2018)

(a) Thermocline deepening

(b) Transport of stored methane

(c) Growth of MOB

(d) Methane emissions

(a) Convective regime

Normalized flux [-]

— methane supply per area at mixed layer interface
— methane supply per volume
— methane oxidation capacity per volume

(b) Wind-driven regime

convection ——— **main contribution to thermocline deepening** ——— wind

3 day event
0.5 day event

Fraction of stored CH_4 emitted to atmosphere

Mixed layer depth [m]

Wind-speed [km h^{-1}]