Automated methods enable direct computation on phenotypic descriptions for novel candidate gene prediction

Ian R. Braun[1,2] and Carolyn J. Lawrence-Dill[1,2,3]

[1]Department of Genetics, Development, and Cell Biology; Iowa State University, Ames, IA 50011

[2]Interdepartmental Bioinformatics and Computational Biology; Iowa State University, Ames, IA 50011

[3]Department of Agronomy; Iowa State University, Ames, IA 50011

July 3, 2019

1 Abstract

Natural language descriptions of plant phenotypes are a rich source of information for genetics and genomics research. We computationally translated descriptions of plant phenotypes into structured representations that can be analyzed to identify biologically meaningful associations. These representations include the EQ (Entity-Quality) formalism, which uses terms from biological ontologies to represent phenotypes in a standardized, semantically-rich format, as well as numerical vector representations generated using Natural Language Processing (NLP) methods (such as the bag-of-words approach and document embedding). We compared resulting phenotype similarity measures to those derived from manually curated data to determine the performance of each method. Computationally derived EQ and vector representations were comparably successful in recapitulating biological truth to representations created through manual EQ statement curation. Moreover, NLP methods for generating vector representations of phenotypes are scalable to large quantities of text because they require no human input. These results indicate that it is now possible to computationally and automatically produce and populate large-scale information resources that enable researchers to query phenotypic descriptions directly.

2 Background

Phenotypes encompass a wealth of important and useful information about plants, potentially including states related to fitness, disease, and agricultural value. They comprise the material on which natural and artificial selection act to increase fitness or to achieve desired traits, respectively. Determining which genes are associated with traits of interest and understanding the nature of these relationships is crucial for manipulating phenotypes. When causal alleles for phenotypes of

interest are identified, they can be selected for in populations, targeted for deletion, or employed as transgenes to introduce desirable traits within and across species. The process of identifying candidate genes and specific alleles associated with a trait of interest is called candidate gene prediction.

Genes with similar sequences often share biological functions and therefore can create similar phenotypes. This is one reason sequence similarity search algorithms like BLAST are so useful for candidate gene prediction (Altschul et al., 1990). However, similar phenotypes can also be attributed to the function of genes that have no sequence similarity. This is how protein-coding genes that are involved in different steps of the same metabolic pathway or transcription factors involved in regulating gene expression contribute to shared phenotypes. For example, knocking out any one of the many genes involved in the maize anthocyanin pathway can result in pigment changes (reviewed in Sharma et al., 2011). This concept is modelled in Figure 1, where, notably, the sequence-based search with Gene 1 as a query can only return genes with similar sequences, but querying for similar phenotypes to those associated with Gene 1 returns many additional candidate genes.

High-throughput and computational phenotyping methods are largely sensor and image-based (Fahlgren, Gehan, and Baxter, 2015). These methods can produce standardized datasets such that *e.g.*, an image dataset can be interrogated using an image as the query (Gehan et al., 2017; Green et al., 2012; Miller et al., 2017). However, while such methods are adept at comparing phenotypic information between plants that are physically similar, they are limited in their ability to transfer this knowledge between physically dissimilar species. For example, traits such as leaf angle vary greatly among different species, and therefore cannot be compared directly. Moreover, where shared pathways and processes are conserved across broad evolutionary distances, it can be hard to identify equivalent phenotypes. McGary et al. call these non-obvious shared phenotypes phenologs (2010). Between species, phenologs may present as equivalent properties in disparate biological structures (Braun et al., 2018). For example, Arabidopsis KIN-13A mutants and mouse KIF2A mutants both show increased branching in single-celled structures, but with respect to neurons in mouse (Homma et al., 2003) and with respect to trichomes in Arabidopsis (Lu et al., 2004). Taken together, the ability to compute on phenotypic descriptions to identify phenologs within and across species has the potential to aid in the identification of novel candidate genes that cannot be identified by sequence-based methods alone and that cannot be identified via image analysis.

In order to identify phenologs, some methods rely on searching for shared orthologs between causal gene sets (McGary et al., 2010; Woods et al., 2013). For example, McGary et al. identified a phenolog relationship between 'abnormal heart development' in mouse and 'defective response to red light' in Arabidopsis by identifying four orthologous genes between the sets of known causal genes in each species (2010). However, these methods are not applicable when the known causal gene set for one phenotype or the other is small or non-existent. In these cases, using natural language descriptions to identify phenologs avoids this problem by relying only on characteristics of the phenotypes, per se. These phenotypic descriptions are a rich source of information that, if leveraged to identify phenolog pairs, can enable identification of novel candidate genes potentially involved in generating phenotypes beyond what has already been described.

Unfortunately, computing on phenotype descriptions is not straightforward. Text descriptions of phenotypes present in the literature and in online databases are irregular because natural language representations of even very similar phenotypes can be highly variable. This makes reliable

quantification of phenotype similarity particularly challenging (Thessen, Cui, and Mozzherin, 2012; Braun et al., 2018). To represent phenotypes in a computable manner, researchers have recently begun to translate and standardize phenotype descriptions into Entity-Quality (EQ) statements composed of ontology terms, where an Entity (e.g., 'leaf') is modified by a Quality (e.g., 'increased length'; Mungall et al., 2010). Using this formalism, complex phenotypes are represented by multiple EQ statements. For example, multiple EQ statements are required to represent dwarfism, where the entity and quality pairs ('plant height', 'reduced') and ('leaf width', 'increased') may be used, among others. Each of these phenotypic components of the more general phenotype is termed a 'phene'. Because both entities and qualities are represented by terms from biological ontologies (fixed vocabularies arranged as hierarchical concepts in a directed acyclic graph), quantifying the similarity between two phenotypes that have been translated to EQ statements can be accomplished using graph-based similarity metrics (Hoehndorf, Schofield, and Gkoutos, 2011).

Oellrich, Walls et al. (2015) developed Plant PhenomeNET, an EQ statement-based resource primarily consisting of a phenotype similarity network containing phenotypes across six different model plant species, namely Arabidopsis (*A. thaliana*), maize (*Z. mays* ssp. *mays*), tomato (*S. lycopersicum*), rice (*O. sativa*), Medicago (*M. truncatula*), and soybean (*G. max*). Their analysis demonstrated that the method developed by Hoehndorf et al. (2011) could be used to recover known genotype to phenotype associations for plants. The authors found that highly similar phenotypes in the network (phenologs) were likely to share causal genes that were orthologous or involved in the same biological pathways. In constructing the network, text statements comprising each phenotype were converted by hand into EQ statements primarily composed of terms from the Phenotype and Trait Ontology (PATO; Gkoutos et al., 2005), Plant Ontology (PO; Cooper et al., 2013), Gene Ontology (GO; Ashburner et al., 2000), and Chemical Entities of Biological Interest (ChEBI; Hastings et al., 2013) ontology.

The success of this plant phenotype pilot project was encouraging, but to scale up to computing on all phenotypes represented in the six species' respective model organism databases was not a reasonable goal given that curating data for this pilot project took a good deal of time and covered only phenotypes of dominant alleles for 2,747 genes across the six species. More specifically, human translation of text statements into EQ statements is the most time consuming aspect of generating phenotype similarity networks using this method. Automation of this translation promises to increase the rate at which such networks can be generated and expanded. Notable efforts to automate this process include Semantic Charaparser (Cui, 2012, Cui et al., 2015), which extracts characters (entities) and their corresponding states (qualities) after a curation step that involves assigning terms to categories, and then mapping these characters and states to EQ statements constructed from input ontologies. Other existing annotation tools such as NCBO Annotator (Musen et al., 2012) and NOBLE Coder (Tseytlin et al., 2016) are fully automated, relying only on input ontologies. Both map words in the input text to ontology terms without imposing an EQ statement structure. State-of-the-art machine learning approaches to annotating text with ontology terms also have been developed (Hailu et al., 2019). These can be trained using a dataset such as the Colorado Richly Annotated Full-Text corpus (CRAFT; Bada et al., 2012), but are not readily transferable to ontologies that are not represented in the training set.

In addition to using ontology-based methods, similarity between text descriptions of phenotypes can also be quantified using natural language processing (NLP) techniques such as treating each description as a bag-of-words and comparing the presence or absence of those words between descriptions, or using neural network-based tools such as Doc2Vec to embed descriptions into abstract

high-dimensional numerical vectors between which similarity metrics can then be easily applied (Le and Mikolov, 2014). Conceptually, this process involves converting natural language descriptions into locations in space, such that descriptions that are near each other are interpreted as having high similarity and those that are distant have low similarity.

In this work, we used a combination of existing automated annotation tools, current methods in NLP, and simple machine learning techniques to analyze phenotypes represented in the dataset reported by Oellrich, Walls et al. (2015). We evaluated the performance of these computational methods for generating similarity networks comparable to networks derived from the hand-curated datasets they reported (see Figure 2 for an experimental overview concept overview). Results demonstrate that fully automated approaches can be used to recover known biological relationships among phenotypes and causal genes. Most importantly, we describe how to use these methods to automatically generate the datasets necessary to identify phenotypic similarities within and across species without requiring the use of time-consuming and costly hand-curation.

3 Methods

3.1 Dataset of Phenotypic Descriptions and Curated EQ Statements

The pairwise phenotype similarity network described in Oellrich, Walls et al. (2015) was built based on a dataset of phenotype descriptions across six different model plant species (*A. thaliana*, *Z. mays* ssp. *mays*, *S. lycopersicum*, *O. sativa*, *M. truncatula*, and *G. max*). Each phenotype description was split into one or more atomized statements describing individual phenes, each of which mapped to exactly one curated EQ statement (Table 1). The EQ statements in this dataset were primarily built from terms present in PATO, PO, GO, and ChEBI, and in general follow the form

$$\text{primary } E_1 + [\text{primary } E_2] + Q + [QL] + [\text{secondary } E_1] + [\text{secondary } E_2]$$

where optional components are enclosed in square brackets. Entities are given as E_x and the Quality is given as Q which can be additionally described by an optional qualifier term QL. EQ statements were constructed within additional constraints described by Oellrich, Walls et al.; for example, terms from the ChEBI ontology cannot be used to describe the first primary Entity and the Quality must be relational if any secondary entity is present (2015).

3.2 Similarity Metrics

3.2.1 Jaccard Similarity

The Jaccard similarity between two sets is generally defined as the ratio of the cardinalities of the intersection and union of the sets. If $S(t)$ is defined as the set of ontology terms containing both term t and all the terms that are inherited by t through the ontology graph's structure, then this metric can be used to calculate the similarity of two terms t_1 and t_2 by first finding $S(t_1)$ and $S(t_2)$ and then applying the Jaccard similarity equation to these sets. Formally this equation is given as

$$J_{\text{sim}}(t_1, t_2) = \frac{|S(t_1) \cap S(t_2)|}{|S(t_1) \cup S(t_2)|}$$

3.2.2 EQ Statement Similarity

Similarity between EQ statements can be measured using Jaccard similarity. An EQ statement inherits all the EQ statements where the Entity and Quality are equivalent to or are a subclass of the Entity and Quality in the original statement respectively. The Jaccard similarity between two EQ statements can then be calculated between the sets of EQ statements that each inherits. We refer to this method as S_1. EQ statements can also be treated as sets of individual ontology terms, taking the union of all terms in the statement and those they inherit. Using this approach, the Jaccard similarity between two EQ statements can then be calculated between the sets of terms representing each statement. We refer to this method as S_2. For phenotypes for which multiple EQ statements are annotated, similarity can be calculated using S_1 by taking the average maximal Jaccard similarity between each EQ statement in one phenotype to any EQ statement in the other. Similarity can be calculated using S_2 by taking the union of the terms for all EQ statements from each phenotype and calculating the Jaccard similarity between those sets.

3.2.3 Partial Precision and Partial Recall

Partial precision and partial recall are metrics that can be used to measure the similarity between a set of target annotations, such as ontology terms assigned by curators, and a set of predicted annotations, such as those generated computationally by an algorithm (Dahdul et al., 2018). We use these metrics to evaluate the performance of methods that computationally perform semantic annotation (mapping ontology terms to input text descriptions) in order to compare the annotations made by these computational methods to the hand-curated annotations produced by Oellrich, Walls et al. (2015).

Partial precision (PP) is defined as the average similarity between each predicted term and the most similar corresponding target term. Corresponding terms are defined as those that were annotated to the same input text. This metric is similar to the traditional notion of binary precision because it captures the fraction of predicted information which is in fact true. Partial recall (PR) is defined as the average similarity between each target term and the most similar corresponding predicted term. Again, this is similar to the concept of binary recall because it captures the fraction of true information which is present in (recalled by) the predicted annotations. Formally these metrics can be given as

$$PP = \frac{1}{m} \sum_{m}^{i=1} \mathrm{argmax}_j J_{\mathrm{sim}}(t_i, t_j) \mathbb{1}\{y(t_i, t_j)\}$$

$$PR = \frac{1}{n} \sum_{n}^{j=1} \mathrm{argmax}_i J_{\mathrm{sim}}(t_j, t_i) \mathbb{1}\{y(t_i, t_j)\}$$

where n is the number of target (curated) terms indexed by j, m is the number of predicted terms indexed by i, t_i is a particular predicted term, t_j is a particular target term, and let $y(t_i, t_j)$ be true if the terms were annotated to the same input text description and false otherwise.

3.3 Methods for Annotating Descriptions with Ontology Terms

Semantic annotation is the process of mapping semantically-rich identifying concepts to text, or to specific words within a larger text. In the case of this work, this process involved mapping ontology terms to phenotype or phene descriptions so that these terms could be used downstream to construct EQ statements. For this task, we used NCBO Annotator, NOBLE Coder, and a Naïve Bayes bag-of-words classifier, all supported by word embedding models to account for variance in word choice. The motivation for using these tools and methods was to determine if semantic annotation could be accomplished on the dataset of phenotype and phene descriptions described in Oellrich, Walls et al. (2015) using techniques that require no manual curation.

3.3.1 NCBO Annotator and NOBLE Coder

The NCBO (National Center for Biomedical Ontology) Annotator (Musen et al., 2012) is a web service available through Bio Portal (Whetzel et al., 2011) that uses the `mgrep` concept recognition algorithm (Dai et al., 2008) to map natural language text inputs to ontology terms from a predefined set of available ontologies. The NOBLE Coder annotation tool (Tseytlin et al., 2016) is another method developed for mapping natural language inputs to ontology terms. NOBLE Coder takes user provided ontology files as reference vocabularies of synonyms and terms, and therefore can be used as a general solution for semantic annotation tasks provided only that ontologies to describe the entities of interest exist. Depending on parameter selections, this annotation tool can account for partial matches between words and ontology terms, matches with alterations in the ordering of words, and matches to multiple ontology terms that overlap in the input text. As output, both of these tools provide a set of ontology terms mapped to the text input, as well as the position within the text to which each term mapped. We used NCBO Annotator with the default set of parameters and NOBLE Coder with both precise and partial matching.

3.3.2 Naïve Bayes Classifier

A Naïve Bayes classifier was used to determine a probability $p(t|w)$ for each term t and bag-of-words (un-ordered list of words) w representing a given phenotype or phene description, where $p(t|w) = p(t) \prod_{i=1}^{n} p(w_i|t)$ and the bag-of-words contains n individual words indexed by i. This value reflects the probability that t should be annotated to the description given the words present in that description. The values of $p(t)$ and $p(w_i|t)$ were obtained from a fold of training data drawn from the dataset of phenotype and phene descriptions by looking at the frequency of t in the curated EQ statements and co-occurrence of t in an EQ statement with w_i in the corresponding phenotype or phene description, respectively. Four disjoint folds of training data were used across the dataset to obtain predicted annotations for all of the phenotype and phene descriptions. In each testing data fold, the k terms of an ontology O with the highest values of $p(t|w)$ were output as annotations where k is the average number of terms from O per description in the corresponding training data multiplied by number of descriptions in the testing data. The motivation for including this method is that the Naïve Bayes classifier is capable of learning arbitrary associations between text and terms annotated to that text by curators, and unlike NCBO Annotator and NOBLE Coder, does not explicitly take into account any syntactic similarity between the text and terms.

3.3.3 Variation in Vocabulary

Word embeddings generated with Word2Vec (Mikolov et al., 2013) were incorporated to support the semantic annotation process using the above tools and methods. A model pre-trained on Wikipedia was used (Lau and Baldwin, 2016). For a particular threshold value, related words were defined as any pair of words with cosine similarity between vector representations greater than that value given the Word2Vec model. For NOBLE Coder, related words obtained through this method at a particular threshold were incorporated by inputting multiple versions of each phenotype or phene description, where additional versions were generated by iteratively substituting each word for any available related words. For the Naïve Bayes classifier, related words obtained using this method were accounted for during training when estimating the probabilities for $p(w_i|t)$. The frequency of each word w_i observed in the data for a given term t was increased simultaneously with the frequency of any word related to w_i for that term, even though that related word was not explicitly contained within the phenotype or phene description. In this way, words were associated with terms even if those words were not explicitly present within the dataset of phenotypic descriptions.

3.4 Constructing EQ Statements

3.4.1 Aggregating Ontology Terms

The terms annotated by each method were combined into an aggregated set of candidate ontology terms from which EQ statements were constructed. In aggregating these annotations, the union of the individual sets of annotations was taken. Terms annotated with NOBLE Coder using the precise matching parameter and NCBO Annotator were assigned a score of 1, terms annotated with NOBLE Coder using the partial matching parameters were scored based on the alignment score between the text representing the term and the portion of the description it matched, and terms annotated with the Naïve Bayes method were assigned as a score the probability $p(t|w)$ determined by the model. When aggregating terms, the maximum score for a term was retained if it was annotated by more than one method. Similarly, if two methods identified different words from the phenotype or phene description that a given term mapped to, the union of those sets of words was retained.

3.4.2 Combining Terms to Form EQ Statements

The aggregate set of ontology terms annotated to each phene or phenotype description were used to generate EQ statements. First, if no Entity terms (from PO, GO, or ChEBI) were present in the aggregated set, then the default subject term *whole plant* (PO:0000003) was added to the set of terms. If the set contained a biological process term from GO then *process quality* (PATO:0001236) was added to the set if not already present. All possible EQ statements (adhering to the format described by Oellrich, Walls et al., 2015) were then generated. From these generated EQ statements, any in which an Entity term overlapped with a Quality term were removed. (Overlapping terms in this case are defined as two terms that have an overlap in the set-of-words from the text description that was associated with those terms by the semantic annotation methods.) EQ statements were ranked by the average scores assigned during semantic annotation to ontology terms from which

they were composed, then by the fraction of the words in the text description directly corresponding to an ontology term in the EQ statement. Up to the k highest ranked EQ statements were retained for each text description, with $k = 4$ being the default value and used for the results described here.

3.5 Characterizing High-Quality EQ Statements

3.5.1 Generating Dependency Graphs

Phene and phenotype descriptions were processed using the Stanford CoreNLP pipeline (Manning et al., 2015), and the neural net dependency parser module of the pipeline was used with default parameters to generate a dependency graph of each description. Dependency graphs have nodes corresponding to tokens (generally words), and directed edges describing grammatical dependencies between these tokens. For example, the adjective 'insensitive' might depend on the noun 'growth', which it modifies. In a dependency graph, this is represented by a directed 'dependent' edge from the 'insensitive' node to the 'growth' node (Figure 3).

3.5.2 Mapping Ontology Terms to Dependency Graph Nodes

The ontology terms mapped to each description during semantic annotation were mapped (where possible) to specific node sets within the dependency graph (as in Figure 3). For example, if NCBO Annotator mapped the term *green* (PATO:0000320) to the word 'green' in a phene description, then at this step that term was mapped to the node representing the word 'green' in the corresponding dependency graph. With each ontology term mapped to a set of nodes within the dependency graph, the relationship between any two terms (t_1 and t_2) in an EQ statement can be described by the shortest undirected path between any node mapped to t_1 and any node mapped to t_2. As a result, an EQ statement as a whole can be described by the set of minimal paths between the nodes corresponding to a set of pairs of ontology terms in the EQ statement. Specifically, we looked at the minimal paths between two terms that make up a compound Entity (primary E_1 and E_2, or secondary E_1 and E_2), between the primary Entity and the Quality, and between the primary Entity and the secondary Entity (when a relational Quality is present). For all phenotypic descriptions where the computationally annotated ontology terms match those present in the hand-curated EQ statements, we quantified the minimal path lengths of each type in order to determine whether consistent dependency graph path lengths existed within high-quality EQ statements.

3.6 Generating Document Embeddings of Descriptions

In addition to generating EQ statements for each phenotype and phene description in the dataset, Doc2Vec was used for generating numerical vectors for each description. A model pre-trained on Wikipedia was used (Lau and Baldwin, 2016). In these document embeddings, positions within the vector do not refer to the presence of specific words but rather abstract features learned by the model. A size of 300 was used for each vector representation, which is the fixed vector size of the pre-trained model. In addition, vectors were generated for each description using bag-of-words and set-of-words representations of the text. For these methods, each position within the vector

refers to a particular word in the vocabulary. Each vector element with bag-of-words refers to the count of that word in the description, and each vector element with set-of-words is a binary value indicating presence or absence of the word. In cases where phene descriptions were used instead of phenotype descriptions, the descriptions were concatenated prior to embedding to obtain a single vector.

3.7 Creating Gene/Phenotype Networks

Oellrich, Walls et al. (2015) developed a network with phenotypes as nodes and similarity between them as edges for all the phenotypes in the dataset. For each type of text representations that we generated with computational methods, comparable networks were constructed. For EQ statement representations, similarity metrics described above were used to determine edge values. For vector representations generated using Doc2Vec and bag-of-words, cosine similarity was used. For the vector representations generated using set-of-words, Jaccard similarity was used. These networks are considered to be simultaneously gene and phenotype similarity networks, because each phenotype in the dataset corresponds to a specific causal gene, and a node in the network represents both that causal gene and its cognate phenotype. However, two phenotype descriptions corresponding to the same gene are retained as two separate nodes in the network, so while each node represents a unique gene/phenotype pair, a single gene may be represented within more than one node.

4 Results

4.1 Performance of Computational Semantic Annotation Methods for Reproducing Hand-Curated Annotations

The performance of each automated semantic annotation method we tested was evaluated based on the phenotype and phene descriptions available in the hand-curated dataset developed by Oellrich, Walls et al. (2015). Specifically, the ontology terms mapped by each method to a particular description were compared against the terms present in the EQ statement(s) that were created by hand-curation for that same description. Metrics of partial precision (PP) and partial recall (PR), as well as the harmonic mean of these values (PF_1) as a summary statistic were used to evaluate performance (Table 2).

NOBLE Coder and NCBO Annotator generally produced semantic annotations more similar to the hand-curated dataset using phenotype descriptions as input than using the set of phene descriptions as input, a result consistent across ontologies. We considered this to be counter-intuitive, because the phene descriptions are more directly related to the individual EQ statements in terms of semantic content. However, the set of target ontology terms considered correct is larger in the case of the phenotype descriptions because this set of terms includes all terms in any EQ statements derived from that phenotype rather than a single EQ statement, which could contribute to this measured increase in both partial recall and partial precision. Accounting for synonyms and related words generated through Word2Vec models increased PR in the case of specific annotation methods as the threshold for word similarity was decreased (from 1.0 to 0.5) but did not increase PF_1 in any instance due to the corresponding losses in PP (Figure 4).

NOBLE Coder and NCBO Annotator performed comparably in the case of each type of text description and ontology, with NOBLE Coder using the precise matching parameter slightly outperforming the other annotation method with respect to these particular metrics for these particular descriptions. Both outperformed the Naïve Bayes classifier, for which performance dropped significantly for the ontologies with smaller relative representation in the dataset (GO and ChEBI) as might be expected. When the results were aggregated, the increase in partial recall for PATO, PO, and GO terms relative to the maximum recall achieved by any individual method indicates that the curated terms that were recalled by each method were not entirely overlapping. This is as expected given that different methods used for semantic annotation recalled target (curated) ontology terms to different degrees, as measured by Jaccard similarity of a given target term to the closest predicted term annotated by that particular method. These sets of obtained similarities to target terms were comparable between NCBO Annotator and NOBLE Coder ($\rho = 0.84$ with phene descriptions and $\rho = 0.86$ with phenotype descriptions), and dissimilar between either of those methods and the Naïve Bayes classifier ($\rho < 0.10$ in both cases for either type of description), using Spearman rank correlation adjusted for ties.

4.2 Dependency Graph Trends for Hand-Curated EQ Statements

Dependency graphs were generated for all the phene descriptions using the Stanford CoreNLP parser, and undirected minimal paths between words mapped to the ontology terms in the corresponding curated EQ statements were calculated. The distribution of non-zero path lengths between pairs of ontology terms were calculated (Table 3). The mode path length between the primary entity and quality was 1, as was the mode path length between two terms describing a single entity. The mode path length between the primary and secondary entity was 2. These results indicate trends in how ontology terms within the EQ statement structure relate to dependency graphs of the natural language to which they were annotated. This result indicates that there is potential to leverage these trends towards interpreting the plausibility of a computationally generated EQ statement against the text description for which it was predicted.

4.3 Directly Comparing Curated and Predicted Similarity Networks

Oellrich, Walls et al. (2015) developed a network with phenotype/gene pairs as nodes and similarity between them as edges for all phenotypes in the dataset. In this work, comparable networks were constructed for the same dataset using a number of computational approaches for representing phenotype and phene descriptions and for predicting similarity. For the purposes of this assessment, the network built from curated EQ statements and described in Oellrich, Walls et al. (2015) is considered the gold standard against which each network we produced is compared. The predicted and gold standard networks were compared using the F1 metric to assess similarity in predicted phenolog pairs at a range of k values where k is the allowed number of phenolog pairs predicted by the networks (the k most highly valued edges). Results are reported through k=583,971, which is the number of non-zero similarities between phenotypes in the gold standard network, and were repeated using phenotype descriptions and phene descriptions as inputs to the computational methods (Figure 5). The simplest NLP methods for assessing similarity (set-of-words and bag-of-words) consistently recapitulated the gold standard network the best using phenotype descriptions, whereas the document embedding method using Doc2Vec outperformed these methods for values

of $k \leq 200{,}000$ based on phene descriptions. The differences in the performance of each method are robust to 80% subsampling of the phenotypes present in the dataset.

4.4 Computational Methods Outperform Hand-Curation for Gene Functional Categorization in Arabidopsis

Lloyd and Meinke (2012) previously organized a set of Arabidopsis genes with accompanying phenotype descriptions into a functional hierarchy of groups (*e.g.* 'morphological'), classes (*e.g.* 'reproductive'), and finally subsets (*e.g.* 'floral'), in order from most general to most specific. See Supplemental Table 1 in Lloyd and Meinke (2012) for a full specification of this hierarchy to which the genes were assigned. Oellrich, Walls et al. (2015) later used this set of genes and phenotypes to validate the quality of their dataset of hand-curated EQ statements by reporting the average similarity of phenotypes (translated into EQ statements) that belonged to the same functional subset. We used this same functional hierarchy categorization and a similar approach to assess the utility of computationally generated representations of phenotypes towards correctly categorizing the functions of the corresponding genes, and to compare this utility against that of the dataset of hand-curated EQ statements. For each class and subset in the hierarchy, the mean similarity between any two phenotypes related to genes within that class or subset ('within' mean) was quantified using each computable representation of interest, and compared to the mean similarity between a phenotype related to a gene within that class or subset and one outside of it ('between' mean), quantified in terms of standard deviation of the distribution of all similarity scores generated for each given method. The difference between the 'within' mean and 'between' mean (referred to here as the Consistency Index) for each functional category for each method indicates the ability of that method to generate strong similarity signal for phenotypes in this dataset that share that function (Figure 6). In the case of these data, most computational methods using either phene or phenotype descriptions as the input text were able to recapitulate the signal present in the network Oellrich, Walls et al. (2015) generated from hand-curated EQ statements, and the simplest NLP methods (bag-of-words and set-of-words) produced the most consistent signal.

In order to more directly compare each method on a general classification task, networks constructed from curated EQ statements and those generated using each computational method were used to iteratively classify each Arabidopsis phenotype into classes and subsets. This was accomplished by removing one phenotype at a time and withholding the remaining phenotypes as training data, learning a threshold value from the training data, and then classifying the held out phenotype by calculating its average similarity to each training data phenotype in each class or subset, and classifying it as belonging to any category for which the average similarity to other phenotypes in that category exceeded the learned threshold. Performance on this classification task using each network was assessed using the F1 metric, where the functional category assignments for each gene reported by Lloyd and Meinke (2012) were considered to be the correct classifications (Table 4). The simplest NLP methods (bag-of-words and set-of-words) outperformed the Oellrich, Walls et al. (2015) hand-curated EQ statement network on this classification task in all cases, while using the computationally generated EQ statements or document embeddings generated with Doc2Vec only outperformed the curated EQ statement network in some cases.

4.5 Computational Methods Outperform Hand-Curation for Recovering Genes Involved in Anthocyanin Biosynthesis Both Within and Between Species

Oellrich, Walls et al. (2015) illustrated the utility of using EQ statement representations of phenotypes to provide semantic information necessary to recover shared membership of causal genes in regulatory and metabolic pathways. Specifically, they showed that by querying a six-species phenotype similarity network with the *c2* (*colorless2*) gene in maize, which is involved in anthocyanin biosynthesis, genes *c1*, *r1*, and *b1* (*colorless1*, *red1*, *booster1*) which are also involved anthocyanin biosynthesis in maize are recovered. Querying in this instance is defined as returning other genes in the similarity network, ranked using the maximal value of the edges connecting a phenotype corresponding to the query gene and a phenotype corresponding to each other gene in the network. There are 2,747 genes in the dataset, so querying with one gene returns a ranked list of 2,746 genes. This result was included by Oellrich, Walls et al. (2015) as a specific example of the general utility of the phenotype similarity network to return other members of a pathway or gene regulatory network when querying with a single gene. See Figure 1 for a general illustration of this concept.

To evaluate this same utility in the phenotype similarity networks we generated using computational methods and to compare their utility to that of the network from Oellrich, Walls et al. (2015) generated using hand-curated EQ statements, we first expanded the set of maize anthocyanin pathway genes to include those present in the description of the pathway given by Li et al., (2019), and listed in Supplementary Table 1 of that publication. Of those genes, 10 are present in the Oellrich, Walls et al. (2015) dataset (Table 5). Additionally, we likewise identified the set of Arabidopsis genes known to be involved in anthocyanin biosynthesis (listed in Table 1 of Appelhagen et al., 2014) that were present in the Oellrich, Walls et al. (2010) dataset. This yielded a total of 16 Arabidopsis genes (Table 6).

4.5.1 Recovering Anthocyanin Biosynthesis Genes Within a Single Species

Using each phenotype similarity network, each anthocyanin biosynthesis gene from one species was iteratively used as a query against the network. The rank of each other gene in the set of anthocyanin biosynthesis genes corresponding to the same species as the query was quantified. We grouped the ranks into bins of width 10 for ranks less than or equal to 50, and combined all ranks greater than 50 into a single bin. For each phenotype similarity network, the mean and standard deviation of the number of anthocyanin biosynthesis genes in each bin was calculated (Figure 7). The average number of pathway genes ranked within the top 10 across all queries was greater for all computationally generated networks than for the network built from hand-curated EQ statements, although variance across the queries was high. In general, computational networks built from predicted EQ statements performed best for this task, whereas the network built using the hand-curated EQs performed the worst. The networks constructed using the numerical vector representations (set-of-words, bag-of-words, and Doc2Vec) were intermediate in performance as a group (Figure 7).

4.5.2 Recovering Anthocyanin Biosynthesis Genes Between Two Species

To determine whether the methods performed similarly both within and across species, we repeated the analysis described in the previous section (4.5.1), but instead of quantifying the ranks of all anthocyanin biosynthesis genes from the same species as the query gene, we quantified the ranks of all anthocyanin genes that derived from the other species. In other words, Arabidopsis genes were used to query for maize genes, and maize genes were used to query for Arabidopsis genes. As shown in Figure 8, the phenotype similarity network constructed from hand-curated EQ statements did not recover (provide ranks of less than or equal to 50) any of the anthocyanin biosynthesis genes when queried with genes from the other species. Networks generated using the set-of-words and bag-of-words approaches, or with Doc2Vec, performed similarly. Networks built from computationally generated EQ statements recovered the most anthocyanin biosynthesis genes on average across the queries between species (Figure 8).

5 Discussion

5.1 Computationally Generated Phenotype Representations are Useful

A primary purpose for generating representations of phenotypes that are easy to compute on (EQ statements, vector embeddings, etc.) is to construct similarity networks that enable the use of one phenotype as a query to retrieve similar phenotypes. This process serves as a means of discovering relatedness between phenotypes (potential phenologs) within and across species, thus generating hypotheses about underlying genetic relatedness (reviewed in Oellrich, Walls et al., 2015).

The computational methods discussed in this work were demonstrated to only partially recapitulate the phenotype similarity network constructed by Oellrich, Walls et al. (2015) using hand-curated EQ statements (Section 4.3). Despite the limited similarity between the network built from hand-curated annotations and the computationally generated networks, the computationally generated networks performed as well or better than the hand-curated network (based on curated EQ statements) in terms of correctly organizing phenotypes and their causal genes into functional categories at multiple hierarchical levels (Section 4.4). In addition, each computationally generated network performed better than the hand-curated network for querying with either maize or Arabidopsis anthocyanin biosynthesis genes to return other anthocyanin biosynthesis genes from the same species (Section 4.5.1), a task originally used to demonstrate the utility of the phenotype similarity network constructed in Oellrich, Walls et al. (2015).

Moreover, the networks built from computationally generated EQ statements were useful for recapturing anthocyanin biosynthesis genes from a species different than the species of origin for the queried gene/phenotype pair. None of the other networks, including the network built from curated EQ statements, exhibited this utility for this task (Section 4.5.2). This particular result indicates that high accuracy of constructed EQ statements, as it pertains to the relationship between the Entity and Quality, is not specifically necessary for tasks such as querying for related genes across species, because potentially inaccurate (computationally predicted) EQ statements generated a more successful network for the task. For purely computational representations of phenotype descriptions, this result suggests that a 'bag-of-ontology-terms' approach should perform just as

well or better on similar querying tasks than attempting to computationally generate fully logical EQ statements. Replicating these analyses with phenotype descriptions in a different biological domain, such as vertebrates, would determine whether these results generalize to additional species groups and datasets.

Taken together, these results over this particular dataset of phenotype descriptions suggest that while the EQ statements generated through manual curation are likely the most accurate and informative computable representation of a given phenotype in specific cases, other representations generated entirely computationally with no human intervention are capable of meeting or exceeding the performance of the hand-curated annotations on dataset-wide tasks such as sorting phenotypes and genes into functional categories, as well as in the case of specific tasks such as querying with particular genes to recover other genes involved in the same pathway. Therefore, in cases where the volume of data is large, the results are understood to be predictive, and manual curation is impractical, using automated annotation methods to generate large-scale phenotype similarity networks is a worthwhile goal and can provide biologically relevant information that can be used for hypothesis generation, including novel candidate gene prediction.

5.2 Multiple Approaches to Representing Natural Language are Useful

EQ statement annotations comprised of ontology terms allow for interoperability with compatible annotations from varied data sources. They are also a human-readable annotation format, meaning that a knowledgeable human could fix an incorrect annotation by selecting a more appropriate ontology term (a process that is not possible using abstract vector embeddings). Their uniform structure also provides a means of explicitly querying for phenotypes involving a biological entity that is similar to some structure or process (*e.g.*, trichomes) or matches some quality (*e.g.*, an increase in physical size). Ontology-based annotations have the potential to increase the information attached to a phenotype (through inferring ancestral terms which are not specifically referred to in the phenotype description), but do not necessarily fully capture the detail and semantics of the natural language description.

For this reason, future representations of phenotypes in relational databases for the purpose of generating phenotype similarity networks across a large volume of phenotypes described in literature and in databases likely should include both ontology-based annotations describing the phenotypes, as well as the original natural language descriptions. Although the number of phenotypes in the dataset used here and described in Oellrich, Walls et al. (2015) is relatively small, the results of this work suggest utility of original text representations as a powerful means of calculating similarity between phenotypes, especially within a single species. Computationally generated EQ statements, which in the context of this study do not often meet the criteria for a fully logical curated EQ statement, were demonstrated to be more useful in any other approach for recovering biologically related genes across species.

Ensemble methods are often applied in the field of machine learning, where multiple methods are used to solve a problem, with a higher-level model determining which method will be most useful in solving each new instance of the problem. It is possible that such an approach could be applied to measuring similarity between phenotypes to generate a single large-scale network, where similarity values are based on the best possible method to assess the text representations of each pair of particular phenotypes.

5.3 Additional Challenges with EQ Statement Representation

Although ontology terms and EQ statements composed of ontology terms are an information-rich representation of phenes and phenotypes, flexibility in which terms and statements can represent a particular phenotype can limit the ability to computationally recognize true biological similarity. The graph structures of the ontologies themselves, the metrics used to assess semantic similarity, and the ambiguity inherent in both natural language and EQ statement representations of phenes and phenotypes can all potentially contribute to this problem.

As one example in the Oellrich, Walls et al. (2015) dataset used here, the phene description 'complete loss of flower formation' was annotated with an EQ statement whose entity is *flower development*, whereas the computationally identified entity using the methods described in this work was *flower formation*. In this instance, the Jaccard similarity between these two ontology terms was 0.286, which by comparison is less than the Jaccard similarity between *flower formation* and *leaf formation* in the context of the ontology graph. This selected example illustrates the possible discrepancies between true biological similarity and semantic similarity as measured using graph-based metrics. Although each semantic similarity metric calculates this value differently, those that use the hierarchical nature of the ontology are all constrained by the structure of the graph itself.

Variation in how humans and computational methods interpret how a phenotype as a whole should be conceptualized also has the potential to produce representations that obscure true similarity, as measured by graph-based metrics. In another example from the Oellrich, Walls et al. (2015) dataset, the phene description 'stamens transformed to pistils' was annotated with two different EQ statements. The first EQ statement uses the relational quality *has fewer parts of type* to indicate the absence of stamen in this phenotype, and the second uses the relational quality *has extra parts of type* to indicate the presence of pistils in this phenotype. This representation of the phenotype makes logical sense, but is not easy to generate computationally because it abstractly describes the outcome of the transformation that is explicitly present in the natural language description, and is dissimilar from computationally generated representations that focus on the explicit content (*i.e.*, those which use the relational quality *transformed to*).

5.4 Extending this Work to the Wealth of Text Data available in Databases and the Literature

We plan to apply the methods of semantic annotation, ontology-based semantic similarity calculation, and natural language-based semantic similarity calculation to the wealth of text data available in existing plant model organism databases and biological literature. For the latter, doing so will involve the additional challenge of extracting phenotypes descriptions as well as the genes causative to those phenotypes as a separate identification and processing step. We plan to leverage existing work in the areas of named entity recognition specific to genes (Wei, Kao, and Lu, 2015) and relation extraction, as well as existing methods for extracting information related to phenotypes such as those developed using vector-based representations of phenotype descriptions (Xing et al., 2018) and grammar-tree representations of phenotype descriptions (Collier et al., 2015). These next steps are anticipated to enable researchers to begin to compute on phenotype descriptions directly, and will drive a promising future for forward genetics research approaches where phenotypes can be

used for novel candidate gene prediction as easily as sequence similarity searches can be used to identify putative homologs from sequence data.

Data Availability

The dataset of phenotype and phene descriptions and the corresponding hand-curated EQ statements used in this work are available as supplemental data of Oellrich, Walls et al. (2015). The hierarchical functional categorization of the set of Arabidopsis genes used in this work is available as supplemental data of Lloyd and Meinke (2012). The code used to produce the results of this work is available at `github.com/irbraun/phenologs`. Files necessary to reproduce the discussed results, datasets used to generate figures presented in this work, and other supplemental files are available at `doi.org/10.5281/zenodo.3255020`.

Acknowledgements

We thank Lisa Harper, Sowmya Vajjala, and Ramona Walls for helpful discussions and suggestions. We are grateful to the NSF Phenotype Ontology RCN (#DBI-0956049) for creating foundations for this work by bringing plant and computational biologists together to develop a common vocabulary and for their support to the Plant Phenotype Pilot Project participants who developed the Oellrich, Walls et al. (2015) datasets that our analyses relied upon.

The authors were supported to carry out this work by an Iowa State University Presidential Interdisciplinary Research Seed Grant, the Iowa State University Plant Sciences Institute Faculty Scholars Program, and the Predictive Plant Phenomics NSF Research Traineeship (#DGE-1545453).

Authors Contribution Statement

IRB and CJLD together contributed conception and design of the study; IRB organized the data; IRB performed the analyses; IRB wrote the manuscript; IRB and CJLD contributed to manuscript revision, read, and approved the submitted version.

References

Altschul, Stephen F. et al. "Basic local alignment search tool". In: *J. Mol. Biol.* (1990). ISSN: 00222836. DOI: `10.1016/S0022-2836(05)80360-2`.

Appelhagen, Ingo et al. "Update on transparent testa mutants from Arabidopsis thaliana: characterisation of new alleles from an isogenic collection". In: *Planta* (2014). ISSN: 14322048. DOI: `10.1007/s00425-014-2088-0`.

Ashburner, Michael et al. *Gene ontology: Tool for the unification of biology.* 2000. DOI: `10.1038/75556`.

Bada, Michael et al. "Concept annotation in the CRAFT corpus". In: *BMC Bioinformatics* (2012). ISSN: 14712105. DOI: 10.1186/1471-2105-13-161.

Braun, Ian et al. "'Computable' Phenotypes Enable Comparative and Predictive Phenomics Among Plant Species and Across Domains of Life". In: *Appl. Semant. Technol. Biodivers. Sci.* 2018, pp. 187–206. ISBN: 9783898387330.

Collier, Nigel et al. "PhenoMiner: From text to a database of phenotypes associated with OMIM diseases". In: *Database* (2015). ISSN: 17580463. DOI: 10.1093/database/bav104.

Cooper, Laurel et al. "The plant ontology as a tool for comparative plant anatomy and genomic analyses". In: *Plant Cell Physiol.* (2013). ISSN: 00320781. DOI: 10.1093/pcp/pcs163.

Cui, Hong. "CharaParser for fine-grained semantic annotation of organism morphological descriptions". In: *J. Am. Soc. Inf. Sci. Technol.* (2012). ISSN: 15322882. DOI: 10.1002/asi.22618.

Cui, Hong et al. "CharaParser+EQ: Performance evaluation without gold standard". In: *Proc. Assoc. Inf. Sci. Technol.* (2015). ISSN: 23739231. DOI: 10.1002/pra2.2015.145052010020.

Dahdul, Wasila et al. "Annotation of phenotypes using ontologies: a gold standard for the training and evaluation of natural language processing systems". In: *Database (Oxford).* (2018). ISSN: 17580463. DOI: 10.1093/database/bay110.

Dai, M et al. "An efficient solution for mapping free text to ontology terms". In: *AMIA Summit Transl. Bioinforma.* (2008).

Fahlgren, Noah, Malia A. Gehan, and Ivan Baxter. *Lights, camera, action: High-throughput plant phenotyping is ready for a close-up.* 2015. DOI: 10.1016/j.pbi.2015.02.006.

Gehan, Malia A. et al. "PlantCV v2: Image analysis software for high-throughput plant phenotyping". In: *PeerJ* (2017). DOI: 10.7717/peerj.4088.

Green, Jason M. et al. "PhenoPhyte: A flexible affordable method to quantify 2D phenotypes from imagery". In: *Plant Methods* (2012). ISSN: 17464811. DOI: 10.1186/1746-4811-8-45.

Hailu, Negacy D. et al. "Biomedical Concept Recognition Using Deep Neural Sequence Models". In: *bioRxiv* (2019). DOI: 10.1101/530337. eprint: https://www.biorxiv.org/content/early/2019/01/25/530337.full.pdf. URL: https://www.biorxiv.org/content/early/2019/01/25/530337.

Hastings, Janna et al. "The ChEBI reference database and ontology for biologically relevant chemistry: Enhancements for 2013". In: *Nucleic Acids Res.* (2013). ISSN: 03051048. DOI: 10.1093/nar/gks1146.

Hoehndorf, Robert, Paul N. Schofield, and Georgios V. Gkoutos. "PhenomeNET: A whole-phenome approach to disease gene discovery". In: *Nucleic Acids Res.* (2011). ISSN: 03051048. DOI: 10.1093/nar/gkr538.

Homma, Noriko et al. "Kinesin superfamily protein 2A (KIF2A) functions in suppression of collateral branch extension". In: *Cell* (2003). ISSN: 00928674. DOI: 10.1016/S0092-8674(03)00522-1.

Lau, Jey Han and Timothy Baldwin. "An Empirical Evaluation of doc2vec with Practical Insights into Document Embedding Generation". In: *CoRR* abs/1607.05368 (2016). arXiv: 1607.05368. URL: http://arxiv.org/abs/1607.05368.

Le, Quoc and Tomas Mikolov. "Distributed Representations of Sentences and Documents". In: (2014). arXiv: 1405.4053 [cs.CL].

Manning, Christopher et al. "The Stanford CoreNLP Natural Language Processing Toolkit". In: 2015. DOI: 10.3115/v1/p14-5010.

McGary, K. L. et al. "Systematic discovery of nonobvious human disease models through orthologous phenotypes". In: *Proc. Natl. Acad. Sci.* (2010). ISSN: 0027-8424. DOI: 10.1073/pnas.0910200107.

Mikolov, Tomas et al. "Efficient Estimation of Word Representations in Vector Space". In: (2013). arXiv: 1301.3781 [cs.CL].

Miller, Nathan D. et al. "A robust, high-throughput method for computing maize ear, cob, and kernel attributes automatically from images". In: *Plant J.* (2017). ISSN: 1365313X. DOI: 10.1111/tpj.13320.

Mungall, Christopher J. et al. "Integrating phenotype ontologies across multiple species". In: *Genome Biol.* (2010). ISSN: 14747596. DOI: 10.1186/gb-2010-11-1-r2.

Musen, Mark A. et al. "The National center for biomedical ontology". In: *J. Am. Med. Informatics Assoc.* (2012). ISSN: 10675027. DOI: 10.1136/amiajnl-2011-000523.

Sharma, Mandeep et al. "Identification of the Pr1 Gene Product Completes the Anthocyanin Biosynthesis Pathway of Maize". In: *Genetics* (2011). ISSN: 00166731. DOI: 10.1534/genetics.110.126136.

Thessen, Anne E., Hong Cui, and Dmitry Mozzherin. "Applications of Natural Language Processing in Biodiversity Science". In: *Adv. Bioinformatics* (2012). ISSN: 1687-8027. DOI: 10.1155/2012/391574.

Tseytlin, Eugene et al. "NOBLE - Flexible concept recognition for large-scale biomedical natural language processing". In: *BMC Bioinformatics* (2016). ISSN: 14712105. DOI: 10.1186/s12859-015-0871-y.

Wei, Chih-Hsuan, Hung-Yu Kao, and Zhiyong Lu. "GNormPlus: An Integrative Approach for Tagging Genes, Gene Families, and Protein Domains". In: *Biomed Res. Int.* (2015). ISSN: 2314-6133. DOI: 10.1155/2015/918710.

Whetzel, Patricia L. et al. "BioPortal: Enhanced functionality via new Web services from the National Center for Biomedical Ontology to access and use ontologies in software applications". In: *Nucleic Acids Res.* (2011). ISSN: 03051048. DOI: 10.1093/nar/gkr469.

Woods, John O. et al. "Prediction of gene-phenotype associations in humans, mice, and plants using phenologs". In: *BMC Bioinformatics* (2013). ISSN: 14712105. DOI: 10.1186/1471-2105-14-203.

Xing, Wenhui et al. "A gene-phenotype relationship extraction pipeline from the biomedical literature using a representation learning approach". In: *Bioinformatics*. 2018. DOI: 10.1093/bioinformatics/bty263.

681 **Figure 1.** Conceptual comparison of querying with a gene sequence or its associated phenotypic
682 description. Genes are shown as white ovals. Methods of searching for related genes are shown as
683 light gray boxes. Gray dashed arrows indicate the path from the query gene to the set of genes
684 that are returned from the search. Solid black arrows indicate relationships between genes in a
685 biological pathway or gene regulatory network. Dashed black arrows indicate relationships between
686 the pathway or network and the resulting phenotype.

Figure 2. Overview of computational pipelines used here to generate phenotype similarity networks from text descriptions of phenotypes. Rounded white rectangles represent data in the form of text descriptions as input, or network nodes as output. Rounded black rectangles represent the intermediate data forms that are computable representations of text descriptions. These allow for quantitative similarity metrics to be applied. Gray rectangles represent computational methods carried out at each step. Single-headed arrows represent flow of data through each pipeline. Double-headed arrows represent edges between nodes in resulting similarity networks. Values next to double-headed arrows indicate magnitude of phenotype similarity. One output network is created for each computable representation, but only one example is shown here.

697 **Table 1.** Description of the Oellrich, Walls et al. (2015) dataset in terms of number of phenotype
698 descriptions, phene descriptions, and EQ statements.

Species	Phenotypes	Phenes[1]	EQ statements[2]
Arabidopsis	1385	5172	5172
Maize	117	373	373
Tomato	90	269	269
Rice	86	340	340
Medicago	40	149	149
Soybean	24	61	61
Example gene: Arabidopsis *PKS2* (AT1G14280.1)	Phenotype: short hypocotyl and expanded cotyledon under hourly far red pulses	Phene 1: short hypocotyl	PO:0020100 (hypocotyl) + PATO:0000574 (decreased length)
		Phene 2: expanded cotyledon	PO:0020030 (cotyledon) + PATO:0000586 (increased size)

[1] Also referred to as 'atomized statements'.

[2] Each EQ statement represents a single specific phene.

Dependency Graph

Annotated Terms

$$len(\text{primary } E, Q) = 1$$

Minimal Path Lengths
$$len(E_1, E_2) = 1$$

$$len(\text{primary } E, \text{secondary } E) = 2$$

Figure 3. Example of how minimal path lengths in dependency graphs are identified. Dependency Graph: Words or tokens in phenotype descriptions are represented as nodes in the graph ('NN' and 'JJ' are part-of-speech tags for 'noun' and 'adjective' respectively). Nodes are connected by edges named corresponding to the class of dependency (*e.g.*, 'dep' and 'nmod' are abbreviations for 'dependent' and 'nominal modifier' respectively). Annotated Terms: Ontology terms annotated to the sentences are illustrated as rounded rectangles and are mapped to words (nodes) in the graph, illustrated by bold single-headed arrows. Minimal Path Lengths: The length of minimal paths of interest between nodes mapped to specific terms are shown. For this example, $len(\text{primary } E,Q)=1$ because the path length from E_2 to Q is 1 whereas the path length from E_1 to Q is 2. Because the former is shorter, that path length is chosen as the minimal path length. Image partially constructed using the visualization web tool for Stanford CoreNLP (Manning et al., 2015) found at `http://corenlp.run/`.

 Table 2. Performance metrics for semantic annotation methods.

Annotator	Ontology	n^1	Phenotype Description			Phene Descriptions		
			PP	PR	PF_1	PP	PR	PF_1
NOBLE Coder (precise)	PATO	7882	0.641	0.627	0.634	0.601	0.572	0.586
	PO	5634	0.622	0.380	0.472	0.546	0.294	0.382
	GO	1505	0.514	0.521	0.517	0.510	0.514	0.512
NOBLE Coder (partial)	PATO	7882	0.412	0.748	0.532	0.375	0.689	0.486
	PO	5634	0.309	0.758	0.439	0.269	0.659	0.382
	GO	1505	0.102	0.846	0.182	0.091	0.839	0.165
NCBO Annotator	PATO	7882	0.640	0.619	0.629	0.598	0.563	0.580
	PO	5634	0.550	0.259	0.352	0.458	0.170	0.248
	GO	1505	0.478	0.433	0.454	0.480	0.424	0.450
	ChEBI	775	0.429	0.888	0.579	0.431	0.913	0.586
Naïve Bayes Classifier	PATO	7882	0.517	0.394	0.447	0.642	0.484	0.552
	PO	5634	0.474	0.258	0.334	0.636	0.429	0.512
	GO	1505	0.091	0.073	0.081	0.155	0.157	0.156
	ChEBI	775	0.035	0.031	0.033	0.001	0.001	0.001
Aggregate Annotations[2]	PATO	7882	0.412	0.798	0.543	0.383	0.815	0.522
	PO	5634	0.351	0.809	0.489	0.304	0.831	0.445
	GO	1505	0.107	0.839	0.190	0.090	0.839	0.163
	ChEBI	775	0.366	0.890	0.519	0.305	0.913	0.457

[1] The number of terms from a given ontology in all curated EQ statements in the dataset.
[2] Annotation set formed by taking the union of the annotations from all other methods.

Figure 4. Semantic annotation metrics for methods as Word2Vec similarity threshold is decreased. The threshold indicates the similarity value at which two words are considered the same for the purposes of the semantic annotation step. The lines illustrate metrics calculated based on terms from all ontologies rather than separated by ontology.

718 **Table 3.** Distributions of minimal undirected path lengths between nodes in dependency graphs
719 mapped to terms in high-quality EQ statements.

Term 1	Term 2	n^1	$p(l=1)$	$p(l=2)$	$p(l \geq 3)$
E (primary)	Q	146	0.863	0.110	0.027
E_1	E_2	20	0.700	0.250	0.050
E (primary)	E (secondary)	28	0.286	0.643	0.071

[1] The number of times a path of any non-zero length was observed
between the given terms.

Figure 5. Comparison of phenolog pairs identified by predictive methods in comparison to the Oellrich, Walls et al. (2015) dataset. The x-axis indicates the number of phenologs pairs (highest valued edges in the phenotype similarity network) at each point. The standard deviation of resampling with 80% of the phenotypes in the dataset (network nodes) are indicated by ribbons for each method. Phene descriptions (left) or phenotype descriptions (right) were used as the text input for each particular method.

Figure 6. Heatmap of Consistency Index. The difference between average similarity for two phenotypes within a subset and one phenotype within and one outside, for each functional subset defined in the dataset of Arabidopsis phenotypes, and for each method of quantifying similarity between phenotypes is shown, with darker cells indicating higher consistency within a subset. Differences are measured in standard deviations of the distributions of similarities obtained for each method. The meaning of subset abbreviations are specified in Supplemental Table 1 of Lloyd and Meinke (2012). Methods are listed at left. Input text for calculating similarities between the phenotypes were either derived from phenotype descriptions (top) or phene descriptions (bottom). The far right column in the heatmap refers to an average Consistency Index for a given method across all subsets.

 Table 4. Evaluation (F1 scores) for each method used to categorize Arabidopsis genes by function.

Method	Phenes		Phenotypes	
	Class	Subset	Class	Subset
Curated EQ	0.470	0.359	0.470	0.359
Pred EQ S1	0.472	0.472	0.369	0.320
Pred EQ S2	0.504	0.413	0.437	0.368
Set-of-words	0.613	0.447	0.587	0.426
Bag-of-words	0.595	0.423	0.549	0.409
Doc2Vec	0.455	0.331	0.486	0.377

 Table 5. Maize genes involved in anthocyanin biosynthesis.

Gene Name (Symbol)	Gene Model ID[1]	Category[2]	Encoded Protein[3]
colorless2 (c2)	**GRMZM2G422750**	Enzyme	naringenin-chalcone synthase
chalcone flavonone isomerase1 (chi1)	GRMZM2G155329	Enzyme	chalcone isomerase
red aleurone1 (pr1)	GRMZM2G025832	Enzyme	flavonoid 3'-hydroxylase (flavonoid 3'-monooxygenase)
flavanone 3-hydroxylase1 (fht1; F3H)	GRMZM2G062396	Enzyme	flavonone 3'-hydroxylase (flavonol synthase)
anthocyaninless1 (a1)	**GRMZM2G026930**	Enzyme	dihydroflavonol 4-reductase (flavonone 4-reductase)
anthocyaninless2 (a2)	**GRMZM2G345717**	Enzyme	anthocyanidin synthase (leucoanthocyanidin dioxygenase)
bronze1 (bz1)	**GRMZM2G165390**	Enzyme	flavonol 3-O-glucosyltransferase
bronze2 (bz2)	**GRMZM2G016241**	Enzyme	glutathione transferase (maleylacetoacetate isomerase)
multidrug resistance associated protein3 (mrpa3; ZmMrp4)	GRMZM2G111903	Transporter	multidrug-resistance-like-transporter
scutellar node color1 (sn1)	GRMZM5G822829	TF	bHLH
colorless1 (c1)	**GRMZM2G005066**	TF	R2 R3-MYB
pericarp color1 p1	**GRMZM2G084799**	TF	R2 R3-MYB
purple plant1 (pl1)	**GRMZM2G701063**	TF	R2 R3-MYB
colored1 (r1)	**GRMZM5G822829**	TF	bHLH
colored plant1 (b1)	**GRMZM2G172795**	TF	bHLH
pale aleurone color1 (pac1)	GRMZM2G058432	TF	WD40

[1] Gene model IDs in bold were present in the Oellrich, Walls et al. (2015) dataset.
[2] The abbreviation TF is short for transcription factor.
[3] Enzyme encoded protein names from the Plant Metabolic Network (Schlapfer et al., 2017).

Table 6. Arabidopsis genes involved in anthocyanin biosynthesis.

Gene Name (Symbol)	Locus Name[1]	Category[2]	Encoded Protein[3]
TRANSPARENT TESTA 4 (TT4)	**At5g13930**	Enzyme	naringenin-chalcone synthase
TRANSPARENT TESTA 5 (TT5)	**At3g55120**	Enzyme	chalcone isomerse
TRANSPARENT TESTA 6 (TT6)	**At3g51240**	Enzyme	flavanone 3'-hydroxylase (flavonol synthase)
TRANSPARENT TESTA 7 (TT7)	**At5g07990**	Enzyme	flavonoid 3'-hydroxylase (flavonoid 3'-monooxygenase)
TRANSPARENT TESTA 3 (TT3)	**At5g42800**	Enzyme	dihydroflavonol 4-reductase (flavonone 4-reductase)
TRANSPARENT TESTA 11 (TT11) TRANSPARENT TESTA 17 (TT17) TRANSPARENT TESTA 18 (TT18) TANNIN-DEFICIENT SEED 4 (TDS4)	At4g22880	Enzyme	anthocyanidin synthase (leucoanthocyanidin dioxygenase)
ARABIDOPSIS SIP1 CLADE TRIHELIX 1 (AST1) BANYULS (BAN1)	**At1g61720**	Enzyme	anthocyanidin reductase
TRANSPARENT TESTA 14 (TT14) TRANSPARENT TESTA 19 (TT19)	**At5g17220**	Enzyme	glutathione transerase (maleylacetoacetate isomerase)
AUTOINHIBITED H⁺ - ATPASE (AHA10)	At1g17260	Enzyme	ATP-ase
TRANSPARENT TESTA 10 (TT10)	**At5g48100**	Enzyme	laccase
TRANSPARENT TESTA 5 (TT15)	**At1g43620**	Enzyme	3β-hydroxy sterol glucosyltransferase
TRANSPARENT TESTA 12 (TT12)	**At3g59030**	Transporter	MATEefflux proton antiporter
TRANSPARENT TESTA 16 (TT16)	**At5g23260**	TF	K-box, MADS-box
TRANSPARENT TESTA 1 (TT1)	**At1g34790**	TF	C2H2
TRANSPARENT TESTA 2 (TT2)	**At5g35550**	TF	bHLH
TRANSPARENT TESTA 8 (TT8)	**At4g09820**	TF	bHLH
TRANSPARENT TESTA GLABRA 1 (TTG1)	**At5g24520**	TF	WD40
TRANSPARENT TESTA GLABRA 2 (TTG2)	**At2g37260**	TF	WRKY

[1] Locus names in bold were present in the Oellrich, Walls et al. (2015) dataset.
[2] The abbreviation TF is short for transcription factor.
[3] Enzyme encoded protein names from the Plant Metabolic Network (Schlapfer et al., 2017).

Figure 7. Rankings of anthocyanin biosynthesis genes in either maize (**A**) or Arabidopsis (**B**) upon querying phenotype similarity networks generated with genes from the same species. Phenotype networks are organized by the method used to generate them (columns) and by whether those methods were applied to phenotype or phene descriptions (rows). Rank value specifies a range of rankings for each bar in the plots (1-10, 11-20, etc.) and rank quantity indicates the average number of anthocyanin biosynthesis genes that were ranked in a given range over all queries. Black lines indicate plus and minus one standard deviation of the rank quantities in each range over all queries.

Figure 8. Rankings of anthocyanin biosynthesis genes in either maize (**A**) or Arabidopsis (**B**) upon querying phenotype similarity networks generated with genes from the other species. Phenotype networks are organized by the method used to generate them (columns) and by whether those methods were applied to phenotype or phene descriptions (rows). Rank value specifies a range of rankings for each bar in the plots (1-10, 11-20, etc.) and rank quantity indicates the average number of anthocyanin biosynthesis genes that were ranked in a given range over all queries. Black lines indicate plus and minus one standard deviation of the rank quantities in each range over all queries.