Determining Temporal Stability in Dominance Hierarchies

Vilette C.[1,2], Bonnell T.R.[1,2], Henzi S.P. [1,2], Barrett. L[1,2]

[1] Department of Psychology, University of Lethbridge, 4401 University Drive

Lethbridge, Alberta, Canada, T1K 3M4

[2] Applied Behavioural Ecology and Ecosystems Research Unit, University of South Africa

Corresponding author:

9   Chloé Vilette

Department of Psychology, University of Lethbridge, 4401 University Drive

Lethbridge, Alberta, Canada, T1K 3M4

Email: c.vilette@uleth.ca

Abstract:

1. The importance of social hierarchies has led to the development of many techniques for

inferring social ranks, leaving researchers with an overwhelming array of options to

choose from. Many of our research questions involve longitudinal analyses, so we were

interested in a method that would provide reliable ranks across time. But how does one

determine which method performs best?

2. In this study, we attempt to answer this question. We use a training-testing procedure to

compare 13 different approaches for calculating dominance hierarchies (seven methods,

plus 6 analytical variants of these). We assess each method's performance, its efficiency,

and the extent to which the calculated ranks obtained from the training dataset accurately

predict the outcome of observed aggression in the testing dataset.

3. We found that all methods tested performed well (with one exception), despite some

differences in inferred rank order. With respect to the need for a "burn-in" period to

enable reliable ranks to be calculated, again, all methods were efficient and able to infer

reliable ranks from the very start of the study period (i.e., with little to no burn-in period).

Using a common 6-month burn-in period to aid comparison, we found that all methods

could predict aggressive outcomes accurately for the subsequent 10 months. Beyond this

10-month threshold, accuracy in prediction decreased as the testing dataset increased in

length. The decay was rather shallow, however, indicating overall rank stability during

this period.

4. In general, a training-testing approach allows researchers to determine the most

appropriate method for their dataset, given sampling effort, the frequency of agonistic

interactions, the steepness of the hierarchy, and the nature of the research question being

asked. Put simply, we did not find a single best method, but our approach offers

researchers a valuable tool for identifying the method that will work best for them.

1. <u>**Introduction**</u>

"Which of these methods is the best?" was the question that set us on the path of this

paper. The lack of a clear answer convinced us to write it. We were conducting an analysis of

longitudinal data from our long-term study of vervet monkeys and wanted a method of

calculating dominance ranks that would give good reliability; that is, we wanted to know

whether the hierarchy calculated today could reliably predict a later date. If you are looking to

calculate dominance ranks, however, you will soon have "*l'embarras du choix*": there is such an

such an overwhelming array of options that you may not even know where to start, let alone

decide which one to choose. Our analyses revealed that we couldn't hope to provide a

straightforward answer—there is no absolute best method—but we did develop an approach that

enables researchers to find the method that will provide the best fit for their data. Specifically,

we demonstrate the use of a training-testing procedure that not only enables the most appropriate

method to be identified, but also offers greater insight into the structure and dynamics of a given

dataset. In what follows, we compare 13 different approaches for calculating dominance

hierarchies (seven methods, plus six analytical variants of these). We assess the methods'

performance, their efficiency, and the extent to which the calculated ranks obtained from the

training dataset reliably predict the outcome of observed aggression in the testing data set.

<u>A Brief Survey of Analytical Methods for calculating Dominance Ranks</u>

The analytical importance of hierarchies to our understanding of social organisation has

driven the development of several techniques for inferring dominance hierarchies from

observational data (de Vries 1998; reviewed in Bayly, Evans, & Taylor 2006; Whitehead 2008;

Briffa et al. 2013), as well as extensive research directed at their formation and maintenance (e.g.

Parker 1974; Dugatkin & Earley 2004; Sasaki et al. 2016). At present, there are seven methods

that either have been commonly used to calculate dominance hierarchies, or newly offered as

improvements to existing methods.

76   Until recently, all ranking methods were based on interaction matrices. Using this

approach, it is possible to distinguish two ways of quantifying dominance relationships. In the

first, the dominance matrix is reorganized such that some numerical criterion is minimized or

maximized (e.g., Inconsistencies and Strength of Inconsistencies method (I&SI): de Vries 1998;

ADAGIO ('approach for dominance assessment in gregarious species'): Douglas et al. 2017).

The second approach aims to provide a suitable measure of individual overall success, from

which a rank order can be derived directly (e.g. David's score: David 1987, Gammell et al. 2003;

Elo-rating: Elo 1978, Neumann et al. 2011). The I&SI (method 1) and the David's score (method

2) are the two most commonly used ranking techniques. Despite their usefulness, they share a

drawback common to all matrix-based methods. Namely, they gather all observed interactions

within a particular time period to determine a single quasi-static ranking, with the result that the

obtained ratings depend directly on the number of individuals present in the matrix itself. Thus,

any observed fluctuation in rank across two time periods may simply be a consequence of

demographic events rather than variation in competitive abilities. Hence, these methods fail to

provide information about how ranks may change or are maintained over time.

92   In order to address actual, rather than "demographic", changes in a rank hierarchy, a

common approach has been to compare hierarchies across different periods, or before and after

specific events, such as the integration of a new individual (Arseneau- Robar et al. 2017).

However, this still fails to track any potential continuous variation in the rank order of subjects

(c.f. Neumann et al. 2011; Newton-Fisher 2017). At the same time, breaking down the

assessment of rank hierarchies into shorter time windows is itself problematic, as shorter

sampling periods may result in a lack of data from which to infer a reliable hierarchy (Goffe,

Fischer & Sennhenn-Reulen 2018). The I&SI method has an additional downside in that it seeks

to produce a linear rank order, regardless of whether the society in question is expected to show a

linear hierarchy, or whether the data fit the assumption of linearity. These methodological flaws

have led to the emergence of two alternative approaches.

First, given that simple linearity is not likely to characterise the dominance structures of

many animal societies, Fujiii et al. (2015) developed a network-based method, called Percolation

and Conductance (P&C). This permits nonlinear structure to emerge via estimates of network

directional consistency in the flow of dominance interactions, and the detection of blocks of

dominance ambiguity that are indicative of nonlinear segments of a hierarchy. This technique

uses paths within the agonistic network to generate an individual's probability of winning against

all other individuals. Despite overcoming the linearity assumption, P&C nevertheless follows the

two previous methods in being reliant on interaction matrices. This brings us to the second

alternative, which enables a more dynamic assessment of rank over time.

This method can be traced to Neumann et al. (2011), who argued that matrix-based

methods for rank assessment often cannot be applied to highly dynamic animal societies, or to

sparse datasets. With this in mind, he introduced the Elo-rating method (method 4), derived from

its application in competitive games, and famous for its use in rating chess-players (Elo 1978).

This method enables the rating process to continue despite changes in group-composition, thus

circumventing one of the other drawbacks of matrix-based methods (viz. I&SI, DS and P&C). In

other words, Elo-ratings are based on the sequence in which interactions occur, with ranks

continuously updated. This has the advantage of allowing ratings to span changes in group-

composition.

Despite these improvements, Elo-rating also has its limitations. One fundamental

problem is that, in the absence of any knowledge of prior dominance relationships, the method

assigns all individuals the same initial Elo-rating score, which is then updated as interactions are

added across the observation period. Consequently, a "burn-in" period is necessary so that

sufficient observations can accumulate and enable the modeled rankings to catch up with the

computation of reliable ratings of dominance relationships (Albers and de Vries 2001; Neumann

et al. 2011). Both Albers & de Vries (2001) and Neumann et al. (2011) are vague about how long

this process might take, probably because the duration of the burn-in will vary with the

frequency of agonistic interactions (Newton-Fisher 2017).

Another issue with Elo-rating is the assumption that all agonistic interactions entered into

the model are equivalent in their potential influence on rank trajectories. In rating subjects, the

variable k is used to determine the degree to which each interaction influences the future rank

trajectory of both winner and loser. In other words, it determines the number of rating points that

an individual gains or loses after a single encounter (Neumann et al. 2011). Newton-Fisher

(2017) argues that holding k constant makes the implicit assumption that, as long as a clear

winner and loser can be identified, variation in the intensity of aggression does not influence

social dominance rank or rank trajectories.

As Elo-rating has received increasing interest, there have been a number of recent

attempts to address the difficulties associated with its use (e.g. Foerster et al. 2016a; Newton-

Fisher 2017; Goffe, Fischer & Sennhenn-Reulen 2018; Sánchez-Tójar, Schroeder & Farine

2018). This has resulted in the development of a method to calculate dominance, referred to as

the modified Elo-rating method (method 5). Specifically, Newton-Fisher (2017) presents two

developments of Neumann et al.'s (2011) R function to improve its efficiency: (i) the

incorporation of prior history and (ii) the recognition of differing intensities of aggression in

agonistic interactions. Using data from male chimpanzees (*Pan troglodytes*), Newton-Fisher

(2017) showed that incorporating even limited prior knowledge of dominance ranks substantially

reduced the required burn-in period and improved the effectiveness of Elo-rating in resolving

hierarchical structure. In addition, allowing k to vary further improved the Elo-rating models.

Taking another approach to the limitations of the burn-in period, Goffe, Fischer & Sennhenn-

Reulen (2018) used "partial pooling", which rests on the assumption that all initial ratings are

sampled from the same distribution with a shared variation parameter σ. This Bayesian Inference

(BI) approach (method 6) facilitates the estimation of initial ratings, as well as the value of k.

Finally, one of the aims of the original Elo-rating was to track dynamic changes in rank.

However, most behavioural studies assume that individual dominance rank is relatively stable

over time (e.g. Poisbleau, Guillon & Fritz 2010). With this in mind, Sánchez-Tójar, Schroeder &

Farine (2018) suggested a modification to the original Elo-rating based on randomizing the order

in which interactions occurred: the randomized Elo-rating method (method 7). They showed that

randomizing the order in which interactions occurred (1000 times), and estimating mean

individual ranks, improved performance compared to the original Elo-rating, particularly when

hierarchies were not unduly steep. This finding supports the idea that randomizing interaction

order has a beneficial effect when species' social dynamics are relatively stable and rank

acquisition is achieved by the pattern of maternal rank inheritance. The principles underlying all

seven methods are outlined in Figure 1.

171   Figure 1: Main-guiding principles of each cited methods.

172   Several attempts have been made to assist researchers in selecting the most appropriate

method for quantifying dominance ranks, with most focusing on comparing the level of

agreement among several methods when applied to real datasets (e.g. Balasubramaniam et al.

2013; de Vries 1998; Gammell et al. 2003; Neumann et al. 2011). Sánchez-Tójar, Schroeder &

Farine (2018) argue that, while cases where two or more methods closely match one-another

could signify that they are robust, it might also mean that they suffer from a common bias and, if

so, such comparisons can provide no information about their accuracy. Consequently, they

recommend simulating artificial datasets containing individuals of known rank, as well as

simulating interactions among those individuals under different scenarios of known steepness,

and then testing the validity of the method(s) by correlating the inferred hierarchy to the known

hierarchy.

Here we take an alternative, but complementary, approach. Using agonistic data from a

long-term study of vervet monkeys (*Chlorocebus pygerythrus*), we generate training-testing

datasets in order to determine the efficiency of the seven listed methods (along with several

variants of particular methods). The notion that dominance hierarchies reduce uncertainty about

the outcomes of contests between group members (Beaulieu et al., 2014; Mendonça- Furtado et

al., 2014) assumes that the state of the hierarchy at a given time will be predictive of future

interactions (Strauss & Holekamp, 2019). We test this assumption by assessing whether

individual ranks, obtained from the training dataset, can predict the future aggressive outcomes

that occur in the testing dataset. We proceed as follows.

First, we explore each method's performance by determining the proportion of accurate

predictions in aggressive outcomes across the testing dataset. That is, we assess whether the

ranks obtained from a large training dataset are in agreement with the outcomes of aggressive

interactions present in our testing dataset. Given that, over time, groups undergo changes in their

social dynamics due to changes in the social and ecological environment, both of which may

underpin shifts in rank, we predict that interaction sequence-based approaches will perform

better in deducing ranks than the matrix-based ones, as the former methods take into account the

temporal dynamics of the social hierarchy (Neumann et al. 2011; Williamson, Lee & Curley

2016; Newton-Fisher 2017; Goffe, Fischer & Sennhenn-Reulen 2018).

Following this investigation, we assess each method's efficiency in terms of the amount

of data needed to obtain accurate estimations. A burn-in period is necessary for sufficient

observations to accumulate and enable a stable rank position to be calculated. However, an

excessive amount of data may not give a representative picture of the current state of play within

a group, because old, and potentially out-of-date, information will be included in the

calculations. In order to find the right trade-off, we determine the necessary duration of the burn-

in phase for each method by repeatedly reducing the length of training dataset size by 2-month

increments. To allow for comparison, we kept the testing dataset constant. To put this in concrete

terms, we maintain the same end date for the training dataset, while varying its start date. Thus,

as the training dataset decreases in size, only the most recent observations are included. At each

reduction in length, individual ranks are calculated and tested against the testing dataset. We

expect to see the reliability of predicted ranks to increase with the amount of data used until a

threshold is reached (representing the accuracy limits of older information being included in the

calculation), following which ranks should decrease in their reliability.

Finally, we analyze how well future aggressive outcomes can be predicted by values

calculated during an earlier period. To do this, we reversed the above process, keeping the

training dataset constant, while sequentially extending the testing dataset size by 2-month

increments, until we achieved a 30-month testing dataset. Our interest here was to assess the

length of time it would be possible to use previously calculated ranks with minimal loss of

accuracy. As mentioned above, rank positions within a hierarchy can change over time due to

temporal variation in demographic and ecological conditions. Thus, we expect that aggressive

outcomes will be predicted with high accuracy initially and will then manifest a constant decay

as the accuracy of ranks decreases through time.

After investigating these seven methods, we conclude our study by proposing our own

modification to the modified Elo-rating that helps to improve its performance.

2. **Methods**

a. <u>Study site and subjects</u>

Data used for these analyses were collected between January 2015 and December 2017 as

part of a long-term field project at the Samara Private Game Reserve, South Africa (32o22'S,

24o52'E). We used data from one of our three study groups (RBM). All animals were fully

habituated and individually recognisable. The study group occupied semi-arid riverine woodland

(Pasternak et al. 2013). Group composition varied across the study period (Males: 20-6, Females:

13-8; Juveniles: 33-9; Infants: 11-2).

b. <u>Behavioural data collection</u>

Agonistic behaviours, identities of participants and interaction outcomes were recorded

ad libitum on all group members (i.e., across all sex and age categories). In order to make use of

the most diverse and complete dataset, we included agonistic encounters with juveniles and

infants and also those that involved coalitions (i.e., where one or more animal comes to the aid of

another against a common opponent). Unknown outcomes were discarded. Agonistic behaviours

included displacements, threats, chases and bites. The visibility of the habitat, together with the

modal presence of more than one observer (McFarland et al. 2014, Henzi at al. 2013), means it is

unlikely that there was any systematic bias in the recording of agonism. We recorded 11323

agonistic interactions between 66 individuals across the 36-month period. The initial training

dataset comprised 8292 interactions, with the testing dataset accounting for the remaining 3031

interactions.

c. <u>Methods used to infer ranks</u>

We assessed the performance of three commonly used methods for inferring longitudinal

hierarchies: the I&SI method, David's scores (DS) and the Elo-rating method. We also

evaluated the performance of P&C, as well as the three methods derived from Elo-ratings: the BI

approach, the randomized Elo-rating and the modified Elo-rating approach (see Table 2 for a

summary of the seven methods) to give a total of seven methods. As noted above, several

different statistical packages and options are available for the David's score and P&C methods,

thus we assessed 13 methods in all.

All our calculations were implemented in R.

Method	Approach	Outcome	R Package
I&SI	Reorder interaction matrix iteratively to minimize (1) number of inconsistencies (I) and (2) strength of inconsistencies (SI)	Ordinal rank order	Compete

David's score	Matrix based approach in which the relative strength of opponents is taken into account	Individual overall success determined by weighting each dyadic success measure by the un-weighted estimate of the opponent's overall success	Compete, Steepness & EloRating
Percolation & Conductance	Combines information from direct win/loss interactions **and** from indirect pathways to create a matrix of probabilities. The network transitivity determines how much to weight the indirect 'wins' from these pathways	Average dominance probability + dominance uncertainty	Perc
Original Elo-rating	Scores are updated after each interaction depending on the outcome. Individuals start with predefine score while k is a winning/losing shift coefficient that is kept constant	Individual overall success	EloRating
Modified Elo-rating	Attribute a k value to each of the aggression categories	Individual overall success	Code from Newton-Fisher 2017

Bayesian Inference	Estimates both the most probable rank order + the posterior probability of that order	Start ratings, the Elo-rating winning/losing shift coefficient (k) before computing the scores + the uncertainty around the estimates	Code from Goffe, Fischer & Sennhenn-Reulen 2018
Randomized Elo-rating	Randomized interaction sequence	Individual overall success + measure of uncertainty around the estimates	aniDom

255    <u>Table 2</u>: Summary of the different methods tested in this study

256    The following sections explain in more detail the choices made regarding the

257  analyses for each method.

258   i. <u>The I&SI method</u>

259  It is recommended to find the matrix with the lowest SI associated with a certain number

260 of iterations (nTries). To do so, we performed an optimization to find the nTries that best fit our

261 data. We used the DEoptim package (Mullen et al. 2011). The DEoptim function searches for

262 the global optimum of the objective function (fn) between lower and upper bounds on each

263 parameter to be optimized. It is important to emphasize that the result of DEoptim is a random

264 variable, i.e., different results may be obtained when the algorithm is run repeatedly with the

same settings. In our case, the function fn with the highest percentage of accurately predicted

outcomes was kept, along with the optimized parameter corresponding to the number of

iterations (nTries). We assigned to this parameter the lower bound of 50 and the upper bound of

1000. Once the optimal parameter value had been extracted, individual ranks were calculated

using the latest function version "isi13" from the R package "compete".

The use of this optimization led us to modify our training/testing approach into a

training/validation/testing one. Specifically, we divided the original 80% training dataset in two

datasets, commonly called training and validation. The training dataset (i.e., the first 80%) was

used to attribute the nTries value, leading to the calculation of individual ranks based on this

value (Figure 5). The remaining 20%, the validation dataset, allowed us to see how well these

ranks did in predicting the aggressive outcomes. Depending on the percentage of accurately

predicted outcomes, the nTries value was updated accordingly in the training dataset. Once the

optimised nTries value was obtained, it was used to calculate the ranks from the entire, original

80% training dataset. The testing dataset then allowed us to test the efficiency of the calculated

ranks in predicting future aggressive outcomes. Here nTries= 449 was chosen.

ii.   David's Score

This approach proposes two alternative indices to compute David's scores: Pij and Dij.

Pij represents the winning proportion of individual i against j, which leads to a matrix of

observed win proportions as an output. For the Dij index, a matrix is obtained where the

observed proportion of wins (Pij) is corrected for the chance occurrence of this observed

outcome. Balasubramaniam et al. (2013) argued that Pij might be a better choice for species with

high levels of directional asymmetry (i.e., despotic species), whereas Dij may be a better choice

for species with low levels of directional asymmetry (i.e., tolerant species). We compared both

these indices. Furthermore, the David's score method can be calculated with the aid of three

different R packages. The decision was made to include them all in the analysis, producing two

calculated scores per package. This allowed us to assess whether the calculated ranks were the

same across all packages and if not, which package led to the highest percentage of accurate

predictions.

iii.   Percolation and Conductance

The parameter maxLength helps find all indirect pathways of a particular length and then

update the conflict matrix. Examining information gained through indirect pathways provides

information that can be used to decide on the appropriate maxLength for a dataset. To assist with

this decision, the Perc package offers a transitivity function as a way to estimate an alpha value,

which is used to weight the information from the indirect pathways to give an indication of the

extent to which we can trust information from indirect pathways. Greater transitivity is

associated with assigning higher weight to information from indirect pathways (Fushing,

McAssey & McCowan 2011). We tested MaxLengths of 2 and 4.

iv.   Elo-rating method

In the original method, k is held constant and all individuals receive the same elo-rating

at the initiation of the burn-in period. Elo-ratings were calculated with 1000 as the initial value

and k set to 100 (Neumann et al. 2011).

v.   Derivations of the Elo-rating methods

•   <u>Modified Elo-rating (k variation)</u>

In this method, each dominance interaction is classified according to the most intense level of

aggression displayed by the winner (Newton-Fisher 2017). This being required, we excluded

behaviours recorded as "unknown" from the analyses and distinguished among non-aggressive,

stationary, active and physical threats. This classification is based on our inter-troop encounter

protocol (Barrett, L. and Henzi, S.P., unpublished data). Non-aggressive behaviours included

supplants (i.e., where the aggressor takes the victim's place) and displacements (i.e., when one

animal submissively moved away when approached within 10 meters). Any aggressive

behaviour that did not include a forward movement was considered a stationary threat, such as

lunge, facial and vocal threats. Active aggression involved ongoing forward movement (i.e.,

chase or charge) but where no physical contact was made with the target of aggression. Physical

aggression was scored in instances where body contact was made (e.g., a bite or slap). We

assigned a different K value to each of these categories, using the default value of 200 (Neumann

et al. 2011) for the most commonly observed form of aggression (i.e., the non-aggressive

interactions of displace and supplant) and scaling up in multiples of 25 to distinguish varying

intensities. This led to the creation of a modified training data set and its detailed composition is

given in Table 3.

| Aggression Number | Modified training data set | | | | |
	Total	Physical	Active	Stationary	Non-aggressive
RBM Troop	8083	886	1644	1625	3934

K value	-	300	250	225	200

Table 3: Modified training data set for the modified Elo-rating method (Newton-Fisher 2017).

• Bayesian inference (BI) approach

We implemented this method Goffe, Fischer & Sennhenn-Reulen's (2018) code (with no

additional analytical choices or justification required).

• Randomized Elo-rating

By randomising the order of observed interactions, this approach allows the creation of K

replicated datasets, where K corresponds to the number of randomisations performed. In this

study we were only interested in obtaining the final scores (return.as.ranks =TRUE). The

function returns a NxK matrix that gives the final scores for each individual (rows) after each

randomisation of the order. In order to use the information contained in all the iterations, we

extracted the mean ranks for each individual.

We followed the same procedure as Sánchez-Tójar, Schroeder & Farine (2018) and randomized

the order in which interactions occurred 1000 times.

d. Construction of training and testing datasets and comparison of methods

i. Determining the method's performance

Here, we divided our dataset, using the first 80% (2.1.2015 – 25.4. 2017) to train the methods,

with testing undertaken on the remaining 20% (26.4.2017 – 31.12. 2017)(Figure 2). This ensured

that we always had a training dataset with sufficient observations to infer reliable ranks.

This approach is taken from machine learning where it is a common strategy to split data into

training and evaluation subsets, usually with a ratio of 70-80 percent for training and 20-30

percent for evaluation. The two datasets are thus distinct as we are only interested in predicting

future outcomes and not interpolating ranks. For each method, we calculated dominance

hierarchies from our training data.

It is important to note that, in our case, each model (i.e., ranking method) is fit to the data while a

withheld dataset is used to assess the models. As we are interested in the reliability of rank

estimates across time, this approach proves to be useful with time series data as it lets us make

estimates of how well each model performs in forecasting (i.e., predicting future interaction

outcomes). Here, we make the assumption that the process model is the same between the two

time periods (i.e., training and testing) and we make "small world" predictions about which

method is best for our particular dataset.

Figure 2: Original approach used to assess methods' performance.

We first chose to use visualisation to examine how the rank order inferred by each

method differs. Given that the percentage of accurately predicted outcomes results from the

inferred rank order, knowing the extent to which rank order varies can help to better understand

each method's performance. To do so, we implemented a hierarchical clustering approach that

assembled our results according to their similarity. Initially, each method was assigned to its own

cluster. The algorithm then proceeds iteratively, at each stage joining the two most similar

clusters, and continuing until there is just a single cluster. In this way, methods that are most

similar to each other are combined into branches that are themselves fused higher up in the

clustering process. Euclidean distance is used to measure the dissimilarity between each pair of

methods. As the estimated ranks were measured on different scales, we standardized the data and

used the hclust R function (stats package) to generate this hierarchical clustering.

The obtained ranks for each method were then converted into ordinal ranks to enable

comparison across methods. The ordering of these ranks was used to assess how well they

matched the outcome of aggressive interactions for each interaction in the testing dataset (yes =1

or no=0). The proportion of accurately predicted outcomes was then translated into a percentage

allowing us to assess which methods (if any) outperformed others. We expected more accurate

predictions using the more dynamic approaches given changes in the social dynamics of our

study group. We excluded from analysis animals that were only present during the testing phase

of the dataset, but retained those individuals present only in the training dataset, as they were

able to provide information about their opponents.

ii.   Determining the optimal burn-in period

We assessed the methods' efficiency by estimating the necessary burn-in period. As

noted above, we kept our testing dataset constant while modifying the length of the training

dataset. Our original training dataset comprised 28 months, which we reduced sequentially by

two months, until only two months were left. To do so, we truncated the dataset starting from

January 2015 towards April 2017 (figure 3).

Figure 3: Modified approach used to assess the burn-in period by varying the training dataset length.

At each reduction in size, we computed ranks and assessed these against the testing dataset. The

same procedure outlined above was used to calculate the percentage of accurately predicted

outcomes. These percentages were then plotted in order to determine the amount of data needed

to predict reliable and stable ranks.

iii.   Determining rank stability and predictability across time

Here, our aim was to determine the length of time over which obtained ranks would

continue to accurately predict aggressive outcomes. To do so, we gradually increased our testing

dataset size and looked at its impact on the percentage of accurately predicted outcomes. Based

on the burn-in period results (see below), we calculated the average optimal training dataset

length across all methods. Using the average in this way allowed us to keep the training dataset

constant, easing comparisons between the different methods. We then used the remaining data as

our testing dataset, and systematically varied its length. We began with the 2-month period that

followed on directly from the training phase (July-September 2015) and then sequentially

increased the testing dataset by 2 months until the 30-months limit was reached in December

2017 (Figure 4).

Figure 4: Modified approach used to assess the extent of prediction in aggressive outcomes by varying the testing dataset length.

Ranks predicted by the training dataset were then compared to the observed outcomes in each

testing dataset. Percentage accuracy was plotted as a function of testing dataset length, giving us

an insight into the rate of decay in each method's performance.

e.   <u>Elo-rating approach using optimized k</u>

Rather than arbitrarily attribute k values to aggressive categories, we used an

unsupervised way to assign them. The idea here is to find the values to fit each of the aggressive

categories in our dataset. As we are seeking to find the optimised k values, we apply the same

method used to find the number of iterations (nTries) in the isi function. In other words, we

performed an optimization where the function fn with the highest percentage of accurately

predicted outcomes was kept, along with the optimized parameters that corresponded to our four

different categories of threat. We assigned to these parameters the lower bound of 0 and the

upper bound of 500. Once the optimal parameter values had been extracted, individual ranks

were calculated with the modified Elo-rating function provided by Newton-Fisher (2017).

This led us to use again the training/validation/testing approach. As a reminder, in this specific

case, the training dataset was used to attribute k values, leading to the calculation of individual

ranks based on these values (Figure 5). The validation dataset allowed us to see how well these

ranks did in predicting the aggressive outcomes. Depending on the percentage of accurately

predicted outcomes, k values were updated accordingly in the training dataset. Once the

optimised k values were obtained, they were used to calculate the ranks from the original 80%

training dataset. The testing dataset then allowed us to test the efficiency of the calculated ranks

in predicting aggressive outcomes.

Figure 5: Modified approach used to improve the performance of the modified Elo-rating.

(1) Training dataset (80%) used to (i) attribute k values to the different types of aggression (ii) calculate individual ranks.
(2) Validation dataset (20%) used to (i) run the optimisation loop. Its outcome, the percentage of accurately predicted outcomes, will reveal how well the ranks match the aggressive outcomes and allow the loop to modify the k values in order to improve the prediction.
(3) Once the optimized k values obtained, final ranks are computed using the original training dataset.
(4) Percentage of accurately predicted outcomes is extracted after testing the ranks on the testing dataset.

3. **Results**

a. Which method performs best?

Our dendogram identifies the extent to which the methods provide similar estimates of

rank order in our study group (Figure 5a). The height of the fission on the vertical axis indicates

the similarity of ranks between two methods. The higher the height of fusion occurs, the less

similar the methods are in terms of their outputs. With this in mind, the output from the original

Elo-rating appears to be most different from the others, followed by the modified Elo-rating and

then the I&SI method. The green cluster comprising the David's scores method is the most

similar in its outputs followed by the P&C method and then by the BI and randomized Elo-rating

cluster.

The violin plot, which shows the percentage of accurately predicted outcomes in the testing

dataset, presents interesting results when combined with the dendogram (Figure 5b). While the

dendogram shows how similar the methods are in their outputs (rank order), the violin plots

show the variance in the percentage of accurate predictions produced by each method, i.e., they

give us a sense of the "uncertainty" in the rank outputs produced. Looking at the blue cluster (BI

and the randomized Elo-rating), we can see that both methods produce similar outputs (Fig 5a)

and, yet, differ in their performance: the BI approach has a higher percentage of accurate

predictions than the modified Elo-rating (Fig. 5b). Interestingly, the blue cluster of the

BI/randomized Elo-rating and the modified Elo-rating (orange cluster) differ in their outputs (Fig

5a), but the randomized Elo-rating method's performance is more similar to the modified one

than the BI method (Fig 5b).

Figure 5: (a) How similar are the rank orders produced by each method? (b) How similar are the methods in their performance? Distribution of the percentage of accurately predicted outcomes across the methods used. Red, orange and blue clusters represent the interaction-based approaches while pink, brown and green ones are matrix-based methods. Green corresponds to the David's score variants.

The percentages of accurately predicted outcomes for each method are given in Table 4.

These indicate that all methods performed well in inferring reliable ranks (ranging from 77.5% to

82.9%). The I&SI method provided the best fit to our data, accurately predicting 82.9% of

aggressive outcomes, with the BI approach producing an almost identical value of 82.6%. The

David's score obtained from the three different packages, and via the two different functions (Dij

and Pij), were the lowest performing with the percentage of accurate prediction ranging from

77.5% to 79.9%, as well as the modified Elo-rating with a percentage of predicted outcomes of

79.9. The David's scores from the "EloRating" package and the ones from the "steepness"

package (Pij and Dij function) gave the exact same percentage outcomes. Compared to Dij

function, the Pij predicted a higher number of accurate outcomes across all three packages used.

Moreover, the "compete" package with Pij has the same efficiency as the k modified Elo-rating

approach (79.91%). The I&SI method apart, the interaction-based approaches outperformed the

matrix-based ones. Taken together, these results show that, despite these methods differing in

their approach and the nature of their outputs, they all show a high level of efficiency in

predicting future outcomes of aggressive interactions in our dataset.

Method	Package	Option	% prediction RBM
I&SI	Compete	isi13	81.9
David's scores	Compete	Dij	79.6
		Pij	79.9
	Steepness	Dij	77.5
		Pij	78.7
	EloRating	Dij	77.5

		Pij	78.7
Percolance & Conductance	Perc	maxLength4	81.1
		maxLength2	80.7
Elo-rating	EloRating	default	81.8
	Newton-Fisher's code	K variation	79.9
Bayesian Inference	Goffe's code	Rstan	82.6
Randomized elo-rating	aniDom	n.rands=1000	80.9

485 <u>Table 4</u>: Percentage in aggressive outcome prediction over an 8-month testing dataset for our

486         vervet monkeys' troop (RBM).

488     b. <u>Burn-in period: are some methods more efficient than others?</u>

489    We sought to find a balance between using too few and too many data in our training

490 dataset. We expected to see that, as the length of our training dataset increased, so the percentage

491 of accurately predicted aggressive outcomes should also increase. However, as the training

492 dataset begins to accumulate older aggressive interactions, we expected the accuracy of the

493 percentage of predicted outcome to decrease. This assumption was borne out by our results to a

494 certain extent (Figures 6 and 7). For the most part, however, accuracy of predicted outcomes was

495 not greatly affected by the length of the training dataset.

496    For ease of presentation and interpretation, we chose to look at the dynamic and static

497 approaches separately. Figure 6 presents the dynamic approaches, and shows that the length of

498 the training dataset does not have any impact on three of the four methods: the original Elo-

rating, the BI and the modified Elo-rating. In fact, these three methods perform very well

regardless of the length of the training dataset. There is some evidence to suggest, however, that

the BI approach and original Elo-rating method produce slightly better predictions once the

training dataset has exceeded four months. As for the randomized Elo-rating method, this shows

a more acute sensitivity to the amount of data in the training set. A first peak in accurate

prediction appears at training set lengths between 4 and 8 months. Past 8 months, the accuracy in

outcome prediction decreases as the training dataset length increases.

<u>Figure 6</u>: Variation of the percentage of outcome prediction with the dynamic approaches in

function the number of months included in the training dataset.

The static approaches (Figure 7) display much more variation in the percentage of

accurately predicted outcomes depending on the length of the training dataset. Despite this

sensitivity, a maximum in prediction accuracy can be found for each of these methods. On

average, these peaks occur at 6 months, which we suggest represents the optimal length of burn-

in period needed to accurately predict future outcomes in the data. As the number of months in

the training dataset increases, we also see more of a decay in accurate prediction compared to the

more dynamic methods (as one would expect). Moreover, the I&SI method displays a higher

percentage of accurately predicted outcomes compared to the dynamic methods when the

training dataset spans the period of 2 to 12 months.

<u>Figure 7</u>: Variation of the percentage of outcome prediction with the static approaches in

function the number of months included in the training dataset.

c. <u>Ranks stability: increasing the testing dataset</u>

To construct our training dataset for this analysis, the start date was determined by the

average optimal burn-in period obtained from the previous analysis. With the exception of P&C,

all methods from the static approaches had an optimal percentage of accurate prediction with a 6-

month burn-in period. The dynamic approaches reached saturation sooner, between 2 and 4

months, the randomized Elo-rating being the exception with an 8-month burn-in period. We

therefore used a 6-month burn-in period as this represents the best compromise in terms of

enabling comparison across all methods. Shortening the burn-in period in this manner this

manner gave us a larger testing dataset of 30 months in total (2.5 years).

The percentage of accurate predictions for each testing dataset length is plotted in Figure 8a-c.

All methods show the same pattern. First, a decline in outcome predictability occurs at 4 months,

which is then followed by a peak in prediction accuracy corresponding to a testing dataset of 8-

10 months in length (Fig.8a). Past 10 months, the accuracy of predicted outcomes shows a

constant and slow decay. These fluctuations are more or less marked depending on the method

used. This pattern (i.e., where the curve's fluctuation is more marked) is picked up by all

dynamic approaches, while some of the static ones (I&SI and P&C) display the same pattern in

fluctuations for the first 10 months, but this is much less pronounced. The I&SI, as well as the

P&C approach, stand out as the methods producing a set of ranks that will lead to the highest

percentage of accurately predict outcomes over the whole testing dataset's length (Figure 8.a),

followed by the BI approach that presents an overall slower decay in prediction. The rest of the

methods are clustered with a lower percentage of accurately predicted outcomes throughout the

testing dataset's length.

In order to examine these patterns in more detail, we separated the dynamic and static

approaches (Fig. 8 b and c). With respect to dynamic approaches, as mentioned above, the BI

and the original Elo-rating display the general pattern described above. The randomized and the

modified Elo-rating show lower performance overall but, following the peak in prediction

accuracy at 10 months, the accuracy of the randomized Elo-rating then remains constant, while

the modified Elo-rating produces an increasing percentage of accurately predicted outcomes as

the length of the testing dataset increases. With regard to the static approaches, both the I&SI and

P&C methods display the same pattern as the BI and the original Elo-rating. The David's score

shows a smoother curve, with a constant decrease in accuracy once past a testing dataset of 2

months. The "compete" package appears to perform better than the "steepness" and "EloRating"

packages, which produce equivalent curves. Finally, the I&SI and P&C methods display a

higher percentage of accurately predicted outcomes compared to the dynamic methods

throughout the whole testing dataset length, except for P&C with maxLength 2 past 26-months

of the testing dataset.

Figure 8: Variation of the percentage of accurate predictions as a function of testing dataset

length across (a) all methods, (b) dynamic approaches only, (c) static approaches only.

d. A further modification to the modified Elo-rating

An optimization was performed on the last 20% of the original training dataset in order to

obtain the best-maximised k values leading to the calculation of accurate ranks. The values

attributed to the aggression categories are represented in Table 5.

	Modified Elo-rating	Alternative k values
Physical aggression	300	47.8
Active aggression	250	33.4
Stationary aggression	225	43.1
Non-aggressive	200	31.4

568   Table 5: k values attributed to the four types of aggressive categories for the two different

569   methods

With these new k values, 84.3% of accurately predicted outcomes were obtained over the 8-

month testing dataset. This alternative approach thus offers the best performance among all the

tested methods. The use of the optimisation enabled us to increase its performance by nearly 5%.

4. Discussion

The short answer to our original question is that there is no best method per se. Rather, all

methods performed well. Given this, it seems tempting to conclude that it is possible to simply

flip a coin or otherwise choose a method randomly. This would be the wrong conclusion,

however, as our analyses forced us to the realisation that the best method will always be a

dataset-specific phenomenon. The true value of our analyses lies in the demonstration that a

training-testing procedure provides researchers with the tool they need to guide their choice of

method. In other words, although we have failed to identify *the* best method, we have generated

a means by which researchers can find the best method for *them*.

More specifically, the training-testing procedure we used here not only enables

informative comparisons to be made between different methods, but also gives researchers

important insights into the length of the burn-in period needed to produce accurate rank

predictions, as well as the future duration over which a given set of ranks can be used in analysis.

In this way, researchers can determine which will be the most appropriate method, given

sampling effort, the frequency of agonistic interactions, the steepness of the hierarchy, and the

nature of the research question being asked.

The use of this procedure also allows researchers to probe the social dynamics of their

study species in more depth. For example, when comparing ranks and outcomes, our assumption

was that any mismatches represented a rank being wrongly attributed. However, it would be

interesting (and possible) to look at the outcomes of aggressive encounters that do not match the

ranks assigned to each participant, when both were extracted on the same day. This would give

us a better idea of the true degree of outcome unpredictability, allowing us to assess whether

uncertainty in rank assignment is due to the nature of the aggressive interaction itself or whether

it reflects something about the context in which it takes place. Indeed, in cases of high outcome

predictability and rank stability (i.e., where rank challenges would seem unprofitable), it may be

the initiation and/or escalation of aggressive interactions that is unpredictable and linked to the

broader ecological and social context. The procedure can also be used to assess the rate at which

immature animals integrate into the adult hierarchy. In other words, the training/testing approach

enables researchers to investigate dynamic pattern of hierarchy formation and maintenance, and

is not simply a means of determining the most appropriate ranking method. Indeed, it can also be

used to investigate temporal aspects of the aggressive outcome prediction at a dyadic level,

rather than the whole group, and could thus offer a better understanding of the detailed social

dynamics of a given study species. Another way to look at social dynamics is offered by Strauss

& Holekamp (2019) who propose the concept of a longitudinal hierarchy to estimate the

dynamics (Δ) of dominance hierarchies.

More generally, our findings demonstrate how researchers can use the training-testing

procedure to choose the most appropriate method for their needs, given the amount of data they

have at their disposal, and the nature of their study question. We acknowledge, however, that the

use of empirical data does not allow us to distinguish between the two sources of error that could

explain the methods' performance: (i) inadequacies of the method, and (ii) real biological

change. Thus our findings on how different methods compare are only valid with respect to our

data and cannot be assumed to apply to other datasets. Within our dataset, we feel it is safe to

assume that variation in a method's performance compared to others reflects something about the

method itself, given that we tested all methods on the same training/testing datasets such that any

biological changes within the dataset should have be detected by all methods equally.

This is where the usefulness of simulated data comes into play as this allows one to tease

apart these two sources of error more effectively, as well as gaining some more general insights

into each method (Sánchez-Tójar, Schroeder & Farine, 2018). For example, Goffe, Fischer &

Sennhenn-Reulen's (2018) advocate running simulation approaches to test how well Elo-

ratings reflect the (simulated) true structure and how sensitive the rating is to true changes in the

hierarchy. Nevertheless, we believe the training-testing procedure is valuable empirically for

those interested in determining how much the methods vary when run on the exact same dataset,

and why this might be. It is also the case that, although simulated data provide insight into how

well a given method is able to recover the true hierarchy, simulated data are also much tidier and

"well behaved" compared to actual field data, so one should still be cautious about proclaiming

any one method better than the others, as it may be sensitive to qualities of empirical data that do

not occur in simulations.

With respect to our specific dataset, our main finding is that all methods tested performed

well, despite some differences in inferred rank order. With respect to the required burn-in period,

again, all methods appear to be efficient in inferring reliable ranks from the very start (i.e., with

little to no burn-in period), but all showed improvement as the burn-in period increased. In

general, we found that dynamic methods were less sensitive to the amount of data present in the

training dataset compared to the static approaches. As a result, dynamic approaches show a

constant efficiency regardless the length of the training dataset compared to the static

approaches. This is not unexpected given that methods dynamic approaches track rank variations

continuously and update the ranks after each interaction. We should also highlight that, when the

training dataset did not exceed 12 months, it was the static I&SI and P&C methods that produced

the highest percentage of accurately predicted outcomes.

When we adopted a common 6-month burn-in period, all methods could predict

aggressive outcomes accurately for the subsequent 10 months. Past this 10-month threshold,

however, accuracy in prediction decreased as the testing dataset increased in length, but the

decay was rather shallow, and there was a high predictability in aggressive outcomes across time,

indicating overall rank stability during this period. This is not to say, however, that rank

predictability did not fluctuate as the length of the training period increased, with the degree of

fluctuation was dependent on the length of the method used. This suggests that real rank shifts

were occurring in the study group during particular periods, and that the training-testing

procedure provides a way to home in on such periods of instability. The combination of high

overall predictability in aggressive outcomes with some temporal fluctuation suggests that, in our

study species, rank order shows a form of "regression to the mean". That is, individuals may

experience very mild shifts in relative rank position up or down the hierarchy across time, but

nevertheless occupy more or less the same "absolute" position in the hierarchy. This, in turn,

suggests that rank changes may reflect the ecological and demographic contexts in which they

occur, rather than pointing to genuine changes in inherent power. In line with this interpretation,

the dynamic methods produce more fluctuations than the static methods: the former are likely to

catch small shifts in rank position as they constantly update, whereas the static methods, which

combine and cluster interactions across time, are more likely to produce a rank order that fits the

overall social dynamic.

It is also important to remember that we converted the output from each method to ordinal ranks

to facilitate comparison, and differences between (the various kinds of) Elo-ratings can be

absolutely very small. Such differences would lead to a shift in calculated rank order and hence

to fluctuation in prediction accuracy, but, in reality, may have no discernable impact on an

individual's social standing in the group. That is, such fluctuation may, in effect, represent noise

around a stable rank order. Even though Strauss & Holekamp (2019) recommend the use of

ordinal rankings for identifying hierarchy dynamics, this point thus serves to highlight a

limitation of our study in that we looked only at rank order and did not consider the magnitude of

rank differences nor any uncertainty around rank calculations. These components may very well

matter, especially in species where a linear rank order may not be representative of the social

hierarchy. This point also serves to highlight the true advantage of methods like the BI,

randomized Elo-rating and the P&C approach, which enable researchers to look at the

uncertainty around ranks, and thus gain a better understanding of the social hierarchy.

Our training/testing approach procedure also allowed us greater insight into the working

of certain methods. For example, the randomized Elo-rating approach was developed to enhance

performance in societies where ranks remain fairly stable across time (Sánchez-Tójar, Schroeder

& Farine 2018) —a situation that, as noted above, pertains in our study group. Under such

conditions, the sequence in which interactions occur should not affect the inferred ranks. Our

results help validate this assumption. When the training data set was short (i.e., 6 months), the

sequence of interactions clearly did not matter, and the method gave good results. As the training

dataset increased up to 28 months, however, there was a decline in accuracy, which no doubt

reflects the fact that, over this period, demographic change was inevitable and the order of

interactions may well have begun to exert an influence on the structure of the hierarchy. Given

this outcome with our data (and assuming this holds true across other datasets), this suggests that

the randomised Elo-rating method will also prove useful in determining when and where

interaction order matters in a given dataset. Indeed, Sánchez-Tójar, Schroeder & Farine (2018)

suggest that researchers can control for factors such as changing ranks or winner-loser effects by

controlling which parts of the data are randomised. For example, researchers interested in

tracking how individual ranks change across days could increase the accuracy of the daily rank

estimates by randomizing observations within each day.

Our own modification to the Elo-rating also provided some insight into the method's

workings. We produced an increase of nearly 5% in accurately predicted outcomes compared to

Newton-Fisher's (2017) modified Elo-rating. Newton-Fisher's (2017) argument was that

allowing k to vary would improve accuracy as the specific nature of aggression could affect the

outcome and impact of aggressive encounters. Our results did not support this, but we reasoned

that this was most likely due to the fact that our values of k were assigned arbitrarily. Switching

to a data-driven approach to assign k-values, via the training/validation/testing procedure,

resulted in a marked improvement in performance. Thus, the type of aggression shown does, in

fact, matter to predictive accuracy, but arbitrarily assigning values to aggression types may fail to

represent its importance correctly. It is also worth noting that we did not investigate the extent to

which k-values, and hence ranks, were affected by the relative length of the training and testing

periods used in the optimisation procedure (i.e., we used only a 80:20 split), nor did we consider

any potential variation in values of k through time (e.g., due to seasonal effects). More work is

needed to understand better the impact of relative lengths of training and testing periods, as well

as the stability of k values through time.

In conclusion, we suggest that the insights into group dynamics provided by a training-

testing procedure, combined with the ability to determine which ranking method is best suited to

a given dataset, far outweigh the time costs associated with running the procedure. A training-

testing approach gives researchers the power to tailor the selection of a dominance-ranking

method to the particular nature of the dataset they are using, allowing them to take into account

sampling effort, frequency of agonistic interactions and the steepness of the hierarchy, as well as

the particular kinds of analyses they wish to conduct. In addition, comparison of methods and the

dynamic patterns they reveal further enable researchers to home in on regions of their dataset

that will permit analyses into how and why rank shifts occur and discover the underlying causes

of both rank stability and unpredictability across time.

Acknowledgements:

We thank Mark and Sarah Tompkins for the permission to work at Samara, Kitty and Richard

Viljoen for their continued logistic support. We thank Damien Farine and Alfredo Sánchez-Tójar

for helpful discussions as well as for pointing out an error in the rank's computation with the

randomized Elo-rating method. We are also very grateful to the many research assistants who

contributed to the database, as well as our amazing monkeys (and George), without which only

simulated data would be available.

References:

Albers, PC, & Vries, HD (2001). Elo-rating as a tool in the sequential estimation of dominance

strengths. *Animal Behavior*, 489-495.

Arseneau-Robar, T. J. M., Taucher, A. L., Schnider, A. B., van Schaik, C. P., & Willems, E. P.

(2017). Intra-and interindividual differences in the costs and benefits of intergroup aggression in

female vervet monkeys. *Animal behaviour*, *123*, 129-137.

Balasubramaniam, K.N., Berman, C.M., De Marco, A., Dittmar, K., Majolo, B., Ogawa, H.,

Thierry, B. and De Vries, H., (2013). Consistency of dominance rank order: a comparison of

David's scores with I&SI and Bayesian methods in macaques. *American journal of*

primatology, *75*(9), pp.959-971.

Bayly, K. L., Evans, C. S., & Taylor, A. (2006). Measuring social structure: a comparison of

eight dominance indices. *Behavioural Processes*, *73*(1), 1-12.

Briffa, M., Hardy, I. C., Gammell, M. P., Jennings, D. J., Clarke, D. D., & Goubault, M. (2013).

Analysis of animal contest data. *Animal contests*, *379*.

David, H. A. (1987). Ranking from unbalanced paired-comparison data. *Biometrika*, *74*(2), 432-

436.

De Vries, H. A. N. (1998). Finding a dominance order most consistent with a linear hierarchy: a

new procedure and review. *Animal Behaviour*, *55*(4), 827-843.

Douglas, P. H., Ngomo, A. C. N., & Hohmann, G. (2017). A novel approach for dominance

assessment in gregarious species: ADAGIO. *Animal Behaviour*, *123*, 21-32.

Dugatkin, L. A., & Earley, R. L. (2004). Individual recognition, dominance hierarchies and

winner and loser effects. *Proceedings of the Royal Society of London. Series B: Biological*

Sciences, *271*(1547), 1537-1540.

Elo, A. E. (1978). *The rating of chessplayers, past and present*. Arco Publications.

Foerster, S., Franz, M., Murray, C. M., Gilby, I. C., Feldblum, J. T., et al. (2016). Chimpanzee

females queue but males compete for social status. *Scientific Reports, 6*, 35404.

Fujii, K., Jin, J., Shev, A., Beisner, B., McCowan, B., & Fushing, H. (2015). Perc: using

percolation and conductance to find information flow certainty in a direct network. R Package

Version 0.1.

Fushing, H., McAssey, M. P., & McCowan, B. (2011). Computing a ranking network with

confidence bounds from a graph-based beta random field. Proceedings of the Royal Society A:

Mathematical, Physical and Engineering Sciences, 467(2136), 3590-3612.

Gammell, M. P., Vries, H. D., Jennings, D. J., Carlin, C. M., & Hayden, T. J. (2003). David's

score: a more appropriate dominance ranking method than Clutton-Brock et al.'s index. *Animal*

behaviour, *66*(3), 601-605.

Goffe, A. S., Fischer, J., & Sennhenn-Reulen, H. (2018). Bayesian inference and simulation

approaches improve the assessment of Elo-ratings in the analysis of social behaviour. *Methods in*

Ecology and Evolution, *9*(10), 2131-2144.

Henzi, S. P., Forshaw, N., Boner, R., Barrett, L., & Lusseau, D. (2013). Scalar social dynamics

in female vervet monkey cohorts. *Philosophical Transactions of the Royal Society B: Biological*

Sciences, *368*(1618), 20120351.

McFarland, R., Barrett, L., Boner, R., Freeman, N. J., & Henzi, S. P. (2014). Behavioral

flexibility of vervet monkeys in response to climatic and social variability. *American journal of*

physical anthropology, *154*(3), 357-364.

Mullen, K., Ardia, D., Gil, D. L., Windover, D., & Cline, J. (2011). DEoptim: An R package for

global optimization by differential evolution. *Journal of Statistical Software*, *40*(6), 1-26.

Neumann, Christof, Julie Duboscq, Constance Dubuc, Andri Ginting, Ade Maulana Irwan,

Muhammad Agil, Anja Widdig, and Antje Engelhardt. (2011) Assessing dominance hierarchies:

validation and advantages of progressive evaluation with Elo-rating. *Animal Behaviour* 82, no. 4

(2011): 911-921.

Newton-Fisher, N. E. (2017). Modeling social dominance: Elo-ratings, prior history, and the

intensity of aggression. *International journal of primatology*, *38*(3), 427-447.

Parker, G. A. (1974). Assessment strategy and the evolution of fighting behaviour. *Journal of*

theoretical Biology, *47*(1), 223-243.

Pasternak, G., Brown, L. R., Kienzle, S., Fuller, A., Barrett, L., & Henzi, S. P. (2013).

Population ecology of vervet monkeys in a high latitude, semi-arid riparian

woodland. *Koedoe*, *55*(1), 01-09.

Poisbleau, M., Guillon, N., & Fritz, H. (2010). Preservation of winter social dominance status in

Brent Geese Branta bernicla bernicla within and across winters. *Journal of Ornithology*, *151*(3),

737-744.

D. R. (2018). A practical guide for inferring reliable dominance hierarchies and estimating their

uncertainty. *journal of animal ecology*, *87*(3), 594-608.

Sasaki, T., Penick, C. A., Shaffer, Z., Haight, K. L., Pratt, S. C., & Liebig, J. (2016). A simple

behavioral model predicts the emergence of complex animal hierarchies. *The American*

Naturalist, *187*(6), 765-775.

Strauss, E. D., & Holekamp, K. E. (2019). Inferring longitudinal hierarchies: Framework and

methods for studying the dynamics of dominance. *Journal of Animal Ecology, 88(4), 521-536*.

Whitehead, H. (2008). *Analyzing animal societies: quantitative methods for vertebrate social*

analysis. University of Chicago Press.

Williamson, C. M., Lee, W., & Curley, J. P. (2016). Temporal dynamics of social hierarchy

formation and maintenance in male mice. *Animal behaviour*, *115*, 259-272

Figure 2: Original approach used to assess methods' performance.

Figure 3: Modified approach used to assess the burn-in period by varying the training dataset length.

Figure 4: Modified approach used to assess the extent of prediction in aggressive outcomes by varying the testing dataset length.

Figure 5: Modified approach used to improve the performance of the modified Elo-rating.

(1) Training dataset (80%) used to (i) attribute k values to the different types of aggression (ii) calculate individual ranks.

(2) Validation dataset (20%) used to (i) run the optimisation loop. Its outcome, the percentage of accurately predicted outcomes, will reveal how well the ranks match the aggressive outcomes and allow the loop to modify the k values in order to improve the prediction.

(3) Once the optimized k values obtained, final ranks are computed using the original training dataset.

(4) Percentage of accurately predicted outcomes is extracted after testing the ranks on the testing dataset.