1

Title: Evidence for a deep, distributed and dynamic semantic code in human ventral anterior temporal cortex

Authors: *Timothy T. Rogers[1], Christopher Cox[2], Qihong Lu[3], Akihiro Shimotake[4], Takayuki Kikuch[5], Takeharu Kunieda[5,6], Susumu Miyamoto[5], Ryosuke Takahashi[4], Akio Ikeda[7], Riki Matsumoto[8], *Matthew A. Lambon Ralph[9]

Affiliations:

[1] Dept. of Psychology, University of Wisconsin, Brogden Hall, Madison, WI 53706

[2] Dept. of Psychology, Louisiana State University, Audubon Hall, Baton Rouge, LA 70802

[3] Dept. of Psychology, Princeton University, South Dr, Princeton, NJ 08540

[4] Dept. of Neurology. Kyoto University Graduate School of Medicine, Kawaharacho, Shogoin,, Sakyo-ku, Kyoto, 606-8507, Japan

[5] Dept. of Neurosurgery, Kyoto University Graduate School of Medicine, Kyoto, Japan

[6] Dept. of Neurosurgery, Ehime University Graduate School of Medicine, Shizukawa Toon city, Ehime, 791-0295, Japan

[7] Dept. of Epilepsy, Movement Disorders and Physiology, Kyoto University Graduate School of Medicine, Kyoto, Japan

[8] Div. of Neurology, Kobe University Graduate School of Medicine, Kusunoki-cho, Chuo-ku, Kobe, 650-0017, Japan

[9] MRC Cognition and Brain Sciences Unit, 15 Chaucer Rd., Cambridge, UK, CB2-7EF

Correspondence to: Tim Rogers (ttrogers@wisc.edu; lead contact) or Matthew Lambon Ralph (Matt.Lambon-Ralph@mrc-cbu.cam.ac.uk)

ORCID: 0000-0001-6304-755X

Keywords: Semantic memory, ECoG, cognition, neural networks, temporal lobe, multivariate pattern classification, dynamic models, temporal generalization

Author Contributions

TTR conducted all simulations, contributed to ECoG analysis, and wrote the initial manuscript draft. CRC and QL contributed to ECoG analysis and manuscript revision. AS, TKi, TKu, SM, RT, AT and RM contributed to ECoG study design, and collected and prepared all ECoG data. MLR contributed to all aspects of the study design, analysis of model and ECoG data, and manuscript preparation.

Abstract

How does the human brain encode semantic information about objects? This paper reconciles

two seemingly contradictory views. The first proposes that local neural populations

independently encode semantic features; the second, that semantic representations arise as a

dynamic distributed code that changes radically with stimulus processing. Combining simulations

with a well-known neural network model of semantic memory, multivariate pattern classification,

and human electrocorticography, we find that both views are partially correct: semantic

information is distributed across ventral temporal cortex in a dynamic code that possesses stable

feature-like elements in posterior regions but with elements that change rapidly and nonlinearly

in anterior regions. This pattern is consistent with the view that anterior temporal lobes serve as

a deep cross-modal "hub" in an interactive semantic network, and more generally suggests that

tertiary association cortices may adopt dynamic distributed codes difficult to detect with common

brain imaging methods.

Key words: semantic memory, ECoG, neural networks, MVPA, temporal generalization, dynamics,

representation, temporal lobe

Introduction

Semantic memory supports the remarkable human ability to recognize new items and

events, infer their unobserved properties, and comprehend and produce statements about them

(1, 2). These abilities arise from neural activity propagating in a broadly distributed cortical

network, with different components encoding different varieties of information (perceptual,

motor, linguistic, etc (3–5). The ventral anterior temporal lobes (vATL) form a hub in this network

that coordinates activation amongst the various surface representations(5, 6). In so doing the

vATL acquires distributed representations that allow the whole network to express conceptual similarity structure, supporting inductive generalization of acquired knowledge across conceptually-related items(7).

Within this framework, contemporary theories differ in their proposals about the semantic representation of visually-presented objects. Many researchers view such representations as arising from the propagation of activity upward through a feature hierarchy, beginning with simple perceptual features, moving through intermediate modality-specific features, and ending with abstract cross-modal features that express semantic category structure. This perspective has strongly influenced computational models of object recognition developed in visual neuroscience(8, 9) and associated brain imaging work(10, 11). Alternatively, semantic representations may arise from interactive settling processes within distributed and dynamic brain networks.(5, 12) On this view, semantic representations are activation patterns encoded jointly over many neural populations, with similar concepts evoking similar patterns. The information encoded by a given population depends on the states of other populations, so that the whole representation is best viewed as a point in a multidimensional state space.(2) Stimulus processing involves a transitioning of the system through the space, rather than the activation of increasingly abstract/complex feature detectors, as the whole system settles toward an interpretation of the input(13). Many models of semantic memory adopt this perspective(12, 14–17), which also aligns with the general view that the ventral visual processing stream is recurrent and interactive(18–20)

The two views carry critically different implications for understanding how neural systems represent semantic information. On featured-based views, local populations of neurons independently encode the presence of a particular feature, licensing a straightforward

interpretation of neural activity: when the population is active, the corresponding feature has

been detected, inferred, or called to mind; when inactive, it hasn't. The temporal behavior of the

population directly indicates the time-course with which the represented feature is available to

influence processing, and the mean neural activity over time indicates the strength with which

the feature was activated in a particular trial or task condition. These ideas motivate efforts to

determine which cortical regions encode which features at which points in time by

correlating/predicting the presence of a semantic feature (such as a category label or property)

with/from local neural activity(3, 21). If, however, semantic representations are distributed, the

local behavior of a single population may not be interpretable independent of the others;(22) and

if semantic processing is also dynamic, the contribution of a local population to the distributed

code may change in real time, potentially in highly nonlinear ways(23). These possibilities suggest

that the treatment of neurophysiological signals as arising from independent feature detectors

can mischaracterize how neural systems encode semantic information.

Figure 1 illustrates why. Suppose a participant names images of tools and mammals while

the responses of two neural populations are measured with high temporal and spatial resolution.

The top panels show hypothetical joint responses to each stimulus over time from onset to

response (together with those of other untested living and manmade items), plotted as

trajectories in a 2D space over time. The shaded panels show how a multivariate classifier

partitions the space when trained to discriminate mammals from tools at one timepoint. The

categories are always well differentiated, so the two populations jointly encode semantic

information at every timepoint, but because the trajectories are nonlinear each population's

contribution to this structure changes over time—the category discrimination plane rotates.

Figure 1. A. Hypothetical joint activations of two neural populations to living and manmade items (left), and the classification plane that would best discriminate tools from mammals at different timepoints. B. Independent correlations between each population's activity and a binary category label for the same trajectories plotted above, shown across time for each (left), averaged across the two populations (middle), and averaged over time for each population independently or for both populations (right).

The bottom panels show how each population's behavior would appear if its activity was

analyzed independently via correlation with semantic information. The orange line shows how

Population 1's activity (ie, the projection of the trajectories in panel A against the vertical axis

only) correlates with the tool/mammal label at each timepoint—the correlation becomes positive

about half-way through the time series The blue line shows how Population 2's activity(ie the

Panel A trajectories projected onto the horizontal axis) correlates with the tool/mammal label: it

quickly shows a negative correlation(tools more active than mammal), then no correlation, then

a positive correlation (mammals more active than tools). From these independent analyses it

might seem that (a) animals are detected only midway through the time-series, (b) tools are

detected earlier than animals and (c) there exist populations that "switch" from tool-detectors to

mammal-detectors. The bottom middle panel shows the mean response across the two

populations at each point in time, as might be observed if the neurophysiological measurement

lacks spatial resolution (e.g., EEG/MEG). The populations appear to detect animals late in the trial.

The right panel shows mean responses across time for each population (consistent with high

spatial and low temporal resolution; e.g. fMRI) and for both populations together (low spatial and

temporal resolution). The former suggests that population 2 plays no important role

distinguishing the categories, while the latter suggests the two populations together selectively

detect animals. These conclusions are incorrect from the distributed and dynamic perspective,

under which the two populations always jointly differentiate the categories but the contribution

of each changes over time (Figure 1A).

The interpretation of neurophysiological signals in the cortical semantic system thus

depends critically upon whether the neuro-semantic code is feature-based or distributed and

dynamic at whatever scale measurements are taken. Efforts to adjudicate the question face three

significant hurdles. First, spatial and/or temporal averaging can obscure signal if the code truly is

distributed and dynamic—discovery requires neural data with high temporal and spatial

resolution, ruling out the non-invasive methodologies that constitute the majority of work in this

area(24). Second, independent univariate analysis can mischaracterize information distributed

across multiple channels—discovery requires multivariate methods(25). Third, studies connecting

neurophysiologal measurements to computational models of visual recognition have primarily

focused on feed-forward models that do not exhibit dynamic processing(10, 26). While some

recent decoding evidence suggests visual processing in ventral temporal cortex is dynamic(20), no

prior work has assessed how representations evolve within distributed and dynamic semantic

models, and consequently it is unclear what this view predicts or how it differs from feature-based

approaches.

We therefore combined computational modeling, multivariate pattern classification, and

electrocorticography (ECoG) to assess whether semantic representations in human vATL are

distributed and dynamic. We focused on vATL due to its central role in semantic representation(5,

6) and because it is a common target for grid implantation in patients awaiting surgery to

remediate epilepsy. We first showed that the nonlinear dynamics highlighted in our thought

experiment arise in a well-studied neurocomputational model of semantic memory(7, 12), then

used temporal generalization of pattern classifiers(27) to establish the predicted "signature" of a

dynamically changing semantic code under this model. We next applied this technique to

intracranial local field potentials collected from the surface of the left vATL while participants

named line drawings of common items, and found the critical decoding signature—providing

strong evidence that, at the level of spatiotemporal resolution captured by ECoG, semantic

structure in vATL is expressed by a distributed code that changes dynamically with stimulus

processing. Finally we considered how the neural code exploited by classifiers changed over time

and across the ventral temporal surface, with results that reconcile the two divergent views of

semantic representation in the brain .

Results

Simulation study. Simulations provide a formal basis for understanding the implications of the

distributed and dynamic view, because a computer model's architecture, behavior, learning and

testing patterns are fully known. We therefore adapted the well-known "hub and spokes" model

of semantic memory (5, 12, 28) to assess whether semantic representations change dynamically

with stimulus processing and how the temporal generalization method can uncover such a code.

The model was a fully continuous and recurrent neural network that learns cross-modal

associations between distributed visual and verbal representations via three reciprocally-

connected hidden layers (Figure 2A). Given positive input to a subset of visual or verbal units, it

learns to activate the corresponding item's unspecified visual and/or verbal attributes. Activity

propagates in both directions, from surface representations to hub and back, so that the trained

model settles to an attractor state representing any item specified by the input. We trained the

model to complete patterns representing ninety items from three model conceptual domains

(e.g., animals, objects, and plants), each organized into three categories containing ten items (see

Methods for details). Items from different categories in the same domain shared a few properties

while those in the same category shared many. We then presented the trained model with visual

input for each item and recorded the resulting activation patterns over hub units for each tick of

simulated time as the network settled.

To visualize how model internal representations changed during stimulus processing, we

computed a 3D multi-dimensional scaling (MDS) of activation patterns at all timepoints during

"perception" of each stimulus, then plotted the changing representation for each item as a line in

this space. The result in Figure 2B shows a systematic but nonlinear elaboration of the conceptual

structure latent in the stimulus patterns: the domains separate from one another early on, but

each item follows a curved trajectory over time. The curves are not an artifact of data-reduction—

Figure 2C shows these trajectories in the native activations of randomly-sampled unit pairs in one

network run, where they are clearly nonlinear (and see SI-1 for comparative results with linearly-

changing representations). Consequently, independent correlation analysis of each unit's

behavior produces mixed results (Figure 2D), with some behaving like tonic category detectors

(green squares), some like transient detectors (blue), some appearing to flip their category

preference (red) and others appearing not to code category information at all (gray).

Figure 2. A. Model architecture. B. 3D MDS of hub activation patterns learned in one model run—each line shows the trajectory of a single item over time in the compressed space. C. The same trajectories shown in uncompressed unit activations for 9 randomly sampled unit pairs, horizontal and vertical axes each showing activation of one unit. D. Feature-based analysis of each hub unit in one network run. Each square shows one unit. Lines trace, across time, the correlation between unit activation and category labels across items category labels with dashed lines showing significance thresholds. Color indicates different patterns of responding (see text).

Thus the full distributed pattern across hub units elaborates conceptual structure from

early in processing, but the progression is nonlinear and only clearly discernable in a low-

dimensional embedding of the space. Such an embedding can be computed for the model

because we know which units are important and can apply the MDS to all and only those units.

The same approach cannot be applied to ECoG data for two reasons. First, one cannot know a-

priori which channels record signals relevant for semantic representation and thus cannot simply

compute a low-dimensional embedding of all data collected. Instead one must fit a statistical

model that will selectively weight signals useful for discerning semantic structure. Second,

whereas the model allows access to the entire network, a cortical surface sensor array only

sparsely samples the neural responses contributing to a semantic representation. The problem

thus requires a multivariate statistical model capable of revealing a dynamically changing neural

code when fitted to sparsely-sampled neural data.

We therefore used multivariate logistic classifiers to decode semantic category

information from hub activation patterns and assessed their behavior on simulated ECoG data.

For each simulated participant we selected a sparse random subsample (15%) of all hub units—

analogous to the sparse sampling of neural responses provided by a cortical sensor array—and

recorded their responses to each stimulus at every tick of time. We fitted a separate classifier at

each timepoint to distinguish two semantic domains from the activation patterns elicited over the

subsampled units. Figure 3A shows the cross-validated accuracy at each timepoint averaged over

many network runs and subsamples. The classifiers performed well above chance as soon as input

activation reached the hub units and throughout the time window.

Figure 3. A. Mean and 95% confidence interval of the hold-out accuracy for classifiers trained at each tick of time in the model. B. Accuracy for each classifier (rows) tested at each point in time (columns). C. Mean accuracy for each cluster of classifiers at every point in time. Colored dots show the timepoints grouped together in each cluster. D. Proportion of the full time-window for which mean classifier accuracy in each cluster was reliably above

chance.

To assess representational change over time we next adopted a temporal generalization

approach(27), using the classifier fitted at one timepoint to decode the patterns observed at each

other timepoint. Accuracy should remain high if the information a classifier exploits at the training

time persists at other timepoints. The temporal generalization profile of each classifier thus

indicates how the underlying neural code persists or changes over time. Classifiers fitted to earlier

activation patterns generalized only to immediate temporal neighbors, while those fitted to later

patterns generalized over a wider window but failed at decoding earlier states (Figure 3B). To

better visualize these results, we clustered the rows of the matrix in Figure 3B and plotted the

mean accuracy of the classifiers in each cluster across time (Figure 3C). The results exhibit an

"overlapping waves" pattern: classifiers that work on early patterns quickly fail at later timepoints

where a different classifier succeeds. As time progresses, the clusters include more classifiers and

the breadth of time over which the classifiers perform well widens (Figure 3D).

This pattern reflects the nonlinear trajectories apparent in the sparsely-sampled

representational space as the network settles to an attractor state. When trajectories curve,

earlier classification planes fail later in time while later planes fail at earlier time-points. If

representations simply moved linearly from initial to final state, early classifiers would continue

to perform well throughout processing—a pattern observed in simulations with feature-based

models, models with distributed representations that evolve linearly, and recurrent but shallow

neural networks (see SI-1). In the deep network, the non-linear dynamic pattern was observed

only in the hub layer—in more superficial layers, the code remained stable (SI-2). The simulations

thus suggest that distributed and dynamic semantic representations can arise in deep layers of

interactive networks and will elicit a particular "signature" when multivariate pattern classifiers

are used to decode semantic structure from ECoG data. Specifically, such classifiers will show:

1.   Constant decodability. Neural activity predicts stimulus category at every time point once

activation reaches the vATL.

2.   Local temporal generalization. Classifiers generalize best to immediate temporal neighbors

and worst to distal timepoints.

3.   Widening generalization window. The temporal window over which classifiers generalize

grows wider over time.

4.   Change in code direction. Elevated neural activity can signify different semantic information

at different points in time.

These are the characteristics we looked for in the ECoG study.

ECoG study. The dataset included local field potentials (LFPs) collected at 1000Hz from 16-24

electrodes situated in the left ventral anterior temporal cortex of 8 patients awaiting surgery while

they named line-drawings of common animate and inanimate items matched for a range of

confounds (see Methods). We analyzed LFPs over the 1640ms following stimulus onset, a window

that allows us to assess decodeability both before and after the mean onset of naming (1190ms).

LFPs were decoded using a 50ms sliding-window, with separate classifiers fitted at each window

and the window advancing in 10ms increments. This yielded 160 classifiers per subject, each

decoding LFPs across all vATL electrodes in a 50ms window. Each classifier was then tested on all

160 time-windows. The classifiers were logistic regression models fitted with L1 regularization to

encourage coefficients of 0 for many features (see Methods).

Figure 4. A. Mean and 95% confidence interval of the hold-out accuracy for classifiers trained at each 50ms time window of ECoG data. B. Mean accuracy across participants for each classifier (rows) tested at each timepoint (columns) in the ECoG data. C. Mean accuracy for each cluster of classifiers at every point in time. Colored bars show the timepoints grouped together in each cluster. D. Proportion of the full time-window for which mean classifier accuracy in each cluster was reliably above chance. E. Mean classifier coefficients across participants plotted on a cortical surface at regular intervals over the 1640ms window. Warm vs cool colors indicate positive versus negative mean coefficients, respectively. In A and C, vertical line indicates mean onset of naming.

Hold-out accuracy exceeded chance at about 200ms post stimulus onset, well before

name initiation, and remained statistically reliable throughout the time window (Figure 4A) with

no obvious change at the mean time of naming onset. At 200ms classifiers generalized well to

timepoints near the training window but poorly to more distal timepoints, with the generalization

envelope widening as time progressed (4B). We again clustered the classifiers based on their

temporal accuracy profile, then plotted mean profiles for each cluster (4C). The result was an

"overlapping waves" pattern strikingly similar to the simulation: classifiers that performed well

early in processing quickly declined in accuracy, replaced by a different well-performing set. Over

time neighboring classifiers began to show similar temporal profiles, forming larger clusters that

performed above chance for a broader temporal window (4D).

Finally, we considered whether and how the neuro-semantic code changed over time. For

each time window we projected the classifier weights for all electrodes in all subjects to a cortical

surface model, then animated the results (see movie S1). Figure 4E shows snapshots every 200ms

post stimulus onset. In mid-posterior regions the code was spatially and temporally stable—

weights on the lateral aspect were positive while those on the medial aspect were negative,

consistent with feature-based views of representation. The anterior pattern differed, flipping

from mainly positive at 200ms to mainly negative by 800ms and fluctuating across time and space

throughout. In other words, the "meaning" of a positive deflection in the LFP—whether it signaled

animal or non-animal—stayed constant posteriorly but changed direction over time anteriorly,

consistent with the deep, distributed, dynamic view (see SI-3).

268   **Discussion**

We have combined computational modeling, multivariate pattern classification, and

human ECoG to better understand how ventral temporal cortex encodes semantic information

about visually-presented stimuli. The results suggest that, at the scale of intracranial LFPs, neural

signals throughout ventral temporal lobe jointly express semantic information from about 200ms

post stimulus-onset, via a distributed code that is stable and feature-like in middle/posterior

regions but dynamic and nonlinearly-changing in anterior regions. In simulation we showed that

similar phenomena arise in a deep, interactive neuro-semantic model, producing a characteristic

decoding signature: classifiers perform well in the time-window when they were trained, but

generalize over a narrow time envelope that widens as the system settles. This pattern was only

observed in a model combining distributed representation, interactive processing, and a deep

architecture (see SI). Remarkably similar phenomena were observed in ECoG data collected from

the surface of ventral temporal lobe while participants named line-drawings, supporting the

proposal that vATL encodes distributed semantic representations that change dynamically and

nonlinearly with stimulus processing by virtue of this region's role as a deep hub within the cortical

semantic network.

This proposal resolves a long-standing puzzle. Convergent methods have established the

centrality of vATL for semantic memory, including studies of semantic impairment[29–31], lesion-

symptom mapping[32], functional[33, 34] and structural37[35, 36] brain imaging, and transcranial

magnetic stimulation[37, 38]. Yet multivariate approaches to discovering neuro-semantic

representations rarely identify the vATL, instead revealing semantic structure more

posteriorly[39–41]. One prominent study suggested that semantic representations may tile the

entire cortex except for the vATL[4]. Setting aside significant technical challenges of successful

neuroimaging of this region36, almost all such studies have employed non-invasive imaging

techniques that sacrifice either temporal or spatial resolution—a compromise that will destroy

signal in vATL if semantic representations there are distributed and dynamic at the scale we have

measured, but will preserve signal in posterior regions where the code is more stable. Thus the

widespread null result may arise precisely because semantic representations in vATL are

distributed and dynamic.

Consistent with this view, the current results in middle/posterior regions accord well with

evidence from classical functional brain imaging of visual semantics. Several fMRI studies have

reported category effects in the mid-posterior fusiform, with animate items eliciting greater

activation on the lateral bank and inanimate items eliciting greater activation on the medial

bank(42–44). In our analysis, these are regions where a stable, feature-like code arises, with

animate items signaled by positive LFPs on the lateral aspect and negative LFPs on the medial

aspect. Since the location and direction of the code are stable in these regions within and across

subjects, the signal remains detectable even with the spatial and temporal averaging that occurs

in univariate fMRI.

These conclusions rest partly on the analysis of classifier weights. When multiple channels

are affected by a common source of noise, multivariate decoders can place weights on

uninformative channels that "subtract out" the noise corrupting the signal on informative

channels(45). Might the fluctuating weights observed in vATL arise, not because the region

encodes semantic structure, but because it serves to "cancel out" effects of correlated noise on

the signal-carrying channels more posteriorly? Four lines of evidence suggest not. First, we fit

classifiers to only the anterior electrodes in each participant and observed reliable decoding (SI-

4). Second, an earlier study applied searchlight representational similarity analysis (RSA) to the

same data(46), and found that vATL was the only local region that reliably encodes semantic

similarity structure. Neither result could obtain if vATL simply subtracted out correlated noise

from more posterior areas. Third, the observed pattern of a stable code posteriorly and

fluctuating code anteriorly was predicted by the current simulations, using an model validated

against neuropsychological, anatomical, and brain-imaging results in prior work(5). Fourth, the

critical importance of ATL for semantic representation has been established by the broad range

of converging evidence cited previously.

Prior studies applying temporal generalization to MEG data in visual semantic tasks

uniformly report a very narrow and unchanging band of temporal generalization(47, 48), a pattern

consistent with the proposal that the neuro-semantic code changes rapidly over the course of

stimulus processing. Our results differ from the MEG pattern, and indeed from most other work

applying the temporal generalization approach(27), in showing a gradual widening of the

temporal generalization window. This phenomenon does not arise from the autocorrelational

structure of the data itself—the window of time over which an electrode reliably predicts its own

future state does not grow wider with stimulus processing (SI-5). Instead the widening must

reflect an increasingly stable semantic code. The simulation explains why the pattern arises in

anterior temporal cortex: hub representations in vATL change rapidly early on due to interactions

with modality-specific representations throughout cortex, but these changes slow as the full

activation pattern emerges across network components.

While ECoG provides simultaneously high spatial and temporal resolution compared to

non-invasive brain imaging, its measurements are nevertheless influenced by activity in hundreds

of neurons. For this reason we have emphasized that the anterior neuro-semantic code appears

distributed and dynamic at the scale of local neural population activity, as measured by LFPs. Our

conclusions do not shed light on the code employed by single neurons, or other fine-grained units

such as cortical columns, though the temporal-generalization approach we have deployed may

extend well to data collected at this scale.

Finally, why should a dynamic distributed code arise specifically within the vATL? The area

is situated at the top of the ventral visual stream, but also connects directly to core language

areas(49) and, via middle temporal gyrus, to parietal areas involved in object-directed action(12).

It receives direct input from smell and taste cortices (50) , and is intimately connected with limbic

structures involved in emotion, memory, and social cognition(51). Thus vATL anatomically forms

the hub of a cross-modal network ideal for encoding associations among visual, linguistic, action,

sensory, and social/motivational representations. Hub neurons interact Light a wide variety of

subsystems, each encoding a different kind of structure and content, potentially pushing the hub

representations in different directions over time as activity propagates in the network. Other

network components lying closer to the sensory or motor periphery connect mainly within

individual modality-specific systems(35), so may be less impacted by such cross-modal

interactions, as observed in the model. For this reason, the feature-based approach that has

proven indispensable for characterizing neural representations in modality-specific cortices may

be less suited to understanding the distributed and dynamic representations that arise in deeper

and more broadly-connected (tertiary association) cortical regions. These include regions critical

for human semantic knowledge, and potentially other higher-level cognitive functions.

356   **Materials and Methods**

Simulation study.

The model implements the "distributed-plus-hub" theory of semantic representation

developed in prior work(5, 6, 12, 52, 53). It is a deep, fully continuous and recurrent neural

network48 that learns associations among visual representations of objects, their names, and

verbal descriptors, via a central cross-modal hub, with units and connectivity shown in Figure 2A

of the main paper. Simulations were conducted using the open-source Light Efficient Network

Simulator updated for contemporary libraries (https://github.com/crcox/lens). Code for

replicating the simulations and the data reported in this paper are available at

https://github.com/ttrogers.

All units employed a continuous-time sigmoidal activation function with a time-constant

of 0.25. Visual and Verbal units were given a fixed, untrainable bias of -3 that produced a low

activation state without positive input. Hidden units had trainable biases. To simulate perception

of an image, units encoding the item's visual representation were given direct positive stimulation

of +6 so that, combined with the fixed bias, they received a net input of +3 (in addition to any

inputs from other units in the model). The resulting changes in unit activations propagated

through visual hidden, hub, and verbal hidden units to eventually alter activation states in the

verbal units. Because the model was reciprocally connected, such downstream changes fed back

to influence upstream states at each moment of simulated time, as the whole system settled to a

stable state. To simulate verbal comprehension, the same process unfolded, but with positive

input externally provided to verbal units. Units updated their activation states asynchronously in

permuted order on each tick of time and were permitted to settle for 5 time intervals (a total of

20 updates) during training and 8 time intervals (32 updates) during testing.

Model environment. The model environment contained visual and verbal patterns for

each of 90 simulated objects, conceived as belonging to 3 distinct domains (e.g. animals, objects,

and plants). Each domain contained 10 items from each of 3 sub-categories—thus there were 30

"animals," 30 "objects" and 30 "plants." Visual patterns were constructed to represent each item

by randomly flipping the bits of a binary category prototype vector in which items from the same

domain shared a few properties and items from the same category shared many. The verbal

patterns were constructed by giving each item a superordinate label true of all items within a

given domain (animal, object, plant), a basic-level label true of all items within a category (e.g.

"bird", "fish", "flower", etc), and a subordinate label unique to the item (e.g. "robin", "salmon",

"daisy", etc). These procedures, adopted from prior work(52), generated model input/target

vectors that approximate the hierarchical relations among natural concepts in a simplified manner

that permits clear understanding and control of the relevant structure.

Training. For each input, target patterns that fully specified the item's visual and verbal

characteristics were applied throughout the duration of stimulus processing. The model was

trained with backpropagation to minimize squared error loss. Half of the training patterns

involved generating verbal outputs from visual inputs, while the other half involved generating

visual outputs from verbal inputs. The model was initialized with small random weights sampled

from a uniform distribution ranging from -1 to 1, then trained for 30,000 epochs in full batch mode

with a learning rate of 0.002 and without weight decay. For each pattern, the settling process was

halted after 20 activation updates, or when all Visual and Verbal units were within 0.2 of their

target values, whichever came first. For all reported simulations the model was trained 5 times

with different random weight initializations. After training, all models generated correct output

activations (ie, on the correct side of the unit midpoint) for more than 99% of output units across

all training runs. Each model was analyzed independently, and the final results were then

averaged across the five runs.

Testing. The picture-naming study was simulated by presenting visual input for each item,

recording the resulting activations across the 25 hub units at each update as the model settled

over 32 updates, and distorting these with uniform noise sampled from -0.005 to 0.005 to

simulate measurement error. As the model settles over time it gradually activates the word unit

corresponding to the item name, and in this sense simulates picture naming. Just as in the ECoG

data, we recorded unit activations across a fixed period of time, regardless of when the correct

name unit became active.

Note that, whereas the ECoG study employed items drawn from two general semantic

domains (living and nonliving), the model was trained on 3 domains. This provided a simple model

analog to the true state of affairs in which people know about more semantic kinds than just those

appearing in the ECoG stimulus set. To simulate the study, the model was presented with 60 items

selected equally from 2 of the 3 semantic domains—so as in the study, half the stimuli belonged

to one domain and half to another. To ensure results did not reflect idiosyncrasies of one domain,

we simulated the task with each pair of domains and averaged results across these.

Analysis. All analyses were conducted using R version 3.6. To visualize the trajectory of

hub representations through unit activation space, we computed a simultaneous 3-component

multidimensional scaling of the unit activation patterns for all 90 items at all 33 timepoints using

the native R function cmdscale. The resulting coordinates for a given item at each point in time

over the course of settling were plotted as lines in a 3D space using the scatterplot3d package in

R. Figure 2B shows the result for one network training run. Figure 2C shows the same trajectories

in the raw data (ie actual unit activation states rather than latent dimensions in a MDS) for

randomly-sampled pairs of hub units.

To simulate decoding of ECog data, we evaluated logistic classifiers in their ability to

discriminate superordinate semantic category from patterns of activity arising in the hub at each

timepoint. As explained in the main text, we assume that ECoG measures only a small proportion

of all the neural populations that encode semantic information. We therefore sub-sampled the

hub-unit activation patterns by selecting 3 units at random from the 25 hub units and using their

activations to provide input to the decoder. Classifiers were fitted using the glm function and the

binomial family in R. A separate decoder was fitted at each time-point, and unit activations were

mean-centered independently at each time point prior to fitting. We assessed decoder accuracy

at the time-point where it was fitted using leave-one-out cross-validation, and also assessed each

decoder at every other time point by using it to predict the most likely stimulus category given

the activation pattern at that time point and comparing the prediction to the true label. This

process was repeated 10 times for each model with a different random sample of 3 hub units on

each iteration. The reported results then show mean decoding accuracy averaged over the 5

independent network training runs, for decoders trained and tested at all 33 time points. The

above procedure yielded the decoding accuracy matrix shown as a heat plot in Figure 3B.

Each row of this matrix shows the mean accuracy of decoders trained at a given timepoint,

when those decoders are used to predict item domain at each possible timepoint. The diagonal

shows hold-out accuracy for decoders at the same time point when they are trained, but off-

diagonal elements show how the decoders fare for earlier (below diagonal) or later (above)

timepoints. Decoders that perform similarly over time likely exploit similar information in the

underlying representation, and so can be grouped together and their accuracy profiles averaged

to provide a clearer sense of when the decoders are performing well. To this end, we clustered

the rows of the decoding accuracy matrix by computing the pairwise cosine distance between

these and subjecting the resulting similarities to a hierarchical clustering algorithm using the

native hclust function in R with complete agglomeration. We cut the resulting tree to create 10

clusters, then averaged the corresponding rows of the decoding accuracy matrix to create a

temporal decoding profile for each cluster (lines in Figure 3C). We selected 10 clusters because

this was the highest number in which each cluster beyond the first yielded a mean classification

accuracy higher than the others at some point in time. Similar results were obtained for all cluster-

sizes examined, however.

Finally, to understand the time-window over which each cluster of decoders performs

reliably better than chance, we computed a significance threshold using a one-tailed binomial

probability distribution with Bonferroni correction. Each decoder discriminates two categories

from 60 items, with probability 0.5 of membership in either category. We therefore adopted a

significance threshold of 44 correct items out of 60, corresponding to a binomial probability of p

< 0.03 with Bonferroni correction for 330 tests (10 clusters at each of 33 time points). The barplot

in Figure 3D shows the proportion of the full time window during which each decoding cluster

showed accuracy above this threshold.

ECoG study.

Participants. Eight patients with intractable partial epilepsy (seven) or brain tumor (one)

originating in the left hemisphere participated in this study. These include all left-hemisphere

cases described in a previous study[50], and we will use the same case numbers reported in that

work (specifically cases 1-5, 7, and 9-10). Background clinical information about each patient is

summarized in Table S1. Subdural electrode implantation was performed in the left hemisphere

for presurgical evaluation (mean 83 electrodes, range 56-107 electrodes/patient). 16-24

electrodes (mean 20 electrodes) covered the ventral ATL in each patient. The subdural electrodes

were constructed of platinum with an inter-electrode distance of 1 cm and recording diameter of

2.3 mm (ADTECH, WI). ECoG recording with subdural electrodes revealed that all epilepsy patients

had seizure onset zone outside the anterior fusiform region, except one patient for whom it was

not possible to localize the core seizure onset region. The study was approved by the ethics

committee of the Kyoto University Graduate School of Medicine (No. C533). Participants all gave

written information consent to participate in the study.

	Patient 1	Patient 2	Patient 3	Patient 4
Age, gender, handedness	22M R	29M R&L	17F R	38F R
WAIS-R (VIQ,PIQ,TIQ)	70, 78, 69	72, 78, 72	67, 76, 69	84,97,89
WMS-R (Verb, Vis , Gen, Attn, Del recall)	99, 64, 87, 91, 82	99, 92, 97, 87, 83	51, <50, <50, 81, 56	75,111,83,62,53
WAB	95.6	96	97.2	98.5
WADA test (Language)	Left	Bilateral	Left	Left
Age of seizure onset	16	10	12	29
Seizure type	non-specific aura → CPS, GTCS	aura (metamorphosia, ERS) → CPS	discomfort in throat → CPS	ERS → CPS
Ictal ECoG onset	aMTG	PHG	PHG	PHG
MRI	L basal frontal cortical dysplasia L anterior temporal arachnoid cyst	L posterior temporal cortical atrophy	L temporal tip arachnoid cyst	L hippocampal atrophy/sclerosis
Pathology	FCD type IA	FCD type IA Hippocampal sclerosis*	FCD type IB	Hippocampal sclerosis**

	Patient 5	Patient 7	Patient 9	Patient 10
Age, gender, handedness	55M R	41F R	51M R	38F R
WAIS-R (VIQ,PIQ,TIQ)	105,99,103	72, 83, 75	73, 97, 83	109, 115,112
WMS-R (Verb, Vis, Gen, Attn, Del recall)	71,117,84,109,72	83,111,89,94,82	80,101,85,1919,91	71,79,70,90,58
WAB	98	97.3	89.6	96.9
WADA test (Language)	Left	Right	Left	Left
Age of seizure onset	55	19	43	28
Seizure type	CPS (once)	aura (nausea,feeling pale) → CPS	CPS	non-specific aura → CPS
Ictal ECoG onset	none	PHG	mITG	SMG
MRI	Low-grade glioma L medial temporal lobe	L hippocampal atrophy/screrosis L parieto-occipital perinatal infarction	Left temporal cavernoma	L parietal opercurum tumor
Pathology	Diffuse astrocytoma	FCD IA Hippocampal sclerosis*	arteriovenous malformation	Oligoastrocytoma

Table 1. Patient characteristics. CPS: complex partial seizure; GTCS: generalized tonic clonic seizure; ECoG: electrocorticogram; ERS: epigastric rising sensation; a/pMTG: anterior/posterior part of the middle temporal gyrus; a/pMTG: anterior/posterior part of the middle temporal gyrus; FCD: focal cortical dysplasia; * dual pathology ** diagnosed by clinical findings

Stimuli and Procedure. One hundred line drawings (50 living and 50 nonliving items) were

obtained from previous norming studies(51,52). A complete list of all items can be found in (50).

Living and nonliving stimuli were matched on age of acquisition, visual complexity, familiarity and

word frequency, and had high name agreement. Independent-sample t-tests did not reveal any

significant differences between living and nonliving items for any of these variables.

Participants were presented with stimuli on a PC screen and asked to name each item as

quickly and accurately as possible. All stimuli were presented once in a random order in each

session and repeated over four sessions in the entire experiment. The responses of participants

were monitored by video recording. Each trial was time-locked to the picture onset using in-house

MATLAB scripts (version 2010a, Mathworks, Natick, MA). Stimuli were presented for 5 seconds

each and each session lasted 8 minutes 20 seconds. Participants' mean naming time was 1190ms.

Responses and eye fixation were monitored by video recording.

Data preprocessing. Data preprocessing was performed in MATLAB. Raw data were

recorded at sampling rate of 1000 Hz for six patients and at 2000Hz for two patients. The higher

sampling rates for the two patients were down-sampled to 1000Hz by averaging measurements

from each successive pair of time-points. The raw data from the target subdural electrodes for

the subsequent analysis were measured in reference to the electrode beneath the galea

aponeurotica in 4 patients (Patients 4,5,7 and 10) and to the scalp electrode on the mastoid

process contralateral to the side of electrode implantation in 4 patients (Patients 1-3 and 9).

Multivariate pattern-classification analyses were also conducted without such referencing and

yielded near-identical results. Baseline correction was performed by subtracting the mean pre-

stimulus baseline amplitude (200 ms before picture onset) from all data points in the epochs.

Trials with greater than +/-500 µV maximum amplitude were rejected as artifacts. Visual

inspection of all raw trials was conducted to reject any further trials contaminated by artifacts,

including canonical interictal epileptiform discharges. The mean waveform for each stimulus was

computed across repetitions. Data included, for each stimulus at each electrode, all

measurements beginning at stimulus onset and continuing for 1640ms. While this window

includes the onset of articulation toward the end, the critical results cannot reflect such motor

activity since all key phenomena are observe prior to mean time to initiate the utterance (1190

ms).

*Multivariate classification analysis.*The pre-processed data yielded, for each electrode in

each patient, a times-series of local field potentials sampled at 1000Hz over 1640ms for each of

100 stimuli. For each patient we trained classifiers to discriminate animal from non-animal images

given the LFPs evoked by each stimulus across all ventral-temporal electrodes in a 50ms time-

window. In a patient with 20 electrodes, one 50ms window contains 1000 measurements (50 LFPs

for each electrode x 20 electrodes). For each time window in every patient these measurements

were concatenated into feature vectors for each of the 100 stimuli, with the time windows

advancing along the time-series in 10ms steps. Thus the first window included 1-50ms post

stimulus onset, the next included 11-60ms, and so on. This procedure yielded feature vectors for

all 100 items in 160 time-windows for every subject.

The classifiers were logistic regression models fitted with L1 regularization[53] using the

glmnet function in Matlab. L1-regularization applies an optimization penalty that scales with the

sum of the absolute value of the classifier coefficients and thereby encourages solutions in which

many features receive coefficients of 0. This approach is useful for a sliding-window analysis

because features receiving a 0 coefficient in the classifier have no impact on its performance when

it is assessed at other time points. So long as the information exploited by a classifier at time t is

present at a different time t +/- n, the classifier will continue to perform well, even if other

features are in very different states. Thus classifiers trained with L1 regularization have the

potential to show dynamic changes in the underlying code.

Classifier accuracy for a given time-window and subject was assessed using nested 10-

fold cross-validation. In each outer fold, 10% of the data were held out, and the remaining 90% of

the data were used with standard 9-fold cross-validation to search a range of values for the

regularization parameter. When the best weight was selected, a model was fitted to all

observations in the 90% of the training data and evaluated against the remaining 10% in the outer-

loop hold-out set. This process was repeated 10 times with different final hold-outs, and classifier

accuracy for each patient was taken as the mean hold-out accuracy across these folds. The means

across patients are the data shown in Figure 4A and the diagonal of 4B in the main paper. A final

classifier for the window was then fitted using all of the data and the best regularization

parameter. This classifier was used to decode all other time-windows, yielding the off-diagonal

accuracy values shown in Figure 4B.

The above procedures produced a pattern classifier for each of 160 50ms time-windows

in every subject, with every classifier then tested at every time-window within each subject. Thus

the classifier accuracy data were encoded in a 160x160-element decoding matrix in each subject.

The matrices were averaged to create a single 160x160-element matrix indicating the mean

decoding accuracy for each classifier at each point in time across subjects. This is the matrix shown

in Figure 4B.

To better visualize how the code exploited by each classifier changes over time, we

clustered the rows using the same agglomerative hierarchical approach described for the

simulations. We considered solutions ranging from 4 to 15 clusters and plotted the mean

decoding accuracy over time across the classifiers within each cluster. All cluster sizes produced

the overlapping-waves pattern. In the main paper we show the 10-cluster solution as it is the

largest number in which each cluster after the first has a mean accuracy profile that is both

statistically reliable and higher than every other cluster at some point in time.

To assess the breadth of time over which a cluster showed reliable above-chance

classification accuracy, we again set Bonferroni-corrected significance thresholds using the

binomial distribution. Stimuli included 100 items, with a .5 probability of each item depicting an

animal. In the 1640ms measurement period there are 32 independent (ie non-overlapping) 50ms

time windows, and we assessed the mean classifier performance for each of 10 clusters at every

window. We therefore corrected for 320 multiple comparisons using a significance threshold of

68 correct ($p < 0.0001$ per comparison, $p < 0.03$ with correction).

Surface plot visualization. Magnetization-prepared rapid gradient-echo (MPRAGE)

volumetric scan was performed before and after implantation of subdural electrodes as a part of

presurgical evaluations. In the volumetric scan taken after implantation, the location of each

electrode was identified on the 2D slices using its signal void due to the property of platinum

alloy[54]. Electrodes were non-linearly co-registered to the patient MRI (MPRAGE) taken before

implantation, and then to MNI standard space (ICBM-152) using FNIRT

(www.fmrib.ox.ac.uk/fsl/fnirt/). The native coordinates of all the electrodes for all patients were

morphed into MNI space and resampled into 2 mm isotropic voxels[55].

Projecting classifier coefficients to the surface. As described above, a separate logistic

classifier was fitted to each 50ms window in each subject. The classifier was specified as a set of

regression coefficients, with one coefficient for each timepoint at each electrode in the patient,

and many coefficients set to 0 due to L1-regularization. The sign of the classifier coefficient

indicates the "meaning" of a LFP deflection in a particular direction: a positive coefficient indicates

that animals are "signaled" by a positive deflection in the LFP, while negative coefficients indicate

that animals are signaled by a negative deflection. The magnitude of the coefficient indicates the

"importance" of the measurement, in the context of all other LFPs appearing in the classifier. The

distribution of coefficient directions and magnitudes across the cortex and over time thus

provides an indication of how the underlying neuro-semantic code changes over time.

For a single time window we computed, separately for each electrode in each participant,

the magnitudes (sum of absolute values) of the classifier weights across the 50 time points in the

window. The resulting data were exported from Matlab to NIFTI volumes using the NIFTI

toolbox(https://www.mathworks.com/matlabcentral/fileexchange/8797-tools-for-nifti-and-

analyze-image) and projected from all electrodes and subjects onto the common cortical surface

map using AFNI's 3dVol2Surf relative to the smooth white matter and pial surfaces of the ICBM

152 surface reconstructions shared by the AFNI team and the NIH (https://afni.nimh.nih.gov/

pub/dist/tgz/suma_MNI152_2009.tgz). The space between corresponding nodes on the two

surfaces were spanned by a line segment sub-divided at 10 equally spaced points. The value

displayed on the surface is the average of the values where these 10 points intersect with the

functional volume along that line segment. Once mapped to the surface, the results were spatially

smoothed along the surface with an 8mm full-width half-max Gaussian kernel using the

SurfSmooth function in SUMA. We inclusively masked any surface point with a non-zero value in

this surface projection. A separate mask was generated for each time window.

To visualize how the representational code changes over time within the surface mask we

next carried out a similar procedure on the classifier coefficients themselves, without taking the

absolute values. At each electrode in every subject we summed the classifier coefficients over the

50ms time window, yielding a single positive or negative real-valued number at each electrode

for each time window. These values were again projected onto a common brain surface and

spatially smoothed with an 8mm FWHM Gaussian blur along the surface. In the resulting maps,

any colored point indicates a cortical region that received a non-zero value in the weight

magnitude mask, while the hue indicates the direction of the classifier coefficient in the area—

that is, whether a positive deflection of the LFP for nearby electrodes indicated that the stimulus

was an animal (warm colors), a non-animal (cool colors), or showed no systematic direction

(green). A separate map of this kind was generated for each of 160 time windows. We animated

the results to visualize how they change over time using the open-source ffmpeg software

(https://ffmpeg.org/) with linear interpolation between successive frames. The animation is

shown in Movie S1; snapshots of this visualization are shown in Figure 4E.

Acknowledgments

This work was partially supported by Medical Research Council Programme Grant MR/J004146/1

and by European Research Council grant GAP: 502670428 - BRAIN2MIND_NEUROCOMP.

Competing interests

The authors declare no competing interests.

Supplementary Information

SI-1: Comparison of deep model results to control models.

The main paper highlights four properties of the neural decoding results observed in both the

deep neural network model and in the human ECoG data: constant decodability, local temporal

generalization, a widening window of generalization, and change in neural code direction in the

ATL hub. We suggested that these properties arise because semantic structure is encoded as

distributed activation patterns that change in highly nonlinear ways due to their situation in the

deep cross-modal hub of a dynamic cortical network. This argument implies that the signature

pattern would not arise in models that adopt different kinds of representation and processing

mechanisms, nor in the shallower layers of the deep model. In this section we assess this

implication by comparing the main results with those observed in three alternative models of

semantic representation.

Distributed versus feature-based representations.

By distributed representation, we mean that many neural populations or units can jointly

contribute to representation of structure even if they do not each independently encode the

structure. Deep neural network models are capable of acquiring distributed representations of

this kind (22) and may be contrasted with models proposing that semantic representations are

comprised of elements that each independently detect a particular semantic feature, such as

membership in a particular conceptual domain or category. We therefore considered what the

decoding signature would look like in such a feature-based model. The 90 items were represented

with a vector in which two elements were dedicated to each conceptual domain (animal, plant,

object) and to each basic-level category (bird, fish, flower, etc; total of 9 categories). For instance,

a particular instance of flower would activate the two "plant" features and the two "flower"

features; an instance of tree would activate the same two "plant" features and two "tree"

features, etc. This yielded 24 elements total; to equate the number of features with the number

of units in the deep network simulation, we added a 25th vector element that always adopted a

low activation value.

We simulated the gradual activation of features over the course of processing by generating a 33-

step time-series for each feature and each item presentation. All units began with an activation

of 0, and features true of the stimulus would ramp up their activation according to a sigmoid

function with a constant slope and a randomly-sampled offset term determining when in the

stimulus presentation window the feature would begin to activate. This procedure yielded a

dataset analogous to the evolution of internal representations in the deep network, but with

feature-based semantic representations in which features activated with randomly-sampled

time-courses.

Dynamic versus linear.

By dynamic processing, we mean that units can influence themselves via feedback from the other

units to which they send connections. Reciprocally connected sets of units are coupled and so

behave as a dynamic system in which states evolve together over time. Often the dynamics in

such a system are non-linear, producing radical changes in the ways that neural states encode

information. Thus the importance of dynamic processing in the deep neural network model can

be assessed by contrasting the primary results with an alternative model that employs starting

and ending representations identical to the deep model, but with intermediate states simply

moving in a straight line from start to finish. We created such a model by recording the initial and

final representations arising in the deep neural network model, then creating a 33-step time-

series for each stimulus representing a linear interpolation of the representation moving from

initial to final state. For a given stimulus, each step of the time series was created as a proportional

weighted average of the initial and final states, with the first step giving all the weight to the initial

representation, subsequent steps gradually shifting more weight to the final representation, and

the last step giving zero weight to the initial representation. This procedure yielded a dataset in

which initial and final representations were distributed identically to the deep network, but the

trajectories of the representations over time were linear interpolations between these.

Deep versus shallow.

By deep network, we mean a neural network that has multiple hidden layers interposing between

Visual and Verbal representation units. Depth generally allows neural networks to discover and

represent more complex statistical relations amongst connected units(54). It also allows for more

complex temporal dynamics as mutual influences across distal network components take more

processing time. We assessed the importance of network depth in two ways.

First we compared the behavior of the hub layer in the deep network to that of a shallow network

employing just a single hidden layer containing 25 units reciprocally connected to Visual and

Verbal units and parameterized identically to the hub units in the deep model. We trained the

network for 30k epochs exactly as described for the deep network, using the same training and

testing patterns and procedures. This procedure yielded a dataset in which internal

representations were distributed and dynamic as in the deep model, but arose within a shallower

network.

Second, we compared the behavior of the hub layer in the deep network to the patterns emerging

across intermediate (visual hidden and verbal hidden) and shallow (visual representation and

verbal representation) layers in the same model. For this comparison, we recorded the activation

time-series produced in response to each visual stimulus, for every unit in the model. We then

assessed the propensity for units in each layer to behave like individual feature detectors,

unresponsive units, or units that appear to "switch" their category preference over time, taking

the "switch" behavior as a marker of distributed and dynamic representation.

Results.

In the first analysis, we subjected each alternative model to the same analyses reported for the

primary model and assessed whether they also show the four signature properties identified in

the main paper.

Constant decodeability. All four models showed cross-validation accuracy reliably above chance

and consistently high across the time-window once input signals reached the representation

units—thus all models showed constant decodeability.

Local temporal generalization. Figure SI-1A shows a 3D MDS of the trajectories for all items

through the corresponding representation space in each model. For feature-based, linear, and

shallow models, the trajectories are strictly or nearly linear—only the deep, distributed and

dynamic model shows the nonlinearities discussed in the main paper. Consequently the models

show qualitatively different patterns of generalization over time: feature-based, linear, and

shallow models show a pattern in which all classifiers generalize poorly to earlier timepoints and

well to later timepoints. Thus local temporal generalization—in which classifiers do well only for

neighboring time points in both past and future—is only observed in the deep, distributed and

dynamic model (SI-1B).

Widening generalization window. In contrast to the ECoG data and the deep, distributed and

dynamic model, the alternative models all show a narrowing window of temporal generalization:

models fitted early in processing show good performance over a wider window than those trained

later. This follows from the linear progression of internal representations observed in these

models: a classification plane that succeed for early representations must also succeed for later

representations. Conversely, because representations are very well-separated toward the end of

processing, classification planes that succeed later in time may not perform well for earlier

representations, producing an symmetric temporal generalization profile.

Figure SI-1. Comparison of simulation results for a feature-based model, a distributed linear model, a shallow recurrent network, and the deep, distributed and dynamic model. A. Multi-dimensional scaling showing the trajectory of each item through representation space under four different models. Only the deep model shows radically nonlinear change. B. Mean accuracy for clusters of classifiers under each model type. Only the deep model shows the overlapping-waves pattern. C. Proportion of time-window where classifiers in each cluster show reliably above-chance responding. Only the deep model shows a generalization window that widens over time.

Change in code direction. The deep, distributed and dynamic model acquired representations in

which some single units, when analyzed independently, behaved like feature-detectors that

change in direction over processing—with high activations initially predicting an animal stimulus,

for instance, then later predicting a non-animal stimulus. A similar flipping of signal direction was

also observed in the more anterior parts of the ventral temporal lobe, via the changing sign of the

classifier coefficients identified in the ECoG data. We therefore considered whether a change in

code direction was observed for single units considered independently in the alternative models.

Figure SI-2. For each model type, the proportion of units that behave like feature-detectors (red), detectors that switch their category preference over time (green), and units that seem unresponsive to the semantic category (blue). Only the deep, distributed, dynamic model has units whose responses switch their category preference over time.

Specifically, we classified each unit in each simulation as (1) a feature-detector if its activity

correlated significantly with conceptual domain in only one direction over the time-course of

processing, (2) as a switch feature if it correlated significantly in both the positive and the negative

direction at different points in time, and as (3) non-responsive if it never correlated significantly

with conceptual domain. Across all five simulations and all three classification tasks, we computed

the proportion of units falling into each category for each model type. The results are shown in

Figure SI-2. For feature-based and linear models, the results are trivial, since the representations

are constrained to show only non-responses or feature-like behaviors, as was indeed observed.

That such a result is observed in these cases validates the analysis. More interestingly, the shallow

interactive model also learned unit responses that behaved either as feature-detectors or were

non-responsive. Only the deep, distributed and dynamic model acquired units that appeared to

switch their category preference.

SI-2: Stable features posteriorly with dynamic features anteriorly

Our analysis of ECoG data showed more consistent feature-like responding in more posterior

ventral temporal regions, and more variability in code direction over time in vATL. We suggested

that this difference between posterior and anterior regions arises because the vATL is deeper in

the network and is connected cross-modally—that is, it resides in tertiary association cortex. In

the model, the visual and verbal hidden layers are shallower and not directly cross-modal—they

receive modality-specific inputs, and interact only with the hub layer. Thus our explanation of the

ECoG data has a direct model analog: if it is correct, more superficial layers should be more likely

to learn static, feature-like representations, while the hub should be more prone to acquire

distributed dynamic representations. We tested this hypothesis by computing the number of units

in each layer that behave as feature-detectors, switch-units, or unresponsive units, taking switch-

units to indicate a distributed and dynamic code.

Results are shown in Figure SI-3. Units in both shallow and intermediate model layers behaved

like consistent feature-detectors, or appeared unresponsive to the superordinate semantic

category. The switching pattern diagnostic of nonlinear representational change only emerged in

the deep hub layer. Note that the pattern cannot reflect overall distance in the network from the

input activation, since the verbal hidden and representation units are further away from the visual

inputs in the network than are the hub units but still show the same feature-like responding.

Instead the pattern must reflect the centrality of the hub units in computing interactive mappings

between visual and verbal representations.

Figure SI-3. For each layer in the deep, distributed and dynamic model, the proportion of units that behave like feature-detectors (red), detectors that switch their category preference over time (green), and units that seem unresponsive to the semantic category (blue) when the model processes visual inputs. Only the hub layer of the network—the model analog to the ventral anterior temporal cortex—contained units whose responses switch their category preference over time.

750   Together these simulations establish that all three properties—distributed representation,

751   dynamic processing, and network depth—conspire to yield the decoding signature observed in

752   the ECoG data: local temporal generalization, a widening window of generalization, and neural

753   populations whose code direction appears to change over time when considered independently.

 SI-3: Independent correlation analysis of individual electrodes.

Figure SI-4. Each panel shows, for each electrode in each participant, the correlation over time between the measured LFP for each item and the category label. Dotted lines show statistical significance thresholds for this correlations. Gray panels never exceed the threshold in either direction. Blue panels exceed it in one direction only. Red panels exceed it in both directions at different points in time.

756   The preceding simulations, together with those reported in the main paper, find model

757 units that, considered independently, seem to "flip" their category preference over time. A similar

758 phenomenon was observed in the anterior part of the ventral temporal lobe when visualizing

classifier weights plotted on the cortical surface: the direction and spatial organization of classifier

coefficients fluctuated over time. The coefficients show how the LFPs measured at a particular

location and timepoint contribute to the classifier's response when the responses of other regions

are also taken into account, and so are useful for visualizing a distributed neural code. Because

coefficients do not reflect the independent correlation of an electrode's activity with the category

label, however, the model and ECoG analyses are not strictly analogous. For an apples-to-apples

comparison, we conducted the same independent-correlation analysis of individual electrodes in

each participant. At every timepoint following stimulus onset, for each electrode across all stimuli,

we computed the correlation between the electrode's measured field potential and a binary

category label.

Figure SI-4 shows these correlations plotted over time. Dotted lines indicate the correlation

significance threshold of $p < 0.05$ for a two-tailed probability test on the correlation coefficient.

Gray panels show electrodes that never exceeded the threshold; blue panels show electrodes that

exceeded it in one direction only; red panels show electrodes that exceeded the threshold in

different directions at different points in time. Two observations are warranted. First, electrodes

in 5 of 8 patients show "switching" behavior analogous to that identified in the model, consistent

with a distributed and dynamic code. Second, independent correlations never exceeded the

significance threshold for one participant (patient 9)—but semantic category was nevertheless

decodeable in this patient for some time windows, indicating that information can be present in

a distributed code even when not discernable in individual channels.

SI-4: Decoding anterior electrodes only.

Figure SI-5. Accuracy for classifiers trained on anterior electrodes only. Curve shows expected probability of correct classification and 95% confidence intervals across participants at each window for classifiers trained only on vATL electrodes.

As noted in the main text, the interpretation of weights in a multivariate pattern classifier can be

problematic in the presence of correlated noise(45). When measurements from informative and

informative channels are corrupted with the same noise source, a classifier will place weights of

contrasting sign on both, with the weight on the uninformative channel serving to "cancel out"

the noise on the informative channel, boosting overall classifier performance. Thus an alternative

explanation of the ECoG results is that semantic information is encoded solely within the stable,

feature-like responses of mid/posterior regions of ventral temporal cortex, but correlated noise

across channels leads the classifier to place fluctuating non-zero weights on vATL areas. Under

this hypothesis, classifiers trained only on vATL electrodes should not show above-chance

classification. We therefore assessed whether semantic category (animate/inanimate) can be

decoded only from the more anterior electrodes.

We first computed a median split of electrodes based on their rostral/caudal location, discarding

the most posterior half of the electrodes (those more posterior than -17 in the anterior/posterior

dimension of MNI space). We then fit L1-regularized logistic classifiers to the anterior electrodes

only, using the same procedure described for the main analysis on a 100ms moving window,

computed every 50ms across the 1650ms post-stimulus response time. Classifiers were fit

separately at each window, for each participant, and were evaluated using 10-fold cross-

validation. From these data we computed, for each classifier, total number of items classified

correctly across the 10 holdouts. Across participants, we then computed expected probability of

correct classification and 95% confidence intervals (from the binomial distribution) on this

expectation at each window. The results are shown in Figure SI-5: from about 200ms post stimulus

onset, accuracy remained reliably above chance across most of the decoding window. Thus,

consistent with other arguments presented in the main paper, vATL regions encode semantic

structure even considered independent of the more posterior regions that adopt a more stable

and feature-like code.

SI-5: Autocorrelation analysis.

In both the simulation and ECoG data we observed that pattern classifiers generalize over a

temporal window that widens over time as a stimulus is processed. We suggested this widening

arises because the pattern of activation over hub units grows increasingly stable as the system

generates the correct activation pattern across the rest of the network. This section considers an

alternative explanation of the ECoG result: perhaps the ECoG data itself is temporally structured

so that it becomes self-predictive over a broader timescale as a stimulus processed. To test this

possibility, we measured the temporal autocorrelation of each electrode at lags of 1-100ms,

calculated over a 300ms sliding window, beginning with stimulus onset and moving the window

forward in 100ms increments. If temporal autocorrelation broadens over time, we would expect

significant correlation over a longer lag in windows selected from later in the time series.

Figure SI-5 shows, for each subject, the temporal autocorrelation across lagtime, averaged across

all electrodes, for 300ms beginning at stimulus onset and sliding forward to the end of the time-

series. Line colors indicate when in the time-series the 300ms window was selected. If electrode

signals grow self-predictive over a broader timespan with processing, cooler colors would show a

shallower slope and a later intersection with the 0 line on the y axis. Instead all lines are practically

on top of one another, and showing that temporal autocorrelation within a 300ms window drops

to 0 at a lag of about 60ms. Thus the "widening window" pattern observed in the ECoG temporal

generalization data does not arise from shifts in the temporal autocorrelation of the data itself,

and must reflect an increasingly stable distributed code.

References

1.   J. L. McClelland, T. T. Rogers, The parallel distributed processing approach to semantic

830   cognition. *Nature Reviews Neuroscience* **4** (2003).

831   2.   T. T. Rogers, J. L. McClelland, *Semantic Cognition: A Parallel Distributed Processing*

832   *Approach* (MIT Press, 2004).

3.   A. Martin, GRAPES—Grounding representations in action, perception, and emotion

systems: How object properties and categories are represented in the human brain.

Psychonomic Bulletin & Review **23**, 979–990 (2016).

4.   A. G. Huth, W. A. de Heer, T. L. Griffiths, F. E. Theunissen, J. L. Gallant, Natural speech

reveals the semantic maps that tile human cerebral cortex. *Nature* **532**, 453–458 (2016).

5.   K. Patterson, P. J. Nestor, T. T. Rogers, Where do you know what you know? The

representation of semantic knowledge in the human brain. *Nature Reviews Neuroscience*

8 (2007).

6.   M. A. L. Ralph, E. Jefferies, K. Patterson, T. T. Rogers, The neural and computational bases

of semantic cognition. *Nature Reviews Neuroscience* **18**, 42–55 (2017).

7.   T. T. Rogers, *et al.*, Structure and Deterioration of Semantic Memory: A

Neuropsychological and Computational Investigation. *Psychological Review* **111** (2004).

8.   L. Isik, E. M. Meyers, J. Z. Leibo, T. Poggio, The dynamics of invariant object recognition in

the human visual system. *Journal of Neurophysiology* **111**, 91–102 (2014).

9.   T. Serre, A. Oliva, T. Poggio, A feedforward architecture accounts for rapid categorization.

Proceedings of the National Academy of Sciences **104**, 6424–6429 (2007).

10.   R. M. Cichy, A. Khosla, D. Pantazis, A. Torralba, A. Oliva, Comparison of deep neural

networks to spatio-temporal cortical dynamics of human visual object recognition reveals

hierarchical correspondence. *Scientific Reports* **6**, 27755 (2016).

11.   N. Kriegeskorte, Deep Neural Networks: A New Framework for Modeling Biological

Vision and Brain Information Processing. *Annual Review of Vision Science* **1**, 417–446

(2015).

12.   L. Chen, M. A. Lambon Ralph, T. T. Rogers, A unified model of human semantic

knowledge and its disorders. *Nature Human Behaviour* **1**, 0039 (2017).

13.   T. T. Rogers, L. Watling, J. R. Hodges, K. Patterson, A basic-level disadvantage for

speeded category verification in *Cognitive Neuroscience Society*, (2005), p. 211.

14.   M. J. Farah, J. L. McClelland, A computational model of semantic memory

impairment: Modality-specificity and emergent category-specificity. *Journal of*

Experimental Psychology: General **120**, 339–357 (1991).

15.   G. Cree, K. McRae, C. McNorgan, An attractor model of lexical conceptual processing:

Simulating semantic   priming. *Cognitive Science* **23**, 371–414 (1999).

16.   M. W. Harm, M. Seidenberg, Computing the meanings of words in reading: cooperative

division of labor between visual and phonological processes. *Psychological Review* **111**,

662–720 (2004).

17.   D. C. Plaut, T. Shallice, Perseverative and Semantic Influences on Visual Object Naming

Errors in Optic Aphasia: A Connectionist Account. *JCN* **5**, 89–117 (1993).

18.   D. J. Kravitz, K. S. Saleem, C. I. Baker, L. G. Ungerleider, M. Mishkin, The ventral visual

pathway: an expanded neural framework for the processing of object quality. *Trends in*

Cognitive Sciences **17**, 26–49 (2013).

19.   E. Goddard, T. A. Carlson, N. Dermody, A. Woolgar, Representational dynamics of object

recognition: Feedforward and feedback information flows. *NeuroImage* **128**, 385–397

(2016).

20.   T. C. Kietzmann, *et al.*, Recurrence is required to capture the representational dynamics

of the human visual system. *Proceedings of the National Academy of Sciences* **116**,

21854–21863 (2019).

21.   F. Pulvermüller, How neurons make meaning: brain mechanisms for embodied and

abstract-symbolic semantics. *Trends in Cognitive Sciences* **17**, 458–470 (2013).

22.   C. R. Cox, M. S. Seidenberg, T. T. Rogers, Connecting functional brain imaging and Parallel

Distributed Processing. *Language, Cognition and Neuroscience* **30**, 380–394 (2015).

23.   V. Mante, D. Sussillo, K. v. Shenoy, W. T. Newsome, Context-dependent computation by

recurrent dynamics in prefrontal cortex. *Nature* **503**, 78–84 (2013).

24.   E. W. Contini, S. G. Wardle, T. A. Carlson, Decoding the time-course of object recognition

in the human brain: From visual features to categorical decisions. *Neuropsychologia* **105**,

165–176 (2017).

25.   T. Grootswagers, S. G. Wardle, T. A. Carlson, Decoding Dynamic Brain Patterns from

Evoked Responses: A Tutorial on Multivariate Pattern Analysis Applied to Time Series

Neuroimaging Data. *Journal of Cognitive Neuroscience* **29**, 677–697 (2017).

26.   A. Clarke, B. J. Devereux, B. Randall, L. K. Tyler, Predicting the Time Course of Individual

Objects with MEG. *Cerebral Cortex* **25**, 3602–3612 (2015).

27.   J.-R. King, S. Dehaene, Characterizing the dynamics of mental representations: the

893   temporal generalization method (2014) https:/doi.org/10.1016/j.tics.2014.01.002 (July 8,

894   2019).

895   28.   T. T. Rogers, *et al.*, The structure and deterioration of semantic memory: a

896   computational and neuropsychological investigation. *Psychological Review* **111**, 205–235

897   (2004).

898   29.   J. S. Snowden, P. J. Goulding, D. Neary, Semantic dementia: A form of circumscribed

899   temporal atrophy. *Behavioural Neurology* **2**, 167–182 (1989).

900   30.   J. R. Hodges, N. Graham, K. Patterson, Charting the progression in semantic dementia:

901   Implications for the organisation of semantic memory. *Memory* **3**, 463–495 (1995).

902   31.   M. A. Lambon Ralph, C. Lowe, T. T. Rogers, The neural basis of category-specific semantic

903   deficits for living things: Evidence from semantic dementia, HSVE and a neural network

904   model. *Brain* **130**, 1127–1137 (2007).

905   32.   J. Acosta-Cabronero, *et al.*, Atrophy, hypometabolism and white matter abnormalities in

906   semantic dementia tell a coherent story. *Brain* **134**, 2025–2035 (2011).

907   33.   M. Visser, E. Jefferies, M. A. Lambon Ralph, Semantic processing in the anterior temporal

908   lobes: A meta-analysis of the functional neuroimaging literature (2010) (July 31, 2013).

909   34.   T. T. Rogers, *et al.*, Anterior temporal cortex and semantic memory: Reconciling findings

910   from neuropsychology and functional imaging. *Cognitive, Affective and Behavioral*

911   *Neuroscience* **6** (2006).

912   35.   R. J. Binney, G. J. M. Parker, M. A. Lambon Ralph, Convergent Connectivity and Graded

913   Specialization in the Rostral Human Temporal Lobe as Revealed by Diffusion-Weighted

914   Imaging Probabilistic Tractography. *Journal of Cognitive Neuroscience* **24**, 1998–2014

915   (2012).

916   36.   R. J. Binney, K. v Embleton, E. Jefferies, G. J. M. Parker, M. A. L. Ralph, The ventral and

917   inferolateral aspects of the anterior temporal lobe are crucial in semantic memory:

918   evidence from a novel direct comparison of distortion-corrected fMRI, rTMS, and

919   semantic dementia. *Cerebral cortex (New York, N.Y. : 1991)* **20**, 2728–38 (2010).

920   37.   G. Pobric, E. Jefferies, M. A. Lambon Ralph, Category-specific versus category-general

921   semantic impairment induced by transcranial magnetic stimulation. *Current biology : CB*

922   **20**, 964–8 (2010).

923   38.   G. Pobric, E. Jefferies, M. A. Lambon Ralph, Anterior temporal lobes mediate semantic

924   representation: mimicking semantic dementia by using rTMS in normal participants.

925   *Proceedings of the National Academy of Sciences of the United States of America* **104**,

926   20137–41 (2007).

927   39.   R. Bruffaerts, *et al.*, Similarity of fMRI activity patterns in left perirhinal cortex reflects

928   semantic similarity between words. *The Journal of neuroscience : the official journal of*

929   *the Society for Neuroscience* **33**, 18597–607 (2013).

930   40.   B. J. Devereux, A. Clarke, A. Marouchos, L. K. Tyler, Representational similarity analysis

931   reveals commonalities and differences in the semantic processing of words and objects.

932   *The Journal of neuroscience : the official journal of the Society for Neuroscience* **33**,

933   18906–16 (2013).

41.   L. Sha, *et al.*, The Animacy Continuum in the Human Ventral Vision Pathway. *Journal of*

Cognitive Neuroscience **27**, 665–678 (2015).

42.   A. Martin, L. L. Chao, Semantic memory in the brain: Structure and processes. *Current*

Opinion in Neurobiology **11**, 194–201 (2001).

43.   S. Anzellotti, B. Z. Mahon, J. Schwarzbach, A. Caramazza, Differential activity for animals

and manipulable objects in the anterior temporal lobes. *Journal of cognitive neuroscience*

23, 2059–67 (2011).

44.   B. Z. Mahon, S. Anzellotti, J. Schwarzbach, M. Zampini, A. Caramazza, Category-specific

organization in the human brain does not require visual experience. *Neuron* **63**, 397–405

(2009).

45.   S. Haufe, *et al.*, On the interpretation of weight vectors of linear models in multivariate

neuroimaging. *NeuroImage* **87**, 96–110 (2014).

46.   Y. Chen, *et al.*, The 'when' and 'where' of semantic coding in the anterior temporal lobe:

Temporal representational similarity analysis of electrocorticogram data. *Cortex* **79**, 1–13

(2016).

47.   T. Carlson, D. A. Tovar, A. Alink, N. Kriegeskorte, Representational dynamics of object

vision: The first 1000 ms. *Journal of Vision* **13**, 1–1 (2013).

48.   R. M. Cichy, D. Pantazis, A. Oliva, Resolving human object recognition in space and time.

Nature Neuroscience **17**, 455–462 (2014).

49. A. C. Nobre, T. Allison, G. McCarthy, Word recognition in the human inferior temporal

lobe. *Nature* **372**, 260–263 (1994).

50. P. Gloor, *The Temporal Lobe and Limbic System* (Oxford University Press, 1997).

51. M. Mesulam, From sensation to cognition. *Brain* **121**, 1013–1052 (1998).

52. T. T. Rogers, *et al.*, The structure and deterioration of semantic memory: A

computational and neuropsychological investigation. *Psychological Review* **111**, 205–235

(2004).

53. L. Chen, M. A. Lambon Ralph, T. T. Rogers, A unified model of human semantic

knowledge and its disorders. *Nature Human Behaviour* **1** (2017).

54. R. K. Srivastava, K. Greff, J. Schmidhuber, Training Very Deep Networks. 2377–2385

(2015).