genBaRcode – a comprehensive R package for genetic barcode analysis

Lars Thielecke[1], Kerstin Cornils[2], Ingmar Glauche[1]

[1] *Institute for Medical Informatics and Biometry, Faculty of Medicine Carl Gustav Carus, Technische Universität Dresden, Dresden*

[2] *University Medical Center Hamburg-Eppendorf, Department of Pediatric Hematology and Oncology,*

Division of Pediatric Stem Cell Transplantation and Immunology and Research Institute,

Children's Cancer Center Hamburg, 20246 Hamburg, Germany

corresponding author: Lars Thielecke, lars.thielecke@tu-dresden.de

Abstract

Background: Genetic barcodes have been established as an efficient method to trace clonal progeny of uniquely labeled cells by introducing artificial genetic sequences into the corresponding genomes. The assessment of those sequences, commonly known as genetic or cellular barcodes, relies on next generation sequencing and the subsequent analysis aiming to identify sequences of interest and correctly quantifying their abundance. Although the statistics software R evolved into a standard tool for bioinformatical analyses, there is no comprehensive R-package available, providing the necessary functionality for the analysis of genetic barcodes and the respective visualization routines.

Results: We developed the *genBaRcode* package as a comprehensive toolbox spanning the range from the analysis of next generation sequencing data over error-correction approaches to a variety of suitable visualisations. The package allows the user to work with the same data structure across all implemented methods, therefore simplifying the usability and ensuring consistency throughout the entire package. We furthermore incorporated a graphical user interface, allowing less experienced R users the package-based analyses and also serving as an intuitive help for package novices.

Conclusions: The *genBaRcode* package provides access to genetic barcode analyses for a broad audience with different backgrounds in computational methods. It combines the flexibility of digesting next generation sequencing reads with or without a sophisticated barcode structure with a variety of analysis tools, the availability of several types of visualization routines and the advantages of a graphical user interface into a single overarching software package. We provide a tool that bridges the gap between generating and analysing barcode data and thereby support the establishment of standardized and reproducible analysis strategies.

Keywords

R-package, genetic barcodes, error correction, visualization, barcode analyses

Background

The ability to mark single cells and to follow their progeny is a key requirement for many biological

experiments. During the last decade, genetic barcodes were introduced as a new tool to genetically

label single cells and all their future descendants [1-4]. It quickly became the method of choice for the

majority of cellular labeling studies. Consequently, research groups developed their own barcode

constructs, including the selection of different viral vectors, different amplification protocols and also

specifically tailored software in order to analyze the resulting data [2, 3, 5-9]. Unfortunately, those

different analysis strategies harbor the risk of generating results that at the very least are difficult to

compare. Encountering similar problems while developing our own barcode constructs [10, 11] and

comparing our solutions to already published results, we decided to develop a comprehensive R-

package combining basic functionalities for data extraction and analysis with a collection of

visualizations wrapped in a set of simple albeit adjustable R-functions. By adding an ancillary *shiny-app*

we also provide a graphical user interface (GUI) to make the package accessible not only to experienced

R-programmers but also to investigators lacking the necessary programming skills.

Furthermore, we are convinced that such a "toolbox"-like software package will also contribute to

standardization efforts in the field of barcode analysis [12]. Therefore, we deliberately chose R as a

platform, as it is one of the most wide-spread tools for data analyses utilized by both bioinformaticians

and biologists. Furthermore, R is a freely available software that has already a large community

constantly developing and publishing a large variety of additional functionality (CRAN [13], Bioconductor

[14]). In the following we present the "*genBaRcode*"-package, currently at version 1.2.0, and describing

an exemplary work flow spreading from data extraction to data visualization.

Implementation and Results

The package is available at CRAN [15] and can be installed like every other CRAN R-package:

> install.packages("genBaRcode")

After the automatic installation process, it can simply be loaded and used:

> library("genBaRcode")

Data extraction and analysis

The first part of the package is dedicated to the initial data processing. It provides the function *processingRawData()*, which conveniently combines all necessary steps for the translation of raw next generation sequencing (NGS) data files into a sorted table of barcode (BC) sequences and its corresponding read counts.

> *BC_dat <- processingRawData (file_name = "test_data.fastq", source_dir = "./source/", results_dir = "./results/", mismatch = 1, label = "test", bc_backbone = getBackbone(1), min_score = 30, min_reads = 2, save_it = TRUE, seqLogo = TRUE, cpus = 4, bc_extraction = TRUE, dist_method = "hamming")*

Technically, the user has to supply one or multiple NGS data files (*file_name*) and the path to the corresponding directory (*source_dir*). Within the current version FASTA as well as FASTQ file formats will be accepted. Furthermore, the user can provide none, one or multiple BC design pattern(s), so-called BC-backbones (*bc_backbone*), which, if supplied, are then used as identifier for the actual BCs within the individual NGS reads. A BC-backbone needs to be encoded as a character string containing 'N's at the actual BC positions (also called wobble positions) and nucleotides (A, T, G, C) at the accompanying fixed positions. Those fixed positions are essential in order to identify individual BC sequences by matching them against the actual read. An exemplary backbone could look like this: *"ATCNNTAGNNTCCNNAAGNN"*. The matching procedure also allows to specify a number of acceptable sequence mismatches (*mismatch*). Moreover, if the parameter *bc_extraction* was set to *TRUE*, the identified sequences will be stripped from their fixed backbone positions and only the actual BC sequences (wobble positions) will be sustained. Otherwise only the flanking regions of the read will be stripped and the identified BC including the wobble positions will be returned. In case no BC backbone was chosen, all NGS reads will be treated as BCs and clustered based on the declared number of accepted dissimilarities (*mismatch*) and the elected distance measure (*dist_measure*).

Furthermore, there are additional possibilities to customize the analysis procedure. In case a FASTQ data file is available, the *min_score* parameter restricts the analysis to reads with a certain minimum sequence quality (calculated as the Phred-score average over the entire read length). Optionally, the quantified BC sequences can automatically be filtered for a minimum number of reads (*min_reads*) to

exclude contaminations or untrustworthy reads. A sequence logo of the entire NGS data file can be created (*seqLogo*) and a csv-file of all detected BCs including their corresponding read counts can be saved (*save_it*). Both will be stored within the specified results directory (*results_dir*) for all the subsequent analyses.

In case of only one specified BC-backbone, only one csv-file will be created while the function returns a specifically designed S4 data object (called *BCdat* data type) containing not only the detected BCs but also important parameters such as the used backbone pattern, a unique label used as name tag e.g. for all saved csv-files and the path to the results directory. If multiple backbones and/or NGS files are provided, also multiple csv-files will be created while the returned object will be a list containing several similar S4 data objects in the same order as the provided NGS files and backbones.

The user also can decide, if available, how many CPUs (*cpus*) should be utilized. The algorithm will then automatically start the analyses in a parallelized fashion, distributing not only the BC extraction but also the parallel analysis of multiple NGS data files onto multiple cores. Providing several BC-backbones at once will shorten the computational time compared to individual function calls with only one given backbone each. Admittedly, the algorithm sequentially searches for a given BC-backbone but since the read length typically only allows for just one BC construct per NGS read, it will automatically dismiss reads with an already identified BC and therefore significantly reduce the search space for the next BC-backbone(s). Furthermore, since the parallelization is based on the *future* R-package, it is also possible to choose a future-specific strategy in order to utilize the capacity of different resources in the best way possible.

The entire package is suitable for any kind of BC designs as long as they adhere to the aforementioned backbone structure. The BC extraction function is based on the "*Biostrings*"-package, meaning that the BC design pattern will not only allow for the wildcard letter 'N' but also for all letters which are part of the nucleic acid notation of the International Union of Pure and Applied Chemistry (IUPAC notation), making it highly customizable and capable of searching for almost every kind of BC design. Additionally, utilizing the *getBackbone()* function, the user can select from eight predefined and already published BC designs [10, 11].

After the BC identification, the newly created *BCdat* object(s) can then be subjected to the following function to initiate the error-correction (EC) of the detected BCs.

> BC_dat_EC <- errorCorrection(BC_dat, maxDist = 8, save_it = FALSE, cpus = 4, m = "hamming", type = "standard", EC_analysis = FALSE)

This default EC-procedure (*type = "standard"*) is an implementation of the method described in Thielecke et al. [10] that merges highly similar BC sequences in order to reduce erroneous/diverging BC sequences, which regularly occur as a result of polymerase chain reactions (PCR) during sample preparation and NGS. Sequence similarity calculations are based on a given distance measure *m* (we recommend using the *Hamming* distance) and are further defined by an adjustable similarity threshold *maxDist*. BCs with a distance $< maxDist$ will be clustered together, starting with the least frequent BC. In case there is more than one BC with the same distance, per default, only the two BCs with the lowest read count will be clustered together (the method is inspired by the idea that during PCR successive point mutations occur and, in a perfect world, one would find a chain of BCs successively increasing the number of diverging nucleotides while decreasing the number of read counts).

Although the *"standard"* method is recommended by us, the parameter *start_small*, if set to FALSE, offers the possibility to invert the procedure and therefore to always cluster the BC of interest starting with the most frequent one.

There is also the EC-type *"connectivity based"* available, which follows the *"standard"* procedure but instead of ordering the available BCs by read counts and starting the clustering with the least frequent one, it now will be ordered by the amount of highly similar analogues (depending on the *maxDist* value) and consequently the clustering will start with the BC possessing the lowest number of highly similar counterparts.

The *"graph based"* EC-type is based on the idea of graph-theoretic (connected) components. Firstly, for each and every BC the distances to all the other BCs will be calculated and all distances $> maxDist$ will then be set to zero. Secondly, the resulting matrix will serve as an adjacency matrix for which existing components can be identified. Finally, all of the "member-BCs" of those components will be clustered together, with the most abundant BC as the respective "cluster-label".

The EC-type called *"clustering"* just starts with the most frequent BC, identifies all highly similar counterparts (again based on the method *m* and the threshold *maxDist*), adds up all of the corresponding

reads and lastly all of those added up BC sequences will be dismissed. Then, the procedure continues

with the second most abundant BC until all BCs are processed.

Since the actual EC-algorithms are hardly parallelizable, parallel computations are only feasible if a list

of *BCdat*-objects is supplied. The *errorCorrection()* routine will automatically initiate a parallel execution

depending on the number of data objects and the *cpus* parameter. The resulting data object will again

be one or a list of *BCdat* objects. Optionally, the final list of corrected BC sequences can also be saved

as a common csv-file (*save_it*) in the specified directory (*results_dir*).

Figure 1. The quality of NGS data files can be visualized by plotting **(a)** the frequency of the mean quality scores

over all reads, **(b)** the mean and median quality scores per sequencing cycle and/or **(c)** the sequence logo of the

whole NGS file over the entire read length.

Data visualization

The second part of the package covers the data visualization. The implemented routines also include

illustrations to check the quality of the supplied NGS data. As such, it is possible to visualize the

frequency of mean quality scores over all reads (Fig. 1a) and an overview plot which displays the quality

score distribution per sequencing cycle (Fig. 1b). Additionally, the function *plotSeqLogo()* creates a

sequence logo either from all NGS reads (see *processingRawData()*), the entire barcode construct or

only the wobble positions. Such plots offer the possibility to visually check for prominent mismatch

positions within the backbone or general irregularities regarding the nucleotide distribution (Fig. 1c).

To examine the actual BC data, the plot function *generateKirchenplot()* depicts the sorted read counts

of all detected BCs (before or after error-correction) as a simple barplot (Fig. 2a).

> *generateKirchenplot (BC_dat, ori_BCs = NULL, ori_BCs2 = NULL, col2 = NULL, loga = TRUE,*

col_type = NULL, m = "hamming")

Figure 2. A simple barplot of sorted read counts of all detected BCs **(a)** will be generated by the function
generateKirchenplot(). If the user also provides a list of known reference BCs **(b)** there will be a color-coding of
each detected BC according to its sequence similarity value of the most similar reference BC. (**c**) If, at the same
time, two distinct subsets of known BCs are provided there will be three panels containing the respective BC
subsets.

If the user is interested in a subset of known BCs, a corresponding list of those reference BCs can be

provided (*ori_BCs*), thereby enabling a color-coding of each measured BC according to its minimal

sequence similarities to the entire subset of reference BCs (Fig. 2b). It is also possible to provide two

distinct subsets of known BCs (*ori_BCs, ori_BCs2*), e.g. BCs of the designed BC library and known

contaminations (Fig. 2c). To make a visual discrimination of those two subsets easier, the resulting plot

consists of three panels containing all BCs of the respective subset. By default, the function calculates

the *Hamming* distances (HD, number of nucleotide differences) between the reference set and all other

BCs and uses the minimum HD as color-coding basis. The information about sequence similarities

(before EC) can be used to either approximate the extend of generated sequence errors (assuming that

highly similar sequences are caused by one or few single nucleotide exchanges) or to visually check

the uniqueness/discriminability of the used BCs in terms of total sequence variations (after EC).

Figure 3. The sequence similarities can also be visualized in a network- or tree-like structure. Within a network-
based visualization, every BC sequence will be represented as a node and every edge indicates a minimal similarity
value between adjacent nodes (BC sequences). By default a minimal Hamming distance of 1 will be visualized but
it is also possible to always connect each node with its most similar neighbor, therefore assuring that each node
will be connected to at least one other node (allowing for a possible hamming distance of > 1).

The sequence similarities can also be conveniently visualized in a network-like structure. Figure 3 shows

one instance of a possible variety of different network plots utilizing different third-party R-packages

(*ggnetwork: ggplotDistanceGraph*, *igraph: plotDistanceIgraph, visNetwork: plotDistanceVisNetwork*).

This kind of visualization represents every BC sequence as a node and every edge indicates a minimal

similarity value between adjacent nodes or BC sequences (by default a minimal Hamming distance of

$m = 1$ will be visualized). It is also possible to connect each node with its most similar neighbor

(*complete*), assuring at least one edge per node and therefore allowing for Hamming distances > 1.

While these plots are 2D representations, utilization of the "*rgl*"-package allows for the creation of an

interactive 3D graph (encoded by the *threeD* parameter of the *plotDistanceIgraph*() function). As further

options, the user can also create a *gdf*-file (*createGDF()*), which was defined and is used by GUESS

(Graph Exploration System) but can also be imported into the open source graphic software *Gephi* [16]. Both programs are specialized in visualizing networks and allow for an even broader variety of design options.

Besides a network-based representation it is also possible to visualize sequence similarities as a tree-like structure utilizing the *plotClusterGgTree()* function. Within those tree plots the estimated sequence relationship is represented by the distance of each forked branch to the corresponding previous branch. Additionally, it is also possible to visualize the EC-procedure in order to develop an understanding of the amount and specificity of the corrected errors or/and to decide which EC-approach best suits the specific data set. In order to generate the needed data, the *errorCorrection()* function provides the parameter *EC_analysis* which, if set to TRUE, will document the entire EC-process (since a lot of additional data will be calculated and stored, it will slow down the execution time noticeable, therefore it is recommended to activate it only when needed). The returned *BCdat* object will then be composed not only of the usual BC list but will also include EC-specific cluster information (i.e. cluster sizes, added read counts, cluster specific BC lists) necessary for the aforementioned EC plots.

Depending on the EC method the composition of single clusters is not always foreseeable therefore the function *error_correction_clustered_HDs()* will create a scatter plot displaying the maximal distances within each of the barcode sequence clusters. Furthermore, the two functions *error_correction_circlePlot()* and *error_correction_treePlot()* will both create a specialized plot visualizing the size of the emerged barcode clusters including the abundance of the involved BCs. Both functions visualize the same kind of data but one in a circular and the other in a tree-like representation style.

The "*genBaRcode*"-package also offers the possibility to analyze and visualize time series data. As already mentioned, the *processingRawData()* function also accepts a list of NGS files which if $cpus >$ 1 will be analyzed in parallel and will result in a list of *BCdat* objects. In order to analyze repetitive measurements, *generateTimeSeriesData()* takes such a list of *BCdat* objects and calculates a matrix containing all unique BC sequences over all single *BCdat* objects as rows and their respective number of read counts over all time points (data objects) as columns. The *plotTimeSeries()* function utilizes such a matrix to depict the time dependent development of each and every BC detected at least once.

Furthermore, it is also possible to provide a vector containing the time information of each measurement

which will then be factored in the final plot to achieve the appropriate time scale.

Finally, the package also offers the option to visualize multiple measurements as Venn diagrams. The

function *plotVennDiagramm()* also accepts a list of *BCdat* objects from which the corresponding Venn

diagram will be generated. Almost all of the mentioned plotting functions return a *ggplot2* object which

can be plotted directly or customized further.

Figure 4. The included app allows for **(a)** a selection of one or multiple NGS or csv files for subsequent analyses
and to also specify further essential analysis parameters. After finishing the necessary calculations, **(b)** a list of
selectable plots and supplementing tabs containing meta-information will be available.

In addition to the described functionality of the R package, we developed an easy-to-use interface mainly

for investigators with little or no programming experience. Therefore, the third and final piece of the

package consists of a *shiny app* making the majority of the aforementioned functions available within a

graphical user interface (GUI). The GUI enables the unexperienced user to perform the majority of the

available analyses essentially without typing any line of R-code. The app not only allows for the BC

extraction from raw NGS data files, the error-correction and the storage of those BC sequences within

external csv-files but also for a visual inspection of the corresponding results directly within the app and

to further manipulate and save the generated figures. Furthermore, for the more skilled user the app

doubles as a convenient possibility to familiarize oneself with the package's functionality and its intended

usage. It can easily be started utilizing the *genBaRcode_app()* function, immediately prompting the user

to specify a path to the NGS files of interest. If no specific path is provided, the included template will

be made available for example analyses.

Within the app, the user can specify one or multiple NGS files for a quantitative analyze and adjust

further essential parameters (Fig. 4a). It is also possible to just read one or multiple existing csv-file(s)

containing already extracted and counted BC sequences in order to generate new plots or to reanalyze

certain data sets. If multiple files have been chosen, the app automatically initiates a time series

analysis. BC extraction and error-correction will be performed according to the user specifications. After

finishing the necessary calculations, a list of selectable plots and supplementing tabs containing meta-

information as well as lists of the detected barcodes in combination with their respective read-counts

before and after error-correction will become available (Fig. 4b).

Selecting a particular plot style prompts the app to display the corresponding figure utilizing the *shiny*

specific output und render function of the "*plotly*"-package, allowing not only an inspection but also an

interaction with the produced figures via clicking, hovering and/or dragging. The user can freely zoom

in and out, scroll through the image and extract additional information by hovering over certain elements

of interest, thereby providing the functionality to intuitively explore the results and customize the

respective visualizations.

In order to augment the support for less experienced users, an additional tab provides all the

corresponding R-code, necessary to reproduce the presented results and figures within the command-

line interpreter and without the assistance of the shown GUI. Furthermore, there is a detailed help-page

available, designed to guide the user step-by-step through the app and also to make the basic R help

accessible in order to further familiarize the user with the underlying R-functions.

Conclusions

The establishment of genetic barcoding and the availability of NGS boosted clonal studies in many areas

of biology. This ultimately leads to an increasing demand for the analysis of the resulting BC data and

calls for standardization efforts including BC calling, quantification, error-correction and visualization.

Our R-package comprises currently available analysis routines and combines them with a user-friendly

GUI. It is compatible with a variety of different BC constructs, published or newly developed, and it

provides the necessary means to quantitatively analysis and visualize the resulting data obtained by NGS.

Furthermore, the GUI makes the analysis software accessible for investigators with only basic or no R-knowledge. Thereby our package bridges the gap between data generation and analysis, and supports interactions between investigators and data scientists, not only with respect to experiment-specific analysis pipelines, but also concerning the establishment of a consensual, standardized data processing and analysis strategy.

Availability and requirements

Project Name: genBaRcode

Project Home Page: The R-package is freely available at the Comprehensive R Archive Network (https://cran.r-project.org/web/packages/genBaRcode/index.html)

Operating system(s): Platform independent

Programming language: R (>= 3.4.0)

License: LGPL

Consent for publication

All authors read and approved the final manuscript.

Availability of data and materials

The R-package contains an exemplary data set.

Funding

This work was supported by the Deutsche Forschungsgemeinschaft (DFG) [CO 1692/1-1 to KC and GL 721/1-1 to IG] and the German Federal Ministry of Research and Education (BMBF) [grant number 031A315 "MessAge" to IG].

Acknowledgements

The authors would like to thank Andreas Dahl and Sebastian Gerdes for fruitful discussions concerning methods development and Ingo Roeder for providing the necessary infrastructure to perform this work. The authors also thank Sebastian Wagner and Christoph Baldow for testing the software and suggesting improvements.

References

1.   Bystrykh LV, de Haan G, Verovskaya E: **Barcoded vector libraries and retroviral or lentiviral barcoding of hematopoietic stem cells**. *Methods Mol Biol* 2014, **1185**:345-360.

2.   Nguyen LV, Makarem M, Carles A, Moksa M, Kannan N, Pandoh P, Eirew P, Osako T, Kardel M, Cheung AM *et al*: **Clonal analysis via barcoding reveals diverse growth and differentiation of transplanted mouse and human mammary stem cells**. *Cell Stem Cell* 2014, **14**(2):253-263.

3.   Gerrits A. DB, Kalmykowa O. J., Klauke K., Verovskaya E., Broekhuis M. J. C., de Haan G., and Bystrykh L. V.: **Cellular barcoding tool for clonal analysis in the hematopoietic system**. *Blood* 2010, **115**(13):2610-2618.

4.   Perie L, Hodgkin PD, Naik SH, Schumacher TN, de Boer RJ, Duffy KR: **Determining lineage pathways from cellular barcoding experiments**. *Cell Rep* 2014, **6**(4):617-624.

5.   Peikon ID, Gizatullina DI, Zador AM: **In vivo generation of DNA sequence diversity for cellular barcoding**. *Nucleic Acids Res* 2014, **42**(16):e127.

6.   Lu R, Neff NF, Quake SR, Weissman IL: **Tracking single hematopoietic stem cells in vivo using high-throughput sequencing in conjunction with viral genetic barcoding**. *Nat Biotechnol* 2011, **29**(10):928-933.

7.   Nguyen LV, Pellacani D, Lefort S, Kannan N, Osako T, Makarem M, Cox CL, Kennedy W, Beer P, Carles A *et al*: **Barcoding reveals complex clonal dynamics of de novo transformed human mammary cells**. *Nature* 2015, **528**(7581):267-271.

8.   Cheung AM, Nguyen LV, Carles A, Beer P, Miller PH, Knapp DJ, Dhillon K, Hirst M, Eaves CJ: **Analysis of the clonal growth and differentiation dynamics of primitive barcoded human cord blood cells in NSG mice**. *Blood* 2013, **122**(18):3129-3137.

9.   Wu C, Li B, Lu R, Koelle SJ, Yang Y, Jares A, Krouse AE, Metzger M, Liang F, Lore K *et al*: **Clonal tracking of rhesus macaque hematopoiesis highlights a distinct lineage origin for natural killer cells**. *Cell Stem Cell* 2014, **14**(4):486-499.

10.   Thielecke L, Aranyossy T, Dahl A, Tiwari R, Roeder I, Geiger H, Fehse B, Glauche I, Cornils K: **Limitations and challenges of genetic barcode quantification**. *Sci Rep* 2017, **7**:43249.

11.   Cornils K, Thielecke L, Huser S, Forgber M, Thomaschewski M, Kleist N, Hussein K, Riecken K, Volz T, Gerdes S *et al*: **Multiplexing clonality: combining RGB marking and genetic barcoding**. *Nucleic Acids Res* 2014, **42**(7):e56.

12. Lyne AM, Kent DG, Laurenti E, Cornils K, Glauche I, Perie L: **A track of the clones: new developments in cellular barcoding**. *Exp Hematol* 2018, **68**:15-20.

13. **The Comprehensive R Archive Network. https://cran.r-project.org. Accessed 08 Nov 2017**

14. **Bioconductor - Open Source Software for Bioinformatics. http://bioconductor.org. Accessed 08 Nov 2017**

15. **genBaRcode R-package. https://cran.r-project.org/web/packages/genBaRcode/index.html. Accessed 14 Aug 2018**

16. Bastian M, Heymann S, Jacomy M: **Gephi: An Open Source Software for Exploring and Manipulating Networks**; 2009.