1

The development of methodology and techniques for crop disease identification

N. S. Tiwari[1], J. W. Richmond[2]

[1]Boston University and Tata Group Technology and Innovation Office. Current: View, Inc

[2]Tata Group Technology and Innovation Office

* **Author for correspondence:** N. S. Tiwari, E-mail: nidhit@bu.edu

The development of methodology and techniques for crop disease identification

Abstract

In India, an estimated 15-25% of potential crop production is lost due pest and diseases (Roy

and Bezbaruah, 2002). The country needs not only to raise production but also ensure food

security for its growing consumption needs while curbing excessive pesticide usage. Detection

of pests and diseases at an early stage plays a significant role in addressing the above-

mentioned concerns and image classification offers a cost-effective and scalable solution to the

disease detection problem (A. Ramcharan *et al.* 2017). Here, the principles of transfer learning

are implemented with pretrained model – Resnet34 (K. He *et al.* 2015), and test its

effectiveness in image classification using a dataset of tea leaves. The novelty of this work is

that the images used are not curated, individual leaves with controlled backgrounds but of

plants in-situ. The effect of the level of zoom and background is examined and class activation

maps are used to validate that the basis of classification is indeed the disease and not an

artificial bias from factors such as background, lighting etc.

Introduction

Protecting crop yields from the devastation caused by pest and disease infestations is a very

important concern for the food security of humans. With farmland coming under increased

pressure, it is becoming vital to detect the onset of diseases and pests at an early stage to reduce

the economic loss caused due to the reduction in crop yields. Tackling pests and diseases at an

early stage also helps in reducing the amount of pesticides used to bypass all the detrimental

effects that overuse of pesticides has for the plant, the soil and future crop yields.

The intention of this work is to develop an analysis procedure to enable farmers to

accurately identify different pests and diseases using images taken from smartphone cameras.

It was anticipated that this could be done using deep neural networks to carry out classification

based on images of crop pest/disease symptoms. In this scenario the neural network would be

trained using a dataset of images collected from actual incidents of the diseases (Alfarisy et al.

2018; Kamilaris and Prenafeta-Boldú 2018). Once the model had been trained, it could then

be deployed either centrally on a cloud server or locally via an app on a smartphone (if

sufficient processing power is available). This paper summarises the work carried out to date

and shows that neural networks can indeed provide a very powerful and accurate means of

identifying crop disease based on symptoms.

Over recent years deep learning using various architectures has been shown to provide

state of the art image classification and object recognition capability (Zhao et al. 2018). Much

of this development has been carried out using datasets such as Imagenet (Krizhevsky *et al.*

2012), CocoNet (Lin *et al.* 2014), etc. These datasets, whilst being trained on vast numbers of

images and object classes are of limited relevance to many real-world problems since the

domain of the classes do not pertain to the specific application. Unfortunately, given the

complexity and very large number of parameters of modern image classifiers such as Resnet

(Kaiming He *et al.* 2015), DenseNet (G. Huang *et al.* 2016), ResNeXt (S. Xie *et al.* 2017), etc,

it is necessary to have hundreds of thousands, even millions of labelled images to train the

models. Such large numbers of images are rarely available in real world applications. This

issue is overcome by using a process called transfer learning to re-train a neural network that

has been trained on one of these large datasets and make it specific and applicable to a new

problem domain (S. Ruder, online).

There is a significant body of work where Artificial Neural Networks, Support Vector

Machines (SVM) and fuzzy logic have been applied to the domain of crop disease detection

using an image dataset by a number of authors (Kaur and Singla 2016; Abdullahi *et al*. 2017).

Mohanty et al. used the Plant Village dataset, a public domain image dataset consolidated in a

controlled setting, to train deep convolutional neural networks and the performance different

network architectures were compared in different experiments based on their F1 scores

(Mohanty *et al*. 2016). CaffeNet has been used as a starting point to develop an image

classification model on a specially curated dataset of leaves spanning 13 classes (Sladojevic *et*

al. 2016; Alfarisy *et al*. 2018). Transfer Learning has also been applied to the purpose of image

classification in the crop disease detection domain using field level images of cassava plants.

The techniques as applied in the works mentioned above, coupled with remote sensing, IoT,

cloud computing and big data analysis can go a long way to address a variety of challenges

facing precision agriculture (Kamilaris and Prenafeta-Boldú 2018).

Whilst deep learning has been shown to be a very powerful tool there are known problems

that mean that good results can be generated on specific datasets, however, these sometimes

do not generalise well and give poor results in production. There are many reasons for this

behaviour, the most important of which is the lack of exposure during training of the model to

scenarios that the application will encounter in the field. The imbalance in the number of

images belonging to different classes in the training dataset, nature of images including

attributes like colour, zoom level, angle of image capture, texture among others also introduces

bias in the model. The nature of the dataset can also result in overfitting in the model which

will be explored in detail when reviewing results of the analyses.

The focus of this paper is to explain the development and validation of a methodology for

data capture and processing to avoid the above problems and the initial application of deep

learning models for this specific application. The work presented provides a strong foundation

for future development of robust and scalable crop disease diagnostic tools.

Since the ultimate intention of this work is to help farmers accurately identify different

pests and diseases using images taken from smartphone cameras, the images in the training

dataset have been taken in-situ. This is a very different approach than those adopted in previous

works such as Mohanty (Mohanty *et al.* 2016), and implies that each image is likely to have a

complex set of attributes, background noise, contain multiple leaves and/or plants and more

than one type of pest or disease. It is also likely that the farmers will take images under varied

lighting conditions, zoom levels and from different angles. Hence, the initial focus was to

examine what sort of images would be effective in training the model to make predictions with

high accuracy levels. The results demonstrated in this work will be used to establish a baseline

for the methodology of dataset collection and its importance in the development of a robust

automated disease recognition system.

The experimentation elaborated in this paper was done on the leaves of different sections and

growing conditions in a tea plantation. This was done with the support of Amalgamated

Plantations Private Limited (APPL is an associate company of Tata Global Beverages) and Mr.

Kailyanjeet Borah, R&D manager who provided essential assistance during the data collection

exercise, which was carried out in Teok Tea Estate in the Jorhat city of the state of Assam,

India.

Materials and Methods

Targeting the different kinds of pest & disease symptoms in a single plant type, the Tea Crop

facilitated consistency in the physical attributes and features of the leaves and provided

uniformity in model testing. The pests/ diseases of interest were:

(i)   Tea Mosquito Bug

(ii) Red Rust

(iii) Grey Blight

The fourth category of classification was healthy tea leaves. The images were taken with

a high-resolution smartphone camera and therefore, there were plenty of pixels of work with

when reducing the resolution of images during model training (most deep learning models crop

/ scale images down to less that 300 by 300 pixels). A set of pre-decided guidelines were

followed during the process of image collection:

1) As the first rule, the images taken for training purposes should be similar to those the

farmers are likely to use for monitoring purposes.

2) Images were taken from varied zoom levels to ensure visibility of multiple individual

leaves/ stems. Zoomed in images of single leaves that are affected by the pest/ disease

infestation were taken.

3) The images of the tea leaves were taken in their natural arrangement rather than against a

controlled background. The reason for leaving them in situ is so that the model can learn to

identify the pests/disease with high accuracy when used in the field itself rather than being used

necessarily in a controlled environment.

4) The images were free of any artifacts/ distortions like timestamps, etc. This is so that so

that the model does not learn any unintended features.

5) The following metadata was to be recorded for each class of images so that after initial

testing, the model can build on this information:

● Geographic Location (latitude/longitude or descriptive)
● Type of Crop
● Maturity of crop
● Type of pest or disease
● Description of stage of development of the infestation
● Zoom category
● Time of day
● Ambient weather (overcast, sunny, etc)

The images were internally classified according to the stages of infestation. However, for initial model training and testing, only the classification at the pest/disease level were focussed upon. The resulting image dataset consisted of approximately 500 images for each class taken at varying zoom levels, angles and sunlight intensity.

Examples of images at zoom levels 2 and 4 are shown in Figures 1 and 2 respectively.

For implementing the planned framework, a library called FastAi was used which is built on top of the deep learning package PyTorch. **PyTorch**, in common with other deep learning frameworks such as TensorFlow, provides what is called a model zoo. This is a set of models that have been developed for specific purpose and trained on large datasets so that they can be used with very little work provided that the task at hand is similar to that for which they have been developed. In the case of image recognition and classification there has been tremendous advances over the last six years since AlexNet (Krizhevsky *et al.* 2012). developed the first deep learning neural network to outperform traditional computer vision techniques. Such models are often trained upon a large corpus of over a million images, consisting of 1000 categories or more, called Imagenet (Russakovsky *et al.* 2015). With the weights learned from this training these models are then available in the model zoo and can be used to classify any image into one of the categories used in the training.

Transfer Learning

Domain adaptation is a common requirement since often the data where labelled information is easily accessible and the data encountered in the application domain are different (Ruder, online). The model needs to be able to disentangle the general features and use that as an initialization to learn the domain specific features. Deep Learning models learn objects by learning features, and the different layers of the model recognise different types of features.

Layers near the input learn low level features such as edges, gradients etc. Layers deeper in the

model recognise how such low-level features come together to create objects which are specific

to the images. What has been discovered over recent years is that these feature extraction layers

can relatively easily be re-trained to recognise objects different from those they were originally

trained upon, and the re-training needs far fewer images than the original training - typically in

the order of hundreds rather than millions originally used. (Tan *et al*. 2018).

The process of taking a model that is pre-trained and adapting it in other domains is called

transfer learning. The FastAi framework allows the user to very quickly and easily apply best

practices in transfer learning. That is the basis of the work carried out here where a pretrained

model is re-trained to classify the images in the dataset that contains the different types of pest/

disease symptoms in tea leaves. The pre-trained model used in this work was Resnet 34. There

are many versions of Resnet and indeed many other alternatives such as ResNext, Inception,

SqueezeNet, Densenet, MobileNet etc. Resnet was chosen since it provides a good balance

between computational requirements in terms of memory, processing power and accuracy. The

approach followed here could be repeated with any of the other models and would achieve still

greater accuracy with some of the more complex models, however, the aim here was to

establish the methodology first and Resnet34 provides a good platform to accomplish that.

Resnet34: Architecture Overview

The winners of the ILSVRC 2015 image classification challenge introduced a new concept

called a deep residual learning framework that made it possible to train hundreds of layers and

still achieve compelling performance without worries of performance saturation (Bengio *et al*.

1994). Residual networks allow the training of deep networks by adding layers and adjusting

the parameter values such that the additional layer does not change the output of the layer from

which it receives input. This is known as identity mapping (Kaiming He *et al.* 2015; A.

Ramcharan *et al.* 2017).

The training error of the overall module (with the additional identity layers) is the same

as the error would be without the additional layers. Therefore, the additional identity mapping

layer is used only for feature learning on top of the already available input. Since the

additional layer is learning only the residual, the whole module is called a residual module.

Resnet34, as used in implementation outlined in this paper, is a 34-layer deep residual

learning framework and is illustrated in Figure 3.

The architecture of a Convolutional Neural Network consists of 4 main operations which are

the basic building blocks of every CNN (Goodfellow *et al.* 2016). These are:

1. **Convolution**: The primary purpose of convolution is to extract features from an input
   image. The convolution operation occurs between a filter (usually 3x3) and the pixels
   of the input image and an activation or feature map is produced. Different filter values
   extract different features (edges, gradients, etc) from the image.

2. **Non-Linearity (ReLU)**: Element wise operation that replaces all negative pixel values
   in the feature map by zero.

3. **Max Pooling**: A spatial neighbourhood (for example a 2 x 2 window) is defined and
   the largest element from the rectified feature map, within that window, is retained. This
   reduces the dimensionality of each feature map. Note that in many modern architectures
   the Max Pooling layer is being replaced at some or all locations by Global Average
   Pooling layer that effectively, instead of taking the maximum value in each area instead
   takes the average value.

4. **Fully Connected Layer**: The output of the convolutional and pooling layers are high
   level features of the input image. Fully connected layers at the end of the model use

these features for classifying the input image into various classes based on the training

dataset. The output layer uses a special layer based on a Softmax function so the sum

of the output probabilities is unity.

The above CNN architecture is common to all models like Alexnet, Resnet, VGG etc

(Krizhevsky *et al.* 2012; Kaiming He *et al.* 2015; Simonyan and Zisserman, 2014). The FastAi

library groups the layers in the pre-trained model into 3 groups. Two groups are the

convolutional layers (divided into two) and the third group is the fully connected layers part

(J. Howard and R. Thomas, online).

Convolutional Layers Feature Learning

The higher convolutional layers in the Resnet34 model capture generic features like edges,

gradients, colour blobs while the deeper convolutional layers capture features that are more

complex and specific to the dataset. The final fully connected layers capture information that

is relevant for solving the specific classification task. Therefore, the approach while fine-tuning

the weights in the pre-trained model would be to make significant changes in the weights of

the deeper convolutional layers but smaller changes in the higher layers.

Cost Function: The cost function is a wrapper around the model that guides the

calculation of changes in model parameters during model training. In this case the FastAI

model automatically used the PyTorch Negative Log Likelihood (NLL Loss) function. This is

commonly used for classification problems where there are more than two classes.

Gradient Descent: An optimization algorithm is used to minimize the loss function by

iteratively moving in the direction of steepest descent as defined by the negative of the gradient.

In the implementation outlined in this paper, gradient descent is used to update the parameters

of the model to fit the tea dataset. Parameters refer to weights and bias values of each layer in

neural networks. The goal is to adjust the parameters is such a way that the cost function is

minimised. The way to do this is through calculation of the sensitivity (called the gradient) of

each parameter upon the loss (effectively a measure of the error in the predictions). Given these

gradients each parameter is adjusted to effect a reduction in the loss. The model is then run

again and the process is repeated until a local minimum is reached and/ or the accuracy attained

is adequate.

Learning Rate: The size of the adjustments made to the parameters in each step is called

the learning rate. With a high learning rate, more ground can be covered each step, but there is

a risk of overshooting the lowest point and the system becoming unstable. With a low learning

rate, the cost function moves in the direction of negative gradient in a precise manner, however

this approach is time consuming and it takes long to approach the local minimum (Krizhevsky

et al. 2012; Bottou, 2012).

Batch Size and Epochs: The training set is divided into small subsets called mini-batches

to update the parameters. However, to prevent any loss in accuracy and generality of the model,

the model is trained on the whole dataset, divided into mini-batches, for several epochs. The

batch size should be fixed in proportion to the image dataset i.e. small datasets should be

assigned a smaller batch size (B. Kunwar, online).

Re-training the Pre-trained model:

Initial Run without unfreezing layers

An initial run is done to check how well the pre-trained model can be generalized to the

collected dataset and test how effective the dataset is for this purpose. It also helps in getting

a rough estimate of the maximum accuracy that can be achieved with the dataset. The

procedure is:

Step 1: Partition the dataset into train and validation sets.

Step 2: Centre crop of the image after scaling down to 300 pixels minimum for any side

Step 3: Use the FastAi library transformation features to apply random lighting, rotation and

flip transforms and zoom levels. This augmentation of the dataset has a significant bearing on

improving the accuracy of the model and also helps to reduce overfitting.

Step 4: The largest learning rate that can results in the fastest reduction of loss from a plot of

loss vs. learning rate is selected (Bengio, 2012). In this implementation a value of 0.01 was

chosen.

Learning Rate Adjustment:

As mentioned above, training with low learning rate is more reliable, but optimisation takes

time because the steps taken towards the minimum of the loss function are small. Training with

high learning rate may not converge as the weight changes are so large that it overshoots the

optimiser overshoots the minimum and makes the loss worse. To overcome these issues, two

features incorporated in the FastAi library are used:

1 - Learning Rate Annealing: As the model get closer to the local minimum, the learning rate

should be reduced. This allows taking of larger steps in the early runs, thereby saving

computing resources, and allows more accurate solutions as a minimum is approached. The

approach used is to assign a functional form to the learning rate. In FastAi's implementation,

the cosine form is used to maintain the learning rate high in the starting gradients and then drop

quickly towards the minimum (Bengio, 2012). The learning rate is changed for every mini-

batch, i.e. for every epoch.

2 - Stochastic Gradient Descent with Restarts (SGDR): In some weight spaces, small

changes in weights result is large changes in loss. The goal is to enable the model to find a

weight space which is stable and accurate. This is done by a periodically imposing a large

increase in the learning rate ('restarts') which will force the model to jump into a different part

of the weight space if the current area is not resilient (G. Huang *et al.* 2017). The number of

restarts is referred to as the number of cycles. The number of epochs between resetting the

learning rate is set by the parameter cycle_len.

Initial run Results and Insights

Using the learning rate finder provided by the FastAi library, the learning rate was fixed at 0.01

to carry out the initial run of the model according to the procedure above. The pre-trained

model was run for 4 epochs. The accuracy at the end of the 4th epoch was 89%. It was observed

that this result was obtained without retraining any of the pre-trained features or any of the

weights in the convolutional kernels, the only training was related to the final fully connected

layers that feed into the classification output. This result was very encouraging as it implied

that after retraining the convolutional weights of the pre-trained model with the tea dataset,

significantly high levels of accuracy would be achieved.

Unfreezing and Retraining

Differential Learning Rate

Most pre-trained model architectures have many layers and specifying a learning rate for every

single layer may be complicated for future fine-tuning purposes. FastAi provides the concept

of 'layer-groups', which are layers in the same general part of the network are grouped together.

The fully connected layers are one group and the convolutional layers are divided into two

groups. The learning rates for each group is passed into the model as an array of three learning

rates, one for each group (Howard, online).

The next step was to unfreeze all of the remaining layers of the model so that they could

be retrained once an initial training of the new fully connected layers had been carried out.

Before the unfrozen layers are trained, the appropriate learning rates have to be defined. As

mentioned above, the earlier convolutional layers in the Resnet34 model capture generic

features like edges, gradients, colour blobs while the upper convolutional layers capture

features that are more complex and specific to the dataset. For the lower layers, the learning

rate can be kept low, for the upper layers, the learning rate needs to be higher. The pre-trained

model was retrained with the following learning rates: [lr/9, lr/3, lr] where lr or learning rate =

0.01. The model was run 14 epochs and an accuracy of 96% was obtained.

Fine tuning attempt 1: During image collection, it was observed that the disease Red

Rust co-occurred with Grey Blight in many locations and some of the images. Examining the

results of the analysis showed that a lot of red rust was getting misclassified as grey blight. To

overcome this issue, the dataset was re-examined and images which contained both red rust

and grey blight were cropped to leave either one or the other. After running the model on the

edited dataset, the accuracy was found to have increased up to 97% and there were fewer

incidences of misclassification due to confusion between red rust and grey blight.

Fine tuning attempt 2: Next, the above steps were repeated, but changing the learning

rate for the layer groups to [5e-4, 5e-3, 0.02]. This process resulted in an increase of accuracy

to $\approx$ 98.4%. The confusion matrix in Figure 3 shows a significant number of healthy labelled

images being misclassified as grey blight and thus worthy of further analysis by implementing

multi-label classification. Figure 4 shows examples of correctly classified images.

(a) (b) (c)

Fig. 1. Examples of images at zoom level 2 showing (a) grey blight, (b) red rust, (c) tea mosquito bug

(a) (b) (c) (d)

Fig. 2. Examples of images at zoom level 4 showing (a) grey blight, (b) healthy, (c) red rust, (d) tea mosquito bug

Fig. 3. Confusion matrix for analysis

(a)

(b)

(c)

(d)

Fig. 4. Examples of correctly classified images showing (a) grey blight, (b) healthy, (c) red rust, (d) tea mosquito bug

[0.03927 0.00084 0.95905 0.00085]

[0.00886 0.46421 0.00026 0.52666]

(a)

(b)

[0.1457 0.36715 0.48368 0.00347]

(c)

Fig. 5. Examples of incorrectly classified images showing (a) grey blight, (b) healthy and (c) red rust and grey blight

2.7 Incorrectly classified images

Figures 5 shows examples of incorrectly classified images. In Figure 5a this is actually grey

blight, but it has been classified as red rust. One of the features of this image is that there is a

lot of soil in the background.

After by looking at all of the misclassified images it was observed that that uncertainty or

misclassification usually occurs in zoomed out images or in the ones where soil occupies a

significant proportion of the image. It was also observed that zoomed in images also lead to

correct classification with high accuracy (Noord and Postma, 2017). One reason for this is that

the relatively low resolution of 300x300 pixels used in the classifier means that the fine detail

of the disease is not clear in zoomed out images.

Another aspect of the dataset that was noticed while analysing the results from the above

experiment was the images taken in the field contained leaves or set of leaves from different

parts of the same plant and also the same set of leaves at multiple angles and zoom levels. This

resulted in images containing leaves or set of leaves from the same plant in both training and

validation sets due to the data splitting using a random process. This observation raised the

possibility that the training process might be biased due to the presence of images of leaves

from the same plant or plant group in both the training and validation sets. A well generalised

model should have high prediction capabilities on the training set but also be able to generalise

well over previously unseen data and this target is compromised by the effective leakage of the

training data into the validation set (Reitermanov´a, 2010). A methodology was therefore

developed to avoid this data leakage as outlined further.

From the above observations, it was hypothesised that in order to optimise the results there

was a need to create a new dataset where the use of images that are zoomed out too far is

avoided and to create a methodology for splitting out training and validation sets without the

above-mentioned leakage.

The approach to overcoming these issues was:

1. As described above, the collected dataset consisted of multiple images of leaves that

belonged to different parts of the same plant or group of plants at different angles and

zoom levels. Therefore, the first logical step was to label the images according to the

plant group to which they belong. This was done by assigning numeric codes to

different plant groups (1, 2, 3, …, etc). The images belonging to the plant groups were

assigned the respective plant group code. This ensured that when the dataset was split

into train and validation, all the images from any group were in either the train or

validation sets but not both.

2. Zoom levels were demarcated for each of the images again by assigning number codes for each level to maintain consistency. Images that are zoomed out have a lower numeric code, more zoomed in images have higher numeric codes. The next step involves modification of images which are zoomed out beyond a particular level and this helps in identifying the images that require modification.

3. Images with unrelated ambient content, e.g. soil occupying more than a reasonable proportion of the image, trees or fences in the background, etc required modification to remove the information that had the potential to influence the training process. In the images that were zoomed out to the point that more than one disease category was visible in the image, the image was cropped into two or more images so that only one disease or healthy category was visible in the image. The images produced by taking multiple crops of the original images were placed in the same plant group as the original image.

4. Finally, a master csv file was maintained to keep track of the changes being made to the dataset. The csv consisted of the following headers: Image File names, class, Plant Group, Remove code, Zoom Level, Modified. The Remove Code header refers to whether the original image has been divided and modified to the extent that the presence of the original image is irrelevant to the model training process. This csv was used as the medium to feed the images to the pre-trained model.

5. Once the images were ready using the abovementioned format, they were divided into training and validation sets using an algorithm that ensured any plant group was contained only in either the training or validation set

Once the new training and validation sets were produced, the same analysis process used for the original dataset was followed.

Class Activation Maps:

All the experiments undertaken above provided the insight that the images the model is exposed to in the field are complex, with myriad of attributes, distortions and ambient noise. This buttressed the need to validate the decision making of the network due to the complexity of the images that it was exposed to and understand the properties of the modules of the model network. This was done by visualising the weighted activations of the network for the images using class activation maps or CAM (Simonyan *et al*. 2013).

Since the model is trained using Resnet34 as the base model, the layers are not sequential but nested into modules followed by final pooling, dropout, batchnorm and fully connected layers ending with a log SoftMax (Ozbulak, Online; Erhan *et al*. 2009). The way visualization of the CAM was enabled was to change the model in the following ways. First, the model was cloned without the last 10 layers leaving an architecture that finished at the end of the last convolutional layer. A new convolution layer with 512 three by three filters but with only four outputs was added. Given the propagation of the 300x300 input image dimensions through the model this resulted in the layer output being four ten by ten arrays.

Following this layer, an adaptive average pooling layer was applied before finally flattening and applying to a log softmax. The model was then retrained by freezing all of the layers apart from the new ones, hence all of the original convolution layers remained exactly as they were. The final layers thus ended up with the 4 ten by ten outputs of the new convolution layer representing the feature maps or (CAM) of each of the final classes they were connected to.

These feature maps for each class are then overlaid on the input image in order to get the class activation maps. Note that it is important not to go back to the original image but to the

image input to the model, since pre-processing will have resulted in cropping and other

changes.

These class activation maps are helpful in assessing the importance of the image regions

to the network activations and therefore, are very beneficial in identifying the discriminative

regions and features of the leaves that activate the convolutional layers which facilitate the

classification task (Selvaraju *et al*. 2016; Zhou *et al*. 2015). Mapping the activations for all

classes are useful in understanding the reasons for misclassifications and if the model is getting

confused between two classes due to similarity of features which is expected to happen between

grey blight and red rust.

It should be noted that the exact classifications from this model might not be identical to

that of the original model since the classification layers have been changed, however, the

activations will be the same since all of the convolution layers are unchanged. In reality this

modified classifier gives almost the same results in most cases.

Results

Correctly classified images of original dataset:

In the following figures the numbers in brackets above each image show the predicted

probability of the image content being of one of the four classes. A value of 1 indicated

effective certainty that the content belongs to that class, a value of 0 suggests there is almost

no probability that it belongs to that class. The class order is:

1. Grey blight

2. Healthy

3. Red rust

4. Tea mosquito bug

Figure 4 shows images that have been correctly classified with very high levels of

certainty and Figure 5 shows one of the rare incorrectly classified images.

Results of analysis of modified dataset:

After training with the modified dataset an accuracy of 99.6% was achieved. This is better

than the result of the previous analysis. This improvement is because the enhanced accuracy

from the zoomed in images and removal of multiple classes in the same image acted to improve

the accuracy and outweighed the reduced accuracy due to removal of data leakage. Overall,

however, this model would be able to generalise much better on a potential test set. The

confusion matrix for the modified dataset is shown in Figure 6 and it can be seen that only one

incorrectly classified image resulted. Examples of correctly classified images are shown in

Figure 7.

Figure 8 shows the predictions for an image that has leaf damage. In previous models this

had been incorrectly classified as grey blight. In fact, the leaves are either healthy or damaged

but not diseased. This is correctly classified with the new model.

Fig. 6. Confusion matrix for modified dataset

Fig. 7. Examples of correctly classified images using the modified dataset (a) grey blight, (b) healthy, (c) red rust and (d) tea mosquito bug

Fig. 8. Correct classification of damaged and healthy leaves

Class Activation Map Plot Analysis:

In the following plots the title above each image refers to which of the CAM's is being overlaid.

In each case the order is according to decreasing final probability as per the last SoftMax are

shown in the "Actual predictions" caption below the image. The non-linear nature of the

classification process means that is not uncommon for the prediction probabilities to assume

values of unity for one class and zero for other classes. Unless otherwise stated, to enhance

understanding, the colour range of the CAM has been adjusted to cover the range from

maximum to minimum over the displayed classes and the same scale used for all of the

displayed images. Where there are very low activations for the other classes this often means

that there is no significant colouring over the subsequent classes, which is why instead of

showing the CAM plots for all four classes, in most instances, the plots for the two classes with

highest prediction probabilities have been displayed.

Figure 9 shows prediction from leaves that have grey blight. The predictions show that the

model has correctly identified the above image as grey blight and with a high degree of

grey_blight   red_rust

Actual predictions: [GB:1. H:0. RR:0. TMB:0.]

Fig. 9. CAM for image IMG_2848

accuracy. However, the CAM for grey blight shows that apart from the prominent grey blight

infected part of the leaf, the network is picking up a little bit of the leaf in the forefront (right)

which is only damaged and uninfected, but the network could be confusing the damaged leaf

to be symptomatic of grey blight because of the similarity in physical attributes.

Figure 10 and 11 examine classification of the same leaves that are classified differently

at different levels of zoom. Note that in this case the colour map scale was modified to focus

upon areas with the highest activation levels since the default levels made most of the images

a mid-intensity orange. Figure 10 is zoomed out significantly more than Figure 11. Figure 10

is the most worrying of all in that it is a clear misclassification. The actual disease here is grey

blight, however the class with the highest prediction probability is red rust, despite this having

relatively low levels of activation, although what there is cover a wide area hence giving a

higher value from the global average pooling. In this case max pooling would give a different

result, however, the result would still be a miss-classification since the class with the second

highest probability is tea mosquito bug. This is probably because the two dark holes in the leaf

could be mistaken for tea mosquito bug. It is noticeable that in the healthy image the good

leaves on the right-hand side of the image are recognised. In the grey blight image, it can be

Actual predictions: [GB:0. H:0. RR:1. TMB:0.]

Fig. 10. CAM for image IMG_2980 showing miss-classification

seen that the larger area of grey blight is picked up correctly, but the activations are quite low

suggesting the model is uncertain. Figure 11 shows the same leaf but enlarged and from an

angle where the large grey blight is not partially obscured by the leaf in front. In this case the

classification is accurate, and both areas of grey blight are identified correctly. This

demonstrates that predictions should be based upon ensemble models based upon several

images taken with variable viewpoint and magnifications, rather than just one image. This is

a very important finding and conclusion.

Actual predictions: [GB:0. H:0. RR:1. TMB:0.]

Fig. 11. CAM for image IMG_2981 showing correct classification when the image is more zoomed in

Actual predictions: [GB:1. H:0. RR:0. TMB:0.]

Fig. 12. CAM for image IMG_2983 showing correct localization of grey blight. It is noticeable that the light black dots on the leaf on the right are seen as potential tea mosquito bug

Figure 12 shows an image where the centre leaf is correctly classified as grey blight

infected. Interestingly, looking at the CAM for tea mosquito bug, the network does localise

some features in the leaf on the right as indicative of tea mosquito bug. To understand this, the

original image was analysed to find that the leaf simply has some black spotty coloration which

can look in some respect similar to tea mosquito bug but is not. This confusion of features is

an added complexity of working on an image dataset collected in the field. The CAM

visualisation goes a long way in providing these insights.

Figure 13 shows an image that is correctly classified as grey blight, however, there are

several leaves in this zoomed out image that are infected with grey blight but the CAM

localisation shows that the convolutional network is being activated primarily by the large grey

blight features present in the leaf in the foreground and is ignoring the others that are present

in background. Therefore, in the field, the model will prioritise features of the leaves in the

foreground and in focus. It is likely that the model gains in confidence that larger areas of grey

blight are indeed grey blight, but lower confidence in smaller areas that could be confused with

tea mosquito bug or simply damaged leaves in otherwise healthy leaves.

Actual predictions: [GB:1. H:0. RR:0. TMB:0.]

Fig. 13. CAM of IMG_2984 showing detection biased to largest regions

530 Figure 14 shows an image where there are two leaves that are symptomatic of red rust.

531 The localisation of the CAM shows that the network is successfully picking up features on both

532 the leaves, even those features that are not very pronounced (red rust in early stages).

red_rust   grey_blight

Actual predictions: [GB:0. H:0. RR:1. TMB:0.]

Fig. 14. CAM of IMG_3217 showing correct identification of Red Rust on several leaves

Figure 15 shows CAM activations for one of the images that was found to have reduced

confidence in the predicted class. In fact, it is correctly classified as red rust but with

relatively low accuracy. The CAM visualisations show the reduced confidence is not due to a

problem with the identification of the red rust, but instead due to the fact that all of the other

classes are also detected in the image. Since the model is being forced to choose only one

class the presence of a host of other features reduces the confidence level. This result is

encouraging and lends support to the viability of developing the model into a multi-class

prediction tool in the future.

Actual predictions: [GB:0.187 H:0.000 RR:0.8132. TMB:0.000]

Fig. 15. CAM of IMG_3415 showing how the presence of multiple classes can reduce predictive confidence

551   The image shown in Figure 16 has a lot of soil showing in the background. There was

552 some concern that this would be detrimental to the analysis, however, it can be seen that the

553 network is able to localise the features of the red rust and ignore the noise added by the soil.

Actual predictions: [GB:0. H:0. RR:1. TMB:0]

Fig. 16. CAM activations for IMG_3430 showing that soil in the background is not detrimental

561   Figure 17 shows the convolutional network is able to sufficiently ignore the noise from the

562   object in the background of the image and focus on the features of the leaf infested with tea

563   mosquito bug. However, CAM visualisation does show a small amount of the background

564   object being picked up by the convolutional network which shows that the presence of such

565   noise impacts the way the convolutional layers recognise the features.

Actual predictions: [GB:0. H:0. RR:0. TMB:1]

Fig. 17. CAM for IMG_2159 showing detection of tea mosquito bug despite the presence of material in the background

Discussion

This work was intended to investigate the feasibility of using deep learning image recognition tools for diagnosis of plant disease from smartphone camera images. The work has three stages: the original dataset; the dataset with groups; and the class activation mapping investigation.

Original dataset:

The model performed suitably well after it was trained on the original dataset and gave an accuracy of 98.4 % post fine-tuning steps such as learning rate adjustments for each group of layers. Despite this high accuracy, analysis of the confusion matrix showed a number of misclassifications between healthy and infected leaves. The reasons for this were believed to be three-fold, these were the presence of multiple diseases in the same image, the model focussing on leaves other than the target infected leaves and also that some of the images were zoomed out too far. There were also concerns about leakage between the training and validation sets. The high overall level of accuracy of this work gives confidence that the approach was viable and led to the methodology for development of the modified dataset.

The Modified Dataset:

The original dataset was modified by reducing the zoom level of highly zoomed out images and assigning images to plant group where there was no leakage of leaves from one group to another. The training and validation sets were created based on these groups. It was anticipated that certain biases might have crept into the model due to an imbalanced partition of the data into training and validation sets and therefore the dataset partitioned according to groups might face some loss of accuracy during validation. However, the accuracy after unfreezing and training with differential learning rates was 98.3% and after using an optimal learning rate of

0.001, became steady at 98.6%. The validation loss showed a steady decline, being greater than

the training loss only by a small margin ≈ 0.02 so there was no fear of overfitting. It became

germane to the discussion of training a model to be suitable for field use to understand where

any remaining errors were coming from and to see what factors could reduce confidence even

if they did not result in a mis-classification. This led to the work with CAM visualization.

CAM Visualisation:

The Class Activation Mapping visualisations helped identify the regions of the image that were

being focussed on by the layers of the classifier and also enabled prediction of the way in which

the model, when loaded on a system like a smartphone, would behave in the field. As evident

from the results, the model identifies the symptomatic parts of the leaf in the case of an

infection and is able to carry out the single class recognition task to a significantly low zoom

level. From the highly zoomed images, the model is able to learn detailed features of the leaf

and performs classification with very high accuracy. However, for images that are significantly

zoomed out, the CAM visualisation shows that the model prioritises the leaves that are in the

foreground. The visualisations also indicated that it is possible for the CNN to get confused

when multiple leaves are present in the foreground causing the accuracies of the predictions to

drop. The model is currently not optimised to differentiate between physically damaged healthy

leaves and diseased leaves. In an image which high level of background noise, CAM shows

that when the proportion of noise (example: soil) is below a certain value, the classifier

successfully ignores the distraction and focusses on the learned features. However, when the

proportion of the noise in the image increases (example: a black pepper tree along with

significant part of the landscape), the prediction accuracies tend to drop. This is an idea that

needs to be kept in mind when applying this classifier on the field level because the images

that the classifier will encounter will contain multiple leaves and most likely have more than

one diseased leaf in the same frame surrounded by many healthy leaves with high noise levels. From the CAM visualisations it can be estimated that the model will perform well in the field, however a multi class model would be more practical for a field level application.

The CAM visualisation also informs the image collection process. This entire project impresses the fact that working with leaves and their images in the field is a relatively complex process in comparison to training a model on a leaf dataset in a controlled set up and a noise free environment. As seen in Figure 10 a model trained on such a controlled dataset might work very well on paper but may fail on the complex and noise intense conditions of the field. Analysing and deciphering model behaviour based on CAM visualisations form a very important part of incorporating this model in an application that can be tested on the field level with reasonable results.

Conclusions

Based upon the work to date it is considered that the approach adopted can be developed as a way to help farmers diagnose plant disease. Important learning points for the next phase are:

1. Analysis should be made using ensemble analysis of multiple images of the same leaves

2. The level of zoom should be such that features can be clearly recognised in a scaled down 300x300 pixel image, ideally with one of the diseased leaved occupying a large proportion of the image

3. Once the convolution layers have been trained it would be sensible to look to enable multi-class classification, which should be a relatively easy change to make and would allow the model to cope with features it commonly encounters

4. Although not mentioned here in the future region-based models such as Unet [ref] might be necessary to enable quantification of the stage of the disease (based upon for example size and number of disease areas). This should be possible but will require development of a training dataset with bounding boxes added as well as disease classification.

5. Alternative base models such as ResNext could provide greater robustness of classification albeit at the cost of increased training and application resources.

6. The use of Class Activation Maps to validate and understand what is being recognised by the convolutional layers is a very valuable tool.

Acknowledgements:

This research was supported by the Group Technology and Innovation Office (Tata Sons), Rallis India Limited and Tata Global Beverages. We are thankful to Vidya Hegde and Dr. Mallikarjunappa (Rallis India Limited) for providing assistance that was helpful in guiding the research. We express our appreciation for Kailyanjeet Borah (Tata Global Beverages) for providing the necessary support that expedited the process of data collection and expert knowledge about the tea crop and various pests examined in this work.

We are grateful to our colleagues Dr. Gopichand Katragadda, Kamesh Gupta, Piyush Mishra, Aditi Olemann and Arati Nijhawan from the Group Technology and Innovation office for providing wisdom and support that was instrumental in taking this research to its fruition.

References

Abdullahi HS, Sheriff RE and Mahieddine F (2017) *Convolution neural network in precision agriculture for plant image recognition and classification.* 2017 Seventh International Conference on Innovative Computing Technology (INTECH), Luton, 2017, pp. 1-3.

Alfarisy A, Chen Q, and Guo M (2018) *Deep learning based classification for paddy pests & diseases recognition.* Proceedings of 2018 International Conference on Mathematics and Artificial Intelligence - ICMAI '18, pp. 21–25.

Bengio Y (2012) *Practical Recommendations for Gradient-Based Training of Deep Architectures.* In: Montavon G., Orr G.B., Müller KR. (eds) Neural Networks: Tricks of the Trade. Lecture Notes in Computer Science, vol 7700. Springer, Berlin, Heidelber

Bengio Y, Simard P and Frasconi P (1994). Learning long-term dependencies with gradient descent is difficult. IEEE Transactions on Neural Networks, 5(2), 157–166.

Bottou L (2012) *Stochastic Gradient Descent Tricks.* In: Lecture Notes in Computer Science (LNCS), Neural Networks, Tricks of the Trade, Reloaded, Springer, vol. 7700, p. 430-445, January 2012.

Erhan D, Bengio Y, Courville A and Vincent P (2009) *Visualizing Higher-Layer Features of a Deep Network.* Technical Report, Univeristé de Montréal.

Goodfellow I, Bengio Y and Courville A (2016). *Deep Learning.* MIT Press. Available: https://www.deeplearningbook.org/

He K, Zhang X, Ren S and Sun J (2015), *Deep Residual Learning for Image Recognition.* Microsoft Research, December, 2015

Howard J (2017). *How differential learning rate are applied to*
model. (Online) Available: http://forums.fast.ai/t/question-on-how-differential-learning-
rates-are-applied-to-model/7320/2

Howard J and Thomas R (2017) *Recognizing cats and dogs.* Fast.ai: Deep Learning
for Coders. (Online) Available: http://course18.fast.ai/lessons/lesson1.html. Published on
Dec 30, 2017. Accessed: 02-Nov-2018.

Huang G, Li Y, Pleiss G, Liu Z, Hopcroft JE and Weinberger KQ (2017). *Snapshot*
Ensembles: Train 1, get M for Free. Published as a conference paper at International
Conference on Learning Representations 2017

Huang G, Liu Z, Weinberger KQ and Van Der Maaten L (2016) *Densely*
Connected Convolutional Networks. IEEE Conference on Computer Vision and Pattern
Recognition (CVPR), 2016.

Kamilaris A and Prenafeta-Boldú F (2018) *A review of the use of convolutional*
neural networks in agriculture. The Journal of Agricultural Science, 156(3), 312-322.
doi:10.1017/S0021859618000436

Kaur R and Singla S (2016) *Classification of Plant Leaf Diseases Using Gradient and*
Texture Feature. Proceedings of International Conference on Advances in Information
Communication Technology & Computing. - AICTC '16, Article No. 96, pp. 1–7.

Krizhevsky A, Sutskever I and Hinton GE (2012) *Imagenet classification with deep*
convolutional neural networks. Published In: Advances in Neural Information Processing
Systems 25. (NIPS 2012_4824) Pages 1097–1105

Kunwar B (2018) *Forums for fast.ai with Discourse.org.* (Online)
Available: http://forums.fast.ai/t/learn-sched-plot-doesnt-show-anything/11725/9

Lin TY, Maire M, Belongie S, Bourdev L, Girshick R, Hays J, Perona P, Ramanan
D, Zitnick CL and Dollár P (2014) *Microsoft COCO: Common objects in context.*
Lecture Notes Computer Science (including Subseries Lecture Notes Artificial

Intelligence Lecture Notes Bioinformatics), vol. 8693 LNCS, no. PART 5, pp. 740–755, 2014.

Mohanty SP, Hughes D and Salathé M (2016) *Using Deep Learning for Image-Based Plant Disease Detection.* Frontiers in Plant Science. 2016;7:1419. April 15, 2016

Van Noord N and Postma E (2017) *Learning scale-variant and scale-invariant features for deep image classification.* Pattern Recognition, Volume 61, 2017, Pages 583-592, ISSN 0031-3203

Ozbulak U (2017) *Pytorch implementation of convolutional neural network visualization techniques.* (Online) Available: https://github.com/utkuozbulak/pytorch-cnn-visualizations.

Ramcharan A, Baranowski K, McCloskey P, Ahmed B, Legg J and Hughes DP (2017) *Deep Learning for Image-Based Cassava Disease Detection.* Frontiers in Plant Science, vol. 8, p. 1852, Oct. 2017.

Reitermanov´a Z (2010) *Data Splitting.* WDS'10 Proceedings of Contributed Papers, Part I, 31–36, 2010, ISBN 978-80-7378-139-2, Copyright MATFYZPRESS

Roy N and Bezbaruah MP (2002) *Agricultural growth and regional economic development (a study of Barak Valley).* Mittal Publications, 2002.

Ruder S (2017) *Transfer Learning - Machine Learning's Next Frontier.* (Online) Available: http://ruder.io/transfer-learning/

Russakovsky O, Deng J, Su H, Krause J, Satheesh S, Ma S, Huang Z, Karpathy A, Khosla A, Bernstein M, Berg AC and Li Fei-Fei (2015) *ImageNet Large Scale Visual Recognition Challenge*. International Journal of Computer Vision, vol. 115, no. 3, pp. 211–252, 2015.

Selvaraju RR, Cogswell M, Das A, Vedantam R, Parikh D and Batra D (2016) *Grad-CAM: Why did you say that?* Visual Explanations from Deep Networks. CoRR, abs/1610.02391, 2016

Simonyan K, Vedaldi A and Zisserman A (2013) *Deep Inside Convolutional*
Networks: Visualising Image Classification Models and Saliency Maps. International
Conference on Learning Representations Workshop 2014, CoRR, abs/1312.6034, 2013

Simonyan K and Zisserman A (2014) *Very Deep Convolutional Networks for Large-*
Scale Image Recognition. arXiv preprint arXiv:1409.1556

Sladojevic S, Arsenovic M, Anderla A, Culibrk D, and Stefanovic D (2016) *Deep*
Neural Networks Based Recognition of Plant Diseases by Leaf Image Classification.
Computational Intelligence and Neuroscience, Volume 2016, Article ID 3289801, 11
pages http://dx.doi.org/10.1155/2016/3289801

Tan C, Sun F, Kong T, Zhang W, Yang C and Liu C (2018). *A Survey on Deep*
Transfer Learning. Published in 2018 International Conference on Artificial Neural
Networks ICANN '18, Pages 270-279

Xie S, Girshick R, Dollár P, Tu Z and He K (2017) *Aggregated Residual*
Transformations for Deep Neural Networks. IEEE Conference on Computer Vision and
Pattern Recognition (CVPR), 2017, Apr. 2017

Zhao ZQ, Zheng P, Xu S and Wu X (2018) *Object Detection with Deep Learning: A*
Review. Jul 2018.

Zhou B, Khosla A, Lapedriza A, Oliva A and Torralba A (2015) *Learning Deep*
Features for Discriminative Localization. Computer Vision and Pattern Recognition
(CVPR), 2016 CoRR, abs/1512.04150, 2015