1

Terminitor: Cleavage Site Prediction Using Deep Learning Models

Chen Yang[1,2], Chenkai Li[1,2], Ka Ming Nip[1,2], René L Warren[1], Inanc Birol[1,2*]

[1] Canada's Michael Smith Genome Sciences Centre, BC Cancer, Vancouver, V5Z 4S6, Canada

[2] University of British Columbia, Vancouver, V6T 1Z4, Canada

* Corresponding author

E-mail: ibirol@bcgsc.ca (Birol I)

Abstract

As a widespread RNA processing machinery, alternative polyadenylation plays a crucial role in gene regulation. To help decipher its underlying mechanism and understand its impact, it is desirable to comprehensively profile 3'-untranslated region cleavage and associated polyadenylation sites. State-of-the-art polyadenylation site detection tools are known to be influenced by library preparation artefacts or manually selected features. Moreover, recently published machine learning methods have only been tested on pre-constructed datasets, thus lacking validation on experimental data. Here we present Terminitor, the first deep neural network-based profiling pipeline to make predictions from RNA-seq data. We show how Terminitor outperforms competing tools in sensitivity and precision on experimental transcriptome sequencing data, and demonstrate its use with data from short- and long-read sequencing technologies. For species without a good reference transcriptome annotation, Terminitor is still able to pass on the information learnt from a related species and make reasonable predictions. We used Terminitor to showcase how single nucleotide variations can create or destroy polyadenylated cleavage sites in human RNA-seq samples.

Author Summary

3' cleavage and polyadenylation of pre-mRNA is part of RNA maturation process. One gene can be cleaved at different positions at its 3' end, namely alternatively polyadenylation, thus identifying the correct polyadenylated cleavage site (poly(A) CS) is essential to unveil its role in gene regulation under different physiological and pathological conditions. The current poly(A) CS prediction tools are either heavily influenced by RNA-Seq library preparation artefacts or have only been designed and tested on *ad hoc* datasets, lacking association with real world applications. In this study, we present a deep learning model, Terminitor, that predicts the probability of a nucleotide sequence containing a poly(A) CS, and validated its performance on human and mouse data. Along with the model, we propose a poly(A) CS profiling pipeline for RNA-seq data. We benchmarked our pipeline against competing tools and achieved higher sensitivity and precision in experimental data. The usage of Terminitor is not limited to genome and transcriptome annotation and we expect it to facilitate the identification of novel isoforms, improve the accuracy of transcript quantification and differential expression analysis, and contribute to the repertoire of reference transcriptome annotation.

Introduction

Since polyadenylated (poly(A)) sequences were first discovered on the 3' ends of eukaryotic mRNAs 40 years ago [1], numerous studies have contributed to the understanding of the mechanisms, evolution, regulation, and impacts of polyadenylation [2–5]. As an essential step in mRNA maturation, RNA polyadenylation involves two phases: 3' end cleavage of nascent RNA and addition of a poly(A) tail. This process is facilitated by several *cis*-acting RNA elements, represented by the poly(A) signal (PAS), conserved hexamer motifs with AATAAA being the most strongest, located 10-30 nt upstream of the cleavage site (CS) [6]. Because most nascent RNA in eukaryotes have more than one possible 3' end CS, mRNAs with different 3' ends are formed following these two coupled processes [7]. This phenomenon is also known as alternative polyadenylation (APA), which results in transcripts with different 3' untranslated regions (UTR). In recent years, advances in DNA/RNA sequencing technology allowed detailed study of APA modulation under different physiological and pathological conditions, and shed light on its implications in some diseases, especially cancer [5,8–10].

The importance of profiling 3' UTR cleavage

APA, together with alternative splicing, has considerable impact on the modulation of gene expression and contributes to transcriptome complexity. As of date, the catalogue of profiled poly(A) CS, especially cancer-specific ones, is far from complete [11]. Ensembl annotation version GRCh38.94 records 63,620 poly(A) CS for 19,907 protein coding genes in human, and among them, 73.13% genes can produce two or more APA isoforms (S1 Fig) [12]. The most recent poly(A) database, PolyA_DB3, compiled 24 human samples and cataloged 108,042 poly(A) CS for 20,998 genes [13]. The substantial improvement in 3' end annotation compared to Ensembl suggests the

sample-specific usage of poly(A) CS, highlighting the incompleteness of the current annotation.

Moreover, usage of these poly(A) CS is dynamically regulated under different developmental

stages and pathological changes, as elucidated in previous studies [5,8,14,15]. Profiling poly(A)

CS with respect to biological conditions serves as the first step towards deciphering the

underlying mechanism of APA-mediated gene regulation. Hence, it is desirable to incorporate a

fast and robust poly(A) CS characterization tool into standard transcriptome analysis pipelines.

Current methods and their limitations

In the past decades, continuous efforts have been made to annotate 3' ends in the genome

and predict poly(A) CS in the transcriptome, using methods designed for two major sequencing

protocols: 3' end targeted sequencing and poly(A)-selected RNA-seq. The former is a specialized

high throughput sequencing technique that is developed to overcome the low sequence

complexity at the 3' end of transcripts. These methods, including TAIL-Seq, PolyA-Seq, PAS-seq,

and PAT-seq [16–19], only interrogate the 3' ends of transcripts by primers, followed by

sequencing and bespoke analysis pipelines. Compared to methods that use RNA-seq, a critical

advantage of these protocols is their high sensitivity in detecting poly(A) CS from lowly expressed

transcripts. With the help of 3' end sequencing technologies, several poly(A) CS databases have

been established [13,20–22]. Though powerful, they require specialized library preparation,

which can be costly and laborious, and their utility is restricted to poly(A) detection. As a result,

they have not yet been widely adopted in genetic research.

In contrast, RNA-seq is the established sequencing method of choice for a wide range of

transcriptomics projects. It can also be used for poly(A) CS profiling on a per-sample basis, as well

as for systematic APA analysis of large cohorts of individuals, including retrospective studies.

Poly(A) CS prediction and annotation tools designed for RNA-seq have demonstrated that with

suitably redundant coverage (read coverage ≥ 2), RNA-seq data type contains sufficient

information for the identification of poly(A) tails, and thus permits the discovery of novel poly(A)

CS [23,24]. Generally speaking, these tools can be classified into three approaches: read-evidence

based, expression level based, and machine learning based.

Read-evidence based approaches, such as KLEAT [23] and ContextMap2 [24], search for

untemplated adenosines (As) in aligned sequences as evidence to determine the location of

poly(A) CS. Although these tools are able to discover novel poly(A) CS with high resolution, they

may lose sensitivity in low coverage sequencing libraries and when transcript expression is low.

For approaches based on expression levels, poly(A) CS prediction is a by-product of APA

analysis. Tools adopting this approach, which include DaPars, APAtrap, and QAPA [25–27], all rely

on differential expression in the 3' UTRs of matched samples. However, due to the low sequence

complexity of 3' UTRs and the resulting sequencing data artefacts, read coverage in these regions

may not reflect true expression levels, impacting differential expression analysis and associated

statistical tests. Consequently, these methods may fail to detect real but lowly represented APA

events. Moreover, they only report poly(A) CS involved in significant APA events through

comparative analyses, and thus these tools are not capable of profiling poly(A) CS in given

samples.

Another approach to address the prediction problem is through the use of deep learning

methods, and several such models have been proposed recently, such as DeeReCT-PolyA [28],

DeepGSR [29], and DeepPASTA [30]. For these tools, hidden features are learnt and modeled

directly from input nucleotide sequences. Using this approach, DeeReCT-PolyA and DeepGSR

have been reported to show around 90% accuracy on test sequences [28,29]. Combining both

sequence and RNA secondary structure information, DeepPASTA, was reported to have an area

under the curve score over 93% in predicting poly(A) CS. However, these tools were only bench-

marked on pre-constructed datasets composed of positive and negative genomic sequences, and

none have been applied to real experimental transcriptome data for prediction. Another

limitation of DeeReCT-PolyA and DeepGSR is that they were only trained to distinguish whether

a PAS is real. However, it is known that a small fraction (yet a substantial number) of functional

human poly(A) CS does not require a PAS [32,33]. At present, these approaches overlook poly(A)

CS with noncanonical *cis*-acting elements, which would likely negatively impact their

performance on experimental data.

Terminitor

Despite the availability of various tools, comprehensively and efficiently profiling poly(A) CS in

RNA-seq samples remains challenging. In this study, we present Terminitor, a deep neural

network (NN) model for fast and accurate poly(A) CS recognition, independent of the existence

of a PAS. Terminitor takes fixed length sequences as input and performs a three-label

classification to determine whether the sequence contains a poly(A) CS, a non-polyadenylated

CS, or non-CS. Coupled with Terminitor, we also propose a profiling pipeline that generates

prediction of poly(A) CS using raw RNA-seq data as input. The performance of this pipeline was

cross-validated on two datasets of sequences (describing human and mouse transcriptomes) to

select the optimal input sequence length and model hyperparameters. We have benchmarked

our pipeline against competing tools on experimental paired-end RNA-seq libraries generated

from the Illumina (San Diego, CA) TruSeq paired-end and Pacific Biosciences (Menlo Park, CA)

Single Molecule, Real-Time (SMRT) Sequencing platforms.

Results

Performance of Terminitor using different sequence lengths

Terminitor is trained on experimentally validated annotated nucleotide sequences containing

three classes of sites: (1) poly(A) CS, (2) non-poly(A) CS, and (3) non-CS. Using cross-validated

optimal hyperparameters, it computes the probability of a test sequence belonging to one of the

three classes.

To train, validate, and test the model, we collated two reference datasets describing human

and mouse transcriptomes, based on poly(A) CS databases and Ensembl annotations. These

datasets are composed of labeled sequences of uniform length with three parts: upstream

sequence, a site from one of the three classes, and downstream sequence. Upstream sequences

are from corresponding transcripts for the first two classes and from genomic regions for the

third class, while downstream sequences are genomic, and the transition from upstream

sequence to downstream sequence is marked as the cleavage site or lack thereof (S2 Fig). Since

there is no consensus from previous work on how the input sequence length influences

prediction accuracy, we built models with different lengths to evaluate its effect on performance.

Eight upstream lengths (200, 160, 120, 100, 80, 60, 40 and 20 nt) and five downstream lengths

(200, 100, 40, 20 and 0 nt) were chosen to create a total of 40 models, which were trained to

explore the impact of sequence length on poly(A) CS prediction (Fig 1). In general, all models

show clear separation between poly(A) CS and the other two labels (S3 Fig). The accuracy of all

40 models is above 87%, including the one trained with only 20 nt long upstream sequence. As

expected, models trained with sequences containing both upstream and downstream sequences

perform better than the ones trained with upstream sequences alone (0 nt downstream

sequence length). However, given the same upstream sequences, models trained with

downstream sequences longer than 20 nt perform comparably to each other. The 28 models

trained with upstream sequence lengths in {40, 60, 80, 100, 120, 160, 200} and downstream

sequence lengths in {20, 40, 100, 200} have an average accuracy of 94.50% ± 0.0015. More

interestingly, longer downstream sequences do not necessarily lead to better performance.

Models trained with 200 nt downstream sequences have slightly lower accuracy than the ones

trained with shorter lengths, suggesting that some polyadenylation recognition patterns maybe

obscured by sequence motifs further downstream.

Fig 1. Model performance on human reference dataset. Each facet represents one
downstream sequence length, and the x-axis of each facet plot shows the up-stream sequence
length. Each data point is the mean of 5-fold cross validation and the error bar is the standard
deviation.

On the other hand, given the same downstream sequence, the performance of models

plateaus when the upstream sequence is 40 nt or longer. Similarly, longer upstream sequences

do not guarantee better performance either, especially when the upstream length is much longer

than the downstream length. For example, the model with 120 nt upstream and 20 nt

downstream sequences is nearly 0.5% more accurate than the one with 200 nt upstream and 20

nt downstream sequences. This decrease is mainly due to a drop in specificity, which means the

model has more false positive predictions with longer upstream sequence.

Tool comparison on experimental data

In order to demonstrate the application of Terminitor on poly(A) CS profiling, we designed a

prediction pipeline and applied it on two human RNA-seq samples, Human Brain Reference RNA

(HBR) and Universal Human Reference RNA (UHR), to predict poly(A) CS from reconstructed

transcripts. As done previously, we trained Terminitor with 40 length combinations, applied all

40 models on UHR sample, and computed the Pareto frontier based on sensitivity and precision.

The sensitivity of Terminitor is positively correlated with upstream sequence length, while there

is no clear trend between the downstream sequence length and the performance metrics (S4 Fig).

For demonstration purposes, we chose ± 100 nt model for performance benchmarking and

comparison.

Profiling poly(A) CS for species without a good reference annotation can be challenging. Thus

it is interesting to test whether the information learnt from one species is transferable to another.

In addition to the model built on the above-mentioned human reference dataset, we also

generated a model that was separately trained on the mouse dataset. We applied these two

models on the UHR and HBR samples and compared the performance with KLEAT, DeepPASTA,

DeeReCT-PolyA and DeepGSR (Fig 2A, S5A Fig). Poly(A) CS predicted by these methods were

compared against Ensembl annotation to calculate the sensitivity and precision. Note that the

denominator in sensitivity calculations represents all Ensembl annotations, yet for a given sample

not all transcripts would be expressed. Without a *priori* information on gene and isoform

expression, this is the most appropriate solution at it penalizes all methods the same way,

preserving their relative performance for fair comparisons.

Fig 2. Performance comparison on the UHR sample. A. Sensitivity and specificity of poly(A)
CS predictions from Terminitor, KLEAT, DeepPASTA, DeeReCT-PolyA and DeepGSR on Ensembl
annotated poly(A) CS. The two pre-trained models of DeepGSR are the one with sequences
containing only the strongest PAS hexamer AATAAA, and the one with sequences containing 16
hexamer motifs pooled together. The two pre-trained models of DeeReCT-PolyA are derived from
the dragon dataset and omni dataset as described (Xia et al., 2019). Two pre-trained Terminitor
models are derived from the human and mouse datasets. The navy/blue crosses on Terminitor

human/mouse model represent probability = 0.5 cut-off, respectively. **B.** Percentage of poly(A)
CS that are missing from Ensembl annotation are supported/not supported by PolyA-Seq. We
used probability = 0.5 cut-off for Terminitor and DeepPASTA predictions.

We also note that DeeReCT-PolyA and DeepGSR are binary classifiers, while Terminitor

outputs a probability value that can be tuned in favour of either sensitivity or precision.

Nevertheless, Terminitor trained on human sequences consistently outperforms all competing

tools in both metrics, except for one data point, which corresponds to the raw, unfiltered KLEAT

predictions. However, the precision of raw KLEAT predictions is arguably too low (35.90% and

25.52% for UHR and HBR samples, respectively) to be used for high-confidence profiling.

Although KLEAT performs comparably to Terminitor on UHR sample, its performance is

surprisingly low on HBR sample regardless of what read evidence is used to filter its raw

predictions. It is also worth mentioning that the four models built by DeeReCT-PolyA and

DeepGSR all have a precision lower than 50%, while precision of the Terminitor human model (at

probability = 0.5 cut-off) is 55.59% and 57.72% for UHR and HBR samples, respectively.

Since a given sample may express novel transcripts or transcripts with novel poly(A) CS, we

compared the falsely predicted poly(A) CS determined by Ensembl annotation with the

corresponding PolyA-seq predictions to identify putative novel events with PolyA-seq evidence

(Fig 2B, S5B Fig). Although Terminitor did not predict the highest number of high confidence

poly(A) CS overall, it is always the pipeline having the highest percentage (35.45% and 36.95% for

UHR and HBR sample, respectively) of predictions that have PolyA-seq evidence support. This

suggests its high precision in detecting novel poly(A) CS when compared to the other methods.

Although the raw KLEAT predictions identified a large number of poly(A) CS, only a small

proportion can be verified by PolyA-seq. We observed that to maintain precision, certain filters

have to be applied to make use of KLEAT predictions, while the choice of filter may be highly

library-dependent.

We compared the runtime and peak memory usage of all competing tools under the same

computing environment (Table 1). All five pipelines used RNA-Bloom [34] as the *de novo* RNA-

seq assembler to start with, and the peak memory usage of all pipelines is the same (37.87 GB),

contributed by RNA-Bloom. Terminitor, DeepPASTA, DeepGSR, and DeeReCT-PolyA shared the

same pipeline to identify candidate sequences, and the only difference is the NN used for

sequence classification, which resulted in runtime differences. With a runtime of 7:06:52 hours,

DeeReCT-PolyA is the fastest tool, followed by Terminitor with less than 5-minute (1.17%) run

time difference. DeepPASTA took two hours more than the first two competitors because of the

RNA structure prediction step, although this extra step did not help improve its prediction

performance. The long runtime of DeepGSR is probably due to its implementation, which was

only compatible with Python 2.7 and older versions of Keras and Theano. KLEAT is more than

three times slower compared to all other tools because it involves computationally expensive

read-to-contig and contig-to-genome alignments.

Table 1 Runtime comparison. The runtime for all four pipelines includes *de novo* assembly of UHR sample (two replicates), alignments, candidate poly(A) CS identification and classification.

Pipeline	Wallclock Runtime (hh:mm:ss)	Wallclock Runtime without assembly
DeeReCT-PolyA	7:06:52	17:29
Terminitor	7:11:23	22:00
DeepPASTA	9:17:49	2:28:26
DeepGSR	11:10:22	4:20:59
KLEAT	25:17:00	18:27:37

Impact of expression level on prediction accuracy

The Ensembl annotation is a repertoire of transcript annotations from multiple tissues and cell

lines in a range of biological states, so not all of the annotated poly(A) CS are expressed in the

HBR and UHR samples, as noted above. We quantified the expression levels of all polyadenylated

reference transcripts in Ensembl, and then examined how the four tools perform with respect to

poly(A) CS at different expression levels (Fig 3, S6 Fig). Aside from the spikes corresponding to

KLEAT raw predictions, Terminitor consistently performs better than all competitors in four tiers

of expression thresholds. As expected, the sensitivity of all tools increases as the expression level

threshold increases, because unexpressed transcripts are removed from the denominator. The

performance difference between Terminitor and other tools increases as well when the

expression cut-off increases. In fact, the performance metrics of Terminitor mouse model on

poly(A) CS expressed at > 20 TPM are similar to, or better than, DeepPASTA, DeepGSR and

DeeReCT-PolyA models for both UHR and HBR samples, showing the promising application of

Terminitor on species without a good reference transcriptome annotation.

Fig 3. Performance comparison on the UHR sample with different expression level cut-offs.
Sensitivity and precision of poly(A) CS predictions of Terminitor, KLEAT, DeepPASTA, DeeReCT-
PolyA and DeepGSR on expressed Ensembl transcripts. The four facet plots represent the
comparison between all expressed transcripts, expressed transcript with TPM > 1, > 10, and > 20,
as indicated.

Single nucleotide variation in PAS affects APA choices

One of the advantages of Terminitor is that it is capable of predicting poly(A) CS solely based

on sequence context. Consequently, poly(A) CS created or destroyed by base changes can also

be identified. We carefully examined all candidate sequences belonging to the UHR sample, and

identified sequences containing different PAS hexamer motifs from the reference human

genome assembly. Through comparisons between the predicted probabilities and the base

variation, we discovered two cases of variation-associated polyadenylation.

The first variant base is recorded in dbSNP as rs6484833, a C-to-T change at chr11:36273982

(GRCh38.p12) on the reverse strand as seen in Integrative Genomics Viewer (S7A Fig) [35,36].

This polymorphism creates the strongest hexamer AATAAA on gene *COMMD9*, and it is

associated with an unannotated poly(A) CS at chr11:36273960 on the terminus exon. We

speculate that this association may be causal, the former causing the latter. In our pipeline, RNA-

Bloom successfully reconstructed this novel transcript to full length with a poly(A) tail, and

Terminitor predicted it as a poly(A) CS with 99% probability. This poly(A) CS is also detected in

PolyA-Seq of the same sample. Based on Ensembl annotation, *COMMD9* has three poly(A) CS

associated with the same terminus exon. This site results in the second-longest 3' UTR, which

harbours three miRNA binding sites and extensive RNA binding protein (RBP) sites for 19 RBPs

(S8 Fig).

The second variant base is rs15342, a T-to-C change at chr15: 101070089 on gene *LRRK1* (S7B

Fig). This polymorphism destroys the strongest hexamer AATAAA, which is associated with an

annotated poly(A) CS 22 nt downstream. There are 21 sequencing reads containing this

polymorphism extend beyond this poly(A) CS, while reads carrying the wildtype are all

polyadenylated. RNA-Bloom successfully assembled both the wildtype transcript with a poly(A)

tail and the variant transcript without poly(A) tail. Terminitor classifed the wildtype and variant

transcripts to contain poly(A) CS with a probability of 98% and 1%, respectively. This

polymorphism may prevent cleavage at the poly(A) CS immediately downstream, leading to the

alternative usage of the distal poly(A) CS, and producing a transcript with longer 3' UTR. Similarly,

extensive (16) miRNA binding sites and RBP sites for 77 RPBs are also predicted to exist on this

extended 3' UTR (S9 Fig).

Terminitor performance on long reads

Although the current short read sequencing followed by *de novo* transcriptome assembly is

part of Terminitor's mainstream RNA-seq analysis pipeline, the advent of long read sequencing

technologies provides unprecedented opportunity to study APA at the transcript isoform level.

Here we applied the Terminitor pipeline on two sequence libraries from the human sample

NA12878, namely Illumina short reads and PacBio circular consensus sequence (CCS) reads (see

Methods for details). Terminitor consistently profiles three times or more poly(A) CS in the PacBio

library as in the Illumina library, even under different expression level cut-offs (Fig 4). However,

with the Illumina library, Terminitor is able to detect more poly(A) CS at a higher precision (>

70%). As the probability cut-off becomes more stringent, less positive poly(A) CS are predicted

by both libraries, but the overlapping percentage with respect to the Illumina library increases

(S10 Fig). For predicted poly(A) CS with a probability > 90%, 59.27% of the CSs found in the

Illumina library are also found in the PacBio library.

Fig 4. Performance comparison between PacBio library and Illumina library on a *H. sapiens*
NA12878 sample. Sensitivity and precision of poly(A) CS predicted by Terminitor on PacBio and
Illumina libraries at different expression level cutoffs. The four facet plots represent the
comparison between all expressed transcripts, expressed transcript TPM > 1, > 10, and > 20, as
indicated.

Discussion and Conclusions

Here we introduce a novel deep learning model named Terminitor to detect and classify 3' UTR

cleavage sites with or without poly(A) tails, and a profiling pipeline that starts from raw RNA-seq

reads to characterize expressed poly(A) CS. The novelties of our model and contributions in this

work are as follows:

1. The use of concatenated *k*-mer representations instead of raw sequence as model input.

Previous applications of deep learning in omics research have shown that designing a proper

representation of the raw data is critical to facilitate classification performance. Inputting

additional information, namely well-studied sequence features, can also alleviate the burden of

learning complex structures. In the case of polyadenylation, several *cis*-acting elements have

been revealed, such as the GU-rich sequences in the downstream, UGUA elements in the

upstream, and the conserved hexamer motif. Inspired by the usage of *k*-mer in the

genome/transcriptome assembly tasks, Terminitor uses *k*-mer representations of raw sequences

to mimic functional motifs. Since the auxiliary elements may have different lengths, multiple *k*-

mer representations are jointly used to, and are observed to push the accuracy higher.

2. The use of an embedding layer to learn the similarities between *k*-mer pairs. One-hot

encoded *k*-mer representation of raw sequence is high dimensional and sparse. In our case, the

input dimension is exponential to *k*, and most positions in the input vector are zeros. This is

computationally inefficient, and would not capture similarities between *k*-mers. To address this,

we borrowed the concept of word embedding from natural language processing and used it as

an interface between the input layer and the subsequent hidden layers. Essentially, in the

embedding layer, one-hot encoded *k*-mers are converted into dense vectors, representing the

projection of *k*-mers in a continuous vector space. Consequently, motifs with similar functions

are likely to have similar weights, and treated similarly in the subsequent layers.

3. Separation of non-polyadenylated CSs from polyadenylated CSs. To our knowledge,

Terminitor is the first poly(A) CS classifier that includes non-polyadenylated CS label. Although

most protein-coding and long-noncoding RNAs contain poly(A) tails at their 3' ends, a significant

number of functional transcripts are not polyadenylated [37]. Since the 3' end processing

mechanism of this group is distinct from polyadenylated CS group, separating it out as a new

class improves the performance of the model. Sequence clustering based on Terminitor's last

hidden layer also groups sequences containing non-polyadenylated CS and non-CS together as a

big cluster (S3 Fig).

Compared to targeted 3' end sequencing technologies, RNA-seq data, whether generated

using short or long read techniques, are more accessible and widely used in transcriptome studies.

In the reported work, we demonstrate that the Terminitor pipeline can identify poly(A) CS on

expressed transcripts with high precision in comparison to the state-of-the-art methods for RNA-

seq data. Failure in detecting a real and expressed poly(A) CS is mostly due to the failure of

reconstructing transcripts to their 3' ends. For instance, in the UHR sample, among the 58,925

expressed poly(A) CS that were not detected, more than half (30,181) have a TPM less than one,

and the majority of them have very few or no reads supporting the poly(A) tail because of

sequencing bias.

We observed that false positive predictions by Terminitor generally occur for three reasons.

The first and most common scenario is mis-assemblies due to the low sequence complexity of

the 3' UTR. Second, these poly(A) CS are in fact real novel events, but unannotated; around 30%

of the Terminitor false positives (using the Ensembl annotation) are corroborated by PolyA-Seq

evidence (Fig 2B, S5B Fig). Third, mis-alignment of upstream sequences, meaning the sequence

may contain a real poly(A) CS, but the genomic location is incorrect. In the Terminitor pipeline,

when an upstream sequence is multi-mapped, only the primary alignment is chosen to help

reduce the false positive rate. However, when the sequence comes from gene paralogs, the

genomic location inferred from the chosen alignment does not necessarily correspond to that of

the expressed paralog.

In principle, the Terminitor pipeline can be applied on any reconstructed transcripts to

determine if its 3'-end contains a poly(A) CS, or non-polyadenylated CS, or no site (3' incomplete).

Aside from benchmarking its performance on traditional Illumina short read assemblies, we also

explored its application on PacBio long read technology. Terminitor demonstrated more than

twice the CS prediction sensitivity when using the PacBio vs. Illumina library, probably because

more sequences containing real poly(A) CS are fed into the NN model. PacBio CCS reads are self-

corrected through consensus calling step, resulting in near- or full-length transcripts with poly(A)

tails. In contrast, transcripts reconstructed from an Illumina library may suffer from mis-

assemblies, and lowly expressed poly(A) CS may be obscured by longer transcripts. In our analysis,

among the 548,448 candidate sequences extracted from the PacBio library, 29.71% of them

contain untemplated poly(A)s, while the ratio is much lower (7.22%) in 381,934 assembled

sequences using the Illumina library.

In summary, Terminitor outperforms all state-of-the-art methods in the datasets we

benchmarked them on, and executes within a reasonable time, making it an attractive tool to

complement other RNA-seq analysis pipelines. The performance of Terminitor is robust on both

short and long-read sequencing technologies. As long-read RNA-seq finds broader uptake in

transcriptome studies, it is poised to shed light on the association between poly(A) CS and

transcript isoforms, fueling a new era of APA research. Terminitor is a candidate enabling

technology for such studies. Further, we have observed how Terminitor can identify novel poly(A)

CS caused by base variations. As has been elucidated in previous studies, novel poly(A) CS are

expressed in cancer tissues, and with the help of Terminitor, mechanisms and impacts of APA can

be better understood. Even for species without an established poly(A) CS database, their

expressed poly(A) CS can be identified with Terminitor using transfer learning, where the model

is trained on a different but related species. The usage of Terminitor, as a sequence classifier, is

not limited to poly(A) CS profiling, but can also be extended to facilitate gene annotation and

testing the completeness of assembled transcripts. We expect Terminitor to have broad

applications in genome/transcriptome annotation, novel isoform identification, APA analysis and

gene regulation studies.

Methods

Datasets

To train and validate the NN model, and to demonstrate transfer learning, we collated two

reference datasets describing human and mouse transcriptomes, based on poly(A) CS databases

and Ensembl annotations. Each dataset is composed of sequences with equal lengths coming

from three classes: poly(A) CS, non-poly(A) CS, and non-CS (Table 2). PolyA_DB version3.1 was

used as our primary poly(A) CS library [13]. We first mapped poly(A) CS recorded in PolyA_DB3

to Ensembl annotation release 94 using `bedtools closest` (v2.27.1) and selected the most

compatible transcript for each site. Poly(A) CS supported by less than 1 Reads Per Million (RPM)

or located more than 1000 nt downstream of any annotated transcript were considered

unreliable and were discarded.

Table 2. Size and origin of datasets for model training, testing, and validation

Species	poly(A) CS	non-poly(A) CS	non-CS
H. sapiens	52,457	27,595	52,460
M. musculus	75,661	37,028	75,660

To avoid potential poly(A) CS contaminating the other two classes, we expanded our poly(A)

CS library by incorporating three additional poly(A) databases, including APADB v2, APASdb, and

PolyASite. Again, we used `bedtools closest` to assign poly(A) CS in the compiled poly(A)

library to Ensembl transcripts. Transcripts with no poly(A) CS from the above-mentioned

databases assigned were considered as cleaved but not polyadenylated, and their 3' ends

constituted the non-polyadenylated CS set.

Non-CS comprises five types of genomic locations: exonic, intronic, intergenic, 5' and 3'

untranslated regions, and are randomly selected at least 100 nt away from any annotated 3' ends,

including Ensembl annotation and compiled poly(A) library.

Our datasets are imbalanced in their label abundances due to the limited number of non-

polyadenylated CS. However, to fully exploit the potential of deep NNs, we used all non-

redundant poly(A) CS and CS generated as above descriptions, and deliberately matched the

number of pseudo sites to the number of poly(A) CS. Because the label abundances are

imbalanced, we used both accuracy and the F-measure, the harmonic mean of precision and

recall, as assessment metrics during model training and benchmarking.

Model training

The NN model is implemented in Python 3.6.6, using Keras library 2.2.4 [38] with TensorFlow

1.11.0 [39] as the backend. To evaluate the performance of the model with different

hyperparameter combinations and input sequence lengths, we used stratified 5-fold cross

validation on the whole dataset to monitor the overall accuracy of three labels, and accuracy,

sensitivity, and specificity on poly(A) label. All performance metrics on the training sets reported

in this study are the mean and standard deviation of five validation runs. In each run, 80% of data

is used for training and 20% is used for validation. Next, we trained the model using the entire

training set and used it for benchmarking the performance on experimental data.

Model architecture and hyperparameter tuning

Searching for the optimal hyperparameters for a deep NN has always been a tedious task, as

many parameters are dependent on each other in the way they influence performance. We first

built the basic frame with one input layer, one embedding layer, and one output classification

layer, and then fine-tune hyperparameters related to architecture and training using grid search,

as listed in Table 3. For all models, initial model weights were randomly drawn from Glorot

uniform initializer [40]. The weights of the three neurons in the output layer are computed via

softmax activation function, representing the probability distribution of the three labels, and they

always add up to one. To avoid over-fitting, we applied early stopping in training each model. As

an iterative method, the validation loss is monitored at each training epoch, and when it stays

the same or increases for the next ten epochs, the training process is stopped. Without early

stopping, too many training epochs will lead to nearly 100% accuracy on training set, yet yield

very low accuracy on validation and test sets.

Table 3 Model hyperparameter tuning. Bolded parameters are the selected optimal values

Parameter type	Parameter	Search space
Training	Optimizer	SGD, **Adam**, Adagrad, RMSprop
	Learning rate	0.1, 0.01, **0.001**, 0.0001
	Loss function	**Categorical_cross_entropy**, mean_squared_error
	K-mer representation	{1}, {2}, {3}, {4}, {5}, {6}, {7}, {8}, {9}, {10}, {11}, {12}, {4, 5}, {4, 6}, {4, 8}, {4, 10}, {4, 11}, {4, 5, 6}, {4, 6, 8}, {4, 5, 6, 10}, **{4, 6, 8, 10},** {4, 5, 6, 8, 10}
	Batch size	32, **64**, 128, 256

Architecture	Number of layers	1, 2, 3, **4**, 5
	Number of nodes for layers	4, 16, **32**, **64**, **128**, 256, **512**, 1024 (Refer to Fig 6 for details)
	Regularization	Dropout: **0**, 0.1, 0.2, 0.5
	Activation function for hidden layers	tanh, **ReLU**
	Activation function for output layer	**Softmax**, Sigmoid

436   The final architecture of Terminitor is depicted in Fig 5 and the selected optimal

437   hyperparameters are in bold font in Table 3. The first step of Terminitor is to concatenate all k-

438   mer representations of the raw DNA sequence. Each k-mer in the one-hot encoded raw sequence

439   is represented as a vector of length l, where

$$l = \sum_{k \in \{4,6,8,10\}} 4^k \qquad (1)$$

Fig 5. Architecture of Terminitor. The information flows from bottom up. During training stage,
reference transcripts are aligned back to the reference genome, and flanking sequence on both
side of the poly(A) CS is extracted (grey thick sequence). The sequence is k-merized and four k
values are used. Then all k-mer representations are concatenated and each k-mer is one-hot
encoded (each square represents one k-mer). The input sequences are fed into an embedding
layer, followed by three fully connected layers, and then the probability of belonging to one of
the three classes is calculated through a Softmax function.

Then an embedding layer with 128 nodes is used to connect the input layer and hidden layers.

The next four layers are all fully connected, and the activation function between each adjacent

layer is the rectified linear unit (ReLU) function. Since dropout regularization did not achieve

better performance, it was not performed in the final model.

Experimental data

The raw RNA-seq reads for the two MicroArray Quality Control project reference human samples,

HBR and UHR, were downloaded from Illumina BaseSpace, and each sample has two replicates

(https://basespace.illumina.com/projects/3777775/samples) [41]. RNA-seq libraries of the four

samples were prepared with Illumina TruSeq Stranded kits using poly(A) selection, and

sequenced as 75bp paired-end reads. The Illumina and PacBio reads for NA12878 were obtained

from an earlier study under accession number SRR1153470 and SRR1163655, respectively [42].

The Illumina reads are from a poly(A) selected library sequenced with 75 bp stranded paired-end

reads. The PacBio library was prepared from the same batch of poly(A) selected RNA and

sequenced with PacBio CCS method. The filtered PolyA-Seq sites were downloaded from the NCBI

Gene Expression Omnibus (GEO) under study GSE30198. We combined sites detected by the two

HBR replicates (GSM747473 and GSM GSM747474), and sites detected by the two UHR replicates

(GSM747475 and GSM747476) together respectively for benchmarking analysis.

Prediction pipeline

We also provide a poly(A) CS prediction pipeline based on Terminitor. When using Illumina short

reads, the pipeline starts by assembling RNA-seq data using RNA-Bloom [34]. RNA-Boom is run

with the option `-stratum 01`, which allows extension of all fragments regardless of its

coverage, and the option `--polya`, which prioritizes the assembly of transcripts with poly(A)

tails. The false positive rate (FPR) of Bloom filters in the program is set to 0.005. Then, all

assembled transcripts are aligned to the reference genome hg38 and compared to Ensembl

annotation release 94 to select sequences with untemplated As at their 3' ends, or sequences

that end in the 3' UTR of annotated transcripts. Similar to the structure of sequences in the

training dataset, selected sequences are used to construct test sequences, each composed of

three parts: a fixed length (100 nt) of upstream sequence extracted from the assembled

transcript, a potential cleavage site, and a fixed length (100 nt) of downstream genomic sequence

extracted from the reference. Finally, these test sequences are fed into the trained Terminitor

model for classification.

Evaluation of prediction pipeline

Poly(A) CS are often observed as a group of neighboring sites rather than a precise genomic

location [7]. To accommodate, predicted poly(A) CS within 30 nt of each other are clustered, and

the one with the highest probability score is chosen. Ensembl annotated poly(A) CS are also

clustered in the same way, and the one located in the median position is chosen as the

representative. Then, the predicted list is compared with the annotated list to compute hits and

misses. In our evaluation system, a true positive poly(A) CS is a predicted one that lies within ±

30 nt of an annotated site; a false positive site is a predicted poly(A) CS that does not lie within ±

30 nt of any annotated ones; false negative means an annotated site does not have any predicted

site within ± 30 nt. For this analysis, true negative (no real or predicted poly(A) CS in a certain

location) is not informative for experimental data. Using these definitions, we report sensitivity

and precision as performance measures for all experimental data tests. Note that in the training

data, true negative is informative, and we also report accuracy for our cross validation results.

Tool comparison

We applied the proposed prediction pipeline on experimental data and compared its

performance with the performance of the state-of-the-art methods. All experiments were run on

Centos 6.7 system with 12 Intel Xeon E5-2650 CPUs and 84 GB memory.

KLEAT pipeline was chosen as a representative of read-evidence based approaches. The

auxiliary files KLEAT uses include: 1) RNA-seq assemblies from RNA-Bloom, 2) read to contig

alignment files generated by BWA-MEM 0.7.17-r1188 [43], and 3) contig to genome alignment

files generated by GMAP version 2017-01-14 [44]. Since KLEAT only works for the human genome

reference hg19, all predicted poly(A) CS were converted into hg38 genomic coordinates by UCSC

liftOver [45]. KLEAT outputs all possible poly(A) CS and their supporting evidence, such as the

length of poly(A) tail in reconstructed transcripts, the number of reads containing poly(A) tail,

and the length of poly(A) tail of reads that can be mapped to a reconstructed transcript. We

applied filters to the raw predictions with different combinations of three evidence types and

computed the Pareto frontier on the sensitivity-precision plane.

Two recent deep learning models, DeepGSR and DeeReCT-PolyA, were also included in the

comparison. Like Terminitor, these two tools are NN models expecting fixed length sequences as

input. Starting from all candidate sequences processed from our prediction pipeline, we selected

only the ones containing PAS as these tools expects PAS in the input sequences. Then we adjusted

the sequence lengths as required by the two models (± 300 nt around the PAS for DeepGSR; ±

100 nt around the PAS for DeeReCT-PolyA), and fed into these two models for classification. For

DeepGSR, we used two pre-trained models from its publication, one only on the AATAAA

hexamer, and the other on all 16 hexamers [29]. Similarly, the DeeReCT-PolyA package provides

two pre-trained models based on two human datasets, dragon and omni, both of which were

included in the comparison. Both datasets were generated by previous poly(A) prediction

researches [46,47]. Both DeepGSR and DeeReCT-PolyA only output a binary value instead of a

confidence score that can be tuned with different cut-offs, so their predictions contributed to

four data points in the comparison plot: two models for two tools.

Data access

Terminitor is implemented using Python 3.6 with Keras package. The software package is freely

available under GNU General Public Licence. The source code and manual are available at our

GitHub repository https://github.com/bcgsc/Terminitor. Previously published data used in this

work are described in the Methods section, and are available from several public repositories.

The human and mouse reference datasets colated in this study and trained models are deposited

in public ftp site http://www.bcgsc.ca/downloads/supplementary/Terminitor.

Reference

1.   Edmonds M, Vaughan MH, Nakazato H. Polyadenylic acid sequences in the heterogeneous
nuclear RNA and rapidly-labeled polyribosomal RNA of HeLa cells: possible evidence for a
precursor relationship. Proc Natl Acad Sci U S A. 1971;68: 1336–40. doi:10.1073/pnas.68.6.1336
2.   Neve J, Patel R, Wang Z, Louey A, Furger AF. Cleavage and polyadenylation: Ending the message
expands gene regulation. RNA Biol. 2017;14: 865–890.
3.   Barrett LW, Fletcher S, Wilton SD. Regulation of eukaryotic gene expression by the untranslated
gene regions and other non-coding elements. Cellular and Molecular Life Sciences. 2012. pp.
3613–3634. doi:10.1007/s00018-012-0990-9
4.   Shi Y, Chan S, Martinez-Santibañez G. An up-close look at the pre-mRNA 3'-end processing
complex. RNA Biol. 2009;6: 522–525. doi:10.4161/rna.6.5.9554
5.   Zhang H, Lee JY, Tian B. Biased alternative polyadenylation in human tissues. Genome Biol.
2005;6: R100. doi:10.1186/gb-2005-6-12-r100
6.   Tian B, Graber JH. Signals for pre-mRNA cleavage and polyadenylation. Wiley Interdisciplinary
Reviews: RNA. 2012. pp. 385–396. doi:10.1002/wrna.116
7.   Tian B, Hu J, Zhang H, Lutz CS. A large-scale analysis of mRNA polyadenylation of human and
mouse genes. Nucleic Acids Res. 2005;33: 201–212. doi:10.1093/nar/gki158
8.   Lianoglou S, Garg V, Yang JL, Leslie CS, Mayr C. Ubiquitously transcribed genes use alternative
polyadenylation to achieve tissue-specific expression. Genes Dev. 2013;27: 2380–2396.
doi:10.1101/gad.229328.113
9.   Lembo A, Di Cunto F, Provero P. Shortening of 3'UTRs correlates with poor prognosis in breast
and lung cancer. PLoS One. 2012;7. doi:10.1371/journal.pone.0031129
10.   Li L, Wang D, Xue M, Mi X, Liang Y, Wang P. 3'UTR shortening identifies high-risk cancers with
targeted dysregulation of the ceRNA network. Sci Rep. 2015;4: 5406. doi:10.1038/srep05406
11.   Xue Z, Warren RL, Gibb EA, MacMillan D, Wong J, Chiu R, et al. Recurrent tumor-specific
regulation of alternative polyadenylation of cancer-related genes. BMC Genomics. 2018;19.
doi:10.1186/s12864-018-4903-7

12.   Aken BL, Ayling S, Barrell D, Clarke L, Curwen V, Fairley S, et al. The Ensembl gene annotation
553   system. Database. 2016;2016: baw093. doi:10.1093/database/baw093
554   13.   Wang R, Nambiar R, Zheng D, Tian B. PolyA-DB 3 catalogs cleavage and polyadenylation sites
555   identified by deep sequencing in multiple genomes. Nucleic Acids Res. 2018;46: D315–D319.
556   doi:10.1093/nar/gkx1000
557   14.   Liu D, Brockman JM, Dass B, Hutchins LN, Singh P, McCarrey JR, et al. Systematic variation in
558   mRNA 3'-processing signals during mouse spermatogenesis. Nucleic Acids Res. 2007;35: 234–246.
559   doi:10.1093/nar/gkl919
560   15.   Mayr C. Evolution and Biological Roles of Alternative 3'UTRs. Trends in Cell Biology. 2016. pp.
561   227–237. doi:10.1016/j.tcb.2015.10.012
562   16.   Shepard PJ, Choi E-A, Lu J, Flanagan LA, Hertel KJ, Shi Y. Complex and dynamic landscape of RNA
563   polyadenylation revealed by PAS-Seq. RNA. 2011;17: 761–772. doi:10.1261/rna.2581711
564   17.   Harrison PF, Powell DR, Clancy JL, Preiss T, Boag PR, Traven ANA, et al. PAT-seq : a method to
565   study the integration of 3' -UTR dynamics with gene expression in the eukaryotic transcriptome.
566   Rna. 2015;21: 1502–1510. doi:10.1261/rna.048355.114.
567   18.   Chang H, Lim J, Ha M, Kim VN. TAIL-seq: Genome-wide determination of poly(A) tail length and 3'
568   end modifications. Mol Cell. 2014;53: 1044–1052. doi:10.1016/j.molcel.2014.02.007
569   19.   Derti A, Garrett-Engele P, MacIsaac KD, Stevens RC, Sriram S, Chen R, et al. A quantitative atlas of
570   polyadenylation in five mammals. Genome Res. 2012;22: 1173–1183. doi:10.1101/gr.132563.111
571   20.   Müller S, Rycak L, Afonso-Grunz F, Winter P, Zawada AM, Damrath E, et al. APADB: a database for
572   alternative polyadenylation and microRNA regulation events. Database (Oxford). 2014;2014.
573   doi:10.1093/database/bau076
574   21.   You L, Wu J, Feng Y, Fu Y, Guo Y, Long L, et al. APASdb: A database describing alternative poly(A)
575   sites and selection of heterogeneous cleavage sites downstream of poly(A) signals. Nucleic Acids
576   Res. 2015;43: D59–D67. doi:10.1093/nar/gku1076
577   22.   Gruber AJ, Schmidt R, Gruber AR, Martin G, Ghosh S, Belmadani M, et al. A comprehensive
578   analysis of 3' end sequencing data sets reveals novel polyadenylation signals and the repressive
579   role of heterogeneous ribonucleoprotein C on cleavage and polyadenylation. Genome Res.
580   2016;26: 1145–1159. doi:10.1101/gr.202432.115
581   23.   Birol I, Raymond A, Chiu R, Nip KMi, Jackman SD, Kreitzman M, et al. Kleat: Cleavage Site Analysis
582   of Transcriptomes. Biocomput 2015. 2014; 347–358. doi:10.1142/9789814644730_0034
583   24.   Bonfert T, Friedel CC. Prediction of poly(A) sites by poly(A) read mapping. PLoS One. 2017;12.
584   doi:10.1371/journal.pone.0170914
585   25.   Xia Z, Donehower LA, Cooper TA, Neilson JR, Wheeler DA, Wagner EJ, et al. Dynamic analyses of
586   alternative polyadenylation from RNA-seq reveal a 3'-UTR landscape across seven tumour types.
587   Nat Commun. 2014;5: 5274. doi:10.1038/ncomms6274
588   26.   Ye C, Long Y, Ji G, Li QQ, Wu X. APAtrap: Identification and quantification of alternative
589   polyadenylation sites from RNA-seq data. Bioinformatics. 2018;34: 1841–1849.
590   doi:10.1093/bioinformatics/bty029
591   27.   Ha KCH, Blencowe BJ, Morris Q. QAPA: A new method for the systematic analysis of alternative
592   polyadenylation from RNA-seq data. Genome Biol. 2018;19. doi:10.1186/s13059-018-1414-4
593   28.   Xia Z, Li Y, Zhang B, Li Z, Hu Y, Chen W, et al. DeeReCT-PolyA: A robust and generic deep learning
594   method for PAS identification. Bioinformatics. 2019;35: 2371–2379.
595   doi:10.1093/bioinformatics/bty991
596   29.   Kalkatawi M, Magana-Mora A, Jankovic B, Bajic VB. DeepGSR: an optimized deep-learning
597   structure for the recognition of genomic signals and regions. Bioinformatics. 2018.
598   doi:10.1093/bioinformatics/bty752
599   30.   Arefeen A, Xiao X, Jiang T. DeepPASTA: deep neural network based polyadenylation site analysis.

600   Bioinformatics. 2019. doi:10.1093/bioinformatics/btz283

601   31.   Min S, Lee B, Yoon S. Deep learning in bioinformatics. Briefings in bioinformatics. 2017. pp. 851–
602   869. doi:10.1093/bib/bbw068

603   32.   Venkataraman K, Brown KM, Gilmartin GM. Analysis of a noncanonical poly(A) site reveals a
604   tripartite mechanism for vertebrate poly(A) site recognition. Genes Dev. 2005;19: 1315–1327.
605   doi:10.1101/gad.1298605

606   33.   Nunes NM, Li W, Tian B, Furger A. A functional human Poly(A) site requires only a potent DSE and
607   an A-rich upstream sequence. EMBO J. 2010;29: 1523–1536. doi:10.1038/emboj.2010.42

608   34.   Nip KM, Chiu R, Yang C, Chu J, Mohamadi H, Warren RL, et al. RNA-Bloom provides lightweight
609   reference-free transcriptome assembly for single cells. bioRxiv. 2019; 701607.
610   doi:10.1101/701607

611   35.   Smigielski EM. dbSNP: a database of single nucleotide polymorphisms. Nucleic Acids Res.
612   2000;28: 352–355. doi:10.1093/nar/28.1.352

613   36.   Thorvaldsdóttir H, Robinson JT, Mesirov JP. Integrative Genomics Viewer (IGV): High-
614   performance genomics data visualization and exploration. Brief Bioinform. 2013;14: 178–192.
615   doi:10.1093/bib/bbs017

616   37.   Yang L, Duff MO, Graveley BR, Carmichael GG, Chen LL. Genomewide characterization of non-
617   polyadenylated RNAs. Genome Biol. 2011;12. doi:10.1186/gb-2011-12-2-r16

618   38.   Chollet F. Keras: Deep Learning for humans. In: Github [Internet]. 2015. Available:
619   https://github.com/keras-team/keras

620   39.   Abadi M, Barham P, Chen J, Chen Z, Davis A, Dean J, et al. TensorFlow : A System for Large-Scale
621   Machine Learning This paper is included in the Proceedings of the TensorFlow : A system for
622   large-scale machine learning. Proc 12th USENIX Conf Oper Syst Des Implement. 2016; 272–283.

623   40.   Glorot X, Statistics YBBT-P of the TIC on AI and. Understanding the difficulty of training deep
624   feedforward neural networks. Teh YW, Titterington M, editors. PMLR   ; 2010. pp. 249–256.
625   Available: http://proceedings.mlr.press/v9/glorot10a/glorot10a.pdf

626   41.   Shi L, Reid LH, Jones WD, Shippy R, Warrington JA, Baker SC, et al. The MicroArray Quality Control
627   (MAQC) project shows inter- and intraplatform reproducibility of gene expression
628   measurements. Nat Biotechnol. 2006;24: 1151–1161. doi:10.1038/nbt1239

629   42.   Tilgner H, Grubert F, Sharon D, Snyder MP. Defining a personal, allele-specific, and single-
630   molecule long-read transcriptome. Proc Natl Acad Sci. 2014;111: 9869–9874.
631   doi:10.1073/pnas.1400447111

632   43.   Li H. Aligning sequence reads, clone sequences and assembly contigs with BWA-MEM. arXiv Prepr
633   arXiv. 2013;00: 3. doi:10.1186/s13756-018-0352-y

634   44.   Wu TD, Watanabe CK. GMAP: A genomic mapping and alignment program for mRNA and EST
635   sequences. Bioinformatics. 2005;21: 1859–1875. doi:10.1093/bioinformatics/bti310

636   45.   Hinrichs AS, Karolchik D, Baertsch R, Barber GP, Bejerano G, Clawson H, et al. The UCSC Genome
637   Browser Database: update 2006. Nucleic Acids Res. 2006;34: D590–D598.
638   doi:10.1093/nar/gkj144

639   46.   Kalkatawi M, Rangkuti F, Schramm M, Jankovic BR, Kamau A, Chowdhary R, et al. Dragon polya
640   spotter: Predictor of poly(A) motifs within human genomic DNA sequences. Bioinformatics.
641   2012;28: 127–129. doi:10.1093/bioinformatics/btr602

642   47.   Magana-Mora A, Kalkatawi M, Bajic VB. Omni-Polya: A method and tool for accurate recognition
643   of poly(A) signals in human genomic DNA. BMC Genomics. 2017;18. doi:10.1186/s12864-017-
644   4033-7

647 **Supporting information**

648 **S1 File. Supplementary material.** This file contains all supplementary figures S1-10 Fig.