Visual search mimics configural processing in associative learning

Omar D. Perez[1, 3], Sanjay Narasiwodeyar[2], & Fabian A. Soto[2]

[1] Division of the Humanities and Social Sciences, California Institute of Technology, Pasadena, California

[2] Department of Psychology, Florida International University, Florida, USA

[3] Nuffield College CESS-Santiago, Facultad de Administracion y Economia, Universidad de Santiago, Santiago, Chile

Author Note

Correspondence concerning this article should be addressed to Omar D. Perez, 1200 E. California Blvd., Pasadena, California, CA91125. E-mail: odperez@caltech.edu

11   Abstract

Theories of generalization distinguish between elemental and configural stimulus processing,

depending on whether stimuli in a compound are processed independently or as distinct

entities. Evidence for elemental processing comes from findings of summation in animals,

where a compound of two stimuli that independently predict an outcome is deemed to be

more predictive of the outcome than each stimulus alone. Configural processing, on the other

hand, is supported by experiments that fail to find this effect when the compound is

comprised of similar stimuli. In humans, by contrast, summation seems to be robust and

independent of similarity. We show how these results are best explained by an alternative

view in which generalization comes about from a visual search process in which subjects

process the most predictive or salient stimulus in a compound. We offer empirical support

for this theory in three human experiments on causal learning and formalize a new elemental

visual search model based on reinforcement learning principles which can capture the present

and previous data on generalization, bridging two different research areas in psychology into

a unitary framework.

Keywords: generalization, Rescorla-Wagner, configural, summation, elemental, visual

search

Word count: 11,102

₂₉   Visual search mimics configural processing in associative learning

₃₀   **Introduction**

₃₁   In the psychology of learning and decision-making one of the most important and

₃₂ studied topics is the process of generalization. From calory intake to escaping from predators,

₃₃ generalizaton is critical for organisms, as it alows them to take previous instances of similar

₃₄ situations to inform their future behavior and increase their chances of survival and

₃₅ reproduction (Soto & Wasserman, 2010). Understanding the specific mechanisms that give

₃₆ rise to different generalization strategies is therefore fundamental to understanding behavior

₃₇ in general.

₃₈   A particular type of generalization problem that all animals face in natural

₃₉ environments is that of *compound generalization*, which requires them to generalize

₄₀ knowledge acquired about certain combinations of stimuli to novel combinations of stimuli,

₄₁ which may include familiar stimuli and completely novel stimuli. In this regard, one

₄₂ paradigm that has been widely used in the animal literature due to its capacity to

₄₃ distinguish between different generalization strategies is the summation procedure. In this

₄₄ procedure, two cues, say A and B, are separately paired with an outcome during a first stage

₄₅ of training and responding to a compound of the two stimuli, AB, is assessed in a final

₄₆ testing phase. A summation effect is obtained if subjects respond more to AB than to each

₄₇ of A or B alone. An analogous effect can be found in human causal learning when a

₄₈ compound is deemed to be more predictive of an outcome than each of A or B alone (Aydin

₄₉ & Pearce, 1997; Kehoe, Horne, Horne, & Macrae, 1994; Pérez, San Martín, & Soto, 2018;

₅₀ Soto, Vogel, Castillo, & Wagner, 2009; Thein, Westbrook, & Harris, 2008).

₅₁   To illustrate this procedure, imagine that a foraging animal finds and consumes a red

₅₂ apple, call it R, and gets an allergic reaction afterwards. Now imagine that on a different

₅₃ occasion the animal gets the allergic reaction by eating a green apple, G. The question at

₅₄ issue is the allergy level that the animal will predict if consuming a green and a red apple at

the same time, the RG compound. Will the animal predict twice as much allergy when

eating the two types of apple together? What would the animal predict if the apples were

both red (RR compound) or both green (GG compound)? What if these were different types

of food altogether, with very different sensory properties, such as an apple and a nut?

In the learning literature, the summation effect is anticipated by a class of Pavlovian

conditioning models called *elemental* (Rescorla & Wagner, 1972). These models assume that

subjects represent A and B independently, and that the presence of the compound AB will

simply make subjects sum their individual predictions, anticipating twice as much allergy

after consuming two apples than after eating one apple alone. This additive generalization

strategy makes efficient use of the available evidence under the assumption that the two cues

are independent causes of the sickness (Pérez et al., 2018).

A challenge to this elemental view comes from a different class of models called

configural (Pearce, 1987, 1994), which assume that subjects process and associate whole

configurations with the outcomes that follow. Under a configural view, the total responding

to a compound AB depends on the similarity between the training configurations A and B,

and the testing configuration AB. In the basic formulation of configural theory proposed by

Pearce, the prediction of outcome from AB is the average of the prediction from each of its

components A and B. A foraging animal should thus predict the same level of sickness after

eating the two apples together as after eating each one of them separately (1987, 1994). In

this case, summation should not be observed.

Empirically, the evidence on summation has been mixed, although one general

observation is that summation is usually obtained when A and B come from different sensory

modalities (e.g., auditory and visual) (Kehoe et al., 1994; Thein et al., 2008) but not with

stimuli from the same modality (e.g., two visual stimuli) (Aydin & Pearce, 1995, 1997). In

humans, apart from modality, spatial and temporal contiguity can also impact on the level of

summation observed (Glautier, 2002; Glautier, Redhead, Thorwart, & Lachnit, 2010). Given

this evidence, contemporary associative models of learning assume that the similarity

between the components A and B plays a key role in whether the level of summation

observed is closer to the one predicted by elemental or configural theories (Harris, 2006;

McLaren & Mackintosh, 2002; Melchers, Shanks, & Lachnit, 2008; Pérez et al., 2018; Soto et

al., 2014a; Thorwart, Livesey, & Harris, 2012; Wagner, 2008). A similar prediction is made

by a recent normative model proposed by Soto, Gershman and Niv (2014a; Soto, Quintana,

Pérez-Acosta, Ponce, & Vogel, 2015), which predicts that not only higher perceptual

similarity, but also higher spatial or temporal contiguity should produce more configural

processing and reduce the summation effect (see also Thorwart et al., (2012)).

In a recent series of studies, we tested these predictions and found no evidence for

similarity affecting summation in humans (Pérez et al., 2018). Instead, we found that

subjects consistently summed the predictions of A and B when presented with the compound

AB, disregarding similarity and spatial contiguity in making their predictions. We attributed

these results to a causal inference process whereby participants represent independent stimuli

as individual entities (Cheng, 1997; Cheng & Buehner, 2012; Mitchell, De Houwer, &

Lovibond, 2009). Under these conditions, as long as participants are able to distinguish that

the two previously trained cues A and B are present on the screen during the test with the

compound AB, they will always encode them as independent causes and sum their

predictions.

The fact that similarity plays a role in animal learning experiments but not in humans

seem to suggest that the principles of similarity-based generalization may be different across

species. However, our current understanding is that the principles of generalization share

much in common across species (Shepard, 1987), probably because generalization poses a

similar problem to all species that are capable of learning (Soto & Wasserman, 2010). The

answer, perhaps, lies in searching for a different principle to unify the animal and human

literatures.

Studies using animals offer a potential hypothesis for a unifying principle. There,

evidence for configural processing, including the absence of a summation effect, has been

obtained from auto-shaping experiments in pigeons using visual stimuli (Aydin & Pearce,

1995, 1997). In this type of procedure, hungry pigeons receive pairings of visual stimuli and

food, which results in the animals approaching the stimuli and pecking at them. Two notable

features of autoshaping experiments may explain why summation is not obtained. First, the

proximity of the pigeon to the screen in which stimuli are displayed may limit its ability to

sample the large and complex stimuli usually displayed in compound generalization

experiments. In addition, just before the final ballistic movement that produces a peck, the

peck's target is centered on the area dorsalis of the pigeon's retina (Goodale, 1983;

Martinoya, Le Houezec, & Bloch, 1984), which is considered a "second fovea" due to its high

density of cells. That is, pigeons specifically sample visual information from the pecked area,

and they tend to peck on a circumscribed area of the screen displaying visual features

predictive of reward (Dittrich, Rose, Buschmann, Bourdonnais, & Güntürkün, 2010; Soto et

al., 2012; Wasserman & Anderson, 1974).

These two factors suggest that pigeons may process only those visual features that they

happened to be pecking during a particular trial rather than processing whole configurations.

For example, in a summation test with the compound AB, the pigeon may be sampling only

part of one stimulus, and predict the outcome level associated with that specific stimulus

part. Under these circumstances, a reduction in the summation effect is explained not as a

consequence of configural processing prompted by the high similarity of unimodal stimuli,

but rather from *limited and inefficient sampling* of the stimulus compound.

This interpretation makes the auto-shaping procedure seem very similar to an overt

visual search task (Wolfe, 2018) in which the pigeon samples information from the display by

pecking and foveating a circumscribed area until it encounters an area previously associated

with reward, or *target.* At this point, the pigeon might continue to sample information from

the target while relevant information from the rest of the display is never sampled. In the search literature this effect is known as *satisfaction of search* (Berbaum et al., 1990), and it leads to a sub-optimal sampling of useful information in the stimulus, missing any other targets that may be present. This type of visual search, known as *serial*, is considered to be inefficient (Treisman, 1988; Treisman & Gelade, 1980; Wolfe, 2018), taking longer as the display size increases and being prone to satisfaction of search. By contrast, people in human causal learning experiments see the stimuli from a distance and can process all the cues at the same time. When there is only a few of such cues that are easily distinguishable, they can be detected in parallel (Treisman, 1985, 1988), which is an efficient sampling strategy (Wolfe, 2018). In that case, all the relevant cues are sampled from the stimulus array (Pérez et al., 2018; Soto et al., 2009). The lack of an effect of similarity in our previous studies could have been be due to the fact that some features of our stimuli (e.g., fixed spatial position of cues, lack of non-target cues) produced parallel processing and efficient sampling of information from the compound in a visual search process. When all the stimuli on the screen are processed, participants simply count the number of stimuli on the screen and sum the predictions learned during the training stage.

One further aspect of visual search that reinforces this hypothesis is that similarity between different stimuli on the display is thought to be one of the critical factors determining if search is parallel or serial (Duncan & Humphreys, 1989), which is consistent wit the argument of similarity affecting configural/elemental processing in the learning literature. In particular, increasing the similarity between the target and non-target cues makes search appear more serial, and thus less summation should be observed. By contrast, more summation should obtain if similarity is decreased so that search appears more parallel.

Our claim in this paper is that tasks and stimuli that promote a serial search strategy will produce behavioral results that mimic configural processing in key generalization designs. Using the summation design, we present empirical evidence in line with this hypothesis from

159 three experiments in humans. To further support our view, we present a computational

160 reinforcement learning model which can capture both the present and previous results taken

161 as evidence for a configural processing approach. This work leads to a more parsimonious

162 explanation of the pattern of generalization results obtained across species, and the

163 unification of two seemingly unrelated areas of research in experimental psychology.

Figure 1. **Stimuli used in the experiments reported in this paper.** Each stimulus was formed by a central point which extended in three different components. Target cues A and B were accompanied by two other non-target cues, X and Y. The compound AB was accompanied by one of the non-target stimuli X or Y. All stimuli were presented in three different planar orientations, so that each component was equally likely to appear in one of three positions.

₁₆₄ **Experiment 1**

₁₆₅ In the three experiments reported in this paper, participants were asked to play the

₁₆₆ role of an allergist whose goal was to judge the extent to which various drugs, represented by

₁₆₇ different shapes, caused allergy in a fictitious patient (see Vogel, Glynn, & Wagner, 2015;

₁₆₈ Pérez et al., 2018; Soto et al., 2009). We used a summation design with two stages. In each

₁₆₉ trial of the training stage, participants were presented with different cues and asked to

₁₇₀ predict the level of allergy produced by each cue. During the test stage, they were asked to

₁₇₁ estimate the level of allergy produced by each of the cues seen during training but, in

₁₇₂ addition, they sometimes had to estimate the allergy produced by the compound of A and B.

₁₇₃ In Experiment 1, our hypothesis was that the strong and robust summation found in

₁₇₄ previous human studies (Pérez et al., 2018; Soto et al., 2009) resulted from the use of cues

₁₇₅ that could be easily parsed and sampled by participants - thanks to properties like their

₁₇₆ reliable spatial position and the absence of non-target cues. Indeed, when the cues are easily

₁₇₇ distinguishable they can be detected in parallel (Treisman, 1985, 1988). Summation follows

₁₇₈ from a simple additive rule for all the stimuli processed by the participant. By contrast, a

₁₇₉ task in which the target cues must be searched sequentially in the stimulus configuration is

₁₈₀ more similar to the situation of pigeon auto-shaping, and should lead to less summation if

₁₈₁ the similarity between target (A or B) and non-target (X and Y) cues is increased. To test

₁₈₂ these predictions, in all trials we presented participants with a configuration of three cues, so

₁₈₃ that each trial included one target cue (A, B, C or D) and two non-target cues (X and Y).

₁₈₄ As shown in Figure 1, all stimuli consisted of the three cues joined at a central point. In

₁₈₅ training trials, one of the target cues (A or B) was presented together with the non-target

₁₈₆ cues X and Y. During the test stage, in some trials both A and B were presented in the same

₁₈₇ configuration with one of the non-target cues (either X or Y, counterbalanced). Two

₁₈₈ additional target cues, C and D, were associated with no allergy. These cues were included

₁₈₉ to check which participants correctly learned the contingencies between the cues and their

Figure 2. **Trial design for all experiments.** In each training trial, participants observed one target cue (A,B, C or D) and two non-target cues (X and Y) in the same configuration (AXY, BXY, CXY, DXY) and were asked to rate the level of allergy they thought would be produced by it, on a scale from 0 to 35. After an inter-stimulus interval, feedback was presented ("Correct!" if the prediction was correct, "Incorrect!" if the prediction was incorrect), followed by the message "Allergic reaction: 10 points in the allergy scale" for cues that predicted allergy or "No allergic reaction: 0 points in the allergy scale" for cues that did not predicted allergy. During the test phase, the cues were presented in the same way as in training, but now the compound AB, together with one non-target cue (X or Y) was presented in some trials (i.e., ABX, ABY). The predictions were assessed in the same way as in training but no feedback was given during the testing stage.

respective outcomes.

In the studies reported in Perez et al. (2018), the stimuli always had different spatial

positions, which may have facilitated parsing them into independent cues. For this reason,

we also rotated the stimuli across trials, so that each cue was presented in each of the three

possible spatial positions within the configuration. The same number of elements was

therefore always presented and their spatial position was irrelevant.

Our critical manipulation was varying similarity between target and non-target cues. If

the similarity between the target cues (A or B) and the non-target cues (X and Y) was

increased, we expected this to prompt a serial search process, thereby reducing summation

(Duncan & Humphreys, 1989). By contrast, if the target and non-target cues are disimilar,

we expected this to prompt parallel search, thereby strengthening summation.

To test this hypothesis, we manipulated the similarity of the three cues within a

configuration in three different groups. Group *intra* included cues that varied only in shape

(i.e., intra-dimensional differences, see Figure 1). We expected very inefficient search with

stimuli composed of the same features (points and lines) and differing only in spatial

arrangement (Wolfe, 2018), and consequently low summation. For the two *extra* groups, cues

varied both in shape and in color (i.e., extra-dimensional differences). In group *extra1*, A and

B had different color (black vs. gray), but the colors were shared with the non-target cues X

and Y (one of them black and the other gray, see top-left stimulus in Figure 1). This means

that although A and B can be easily distinguished, they are not easily distinguishable from

the non-target cues. This high similarity between target and non-target cues should produce

inefficient search. By contrast, similarity between target cues is less relevant (Duncan &

Humphreys, 1989). Thus, from a visual search perspective, we would expect inefficient

sampling and low to no summation effect in group *extra1*. Finally, in group *extra2*, A and B

had different color (black vs. gray), and they also differed in color with the non-target cues X

and Y (light gray with black contours, see Figure 1). In this case, we anticipated efficient

²¹⁶ sampling of all cues and a stronger summation effect.

Figure 3. **Design and results of Experiment 1**. (a) Letters denote cues, represented by different chemical shapes that can cause different levels of allergy to a fictitious patient. Each cue is represented by a capital letter. Cues A, B, C and D were the target cues (shown in bold), whereas X and Y were non-target cues. In Experiment 1, all cues were followed (+) or not followed (-) by the same level of allergy (10 points of allergy out of a total of 35). (b) Average ratings given to each cue during the test. Individual ratings for each test trial are shown in dots).

²¹⁷   The comparison between groups *extra1* and *extra2* is critical to evaluate the

²¹⁸ mechanism underlying the potential effect of similarity on summation. Contemporary

²¹⁹ learning models (Harris, 2006; McLaren & Mackintosh, 2002; Soto et al., 2014b; Thorwart et

²²⁰ al., 2012; Wagner, 2008) assume that the key variable controlling summation is the similarity

²²¹ between the target cues A and B. In group *extra1*, these two cues were as dissimilar as in

²²² group *extra2*. If the effect of cue similarity acted through the mechanisms proposed by these

²²³ learning models, then we should observe a similar summation effect in groups *extra1* and

²²⁴ *extra2*. If, by contrast, the effect of cue similarity acts through a visual search mechanism,

²²⁵ the similarity between the targets A and B and the non-targets X and Y should also be

important (Duncan & Humphreys, 1989). More specifically, during test with the compounds ABX and ABY in group *extra1*, one of the target cues shares color with the non-target cue X or Y, which would make the other target cue "pop-out" from the compound (Treisman, 1985, 1988). Once the "popped-out" cue is sampled, the search process ends and the participant should report the value of this sampled cue. In this case, we should observe no summation effect in both groups *extra1* and *intra*.

Method

Participants

86 undergraduate students from Florida International University participated in Experiment 1. Participants did not have previous experience with the experimental procedure and were tested simultaneously and in the same room. The Institutional Review Board of Florida International University approved all the studies in this paper (IRB-15-0460). Written informed consent was obtained from all participants.

Participants were randomly assigned to one of three groups: *intra* ($n_{intra} = 27$), *extra1* ($n_{extra1} = 28$) and *extra2* ($n_{extra2} = 31$). In all of the studies in this paper, we set our exclusion criteria before data collection. We followed the same exclusion criteria of our previous study on summation (Pérez et al., 2018): participants that did not score on average 10 (+/-3) points of allergy to cues that predicted allergy and 0 (+3) points of allergy to cues that did not predict allergy, were left out from the analysis. The final number of participants in Experiment 1 was $n_{intra} = 18$, $n_{extra1} = 13$, $n_{extra2} = 27$.

Materials

Participants were tested in Windows (c) computers running Psychopy (Peirce, 2007) 1.75. Responses were recorded from standard PC keyboards.

Procedure

Participants were presented with a task in which they were asked to play the role of an allergist that had to predict the levels of allergy caused by different drugs in a hypothetical patient, Mr. X (Pérez et al., 2018; Soto et al., 2009). During training, a configuration comprising one of the target and the two non-target cues was presented at the center of the screen (see Figure 2), and participants were required to give an assessment of the level of allergy that each drug would cause in a fictitious patient, Mr. X, on a scale of 0 to 35. After clicking with the mouse on the rating scale, participants had to confirm their predictions by clicking on a button below the rating scale. There were 120 trials during training. The presentation of the stimuli was randomized. Trials were self-paced.

During the training stage, and after entering their prediction and confirming it, participants were presented with a feedback screen with the phrase "Allergic reaction: 10 points in the allergy scale" for cues that predicted allergy or "No allergic reaction: 0 points in the allergy scale" for cues that did not predict allergy. This message was presented simultaneously with the message "Correct!" if participants' estimation was correct, or the message "Incorrect!" if the estimation was incorrect. A similar procedure was used for testing, with two key differences. First, participants were presented not only with the same stimuli seen during training (AXY, BXY, CXY, DXY), but also stimuli where A and B were part of the same configuration (ABX, ABY). Second, no feedback was provided during the test stage.

Groups differed in the similarity between cues in the display (see Figure 1). Each stimulus was created from three different cues that "branched out" from a central point. Among these branches, only one of them represented the target cue associated with either allergy or no allergy during training (A, B, C or D). The other two branches were non-target cues that could not predict the presence or absence of allergy (X and Y). During the test, the compound AB was comprised by two target branches together with an additional

non-target cue (ABX or ABY). In group *intra*, all these "branches" were of the same color

(black), but differed in shape. In group *extra1*, A and B differed in color (grey and black),

but they shared color with the non-target cues (X and Y, one grey and one black). In group

extra2, the target cues were the same as in group *extra1*, but now the non-target cues had a

distinctive color as well. In all groups, A and B, which predicted allergy, shared color with

cues C and D, which predicted no allergy. Thus, all participants, regardless of group, had to

attend to shape; color was irrelevant to solve the discrimination.

Results and discussion

Statistical analyses were performed using the R programming language (Version 3.4.3;

R Core Team, 2017) under RStudio (RStudio Team, 2015), using the packages *BayesFactor*

(Version 0.9.12.2; Morey & Rouder, 2015), *bootES* (Version 1.2; Gerlanc & Kirby, 2015),

dplyr (Version 0.7.4; Wickham, Francois, Henry, & Müller, 2017), *ggplot2* (Version 2.2.1;

Wickham, 2009), *ggpubr* (Version 0.1.6; Kassambara, 2017) and *lme4* (Version 1.1.15; Bates,

Mächler, Bolker, & Walker, 2015). For all the pre-planned comparisons we calculated a

Welsh *t*-test and included Cohen's D, along with a 95% confidence interval on this estimate,

as a measure of effect size. When reporting interactions between factors, we computed η^2

and a 90% confidence interval on this estimate. The reliability of the results was contrasted

against the usual criterion of $\alpha = .05$.

The results of Experiment 1 are shown in Figure 2B. To analyze these data, we ran a

2(group) x 3(cue) mixed ANOVA with group as between-subject and cue as within-subject

factors. We found a significant main effect of cue $(F(2, 110) = 16.54, p < .01)$ and group

$(F(2, 55) = 3.79, p = .03)$. More importantly, we found a significant difference in the

summation effect between the groups $(F(4, 110) = 4.00, p < .01, \eta^2 = .13, 90\% CI[.02, .20])$.

Consistent with a visual search approach, the significance of this interaction effect was due

to a difference in scores for the compound in groups *intra* and *extra2*

$(t(177.48) = 4.54, p < .001, D = 0.71, 95\% CI[0.06, 1.36])$.

The results of this experiment agree with our hypothesis that stimulus similarity

affects the summation effect via visual search strategies. First, unlike the results of our

previous studies (Pérez et al., 2018; Soto et al., 2009), we find for the first time that humans

can show little to no summation if the right conditions are in place. This was the case for

participants in group *intra*, which we hypothesize is due to inefficient visual search and

sub-optimal sampling of information from the display. Second, we found an effect of

similarity on the summation effect,as can be expected from the visual search literature

(Duncan & Humphreys, 1989). However, in contrast to contemporary learning models, the

main driver of this effect was the similarity between targets and non-targets rather than the

similarity between the two targets A and B (Harris, 2006; McLaren & Mackintosh, 2002;

Soto et al., 2014b; Thorwart et al., 2012; Wagner, 2008). This observation is also consistent

with a visual search strategy.

Experiment 2

We have hypothesized that the data of group *intra* from Experiment 1 can be

explained by participants deploying a visual search strategy similar to the strategy that we

assume pigeons may be deploying during auto-shaping experiments. That is, when presented

with the compound AB (ABX or ABY), subjects search for a "familiar" cue (either A or B)

and report the outcome associated with that cue only. To test this hypothesis further, in

Experiment 2 we used the same stimuli as group *intra* of Experiment 1, but assigned

different outcome values (i.e., different allergy magnitudes) to cues A (AXY) and B (BXY)

in different groups (see Figure 3a). Group *intra* was a replication of the same group from the

previous experiment in which the outcome associated to both A (AXY) and B (BXY) was 10

points of allergy. By contrast, group *intra2* involved two different outcome values: 10 points

of allergy for cue A (AXY) and 8 points of allergy for cue B (BXY). As in the previous

experiment, we expected participants to score the compound AB (ABX or ABY) in group

intra as producing 10 points of allergy, so that no summation should be observed in this

group. By contrast, to the extent that our stimulus manipulation prompts a serial search

strategy, participants in group *intra2* should score the compound AB (ABX or ABY) as

producing either 8 or 10 points of allergy, indicating that they have responded in accord with

the value of only one of the two single components. We also expected a null, or very weak

summation effect for group *intra2* under these conditions.

An additional reason to use this design is that, according to some learning models,

discrimination training with A (AXY) and B (BXY) having different outcome values should

lead to learning to differentiate these two highly-similar cues (Soto et al., 2014b). Since the

elements are perceived as dissimilar by virtue of being associated with different consequences,

agents should process them independently, predicting $8 + 10 = 18$ points of allergy to the

compound AB (ABX or ABY). In the associative learning literature, this effect is known as

acquired distinctiveness (for a review, see Honey, Close, & Lin (2010)). Therefore, the present

experiment allows us to compare the predictions of the traditional summation analysis

offered in associative learning models against those of the visual search analysis offered here.

Method

Participants

75 undergraduate students from Florida International University were randomly

assigned to one of two groups ($n_{intra} = 40, n_{intra2} = 35$) and were compensated with course

credit for their participation. The final number of participants per group was $n_{intra} = 40$,

$n_{intra2} = 33$.

Materials

Participants were tested as described for group *intra* of Experiment 1 using Windows

(c) computers running Psychopy (Peirce, 2007) 1.82.4.

Figure 4. **Design and results of Experiments 2 and 3**. (a) In Experiment 2, cues were followed by different levels of allergy, which are represented by the numbers shown next to each of them. The only difference between Experiments 2 and 3 was the assignment of allergy levels to cues A (AXY) and B (BXY) in group *intra2*: in Experiment 3 the outcomes of A (AXY) and B (BXY) were swapped so that they predicted 8 and 10 points of allergy, respectively. (b) Average ratings given to each cue during the test. Individual ratings for each test trial are shown in dots.

Procedure

The procedure was the same as described for group *intra* of Experiment 1, with only one exception: In group *intra2*, stimulus B (BXY) was associated with 8 points of allergy during training (see Figure 4).

Results and discussion

Figure 3b presents the results of Experiment 2. As expected for group *intra*, participants scores for A (AXY), B (BXY) and AB (ABX, ABY) did not differ $(F(2, 77) = 1.48, p = .24)$, replicating the absence of a summation effect found in Experiment 1. By contrast, we found a significant difference between these cues in group *intra2* $(F(4, 76) = 529.24, p < .0001)$. More importantly, group *intra2* scored the compound AB (ABX, ABY) as giving around 10 points of allergy, and this value did not differ from the value assigned to A (AXY) $(t(32) = -0.09, p = .92, D : -0.07\ 95\%CI[-0.38, 0.52], BF_{01} = 5.35)$.

Note that even though the average rating for AB (ABX, ABY) in group *intra2* was 10 points of allergy ($95\%\ CI\ [9.19, 10.48]$) the mode of scores was 8, and most participants in this group predicted that the compound would cause near 8 points of allergy—the level caused by B during training. In fact, 43% (15 participants) gave scores to AB (ABX, ABY) between 7 and 9 points of allergy, while only 17% (6 participants) scored AB (ABX, ABY) between 9 and 11 points. The rest of participants gave scores higher than 11 points to the compound, and only one participant showed full summation (18 points of allergy).

While these data are in agreement with our visual search hypothesis in that the score given to AB (ABX, ABY) was similar to that of cue B (BXY), they do not allow us to completely rule out configural processing, as a high proportion of participants scored the compound AB (ABX, ABY) between 8 and 10 points, which is the "average" effect that configural models of learning would predict (Pearce, 1987, 1994). Experiment 3 was designed

to rule out this explanation.

Experiment 3

The aim of Experiment 3 was to further test the visual search hypothesis using a design that would allow us to rule out configural processing as an explanation for lack of summation in group *intra*. Having observed that the weak summation obtained in Experiment 2 was due to the majority of participants choosing the value predicted by B to make their predictions for the compound AB (ABX, ABY), a question arises as to why this might have been the case. A natural possibility is that stimulus B was somehow more salient than stimulus A. If that was the case, then B would attract more attention during the test phase and should, as a consequence, be sampled more than the other cues forming the compound.

One way of testing for this possibility is keeping everything as in Experiment 2, but swapping the outcome values produced by the components A and B in group *intra2* so that A (AXY) now predicts 8 points of allergy while B (BXY) predicts 10 points of allergy. If stimulus B is truly more salient and attracting participants' attention during a search process, the majority of participants should give a higher rating to the compound AB (ABX, ABY) (closer to 10 rather than 8) in response to the compound presentation. This would suggest that the properties of B were somehow more salient that those of A. Configural processing, by contrast, predicts that responding should be the same as in the previous experiment; that is, an averaging effect is anticipated, with a value between 8 and 10 points for the compound AB (ABX, ABY).

Method

Participants

80 undergraduate students from Florida International University were randomly assigned to one of two groups ($n_{intra} = 42, n_{intra2} = 38$) and were tested under the same conditions of Experiment 2. The final number of participants per group was $n_{intra} = 22$,

400   $n_{intra2} = 32$.

Materials

402   Participants were tested in the same way as in Experiment 2.

Procedure

404   The procedure was the same as in Experiment 2. Only the outcomes of A and B were

405   interchanged in group *intra2*. The outcome assigned to A was 10 while a value of 8 was

406   assigned to B.

Results and discussion

The results of Experiment 3 are shown in Figure 3c. As expected, we found no

difference between the ratings to A (AXY), B (BXY) and AB (ABX, ABY) in group *intra*,

$(F(1, 42) = 1.41, p = .26)$, replicating the lack of summation in group *intra* of Experiment 2.

In group *intra2*, participants rated AB (ABX, ABY) as producing near 11 points of allergy

(mean=$11.69, 95\% CI[10.39, 12, 99]$), a value higher than the score to AB (ABX, ABY) in

Experiment 2 $(t(62.13) = 2.30, p = .03)$. However, the mode of scores was again the same as

the outcome predicted by B (BXY) (10 points of allergy). Moreover, the distribution of

scores showed that the majority of participants (15 participants, 66% of the sample) scored

the compound AB (ABX, ABY) as producing between 9 and 11 points of allergy while only

2 participants (5% of the sample) scored the compound as producing between 7 and 9 points

of allergy. This change in the distribution of scores from Experiment 2 to Experiment 3

confirms our hypothesis that the compound AB (ABX, ABY) is rated as equal to the

outcome predicted by B due to this cue being more salient. In contrast, configural processing

does not predict that the mode of scores to AB (ABX, ABY) tracks the outcome value

assigned to B. This is further evidence suggesting that the mechanism by which participants

score the compound is a serial search one.

⁴²⁴   Taken together, the three studies reported here provide empirical evidence for the

⁴²⁵ hypothesis that inefficient visual search strategies can mimic configural processing using a

⁴²⁶ summation design. Although we have presented our evidence in causal learning experiments,

⁴²⁷ we believe that a similar process of serial search might underlie many results from the animal

⁴²⁸ learning literature which are usually interpreted as favoring a configural approach. In the

⁴²⁹ next section we formalize this hypothesis in a computational reinforcement learning model

⁴³⁰ and show through simulations how many patterns of results taken as evidence for configural

⁴³¹ processing can be better captured by this elemental visual search approach.

Figure 5. **An elemental visual search model.** On each trial where the agent is presented
with a compound of cues that predict an outcome, the actor samples one of the cues according
to their current value and salience. In this example, the compound AB is presented together
with the unique cue X. For illustrative purposes, we assume that cue A has been sampled
in this trial (colored in red). Once the actor samples the cue, the critic updates the value
according to a prediction error rule. Only the value of the sampled cue (A, in our example)
is updated for the following trial.

An elemental visual search model

Having established an elemental-type of representation with a visual search process as
the best interpretation for our data, we now set out to formalize a computational model
based on this idea. This model, which we call elemental-visual-search (EVS) model, can
capture both the present and previous data from the learning literature, and shows how two
different areas of research can be unified in a single framework to explain not only the data
from summation designs but also data from a wide range of experiments on generalization
which are taken as evidence in favor of a configural-type of representation.

The model proposed here is related to the actor-critic reinforcement learning model
(Maia, 2010; O'Doherty et al., 2004). Our model assumes a *critic* that learns according to a
prediction-error algorithm, where the predictive value or *associative strength* of stimulus i in
trial n , v_i^n, is updated in accord with Equation 1

$$v_i^{n+1} = v_i^n + \alpha_i\beta(\lambda^n - v_i^n) \tag{1}$$

, where α and β are learning rate parameters ($\alpha \in [0,1], \beta \in [0,1]$) which represent
how much the subject updates the value of cue i in trial n and λ^n is an indicator function
that takes the value one if a reward is presented in trial n and zero if the reward is not
presented ($\lambda \in \{0,1\}$). This algorithm assumes that the change in the associative or
predictive value of stimulus i is determined by the difference between the observed outcome
and the current outcome expected from that stimulus.

The next step is formulating the type of elemental representation that is brought about
when compound of stimuli are presented to the agent. Assuming that the actual stimuli
presented by the experimenter are the only cues represented by the agent, and that
compounds are simply comprised of the same components is problematic, as such a model

cannot account for the fact that animals learn non-linear discriminations in which elements

and compounds are differentially rewarded. For this reason, we follow a previous model

offered by Wagner and Rescorla (1972). Under this model, any component can activate its

own elemental representation and acquire its own predictive value in accord with Equation 1,

but the modification concerns how the agent represents cues in isolation and in compound.

When a stimulus is presented in compound with other stimulus, this model assumes that an

additional element enters into an association with the outcome. This *unique-cue* element

follows the same learning algorithm as in Equation 1.

Three important aspects of this unique cue are worth noting. First, the addition of a

cue representing the compound does not imply that subjects process stimuli in a configural

manner. The key property of configural processing is whether or not the representation of a

given cue, like A, is "context-specific" (Wagner, 2008), changing when A is presented alone

versus when it is presented in compound with other stimuli. This is not the case for the

Wagner-Rescorla approach that we follow here. In a summation design, A and B are still

represented and processed elemntally, and a summation effect is still predicted by the model.

Second, the unique cue is usually interpreted as an internal representation of a

compound. However, this interpretation is not necessary in the present application. As long

as visual cues are presented in close proximity during compound trials (i.e., either

overlapping or close to one another), it is possible for the subject to sample visual

information in some areas of the display that are unique to compound trials (e.g., line

intersections), which makes the compound trial different to a single cue trial.

Third, the unique cue is not necessary to explain results from simple summation

experiments, like those presented in this paper. This aspect of the model is only important

for the explanation of more complex designs, like the non-linear discriminations just

mentioned. To illustrate this point, take one of the cardinal results suggesting a configural

type of processing, the negative patterning design (Myers, Vogel, Shin, & Wagner, 2001).

Under this design, each component A and B is rewarded in isolation, but the compound AB

is not (A+,B+,AB-). Given the above equations, it is relatively clear that an agent should

never be able to solve this problem under an elemental-type of representation; that is, it

should never learn to respond less to AB than to each of A or B alone. Given the assumption

that predictions are summed linearly ($v_{Total} = v_{AB} = v_A + v_B$), the presentation of AB

should always produce a summation effect. And yet animals are able to solve this problem

and respond less to AB than to either of A and B (see also Saavedra (1975)). However, the

assumption of an additional unique cue is able to correctly predict these data. Assume, for

example, that a unique cue X is active whenever the compound AB is presented, but inactive

when A and B are presented in isolation. This is equivalent to A+, B+ and ABX- training,

which according to the Wagner and Rescorla model (1972), implies that X will acquire

negative predictive value. If the salience of X is sufficiently high so that its value is higher (in

absolute value) that the predictions of A and B together, the discrimination is readily solved.

To model our agent's visual search process, in addition to the critic learning the value

of a cue according to Equation 1 we assume an additional system, the actor, which searches

in the stimulus array for a single stimulus to process. We model this actor through sampling

from a multinomial distribution with parameter $\mathbf{p} = [p_1, p_2, ..., p_k]$ where k is the number of

stimuli presented in a given training or testing trial. In line with the visual search literature

where both higher salience (α) (Parkhurst, Law, & Niebur, 2002) and higher predictive value

(v) (Anderson, Laurent, & Yantis, 2011) increase the probability of a stimulus capturing

attention, we assume that the probability of stimulus i being processed is given by a softmax

function incorporating both of these factors (Sutton & Barto, 1998):

$$p_i = \frac{\exp\left(\eta\alpha_i \left|v_i\right|\right)}{\sum\limits_{j} \exp\left(\eta\alpha_j \left|v_j\right|\right)} \tag{2}$$

, where η is a decisiveness or *temperature* parameter that determines the extent to

which the actor is biased to sample cues with low salience or predictive value

($j = [1, 2, ..., i, ...k]$). We use the absolute value of v, since cues with high inhibitory strength

(negative v) should command more attention than other cues in a given array (Parkhurst et

al., 2002).

To illustrate how this model operates, see the schematic representation of the model in

Figure 4. In this example, we assume that the compound AB is being presented to the

subject. In this case, the agent represents an additional unique cue X for this particular

combination of elements. Once the actor samples cue A (shown in red), its value is then

updated by the critic according to the difference between the current value or prediction (v_i)

and the outcome observed (λ) in that trial.

For all the simulations in this paper, we assume that the salience of the unique cues is

equal to the salience of the target cues, that is, $\alpha_{target} = \alpha_{nonTarget}$, and that the order of

presentations of different trial types in an experiment is random. The former

assumption—that the salience of the cues presented and the unique cues represented by the

subject in compound trials are equal—is an assumption generally held by Pearce (1994,

2002) in his modelling of configural theory and is the one that, unless otherwise noted, we

follow in all the subsequent simulations in this paper.

To allow the actor to sample cues with low predictive value we set the temperature

parameter η to 30 and the initial predictive value of each cue, both target and unique cues,

v_i, $i \in [1, ..., k]$, to 0.05. Unless otherwise noted, the value of λ was set to 1 for reward trials

and to zero for non-rewarded trials. Finally, we assume that the agent represents an

additional unique cue for each one of the possible combinations of cues (for example, if the

compound ABC is presented, we assume that there is an additional unique cue represented

for each possible pair—AB, AC, BC—and the compound of three cues—ABC). We ran 80

simulations for each experimental design. The values shown in the following figures are the

average values across all simulations.

Summation

As we have previously noted, support for configural theory comes from studies in pigeon auto-shaping (Aydin & Pearce, 1995, 1997). In these studies, a summation effect is usually not found when visual stimuli are presented in compounds. The purpose of this section is to simulate these summation procedures and the results obtained in Experiments 2 and 3 reported here.

We start by simulating the conditions of autoshaping in pigeons. To this end, we assume that both components predict the same outcome value and have equal saliencies ($\alpha_A = \alpha_B = .4$). The results of this simulation are shown in the right panel of Figure 5a. As shown in the figure, the EVS model correctly predicts the failure to find a summation effect when an inefficient search strategy is adopted. Importantly, as can be seen in the left hand panel of Figure 5a, a similar result has been reported by Rescorla and Coldwell (1995). Intuitively, during the test phase the actor sometimes samples the unique cue that is only represented in the testing phase, which tends to bring down responding to AB compared to the elements A and B.

In a second set of simulations, we investigated the predictions of the EVS model when cue B predicts a lower outcome value than A, trying to match the conditions of Experiment 2. As suggested by the data, participants' behavior was driven by the higher salience of B, which led to the majority of them to sample this cue during the test stage. To account for the fact that B is more salient, we set the value of α_A to .4 and the value of α_B to .5. A value of .4 was also set to the unique cue X ($\alpha_X = .4$). To account for different outcome values predicted by each cue, we set $\lambda_A = 1 > \lambda_B = .95$. The model correctly predicts the pattern of results of Experiment 2, in that responding to A, the most salient cue, is higher than to B (see Figure 5b). The model also replicates our finding that responding to AB would be closer to B than to A. Lastly, we tried to match the conditions of Experiment 3 by reversing the roles of A and B, so that B predicts a higher outcome value than A

Figure 6. (a) Simulations of the EVS model for different summation designs. The left panel shows the results obtained by Rescorla and Coldwell (1995) using pigeon autoshaping. The right panel shows the simulations of the model assuming that the saliencies of A and B are equal. (b) Results of a simulation of Experiment 2, where the salience of B is assumed to be higher than that of A, but B predicts a lower outcome value. (c) Results of a simulation of Experiment 3, where the salience of B was higher than that of A but the outcome value predicted by B was higher than the value predicted by A.

555 ($\lambda_A = .95, \lambda_B = 1$). Again, the EVS model correctly captures the pattern of behavior

556 observed in this experiment, in that responding to AB should be closer to the outcome

557 predicted by B, and higher than in Experiment 2 (see Figure 5c).

Differential summation

In another experiment in pigeon auto-shaping, Pearce and colleagues (1997) obtained

further evidence in favor of configural processing. Using visual stimuli, these authors found

that responding at test for the compound of three cues, ABC, was weaker when the three

cues were separately paired with a reward (A+, B+, C+) than when the cues were paired

with the same reward, but in compounds (AB+, AC+, BC+) (see Figure 6, left panel).

Elemental models make the opposite prediction, but Pearce's configural model can account

for these results. Figure 6 (right panel) depicts the simulations of this design in the EVS

model. As can be seen, elemental processing with inefficient visual search correctly captures

these results, since the value of the value of ABC is higher after training with the compounds

AB, BC and AC, than separately training subjects with A, B and C. The reason why the

EVS model correctly predicts this result concerns the type of representation for the

compound ABC during testing. In the case of single-cue training, at the end of training

ABC is comprised of four unique cues with very low predictive values (.05 each, by

assumption), whereas the same ABC compund is comprised of the same four unique cues,

some of which have been represented by the agent during training and have therefore

acquired higher predictive values than in the case of single-cue training. During the

presentation of ABC during the test, the actor sometimes sample these higher-valued unique

cues. Consequently, subjects tend to respond more to the compound ABC after compound

training than after single-cue training.

Reversing a conditioned inhibitor

579   Pearce and Wilson ran an experiment which included a negative patterning design of

580 the form A+, AB- in a first phase, and rewarded presentations of B alone in a second phase

Figure 7. **Simulations of a EVS model for a differential summation design.** Left panel. Results obtained by Pearce and colleagues (1997) in pigeon autoshaping. The bars show the responding to the compound ABC after training with the single cues A, B and C or after training with the compounds AB, BC, and AC. Right panel. Simulations of the EVS model for the same design.

(B+). In the animal and human causal learning literature, the first phase turns cue B to

what is referred to as a *conditioned inhibitor*, meaning that B signals the absence of an

otherwise present reward. In contrast to an elemental theory which would predict B to

recover its predictive value so that responding to AB should be higher than A or B alone,

Pearce and Wilson observed that responding to AB during test was indeed lower (see Figure

7, left panel). This result is also anticipated by the EVS model (see Figure 7, right panel).

During the first stage, A acquires more value than B and the unique cue represented for AB.

During the second stage, B acquires more value. During the final test with AB, however, the

actor still samples the unique cue, whose value has not changed during the second phase,

staying at a low level. Responding to AB is therefore lower than to either A or B.

Negative patterning

In another experiment in pigeons, Pearce and Redhead (1993, Exp. 1) found that

subjects mastered a negative patterning discrimination (A+ AB-) easier than the same

discrimination with an added redundant stimulus (AC+ ABC-). Figure 8a shows the results

obtained by these authors in pigeons. The left panel shows the results observed after training

with A+ and AB-; the right panel shows the results observed after training AC+ and ABC-.

Given that the similarity between A and AB is lower than that of AC and ABC, an

elemental approach anticipates that it will be easier for agents to master the discrimination

in the group that is trained with A and AB separately than in the group trained with AC

and ABC as compounds. Pearce's configural model (1987, 1994, 2002), by contrast, correctly

predicts this result. The similarity between the training set AC and the compound ABC is

higher than that between A and AB and, given that similarity determines how much the

compound ABC is processed in each trial, it follows that agents should learn to respond less

to the compound AB than to the compound ABC during training (see Pearce (2002); Pearce

(1994)). Here we show that the EVS model is also able to account for these results.

It is relatively clear that when the actor of the EVS model is highly exploratory,

Figure 8. **Simulations of a EVS model for Experiment 3 of Pearce and Wilson (1991).** The experiment comprises a first phase where A is rewarded and the compound AB is not (A+, AB-). In the second phase B is rewarded in isolation. The left panel shows the original data obtained by these authors. Simulations of the EVS model are shown in the right panel.

solving this problem will be particularly difficult, as there needs to be less sampling of

unique cues that have a low value during training. We therefore tested if our model would

predict this behavioral pattern assuming a low exploratory agent ($\eta = 5$) for which the

unique cue for the compound ABC is more salient than the other cues, that is,

$\alpha_A = \alpha_B = .4 < \alpha_X = .7$, where X is the unique cue for the compound ABC.Figure 8b

shows the results of the simulations of these two negative patterning designs. The left panel

shows the predictive value of A, and AB during training with a A+, AB- discrimination; the

right panel shows a similar simulation for a AC-, ABC- design. The results of this simulation

are reasonably in keeping with those obtained by Pearce and Redhead (1993): the difference

in value between A and AB is higher than that between AC and ABC, and the order of

values also follows the one obtained by these authors.

These simulations have provided computational evidence for an elemental visual search

approach. The results strengthen our hypothesis that the patterns of results taken as

evidence for configural processing in the learning literature can be also captured by this new

approach. Our simulations go beyond the empirical evidence presented in Experiments 1-3,

showing how results from more complex designs than simple summation can also be

accommodated by a reinforcement learning model based on elemental representations of

stimuli with visual search.

Discussion

In this paper, we have presented empirical and computational evidence supporting the

hypothesis that many results from the learning literature usually thought to support

configural processing of stimuli can be also explained by an alternative elemental view in

which the learning process is governed by a critic that, combined with an actor's visual

search mechanism, determines the cues that subjects sample and update during each training

episode. We argued that task conditions fostering inefficient serial search on the stimulus

compound are easily met by visual auto-shaping in pigeons, which explains the ease with

Figure 9. **Simulations of the EVS model for a negative patterning design.** (a) Data obtained by Pearce and Redhead (1993) in pigeons. The left panel shows responding to the compound to A and AB at the end of training after a discrimination with rewarded trials of A and non-rewarded trials with AB (A+, AB-). The right hand panel shows responding to the compounds AC and ABC at the end of training after a discrimination with rewarded trials of AC and non-rewarded trials with ABC (AC+, ABC-). (b) Simulations of the EVS model for a group trained on the A+, AB- discrimination (left panel) and for a group trained on the AC+, ABC- discrimination.

which lack of summation is found using such a procedure. We also suggested that such conditions are more difficult to meet in human causal learning with visual stimuli, which explains our inability to reduce the summation effect through stimulus manipulations in previous studies (Pérez et al., 2018).

In Experiment 1, we showed that when task conditions foster inefficient visual search, it is possible to reduce the summation effect by increasing stimulus similarity. We also showed that, as would be predicted from the visual search literature (Duncan & Humphreys, 1989), not only similarity between the two target stimuli, but also similarity of target and non-target cues produces a reduction in the summation effect. In Experiments 2 and 3, we showed that when similar cues were used, producing no summation effect, responding to the compound AB depended strongly on responding to only one of the cues, as it would be expected from an inefficient serial search strategy rather than from configural stimulus processing.

To further test this visual search hypothesis, we formalized a computational model, the EVS model, that implements our assumptions about the processes involved in these experiments. The model borrows concepts from the reinforcement learning literature, and in particular from the actor-critic model (Maia, 2010; O'Doherty et al., 2004; Sutton & Barto, 1998). The critical assumption of the actor-critic model is the deployment of two different systems that contribute to each other so that the agent can choose which options are best to maximize reward in the long run. The EVS model follows a similar approach. One system, the critic, deploys an elemental learning algorithm as presented by Wagner and Rescorla (1972). What distinguishes our model from the ones offered in the learning literature is that an additional system, the actor, samples cues according to their current value and salience, factors that have been demonstrated to prompt sampling in the visual search literature (Anderson et al., 2011; Parkhurst et al., 2002). The actor, therefore, biases the critic to update the value of only one of the cues in each trial.

The EVS model shares some similarities with a previous model proposed by Harris

(2006; Harris & Livesey, 2010), in which limited attentional capacities force stimulus

representations of individual cues to be processed incompletely. This gating is dependent, in

turn, on the predictive value of cues. However, while Harris' model is based on mechanisms

of limited covert attention, our model assumes that sampling limitations of overt attention

during visual search produce incomplete processing of stimuli in a compound. Similarly, the

model proposed by Mackintosh (1975) shares with our model the assumption that the most

predictive cues should command more attention, but differs with ours in that what is

updated on every trial is the learning rate or associability of the most predictive stimulus,

rather than the probability of the stimulus being processed on a given trial.

Although our claim in this paper is not that all evidence of configural processing is due

to an elemental search process, nor that the EVS model is a good candidate for a complete

model of associative or causal learning, the model can also capture a number of basic

phenomena from the associative learning literature (see Supplemental Material for

simulations). One such phenomenon is external inhibition (Pavlov, 1927), in which less

responding is obtained to a compound AB during testing after training with one of the

elements than responding to the single cue A alone. Pearce's configural model can readily

explain this result because the activation of the configural unit AB depends on the similarity

between AB and A, which is only .5. In the EVS model, by contrast, external inhibition is

anticipated because after A has acquired significant predictive value during training, the

presentation of AB during the test is represented as ABX. Subjects then sample in this space

and process B and X according to the softmax activation function (Sutton & Barto, 1998).

Since B and X have both a low predictive value, and are sometimes sampled, the average

responding to AB will be lower than to A, and external inhibition is obtained.

This attentional mechanism for external inhibition is not new. Pavlov himself had a

similar explanation for it (1927). According to Pavlov, the presentation of the added cue B

during the test stage makes the animal orient (i.e., attend) to it, so that the previous cue A is not processed (i.e., sampled) as it would otherwise be, explaining why responding to the compound AB during the test is lower than responding to A alone.

A number of other learning phenomena, usually known as cue competition phenomena, are also anticipated by our model. In these type of procedures it is usually found that the predictive value of a cue can impede the value otherwise normally accrued to other target cues. Blocking is perhaps the best-known example of cue competition. In a blocking procedure, after having trained A to predict an outcome, A is trained in compound with another cue B during a second stage. Responding to B is then tested against a group that did not undergo the first stage with A and it is usually found that the value of this latter cue B is higher than that of the cue B trained in compound. In terms of the EVS model, the second stage in which A and B are trained in compound produces a visual search in which the added cue B is sampled only in some of the trials as a consequence of the higher predictive value of A at the start of the second stage (Kamin, 1969; Mackintosh & Turner, 1971). Compared to a group that has not undergone the first stage of training, responding to B will be lower, and blocking follows. In addition, when compounds are presented during training the sampling mechanism of the EVS model makes it so that, for the same amount of training, each cue is sampled only half the time it would have been processed during training with either of the single cues alone; the sequential search process will then explain why training compounds brings about less responding to each cue than training the cues in isolation (overshadowing; Mackintosh (1976); Soto (2012)).

Regardless of the generalizability of the EVS model, the empirical and computational evidence in this paper suggests that results usually interpreted in favor of configural processing may be also explained as a consequence of elemental processing combined with visual search strategies. As we have seen, this theory is able to account for the results shown in this paper, and the EVS model can capture the present and previous data on

711 generalization better than configural models of learning. Our work thus bridges two

712 seemingly unrelated areas of experimental psychology, leading to a more parsimonious

713 explanation of the results of summation experiments across species and the discovery of new

714 principles underlying the generalization of learning.

Acknowledgements

716 We thank Jaron Colas and Tony Dickinson for their comments on a previous version of

717 this manuscript. S.D.G.

Open Practices Statement

719 The data and materials for all experiments are available at https://osf.io/xqnpk/

References

Anderson, B. A., Laurent, P. A., & Yantis, S. (2011). Value-driven attentional capture.

Proceedings of the National Academy of Sciences, *108*(25), 10367–10371.

https://doi.org/10.1073/pnas.1104047108

Aydin, A., & Pearce, J. M. (1995). Summation in autoshaping with short-and

long-duration stimuli. *The Quarterly Journal of Experimental Psychology*, *48*(3), 215–234.

Aydin, A., & Pearce, J. M. (1997). Some determinants of response summation. *Animal*

Learning & Behavior, *25*(1), 108–121.

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting linear mixed-effects

models using lme4. *Journal of Statistical Software*, *67*(1), 1–48.

https://doi.org/10.18637/jss.v067.i01

Berbaum, K. S., Franken, E. A., Dorfman, D. D., Rooholamini, S. A., Kathol, M. H.,

Barloon, T. J., . . . el-Khoury, G. Y. (1990). Satisfaction of search in diagnostic radiology.

Investigative Radiology, *25*(2), 133–140.

Cheng, P. W. (1997). From covariation to causation: A causal power theory.

Psychological Review, 104(2), 367–405. https://doi.org/10.1037//0033-295X.104.2.367

Cheng, P. W., & Buehner, M. J. (2012). Causal Learning.

https://doi.org/10.1093/oxfordhb/9780199734689.013.0012

Dittrich, L., Rose, J., Buschmann, J. U., Bourdonnais, M., & Güntürkün, O. (2010).

Peck tracking: A method for localizing critical features within complex pictures for pigeons.

Animal Cognition, 13(1), 133–143. https://doi.org/10.1007/s10071-009-0252-x

Duncan, J., & Humphreys, G. W. (1989). Visual search and stimulus similarity.

Psychological Review, 96(3), 433–458.

Gerlanc, D., & Kirby, K. (2015). *BootES: Bootstrap effect sizes.* Retrieved from

https://CRAN.R-project.org/package=bootES

Glautier, S. (2002). Spatial separation of target and competitor cues enhances blocking

of human causality judgements. *Q J Exp Psychol B, 55*(2), 121–135.

https://doi.org/10.1080/02724990143000207

Glautier, S., Redhead, E., Thorwart, A., & Lachnit, H. (2010). Reduced summation

with common features in causal judgments. *Experimental Psychology, 57*(4), 252–259.

https://doi.org/10.1027/1618-3169/a000030

Goodale, M. A. (1983). Visually guided pecking in the pigeon (Columba livia). *Brain,*

Behavior and Evolution, 22(1), 22–41.

Harris, J. a. (2006). Elemental representations of stimuli in associative learning.

Psychological Review, 113(3), 584–605. https://doi.org/10.1037/0033-295X.113.3.584

Harris, J. A., & Livesey, E. J. (2010). An attention-modulated associative network.

Learning & Behavior, 38(1), 1–26.

Honey, R. C., Close, J., & Lin, T. (2010). Acquired distinctiveness and equivalence: A

synthesis. In C. J. Mitchell & M. E. Le Pelley (Eds.), *Attention and associative learning:*

From brain to behaviour (pp. 159–186). Oxford University Press Oxford.

Kamin, L. (1969). Predictability, surprise, attention, and conditioning. *Punishment*

and Aversive Behavior. Retrieved from

https://scholar.google.co.uk/scholar?q=Predictability,+surprise,+attention,+and+conditioning{\&}btnG=

BR{\&}as{_}sdt=0,5{\#}0

Kassambara, A. (2017). *Ggpubr: 'Ggplot2' based publication ready plots.* Retrieved

from https://CRAN.R-project.org/package=ggpubr

Kehoe, E. J., Horne, A. J., Horne, P. S., & Macrae, M. (1994). Summation and

configuration between and within sensory modalities in classical conditioning of the rabbit.

Animal Learning {&} Behavior, *22*(1), 19–26. https://doi.org/10.3758/BF03199952

Mackintosh, N. J. (1975). A theory of attention: Variations in the associability of

stimuli with reinforcement. *Psychological Review*, *82*(4), 276–298.

https://doi.org/10.1037/h0076778

Mackintosh, N. J. (1976). Overshadowing and stimulus intensity. *Animal Learning {&}*

Behavior, *4*(2), 186–192. https://doi.org/10.3758/BF03214033

Mackintosh, N. J., & Turner, C. (1971). Blocking as a function of novelty of CS and

predictability of UCS. *The Quarterly Journal of Experimental Psychology*, *23*(4), 359–366.

Maia, T. V. (2010). Two-factor theory, the actor-critic model, and conditioned

avoidance. *Learning & Behavior*, *38*(1), 50–67. https://doi.org/10.3758/LB.38.1.50

Martinoya, C., Le Houezec, J., & Bloch, S. (1984). Pigeon's eyes converge during

feeding: Evidence for frontal binocular fixation in a lateral-eyed bird. *Neuroscience Letters*,

45(3), 335–339. https://doi.org/10.1016/0304-3940(84)90248-9

McLaren, I. P. L., & Mackintosh, N. J. (2002). Associative learning and elemental representation: II. Generalization and discrimination. *Animal Learning & Behavior*, 30(3), 177–200. https://doi.org/10.3758/BF03192828

Melchers, K. G., Shanks, D. R., & Lachnit, H. (2008). Stimulus coding in human associative learning: flexible representations of parts and wholes. *Behavioural Processes*, 77(3), 413. https://doi.org/10.1016/j.beproc.2007.09.013

Mitchell, C. J., De Houwer, J., & Lovibond, P. F. (2009). The propositional nature of human associative learning. *The Behavioral and Brain Sciences*, 32(2), 183–246. https://doi.org/10.1017/S0140525X09000855

Morey, R. D., & Rouder, J. N. (2015). *BayesFactor: Computation of bayes factors for common designs.* Retrieved from https://CRAN.R-project.org/package=BayesFactor

Myers, K. M., Vogel, E. H., Shin, J., & Wagner, A. (2001). A comparison of the Rescorla-Wagner and Pearce models in a negative patterning and a summation problem. *Animal Learning & Behavior*, 29(1), 36–45. https://doi.org/10.3758/BF03192814

O'Doherty, J. P., Dayan, P., Schultz, J., Deichmann, R., Friston, K., & Dolan, R. (2004). Dissociable roles of ventral and dorsal striatum in instrumental conditioning. *Science*, 304(5669), 452–454. https://doi.org/10.1126/science.1094285

Parkhurst, D., Law, K., & Niebur, E. (2002). Modeling the role of salience in the allocation of overt visual attention. *Vision Research*, 42(1), 107–123.

Pavlov, I. P. (1927). No Title. In *Conditioned reflexes. An investigation of the physiological activity of the cerebral cortex.* London.

Pearce, J. M. (1987). A model for stimulus generalization in Pavlovian conditioning.

Psychological Review, 94(1), 61–73. Retrieved from

http://www.ncbi.nlm.nih.gov/pubmed/3823305

Pearce, J. M. (1994). Similarity and discrimination: A selective review and a connectionist model. *Psychological Review, 101*(4), 587.

Pearce, J. M. (2002). Evaluation and development of a connectionist theory of configural learning. *Animal Learning & Behavior, 30*(2), 73–95. https://doi.org/10.3758/BF03192911

Peirce, J. W. (2007). PsychoPy—psychophysics software in Python. *Journal of Neuroscience Methods, 162*(1), 8–13.

Pérez, O. D., San Martín, R., & Soto, F. A. (2018). Exploring the effect of stimulus similarity on the summation effect in casual learning. *Experimental Psychology, 65*(February), 183–200. https://doi.org/10.1027/1618-3169/a000406

R Core Team. (2017). *R: A language and environment for statistical computing.* Vienna, Austria: R Foundation for Statistical Computing. Retrieved from https://www.R-project.org/

Rescorla, R., & Coldwell, S. E. (1995). Summation in autoshaping. *Animal Learning & Behavior, 23*(3), 314–326. https://doi.org/10.3758/BF03198928

Rescorla, R., & Wagner, A. (1972). A theory of Pavlovian conditioning: Variations in the effectiveness of reinforcement and nonreinforcement. *Classical Conditioning II: Current Research and Theory, 2*, 64–99.

RStudio Team. (2015). RStudio: Integrated Development Environment for R. Boston, MA: RStudio, Inc. Retrieved from http://www.rstudio.com/

Saavedra, M. A. (1975). Pavlovian compound conditioning in the rabbit. *Learning and*

Motivation, 6(3), 314–326.

Shepard, R. N. N. (1987). Toward a universal law of generalization for psychological

science. *Science.* Retrieved from http://k7moa.com/Shepard{\%}7B{_}{\%}7D1987.pdf

http://k7moa.com/Shepard{_}}1987.pdf

Soto, F. A. (2012). *A Category-Overshadowing Effect in Pigeons: Support for the*

Common Elements Model of Object Categorization Learning.

Soto, F. A., Gershman, S. J., & Niv, Y. (2014a). Explaining compound generalization

in associative and causal learning through rational principles of dimensional generalization.

Psychological Review, 121(3), 526–558.

Soto, F. A., Gershman, S., & Niv, Y. (2014b). Explaining Compound Generalization in

Associative and Causal Learning Through Rational Principles of Dimensional Generalization.

Psychological Review, 1–117. Retrieved from

http://people.psych.ucsb.edu/soto/fabian/docs/PR.14.sgn.pdf

Soto, F. A., Quintana, G. R., Pérez-Acosta, A. M., Ponce, F. P., & Vogel, E. H. (2015).

Why are some dimensions integral? Testing two hypotheses through causal learning

experiments. *Cognition, 143,* 163–177. https://doi.org/10.1016/j.cognition.2015.07.001

Soto, F. A., Siow, J. Y. M., & Wasserman, E. A. (2012). View-invariance learning in

object recognition by pigeons depends on error-driven associative learning processes. *Vision*

Research, 62, 148–161. https://doi.org/10.1016/j.visres.2012.04.004

Soto, F. A., Vogel, E. H., Castillo, R. D., & Wagner, A. (2009). Generality of the

summation effect in human causal learning. *Quarterly Journal of Experimental Psychology*

(2006), 62(5), 877–889. https://doi.org/10.1080/17470210802373688

Soto, F. A., & Wasserman, E. A. (2010). Error-driven learning in visual categorization

and object recognition: a common-elements model. *Psychological Review, 117*(2), 349–381. https://doi.org/10.1037/a0018695

Sutton, R. S., & Barto, A. G. (1998). *Reinforcement learning: An introduction* (Vol. 1). MIT press Cambridge.

Thein, T., Westbrook, R. F., & Harris, J. A. (2008). How the associative strengths of stimuli combine in compound: Summation and overshadowing. *Journal of Experimental Psychology: Animal Behavior Processes, 34*(1), 155–166. https://doi.org/10.1037/0097-7403.34.1.155

Thorwart, A., Livesey, E. J., & Harris, J. A. (2012). Normalization between stimulus elements in a model of Pavlovian conditioning: Showjumping on an elemental horse. *Learning & Behavior, 40*(3), 334–346.

Treisman, A. (1985). Preattentive processing in vision. *Computer Vision, Graphics, and Image Processing, 31*(2), 156–177. https://doi.org/10.1016/S0734-189X(85)80004-9

Treisman, A. (1988). Features and objects: The fourteenth bartlett memorial lecture. *The Quarterly Journal of Experimental Psychology, 40A*(2), 201–237.

Treisman, A. M., & Gelade, G. (1980). A feature-integration theory of attention. *Cognitive Psychology, 12*(1), 97–136.

Vogel, E. H., Glynn, J. Y., & Wagner, A. (2015). Cue competition effects in human causal learning. *The Quarterly Journal of Experimental Psychology*, (May 2015), 1–24. https://doi.org/10.1080/17470218.2015.1014378

Wagner, A. (2008). Evolution of an elemental theory of Pavlovian conditioning. *Learning & Behavior, 36*(3), 253–265. https://doi.org/10.3758/LB.36.3.253

Wagner, A., & Rescorla, R. (1972). Inhibition in pavlovian conditioning: Application

of a theory. *Inhibition and Learning*, 301–336.

Wasserman, E. A., & Anderson, P. A. (1974). Differential autoshaping to common and distinctive elements of positive and negative discriminative stimuli. *Journal of the Experimental Analysis of Behavior*, *22*(3), 491.

Wickham, H. (2009). *Ggplot2: Elegant graphics for data analysis.* Springer-Verlag New York. Retrieved from http://ggplot2.org

Wickham, H., Francois, R., Henry, L., & Müller, K. (2017). *Dplyr: A grammar of data manipulation.* Retrieved from https://CRAN.R-project.org/package=dplyr

Wolfe, J. M. (2018). Visual Search. In J. T. Serences (Ed.), *Stevens' Handbook of Experimental Psychology and Cognitive Neuroscience* (Vol. 2, pp. 1–55). Hoboken, NJ: John Wiley & Sons. https://doi.org/10.1002/9781119170174.epcn213

Anderson, B. A., Laurent, P. A., & Yantis, S. (2011). Value-driven attentional capture. *Proceedings of the National Academy of Sciences*, *108*(25), 10367–10371. https://doi.org/10.1073/pnas.1104047108

Aydin, A., & Pearce, J. M. (1995). Summation in autoshaping with short-and long-duration stimuli. *The Quarterly Journal of Experimental Psychology*, *48*(3), 215–234.

Aydin, A., & Pearce, J. M. (1997). Some determinants of response summation. *Animal Learning & Behavior*, *25*(1), 108–121.

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting linear mixed-effects models using lme4. *Journal of Statistical Software*, *67*(1), 1–48. https://doi.org/10.18637/jss.v067.i01

Berbaum, K. S., Franken, E. A., Dorfman, D. D., Rooholamini, S. A., Kathol, M. H., Barloon, T. J., . . . el-Khoury, G. Y. (1990). Satisfaction of search in diagnostic radiology.

Investigative Radiology, 25(2), 133–140.

Cheng, P. W. (1997). From covariation to causation: A causal power theory. *Psychological Review, 104*(2), 367–405. https://doi.org/10.1037//0033-295X.104.2.367

Cheng, P. W., & Buehner, M. J. (2012). Causal Learning. https://doi.org/10.1093/oxfordhb/9780199734689.013.0012

Dittrich, L., Rose, J., Buschmann, J. U., Bourdonnais, M., & Güntürkün, O. (2010). Peck tracking: A method for localizing critical features within complex pictures for pigeons. *Animal Cognition, 13*(1), 133–143. https://doi.org/10.1007/s10071-009-0252-x

Duncan, J., & Humphreys, G. W. (1989). Visual search and stimulus similarity. *Psychological Review, 96*(3), 433–458.

Gerlanc, D., & Kirby, K. (2015). *BootES: Bootstrap effect sizes.* Retrieved from https://CRAN.R-project.org/package=bootES

Glautier, S. (2002). Spatial separation of target and competitor cues enhances blocking of human causality judgements. *Q J Exp Psychol B, 55*(2), 121–135. https://doi.org/10.1080/02724990143000207

Glautier, S., Redhead, E., Thorwart, A., & Lachnit, H. (2010). Reduced summation with common features in causal judgments. *Experimental Psychology, 57*(4), 252–259. https://doi.org/10.1027/1618-3169/a000030

Goodale, M. A. (1983). Visually guided pecking in the pigeon (Columba livia). *Brain, Behavior and Evolution, 22*(1), 22–41.

Harris, J. a. (2006). Elemental representations of stimuli in associative learning. *Psychological Review, 113*(3), 584–605. https://doi.org/10.1037/0033-295X.113.3.584

Harris, J. A., & Livesey, E. J. (2010). An attention-modulated associative network.
Learning & Behavior, *38*(1), 1–26.

Honey, R. C., Close, J., & Lin, T. (2010). Acquired distinctiveness and equivalence: A
synthesis. In C. J. Mitchell & M. E. Le Pelley (Eds.), *Attention and associative learning:*
From brain to behaviour (pp. 159–186). Oxford University Press Oxford.

Kamin, L. (1969). Predictability, surprise, attention, and conditioning. *Punishment*
and Aversive Behavior. Retrieved from
https://scholar.google.co.uk/scholar?q=Predictability,+surprise,+attention,+and+conditioning{\&}btnG=
BR{\&}as{_}sdt=0,5{\#}0

Kassambara, A. (2017). *Ggpubr: 'Ggplot2' based publication ready plots.* Retrieved
from https://CRAN.R-project.org/package=ggpubr

Kehoe, E. J., Horne, A. J., Horne, P. S., & Macrae, M. (1994). Summation and
configuration between and within sensory modalities in classical conditioning of the rabbit.
Animal Learning {&} Behavior, *22*(1), 19–26. https://doi.org/10.3758/BF03199952

Mackintosh, N. J. (1975). A theory of attention: Variations in the associability of
stimuli with reinforcement. *Psychological Review*, *82*(4), 276–298.
https://doi.org/10.1037/h0076778

Mackintosh, N. J. (1976). Overshadowing and stimulus intensity. *Animal Learning {&}*
Behavior, *4*(2), 186–192. https://doi.org/10.3758/BF03214033

Mackintosh, N. J., & Turner, C. (1971). Blocking as a function of novelty of CS and
predictability of UCS. *The Quarterly Journal of Experimental Psychology*, *23*(4), 359–366.

Maia, T. V. (2010). Two-factor theory, the actor-critic model, and conditioned
avoidance. *Learning & Behavior*, *38*(1), 50–67. https://doi.org/10.3758/LB.38.1.50

Martinoya, C., Le Houezec, J., & Bloch, S. (1984). Pigeon's eyes converge during feeding: Evidence for frontal binocular fixation in a lateral-eyed bird. *Neuroscience Letters*, *45*(3), 335–339. https://doi.org/10.1016/0304-3940(84)90248-9

McLaren, I. P. L., & Mackintosh, N. J. (2002). Associative learning and elemental representation: II. Generalization and discrimination. *Animal Learning & Behavior*, *30*(3), 177–200. https://doi.org/10.3758/BF03192828

Melchers, K. G., Shanks, D. R., & Lachnit, H. (2008). Stimulus coding in human associative learning: flexible representations of parts and wholes. *Behavioural Processes*, *77*(3), 413. https://doi.org/10.1016/j.beproc.2007.09.013

Mitchell, C. J., De Houwer, J., & Lovibond, P. F. (2009). The propositional nature of human associative learning. *The Behavioral and Brain Sciences*, *32*(2), 183–246. https://doi.org/10.1017/S0140525X09000855

Morey, R. D., & Rouder, J. N. (2015). *BayesFactor: Computation of bayes factors for common designs.* Retrieved from https://CRAN.R-project.org/package=BayesFactor

Myers, K. M., Vogel, E. H., Shin, J., & Wagner, A. (2001). A comparison of the Rescorla-Wagner and Pearce models in a negative patterning and a summation problem. *Animal Learning & Behavior*, *29*(1), 36–45. https://doi.org/10.3758/BF03192814

O'Doherty, J. P., Dayan, P., Schultz, J., Deichmann, R., Friston, K., & Dolan, R. (2004). Dissociable roles of ventral and dorsal striatum in instrumental conditioning. *Science*, *304*(5669), 452–454. https://doi.org/10.1126/science.1094285

Parkhurst, D., Law, K., & Niebur, E. (2002). Modeling the role of salience in the allocation of overt visual attention. *Vision Research*, *42*(1), 107–123.

Pavlov, I. P. (1927). No Title. In *Conditioned reflexes. An investigation of the*

physiological activity of the cerebral cortex. London.

Pearce, J. M. (1987). A model for stimulus generalization in Pavlovian conditioning. *Psychological Review, 94*(1), 61–73. Retrieved from http://www.ncbi.nlm.nih.gov/pubmed/3823305

Pearce, J. M. (1994). Similarity and discrimination: A selective review and a connectionist model. *Psychological Review, 101*(4), 587.

Pearce, J. M. (2002). Evaluation and development of a connectionist theory of configural learning. *Animal Learning & Behavior, 30*(2), 73–95. https://doi.org/10.3758/BF03192911

Peirce, J. W. (2007). PsychoPy—psychophysics software in Python. *Journal of Neuroscience Methods, 162*(1), 8–13.

Pérez, O. D., San Martín, R., & Soto, F. A. (2018). Exploring the effect of stimulus similarity on the summation effect in casual learning. *Experimental Psychology, 65*(February), 183–200. https://doi.org/10.1027/1618-3169/a000406

R Core Team. (2017). *R: A language and environment for statistical computing.* Vienna, Austria: R Foundation for Statistical Computing. Retrieved from https://www.R-project.org/

Rescorla, R., & Coldwell, S. E. (1995). Summation in autoshaping. *Animal Learning & Behavior, 23*(3), 314–326. https://doi.org/10.3758/BF03198928

Rescorla, R., & Wagner, A. (1972). A theory of Pavlovian conditioning: Variations in the effectiveness of reinforcement and nonreinforcement. *Classical Conditioning II: Current Research and Theory, 2*, 64–99.

RStudio Team. (2015). RStudio: Integrated Development Environment for R. Boston,

MA: RStudio, Inc. Retrieved from http://www.rstudio.com/

Saavedra, M. A. (1975). Pavlovian compound conditioning in the rabbit. *Learning and Motivation, 6*(3), 314–326.

Shepard, R. N. N. (1987). Toward a universal law of generalization for psychological science. *Science.* Retrieved from http://k7moa.com/Shepard{\%}7B{_}{\%}7D1987.pdf http://k7moa.com/Shepard{_}}1987.pdf

Soto, F. A. (2012). *A Category-Overshadowing Effect in Pigeons: Support for the Common Elements Model of Object Categorization Learning.*

Soto, F. A., Gershman, S. J., & Niv, Y. (2014a). Explaining compound generalization in associative and causal learning through rational principles of dimensional generalization. *Psychological Review, 121*(3), 526–558.

Soto, F. A., Gershman, S., & Niv, Y. (2014b). Explaining Compound Generalization in Associative and Causal Learning Through Rational Principles of Dimensional Generalization. *Psychological Review,* 1–117. Retrieved from http://people.psych.ucsb.edu/soto/fabian/docs/PR.14.sgn.pdf

Soto, F. A., Quintana, G. R., Pérez-Acosta, A. M., Ponce, F. P., & Vogel, E. H. (2015). Why are some dimensions integral? Testing two hypotheses through causal learning experiments. *Cognition, 143*, 163–177. https://doi.org/10.1016/j.cognition.2015.07.001

Soto, F. A., Siow, J. Y. M., & Wasserman, E. A. (2012). View-invariance learning in object recognition by pigeons depends on error-driven associative learning processes. *Vision Research, 62*, 148–161. https://doi.org/10.1016/j.visres.2012.04.004

Soto, F. A., Vogel, E. H., Castillo, R. D., & Wagner, A. (2009). Generality of the summation effect in human causal learning. *Quarterly Journal of Experimental Psychology*

(2006), *62*(5), 877–889. https://doi.org/10.1080/17470210802373688

Soto, F. A., & Wasserman, E. A. (2010). Error-driven learning in visual categorization and object recognition: a common-elements model. *Psychological Review*, *117*(2), 349–381. https://doi.org/10.1037/a0018695

Sutton, R. S., & Barto, A. G. (1998). *Reinforcement learning: An introduction* (Vol. 1). MIT press Cambridge.

Thein, T., Westbrook, R. F., & Harris, J. A. (2008). How the associative strengths of stimuli combine in compound: Summation and overshadowing. *Journal of Experimental Psychology: Animal Behavior Processes*, *34*(1), 155–166. https://doi.org/10.1037/0097-7403.34.1.155

Thorwart, A., Livesey, E. J., & Harris, J. A. (2012). Normalization between stimulus elements in a model of Pavlovian conditioning: Showjumping on an elemental horse. *Learning & Behavior*, *40*(3), 334–346.

Treisman, A. (1985). Preattentive processing in vision. *Computer Vision, Graphics, and Image Processing*, *31*(2), 156–177. https://doi.org/10.1016/S0734-189X(85)80004-9

Treisman, A. (1988). Features and objects: The fourteenth bartlett memorial lecture. *The Quarterly Journal of Experimental Psychology*, *40A*(2), 201–237.

Treisman, A. M., & Gelade, G. (1980). A feature-integration theory of attention. *Cognitive Psychology*, *12*(1), 97–136.

Vogel, E. H., Glynn, J. Y., & Wagner, A. (2015). Cue competition effects in human causal learning. *The Quarterly Journal of Experimental Psychology*, (May 2015), 1–24. https://doi.org/10.1080/17470218.2015.1014378

Wagner, A. (2008). Evolution of an elemental theory of Pavlovian conditioning.

Learning & Behavior, 36(3), 253–265. https://doi.org/10.3758/LB.36.3.253

Wagner, A., & Rescorla, R. (1972). Inhibition in pavlovian conditioning: Application of a theory. *Inhibition and Learning*, 301–336.

Wasserman, E. A., & Anderson, P. A. (1974). Differential autoshaping to common and distinctive elements of positive and negative discriminative stimuli. *Journal of the Experimental Analysis of Behavior, 22*(3), 491.

Wickham, H. (2009). *Ggplot2: Elegant graphics for data analysis.* Springer-Verlag New York. Retrieved from http://ggplot2.org

Wickham, H., Francois, R., Henry, L., & Müller, K. (2017). *Dplyr: A grammar of data manipulation.* Retrieved from https://CRAN.R-project.org/package=dplyr

Wolfe, J. M. (2018). Visual Search. In J. T. Serences (Ed.), *Stevens' Handbook of Experimental Psychology and Cognitive Neuroscience* (Vol. 2, pp. 1–55). Hoboken, NJ: John Wiley & Sons. https://doi.org/10.1002/9781119170174.epcn213