Bayesian transfer in a complex spatial localisation task

Reneta Kiryakova[1], Stacey Aston[1], Ulrik Beierholm[1], Marko Nardini[1]

[1]*Psychology Department, Durham University, UK*

Abstract

Prior knowledge can help observers in various situations. Adults can simultaneously
learn two location priors and integrate these with sensory information to locate
hidden objects. Importantly, observers weight prior and sensory (likelihood)
information differently depending on their respective reliabilities, in line with
principles of Bayesian inference. Yet, there is limited evidence that observers
actually perform Bayesian inference, rather than a heuristic, such as forming a look-
up table. To distinguish these possibilities, we ask whether previously-learnt priors
will be immediately integrated with a new, untrained likelihood. If observers use
Bayesian principles, they should immediately put less weight on the new, less
reliable, likelihood ("Bayesian transfer"). In an initial experiment, observers estimated
the position of a hidden target, drawn from one of two distinct distributions, using
sensory and prior information. The sensory cue consisted of dots drawn from a
Gaussian distribution centred on the true location with either low, medium, or high
variance; the latter introduced after block three of five to test for evidence of
Bayesian transfer. Observers did not weight the cue (relative to the prior)
significantly less in the high compared to medium variance condition, counter to
Bayesian predictions. However, when explicitly informed of the different prior
variabilities, observers placed less weight on the new high variance likelihood
("Bayesian transfer"), yet substantially diverged from ideal. Much of this divergence
can be captured by a model that weights sensory information, according only to
internal noise in using the cue. These results emphasise the limits of Bayesian
models in complex tasks.

Keywords: Bayesian transfer, sensorimotor estimation, decision-making, Bayesian

models

Imagine that you are trying to give your cat a bath, but as soon as it sees the

bathtub, it gets scared and runs away to the garden (Kording et al., 2007; Vilares &

Kording, 2011). So, you are walking around your garden, trying to figure out where

your cat has hidden, and you hear a "meow" *(auditory cue)*. This perceptual cue is

useful but not perfectly reliable and will not allow you to pinpoint exactly the cat's

position. However, from previous experience, you may have learnt that your cat often

hides in the bushes, furthest from the pond *(priors)*. The uncertainty in the two pieces

of information that you have (the auditory cue and the prior information) allow them

to be expressed as probability distributions over location and the optimal strategy for

estimating the cat's location is to integrate the sensory and prior information

according to the rules of Bayesian Decision Theory (BDT). Recent studies show that

people behave as if they deal with uncertainty in this way, for example, when

estimating the position of a hidden target (Berniker, Voss, & Kording, 2010; K.P.

Körding & Wolpert, 2004; Tassinari, Hudson, & Landy, 2006; Vilares, Howard,

Fernandes, Gottfried, & Kording, 2012), direction of motion (Chalk, Seitz, & Series,

2010), speed (Stocker & Simoncelli, 2006; Weiss, Simoncelli, & Adelson, 2002), or

the duration of a time interval (Acerbi, Wolpert, & Vijayakumar, 2012; Ahrens &

Sahani, 2011; Jazayeri & Shadlen, 2010; Miyazaki, Nozaki, & Nakajima, 2012). In all

of these studies, human observers integrated knowledge of the statistical structure of

the experiment (acquired from feedback in previous trials) with sensory information,

taking a weighted average according to their relative reliabilities in order to maximise

his or her score on the task (Ma, 2012). However, other studies report sub-optimal

behaviour, finding that even though observers take into account the uncertainty of

the current and prior information, the weights do not match those of an ideal

Bayesian observer (Bowers & Davis, 2012; Jones & Love, 2011; Rahnev & Denison,

2018). The fact that human performance ranges from close-to-optimal to largely

suboptimal suggests that Bayesian models may describe behaviour well in some

cases, but not in others. Understanding when BDT can and cannot provide an

accurate model of human behaviour is an important step towards understanding the

computations and approximations used by the brain to support adaptive behaviour.

One factor that may influence how close performance is to BDT ("optimal")

predictions is task complexity. For example, Bejjanki, Knill, and Aslin (2016) asked

observers to estimate the position of an unknown target (a bucket at a fairground),

whose true location was randomly drawn from one of two Gaussian distributions,

with different means and variances (*priors*). On each trial, eight dots were drawn

from a Gaussian distribution centered on the true location with either a low, medium

or high variance to form a dot cloud that served as a noisy cue to target location

(*likelihoods*). To successfully estimate the position of the target, subjects could use

both the likelihood, obtained from the displayed dots, and the prior, obtained from the

distribution of previous target positions that they could learn from the trial-by-trial

feedback. The study found that subjects adjusted their responses according to the

reliability of sensory and prior information, giving more weight to the centroid of the

dot cloud (likelihood) when the variance of the prior was high and the variance of the

likelihood was low; a signature of probabilistic inference (Ma, 2012). More generally,

these results are also in agreement with previously described work, which used *a*

single prior change (e.g., Berniker et al., 2010; Vilares et al., 2012). However, unlike

in the studies using only a single prior change, the weight placed on the likelihood

differed from that of the ideal-Bayes observer whenever the likelihood uncertainty

was medium or high. The magnitude of the difference varied with both likelihood and

prior uncertainty. As the likelihood became more uncertain, the difference from

optimal increased, participants placing more weight on the likelihood than optimal. In

addition, the difference from optimal was greater in the narrow prior condition. In a

follow-up experiment, participants experienced one prior distribution only, with

double the amount of trials used in the original study, finding that subjects' weights

on the likelihoods approach optimal with increasing task exposure, suggesting more

time is required to accurately learn the variances of the prior distributions and that

learning is disrupted when trying to learn two distributions simultaneously (Bejjanki et

al., 2016).

Even in cases when likelihood-weighting might match the prediction of an

ideal-Bayes observer, Maloney and Mamassian (2009) noted that such "optimal" or

"near-optimal" performance alone is not enough to show that the brain is following

Bayesian principles. Maloney and Mamassian (2009) showed that a reinforcement-

learning model that learns a mapping from stimulus to response (learning a separate

look-up table for each prior and likelihood pairing in the types of tasks discussed

here) will also appear to optimally weight prior and likelihood information without
learning the individual probability distributions.

Maloney and Mamassian (2009) suggested that the two models may be
distinguished by asking whether subjects are able to immediately transfer
probabilistic information from one condition to another (hereafter known as *Bayesian*
transfer). These transfer criteria are a strong test for use of Bayesian principles
because they make very different predictions for how the observer will behave when
presented with a new level of sensory noise halfway through the task. If people
follow Bayesian principles, we would expect them to *immediately* adapt to the new
sensory uncertainty, and integrate it with an already-learnt prior, without any need for
feedback-driven learning. On the other hand, the reinforcement-learner would
require a certain amount of exposure to the new likelihood and prior pairing (with
feedback) in order to form a look-up table that could then lead to optimal
performance.

To our knowledge, only one study has tested Bayesian transfer in the context
of sensorimotor learning. Sato and Kording (2014) tested the ability of participants to
generalise a newly learnt prior to a previously learnt likelihood. In their task, Sato and
Kording (2014) first trained participants to complete the task when only a single
Gaussian prior was present (either narrow or wide) that could be paired with either a
low or high uncertainty likelihood by giving feedback on every trial. After 400 trials,
the prior switched to the other level of uncertainty (narrow to wide or wide to narrow)
and for the following 200 trials, participants saw the new prior paired only with one of
the likelihoods (either low or high) and continued to receive feedback. In the second
part of the experiment, subjects still saw the second prior variability, but now with the
first likelihood again, which they had so far only seen paired with the first prior. They
did not provide any feedback in this part of the task to examine how subjects
transferred their knowledge of the prior to the new likelihood. The weight placed on
the likelihood in the newly-reintroduced likelihood condition was immediately different
to the weight placed on the same likelihood before the change in the prior. In other
words, participants' behaviour in this likelihood condition changed dependent upon
prior uncertainty without any explicit training with this prior and likelihood pairing.
This is evidence of Bayesian transfer and hence, that participants solved the task

using Bayesian principles – representing probabilities – rather than a simpler

strategy such as a look-up table learned by reinforcement.

Whether the same will hold in more complex scenarios is unclear. Indeed, it

has been repeatedly pointed out that exact Bayesian computations demand

considerable computational resources (e.g., working memory, attention) such that

the brain might not be able to perform these computations in more complex tasks

and will instead resort to heuristics (Beck, Ma, Pitkow, Latham, & Pouget, 2012;

Gardner, 2019). We have already seen that performance in more complex tasks is

far from optimal (e.g., Bejjanki et al., 2016), suggesting that there are limits to

humans' ability to learn and optimally integrate prior distributions with sensory

information when tasks become more complex. Establishing the limits of BDT as a

model of human behaviour will inform models of information processing in the human

brain.

Here we ask whether people will show Bayesian transfer in a complex

situation with multiple priors and likelihood variances, similar to Bejjanki et al. (2016).

We report three experiments in which a target is sampled from one of two possible

prior distributions (with different means and different variances) and then cued with

one of three possible likelihood variances (with the variance itself also displayed).

Likelihood and prior variances were identical to those used in Bejjanki et al. (2016) in

terms of visual angle, in order to match the true (objective) reliabilities of the cue and

prior across the studies. The first two experiments tested for Bayesian transfer by

only introducing the high likelihood variance in blocks 4 and 5 of the task. The only

difference was that in the second experiment, participants were explicitly told that the

prior variances differed, to test whether this would promote closer-to-optimal

performance. The last experiment was used to check whether removing the

additional burden of transfer allows participants to learn the complex environment

correctly by presenting all likelihood conditions from the start of the experiment – a

replication of Bejjanki et al. (2016).

To summarise, in the first experiment, we found that observers did not show

evidence for Bayesian transfer. When a new high variance likelihood was introduced

in blocks 4 and 5, they did not weight it less than the familiar medium variance

likelihood. This is at odds with the idea that observers perform full Bayesian

inference, combining prior and likelihood based on relative variances, and thus does

not provide evidence for Bayesian transfer. In the second experiment, observers did

show evidence for transfer, weighting the newly-introduced high variance likelihood

significantly less than the medium variance likelihood. However, in both experiments,

the weights placed on the medium and high variance likelihoods were much higher

than optimal. These weights remained sub-optimal in the final experiment where all

likelihood variances were present from the start of the task. These results extend our

knowledge of how potentially-Bayesian perceptual processes function in complex

environments.

Experiment 1: Testing transfer to a new level of likelihood variance

In the first experiment, we tested whether Bayesian transfer would occur in a

complex environment with two priors, similar to the one used by Bejjanki et al.

(2016). We trained participants on a spatial localization task with two likelihood

variances and two prior distributions (with different means and variances). In initial

training, they were exposed to all four combinations (trials interleaved), with

feedback. If, like participants in Bejjanki et al. (2016), they weighted the likelihood

and the prior differently across conditions in line with their differing reliabilities, this

would show that they had learned and were using the priors. However, such

reliability-weighting could either be done via Bayesian inference – representing

probabilities – or via a simpler strategy akin to learning a look-up table (Maloney &

Mamassian, 2009). To distinguish these possibilities, after the training trials, we

tested for "Bayesian transfer" by adding a new higher-variance likelihood distribution

to the task. If participants deal with this newly-introduced likelihood in a Bayesian

manner, they should immediately rely less on this new likelihood information than

they did on the likelihoods in previously-trained conditions. Alternatively, if their initial

learning is more rote in nature (i.e., more like a look-up table), participants would

begin to place a different weight on the new likelihood only after extensive training

with feedback.

Methods

Overview

Subjects performed a sensorimotor decision-making task on a computer

monitor where they estimated the horizontal location of a hidden octopus. The true

location was sampled from one of two distinct Gaussian distributions that differed in

mean and variance (narrow or wide priors). On each trial, the relevant prior

distribution was indicated by the colour of the likelihood information - eight dots that

were described to the participant as the "tentacles" of the octopus. The horizontal

locations of the eight dots were sampled from a Gaussian distribution centred on the

true location that had either low, medium, or high variability (the likelihood). To

estimate the octopus' position, participants could use (although this was never

explicitly mentioned) both the likelihood and prior information, with the subjects able

to learn the latter via trial-to-trial feedback. Participants completed five blocks of

trials. Crucially, in blocks one to three only the low and medium likelihood variances

were paired with the narrow or wide priors. The high likelihood condition was only

introduced in blocks four and five to test for evidence of Bayesian transfer.

Participants

Participants were recruited from the Durham Psychology department

participant pool, Durham University newsletter, and by word-of-mouth. Twenty-six

participants were recruited in total (13 female, mean age: 20.1, age range: 18-30

years). All participants had normal or corrected-to-normal visual acuity, and no

history of neurological or developmental disorders. Each participant received either

course credits or a cash payment of £10 for their time.

Ethics

Ethical approval was received from the Durham University Psychology

Department Ethics Board. All participants gave written, informed consent prior to

taking part in the study.

Stimuli and apparatus

Stimuli were displayed on a 22-inch iiyama monitor (1680 x 1050 pixels),

viewed at a distance of 60cm, using the Psychophysics Toolbox for MATLAB

(Brainard, 1997; Kleiner et al., 2007; Pelli, 1997). The stimuli were set against a blue

background (to represent the sea).

The position of the octopus was sampled from one of two Gaussian

distributions (priors): the narrow (standard deviation of $\sigma_{pl} = 1\%$ of screen width) or

wide (standard deviation of $\sigma_{ph} = 2.5\%$ of screen width) priors. The side of the

screen associated with each prior was counterbalanced across participants. One

was always 35% of the way across the screen (from left to right), and the other 70%.

When the narrow prior was centered on 35%, for example, the wide prior had a

mean in the opposite side of the screen (i.e., to the right, centered on 70%). When

the octopus appeared on the left hand side (drawn from the prior centered on 35%) it

was white, and when it appeared on the right (drawn from the prior centered on 70%)

it was black.

At the beginning of each trial, a cloud of eight dots (0.5% of screen width in

diameter) appeared on the screen. The horizontal position of each dot was drawn

from a Gaussian distribution centered on the true octopus location with either low

($\sigma_{ll} = 0.6\%$ screen width), medium ($\sigma_{lm} = 3\%$ screen width), or high ($\sigma_{lh} = 6\%$

screen width) standard deviation (in the following referring to as low, medium and

high variance likelihood conditions). The horizontal positions of the dots were scaled

so that their standard deviation (SD) was equal to the true SD (σ_{ll}, σ_{lm} or σ_{lh}) on

each trial while preserving the mean of the dots. We performed this correction so

that participants would "see" the same variability across trials for each likelihood

condition. This ensures that an observer who computes the reliability for the

likelihood information trial by trial would always calculate the same value within

likelihood trial types. The vertical positions of the dots were spaced at equal intervals

from the vertical center of the screen, with half of the dots appearing above, and the

other half, below the center. The vertical distance between each dot was fixed and

equal to 1% screen width). Given that the vertical positions of the dots were fixed,

only the horizontal position of the target was relevant. Participants estimated location

only along the horizontal axis by moving a vertical green rectangle (measuring 1% of

screen width in width and 3% of screen width in height) left or right, making this a

one-dimensional estimation task. Participants received feedback in the form of a red

dot (0.5% of screen width in diameter) that represented true target position.

The combination of two priors and three likelihoods led to six trial types (all

possible prior x likelihood pairings). The task was split into five blocks of trials with

300 trials per block. In the first three blocks of the task only four trial types were used

(75 trials of each paring), with the high likelihood condition not shown in combination

with either prior. The high likelihood condition was introduced in blocks four and five

(50 trials per paring), in order to test for Bayesian transfer. Within each block, all trial

types were interleaved. The trials were broken into runs of 20 trials. Within each run

the trials for each prior type were arranged such that an ideal learner would have an

exact estimate of the mean and variance of the prior distributions if evidence was

accumulated over those 20 trials.

We also included prior-only trials where subjects were told that a black/white

octopus was hiding somewhere on the screen and instructed to find it. No sensory

information was provided (no likelihood information). These trials were interleaved

with the rest of the trials (one every 9 trials for each prior), and there were 83 trials in

total, for each of the priors (narrow and wide).

Procedure

Participants were instructed to estimate the position of a "hidden" octopus,

indicating their estimate by adjusting the horizontal location of a "net" (green

rectangle). Each trial started with the presentation of eight dots that remained on

screen until the end of the trial (the likelihood information, described to the

participants as the tentacles of the octopus) (Figure 1A). The eight dots could have

one of three levels of uncertainty: low, medium, or high variance likelihood trials

(Figure 1B). When the level of uncertainty was higher, the dots were more dispersed

on the screen and, therefore, were a less reliable indicator of the true location of the

octopus. Participants used the mouse to move the net to their guessed position,

using a right click to confirm their choice (no time limit). Following a response, the

true position of the octopus was shown as a red dot on the screen. Over the course

of the experiment, the feedback served as a second cue to location since the true

locations of the black and white octopi were drawn from different distributions. In

other words, participants could learn a prior over each octopus' location. We

provided performance feedback on a trial-to-trial basis so that the priors could be

learned. Specifically, subjects could potentially learn that the two sets of octopi

(black/white) were drawn from separate Gaussian distributions centred at different

locations on the screen and with differing levels of uncertainty (narrow and wide

variance prior trials).

Figure 1. A) Illustration of the task. Participants were asked to estimate the position

of a hidden target (the "octopus", represented as the red dot) by horizontally moving

a net (green vertical bar). At the beginning of each trial, participants were given noisy

information about the location of the hidden target in the form of eight dots (the

likelihood). Participants then moved the net to the estimated location and clicked to

confirm their response, after which the actual target location was displayed. If the

target was inside, or overlapped with, the net, a score was added to the participant's

score. B) The three likelihood variances. C) Illustration of a Bayes-optimal observer.

A Bayesian observer would combine information about the prior uncertainty (learnt

from the distribution of previous target locations) with the likelihood information on a

given trial to optimally estimate the target location.

To keep participants engaged, we incorporated an animation when the

participant picked the right location of a cartoon octopus moving into a bucket

centred at the bottom of the screen. In addition, participants would get one point

added to their score if they "caught" the octopus. An octopus was caught if the true

octopus position overlapped with the net placement by at least 50% of the red

feedback dot's size. The cumulative score was displayed at the end of each trial.

Participants completed 5 blocks of 300 trials each for a total of 1500 trials. The five

experimental blocks were performed in succession with a short break between each

one. The experiment duration was approximately an hour and a half.

Data Analysis

For each individual participant, we regressed estimated octopus position

against the centroid (mean) of the cloud of dots (likelihood) on each trial. All

regression analyses were done using a least squares procedure (the polyfit function

in MATLAB). The slope of the fitted regression line quantifies the extent to which

participants rely on the current sensory evidence (likelihood), as opposed to prior

information. A slope of one suggests that participants only use likelihood information

and a slope of zero suggests that participants rely only on their prior knowledge,

ignoring the likelihood. A slope between zero and one suggests that both likelihood

and prior information are taken into account, and the steeper the slope, the more

participants rely on the likelihood and less on the prior information. Accordingly, we

will refer to the fitted slope values as the weight placed on the likelihood.

We also computed the weight that would be given to the likelihood in each

condition by an ideal Bayesian observer with perfect knowledge of the prior and

likelihood distributions (see Figure 1C for an illustration). The optimal weight on the

likelihood was computed as:

353
$$w_{optimal} = \frac{\dfrac{1}{\sigma_l^2/n}}{\dfrac{1}{\sigma_l^2/n} + \dfrac{1}{\sigma_p^2}}$$

where σ_l^2 is the variance of the likelihood, n is the number of dots that indicate the

likelihood (in this case, there were 8 dots), and σ_p^2 is the variance of the prior.

Statistical differences were analysed using repeated-measures ANOVA with a

Greenhouse-Geisser correction (Greenhouse & Geisser, 1959) of the degrees of

freedom in order to correct for violations of the sphericity assumption if $\epsilon \leq 0.75$ and

a Huynh-Feldt correction otherwise.

We discarded a trial from analysis if the absolute error for that trial was in the

top 1% of all absolute errors, computed separately for each prior and likelihood

pairing across all blocks and participants (this rule excluded at most 13 trials per

pairing for an individual subject).

Results and Discussion for Experiment 1

We first checked whether subjects took the mean as an estimate from the

sensory cue, and not a heuristic, such as the robust average. In tasks similar to ours

(Bejjanki et al., 2016; Chambers, Gaebler-spira, & Kording, 2018; Vilares et al.,

2012), authors assume that observers use the mean of the dots as their best

estimate of true location from the likelihood information. However, we did not

explicitly tell our participants how the eight dots that formed the likelihood were

generated, or that the best estimate they could take from them was their mean

position, leaving open the possibility that observes may have taken a different

estimate from the cue than the mean (de Gardelle & Summerfield, 2011; Van Den

Berg & Ma, 2012). The mean horizontal position was found to explain the most

amount of variance in participants' responses ($R^2 = 0.996$), relative to the robust

average ($R^2 = 0.995$), median ($R^2 = 0.995$) or the mid-range of the dots ($R^2 =$

0.992). This suggests that the mean of the dots is the estimate that participants take

from the sensory cue.

We then examined whether the weight participants placed on the likelihood,

relative to the prior, varied with respect to trial type (prior/likelihood pairing) for all the

trial types present from the beginning of the experiment. Without this basic result – a

replication of the pattern found by Bejjanki et al. (2016) – we could not expect them

to transfer knowledge of the learnt prior distributions to the new high variance

likelihood in the later blocks. This was a qualified success: for these trial types (blue

and green bars in Figure 2), participants showed the predicted pattern, but placed

more weight on the likelihood than is optimal (compare bar heights to dashed lines in

Figure 2), in line with previous research (Bejjanki et al., 2016; Tassinari et al., 2006).

We conducted a 2 (narrow versus wide variance prior) x 2 (low versus medium

variance likelihood) x 5 (block) repeated measures ANOVA with the weight given to

the likelihood (the displayed dots) as the dependent variable. These results are

shown in Table 1 and summarised here. There was a main effect of prior variance,

with less weight on the likelihood when the prior was narrower ($p < .001$). There

was also a main effect of likelihood variance ($p < .001$), where participants relied

less on the medium variance likelihood. However, there was also a significant

interaction effect of likelihood and prior ($p = .001$). When the prior was narrow, the

decrease in reliance on the likelihood was smaller as the likelihood variance

increased ($t(25) = 3.57, p = .001$).

We found a main effect of block ($p < .001$) and an interaction between block

and likelihood ($p = .014$), with the medium variance likelihood weighted significantly

differently across blocks (simple main effect of block, $F(4,100) = 5.84, p <$

$.001, \eta^2_{partial} = .189$, weights decrease with increasing exposure), but not the low

variance likelihood (no simple main effect of block, $F(4,100) = 1.64, p =$

$.169, \eta^2_{partial} = .063$). This suggests that participants adjusted, through practice, their

weights on the medium variance likelihood, getting closer to optimal.

Figure 2. Mean weight placed on the likelihood information, separated by block and prior width in Experiment 1. Lower values represent a greater weight on the prior. Blue is low-variance likelihood (a tight array of dots), green is medium-variance likelihood (dots somewhat spread out), red is the later-introduced high-variance likelihood (highly spread out dots). Dashed lines show optimal-predicted values. Error bars are +/- 1 SEM. The far right is the average over blocks.

420   Table 1

421   *Results from a 2 (prior) x 2 (likelihood) x 5 (block) Repeated Measures ANOVA for*

422   *the likelihood variances present from the beginning of the task (low and medium) in*

423   *Experiment 1*

	F	*df, df*error	p	Effect size (η_p^2)
Likelihood	104.40	1, 25	<.001	.81
Prior	28.08	1, 25	<.001	.53
Block	7.72	4, 100	<.001	.24
Likelihood x prior	12.77	1, 25	.001	.34
Likelihood x block	3.32	4, 100	.01	.12
Prior x block	.51	4, 100	.21	.06

Examination of the prior-only trials shows successful learning of the priors. On

average, subjects' responses were not significantly different from the prior mean in

the wide prior condition ($t(25) = -0.77, p = .450$). They were significantly different in

the narrow prior condition ($t(25) = -2.78, p = .010$), although the bias was extremely

small (95% CI: [0.06,0.41] percent of the screen width to the left). The median

standard deviation of responses for all subjects was 1.4% (narrow prior) and 2.5%

(wide prior): almost identical to the true prior SDs of 1.3% and 2.5%, respectively.

Participants qualitatively followed the predicted optimal pattern of reweighting:

like the dashed lines (predictions) in Figure 2, actual likelihood weights (bars) were

higher for the wide prior (right) than the narrow prior (left), and higher for the low

variance likelihood (blue) than the medium variance likelihood (green). However,

comparing bar heights with dashed lines (predictions) shows that quantitatively, their

weights were far from optimal. Participants systematically gave much more weight

than is optimal to the likelihood when its variance was medium (Figure 2, green bars

vs lines $- p < .001$ in all blocks for the medium likelihood when paired with either

prior). This over-reliance on the likelihood is in line with previous studies (e.g.,

Bejjanki et al., 2016), although stronger in the present study. Participants, therefore,

accounted for changes in the probabilities involved in the task (e.g., weighted the

likelihood less when it was more variable), but did not perform exactly as predicted

by the optimal strategy.

Having found that participants' performance was in line with the predicted

patterns, we could then ask if they would generalise their knowledge to the new high

likelihood trials added in blocks 4-5 ("Bayesian transfer"), as predicted for an

observer following Bayesian principles. This should lead immediately to a lower

weight for the new high variance likelihood than the familiar medium variance

likelihood. By contrast, lack of a significant difference in weights between the

medium and high likelihood trial types would suggest that the observer is employing

an alternative strategy, such as simply learning a look-up table. To test this, we

performed a 2 (prior) x 3 (likelihood) x 2 (block) repeated measures ANOVA

(summarise only blocks 4 and 5 – those with all likelihoods present). These results

are shown in Table 2 and summarised here. As above, we found a main effect of

likelihood, participants placing less weight on the likelihood as it became more

uncertain ($p < .001$). However, post-hoc analyses showed that the weight placed on

the high likelihood was not significantly lower than the weight placed on the medium

likelihood ($p = .103$). Only the comparison of the weights placed on the likelihood in

low and high variance trial types was significant ($p < .001$). Moreover, there was no

main effect of block ($p < .28$), nor an interaction between block and likelihood ($p =$

.48), suggesting that the weight placed on the newly introduced likelihood variance

did not decrease with increasing exposure.

Finally, we compared mean weights in block 5 against the optimal Bayesian

values for each prior and likelihood pairing. In the low variance likelihood trials we

did not observe significant deviation from the Bayesian prediction, irrespective of

prior (low variance likelihood, narrow prior: $t(25) = .784, p = .440$); low variance

likelihood, wide prior: $t(25) = -1.12, p = .270$). Subjects' weights differed

significantly from optimal in all other conditions ($p < .001$ in all cases).

Overall, our results do not exactly match the predictions of a Bayesian

observer because we find only weak evidence of Bayesian transfer. Specifically,

while we find a main effect of likelihood, the weight on the high variance likelihood is

not significantly different to that placed on the medium variance likelihood (although

the change is in the predicted direction). That said, our results are not simply more

consistent with a rote process, since the weight placed on the high likelihood does

not decrease with increasing exposure (no interaction between likelihood and block).

Table 2

Results from a 2 (prior) x 3 (likelihood) x 2 (block) Repeated Measures ANOVA for

all likelihood variances in Experiment 1

	F	df, df_{error}	p	Effect size (η_p^2)
Likelihood	50.08	2, 50	<.001	.67
Prior	15.52	1, 25	.001	.38
Block	1.21	1, 25	.28	.05
Likelihood x prior	2.39	1.62, 40.41	.10	.09
Likelihood x block	.75	2, 50	.48	.03
Prior x block	4.35	1, 25	.05	.15

Our results point mostly away from a simple variance weighted Bayesian

model being a good model of human behaviour in this particular task. The correct

pattern of weights was present, but evidence of transfer was weak. Participants were

also significantly sub-optimal, overweighting the likelihood whenever its variance was

medium or high. Previous studies have also found that observers give more weight

to the sensory cue than is optimal (e.g., Bejjanki et al., 2016); even so, the level of

sub-optimality that we observe here is still drastically higher, compared to previous

reports. However, Sato and Kording (2014) found better, near-optimal performance

in those participants who were told that the sensory information can have one of two

levels of variance, and that the variance will sometimes change, compared to those

who were not provided with this information. We therefore reasoned that if observers

are given additional information about the structure and statistics of the task (e.g.,

that the variances of the prior distributions are different), the weight they give to the

sensory cue may move closer to optimal. If we find weights closer to optimal, we

may be better able to detect whether transfer had taken place because the effect

size of a change in the likelihood would be bigger. In fact, we wonder whether the

size of this effect could be an important factor behind the lack of significant

differences observed in Experiment 1, i.e., that the effect size of the change from

medium to high likelihood was too small for our statistical analysis to reliably detect.

In view of this, we set out to test whether additional instructions will lead to weighting

of likelihood and prior information that is closer to optimal.

Experiment 2: Additional instructions about prior variance

Experiment 2 was identical to Experiment 1 except for a change in

instructions. In this experiment, subjects were explicitly (albeit indirectly) informed of

the different variances of the prior. We hypothesised that giving participants

additional information about the model structure of the task will move weights closer

to optimal and make any transfer effects more pronounced.

Methods

Twelve participants (8 female, mean age: 20.3, age range: 19-22 years)

participated in Experiment 2. All participants had normal or corrected-to-normal

visual acuity, no history of neurological or developmental disorders and had not

taken part in Experiment 1. Each participant received either course credits or cash

compensation for their time.

The experimental set had the same layout as the main experiment, with the

following difference: in addition to the previously described instructions, subjects in

this version of the task were told that "it is important to remember that one of the

octopuses tends to stay in a particular area, whereas the other one moves quite a

bit!" (i.e., they were indirectly informed that the variances of the priors were different).

(see Appendix A for full instructions).

Results and Discussion for Experiment 2

Similarly to what we saw in Experiment 1, the mean and robust average of the

dots explained the same amount of the variance in participants' responses ($R^2 =$

0.991 for both), followed by the median ($R^2 = 0.990$) and the mid-range ($R^2 = 0.989$).

We, thus, proceed with the mean as the estimate from the likelihood.

Figure 3 shows that the pattern of results was qualitatively similar to those of

Experiment 1 (see Figure 2). A 2 (prior) x 2 (likelihood) x 5 (block) repeated

measures ANOVA (analysing only the low and medium likelihood trials) revealed that

subjects placed less weight on the likelihood as its uncertainty increased (main effect

of likelihood, $p < .001$) and as the prior uncertainty decreased (main effect of prior,

$p = .002$). However, unlike in Experiment 1, there was no significant interaction of

these factors ($p = .123$) (see Table 3).

Figure 3. Mean weight placed on the likelihood information in each block of

Experiment 2. Blue is the low-variance likelihood, green is the medium-variance

likelihood, red is the high-variance likelihood. Dashed lines show optimal values.

Error bars are +/- 1 SEM. The far right is the average over blocks.

We found a main effect of block ($p = .02$) and an interaction between block

and likelihood ($p = .01$), with participants weighting the likelihood significantly less

with increasing task exposure (regardless of prior) when its variance was medium

($F(2.21,25.34) = 3.81, p = .03, \eta_p^2 = .257$, with a Greenhouse-Geisser correction),

but not when it was low ($F(4,44) = 0.70, p = .60, \eta_p^2 = .060$).

Table 3

Results from a 2 (prior) x 2 (likelihood) x 5 (block) Repeated Measures ANOVA for

the likelihood variances present from the beginning (low and medium) in Experiment

2

	F	df, df$_{error}$	p	Effect size (η_p^2)
Likelihood	46.14	1, 11	<.001	.81
Prior	17.28	1, 11	.002	.61
Block	3.15	4, 44	.02	.22
Likelihood x prior	2.80	1, 11	.12	.20
Likelihood x block	3.73	4, 44	.01	.25
Prior x block	1.32	2.07, 22.77	.29	.11

As before, we analysed subjects' responses in the prior-only trials, finding a

good quantitative agreement with the true prior mean (narrow prior: $t(11) =$

$-0.002, p = .999$; wide prior: $t(11) = 0.35, p = .734$). The median standard

deviation (SD) of responses was also remarkably similar to the true prior SDs

(narrow prior: 1.6% vs. 1.3% in screen units; wide prior: 2.5% for both).

Again, subjects' overall performance was suboptimal (as can be seen by

comparing the height of the bars against the dashed lines – the optimal predictions –

in Figure 3). Subjects' placed more weight on both the medium and high variance

likelihoods than is optimal ($p < .001$ in both cases, for both priors). However, it is

worth noting that the weights placed on the medium and high likelihoods are closer
to optimal than they were in Experiment 1 (compare bar heights in Figure 2 and 3).

Finally, we tested for transfer to the newly-introduced high likelihood in blocks
4-5. We conducted a 2 (prior) x 3 (likelihood) x 2 (block) repeated measures ANOVA
(analysing only blocks 4 and 5 with all likelihoods present). These results are shown
in Table 4 and summarised here. There was a main effect of likelihood, with less
weight placed on the likelihood as it became more uncertain ($p < .001$). Unlike in
Experiment 1, post-hoc analysis showed that the weight placed on the high likelihood
was significantly lower than the weight placed on the medium likelihood ($p = .034$).
The weights placed on the likelihood in the low variance trial type were significantly
lower than those in the medium and high variance trial types ($p < .001$ for both).
Moreover, there was no main effect of block ($p < .64$), or an interaction effect of
block and likelihood ($p < .15$), meaning that the weight placed on the newly-added
likelihood information did not vary with increasing exposure.

Again, we find a significant difference between subjects' weights (in block 5)
and optimal predictions when the likelihood variance was medium or high ($p < .001$
in both cases), but not when it was low, irrespective of prior variance (low likelihood,
narrow prior: $t(11) = .120, p = .907$); low likelihood, wide prior: $t(11) = -1.29, p = $
$.163$).

In line with our prediction of transfer, here we show that the observers put
lower weight on the high variance likelihood than the medium variance likelihood
they have experienced before. This is strengthened by the fact that participants'
weights did not change significantly with increasing exposure across blocks 4-5.

590   Table 4

591   *Results from a 2 (prior) x 3 (likelihood) x 2 (block) Repeated Measures ANOVA for*

592   *all likelihood variances in Experiment 2*

	F	df, df_{error}	p	Effect size (η_p^2)
Likelihood	37.98	2, 22	<.001	.78
Prior	18.36	1, 11	.001	.63
Block	.23	1, 11	.64	.02
Likelihood x prior	1.80	2, 22	.19	.14
Likelihood x block	2.09	2, 22	.15	.16
Prior x block	.17	1, 11	.69	.02

To check more directly for differences due to experimental instructions, we

compared subjects' performance in the last 2 blocks across the two experiments. We

ran a 2 (instructions) x 2 (prior) x 3 (likelihood) x 2 (block) mixed ANOVA. We found

a main effect of instructions ($F(1,36) = 6.78, p = .013, \eta_{partial}^2 = .159$) with subjects

weighting the likelihood significantly less with explicit instructions (Experiment 2), i.e.

closer to the optimal weightings. We also found an interaction between instructions

and likelihood ($F(1,36) = 4.79, p = .011, \eta_{partial}^2 = .118$), indicating that the main

effect of instructions is due to a significant decrease in the weight placed on the high,

relative to the medium likelihood in the explicit instructions (Experiment 2) task, but

not the original task (Experiment 1).

These results show that adding extra instructions to the task that make the

participant aware of a change in uncertainty between the two priors has an effect.

The weights placed on the likelihood moved closer to optimal, and the transfer

criterion was met, which suggests that, perhaps, observers are more likely to adopt a

Bayes-optimal strategy when more explicit expectations about the correct model

structure of the task are set. However, even with the additional instructions, the

weight given to the sensory cue was still systematically higher than the "optimal"

weight. Arguably, expecting people to perform optimally is rather unrealistic, as it

presumes that the observer perfectly knows the environmental statistics. However,

Bejjanki et al. (2016) found performance much closer to optimal than what we have

seen in either of our previous experiments. The major difference between their

experiment and ours' is the fact that Bejjanki et al. (2016) presented all likelihood

variances from the start of the task. Therefore, unlike Experiments 1 and 2, which

were designed in order to provide some evidence of transfer, Experiment 3 sought to

test whether subjects' weights would move closer to optimal if we present all

likelihood variances from the beginning, in a more direct replication of Bejjanki et al.

(2016). The likelihood and prior variance parameters were identical to those used in

Bejjanki et al. (2016), and we used a similar number of trials per prior and likelihood

pairing (250 vs. 200 trials in Bejjanki et al. (2016).

624   **Experiment 3: All likelihoods from the beginning**

Experiment 3 was identical to Experiment 1 (lacking the extra instructions of

Experiment 2) except that all likelihood variances were included from the beginning

of the task. The participants experienced all six trial types in every block.

Methods

Twelve participants (10 female, mean age: 22.6, age range: 19-30 years) took

part in Experiment 3. All participants had normal or corrected-to-normal visual acuity,

no history of neurological or developmental disorders and had not taken part in

Experiment 1 and 2. Each participant received either course credits or cash

compensation for their time.

The stimuli and task were identical to those described for Experiment 1,

except that all likelihood conditions (low, medium and high) were now present from

the beginning (50 trials of each likelihood/ prior pairing interleaved in the same

block).

Results and Discussion of Experiment 3

Again, the mean position of the dots explained the most amount of variance in

participants' responses ($R^2 = 0.990$). The amount of variance explained decreased

for the robust average ($R^2 = 0.989$), median ($R^2 = 0.988$) an the mid-range of the

dots ($R^2 = 0.985$). We, thus, proceed with the mean as the estimate from the

likelihood.

Figure 4 shows a similar pattern of results to Experiments 1 and 2. Again, a 2

(prior) x 3 (likelihood) x 5 (block) repeated measures ANOVA shows that the

likelihood information was weighted less as it became more unreliable (main effect of

likelihood, $p < .001$). Specifically, subjects placed significantly more weight on the

low likelihood than on the medium ($p = .001$) or high likelihood ($p < .001$), and more

weight on the medium likelihood than the high likelihood ($p = .005$). No other main

effects or interactions were significant (see Table 5 for a summary of results).

Figure 4. Mean weight placed on the likelihood information in each block of

Experiment 3. Blue is the low-variance likelihood, green is the medium-variance

likelihood, red is the high-variance likelihood. Dashed lines show optimal values.

Error bars are +/- 1 SEM. The far right is the average over blocks.

Table 5

Results from a 2 (prior) x 3 (likelihood) x 5 (block) Repeated Measures ANOVA for
all likelihood variances in Experiment 3

	F	df, df$_{error}$	p	Effect size (η_p^2)
Likelihood	29.90	2, 22	<.001	.73
Prior	2.74	1, 11	.13	.20
Block	.28	4, 44	.89	.03
Likelihood x prior	2.67	2, 22	.09	.19
Likelihood x block	.52	8, 88	.84	.05
Prior x block	.87	4, 44	.49	.07

For the prior-only trials, subjects' responses were, on average, statistically
indistinguishable from the mean of the wide prior distribution ($t(11) = -1.14, p =$
.278), but were significantly different from the mean of the narrow prior ($t(11) =$
$-3.91, p = .002$) (although we note that the bias was small (95% CI: [0.24,0.87]
percent of the screen width to the left). The median standard deviation (SD) of
responses was 2.2% for the narrow prior condition and 2.6% for the wide prior
condition; the SD of responses was, therefore, only close to the true variance of the
wide prior (which was 2.5%). Together, these findings suggest that subjects had not
learnt either the mean, or the variance of the narrow prior condition. This may
explain the lack of difference in performance between the narrow and wide prior
conditions in this task.

A comparison of subjects' weights on the likelihoods in block 5 against
Bayesian predictions showed a significant difference for all likelihood and prior
pairings ($p < .001$), with the exception of the wide prior/ low likelihood condition
($t(11) = -.362, p = .724$).

To sum up, although the correct pattern of weights was present, subjects
were still substantially sub-optimal, even after experiencing all likelihood variances
from the start of the task.

Accounting for Suboptimality

Even when we replicate Bejjanki et al. (2016) very closely with all likelihoods
from the beginning, our participants are strikingly suboptimal. However, we note that
in our initial calculations of optimal behaviour, we assumed that observers weight
sensory and prior information according only to the variance of the dot distribution
(i.e., external noise). However, many of the studies in the cue combination field that
have found near-optimal performance used cues that only have internal noise, not
external (Alais & Burr, 2006; Körding & Wolpert, 2006). It is, therefore, possible that
our participants are sub-optimal because they fail to take account of external noise,
only weighting the sensory and prior information by the internal variability (i.e., error
intrinsic to them) of the sensory cue. Keeping this is mind, we considered the
predicted weights of a model that only takes into account the internal variability σ_{l_i} in
using the sensory cue.

We performed a separate control experiment to see how good participants
were at finding the centroids of dot clouds in the absence of prior information (see
Appendix B for more details). From this control data, we could calculate observers'
internal noise as their responses were not subject to bias from the prior. For each
participant, their internal variability σ_{l_i} was calculated by taking the standard
deviation of their errors from the centroid of the dots (error = dot centroid -
response). The predicted weight on the sensory cue was then calculated as
$w = \sigma_p^2/(\sigma_{l_i}^2 + \sigma_p^2)$.

We first checked whether the internal noise model provides an improved fit for
the data, compared to the Bayes-optimal model. We found a lower mean squared
error (MSE) for the internal noise model, which confirms that this model is a better fit
(see Figure 5). We also found a regression coefficient R^2 of 0.602 between actual
and predicted (according to subjects' internal noise) weights. This suggests that
those individuals who had low internal noise weighted the likelihood more. Therefore,
it seems that participants are not simply under-accounting for the total noise in the
stimuli; rather, it is internal noise that they are paying particular attention to.

Figure 5. Average Mean Squared Error (MSE) for standard Bayesian model and internal noise model.

To further analyse these results, we compared subjects' weights (block 5, Experiment 1) with those predicted when only weighting by internal noise, and found that they were significantly different for all likelihood and prior pairings ($p < .01$). Indeed, Figure 6 shows that the internal noise model still predicts less weight on the sensory cue than we see in our data (compare bars and dotted lines). This could reflect participants downweighing the prior because it is, in fact, subject to additional internal noise, stemming from a need to remember and recall the correct prior from memory. Even so, empirical weights were closer to the internal noise predictions, compared to those, predicted by the optimal strategy (with experimentally-controlled cue variance, dashed lines).

Figure 6. Mean weight placed on the likelihood information in each block of Experiment 1. Blue is the low-variance likelihood, green is the medium-variance likelihood, red is the high-variance likelihood. Dashed lines show optimal values. Dotted lines show predicted weights when only weighting by internal noise. Error bars are +/- 1 SEM.

Finally, we examined the predictions for an observer model that weights sensory information, according to overall variability in the sensory cue. When calculating the optimal predicted weights initially, we assumed that the optimal observer knew how reliable the dots (i.e., the likelihood) were, and could average them perfectly. Since participants will not be perfect at averaging dots, they will be more variable in using the sensory cue than the optimal observer. Therefore, the truly optimal thing to do is for participants to weight the sensory cue, according to their overall variability by taking into account both the variance of the dot distribution and the internal variability in estimating the average of the dots. Since the sensory

739   cue is now less reliable (due to the added internal variability), we would expect

740   participants to put less weight on it, and more weight on the prior.

741   We calculated the overall variability in using the sensory cue as:

742
$$\sigma_{l_o}^2 = \sigma_l^2/n + \sigma_{l_i}^2$$

where σ_l^2/n is the external noise in the sensory cue, and $\sigma_{l_i}^2$ is the individual internal

variability.

As is expected, Figure 7 shows that the predicted weights in this case were

lower than the optimal weights (compare dotted and dashed lines) as participants

are worse than the optimal observer in averaging the dots. They placed less weight

on the sensory cue and more weight on the prior than the optimal observer. We also

compared these predicted weights to subjects' weights in the final block (5) in

Experiment 1, and found that they were still significantly different from the empirical

data when the variance of the likelihood was medium or high (irrespective of prior

variance) and when the likelihood variance was low and the prior variance was

narrow (all $p < .001$). No significant difference was observed when the likelihood

variance was low and the prior variance was wide ($p = .79$). This means that

accounting for the added internal variability fails to explain our results as observers

are placing more weight on the sensory cue than is optimal, not less.

Figure 7. Mean weight placed on the likelihood information in each block of Experiment 1. Blue is the low-variance likelihood, green is the medium-variance likelihood, red is the high-variance likelihood. Dashed lines show optimal values. Dotted lines show predicted weights when overall variability in using the likelihood is taken into account. Error bars are +/- 1 SEM.

In summary, use of only internal and not external variability could potentially explain our subjects' suboptimal behaviour.

Discussion

We set out to test more strictly than before for Bayes-like combination of prior knowledge with sensory information in the context of a sensorimotor decision making task (Beierholm, Quartz, & Shams, 2009; Bejjanki et al., 2016; Berniker et al., 2010; Tassinari et al., 2006; Vilares et al., 2012) by adding transfer criteria to the task (Maloney & Mamassian, 2009).

In Experiment 1, we did this by investigating whether observers are able to learn the variances of two prior distributions, and instantly integrate this knowledge with a new level of sensory uncertainty added mid-way through a task. We found that observers placed more weight on the sensory cue (likelihood) when its variance was low and the variance of the prior was high; behaviour that is in broad agreement with the Bayesian prediction. However, we found only partial evidence of transfer. The weight placed on the high variance likelihood was not significantly lower than that placed on the medium variance likelihood, which is at odds with the prediction of transfer. Importantly, even though qualitatively, our participants behaved like Bayesian observers, their performance fell markedly short of optimal.

In two further experiments we asked: (1) how behavior would be affected by additional instructions, which can clarify whether this suboptimality stems from using the incorrect model structure of the task; (2) whether experiencing the high likelihood variance condition from the start of the experiment would lead to closer-to-optimal weighting of the prior and likelihood information. In the first of these two further experiments, Experiment 2, we found that subjects' performance moved closer to optimal when they were (indirectly) instructed that the prior variances were different – possibly why we were able to detect significant evidence of transfer in the task. However, they were still significantly sub-optimal in multiple experimental conditions. Participants remained significantly sub-optimal in the final experiment (Experiment 3), when the need for transfer was removed (all trials types were present from the start of the task) and the experiment became a more direct replication of (Bejjanki et al., 2016).

Suboptimal weighting of prior and likelihood information

We show that observers take uncertainty into account, giving more weight to the sensory cue as its variance decreases, a result that is consistent across all three experiments. Equally, for a Bayes-like observer, we expect to find that the weight on the sensory cue is higher as the prior variance increases, but we found a main effect of prior in Experiments 1 and 2 only, and not in Experiment 3. Moreover, while our manipulation to the instructions in Experiment 2 moved the weights placed on the likelihood closer to optimal, they were still significantly different to the optimal predictions.

To examine to what extent additional sensory variability in estimating the
centres of dot-clouds could have affected predictions and performance, we ran a
separate, control experiment (see Appendix B). This shows that observers are less
efficient in their use of the likelihood information than an ideal observer: the
variability of their responses is significantly larger than the true variability of the
sensory cue in both the low and medium variance likelihood conditions. However,
this fails to account for suboptimal performance: ideal weights for the likelihood that
are computed using the measured likelihood variabilities in the control task are still
significantly lower than those in the empirical data.

Suboptimal weighting of the prior and likelihood information may also be
caused by incomplete or incorrect learning of the prior information. However, the
prior-only trials suggest that the observers learn the means of the priors and
distinguish between their variances at least in Experiments 1 and 2, if not
Experiment 3 (under the assumption that standard deviations of subjects' responses
are related to the learnt prior variances). Suboptimal weighting of the prior could also
be due to the use of an incorrect Bayesian generative model (causal structure) by
subjects, e.g. if they believe that the prior will change over trials then they should
apply a smaller weight to the prior (could be conceptualized as a meta-prior or
hyperprior in Bayesian terms, Gelman, Carlin, Stern, & Rubin, 2013). The fact that
we found an effect of instructions imply that the causal structure assumed by
subjects can indeed greatly influence behavior (Shams & Beierholm, 2010).

Other research groups have performed similar experiments but using only a
single prior distribution (Acerbi, Vijayakumar, & Wolpert, 2014; Berniker et al., 2010;
Chambers et al., 2018; Tassinari et al., 2006; Vilares et al., 2012). These studies
also find deviations from the optimal predictions; however, the deviations can be
accounted for by adding extra sources of inefficiency to the model that are due to
motor errors, centroid calculation errors, and aim point (in reaching tasks) calculation
errors (Tassinari et al., 2006). Moreover, when trials are blocked by prior condition, it
has been shown that learning after a switch in the prior variance is slower when the
prior variance decreases than when it increases, suggesting participants may
perform optimally after further exposure to the task (Berniker et al., 2010).

We considered elements of the experimental design that could have resulted
in suboptimal behavior in a task similar to others in the literature where performance
was closer to optimal (e.g., Bejjanki et al., 2016). Firstly, describing the dots as the
tentacles of an octopus may have caused participants to assume that another
method of gaining an estimate from the dot colour, other than taking the mean
horizontal position, was more appropriate in this task (de Gardelle & Summerfield,
2011; Van Den Berg & Ma, 2012). However, our analysis shows that participant
responses are not better predicted by the median, mid-range, or robust average,
than they are by the mean. Secondly, our correction of the dot positions so that their
SD on each trial was equal to the true likelihood SD may have influenced
participant's inferred reliability for the likelihood. However, an observer who
computes the reliability for the likelihood trial by trial, by taking the dot cloud SD,
would infer that the likelihood was less reliable ($\frac{1}{\sigma_l^2}$) as a cue to true location than the
centroid of the dots would be for an observer who could perfectly calculate the mean
of the dots ($\frac{1}{\sigma_{l/n}^2}$). This would lead to an observer placing less weight on the likelihood
than the ideal observer. Participants in our experiment place more weight on the
likelihood than the ideal observer, so this is not the source of suboptimality in our
experiment.

Finally, whilst the true likelihood and prior reliabilities used in our task were
matched to those in Bejjanki et al. (2016) observers may have perceived the cue
(dots) as more reliable than it actually was, which in turn would result in more weight
placed on the cue than in previous studies (Bejjanki et al., 2016; Vilares & Kording,
2011).

It is possible that subjects did not experience enough trials of each prior and
likelihood uncertainty to reach optimal performance, and indeed, we find evidence of
decreasing weights on the likelihood with increasing task exposure in both
Experiments 1 and 2 (main effect of block, although not the rise from block 4 to 5 in
Experiment 2). Crucially, however, our participants experienced more trials per prior
than in Bejjanki et al. (2016) (750, compared to 600) where weights were closer to
optimal, ruling out the possibility that observers did not experience enough trials to
learn the complex features of the distributions.

The result that our participants' performance was so different -in terms of level

of sub-optimality- compared to Bejjanki et al. (2016) might be explained by a

difference in instructions. Specifically, their instructions have a social element that

ours do not, i.e., in their task, participants were instructed to interpret the likelihood

dots as "locations that other people have previously guessed the bucket is located

at" (vs. tentacles of the octopus in ours). This means that in Bejjanki et al. (2016)

participants would have to take into account how accurate they think other people's

guesses are. If we assume that people give lower weight to information that is

allegedly based on other people's guesses, this might explain why observers in

Bejjanki et al. (2016) generally weighted the likelihood less than in our experiments

(Martino, Bobadilla-suarez, Nouguchi, Sharot, & Love, 2017). Another aspect about

the instructions that is worth mentioning here is that, perhaps, our participants are

more likely to assume that the body of an octopus is in the center of its tentacles,

compared to previous guesses of other participants (Bejjanki et al., 2016) or

splashes from a coin (Tassinari et al., 2006; Vilares et al., 2012). However, had this

been the case, we would have expected participants' responses to be better

predicted by another estimate, such as the robust average, than the mean of the

dots, and we found no evidence of this in the data.

Another explanation is that observers were being "optimally lazy"; that is, they

deviated from optimal performance in a way that had minimal effects on their

expected reward (Acerbi, Vijayakumar, & Wolpert, 2017). In this case, we would

expect obtained reward to match well with the predictions of the optimal Bayesian

model; instead, the predicted reward resulting from optimally combing sensory and

prior information was higher than that obtained by our observers - particularly when

the variance of the prior was narrow (Appendix C). Therefore, we have no reason to

believe that the suboptimal behaviour we observed in our task was due to our

participants being "optimally lazy" (Acerbi et al., 2017).

Nevertheless, we could show that the suboptimal behaviour in our task can be

best explained by assuming that participants were weighting sensory information

(relative to prior information) only according to the internal variability in using the cue,

ignoring external noise. It is, thus, interesting to consider it as one potential

explanation, on the computational level, for the deviations from optimal consistently

reported in similar studies on combination of sensory and prior information (Bejjanki

et al., 2016; Berniker et al., 2010; Sato & Kording, 2014; Tassinari et al., 2006;

Vilares et al., 2012). However, we note that attending to internal noise may be easily

mistaken for underweighting the total noise; future work could investigate the extent

to which suboptimal behaviour is specifically linked to the use of internal variability,

and not simply a general under-estimation of the total noise in the stimuli.

Evidence for Bayesian transfer

We found only partial evidence for transfer in Experiment 1, as there was no

significant change in the weight placed on the likelihood between the medium and

high likelihood conditions. In fact, subjects seemed to treat the high variance

likelihood the same as the medium variance likelihood (that they had experience

with), suggesting that observers did not adopt a statistically optimal Bayesian

strategy. Nonetheless, performance did not improve with more trials, suggesting that

subjects were not implementing a look-up table decision rule, either (Maloney &

Mamassian, 2009). However, we note that in our data, observers placed much more

weight on the medium and high likelihoods than is optimal. This means that the

effect size of a change in likelihood is much less than was expected; thus, the

observed lack of significant differences might simply be due to lack of statistical

power in our analysis to detect such small effect sizes.

Why do we see more convincing evidence of transfer in the instructions task?

Bayes-like computations demand considerable computational resources (e.g.,

working memory load, attentional focus); it is, therefore, reasonable to expect that if

a task is sufficiently complex, and there is a lot to learn, subjects will start behaving

sub-optimally. The impact of additional instructions in Experiment 2 may be to free

up cognitive resources by providing subjects with (indirect) information about the

variances of the two prior distributions at the start of the task (Ma, 2012; Ma &

Huang, 2009).

Our findings do not allow us to clearly distinguish between the reinforcement-

learning and Bayesian interpretations. We found that when we introduced a new

level of (known) uncertainty to the likelihood, observers immediately changed how

they used this new information in a way that is largely consistent with optimal

predictions; this effect was significant in the second experiment, but not in the first.

Thus, we note that this effect is not particularly robust as it depends on the

experimental procedure used to measure it. Indeed, our findings demonstrate that

whether this effect is observed in the first place is greatly affected by small changes

in experimental layout (e.g., instructions, number of trials). The fact that we observe

no learning during Experiment 3 (no main effect of block), coupled with the

observation that the weight on the likelihood in the 4_{th} block of Experiment 3 were

remarkably similar to those in the 4_{th} block of Experiments 1 and 2 makes a weak

suggestion of a Bayesian interpretation. However, a stronger test of transfer would

be if participants had received no feedback for the new level of uncertainty. We

provided trial-by-trial feedback (true target position) to ensure that participants were

able to learn and recall the correct prior distributions. Therefore, we cannot rule out

the possibility that our participants used the feedback to directly learn a mapping

between the high variance likelihood and each prior, instead of the distribution of

locations.

Sato and Kording (2014) showed that subjects behave in a Bayes-optimal

fashion in a sensorimotor estimation task, where they transferred their knowledge

from the 'learning phase' to the prior in the testing phase in the absence of trial-to-

trial feedback, suggesting that people did not learn a simple likelihood-prior mapping.

This means that the features of our experiments set an approximate upper bound on

learning; in other words, we can generally expect subjects' performance to be less

accurate when performance feedback is not provided.

Nevertheless, in order to meaningfully test whether observers can transfer

probabilistic information across different conditions, an experiment where trial-by-trial

feedback is limited, or excluded altogether, is needed. Hudson, Maloney, and Landy

(2008) argued that providing only blocked performance feedback, for example, would

prevent participants from using a "hill-climbing" strategy in the high variance

likelihood condition (i.e., updating their estimates, based on the feedback from trial to

trial). Alternatively, Acerbi, Vijayakumar, and Wolpert (2014) found that partial

feedback (where participants are told whether they "hit" or "missed" the target, but

the actual target position is not displayed) is sufficient to maintain participant

engagement; however, no meaningful information can be extracted from the

feedback, preventing participants from using it to better their performance. Future

work could investigate how the removal of full performance feedback would affect

behaviour in more complex scenarios.

What are observers if not Bayesian?

Some studies suggest that BDT is generally a good descriptive model of

people's perceptual and motor performance, but quantitative comparison shows

divergence from Bayes-optimal behaviour (Bejjanki et al., 2016; Zhou, Acerbi, & Ma,

2018), not unlike what we report in this study. These deviations from optimality may

have arisen because rather than performing the complex computations that a typical

Bayesian observer would do, observers draw on simpler non-Bayesian, perhaps

even non-probabilistic, heuristics (Gigerenzer & Gaissmaier, 2011; Zhou et al.,

2018). Laquitaine and Gardner (2018) developed a model that switched between the

prior and sensory information, instead of combining the two, which was found to

explain the data better than standard Bayesian models. The authors concluded that

people can approximate an optimal Bayesian observer by using a switching heuristic

that forgoes multiplying prior and sensory likelihood. In another study, Norton,

Acerbi, Ma, and Landy (2018) compared subjects' behaviour to the 'optimal' strategy,

and well as several other heuristic models. The model fit showed that participants

consistently computed the probability of a stimulus as belonging to one of two

categories as a weighted average of the previous category types, giving more weight

to those seen more recently; subjects' responses also showed a bias towards seeing

each prior category equally often (i.e., with equal probability). We note that a

Reinforcement-Learning (RL) model was also tested, where participants could simply

update the decision criterion after making an error with no assumptions about

probability; no participant was best fit by the RL model. This suggests that observers

are, in fact, probabilistic, i.e., take into account probabilities, though not necessarily

in the optimal way; instead, they seem to resort to heuristic strategies. However,

future work should explore which, if any, of these models can capture the behaviour

on this type of complex localisation task.

Acknowledgements

This work was supported by research grants from the Leverhulme Trust (RPG-2017-
097; Marko Nardini, PI) and North East Doctoral Training Centre (ES/J500082/1;
Reneta Kiryakova). We would like to thank Dr. James Negen for helpful comments
on the manuscript.

1000

1001

1002

1003

1004

1005

1006

1007

1008

1009

1010

1011

1012

1013

1014

1015

1016

1017

Appendix A

1018

1019

Instructions in Experiment 1:

"We will ask you to play an "octopus" game!

Imagine that you are on a boat and there are 2 octopuses you are trying to find: one

is white, and the other one is black. The white octopus has square tentacles and the

black octopus has circular tentacles. The 2 octopuses live in different parts of the

sea. Sometimes the octopuses will show their tentacles and at other times they will

hide at the bottom of the sea.

Your job is to try and figure out where the octopus is!

Once you decide on a location, you can click on the green square (your fishing net),

at which point you will see a red dot, which shows you the true location of the

octopus on that trial. If the red dot is inside the net, then you correctly guessed the

location of the octopus and you get a point!"

1032

Instructions in Experiment 2:

"We will ask you to play an "octopus" game!

Imagine that you are on a boat and there are 2 octopuses you are trying to find: one

is white, and the other one is black. The white octopus has square tentacles and the

black octopus has circular tentacles. The 2 octopuses live in different parts of the

sea. Sometimes the octopuses will show their tentacles and at other times they will

hide at the bottom of the sea.

[It is important to remember that one of the octopuses tends to stay in a

particular area, whereas the other one moves quite a bit!]

Your job is to try and figure out where the octopus is!

Once you decide on a location, you can click on the green square (your fishing net),

at which point you will see a red dot, which shows you the true location of the

octopus on that trial. If the red dot is inside the net, then you correctly guessed the

location of the octopus and you get a point!"

Appendix B

1047

1048

Control Experiment: Likelihood-only task

1049

Participants consistently performed sub-optimally across *all* of our

experiments. However, when we calculated the optimal weight on the likelihood, we

did so under the assumption that people know the true values of the reliability of the

sensory cue (i.e., the likelihood). As Sato and Kording (2014) point out, this is clearly

not always the case: in fact, in order to perform optimally on our tasks, observers

may need to learn about their likelihood variability, as well as prior variability. We,

therefore, separately assessed any sensory noise that participants may have had in

judging the centroid of the set of dots. If we find that subjects' estimates of the

reliability of the likelihood differ from the true values, this would mean that subjects

were using incorrect parameters for the task, which may have led to suboptimal

performance. We then recomputed the optimal weights based on errors in observers'

estimates of centroid location; we could, therefore, test whether subjects were, in

fact, near-optimal, when their own sensory variability was taken into account.

Methods

Subjects (*N* = 26; 6 had participated in Experiment 2, 6 had participated in

Experiment 3, and the rest had not completed any of the above tasks) were

instructed to estimate the centroid of eight dots for different likelihood widths. True

locations were drawn from a uniform distribution across the screen (no prior). There

were 90 trials overall, with 30 trials of each likelihood width interleaved in a random

order. No feedback was given.

For each participant, their error on each trial was calculated by taking the

difference between the response and true location for that trial (error = response –

true). Their variable error for each likelihood condition was calculated as the

standard deviation of the errors. Outliers were excluded prior to calculating the

variable error in the same way as described previously.

Results and Discussion of Control Experiment

Participants were significantly worse than ideal (variable error was greater

than the true standard deviation of the likelihoods) in the low ($t(25) = 7.45, p < .001$)

and medium ($t(25) = 3.80, p < .001$), but not the high ($t(25) = 1.48, p = .151$)

variance likelihood conditions (Figure 8).

1080

1081   *Figure 8.* Variable error for each likelihood condition in the likelihood-only

1082   task. The dashed lines show the true standard deviations of the likelihood in each

1083   case (ceiling performance).

1084

This suggests that our optimal predictions place too much weight on the

likelihood, as they were calculated based only on the external variability of the

sensory cue, and failed to also incorporate the added variability from observer's

inability to perfectly calculate the dot centroids. We, therefore, recomputed the ideal

weight for the likelihood, this time using the measured likelihood variances in the

control experiment; we reasoned that this calculation would give us an optimal

prediction that better matches our subjects' performance. Our estimates of the

likelihood variance increased by 16.66% for the low, 2.96% for the medium and

5.26% for the high likelihood. With such large differences between the true and

estimated likelihood variances, we expected that the re-calculated optimal

predictions (based on subjects' estimates) will be closer to the observers' data,

compared to those based on the true likelihood parameters. We compared these

optimal values to subjects' weights in the final block (5) in Experiment 1, and found

that they were still significantly different from the empirical data when the variance of

the likelihood was high or medium, irrespective of prior variance (all $p < .001$) (see

Figure 9). No significant differences were observed when the prior variance was

wide and the likelihood variance was low ($p = .765$).

1102

1103

1104

1105   *Figure 9.* Mean weight placed on the likelihood information in each block of

1106   Experiment 1. Blue is low variance likelihood, green is medium variance likelihood,

1107   red is high variance likelihood. Dashed lines show optimal values. Dotted lines show

1108   optimal values, computed using measured likelihood variances in the control

1109   experiment. Error bars are +/- 1 SEM.

1110

1111   This pattern of results was surprisingly similar to the one we found when using the

1112   predictions of the optimal Bayesian observer, so this analysis did not affect our

1113   conclusions on the observers' suboptimal behaviour. In particular, sensory noise in

1114   determining the centroid of the "likelihood dots" does not play a major role in

1115   explaining subjects' sub-optimality in the task.

Appendix C

1116

The observed lack of statistically significant difference in cue weights does not

necessarily imply a lack of substantial difference in terms of performance (points), as

previous studies have shown that participants can be "optimally lazy" by deviating

from optimal performance in a way that has minimal impact on overall expected

score in a task (Acerbi et al., 2017). First off, we computed the optimal response

variability σ_b^2 in using both the cue (overall likelihood variability σ_o^2) and the prior as

1123
$$\sigma_b^2 = \frac{\sigma_o^2\,\sigma_p^2}{\sigma_o^2 + \sigma_p^2}$$

1124   Since we are interested in the performance of the model in terms of reward, we then

1125   calculated expected gains by first computing the probability of catching an octopus

1126   on a given trial as

1127
$$p = P\left(-\frac{w}{2} \le X \le \frac{w}{2}\right)$$

where p is the probability that a random draw X from a Gaussian distribution with

mean μ (fixed at zero) and standard deviation σ_b^2 will fall within the "hit" distance from

the true location, and that distance is half the width of the net $\frac{w}{2}$. The probability of

catching the octopus p is then multiplied by the number of trials (per trial type in a

block) to calculate the expected number of points.

We then compared expected reward to the average reward earned by those

participants who took part in the control experiment and either Experiment 2 or

Experiment 3 (N = 12; in block 5 only), and found that optimal integration of the

sensory cue and prior knowledge (according to participants' overall noise in using

the cue) resulted in an expected reward that was higher than what our participants

achieved, but only when the variance of the prior was narrow; when the prior

variance was wide, they matched quite well; see Figure 10. This result is particularly

challenging for the notion that people may be "optimally lazy", as this case would

result in predicted and obtained reward values being equal. It can be seen that

contrary to these predictions, our observers were clearly worse than the optimal

observer, and could earn more points when the variance of the prior was narrow; it

is, therefore, unlikely that their suboptimal performance could be explained by them

being "optimally lazy" (Acerbi et al., 2017).

1146

1147 *Figure 10.* Mean number of points earned in Block 5 for participants who took

1148 part in Experiment 2 or Experiment 3 and the control task ($N = 12$). Blue is low

1149 variance likelihood, green is medium variance likelihood, red is high variance

1150 likelihood. Dot-dashed lines show optimal reward values, taking into account

1151 participants' overall noise. Error bars are +/- 1 SEM.

1152

1153

1154

1155

1156

1157

1158

1159

1160

References

Acerbi, L., Vijayakumar, S., & Wolpert, D. M. (2014). On the origins of suboptimality in human probabilistic inference. *PLoS Computational Biology*, *10*(6), e1003661. https://doi.org/10.1371/journal.pcbi.1003661

Acerbi, L., Vijayakumar, S., & Wolpert, D. M. (2017). Target Uncertainty Mediates Sensorimotor Error Correction, 1–21. https://doi.org/10.1371/journal.pone.0170466

Acerbi, L., Wolpert, D. M., & Vijayakumar, S. (2012). Internal Representations of Temporal Statistics and Feedback Calibrate Motor-Sensory Interval Timing. *PLoS Computational Biology*, *8*(11). https://doi.org/10.1371/journal.pcbi.1002771

Ahrens, M. B., & Sahani, M. (2011). Observers exploit stochastic models of sensory change to help judge the passage of time. *Current Biology*, *21*(3), 200–206. https://doi.org/10.1016/j.cub.2010.12.043

Alais, D., & Burr, D. (2006). The Ventriloquist Effect Results from Near-Optimal Bimodal Integration, *14*, 257–262. https://doi.org/10.1016/j.cub.2004.01.029

Beck, J. M., Ma, W. J., Pitkow, X., Latham, P. E., & Pouget, A. (2012). Not Noisy, Just Wrong: The Role of Suboptimal Inference in Behavioral Variability. *Neuron*, *74*(1), 30–39. https://doi.org/10.1016/j.neuron.2012.03.016

Beierholm, U. R., Quartz, S. R., & Shams, L. (2009). Bayesian priors are encoded independently from likelihoods in human multisensory perception. *Journal of Vision*, *9*(2009), 23–23. https://doi.org/10.1167/9.5.23.Introduction

Bejjanki, V. R., Knill, D. C., & Aslin, R. N. (2016). Learning and inference using complex generative models in a spatial localization task, *16*(2016), 1–13. https://doi.org/10.1167/16.5.9.doi

Berniker, M., Voss, M., & Kording, K. (2010). Learning priors for bayesian computations in the nervous system. *PLoS ONE*, *5*(9), 1–9. https://doi.org/10.1371/journal.pone.0012686

Bowers, J. S., & Davis, C. J. (2012). Bayesian just-so stories in psychology and neuroscience. *Psychological Bulletin*, *138*(3), 389–414.

https://doi.org/10.1037/a0026450

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, 433–436.

Chalk, M., Seitz, A. R., & Series, P. (2010). Rapidly learned stimulus expectations
alter perception of motion. *Journal of Vision*, *10*(8), 2–2.
https://doi.org/10.1167/10.8.2

Chambers, C., Gaebler-spira, D., & Kording, K. P. (2018). The development of
Bayesian integration in sensorimotor estimation, *18*, 1–16.

de Gardelle, V., & Summerfield, C. (2011). Robust averaging during perceptual
judgment. *Proceedings of the National Academy of Sciences*, *108*(32), 13341–
13346. https://doi.org/10.1073/pnas.1104517108

Gardner, J. L. (n.d.). Optimality and heuristics in perceptual neuroscience.

Gelman, A., Carlin, J. B., Stern, H. S., & Rubin, D. B. (2013). Bayesian data analysis.
Chapman and Hall/CRC, *146*(4), 165–169.
https://doi.org/10.1017/9781316216491.030

Gigerenzer, G., & Gaissmaier, W. (2011). Heuristic Decision Making. *Annual Review*
of Psychology. https://doi.org/10.1146/annurev-psych-120709-145346

Greenhouse, S. W., & Geisser, S. (1959). ON METHODS IN THE ANALYSIS OF
PROFILE variance . Furthermore , an analysis of variance approach permits the
analysis of a set of data which cannot be handled by multivariate procedures ,
namely , the case where n , the number of random vectors , is less t, *24*(2).

Hudson, T. E., Maloney, L. T., & Landy, M. S. (2008). Optimal Compensation for
Temporal Uncertainty in Movement Planning, *4*(7).
https://doi.org/10.1371/journal.pcbi.1000130

Jazayeri, M., & Shadlen, M. N. (2010). Temporal context calibrates interval timing.
Nature Neuroscience, *13*(8), 1020–1026.
https://doi.org/10.1038/nn.2590.Temporal

Jones, M., & Love, B. C. (2011). Bayesian Fundamentalism or Enlightenment ? On
the explanatory status and theoretical contributions of Bayesian models of
cognition, 169–231.

Kleiner, M., Brainard, D., Pelli, D., Ingling, A., Murray, R., & Broussard, C. (2007). What's new in Psychtoolbox-3? *Perception*, *36*(14), 70821. https://doi.org/10.1068/v070821

Kording, K. P., Beierholm, U., Ma, W. J., Quartz, S., Tenenbaum, J. B., & Shams, L. (2007). Causal Inference in Multisensory Perception, (9). https://doi.org/10.1371/journal.pone.0000943

Körding, K.P., & Wolpert, D. M. (2004). Bayesian integration in sensorimotor learning. *Nature*, *427*(6971), 244–247. https://doi.org/10.1038/nature02169

Körding, Konrad P., & Wolpert, D. M. (2006). Bayesian decision theory in sensorimotor control. *Trends in Cognitive Sciences*, *10*(7), 319–326. https://doi.org/10.1016/j.tics.2006.05.003

Laquitaine, S., & Gardner, J. L. (2018). Article A Switching Observer for Human Perceptual A Switching Observer for Human Perceptual Estimation. *Neuron*, 1–13. https://doi.org/10.1016/j.neuron.2017.12.011

Ma, W. J. (2012). Organizing probabilistic models of perception. *Trends in Cognitive Sciences*, *16*(10), 511–518. https://doi.org/10.1016/j.tics.2012.08.010

Ma, W. J., & Huang, W. (2009). No capacity limit in attentional tracking : Evidence for probabilistic inference under a resource constraint, *9*(2009), 1–30. https://doi.org/10.1167/9.11.3.Introduction

Maloney, L. T., & Mamassian, P. (2009). Bayesian decision theory as a model of human visual perception: Testing Bayesian transfer. *Visual Neuroscience*, *26*(01), 147. https://doi.org/10.1017/S0952523808080905

Martino, B. De, Bobadilla-suarez, S., Nouguchi, T., Sharot, T., & Love, X. C. (2017). Social Information Is Integrated into Value and Confidence Judgments According to Its Reliability, *37*(25), 6066–6074. https://doi.org/10.1523/JNEUROSCI.3880-16.2017

Miyazaki, M., Nozaki, D., & Nakajima, Y. (2012). Testing Bayesian Models of Human Coincidence Timing. *Journal of Neurophysiology*, 395–399. https://doi.org/10.1152/jn.01168.2004.

Norton, E. H., Acerbi, L., Ma, W. J., & Landy, M. S. (2018). Human online adaptation

to changes in prior probability Author summary, 1–24.

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics:
transforming numbers into movies. *Spatial Vision*, *10*(4), 437–442.

Rahnev, D., & Denison, R. N. (2018). Suboptimality in perceptual decision making.
https://doi.org/10.1017/S0140525X18000936

Sato, Y., & Kording, K. P. (2014). How much to trust the senses: Likelihood learning.
Journal of Vision, *14*(13), 1–13. https://doi.org/10.1167/14.13.13.doi

Shams, L., & Beierholm, U. R. (2010). Causal inference in perception. *Trends in*
Cognitive Sciences, *14*(9), 425–432. https://doi.org/10.1016/j.tics.2010.07.001

Stocker, A. A., & Simoncelli, E. P. (2006). Noise characteristics and prior
expectations in human visual speed perception. *Nature Neuroscience*, *9*(4),
578–585. https://doi.org/10.1038/nn1669

Tassinari, H., Hudson, T. E., & Landy, M. S. (2006). Combining Priors and Noisy
Visual Cues in a Rapid Pointing Task. *Journal of Neuroscience*, *26*(40), 10154–
10163. https://doi.org/10.1523/JNEUROSCI.2779-06.2006

Van Den Berg, R., & Ma, W. J. (2012). Robust averaging during perceptual judgment
is not optimal. *Proceedings of the National Academy of Sciences*, *109*(13),
E736–E736. https://doi.org/10.1073/pnas.1119078109

Vilares, I., Howard, J. D., Fernandes, H. L., Gottfried, J. A., & Kording, K. P. (2012).
Differential representations of prior and likelihood uncertainty in the human
brain. *Current Biology*, *22*(18), 1641–1648.
https://doi.org/10.1016/j.cub.2012.07.010

Vilares, I., & Kording, K. (2011). Bayesian models: The structure of the world,
uncertainty, behavior, and the brain. *Annals of the New York Academy of*
Sciences, *1224*(1), 22–39. https://doi.org/10.1111/j.1749-6632.2011.05965.x

Weiss, Y., Simoncelli, E. P., & Adelson, E. H. (2002). Motion illusions as optimal
percepts. *Nature Neuroscience*, *5*(6), 598–604. https://doi.org/10.1038/nn858

Zhou, Y., Acerbi, L., & Ma, W. J. (2018). The Role of Sensory Uncertainty in Simple
Perceptual Organization Author summary.

1279