A neural network for online spike classification that improves decoding accuracy

Deepa Issar[1,2], Ryan C. Williamson[2,3,4], Sanjeev B. Khanna[1], and Matthew A. Smith[3,5,6,7#]

[1]Department of Bioengineering, University of Pittsburgh, Pittsburgh, PA, USA
[2]School of Medicine, University of Pittsburgh, Pittsburgh, PA, USA
[3]Center for the Neural Basis of Cognition, Pittsburgh, PA, USA
[4]Department of Machine Learning, Carnegie Mellon University, Pittsburgh, PA, USA
[5]Department of Biomedical Engineering, Carnegie Mellon University, Pittsburgh, PA, USA
[6]Carnegie Mellon Neuroscience Institute, Pittsburgh, PA, USA
[7]Department of Ophthalmology, Eye and Ear Institute, University of Pittsburgh, Pittsburgh, PA, USA

#: Address correspondence to:
Matthew A. Smith
Carnegie Mellon University
Department of Biomedical Engineering and Carnegie Mellon Neuroscience Institute
Email: matt@smithlab.net

Running head: A neural network for online spike classification

Abstract

Separating neural signals from noise can improve brain-computer interface performance and

stability. However, "spike-sorting" suffers from a lack of ground truth for classifying waveforms, and

most algorithms for separating neural action potentials from noise are not suitable for use in real time and

have shown mixed effects on decoding performance. Our goals were to automate the intuition of human

spike-sorters to operate in real time with an easily tunable parameter governing the stringency with which

spike waveforms are classified. We trained an artificial neural network with one hidden layer on neural

waveforms that were hand-labeled as either spikes or noise. The network output was a likelihood metric

for each waveform it classified, and we tuned the network's stringency by varying the minimum

likelihood value for a waveform to be considered a spike. Using the network's labels to exclude noise

waveforms, we decoded remembered target location during a memory-guided saccade task from electrode

arrays implanted in prefrontal cortex of rhesus macaque monkeys. The network classified waveforms in

real time, and its classifications were qualitatively similar to those of a human spike-sorter. Compared to

decoding with threshold crossings, in most sessions we improved decoding performance by removing

waveforms with low spike likelihood values. Furthermore, decoding with our network's classifications

became more beneficial as time since array implantation increased. Our classifier serves as a feasible

preprocessing step, with little risk of harm, that could be applied to both offline neural data analyses and

online decoding.

New & Noteworthy

Analysis of neural data from extracellular electrodes typically involves a manual step in which the

experimenter isolates neural signals from noise. This process, known as spike-sorting, is tedious and

subjective. We used waveforms sorted by a human as training data to create an artificial neural network to

separate spikes from noise. We found that this network operated in real time and was suitable for both

offline data processing and online decoding.

Introduction

Brain computer interfaces (BCIs) have been used as both research tools to understand neural

phenomena (Sadtler et al. 2014; Chase, Kass, and Schwartz 2012; Golub, Yu, and Chase 2015; Schafer

and Moore 2011) and devices to improve patient control of prosthetics (Velliste et al. 2008; Hochberg et

al. 2012; Collinger et al. 2013). BCIs interpret neural signals arising from electrodes implanted in the

cortex using real-time decoding algorithms; however, their performance is limited by the difficulty of

segregating individual neurons from extracellular voltage signals ("spike-sorting"), the characteristics of

the information present in individual neurons and multi-unit activity (their "tuning"), as well as the

nuances of interactions among neurons (Averbeck, Latham, and Pouget 2006). Refining the raw data is

necessary to improve BCI performance, but identifying waveforms that contain relevant information is

challenging.

One common noise removal method is to use all waveforms crossing a minimum voltage

threshold for decoding, where all waveforms on a particular channel are considered to be from a single

neural "unit" (Lewicki 1998; Christie et al. 2015). Using threshold crossings also serves to reduce the

amount of stored data. However, threshold crossings often capture noise and the summed activity of

multiple nearby neurons, called multi-unit activity, on each channel (Stark and Abeles 2007; Rey,

Pedreira, and Quian Quiroga 2015). Alternatively, since waveforms with the characteristic shape of an

action potential are the focus of most offline neural data analyses, a different approach is to isolate well-

defined spike waveforms from the threshold crossings via spike-sorting, and use only those waveforms

for decoding (Lewicki 1998; Rey, Pedreira, and Quian Quiroga 2015). Unfortunately, most spike-sorting

techniques are unsuitable for BCI use because they are time-intensive and require manual refinement.

Furthermore, even with the development of real-time, automated spike-sorting algorithms (Chung

et al. 2017; Chaure, Rey, and Quian Quiroga 2018), there is no clear ground truth for what constitutes a

spike waveform based solely on extracellular recordings (Rey, Pedreira, and Quian Quiroga 2015; Wood

et al. 2004; Pedreira et al. 2012; Rossant et al. 2016). While some studies have found spike-sorted units

improved decoding performance (Todorova et al. 2014; Ventura and Todorova 2015; Kloosterman et al.

2014; Santhanam et al. 2004), others have found that threshold crossings resulted in comparable or better

decoding that was more stable over time (Christie et al. 2015; Fraser et al. 2009; Chestek et al. 2011; Gilja

et al. 2012; Dai et al. 2019). These conflicting results highlight the gap in our understanding of what

information in neural recordings is most valuable for BCIs. Even within studies, there are inconsistent

effects of spike-sorting on decoding, both between subjects and over time (Fraser et al. 2009; Christie et

al. 2015). It is also difficult to compare the effects of spike-sorting on decoding performance across

studies due to the inherent variability in spike-sorting techniques (Wood et al. 2004; Rossant et al. 2016;

Pedreira et al. 2012; Rey, Pedreira, and Quian Quiroga 2015) and differences in brain regions, parameters

being studied, and decoding algorithms that may influence which waveforms are the most decodable

(Fraser et al. 2009; Oby et al. 2016; Chestek et al. 2011; Lewicki 1998; Bishop et al. 2014).

Given the subjective nature of spike-sorting and its history of variable effects on decoding

performance, we sought to avoid explicitly sorting our data and instead developed an easily tunable spike

classifier that could objectively and efficiently assign waveforms to one of two classes: spike or noise. To

achieve this goal, we sought a classification approach that would (1) take advantage of the spike-sorted

waveforms from previous analyses that formed a readily available, labeled training data set; (2) output a

likelihood of being a spike for each waveform so we could simply adjust the minimum cutoff for binary

spike classification; (3) once trained could operate in real time. We built a neural network classifier that

satisfied these three criteria. To evaluate our classifier's performance, we decoded the activity of

electrode arrays implanted in prefrontal cortex (PFC), and compared decoding accuracy of task condition

with all threshold crossings to decoding accuracy with the waveforms selected by our classifier. We also

assessed how decoding performance changed as a function of the stringency of our classifier (i.e. the

minimum cutoff for spike classification) and explored how decoding accuracy with our classifier changed

as a function of time since the array implantation (array implant age).

By removing waveforms that the network identified as unlikely to be spikes, we improved

decoding performance for most sessions relative to decoding with all threshold crossings. Moreover, in

the remaining sessions there was no substantial detriment to decoding accuracy, meaning we could apply

our method with little risk of harming decoding performance. Our network classifications continued to

improve decoding accuracy in sessions recorded long after array implantation, even though the overall

decoding accuracy decreased and the array recordings became noisier. Thus, our real-time, tunable

waveform classifier demonstrates promise for long-term BCI applications and our findings highlight the

value of spike-sorted data as a training set to inform waveform classification.

85   **Materials and Methods**

We trained a neural network, using a database of spike-sorted waveforms, to assign waveforms to

a spike or noise class. We then tested the network's classifications with another data set that was

independent from the training set. To evaluate the network's classifications, we decoded task location

using only waveforms labeled as signal by the network and compared the accuracy to decoding accuracy

using all recorded waveforms. All experimental procedures were approved by the Institutional Animal

Care and Use Committee of the University of Pittsburgh and were performed in accordance with the

United States National Institutes of Health's *Guidelines for the Care and Use of Laboratory Animals*.

Neural recordings

We analyzed neural recordings from six adult male rhesus macaques (*Macaca mulatta*) which

had previously been spike-sorted for ongoing experiments in the laboratory. Data from four subjects were

used to train our spike-classifying neural network, and data from the remaining two subjects (Monkey Pe

and Monkey Wa) were used to assess decoding accuracy using the network's classifications. Raw

recordings from both 96-electrode 'Utah' arrays (Blackrock Microsystems, Salt Lake City, UT) and 16-

channel linear microelectrode arrays (U-Probe, Plexon, Dallas, TX) were band-pass filtered from 0.3 to

7,500 Hz, digitized at 30 kHz, and amplified by a Grapevine system (Ripple, Salt Lake City, UT). For

each recording session, a threshold was defined for each channel independently based on the root-mean-

squared voltage of the waveforms (V_{RMS}) recorded on that channel at the beginning of the session (i.e.

$V_{RMS}*X$, where X was a multiplier set by the experimenter). Each time the signal crossed that threshold, a

52-sample waveform segment was captured (i.e. a threshold crossing), with 15 samples prior to and 36

samples following the sample in which the threshold excursion occurred.

Offline spike-sorting

Waveform segments were classified as spike or noise waveforms using a custom, offline

MATLAB spike-sorting algorithm that used an automated competitive mixture decomposition method

(Shoham, Fellows, and Normann 2003). These automated classifications for each recording session were

subsequently refined manually by a researcher. While only a single researcher spike-sorted the waveforms

from any particular session, the data in the training set (7 sessions total) collectively consisted of data

spike-sorted by four different researchers. If multiple unique spike waveform shapes were present on a

channel, the sorter would label those as different units.

Training data set

We sought a diverse neural waveform training set that captured a variety of subjects, brain

regions, implanted array ages (i.e. number of days since the array was implanted) and recording devices

(Table 1). The four training data set subjects each had a 96-electrode 'Utah' array implanted in right or

left hemisphere visual area V4. Two of those subjects also had 16-channel U-probe recordings from the

frontal eye field (FEF), located in the anterior bank of the arcuate sulcus. Data from two sessions were

used for three of the subjects: one session recorded shortly after the array implant, and one session

recorded at least four months later. For the fourth subject, only a single recording session recorded shortly

after the array implant was used because there were no later recordings from that array. These recordings

were collected and sorted as part of previous studies which describe the experimental preparations in

detail (Khanna, Snyder, and Smith 2019; Snyder et al. 2014; Snyder et al. 2015; Snyder and Smith 2015).

Data in the training set were assigned a label of 0 or 1. For each session, all waveforms labeled as noise

during spike-sorting were included in the training set (labeled as 0). For the spike waveforms in the

training set, only waveforms that were both labeled as spikes during spike-sorting and from a channel

with very distinct spike waveforms, defined as a channel with a signal-to-noise ratio greater than 2.5

(Kelly et al. 2007), were included in the training set (labeled as 1). The aim of these selections was to

emphasize relatively well-isolated single unit action-potential shapes while also exposing the network to a

variety of noise waveforms. If there were multiple single-units identified by the sorter on a particular

channel, they were not distinguished in the training set and all were treated as spike waveforms (labeled

as 1).

Overall, the network training set consisted of 24,810,795 waveforms from four monkeys, two

brain regions (V4 and FEF), two recording devices (Utah array and U-probe), and different array implant

ages. These waveforms were classified as spikes or noise using the offline spike-sorting technique

described above (Fig. 1a).

Table 1. Training data set information, including time since implant (array age), brain area (RH-right hemisphere, LH-left hemisphere), and number of recording sessions. Utah arrays contained 96 channels and U-Probes had 16 channels.

	Recording device	Brain area	Time since implant	# of sessions
Monkey Wi	Utah array	RH V4	~1 month	1
	Utah array	RH V4	~11 months	1
	U-Probe	RH FEF	-	1
Monkey Ro	Utah array	LH V4	<1 month	1
	Utah array	LH V4	~8 months	1
	U-Probe	LH FEF	-	1
Monkey Bo	Utah array	RH V4	<1 month	1
	Utah array	RH V4	~4 months	1
Monkey Bu	Utah array	RH V4	~1 month	1

Testing data set

We used recordings from two additional subjects, not included in the training set, for testing to

ensure that the trained network was generalizable to subjects not included in its training. The two testing

data set subjects (Monkey Pe and Monkey Wa) each had two 96-electrode 'Utah' arrays implanted, one in

visual area V4 and one in dorsolateral PFC (on the prearcuate gyrus just medial to the principal sulcus,

area 8Ar). Both arrays were implanted in the right hemisphere for Monkey Pe and in the left hemisphere

for Monkey Wa. Only data recorded from PFC were used for analyses (Table 2) because this provided a

matched data set from two monkeys for the purpose of assessing the impact of our method on decoding

and because it allowed us to test our network's generalizability in situations where the data were recorded

from a different region than the training set. However, we repeated some of the analyses in held out data

from V4 and included these results in the supplement (Supplementary Figure 4,

https://figshare.com/s/726cdc56c89113cc43d2). Recordings within 50 days of the array implant were

considered early sessions and recordings from over 50 days after the implant were considered late

sessions (see Table 2 for session counts by subject). For Monkey Pe, the thresholds across channels were

similar for all recording sessions (90% of channels had thresholds between -39 and -20 µV, median: -29

µV). For Monkey Wa, the thresholds were more permissive for the later recording sessions (> 6 months

after the array implant) as the experiments sought to extract the maximum remaining signal in arrays that

were decreasing in recording quality. The median of Monkey Wa's early sessions was -32 µV (90%

between -43 and -23 µV), and the median of the later sessions was -15 µV (90% between -29 and -12

µV). The waveforms in the testing data set were also spike-sorted offline via the technique described

above for a comparative analysis between our network classifications and offline spike-sorting.

Table 2. Testing data set information, including time since implant (array age), brain area (RH-right hemisphere, LH-left hemisphere), and number of recording sessions.

	Recording device	*Brain area*	*Time since implant*	*# of sessions*
Monkey Pe	Utah array	RH PFC	11-43 days	14
		RH PFC	80-147 days	22
Monkey Wa	Utah array	LH PFC	27-40 days	5
		LH PFC	180-224 days	11

Neural Network

Using TensorFlow (Abadi et al. 2016) and Keras (Chollet 2015), we developed a neural network

to classify data segments as spike or noise waveforms (Fig. 1b). The network accepts a waveform

segment with 's' samples (s=52), which passes through a hidden layer with 'n' units (n=50) that uses a

rectified linear unit (ReLU) activation function. The product of the hidden layer passes through one

output unit and then the network applies a sigmoid function to its output.

With the aforementioned training waveforms, the network was trained to maximize accuracy

based on binary labels (0 for noise, 1 for spikes) using an Adam optimization algorithm (Diederik P.

Kingma 2015) and a binary cross-entropy loss function in batch sizes of 100.

For a single waveform input run through the trained network, the output was a value between 0

(likely not a spike) and 1 (likely a spike), which represented the network's assessment of the likelihood

that the input waveform was a spike. While this output value was not a conventional probability, we refer

to it as the probability of being a spike or P(spike) because it was a likelihood metric scaled between 0

and 1. Supplementary Figure 1 (https://figshare.com/s/726cdc56c89113cc43d2) provides more intuition

regarding the hidden layer units and how the network assessed waveforms. In order to classify the

waveforms using the network's output probability, we set a minimum P(spike) for a waveform to be

classified as a spike. We referred to this minimum probability as the γ threshold. A γ threshold of 0

classified all of the waveforms that were captured for the session as spikes; this is often referred to as

'threshold crossings' in the literature. Increasing γ resulted in fewer waveforms classified as spikes

because the P(spike) cutoff was higher.

181
Figure 1. Methods of classifying waveforms: classic (manual) spike-sorting and our neural network spike
classifier, Not A Sorter (NAS). (a) Spike-sorted channels with waveforms that were manually classified as
spikes (green) and noise (grey). The network was trained on 24,810,795 spike-sorted neural waveforms from
four monkeys. The waveforms were recorded on arrays implanted in V4 as well as U-probes placed in FEF.
(b) Neural network structure and output for three sample waveforms. Each s=52 waveform input (I) was
passed through a hidden layer (II) with n=50 units. The resultant linear weighting of the waveform voltages
was passed through a rectified linear unit (ReLU) non-linearity (III). The output was again passed through a
weighted sum (IV) followed by a sigmoid non-linearity (V). The resulting value was the network's assessment
of the likelihood that the input waveform was a spike waveform (VI). We referred to this value as P(s) or the
"probability" of being a spike.

Custom Python and MATLAB scripts used to train the neural network and classify waveforms, as

well as sample training and testing data, will be available on GitHub at the time of publication. We refer

to our neural network as Not A Sorter (NAS), because it classifies waveforms as spikes or noise but does

not attempt to sort the spikes into separable single units.

Memory-guided saccade task

The two testing data set subjects (Monkey Pe and Monkey Wa) performed a memory guided

saccade task (Fig. 2a). Each subject fixated on a central point for 200 ms. Then, a target stimulus flashed

at a set amplitude and direction for 50 ms, followed by a 500 ms delay. There were a total of 40 possible

conditions: the radius could be one of five eccentricities and the target direction could be one of eight

(spaced in 45° steps). After the delay, the fixation point disappeared instructing the subject to make a

saccade to the location where the target flashed. For some sessions, during the saccade the target

reappeared to help the subject; however, for all analyses we only used data from the beginning of the

delay period (i.e. prior to the saccade). Subjects were rewarded with water or juice for making a saccade

to the correctly remembered target location. For all decoding analyses, the decoded condition was the

target location. Trials at a single eccentricity (Monkey Pe: 9.9°, Monkey Wa: ~7.6°) were used to

maximize the number of recording sessions that could be compared. Thus, there were eight unique target

locations to decode.

Only rewarded trials were analyzed. The number of trial repeats per condition varied over

sessions. Monkey Pe had an average of 43 repeats per session (range: 25-75, sd: 17) and Monkey Wa had

an average of 62 repeats per session (range: 51-83, sd: 11) for each target condition.

Decoding

To classify target direction prior to movement from PFC waveforms, we used a Poisson Naïve

Bayesian decoder (Fig. 2b). All decoding analyses were performed offline. Waveforms classified as

spikes from 300 ms to 500 ms after fixation (i.e. 50 ms after stimulus offset) were used for decoding,

while waveforms classified as noise were discarded. Each channel was considered a single decodable unit

with one exception: to calculate decoding accuracy using manual spike-sorting, if there were multiple

single-units identified by the manual spike-sorting method on a channel, each single-unit on that channel

remained separate for the purposes of decoding. Units with an average firing rate across trials below 0.25

spikes per second were discarded. We allocated training and test trials using two different methods. For

one analysis, we assigned 80% of the trials from each session to the training set and the remaining 20% to

the test set (Fig. 4a,b). For the remaining analyses, we wanted two test sets, so we used 60% of the trials

for training and 20% for each of the two test sets. The two test sets allowed us to search for an optimal γ

threshold using the first test set and cross validate this value with the second test set. Training and test

data were rotated such that each trial was used for a test set only once.

226
Figure 2. Offline decoding of planned direction from a memory guided saccade task. (a) Memory guided
saccade task. The monkey fixated on a central point. A brief stimulus flash occurred followed by a delay
period. When the fixation point turned off, the subject was required to make a saccade to the location of the
previously flashed stimulus. (b) Decoding paradigm. The stimulus flash could occur at 8 different angles
around the fixation point. A Poisson Naïve Bayes classifier was used to decode stimulus direction offline using
spikes recorded from a 96-electrode Utah array in PFC 50 ms after target offset. For each recording session,
we used 5-fold cross validation, where for each fold the data were split (step 1) into a training set to create
model distributions for each direction (step 2) and an independent testing set to test the accuracy of the
model's predictions (step 3). Note that the curves in step (2) do not depict actual distributions and simply
represent how a Poisson decoder could use spike counts from trials in the training set to distinguish between
different target conditions.

Our decoding algorithm created a Poisson distribution model for each target location (θ) using

the average spike count for each unit (n_{spike}) in the training set. For each test trial, the target location

with the maximum prediction probability, $P(\theta|n_{spike})$, was the predicted label. In equation (1),

$P(n_{spike}|\theta)$ was calculated using the Poisson model developed with the training trials:

242
$$P(\theta|n_{spike}) = \frac{P(n_{spike}|\theta) * P(\theta)}{P(n_{spike})}$$

243   Decoding accuracy was calculated as the ratio of the number of correct prediction labels to the

244   total number of predictions. We used 5-fold cross validation and computed the average decoding accuracy

245   across folds.

247   **Results**

We trained a one-layer neural network called Not a Sorter (NAS) to evaluate the likelihood that a

neural waveform was a spike. We used a diverse set of waveforms in the training set from different brain

regions, subjects, and array implant ages (time since array implant) in order to expose the network to a

variety of waveform types. Each waveform in the training set was assigned a binary label of noise (0) or

spike (1) via offline spike-sorting with manual refinement by researchers. The network was also exposed

to variability in spike classification due to manual sorting because different researchers sorted different

sets of waveforms in the training data. The network learned to assess how spike-like a waveform was

based on binary labels, but itself output a continuous value between 0 and 1 for each waveform allowing

for tunable classification. We referred to this output as the probability of being a spike or P(spike). The

network classified 1000 waveforms in less than one millisecond on average (computed on a 2011 iMac

with a 2.8 GHz Intel Core processor). In a 10 ms bin, 1000 waveforms would be the expected output of

1000 channels each with a firing rate of 100 spikes/s. Thus, our network could be easily integrated to

operate within real-time computing constraints.

Qualitative assessment of NAS classifications

To assign each NAS-classified waveform a binary spike or noise label, we set a parameter called

the γ threshold, which was the minimum P(spike) a waveform needed to be considered a spike waveform.

We found that even a low γ threshold, such as γ=0.20 (Fig 3a), assigned most waveforms to classes that a

human spike-sorter would deem appropriate. Most spike-sorters and spike-sorting algorithms search for

waveforms with a canonical action potential shape – an initial voltage decrease followed by a sharp

increase, a narrow peak, and a return to baseline. Increasing the γ threshold to 0.70 (i.e. only waveforms

assigned a P(spike) > 0.70 were considered spikes) mimicked the effect of a more selective spike-sorter

(Fig 3b), where the percentage of spike waveforms on the channel decreased since more waveforms were

placed in the noise class and the remaining spike waveforms had a clearer single-unit shape. Considering

all of the waveforms from this same channel, the range of P(spike) values coincided well with our

subjective impression of the match of individual waves with a canonical action potential shape (Fig 3c),

and this was also true across all channels from this array (Fig 3d). Thus, tuning the γ threshold from low

values (near 0) to high values (near 1) resulted in a shift from a more permissive to a more restrictive

regime.

276
Figure 3. Classifying waveforms based on their probability of being a spike, P(spike), by setting γ, a tunable
parameter. (a-b) Waveforms classified as spikes (green) or noise (grey) for a sample channel in Monkey Pe.
The network outputs a value between 0 and 1, referred to as P(spike), for each waveform, where a value close
to 1 means the network identifies that waveform as very likely to be a spike waveform. After running
waveforms through the network, we set the minimum P(spike) to classify waveforms as spikes and referred to
this value as the γ threshold. In (a) only waveforms assigned a spike probability greater than 0.20 (i.e. γ
threshold = 0.20) and in (b) greater than 0.70 (i.e. γ threshold = 0.70) were classified as spikes. Increasing the
γ threshold by definition results in a smaller percentage of waveforms captured in the spike class. (c)
Waveforms from the same channel in (a) and (b) colored based on their network assigned P(spike) value. For
a waveform where γ_1 < P(spike) < γ_2, the waveform would be classified as a spike when the threshold is γ_1, but
would be labeled as noise for γ_2. (d) Similar to (c) except the average of waveforms across all channels within
the indicated P(spike) ranges. Modifying the γ threshold tuned the stringency of the spike classifications.

Quantitative assessment of NAS classifications with decoding

Although by eye the network appeared to classify waveforms reasonably well, there was no

available ground truth data with which to assess its performance. Instead, we sought to objectively assess

its performance by measuring its effect on offline decoding accuracy. Specifically, we hypothesized that

decoding using spikes classified by our network would be better than using threshold crossings. We

applied our network to a set of data recorded from PFC on which the network had not been trained. First,

we set the γ threshold and discarded any waveforms with a P(spike) below the threshold. Next, we split

the data into training and testing sets. We trained the decoder using the training set to decode the task

condition (the remembered location, out of 8 possibilities) during the delay period of a memory-guided

saccade task on each trial (see Methods). Then, we used the trained decoder to assess decoding accuracy

in the test set(s). We repeated this process for the same data set using multiple γ thresholds between 0

(i.e., all threshold crossings were considered spikes) and 0.95 (i.e., only waveforms assigned a 0.95 or

greater probability by the network were considered spikes). Since only waveforms classified as spikes

were used for decoding, as the γ threshold increased, fewer waveforms remained for decoding.

Initially, we used 80% of trials to train the decoder and the remaining to test it. We analyzed

cross-validated decoding accuracy as a function of γ (sample recording sessions in Fig. 4a,b). The

decoding accuracy using threshold crossings (γ = 0) for the sample recording sessions in Fig. 4a and 4b

was close to chance levels (1 out of 8, 12.5%) for Monkey Pe (12.8%) and was also low for Monkey Wa

(20.1%). Using the network's classifications improved decoding accuracy relative to using threshold

crossings. The peak decoding benefit of using the network's spike classifications occurred at a low γ

threshold (Monkey Pe: γ = 0.16, Monkey Wa: γ = 0.16). Being very selective about the spikes used for

decoding (by setting a high γ threshold) did not have a large impact on decoding accuracy, which

appeared to plateau after the peak. We found that increments of the γ threshold did not remove the same

number of waveforms. A substantial proportion of waveforms were removed at the lowest γ threshold

tested (especially in Monkey Pe), and small increments of the γ threshold as it approached a value of 1

could also result in large increases in the proportion of removed waveforms (especially notable in Figure

4b).

Ideally, for the sake of simplicity during online BCI experiments, we could select a single γ

threshold and use it for all recording sessions. We wanted to find the lowest γ threshold that improved

decoding accuracy for the majority of recording sessions. We focused on lower γ thresholds because it

was a conservative approach, and because our intuition from single channels and results in example

sessions (Figure 4) showed it could have the greatest benefit for decoding. In order to ensure the γ

threshold we selected was cross-validated, for the remaining analyses we created two test sets for

decoding (training set: 60% of trials, test set 1: 20% of trials, test set 2: 20% of trials). The first test set

was used to determine the optimal value of the γ threshold and the second to determine its impact on

decoding. For each session, using the first test set, we found the maximum cross-validated decoding

accuracy at any γ threshold, and then searched for the lowest γ threshold that resulted in a decoding

accuracy within 99% of that maximum (Fig. 4c, d).

Since the optimal γ threshold varied between sessions, we computed the median across sessions

of these γ thresholds chosen with our cross-validation approach and rounded it to the nearest tested value

(Monkey Pe: $\gamma = 0.2$, Monkey Wa: $\gamma = 0.08$). We then used that median value as the γ threshold for all

sessions in the second test set and analyzed the change in decoding accuracy from decoding using

threshold crossings in that same test set, which we termed Δ % decoding accuracy (Fig. 4e, f). Combining

sessions from both animals, the average improvement in decoding accuracy was 3.9% (2-tailed, Wilcoxon

signed rank test; across subjects: $p < 0.0001$, Monkey Pe: $p < 0.0001$, Monkey Wa: $p = 0.057$). Thus, our

network's classifications tuned to the previously described γ thresholds resulted in a net benefit for

decoding performance across sessions compared to using threshold crossings. Although we could tune the

γ threshold for each session to maximize the decoding, our choice of a fixed γ threshold was more

consistent with the use of our network in an online decoding context, where it would be desirable to set a

constant γ threshold at the start of each session rather than tuning it as a free parameter. However, an

alternative strategy would be to collect a small data set at the start of each day to find the optimal gamma

value, and then continue experiments for the remainder of that day using the chosen value.

Given the ability of our network to improve decoding accuracy beyond that observed with

threshold crossings, we took advantage of our longitudinal recordings in a fixed paradigm to understand

how our network's performance varied as a function of time. Since there is mixed evidence in the

literature regarding decoding stability with long-term array implants, we were specifically interested in

how the passage of time since array implant (array implant age), and concomitant degradation of

recording quality, could influence our network's performance.

347
Figure 4. Using NAS spike classifications improved decoding accuracy in many sessions. (a-b) Percent
decoding accuracy (black line) and percent of waveforms removed (maroon line) at different γ thresholds for
an example recording session in Monkey Pe and Wa. The decoding accuracy increased for low γ thresholds
and then reached an asymptote as γ increased. At the highest γ thresholds, decoding accuracy fell to chance
(black, horizontal dotted line). Other labeled relevant metrics include: decoding accuracy with threshold
crossings (blue dot) maximum decoding accuracy (green dot), γ threshold with the maximum decoding
accuracy (grey dotted line), and Δ % decoding accuracy (the difference for a given session between the

decoding accuracy using the network classifications at a particular gamma threshold and the decoding
accuracy with threshold crossings). (c-d) Distribution of γ thresholds across sessions (Monkey Pe: N =36,
Monkey Wa: N = 16) that resulted in the maximum decoding accuracy for each session. (e-f) Distribution of Δ
% decoding accuracy across all sessions where the γ threshold was the median from the distributions in (c-d).
Mean Δ % decoding accuracy shown in red. For both monkeys, using spikes classified by the network
improved decoding accuracy on average across sessions; however, this improvement was only statistically
significant for Monkey Pe (2-tailed, Wilcoxon signed rank test, Monkey Pe: p < 0.0001, Monkey Wa: p =
0.057).

Impact of array age

First, we assessed how the overall quality of our neural data changed as a function of time. As the

time since the array implant increased, the percentage of waveforms that were assigned a very low

probability of being a spike (P(spike) < 0.02) also increased (Fig 5a; Spearman's rank order, Monkey Pe:

$\rho = 0.87$, $p<0.0001$; Monkey Wa: $\rho = 0.90$, $p<0.0001$). Conversely, the percentage of waveforms assigned

higher probabilities of being a spike (P(spike) > 0.70) decreased over time (Fig 5b; Monkey Pe: $\rho = -0.87$,

$p<0.0001$; Monkey Wa: $\rho = -0.94$, $p<0.0001$). These classification changes were consistent with our

qualitative observations that the arrays showed an increasing proportion of multi-unit activity (relative to

single-unit activity) and apparent noise on the array over time. We further found that the ratio of the

percentage of waveforms assigned a high P(spike) to the percentage of waveforms assigned a low

P(spike) served as a proxy for a signal to noise ratio metric, and it was highly correlated with the median

signal to noise ratio (across channels) of the array in each session (Supplementary Figure 2,

https://figshare.com/s/726cdc56c89113cc43d2). Both signal to noise metrics decreased over time, and the

decoding accuracy with threshold crossings also decreased the longer the array had been implanted (Fig

5c; Monkey Pe: $\rho = -0.86$, $p<0.0001$; Monkey Wa: $\rho = -0.69$, $p=0.004$).

Given the change in distribution of the types of waveforms present during the session over time,

we tried to optimize the γ threshold based on time since array implant. We used the same method as in

Fig. 4c-d to compute the γ thresholds with approximately maximum decoding (within 1%), except we

calculated the median of the early sessions (recorded 0-50 days post implant) and the median of the late

sessions (recorded >50 days post implant) separately. This did not prove to be a useful optimization as the

median values were similar between early and late sessions in both Monkey Pe ($\gamma_{early} = 0.25$, $\gamma_{late} = 0.18$)

and Monkey Wa ($\gamma_{early} = 0.06$, $\gamma_{late} = 0.08$). Decoding accuracy compared to threshold crossings (Δ %

decoding accuracy) was significantly increased in Monkey Pe (Figure 5d, 2-tailed, Wilcoxon signed rank

test, $p < 0.0001$) and was not significantly helped or hurt in Monkey Wa (p = 0.09). In line with the trends

in signal and noise over time, the decoding accuracies from later sessions (> 50 days post implant) were

helped more by the network classifications in both subjects than those from earlier sessions (Figure 5d,

Wilcoxon rank sum, Monkey Pe: $p = 0.01$; Monkey Wa: $p = 0.01$). When we normalized the decoding

accuracy at each γ threshold by the decoding accuracy using threshold crossings for each session and

separately averaged across early and late sessions, the increased benefit of using the network in the later

sessions compared to the earlier sessions was clear (Figure 5e).

Altogether, these results provide additional evidence that factors such as time since the array was

implanted and signal to noise ratio influence decoding accuracy and affect how noise removal impacts

decoding performance. Despite decreasing signal quality and increasing noise waveforms, the effect of

using our network classifications for noise removal prior to decoding was consistent in that it was most

often beneficial for decoding and at worst minimally detrimental. We also confirmed that these results

were not affected by poor γ threshold selection by using the maximum decoding accuracy regardless of γ

threshold to calculate Δ % decoding accuracy (Supplementary Figure 3a,

https://figshare.com/s/726cdc56c89113cc43d2), nor were the results substantially influenced by

variability in the number of trials across sessions (Supplementary Figure 3b,

https://figshare.com/s/726cdc56c89113cc43d2). Lastly, we assessed whether the benefits of our network

also held in another brain region (V4) recorded from different Utah arrays but in the same sessions from

the same animals in the test data set, and found similar results (Supplementary Figure 4,

https://figshare.com/s/726cdc56c89113cc43d2).

406
Figure 5. Noise on the array increased with the age of the array while decoding accuracy decreased in
Monkey Pe (blue) and Monkey Wa (orange). (a) Percentage of waveforms with a P(spike) < 0.02 over time. A
waveform with a P(spike) less than 0.02 was one that the network found very unlikely to be a spike. The
percentage of these unlikely spike waveforms increased as the array became older (Spearman's rank-order,
Monkey Pe: ϱ = 0.87, p < 0.0001; Monkey Wa: ϱ = 0.90, p < 0.0001). (b) Percentage of waveforms with a
P(spike) > 0.70 over time. The percentage of waveforms that the network found to be strongly spike-like
decreased as the array became older (Spearman's rank-order, Monkey Pe: ϱ = -0.87, p < 0.0001; Monkey
Wa: ϱ = -0.94, p < 0.0001). (c) Decoding accuracy with threshold crossings (i.e. γ = 0) decreased as the array
aged (Spearman's rank-order, Monkey Pe: ϱ = -0.86, p < 0.0001; Monkey Wa: ϱ = -0.69, p = 0.004). (d)
Change in percent decoding accuracy using network-classified spikes relative to decoding accuracy with

threshold crossings (Δ % decoding accuracy). We computed a distribution of the maximum γ threshold
(similar to Fig. 4c-d) for sessions that were 0-50 days post array implant and used the median to set the γ
threshold before computing decoding accuracy for those sessions. We repeated this for sessions more than 50
days post array implant. In Monkey Pe, using NAS classifications improved decoding accuracy (2-tailed,
Wilcoxon signed rank test, p < 0.0001) and in Monkey Wa, using the classifications neither hurt nor helped
decoding significantly (p = 0.09). In both subjects, the network helped decoding more in the late array
sessions (>50 days post implant) compared to the early sessions (2-tailed, Wilcoxon rank sum, Monkey Pe: p =
0.01; Monkey Wa: p = 0.01). (e) Mean normalized decoding accuracy across early sessions (open circles) and
late sessions (filled circles) as a function of γ threshold. Using the network classifications at any γ threshold
greater than zero was more helpful for late sessions than it was for early sessions.

Comparison to spike-sorting

In light of the mixed benefits of spike-sorting on decoding in the literature (Fraser et al. 2009;

Todorova et al. 2014; Christie et al. 2015; Dai et al. 2019), we sought to evaluate the relative merits of

manual spike-sorting and our network classifier on decoding accuracy in our data. We took advantage of

the offline spike-sorting that had already been applied to these data and calculated the decoding accuracy

of spike-sorted data (Fig. 6, data aggregated across subjects in the marginal histograms). Decoding using

spike-sorted waveforms was better than using threshold crossings (Fig. 6 right marginal; 2-tailed,

Wilcoxon signed rank test, $p < 0.0001$) similar to decoding with our network classifications (Fig. 6 top

marginal, data from Fig. 5d aggregated across subjects; $p < 0.0001$). Our network's classifications were at

least as helpful as manual spike-sorting for decoding relative to using threshold crossings (Fig. 6 center;

paired, 2-tailed, Wilcoxon signed rank test, Monkey Pe: $p = 0.75$; Monkey Wa: $p = 0.09$). Furthermore,

the automated real-time operation of our network confers a distinct advantage over manual spike-sorting.

Together, our analyses demonstrate that our network was able to produce classifications of spikes

and noise that matched our qualitative expectations and could be tuned quantitatively to adjust its

permissiveness. Compared to using threshold crossings, our network's classifications most often led to an

improvement or minimally harmful change in decoding accuracy, indicating that there was usually little

downside to the application of our network. These outcomes are valuable particularly in the context of a

BCI where real time operation and maximal decoding accuracy are prized.

Figure 6. Using NAS classifications was comparable to using spike-sorted data for decoding. Δ % decoding accuracy was calculated for both NAS classifications and spike-sorted waveforms as the change from decoding accuracy with threshold crossings. Top: Distribution of Δ % decoding accuracy using NAS classifications aggregated across subjects (γ threshold selected as in 5d). Using NAS classifications improved decoding accuracy from that with threshold crossings (2-tailed, Wilcoxon signed rank test, p < 0.0001). Right: Distribution of Δ % decoding accuracy using manual spike-sorting aggregated across subjects. Using spike-sorted classifications also improved decoding accuracy from that with threshold crossings (2-tailed, Wilcoxon signed rank test, p < 0.0001). Center: The joint distribution of Δ % decoding accuracy with spike-sorting and NAS classified spikes. Using our network's classifications was at least as helpful as spike-sorting for decoding (paired, 2-tailed, Wilcoxon signed rank test, Monkey Pe: p = 0.75; Monkey Wa: p = 0.09).

Discussion

By leveraging our pool of previously spike-sorted data, we trained a neural network classifier to

separate spikes from noise in extracellular electrophysiological recordings in real time. To assess the

value of this method, we used an objective criterion – the ability to decode remembered location from

prefrontal cortex in a memory-guided saccade task. We found that we could set a fixed γ threshold that

resulted in an improvement or at worst a small change in decoding accuracy for the majority of sessions,

and this effect persisted even as recording quality decreased over time. Compared to spike-sorting

(performed offline with substantial manual labor involved), classifying spikes with our network had

similar effects on decoding accuracy relative to threshold crossings and was less tedious.

Training the network

Developing a neural network trained on spike-sorted data allowed us to capture the essence of the

rules by which experienced researchers distinguish spikes from noise without explicitly defining all the

variables and exceptions, a standard challenge in spike classification (Wood et al. 2004). We found that a

simple neural network was quite good at capturing the nuances of the spike-sorted training set. In fact, the

network was sensitive enough to capture a researcher's specific spike-sorting tendencies, such that

networks trained on a particular individual's spike-sorted data performed better on classifying test data

from that individual than from other individual spike-sorters. Lee *et al.* (2017) similarly demonstrated the

promise of using spike-sorted data as a training set for retinal recordings with dense arrays. Our findings

extend this work in a context where the training data were less extensively curated (spike-sorting

performed by multiple researchers), the data were noisier (cortical recordings in an alert macaque

monkey) and the recording electrodes were spatially sparse (at least 150 μm apart for U-probes and 400

μm for Utah arrays), a situation that is common in numerous electrophysiology laboratories. A recent

related effort (Saif-Ur-Rehman et al. 2019) used a neural network trained on hand-sorted spiking data to

determine whether channels contained any spikes for the purpose of rejecting channels with only artifacts.

Our work is synergistic with their findings, and extends them to demonstrate that removal of noise from

single channels can lead to a positive impact on decoding accuracy.

There were potentially misclassifications in our training set, as human spike-sorting is both

subjective and prone to error (Rossant et al. 2016; Pedreira et al. 2012). However, the network was

trained on many waveforms to minimize the impact of any confounders, including waveforms from

multiple subjects, brain regions, and human spike-sorters. An ideal and even more generalizable training

set might include waveforms from different research groups, artificially simulated neural waveforms and

noise in which ground truth could be established, and/or pre-defined quantities of certain types of spikes

(e.g. shifted spikes, slow and fast spike waveforms) and noise (e.g. electrical artifacts) to target what the

network learns. However, no matter how much training data is used, an ideal training set could only be

defined in the context of objective metrics to assess the trained network's performance.

Evaluating the network with decoding

Since there is no obvious ground truth for classifying spikes from extracellular array recordings,

one objective measure with practical benefit for BCI performance is how well we could decode

information from neural activity. We used independent test data to assess the effect of classifications from

our trained network on decoding accuracy. Although the expectation might be that removing noise from

neural data would improve decoding, historically doing so with spike-sorted classifications has had mixed

effects, in some cases hurting performance (Todorova et al. 2014). Nevertheless, many BCIs currently

operate with some amount of online noise removal or visual inspection (such as disabling visibly noisy

channels) to pre-process neural data before decoding (Homer et al. 2013; Hochberg et al. 2006; Sadtler et

al. 2014; Chase, Kass, and Schwartz 2012). The question of whether to spike-sort BCI data prior to

decoding or simply use all threshold crossings has been a source of debate with no clear resolution.

Our findings provide additional support, across multiple sessions over time, that removing certain

noise waveforms prior to decoding provides an advantage over using all threshold crossings, consistent

with findings from Fraser *et al.* (2009) and Christie *et al.* (2015). Contrary to our results, another study by

Todorova *et al.* (2014) found that using spike-sorted waveforms hurt decoding when noise waveforms

were discarded. It is difficult to speculate why removing noise waveforms hurt their result but helped ours

given that our methods of noise removal were different. Todorova *et al*. also found assigning noise

waveforms from spike-sorting to a new unit, rather than discarding them, improved decoding relative to

threshold crossings (2014). Yet, when we assigned our noise waveforms to separate units, decoding

accuracy was worse or unchanged compared to discarding noise waveforms both with our spike-sorted

classifications and our network classifications (Supplementary Figure 5,

https://figshare.com/s/726cdc56c89113cc43d2). Importantly, we defined 'noise' operationally as any

waveform that did not exceed the γ threshold of our network setting. This definition of noise surely

included both electrical artifacts as well as indistinct shapes that were actually neural in origin. Removal

of waveforms from the former class could only help decoding, but removal of the latter class might

actually harm decoding if the multiunit activity contained in those waveforms has information about the

condition of interest for decoding.

518   Apparent noise in neuronal activity, in addition to changing the activity of single electrode

channels, can also be correlated across channels. In the activity of pairs of single neurons, such

fluctuations in trial-to-trial correlated variability are sometimes termed "noise correlation" (also known as

spike count correlation, or r_{sc}). Noise correlation can have a substantial impact on the ability of a decoder

to extract information from neuronal populations (Kohn et al. 2016; Averbeck, Latham, and Pouget

2006), and the activity of multi-unit groups of neurons has a higher noise correlation than that of the

constituent pairs of neurons (Cohen and Kohn 2011). Since our network acted on threshold crossings,

which typically contain the activity of many individual neurons, it likely also impacted the magnitude of

the noise correlation between channels. Our decoder assumed that the noise on each unit was

independent, a choice common to BCI, which permitted training the decoder with a smaller quantity of

trials than is necessary to learn the covariance structure in the population. The effect of our network on

decoding surely depends on not only the structure of the network and the choice of γ threshold, but also

the structure of noise present in the population and the sensitivity of the decoder to that noise.

531   In addition to understanding how the type of noise present in the data impacts decoding, it may

also be useful to evaluate the types of neural waveforms that contribute to decoding. Different levels of

single and multi-unit activity are captured during a neural recording depending on the threshold set by the

researcher (i.e. the minimum voltage level at which the neural activity is marked as a spike). By adjusting

this threshold, we change the candidate waveforms available for decoding. Oby *et al.* (2016) found that

the optimal threshold depended on the type of information being extracted from neural activity. Another

study found that higher thresholds, which captured less multi-unit activity, resulted in worse decoding of

direction from M1 (Christie et al. 2015). These studies in the context of our own findings highlight the

need to identify specific types of waveforms that contribute to the decodable information in different

brain regions and task contexts.

Other variables that impact decoding accuracy

A key concern for practical implementation of BCIs is decoding stability. Array recordings often

get visibly noisier over time, potentially as a result of an immune response to the implant (Ward et al.

2009) or a physical shift in position (Perge et al. 2013). In our study, as the time since array implant

increased there were more "low probability" waveforms and fewer "high probability" waveforms,

indicating the array had fewer well-defined single-unit waveforms. In line with this, several other studies

with chronic array implants have found that the number of single-units decreased over time (Dickey et al.

2009; Downey et al. 2018; Fraser and Schwartz 2012; Tolias et al. 2007). Nevertheless, there are mixed

findings on the stability of decoding performance in chronic array implants. Some studies have found

decoder performance with threshold crossings remained stable over time (Gilja et al. 2012; Chestek et al.

2011; Nuyujukian et al. 2014; Flint et al. 2016); however, other studies, including our own, observed a

decrease in decoding accuracy over time (Perge et al. 2014; Wang et al. 2014). Unlike the previous

literature investigating the effects of threshold crossings and spike-sorting on decoding performance, we

used neural activity from PFC, where decoding accuracy is typically lower (Meyers et al. 2008; Rizzuto et

al. 2005; Tremblay et al. 2015; Jia et al. 2017; Boulay et al. 2016; Parthasarathy et al. 2017; Spaak et al.

2017) than in motor cortex (Sadtler et al. 2015; Masse et al. 2014; Collinger et al. 2013; Koralek et al.

2012). Stability of decoding accuracy with array age may also depend on the brain region of the implant,

the subject's task, initial decoding performance, and the choice to train the decoder daily (Chestek et al.

2011; Gilja et al. 2012) or hold it constant (Nuyujukian et al. 2014). The beneficial effects of our network

on decoding were particularly salient in the case of older array implants, where decoding accuracy had

decreased over time.

Extensions for NAS

Our neural network-based spike sorter is a promising tool for both offline spike-sorting and

improving online decoding performance. However, in designing our network we only scratched the

surface of many potential avenues to address these challenges. We found that using networks with

different numbers of hidden units and layers did not substantially alter decoding accuracy even though

there were some differences in how these different sized networks classified waveforms. Given that our

network was relatively simple, it would be possible to implement similar operations with alternative

algorithms such as logistic regression. We chose a neural network because it was easily trainable from

existing data and there are many ways to modularly build upon its complexity. Although we opted to use

50 hidden units and one hidden layer, it is possible that a more complex network with additional filtering

operations and more categories of waveform classification may result in improved decoding performance

and could help to create a more robust spike-sorter or a pre-processing step for offline analyses. However,

our work had the value of exploring how a smaller network trained on spike-sorted data could identify

features that were most valuable for decoding. While training on spike-sorted data was an efficient choice

because of its easy availability, it may not be the best choice in regimes where canonical spike-shapes,

which spike-sorted classifications prioritize, do not necessarily carry the most decodable information

compared to less well-defined multi-unit activity (Stark and Abeles 2007; Chestek et al. 2011). If the goal

is to improve decoding performance, it might be valuable to train a network to select waveforms or units

that positively contribute to decoding. Ventura and Todorova (2015) developed a method for identifying

the information contribution of units for decoding. Such a method could be used to develop a training set

of neural waveforms that are assigned a label based on how much they positively or negatively

contributed to decoding.

Overall, we developed a new tool for pre-processing BCI data that classified threshold crossings

in a tunable manner that was beneficial for decoding. Furthermore, we showed that spike-sorted

waveform data are an underused training set with potential for building spike classification networks. A

neural network-based spike classifier has the potential to reduce the need for human intervention in spike-

sorting while maintaining sensitivity to nuances that many automated sorting algorithms miss. Our

tunable classifier is a step toward pre-processing methods that both optimize and stabilize online decoding

performance.

Acknowledgements

594 We would like to thank Samantha Schmitt for assistance with data collection and Ben Cowley, Byron Yu,

595 and Steve Chase for their valuable insight on this project.

Grants

D.I. was supported by National Science Foundation (NSF) DBI 1659611, National Institutes of Health

(NIH) T32 GM008208, and the ARCS foundation Thomas-Pittsburgh Chapter Award. M.A.S. was

supported by NIH R01EY022928, R01MH118929, R01EB026953, and P30EY008098; NSF NCS

1734901; a career development grant and an unrestricted award from Research to Prevent Blindness; the

Eye and Ear Foundation of Pittsburgh. R.C.W. was supported by a Richard King Mellon

Foundation Presidential Fellowship in the Life Sciences. S.B.K. was supported by T32 EY017271-08.

Disclosures

606 The authors declare no conflicts of interest.

607
References

Abadi, Martín, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S.
Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow,
Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser,
Manjunath Kudlur, Josh Levenberg, Dan Mane, Rajat Monga, Sherry Moore, Derek Murray,
Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul
Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viegas, Oriol Vinyals, Pete Warden,
Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. 2016. 'TensorFlow: Large-
Scale Machine Learning on Heterogeneous Distributed Systems'.
Averbeck, B. B., P. E. Latham, and A. Pouget. 2006. 'Neural correlations, population coding and
computation', *Nat Rev Neurosci*, 7: 358-66.
Bishop, W., C. C. Chestek, V. Gilja, P. Nuyujukian, J. D. Foster, S. I. Ryu, K. V. Shenoy, and B. M. Yu.
2014. 'Self-recalibrating classifiers for intracortical brain-computer interfaces', *J Neural Eng*, 11:
026001.
Boulay, C. B., F. Pieper, M. Leavitt, J. Martinez-Trujillo, and A. J. Sachs. 2016. 'Single-trial decoding of
intended eye movement goals from lateral prefrontal cortex neural ensembles', *J Neurophysiol*,
115: 486-99.

Chase, S. M., R. E. Kass, and A. B. Schwartz. 2012. 'Behavioral and neural correlates of visuomotor
adaptation observed through a brain-computer interface in primary motor cortex', *J Neurophysiol*,
108: 624-44.
Chaure, F. J., H. G. Rey, and R. Quian Quiroga. 2018. 'A novel and fully automatic spike-sorting
implementation with variable number of features', *J Neurophysiol*, 120: 1859-71.
Chestek, C. A., V. Gilja, P. Nuyujukian, J. D. Foster, J. M. Fan, M. T. Kaufman, M. M. Churchland, Z.
Rivera-Alvidrez, J. P. Cunningham, S. I. Ryu, and K. V. Shenoy. 2011. 'Long-term stability of
neural prosthetic control signals from silicon cortical arrays in rhesus macaque motor cortex', *J
Neural Eng*, 8: 045005.
Chollet, François. 2015. "Keras." In.
Christie, B. P., D. M. Tat, Z. T. Irwin, V. Gilja, P. Nuyujukian, J. D. Foster, S. I. Ryu, K. V. Shenoy, D.
E. Thompson, and C. A. Chestek. 2015. 'Comparison of spike sorting and thresholding of voltage
waveforms for intracortical brain-machine interface performance', *J Neural Eng*, 12: 016009.
Chung, J. E., J. F. Magland, A. H. Barnett, V. M. Tolosa, A. C. Tooker, K. Y. Lee, K. G. Shah, S. H.
Felix, L. M. Frank, and L. F. Greengard. 2017. 'A Fully Automated Approach to Spike Sorting',
Neuron, 95: 1381-94 e6.
Cohen, M. R., and A. Kohn. 2011. 'Measuring and interpreting neuronal correlations', *Nat Neurosci*, 14:
811-9.
Collinger, J. L., B. Wodlinger, J. E. Downey, W. Wang, E. C. Tyler-Kabara, D. J. Weber, A. J.
McMorland, M. Velliste, M. L. Boninger, and A. B. Schwartz. 2013. 'High-performance
neuroprosthetic control by an individual with tetraplegia', *Lancet*, 381: 557-64.
Dai, J., P. Zhang, H. Sun, X. Qiao, Y. Zhao, J. Ma, S. Li, J. Zhou, and C. Wang. 2019. 'Reliability of
motor and sensory neural decoding by threshold crossings for intracortical brain-machine
interface', *J Neural Eng*, 16: 036011.
Dickey, A. S., A. Suminski, Y. Amit, and N. G. Hatsopoulos. 2009. 'Single-unit stability using
chronically implanted multielectrode arrays', *J Neurophysiol*, 102: 1331-9.
Diederik P. Kingma, Jimmy Ba. 2015. "Adam: a Method for Stochastic Optimization." In *International
Conference on Learning Representations*.
Downey, J. E., N. Schwed, S. M. Chase, A. B. Schwartz, and J. L. Collinger. 2018. 'Intracortical
recording stability in human brain-computer interface users', *J Neural Eng*, 15: 046016.
Flint, R. D., M. R. Scheid, Z. A. Wright, S. A. Solla, and M. W. Slutzky. 2016. 'Long-Term Stability of
Motor Cortical Activity: Implications for Brain Machine Interfaces and Optimal Feedback
Control', *J Neurosci*, 36: 3623-32.
Fraser, G. W., S. M. Chase, A. Whitford, and A. B. Schwartz. 2009. 'Control of a brain-computer
interface without spike sorting', *J Neural Eng*, 6: 055004.
Fraser, G. W., and A. B. Schwartz. 2012. 'Recording from the same neurons chronically in motor cortex',
J Neurophysiol, 107: 1970-8.
Gilja, V., P. Nuyujukian, C. A. Chestek, J. P. Cunningham, B. M. Yu, J. M. Fan, M. M. Churchland, M.
T. Kaufman, J. C. Kao, S. I. Ryu, and K. V. Shenoy. 2012. 'A high-performance neural prosthesis
enabled by control algorithm design', *Nat Neurosci*, 15: 1752-7.
Golub, M. D., B. M. Yu, and S. M. Chase. 2015. 'Internal models for interpreting neural population
activity during sensorimotor control', *Elife*, 4.
Hochberg, L. R., D. Bacher, B. Jarosiewicz, N. Y. Masse, J. D. Simeral, J. Vogel, S. Haddadin, J. Liu, S.
S. Cash, P. van der Smagt, and J. P. Donoghue. 2012. 'Reach and grasp by people with tetraplegia
using a neurally controlled robotic arm', *Nature*, 485: 372-5.
Hochberg, L. R., M. D. Serruya, G. M. Friehs, J. A. Mukand, M. Saleh, A. H. Caplan, A. Branner, D.
Chen, R. D. Penn, and J. P. Donoghue. 2006. 'Neuronal ensemble control of prosthetic devices by
a human with tetraplegia', *Nature*, 442: 164-71.
Homer, M. L., A. V. Nurmikko, J. P. Donoghue, and L. R. Hochberg. 2013. 'Sensors and decoding for
intracortical brain computer interfaces', *Annu Rev Biomed Eng*, 15: 383-405.

Jia, N., S. L. Brincat, A. F. Salazar-Gomez, M. Panko, F. H. Guenther, and E. K. Miller. 2017. 'Decoding
676   of intended saccade direction in an oculomotor brain-computer interface', *J Neural Eng*, 14:
677   046007.
678   Kelly, R. C., M. A. Smith, J. M. Samonds, A. Kohn, A. B. Bonds, J. A. Movshon, and T. S. Lee. 2007.
679   'Comparison of recordings from microelectrode arrays and single electrodes in the visual cortex',
680   *J Neurosci*, 27: 261-4.
681   Khanna, S. B., A. C. Snyder, and M. A. Smith. 2019. 'Distinct Sources of Variability Affect Eye
682   Movement Preparation', *J Neurosci*, 39: 4511-26.
683   Kloosterman, F., S. P. Layton, Z. Chen, and M. A. Wilson. 2014. 'Bayesian decoding using unsorted
684   spikes in the rat hippocampus', *J Neurophysiol*, 111: 217-27.
685   Kohn, A., R. Coen-Cagli, I. Kanitscheider, and A. Pouget. 2016. 'Correlations and Neuronal Population
686   Information', *Annu Rev Neurosci*, 39: 237-56.
687   Koralek, A. C., X. Jin, J. D. Long, 2nd, R. M. Costa, and J. M. Carmena. 2012. 'Corticostriatal plasticity
688   is necessary for learning intentional neuroprosthetic skills', *Nature*, 483: 331-5.
689   Lewicki, M. S. 1998. 'A review of methods for spike sorting: the detection and classification of neural
690   action potentials', *Network*, 9: R53-78.
691   Masse, N. Y., B. Jarosiewicz, J. D. Simeral, D. Bacher, S. D. Stavisky, S. S. Cash, E. M. Oakley, E.
692   Berhanu, E. Eskandar, G. Friehs, L. R. Hochberg, and J. P. Donoghue. 2014. 'Non-causal spike
693   filtering improves decoding of movement intention for intracortical BCIs', *J Neurosci Methods*,
694   236: 58-67.
695   Meyers, E. M., D. J. Freedman, G. Kreiman, E. K. Miller, and T. Poggio. 2008. 'Dynamic population
696   coding of category information in inferior temporal and prefrontal cortex', *J Neurophysiol*, 100:
697   1407-19.
698   Nuyujukian, P., J. C. Kao, J. M. Fan, S. D. Stavisky, S. I. Ryu, and K. V. Shenoy. 2014. 'Performance
699   sustaining intracortical neural prostheses', *J Neural Eng*, 11: 066003.
700   Oby, E. R., S. Perel, P. T. Sadtler, D. A. Ruff, J. L. Mischel, D. F. Montez, M. R. Cohen, A. P. Batista,
701   and S. M. Chase. 2016. 'Extracellular voltage threshold settings can be tuned for optimal
702   encoding of movement and stimulus parameters', *J Neural Eng*, 13: 036009.
703   Parthasarathy, A., R. Herikstad, J. H. Bong, F. S. Medina, C. Libedinsky, and S. C. Yen. 2017. 'Mixed
704   selectivity morphs population codes in prefrontal cortex', *Nat Neurosci*, 20: 1770-79.
705   Pedreira, Carlos, Juan Martinez, Matias J. Ison, and Rodrigo Quian Quiroga. 2012. 'How many neurons
706   can we see with current spike sorting algorithms?', *Journal of Neuroscience Methods*, 211: 58-65.
707   Perge, J. A., M. L. Homer, W. Q. Malik, S. Cash, E. Eskandar, G. Friehs, J. P. Donoghue, and L. R.
708   Hochberg. 2013. 'Intra-day signal instabilities affect decoding performance in an intracortical
709   neural interface system', *J Neural Eng*, 10: 036004.
710   Perge, J. A., S. Zhang, W. Q. Malik, M. L. Homer, S. Cash, G. Friehs, E. N. Eskandar, J. P. Donoghue,
711   and L. R. Hochberg. 2014. 'Reliability of directional information in unsorted spikes and local
712   field potentials recorded in human motor cortex', *J Neural Eng*, 11: 046007.
713   Rey, H. G., C. Pedreira, and R. Quian Quiroga. 2015. 'Past, present and future of spike sorting
714   techniques', *Brain Res Bull*, 119: 106-17.
715   Rizzuto, D. S., A. N. Mamelak, W. W. Sutherling, I. Fineman, and R. A. Andersen. 2005. 'Spatial
716   selectivity in human ventrolateral prefrontal cortex', *Nat Neurosci*, 8: 415-7.
717   Rossant, C., S. N. Kadir, D. F. M. Goodman, J. Schulman, M. L. D. Hunter, A. B. Saleem, A. Grosmark,
718   M. Belluscio, G. H. Denfield, A. S. Ecker, A. S. Tolias, S. Solomon, G. Buzsaki, M. Carandini,
719   and K. D. Harris. 2016. 'Spike sorting for large, dense electrode arrays', *Nat Neurosci*, 19: 634-41.
720   Sadtler, P. T., K. M. Quick, M. D. Golub, S. M. Chase, S. I. Ryu, E. C. Tyler-Kabara, B. M. Yu, and A. P.
721   Batista. 2014. 'Neural constraints on learning', *Nature*, 512: 423-6.
722   Sadtler, P. T., S. I. Ryu, E. C. Tyler-Kabara, B. M. Yu, and A. P. Batista. 2015. 'Brain-computer interface
723   control along instructed paths', *J Neural Eng*, 12: 016015.

Saif-Ur-Rehman, M., R. Lienkamper, Y. Parpaley, J. Wellmer, C. Liu, B. Lee, S. Kellis, R. A. Andersen,
I. Iossifidis, T. Glasmachers, and C. Klaes. 2019. 'SpikeDeeptector: A deep-learning based
method for detection of neural spiking activity', *J Neural Eng*, 16.
Santhanam, G., M. Sahani, S. Ryu, and K. Shenoy. 2004. 'An extensible infrastructure for fully automated
spike sorting during online experiments', *Conf Proc IEEE Eng Med Biol Soc*, 6: 4380-4.
Schafer, R. J., and T. Moore. 2011. 'Selective attention from voluntary control of neurons in prefrontal
cortex', *Science*, 332: 1568-71.
Shoham, S., M. R. Fellows, and R. A. Normann. 2003. 'Robust, automatic spike sorting using mixtures of
multivariate t-distributions', *J Neurosci Methods*, 127: 111-22.
Snyder, A. C., M. J. Morais, A. Kohn, and M. A. Smith. 2014. 'Correlations in V1 are reduced by
stimulation outside the receptive field', *J Neurosci*, 34: 11222-7.
Snyder, A. C., M. J. Morais, C. M. Willis, and M. A. Smith. 2015. 'Global network influences on local
functional connectivity', *Nat Neurosci*, 18: 736-43.
Snyder, A. C., and M. A. Smith. 2015. 'Stimulus-dependent spiking relationships with the EEG', *J
Neurophysiol*, 114: 1468-82.
Spaak, E., K. Watanabe, S. Funahashi, and M. G. Stokes. 2017. 'Stable and Dynamic Coding for Working
Memory in Primate Prefrontal Cortex', *J Neurosci*, 37: 6503-16.
Stark, E., and M. Abeles. 2007. 'Predicting movement from multiunit activity', *J Neurosci*, 27: 8387-94.
Todorova, S., P. Sadtler, A. Batista, S. Chase, and V. Ventura. 2014. 'To sort or not to sort: the impact of
spike-sorting on neural decoding performance', *J Neural Eng*, 11: 056005.
Tolias, A. S., A. S. Ecker, A. G. Siapas, A. Hoenselaar, G. A. Keliris, and N. K. Logothetis. 2007.
'Recording chronically from the same neurons in awake, behaving primates', *J Neurophysiol*, 98:
3780-90.
Tremblay, S., G. Doucet, F. Pieper, A. Sachs, and J. Martinez-Trujillo. 2015. 'Single-Trial Decoding of
Visual Attention from Local Field Potentials in the Primate Lateral Prefrontal Cortex Is
Frequency-Dependent', *J Neurosci*, 35: 9038-49.
Velliste, M., S. Perel, M. C. Spalding, A. S. Whitford, and A. B. Schwartz. 2008. 'Cortical control of a
prosthetic arm for self-feeding', *Nature*, 453: 1098-101.
Ventura, V., and S. Todorova. 2015. 'A computationally efficient method for incorporating spike
waveform information into decoding algorithms', *Neural Comput*, 27: 1033-50.
Wang, D., Q. Zhang, Y. Li, Y. Wang, J. Zhu, S. Zhang, and X. Zheng. 2014. 'Long-term decoding
stability of local field potentials from silicon arrays in primate motor cortex during a 2D center
out task', *J Neural Eng*, 11: 036009.
Ward, M. P., P. Rajdev, C. Ellison, and P. P. Irazoqui. 2009. 'Toward a comparison of microelectrodes for
acute and chronic recordings', *Brain Res*, 1282: 183-200.
Wood, F., M. J. Black, C. Vargas-Irwin, M. Fellows, and J. P. Donoghue. 2004. 'On the variability of
manual spike sorting', *IEEE Trans Biomed Eng*, 51: 912-8.
761