A neural network for online spike classification that improves decoding accuracy

Deepa Issar[1,2], Ryan C. Williamson[2,3,5], Sanjeev B. Khanna[1], and Matthew A. Smith[4,5,6#]

[1]Department of Bioengineering, University of Pittsburgh, Pittsburgh, PA, USA
[2]University of Pittsburgh School of Medicine, University of Pittsburgh, Pittsburgh, PA, USA
[3]Department of Machine Learning, Carnegie Mellon University, Pittsburgh, PA, USA
[4]Department of Biomedical Engineering, Carnegie Mellon University, Pittsburgh, PA, USA
[5]Carnegie Mellon Neuroscience Institute, Pittsburgh, PA, USA
[6]Department of Ophthalmology, University of Pittsburgh School of Medicine, University of Pittsburgh, Pittsburgh, PA, USA

#: Address correspondence to:
Matthew A. Smith
Carnegie Mellon University
Department of Biomedical Engineering and Neuroscience Institute
Email: matt@smithlab.net

Running head: A neural network for online spike classification

1   **Abstract**

Separating neural signals from noise can improve brain-computer interface performance and

stability. However, most algorithms for separating neural action potentials from noise are not suitable for

use in real time and have shown mixed effects on decoding performance. With the goal of removing noise

that impedes online decoding, we sought to automate the intuition of human spike-sorters to operate in

real time with an easily tunable parameter governing the stringency with which spike waveforms are

classified. We trained an artificial neural network with one hidden layer on neural waveforms that were

hand-labeled as either spikes or noise. The network output was a likelihood metric for each waveform it

classified, and we tuned the network's stringency by varying the minimum likelihood value for a

waveform to be considered a spike. Using the network's labels to exclude noise waveforms, we decoded

remembered target location during a memory-guided saccade task from electrode arrays implanted in

prefrontal cortex of rhesus macaque monkeys. The network classified waveforms in real time, and its

classifications were qualitatively similar to those of a human spike-sorter. Compared to decoding with

threshold crossings, in most sessions we improved decoding performance by removing waveforms with

low spike likelihood values. Furthermore, decoding with our network's classifications became more

beneficial as time since array implantation increased. Our classifier serves as a feasible preprocessing

step, with little risk of harm, that could be applied to both offline neural data analyses and online

decoding.

20   **New & Noteworthy**

21   While there are many spike-sorting methods that isolate well-defined single units, these methods typically

22   involve human intervention and have inconsistent effects on decoding. We used human classified neural

23   waveforms as training data to create an artificial neural network that could be tuned to separate spikes

24   from noise that impaired decoding. We found that this network operated in real time and was suitable for

25   both offline data processing and online decoding.

Introduction

Brain computer interfaces (BCIs) have been used as both research tools to understand neural

phenomena (Sadtler et al. 2014; Chase, Kass, and Schwartz 2012; Golub, Yu, and Chase 2015; Schafer

and Moore 2011) and devices to improve patient control of prosthetics (Velliste et al. 2008; Hochberg et

al. 2012; Collinger et al. 2013). BCIs interpret neural signals arising from electrodes implanted in the

cortex using real time decoding algorithms; however, their performance is limited by the difficulty of

isolating the activity of individual neurons from extracellular voltage signals ("spike-sorting"), the

characteristics of the information present in individual neurons and multi-unit activity (their "tuning"), as

well as the nuances of interactions among neurons (Averbeck, Latham, and Pouget 2006). Refining the

raw data is necessary to improve BCI performance, but identifying waveforms that contain relevant

information is challenging.

One common noise removal method is to use all waveforms crossing a minimum voltage

threshold for decoding, where all waveforms on a particular channel are considered to be from a single

neural "unit" (Lewicki 1998; Christie et al. 2015). Using threshold crossings also serves to reduce the

amount of stored data. However, threshold crossings often capture noise and the summed activity of

multiple nearby neurons, called multi-unit activity, on each channel (Stark and Abeles 2007; Rey,

Pedreira, and Quian Quiroga 2015). Alternatively, since waveforms with the characteristic shape of an

action potential are the focus of most offline neural data analyses, a different approach is to isolate well-

defined spike waveforms from the threshold crossings via spike-sorting, and use only those waveforms

for decoding (Lewicki 1998; Rey, Pedreira, and Quian Quiroga 2015). Unfortunately, most spike-sorting

techniques are unsuitable for BCI use because they are time-intensive and require manual refinement.

Furthermore, even with the development of real time, automated spike-sorting algorithms (Chung

et al. 2017; Chaure, Rey, and Quian Quiroga 2018), deciding which waveforms should be used by the

decoding algorithm is challenging. There is typically no clear ground truth for what constitutes a spike

waveform based solely on sparse extracellular recordings (Rey, Pedreira, and Quian Quiroga 2015; Wood

et al. 2004; Pedreira et al. 2012; Rossant et al. 2016), except in the case of a few rare data sets

(Anastassiou et al. 2015; Neto et al. 2016). While some studies have found spike-sorted units improved

decoding performance (Todorova et al. 2014; Ventura and Todorova 2015; Kloosterman et al. 2014;

Santhanam et al. 2004), others have found that using pooled spikes from threshold crossings resulted in

comparable or better decoding that was more stable over time (Christie et al. 2015; Fraser et al. 2009;

Chestek et al. 2011; Gilja et al. 2012; Dai et al. 2019). These conflicting results highlight the gap in our

understanding of what information in neural recordings is most valuable for BCIs. Even within studies,

there are inconsistent effects of spike-sorting on decoding, both between subjects and over time (Fraser et

al. 2009; Christie et al. 2015). It is also difficult to compare the effects of spike-sorting on decoding

performance across studies due to the inherent variability in spike-sorting techniques (Wood et al. 2004;

Rossant et al. 2016; Pedreira et al. 2012; Rey, Pedreira, and Quian Quiroga 2015) and differences in brain

regions, parameters being studied, and decoding algorithms that may influence which waveforms are the

most decodable (Fraser et al. 2009; Oby et al. 2016; Chestek et al. 2011; Lewicki 1998; Bishop et al.

2014). Furthermore, it is unclear whether spike-sorting, where the goal is to define isolated single-units, is

the best-suited approach for preprocessing data for decoding, where multi-unit activity has been shown to

be sufficient in some cases (Stark and Abeles 2007).

Given spike-sorting's history of variable effects on decoding performance, we sought to avoid

explicitly sorting our data and instead developed an easily tunable spike classifier that could objectively

and efficiently assign waveforms to one of two classes: spike or noise. To achieve this goal, we sought a

classification approach that would (1) take advantage of the spike-sorted waveforms from previous

analyses that formed a readily available, labeled training data set; (2) output a likelihood of being a spike

for each waveform so we could simply adjust the minimum cutoff for binary spike classification; (3) once

trained could operate in real time. We built a neural network classifier that satisfied these three criteria.

To evaluate our classifier's performance, we decoded the activity of sparse electrode arrays implanted in

prefrontal cortex (PFC), and compared decoding accuracy of task condition with all threshold crossings to

decoding accuracy with the waveforms selected by our classifier. We also assessed how decoding

performance changed as a function of the stringency of our classifier (i.e. the minimum cutoff for spike

classification) and explored how decoding accuracy with our classifier changed as a function of time

since the array implantation (array implant age).

By removing waveforms that the network identified as unlikely to be spikes, we improved

decoding performance for most sessions relative to decoding with all threshold crossings. Moreover, in

the remaining sessions there was no substantial detriment to decoding accuracy, meaning we could apply

our method with little risk of harming decoding performance. Our network classifications continued to

improve decoding accuracy in sessions recorded long after array implantation, even though the overall

decoding accuracy decreased and the array recordings became noisier. Thus, our real time, tunable

waveform classifier demonstrates promise for long-term BCI applications and for efficient offline

preprocessing.

90   **Materials and Methods**

We trained a neural network, using a database of spike-sorted waveforms, to assign waveforms to

a spike or noise class. We then tested the network's classifications with another data set that was

independent from the training set. In contrast to the offline, human supervised spike-sorting that was used

to label the training data, our network did not sort waveforms into isolated single-units, but rather

assigned spike or noise classifications to individual waveforms (hence its name *Not A Sorter, or NAS*). To

evaluate the network's classifications, we decoded task location using only waveforms labeled as spikes

by the network and compared the accuracy to decoding accuracy using all threshold crossings. All

experimental procedures were approved by the Institutional Animal Care and Use Committee of the

University of Pittsburgh and were performed in accordance with the United States National Institutes of

Health's *Guidelines for the Care and Use of Laboratory Animals*.

Neural recordings

We analyzed neural recordings from six adult male rhesus macaques (*Macaca mulatta*) which

had previously been spike-sorted for ongoing experiments in the laboratory. Data from four subjects were

used to train our spike-classifying neural network, and data from the remaining two subjects (Monkey Pe

and Monkey Wa) were used to assess decoding accuracy using the network's classifications. Raw

recordings from both 96-electrode 'Utah' arrays (Blackrock Microsystems, Salt Lake City, UT) and 16-

channel linear microelectrode arrays (U-Probe, Plexon, Dallas, TX) were band-pass filtered from 0.3 to

7,500 Hz, digitized at 30 kHz, and amplified by a Grapevine system (Ripple, Salt Lake City, UT). The

inter-electrode distance on the 'Utah' arrays was 400 μm and on the linear arrays was 150 or 200 μm,

beyond the range over which the two extracellular electrodes are likely to capture the waveform of a

single neuron. For each recording session, a threshold (V_T) was defined for each channel independently

based on the root-mean-squared voltage of the waveforms (V_{RMS}) recorded on that channel at the

beginning of the session (i.e. $V_T = V_{RMS}*X$, where X was a multiplier set by the experimenter). Each time

the signal crossed that threshold, a 52-sample waveform segment was captured (i.e. a threshold crossing),

with 15 samples prior to and 36 samples following the sample in which the threshold excursion occurred.

Offline spike-sorting

All data in this work were spike-sorted to identify well-defined single-units for previous studies.

This pre-sorted data was used to create the labeled training set for this study. Waveform segments were

initially sorted into spike units and noise using a custom, offline MATLAB spike-sorting algorithm that

used an automated competitive mixture decomposition method (Shoham, Fellows, and Normann 2003).

These automated classifications for each recording session were subsequently refined manually by a

researcher using custom MATLAB software (https://github.com/smithlabvision/spikesort). The researcher

modified the classifications on each channel based on visualization of the overlaid waveform clusters,

projections of the waveforms in PCA space (to assess how many clusters were present), the inter-spike

interval distribution of any potential single-unit (ensuring it contained few waveforms separated by less

than a sensible refractory period), and whether each potential single-unit was stationary (i.e. present for

the majority of the recording session). While only a single researcher spike-sorted the waveforms from

any particular session, the data in the training set (7 sessions total) collectively consisted of data spike-

sorted by four different researchers. If multiple unique spike waveform shapes were present on a channel,

the sorter would label those as different units.

Training data set

We sought a diverse neural waveform training set that captured a variety of subjects, brain

regions, implanted array ages (i.e. number of days since the array was implanted) and recording devices

(Table 1). The four training data set subjects each had a 96-electrode 'Utah' array implanted in right or

left hemisphere visual area V4. Two of those subjects also had 16-channel U-probe recordings from the

frontal eye field (FEF), located in the anterior bank of the arcuate sulcus. Data from two sessions were

used for three of the subjects: one session recorded shortly after the array implant, and one session

recorded at least four months later. For the fourth subject, only a single recording session recorded shortly

after the array implant was used because there were no later recordings from that array. These recordings

were collected and sorted as part of previous studies which describe the experimental preparations in

detail (Khanna, Snyder, and Smith 2019; Snyder et al. 2014; Snyder et al. 2015; Snyder and Smith 2015).

Data in the training set were assigned a label of 0 or 1. If there were multiple single-units identified by the

sorter on a particular channel, they were not distinguished in the training set and all were treated as spike

waveforms (labeled as 1). We only included data from channels with very distinct spike waveforms,

defined as channels with a signal-to-noise ratio (SNR) greater than 2.5 (Kelly et al. 2007). These channels

still included both noise (labeled as 0) and spike waveforms (labeled as 1). The aim of using only the high

SNR channels in the training set was to emphasize relatively well-isolated single-unit action potential

shapes while also exposing the network to a variety of noise waveforms. Additionally, excluding low

SNR channels resulted in a training set with a relatively even distribution of spike and noise waveforms

(47.5% spikes, 52.5% noise).

Overall, the network training set consisted of 24,810,795 waveforms from four monkeys, two

brain regions (V4 and FEF), two recording devices (Utah array and U-probe), and different array implant

ages. These waveforms were classified as spikes or noise using the offline spike-sorting technique

described above (Fig. 1a).

Table 1. Training data set information, including time since implant (array age), brain area (RH-right hemisphere, LH-left hemisphere), and number of recording sessions. Utah arrays contained 96 channels and U-Probes had 16 channels.

	Recording device	Brain area	Time since implant	# of sessions
Monkey Wi	Utah array	RH V4	~1 month	1
	Utah array	RH V4	~11 months	1
	U-Probe	RH FEF	-	1
Monkey Ro	Utah array	LH V4	<1 month	1
	Utah array	LH V4	~8 months	1
	U-Probe	LH FEF	-	1
Monkey Bo	Utah array	RH V4	<1 month	1
	Utah array	RH V4	~4 months	1
Monkey Bu	Utah array	RH V4	~1 month	1

Testing data set

We used recordings from two additional subjects, not included in the training set, for testing to

ensure that the trained network was generalizable to subjects not included in its training. The two testing

data set subjects (Monkey Pe and Monkey Wa) each had two 96-electrode 'Utah' arrays implanted, one in

visual area V4 and one in dorsolateral PFC (on the prearcuate gyrus just medial to the principal sulcus,

area 8Ar). Both arrays were implanted in the right hemisphere for Monkey Pe and in the left hemisphere

for Monkey Wa. Only data recorded from PFC were used for the complete set of analyses (Table 2)

because this provided a matched data set from two monkeys for the purpose of assessing the impact of our

method on decoding and because it allowed us to test our network's generalizability in situations where

the data were recorded from a different region than the training set. However, we repeated some of the

analyses in held out data from V4 and similarly found an improvement in decoding with our network

(Supplementary Figure 5). Recordings within 50 days of the array implant were considered early sessions

and recordings from over 50 days after the implant were considered late sessions (see Table 2 for session

counts by subject). For Monkey Pe, the thresholds across channels were similar for all recording sessions

(90% of channels had thresholds between -39 and -20 μV, median: -29 μV). For Monkey Wa, the

thresholds were more permissive for the later recording sessions (> 6 months after the array implant) as

the experimenters sought to extract the maximum remaining signal in arrays that were decreasing in

recording quality. The median threshold of Monkey Wa's early sessions was -32 μV (90% between -43

and -23 μV), and the median threshold of the later sessions was -15 μV (90% between -29 and -12 μV).

The waveforms in the testing data set were also spike-sorted offline via the technique described above for

a comparative analysis between our network classifications and offline spike-sorting.

Table 2. Testing data set information, including time since implant (array age), brain area (RH-right hemisphere, LH-left hemisphere), and number of recording sessions.

	Recording device	Brain area	Time since implant	# of sessions
Monkey Pe	Utah array	RH PFC	11-43 days	14
		RH PFC	80-147 days	22
Monkey Wa	Utah array	LH PFC	27-40 days	5
		LH PFC	180-224 days	11

Neural Network

Using TensorFlow (Abadi et al. 2016) and Keras (Chollet 2015), we developed a neural network

to classify data segments as spike or noise waveforms (Fig. 1b). The network accepts a waveform

segment with 's' samples (s=52), which passes through a hidden layer with 'n' units (n=50) that uses a

rectified linear unit (ReLU) activation function. The product of the hidden layer passes through one

output unit and then the network applies a sigmoid function to its output.

With the aforementioned training waveforms, the network was trained to maximize accuracy

based on binary labels (0 for noise, 1 for spikes) using an Adam optimization algorithm (Diederik P.

Kingma 2015) and a binary cross-entropy loss function in batch sizes of 100.

For a single waveform input run through the trained network, the output was a value between 0

(likely not a spike) and 1 (likely a spike), which represented the network's assessment of the likelihood

that the input waveform was a spike. While this output value was not a conventional probability, we refer

to it as the probability of being a spike or P(spike) because it was a likelihood metric scaled between 0

and 1. Supplementary Figure 1 provides more intuition regarding the hidden layer units and how the

network assessed waveforms. In order to classify the waveforms using the network's output probability,

we set a minimum P(spike) for a waveform to be classified as a spike. We referred to this minimum

probability as the γ threshold. A γ threshold of 0 classified all of the waveforms that were captured for the

session as spikes; this is often referred to as 'threshold crossings' in the literature. Increasing γ resulted in

fewer waveforms classified as spikes because the P(spike) cutoff was higher.

197
Figure 1. Methods of classifying waveforms: classic (manual) spike-sorting and our neural network spike
classifier, Not A Sorter (NAS). (a) Spike-sorted channels with waveforms that were manually classified as
spikes (green) and noise (grey). The network was trained on 24,810,795 spike-sorted neural waveforms from
four monkeys. The waveforms were recorded on arrays implanted in V4 as well as U-probes placed in FEF.
(b) Neural network structure and output for three sample waveforms. Each s=52 waveform input (I) was
passed through a hidden layer (II) with n=50 units. The resultant linear weighting of the waveform voltages
was passed through a rectified linear unit (ReLU) non-linearity (III). The output was again passed through a
weighted sum (IV) followed by a sigmoid non-linearity (V). The resulting value was the network's assessment
of the likelihood that the input waveform was a spike waveform (VI). We referred to this value as P(s) or the
"probability" of being a spike.

Custom Python and MATLAB scripts used to train the neural network and classify waveforms, as

well as sample training and testing data, will be available on GitHub at the time of publication. We refer

to our neural network as Not A Sorter (NAS), because it classifies waveforms as spikes or noise but does

not attempt to sort the spikes into separable single-units.

Memory-guided saccade task

The two testing data set subjects (Monkey Pe and Monkey Wa) performed a memory guided

saccade task (Fig. 2a). Each subject fixated on a central point for 200 ms. Then, a target stimulus flashed

at a set amplitude and direction for 50 ms, followed by a 500 ms delay. There were a total of 40 possible

conditions: the radius could be one of five eccentricities and the target direction could be one of eight

(spaced in 45° steps). After the delay, the fixation point disappeared instructing the subject to make a

saccade to the location where the target flashed. For some sessions, during the saccade the target

reappeared to help the subject; however, for all analyses we only used data from the beginning of the

delay period (i.e. prior to the saccade). Subjects were rewarded with water or juice for making a saccade

to the correctly remembered target location. For all decoding analyses, the decoded condition was the

target location. Trials at a single eccentricity (Monkey Pe: 9.9°, Monkey Wa: ~7.6°) were used to

maximize the number of recording sessions that could be compared. Thus, there were eight unique target

locations to decode.

Only rewarded trials were analyzed. The number of trial repeats per condition varied over

sessions. Monkey Pe had an average of 43 repeats per session (range: 25-75, sd: 17) and Monkey Wa had

an average of 62 repeats per session (range: 51-83, sd: 11) for each target condition.

Decoding

To classify target direction prior to movement from spikes in PFC , we used a Poisson Naïve

Bayesian decoder (Fig. 2b). All decoding analyses were performed offline. Waveforms classified as

spikes from 300 ms to 500 ms after fixation (i.e. 50 ms after stimulus offset) were used for decoding,

while waveforms classified as noise were discarded. Each channel was considered a single decodable unit

with one exception: to calculate decoding accuracy using manual spike-sorting, if there were multiple

single-units identified by the manual spike-sorting method on a channel, each single-unit on that channel

remained separate for the purposes of decoding. Units with an average firing rate across trials below 0.25

spikes per second were discarded. We allocated training and test trials using two different methods. For

one analysis, we assigned 80% of the trials from each session to the training set and the remaining 20% to

the test set (Fig. 4a,b). For the remaining analyses, we wanted two test sets, so we used 60% of the trials

for training and 20% for each of the two test sets. The two test sets allowed us to search for an optimal γ

threshold using the first test set and cross validate this value with the second test set. Training and test

data were rotated such that each trial was used for a test set only once.

242
Figure 2. Offline decoding of planned direction from a memory guided saccade task. (a) Memory guided
saccade task. The monkey fixated on a central point. A brief stimulus flash occurred followed by a delay
period. When the fixation point turned off, the subject was required to make a saccade to the location of the
previously flashed stimulus. (b) Decoding paradigm. The stimulus flash could occur at 8 different angles
around the fixation point. A Poisson Naïve Bayes classifier was used to decode stimulus direction offline using
spikes recorded from a 96-electrode Utah array in PFC 50 ms after target offset. For each recording session,
we used 5-fold cross validation, where for each fold the data were split (step 1) into a training set to create
model distributions for each direction (step 2) and an independent testing set to test the accuracy of the
model's predictions (step 3). Note that the curves in step (2) do not depict actual distributions and simply
represent how a Poisson decoder could use spike counts from trials in the training set to distinguish between
different target conditions.

Our decoding algorithm created a Poisson distribution model for each target location (θ) using

the average spike count for each unit (n_{spike}) in the training set. For each test trial, the target location

with the maximum prediction probability, $P(\theta|n_{spike})$, was the predicted label. In equation (1),

$P(n_{spike}|\theta)$ was calculated using the Poisson model developed with the training trials:

258
$$P(\theta|n_{spike}) = \frac{P(n_{spike}|\theta) * P(\theta)}{P(n_{spike})}$$

259   Decoding accuracy was calculated as the ratio of the number of correct prediction labels to the

260   total number of predictions. We used 5-fold cross validation and computed the average decoding accuracy

261   across folds.

263   **Results**

We trained a one-layer neural network called Not a Sorter (NAS) to evaluate the likelihood that a

neural waveform was a spike. We used a diverse set of waveforms in the training set from different brain

regions, subjects, and array implant ages (time since array implant) in order to expose the network to a

variety of waveform types. Each waveform in the training set was assigned a binary label of noise (0) or

spike (1) via offline spike-sorting with manual refinement by researchers. The network was also exposed

to variability in spike classification due to manual sorting because different researchers sorted different

sets of waveforms in the training data. The network learned to assess how spike-like a waveform was

based on binary labels, but itself output a continuous value between 0 and 1 for each waveform allowing

for tunable classification. We referred to this output as the probability of being a spike or P(spike). The

network classified 1000 waveforms in less than one millisecond on average (computed on a 2011 iMac

with a 2.8 GHz Intel Core i7 processor). In a 10 ms bin, 1000 waveforms would be the expected output of

1000 channels each recording from a single-unit with a firing rate of 100 spikes/s. Thus, our network

could be easily integrated to operate within real time computing constraints. In a realistic simulation of a

real time application of our network, waveforms captured from 192 channels in a 20 ms time step could

be classified in less than 0.1 ms on average, easily sufficient for the updating of a BCI cursor or other

feedback.

Qualitative assessment of NAS classifications

To assign each NAS-classified waveform a binary spike or noise label, we set a parameter called

the γ threshold, which was the minimum P(spike) a waveform needed to be considered a spike waveform.

We found that even a low γ threshold, such as $\gamma=0.20$ (Fig 3a), assigned most waveforms to classes that a

human spike-sorter would deem appropriate. Most spike-sorters and spike-sorting algorithms search for

waveforms with a canonical action potential shape – an initial voltage decrease followed by a sharp

increase, a narrow peak, and a return to baseline. Increasing the γ threshold to 0.70 (i.e. only waveforms

assigned a P(spike) > 0.70 were considered spikes) mimicked the effect of more selective spike-

classification (Fig 3b), where the percentage of spike waveforms on the channel decreased since more

waveforms were placed in the noise class and the remaining spike waveforms had a clearer single-unit

shape. Considering all of the waveforms from this same channel, the range of P(spike) values coincided

well with our subjective impression of the match of individual waves with a canonical action potential

shape (Fig 3c), and this was also true across all channels from this array (Fig 3d). Thus, tuning the γ

threshold from low values (near 0) to high values (near 1) resulted in a shift from a more permissive to a

more restrictive regime.

295
Figure 3. Classifying waveforms based on their probability of being a spike, P(spike), by setting γ, a tunable
parameter. (a-b) Waveforms classified as spikes (green) or noise (grey) for a sample channel in Monkey Pe.
The network outputs a value between 0 and 1, referred to as P(spike), for each waveform, where a value close
to 1 means the network identifies that waveform as very likely to be a spike waveform. After running
waveforms through the network, we set the minimum P(spike) to classify waveforms as spikes and referred to
this value as the γ threshold. In (a) only waveforms assigned a spike probability greater than 0.20 (i.e. γ
threshold = 0.20) and in (b) greater than 0.70 (i.e. γ threshold = 0.70) were classified as spikes. Increasing the
γ threshold by definition results in a smaller percentage of waveforms captured in the spike class. (c)
Waveforms from the same channel in (a) and (b) colored based on their network assigned P(spike) value. For
a waveform where $\gamma_1 < P(spike) < \gamma_2$, the waveform would be classified as a spike when the threshold is γ_1, but
would be labeled as noise for γ_2. (d) Similar to (c) except the average of waveforms across all channels within
the indicated P(spike) ranges. Modifying the γ threshold tuned the stringency of the spike classifications. For
the channel depicted in (a)-(c) the standard deviation of the waveform noise, computed using the method
described in Kelly _et al._ (2007), was 17.1 µV.

Quantitative assessment of NAS classifications with decoding

Although by eye the network appeared to classify waveforms reasonably well, we sought to

objectively assess its performance by measuring its effect on offline decoding accuracy. Specifically, we

hypothesized that decoding using spikes classified by our network would be better than using threshold

crossings. We applied our network to a set of data recorded from PFC on which the network had not been

trained. First, we set the γ threshold and discarded any waveforms with a P(spike) below the threshold.

Next, we split the data into training and testing sets. We trained the decoder using the training set to

decode the task condition (the remembered location, out of 8 possibilities) during the delay period of a

memory-guided saccade task on each trial (see Methods). Then, we used the trained decoder to assess

decoding accuracy in the test set(s). We repeated this process for the same data set using multiple γ

thresholds between 0 (i.e., all threshold crossings were considered spikes) and 0.95 (i.e., only waveforms

assigned a 0.95 or greater probability by the network were considered spikes). Since only waveforms

classified as spikes were used for decoding, as the γ threshold increased, fewer waveforms remained for

decoding.

Initially, we used 80% of trials to train the decoder and the remaining to test it. We analyzed

cross-validated decoding accuracy as a function of γ (sample recording sessions in Fig. 4a,b). Chance

decoding was 12.5% (1 out of 8) and was verified by computing decoding accuracy for shuffled test trials.

The decoding accuracy using threshold crossings ($\gamma = 0$) for the sample recording sessions in Fig. 4a and

4b was close to chance levels for Monkey Pe (12.8%) and was also low for Monkey Wa (20.1%). Using

the network's classifications improved decoding accuracy relative to using threshold crossings. The peak

decoding benefit of using the network's spike classifications occurred at a low γ threshold (Monkey Pe: γ

$= 0.16$, Monkey Wa: $\gamma = 0.16$). Being very selective about the spikes used for decoding (by setting a high

γ threshold) did not have a large impact on decoding accuracy, which appeared to plateau after the peak.

We found that increments of the γ threshold did not remove the same number of waveforms. A substantial

proportion of waveforms were removed at the lowest γ threshold tested (especially in Monkey Pe), and

small increments of the γ threshold as it approached a value of 1 could also result in large increases in the

proportion of removed waveforms (especially notable in Figure 4b). For reference, when we manually

spike-sorted the same data offline (see Methods), we discarded 89.2% of the waveforms in Figure 4a and

71.5% of the waveforms in Figure 4b. These values were similar to the percentage of waveforms the

network removed at higher γ thresholds.

Ideally, for the sake of simplicity during online BCI experiments, we could select a single γ

threshold and use it for all recording sessions. We wanted to find the lowest γ threshold that improved

decoding accuracy for the majority of recording sessions. We focused on lower γ thresholds because it

was a conservative approach, and because our intuition from single channels and results in example

sessions (Figure 4) showed it could have the greatest benefit for decoding. In order to cross-validate both

our decoder and our γ threshold selection for the remaining analyses we created two test sets for decoding

(training set: 60% of trials, test set 1: 20% of trials, test set 2: 20% of trials). Our general strategy was to

use the first test set to identify a γ threshold that optimized decoding accuracy. We then cross-validated

this selection by applying the chosen γ threshold to the data in the second test set and computing decoding

accuracy for those unseen trials.

As described above, after training the decoder for each session using the training trials, we

calculated decoding accuracy with the first set of test trials at each γ threshold. We found the maximum

decoding accuracy at any γ threshold greater than 0, and then searched for the lowest non-zero γ threshold

that resulted in a decoding accuracy within 99% of that maximum (Fig. 4c, d). Since the optimal γ

threshold varied between sessions, we computed the median across sessions of these γ values and rounded

it to the nearest tested value (Monkey Pe: $\gamma = 0.2$, Monkey Wa: $\gamma = 0.08$). We then used that median

value as the γ threshold for all sessions in the second test set and analyzed the change in decoding

accuracy from decoding using threshold crossings in that same test set, which we termed Δ % decoding

accuracy (Fig. 4e, f). Combining sessions from both animals, the average improvement in decoding

accuracy was 3.9% (2-tailed, Wilcoxon signed rank test; across subjects: $p < 0.0001$, Monkey Pe: $p <$

0.0001, Monkey Wa: $p = 0.057$). Thus, our network's classifications tuned to the previously described γ

thresholds resulted in a net benefit for decoding performance across sessions compared to using threshold

crossings. Although we could tune the γ threshold for each session to maximize the decoding, our choice

of a fixed γ threshold was more consistent with the use of our network in an online decoding context,

where it would be desirable to set a constant γ threshold at the start of each session rather than tuning it as

a free parameter. However, an alternative strategy would be to collect a small data set at the start of each

day to find the optimal γ value, and then continue experiments for the remainder of that day using the

chosen value.

Given the ability of our network to improve decoding accuracy beyond that observed with

threshold crossings, we took advantage of our longitudinal recordings in a fixed paradigm to understand

how our network's performance varied as a function of time. Since there is mixed evidence in the

literature regarding decoding stability with long-term array implants, we were specifically interested in

how the passage of time since array implant (array implant age), and concomitant degradation of

recording quality, could influence our network's performance.

Figure 4. Using NAS spike classifications improved decoding accuracy in many sessions. (a-b) Percent
decoding accuracy (black line) and percent of waveforms removed (maroon line) at different γ thresholds for
an example recording session in Monkey Pe and Wa. Chance decoding accuracy was 12.5% (verified by
computing a decoding control with shuffled test trials, grey line). The decoding accuracy increased for low γ
thresholds and then reached an asymptote as γ increased. At the highest γ thresholds, decoding accuracy fell
to chance (grey line). Other labeled relevant metrics include: decoding accuracy with threshold crossings
(blue dot) maximum decoding accuracy (green dot), γ threshold with the maximum decoding accuracy (grey
dotted line), and Δ % decoding accuracy (the difference for a given session between the decoding accuracy
using the network classifications at a particular γ threshold and the decoding accuracy with threshold
crossings). (c-d) Distribution of γ thresholds across sessions (Monkey Pe: N =36, Monkey Wa: N = 16) that
resulted in the maximum decoding accuracy for each session. (e-f) Distribution of Δ % decoding accuracy

across all sessions where the γ threshold was the median from the distributions in (c-d). Mean Δ % decoding
accuracy shown in red. For both monkeys, using spikes classified by the network improved decoding
accuracy on average across sessions; however, this improvement was only statistically significant for Monkey
Pe (2-tailed, Wilcoxon signed rank test, Monkey Pe: p < 0.0001, Monkey Wa: p = 0.057).

Impact of array age

First, we assessed how the overall quality of our neural data changed as a function of time. As the

time since the array implant increased, the percentage of waveforms that the network assigned a very low

probability of being a spike (P(spike) < 0.02) also increased (Fig 5a; Spearman's correlation, Monkey Pe:

$\rho = 0.87$, $p<0.0001$; Monkey Wa: $\rho = 0.90$, $p<0.0001$). Conversely, the percentage of waveforms assigned

higher probabilities of being a spike (P(spike) > 0.70) decreased over time (Fig 5b; Monkey Pe: $\rho = -0.87$,

$p<0.0001$; Monkey Wa: $\rho = -0.94$, $p<0.0001$). These classification changes were consistent with our

qualitative observations that the arrays showed an increasing proportion of multi-unit activity (relative to

single-unit activity) and apparent noise over time. These changes were also reflected in our manual spike-

sorting (performed offline on the same data for previous studies, see Methods) where we discarded a

smaller percentage of waveforms from earlier sessions that were 0-50 days post-implant (mean %

waveforms removed +/- 1 sd, Monkey Pe: 36.1 +/- 8.2%; Monkey Wa: 46.1 +/- 12.2%) and a larger

percentage in later sessions that were greater than 50 days post-implant (mean % waveforms removed +/-

1 sd, Monkey Pe: 87.0 +/- 7.7%; Monkey Wa: 77.8 +/- 10.3%). We further found that the ratio of the

percentage of waveforms assigned a high P(spike) to the percentage of waveforms assigned a low

P(spike) by the network served as a proxy for a signal to noise ratio metric, and it was highly correlated

with the median signal to noise ratio (across channels) of the array in each session (Supplementary Figure

2). Both signal to noise metrics decreased over time, and the decoding accuracy with threshold crossings

also decreased the longer the array had been implanted (Fig 5c; Monkey Pe: $\rho = -0.86$, $p<0.0001$; Monkey

Wa: $\rho = -0.69$, $p=0.004$).

Given the change in distribution of the types of waveforms present during the session over time,

we tried to optimize the γ threshold based on time since array implant. We used the same method as in

Fig. 4c-d to compute the γ thresholds with approximately maximum decoding (within 1%), except we

calculated the median of the early sessions (recorded 0-50 days post implant) and the median of the late

sessions (recorded >50 days post implant) separately. This did not prove to be a useful optimization as the

median values were similar between early and late sessions in both Monkey Pe (γ_{early} = 0.25, γ_{late} = 0.18)

and Monkey Wa (γ_{early} = 0.06, γ_{late} = 0.08). Decoding accuracy compared to threshold crossings (Δ %

decoding accuracy) was significantly increased in Monkey Pe (Figure 5d, 2-tailed, Wilcoxon signed rank

test, $p < 0.0001$) and was not significantly helped or hurt in Monkey Wa ($p = 0.09$). In line with the trends

in signal and noise over time, the decoding accuracies from later sessions (> 50 days post implant) were

helped more by the network classifications in both subjects than those from earlier sessions (Figure 5d,

Wilcoxon rank sum, Monkey Pe: $p = 0.01$; Monkey Wa: $p = 0.01$). When we normalized the decoding

accuracy at each γ threshold by the decoding accuracy using threshold crossings for each session and

separately averaged across early and late sessions, the increased benefit of using the network in the later

sessions compared to the earlier sessions was clear (Figure 5e).

425   Altogether, these results provide additional evidence that factors such as time since the array was

implanted and signal to noise ratio influence decoding accuracy and affect how noise removal impacts

decoding performance. Despite decreasing signal quality and increasing noise waveforms, the effect of

using our network classifications for noise removal prior to decoding was consistent in that it was most

often beneficial for decoding and at worst minimally detrimental. We confirmed that these results were

not affected by poor γ threshold selection by using the maximum decoding accuracy regardless of γ

threshold to calculate Δ % decoding accuracy (Supplementary Figure 3a). Our results were also not

substantially influenced by variability in the number of trials across sessions (Supplementary Figure 3b).

An even simpler alternative to our network might be to adjust the voltage threshold for capturing

waveforms, to make it more or less permissive. We found that increasing this threshold (making it more

negative and therefore excluding the waveforms that did not exceed it) did not improve decoding

performance (Supplementary Figure 4), indicating that our network was not merely acting to exclude

small amplitude waveforms. Lastly, we confirmed that our network was beneficial for decoding in data

recorded from another brain region (V4) with different Utah arrays in the same sessions from the same

animals in the test data set (Supplementary Figure 5).

440
Figure 5. Noise on the array increased with the age of the array while decoding accuracy decreased in
Monkey Pe (blue) and Monkey Wa (orange). (a) Percentage of waveforms with a P(spike) < 0.02 over time. A
waveform with a P(spike) less than 0.02 was one that the network found very unlikely to be a spike. The
percentage of these unlikely spike waveforms increased as the array became older (Spearman's correlation,
Monkey Pe: ϱ = 0.87, p < 0.0001; Monkey Wa: ϱ = 0.90, p < 0.0001). (b) Percentage of waveforms with a
P(spike) > 0.70 over time. The percentage of waveforms that the network found to be strongly spike-like

decreased as the array became older (Spearman's correlation, Monkey Pe: ϱ = -0.87, p < 0.0001; Monkey Wa:
ϱ = -0.94, p < 0.0001). (c) Decoding accuracy with threshold crossings (i.e. γ = 0) decreased as the array aged
(Spearman's correlation, Monkey Pe: ϱ = -0.86, p < 0.0001; Monkey Wa: ϱ = -0.69, p = 0.004). (d) Change in
percent decoding accuracy using network-classified spikes relative to decoding accuracy with threshold
crossings (Δ % decoding accuracy). We computed a distribution of the maximum γ threshold (similar to Fig.
4c-d) for sessions that were 0-50 days post array implant and used the median to set the γ threshold before
computing decoding accuracy for those sessions. We repeated this for sessions more than 50 days post array
implant. In Monkey Pe, using NAS classifications improved decoding accuracy (2-tailed, Wilcoxon signed
rank test, p < 0.0001) and in Monkey Wa, using the classifications neither hurt nor helped decoding
significantly (p = 0.09). In both subjects, the network helped decoding more in the late array sessions (>50
days post implant) compared to the early sessions (2-tailed, Wilcoxon rank sum, Monkey Pe: p = 0.01;
Monkey Wa: p = 0.01). (e) Mean normalized decoding accuracy across early sessions (open circles) and late
sessions (filled circles) as a function of γ threshold. Shading represents +/- 1 SEM. Using the network
classifications at any γ threshold greater than zero was more helpful for late sessions than it was for early
sessions.

Comparison to spike-sorting

In light of the inconsistent effect of spike-sorting on decoding performance in the literature

(Fraser et al. 2009; Todorova et al. 2014; Christie et al. 2015; Dai et al. 2019), we sought to evaluate the

relative merits of manual spike-sorting and our network classifier on decoding accuracy in our data. Our

goal was to place our new method (using our network to remove noise but not sort the data) in context of

previous work that evaluated the impact of human supervised spike-sorting on decoding. We took

advantage of the offline spike-sorting that had already been applied to these data and calculated the

decoding accuracy of spike-sorted data (Fig. 6, data aggregated across subjects in the marginal

histograms). Decoding using spike-sorted waveforms was better than using threshold crossings (Fig. 6

right marginal; 2-tailed, Wilcoxon signed rank test, p < 0.0001) similar to decoding with our network

classifications (Fig. 6 top marginal, data from Fig. 5d aggregated across subjects; p < 0.0001). Our

network's classifications were at least as helpful as manual spike-sorting for decoding relative to using

threshold crossings (Fig. 6 center; paired, 2-tailed, Wilcoxon signed rank test, Monkey Pe: p = 0.75;

Monkey Wa: p = 0.09). Furthermore, the automated real time operation of our network confers a distinct

advantage over manual spike-sorting.

Together, our analyses demonstrate that our network was able to produce classifications of spikes

and noise that matched our qualitative expectations and could be tuned quantitatively to adjust its

permissiveness. Compared to using threshold crossings, our network's classifications most often led to an

improvement or minimally harmful change in decoding accuracy, indicating that there was usually little

downside to the application of our network. These outcomes are valuable particularly in the context of a

BCI where real time operation and maximal decoding accuracy are prized.

483
Figure 6. Using NAS classifications was comparable to using spike-sorted data for decoding. Δ % decoding
accuracy was calculated for both NAS classifications and spike-sorted waveforms as the change from
decoding accuracy with threshold crossings. Top: Distribution of Δ % decoding accuracy using NAS
classifications aggregated across subjects (γ threshold selected as in 5d). Using NAS classifications improved
decoding accuracy from that with threshold crossings (2-tailed, Wilcoxon signed rank test, p < 0.0001). Right:
Distribution of Δ % decoding accuracy using manual spike-sorting aggregated across subjects. Using spike-
sorted classifications also improved decoding accuracy from that with threshold crossings (2-tailed, Wilcoxon
signed rank test, p < 0.0001). Center: The joint distribution of Δ % decoding accuracy with spike-sorting and
NAS classified spikes. Using our network's classifications was at least as helpful as spike-sorting for decoding
(paired, 2-tailed, Wilcoxon signed rank test, Monkey Pe: p = 0.75; Monkey Wa: p = 0.09).

494   **Discussion**

495   By leveraging our pool of previously spike-sorted data, we trained a neural network classifier to

separate spikes from noise in extracellular electrophysiological recordings in real time. To assess the

value of this method, we used an objective criterion – the ability to decode remembered location from

prefrontal cortex in a memory-guided saccade task. We found that we could set a fixed γ threshold that

resulted in an improvement or at worst a small change in decoding accuracy for the majority of sessions,

and this effect persisted even as recording quality decreased over time. Compared to spike-sorting

(performed offline with substantial manual labor involved), classifying spikes with our network had

similar effects on decoding accuracy relative to threshold crossings and was less tedious.

Training the network

Developing a neural network trained on spike-sorted data allowed us to capture the essence of the

rules by which experienced researchers distinguish spikes from noise without explicitly defining all the

variables and exceptions, a standard challenge in spike classification (Wood et al. 2004). Several studies

have demonstrated the promise of using a neural network trained on spike-sorted or human-verified data

for spike detection and classification (Chandra and Optican 1997; Kim and Kim 2000; Racz et al. 2019;

Lee et al. 2017; Saif-Ur-Rehman et al. 2019). Lee *et al.* (2017), Racz *et al.* (2019), and Saif-Ur-Rehman

et al. (2019) used spike-sorted data to train their respective neural networks and developed more complex

network architectures than the one-layer network we explored in this work. Each of these studies was

validated by the performance of the network in correctly labeling held out spiking waveforms. The

intention of our simple architecture was not to compare its performance to existing spike detection and

sorting algorithms, but rather to explore how a relatively simple, fast, and trainable noise removal method

could improve decoding performance.

We found that a simple neural network was quite good at capturing the nuances of the training

set. Experts often disagree on how to classify certain instances of low SNR waveforms. The network was

sensitive enough to capture a researcher's specific spike classification tendencies, such that a network

trained on data classified by a particular individual performed better on classifying test data from that

individual than from other expert spike classifiers. Given this level of sensitivity, a reasonable concern

would be the presence of misclassifications in our training set, as human spike-sorting is both subjective

and prone to error (Rossant et al. 2016; Pedreira et al. 2012). However, the network was trained on many

waveforms to minimize the impact of any confounders, including waveforms from multiple subjects,

brain regions, and human spike-sorters. Additionally, by training the network on labeled data with some

variability introduced by human sorters, the network learned to make stronger predictions (higher

P(spike) values) for obvious spike waveforms and weaker predictions for more ambiguous waveforms.

We then leveraged this range of prediction values to create a tunable parameter for our classifications (i.e.

the γ threshold).

An ideal and even more generalizable training set might include waveforms from different

research groups, artificially simulated neural waveforms and noise in which ground truth could be

established, and/or pre-defined quantities of certain types of spikes (e.g. shifted spikes, slow and fast

spike waveforms) and noise (e.g. electrical artifacts) to target what the network learns. However, no

matter how much training data is used, an ideal training set could only be defined in the context of

objective metrics to assess the trained network's performance.

Evaluating the network with decoding

We compared decoding performance with our network classifications to performance with

threshold crossings, which are the current standard in the BCI community. We used independent test data

to assess the effect of classifications from our trained network on decoding accuracy. Although the

expectation might be that removing noise from neural data would improve decoding, historically doing so

with spike-sorted classifications has had mixed effects, in some cases hurting performance (Todorova et

al. 2014). Nevertheless, many BCIs currently operate with some amount of online noise removal or visual

inspection (such as disabling visibly noisy channels) to preprocess neural data before decoding (Homer et

al. 2013; Hochberg et al. 2006; Sadtler et al. 2014; Chase, Kass, and Schwartz 2012). The question of

whether to spike-sort BCI data prior to decoding or simply use all threshold crossings has been a source

of debate with no clear resolution. Our work reframes this question to investigate how an automated noise

removal method could be used to aid decoding.

Our findings provide additional support, across multiple sessions over time, that removing certain

noise waveforms prior to decoding provides an advantage over using all threshold crossings, consistent

with findings from Fraser *et al.* (2009) and Christie *et al.* (2015). Although there were a few occasions

when decoding accuracy with threshold crossings was better than decoding using the network, it was

never by more than a few percent. Although these few instances might occur merely due to noise in our

estimation of decoding accuracy, another possible explanation is that a lack of non-neural noise on the

array on certain days would limit the benefits of our network and thereby increase the relative likelihood

that waveforms valuable for decoding were removed.

555   Contrary to the benefits of spike-classification that we observed, a study by Todorova *et al.*

(2014) found that using spike-sorted waveforms hurt decoding when noise waveforms were discarded. It

is difficult to speculate why removing noise waveforms hurt decoding in their study but helped it in ours

given that our methods of noise removal were different. They also found assigning noise waveforms from

spike-sorting to a new unit, rather than discarding them, improved decoding relative to threshold

crossings. Yet, when we assigned our noise waveforms to separate units, decoding accuracy was worse or

unchanged compared to discarding noise waveforms both with our spike-sorted classifications and our

network classifications (Supplementary Figure 6). Importantly, we defined 'noise' operationally as any

waveform that did not exceed the γ threshold of our network setting. This definition of noise surely

included both electrical artifacts as well as indistinct shapes that were actually neural in origin. Removal

of waveforms from the former class could only help decoding, but removal of the latter class might

actually harm decoding if the multi-unit activity contained in those waveforms had information about the

condition of interest for decoding.

568   Apparent noise in neuronal activity, in addition to changing the activity of single electrode

channels, can also be correlated across channels. In the activity of pairs of single neurons, such

fluctuations in trial-to-trial correlated variability are sometimes termed "noise correlation" (also known as

spike count correlation, or r_{sc}). Noise correlation can have a substantial impact on the ability of a decoder

to extract information from neuronal populations (Kohn et al. 2016; Averbeck, Latham, and Pouget

2006), and the activity of multi-unit groups of neurons has a higher noise correlation than that of the

constituent pairs of neurons (Cohen and Kohn 2011). Since our network acted on threshold crossings,

which typically contain the activity of many individual neurons, it likely also impacted the magnitude of

the noise correlation between channels. Our decoder assumed that the noise on each unit was

independent, a choice common to BCI, which permitted training the decoder with a smaller quantity of

trials than is necessary to learn the covariance structure in the population. The effect of our network on

decoding surely depends on not only the structure of the network and the choice of γ threshold, but also

the structure of noise present in the population and the sensitivity of the decoder to that noise.

In addition to understanding how the type of noise present in the data impacts decoding, it may

also be useful to evaluate the types of neural waveforms that contribute to decoding. Different levels of

single and multi-unit activity are captured during a neural recording depending on the threshold set by the

researcher (i.e. the minimum voltage level at which the neural activity is marked as a spike). By adjusting

this threshold, we change the candidate waveforms available for decoding. Oby *et al.* (2016) found that

the optimal threshold depended on the type of information being extracted from neural activity. Another

study found that higher thresholds, which captured less multi-unit activity, resulted in worse decoding of

direction from M1 (Christie et al. 2015). These studies in the context of our own findings highlight the

need to identify specific types of waveforms that contribute to the decodable information in different

brain regions and task contexts.

Other variables that impact decoding accuracy

A key concern for practical implementation of BCIs is decoding stability. Array recordings often

get visibly noisier over time, potentially as a result of an immune response to the implant (Ward et al.

2009) or a physical shift in position (Perge et al. 2013). In our study, as the time since array implant

increased there were more "low probability" waveforms and fewer "high probability" waveforms,

indicating the arrays had fewer well-defined single-unit waveforms. In line with this, several other studies

with chronic array implants have found that the number of single-units decreased over time (Dickey et al.

2009; Downey et al. 2018; Fraser and Schwartz 2012; Tolias et al. 2007). Nevertheless, there are mixed

findings on the stability of decoding performance in chronic array implants. Some studies have found

decoder performance with threshold crossings remained stable over time (Gilja et al. 2012; Chestek et al.

2011; Nuyujukian et al. 2014; Flint et al. 2016); however, other studies, including our own, observed a

decrease in decoding accuracy over time (Perge et al. 2014; Wang et al. 2014). Unlike the previous

literature investigating the effects of threshold crossings and spike-sorting on decoding performance, we

used neural activity from PFC, where decoding accuracy is typically lower (Meyers et al. 2008; Rizzuto et

al. 2005; Tremblay et al. 2015; Jia et al. 2017; Boulay et al. 2016; Parthasarathy et al. 2017; Spaak et al.

2017) than in motor cortex (Sadtler et al. 2015; Masse et al. 2014; Collinger et al. 2013; Koralek et al.

2012). Stability of decoding accuracy with array age may also depend on the brain region of the implant,

the subject's task, initial decoding performance, and the choice to train the decoder daily (Chestek et al.

2011; Gilja et al. 2012) or hold it constant (Nuyujukian et al. 2014). The beneficial effects of our network

on decoding were particularly salient in the case of older array implants, where decoding accuracy had

decreased over time.

Limitations of NAS

Our network, NAS, is certainly not sufficient to achieve the goal of obtaining well-isolated

single-units. NAS evaluates each waveform independently and therefore, cannot distinguish between

multiple units recorded on the same channel. A concern for online decoding is that pooling spikes on a

given channel could hurt decoding if there are multiple single-units that respond to the task conditions

differently. This did not appear to be a major issue in our data because we did not find a substantial

difference between decoding performance with pooled spikes from the network classifications and

decoding with well-isolated single-units from spike-sorting (Fig. 7).

NAS was trained using previously sorted data available in our laboratory, rather than simulated

spike waveforms and noise (Chaure, Rey, and Quian Quiroga 2018) or a ground truth data set

(Anastassiou et al. 2015; Neto et al. 2016). This choice had the potential to limit the abilities of NAS to

distinguish spikes from noise, as our training data was subject to errors and biases of individual human

sorters. However, given the rarity of such ground truth data sets, and the particular features of spikes that

are unique to brain areas and the recording hardware in a laboratory, we also view this choice as a

strength. Nearly any laboratory performing extracellular electrophysiology would have such training data

available, already suitable for their particular brain areas and recording methods. Thus our method is

highly customizable for any laboratory, and we view its focus on human-sorted training data as a strength

for the particular application to which it was designed.

Additionally, NAS does not take advantage of temporal or spatial information. When manually

spike-sorting, sorters often use the inter-spike interval and the stationarity of a candidate unit over the

recording to decide whether those waveforms could sensibly belong to a single-unit. For dense arrays and

tetrodes, leveraging spatial information is vital for isolating spikes that appear on multiple channels

(Chung et al. 2017; Pachitariu et al. 2016). However, such dense recordings are still rare relative to the

use of sparse electrodes in electrophysiological experiments. Thus, for traditional offline data processing,

NAS could be used as a quick preprocessing step to remove noise and make preliminary spike

classifications but must be accompanied by another algorithm or manual spike-sorting to isolate single-

units.

Extensions for NAS

Our neural network-based spike classifier is a promising tool for both offline preprocessing of

neural data and improving online decoding performance. However, in designing our network we only

scratched the surface of many potential avenues to address these challenges. We found that using

networks with different numbers of hidden units and layers did not substantially alter decoding accuracy

even though there were some differences in how these different sized networks classified waveforms.

Given that our network was relatively simple, it would be possible to implement similar operations with

alternative algorithms such as logistic regression. We chose a neural network because it was easily

trainable from existing data and there are many ways to modularly build upon its complexity. Although

we opted to use 50 hidden units and one hidden layer, it is possible that a more complex network with

additional filtering operations and more categories of waveform classification may result in improved

decoding performance and could help to create a more robust spike classifier with the ability to

distinguish multi-units and single-units for offline analyses. However, our work had the value of

exploring how a smaller network trained on spike-sorted data could identify features that were most

valuable for decoding.

654   While training on spike-sorted data from channels with well-isolated single-unit action potentials

(SNR>2.5) was an efficient choice because of its easy availability, it may not be the best choice in

regimes where canonical spike-shapes do not necessarily carry the most decodable information compared

to less well-defined multi-unit activity (Stark and Abeles 2007; Chestek et al. 2011). If the goal is to

improve decoding performance, it might be valuable to train a network on waveforms from low SNR

channels that contain more multi-unit waveforms or to select waveforms or units that positively contribute

to decoding. Ventura and Todorova (2015) developed a method for identifying the information

contribution of units for decoding. Such a method could be used to develop a training set of neural

waveforms that are assigned a label based on how much they positively or negatively contributed to

decoding. Alternatively, if the goal is to discard specific types of artifacts, then it might be ideal to train

the network on predominantly low SNR channels that contain those artifacts.

665   Beyond Bayesian decoding, it would be valuable to assess how NAS classifications impact other

neural data analyses. A recent study found that spike-sorting did not provide much benefit over threshold

crossings for estimating neural state space trajectories (Trautmann et al. 2019), a powerful demonstration

that the principles of neural circuits may be accessible in neuronal population recordings even when

single units are not identified. However, this analysis was performed on trial-averaged data. Using NAS

classifications might be more helpful in single-trial data where estimating trajectories through neural state

space could be negatively influenced by the momentary entry of noise into recordings. Another

interesting application would be to assess how NAS classification impacts the measurement of neural

noise correlations, which have been shown to be affected by the stringency of spike-sorting (Cohen and

Kohn 2011). Using NAS classifications with a low γ threshold could prove to be a useful noise removal

tool for applications that are sensitive to classification stringency.

676   Overall, we developed a new tool for preprocessing BCI data that classified threshold crossings in

677   a tunable manner that was beneficial for decoding. A neural network-based spike classifier has the

678 potential to reduce the need for human intervention in removing noise from neural data. Our tunable

679 classifier is a step toward preprocessing methods that both optimize and stabilize online decoding

680 performance.

Acknowledgements

684 We would like to thank Samantha Schmitt for assistance with data collection and Ben Cowley, Byron Yu,

685 and Steve Chase for their valuable insight on this project.

Grants

D.I. was supported by National Science Foundation (NSF) DBI 1659611, National Institutes of Health

(NIH) T32 GM008208, and the ARCS foundation Thomas-Pittsburgh Chapter Award. M.A.S. was

supported by NIH R01EY022928, R01MH118929, R01EB026953, and P30EY008098; NSF NCS

1734901; a career development grant and an unrestricted award from Research to Prevent Blindness; the

Eye and Ear Foundation of Pittsburgh. R.C.W. was supported by a Richard King Mellon

Foundation Presidential Fellowship in the Life Sciences. S.B.K. was supported by T32 EY017271.

Disclosures

696 The authors declare no conflicts of interest.

697
References

Abadi, Martín, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S.
Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow,
Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz
Kaiser, Manjunath Kudlur, Josh Levenberg, Dan Mane, Rajat Monga, Sherry Moore,
Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya
Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda
Viegas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and

706   Xiaoqiang Zheng. 2016. 'TensorFlow: Large-Scale Machine Learning on Heterogeneous
707    Distributed Systems'.
708 Anastassiou, C. A., R. Perin, G. Buzsaki, H. Markram, and C. Koch. 2015. 'Cell type- and activity-
709    dependent extracellular correlates of intracellular spiking', *J Neurophysiol*, 114: 608-23.
710 Averbeck, B. B., P. E. Latham, and A. Pouget. 2006. 'Neural correlations, population coding and
711    computation', *Nat Rev Neurosci*, 7: 358-66.
712 Bishop, W., C. C. Chestek, V. Gilja, P. Nuyujukian, J. D. Foster, S. I. Ryu, K. V. Shenoy, and B. M.
713    Yu. 2014. 'Self-recalibrating classifiers for intracortical brain-computer interfaces', *J
714    Neural Eng*, 11: 026001.
715 Boulay, C. B., F. Pieper, M. Leavitt, J. Martinez-Trujillo, and A. J. Sachs. 2016. 'Single-trial
716    decoding of intended eye movement goals from lateral prefrontal cortex neural
717    ensembles', *J Neurophysiol*, 115: 486-99.
718 Chandra, R., and L. M. Optican. 1997. 'Detection, classification, and superposition resolution of
719    action potentials in multiunit single-channel recordings by an on-line real-time neural
720    network', *IEEE Trans Biomed Eng*, 44: 403-12.
721 Chase, S. M., R. E. Kass, and A. B. Schwartz. 2012. 'Behavioral and neural correlates of
722    visuomotor adaptation observed through a brain-computer interface in primary motor
723    cortex', *J Neurophysiol*, 108: 624-44.
724 Chaure, F. J., H. G. Rey, and R. Quian Quiroga. 2018. 'A novel and fully automatic spike-sorting
725    implementation with variable number of features', *J Neurophysiol*, 120: 1859-71.
726 Chestek, C. A., V. Gilja, P. Nuyujukian, J. D. Foster, J. M. Fan, M. T. Kaufman, M. M. Churchland,
727    Z. Rivera-Alvidrez, J. P. Cunningham, S. I. Ryu, and K. V. Shenoy. 2011. 'Long-term
728    stability of neural prosthetic control signals from silicon cortical arrays in rhesus
729    macaque motor cortex', *J Neural Eng*, 8: 045005.
730 Chollet, François. 2015. "Keras." In.
731 Christie, B. P., D. M. Tat, Z. T. Irwin, V. Gilja, P. Nuyujukian, J. D. Foster, S. I. Ryu, K. V. Shenoy, D.
732    E. Thompson, and C. A. Chestek. 2015. 'Comparison of spike sorting and thresholding of
733    voltage waveforms for intracortical brain-machine interface performance', *J Neural Eng*,
734    12: 016009.
735 Chung, J. E., J. F. Magland, A. H. Barnett, V. M. Tolosa, A. C. Tooker, K. Y. Lee, K. G. Shah, S. H.
736    Felix, L. M. Frank, and L. F. Greengard. 2017. 'A Fully Automated Approach to Spike
737    Sorting', *Neuron*, 95: 1381-94 e6.
738 Cohen, M. R., and A. Kohn. 2011. 'Measuring and interpreting neuronal correlations', *Nat
739    Neurosci*, 14: 811-9.
740 Collinger, J. L., B. Wodlinger, J. E. Downey, W. Wang, E. C. Tyler-Kabara, D. J. Weber, A. J.
741    McMorland, M. Velliste, M. L. Boninger, and A. B. Schwartz. 2013. 'High-performance
742    neuroprosthetic control by an individual with tetraplegia', *Lancet*, 381: 557-64.
743 Dai, J., P. Zhang, H. Sun, X. Qiao, Y. Zhao, J. Ma, S. Li, J. Zhou, and C. Wang. 2019. 'Reliability of
744    motor and sensory neural decoding by threshold crossings for intracortical brain-
745    machine interface', *J Neural Eng*, 16: 036011.
746 Dickey, A. S., A. Suminski, Y. Amit, and N. G. Hatsopoulos. 2009. 'Single-unit stability using
747    chronically implanted multielectrode arrays', *J Neurophysiol*, 102: 1331-9.
748 Diederik P. Kingma, Jimmy Ba. 2015. "Adam: a Method for Stochastic Optimization." In
749    *International Conference on Learning Representations*.

Downey, J. E., N. Schwed, S. M. Chase, A. B. Schwartz, and J. L. Collinger. 2018. 'Intracortical
recording stability in human brain-computer interface users', *J Neural Eng*, 15: 046016.
Flint, R. D., M. R. Scheid, Z. A. Wright, S. A. Solla, and M. W. Slutzky. 2016. 'Long-Term Stability
of Motor Cortical Activity: Implications for Brain Machine Interfaces and Optimal
Feedback Control', *J Neurosci*, 36: 3623-32.
Fraser, G. W., S. M. Chase, A. Whitford, and A. B. Schwartz. 2009. 'Control of a brain-computer
interface without spike sorting', *J Neural Eng*, 6: 055004.
Fraser, G. W., and A. B. Schwartz. 2012. 'Recording from the same neurons chronically in motor
cortex', *J Neurophysiol*, 107: 1970-8.
Gilja, V., P. Nuyujukian, C. A. Chestek, J. P. Cunningham, B. M. Yu, J. M. Fan, M. M. Churchland,
M. T. Kaufman, J. C. Kao, S. I. Ryu, and K. V. Shenoy. 2012. 'A high-performance neural
prosthesis enabled by control algorithm design', *Nat Neurosci*, 15: 1752-7.
Golub, M. D., B. M. Yu, and S. M. Chase. 2015. 'Internal models for interpreting neural
population activity during sensorimotor control', *Elife*, 4.
Hochberg, L. R., D. Bacher, B. Jarosiewicz, N. Y. Masse, J. D. Simeral, J. Vogel, S. Haddadin, J. Liu,
S. S. Cash, P. van der Smagt, and J. P. Donoghue. 2012. 'Reach and grasp by people with
tetraplegia using a neurally controlled robotic arm', *Nature*, 485: 372-5.
Hochberg, L. R., M. D. Serruya, G. M. Friehs, J. A. Mukand, M. Saleh, A. H. Caplan, A. Branner, D.
Chen, R. D. Penn, and J. P. Donoghue. 2006. 'Neuronal ensemble control of prosthetic
devices by a human with tetraplegia', *Nature*, 442: 164-71.
Homer, M. L., A. V. Nurmikko, J. P. Donoghue, and L. R. Hochberg. 2013. 'Sensors and decoding
for intracortical brain computer interfaces', *Annu Rev Biomed Eng*, 15: 383-405.
Jia, N., S. L. Brincat, A. F. Salazar-Gomez, M. Panko, F. H. Guenther, and E. K. Miller. 2017.
'Decoding of intended saccade direction in an oculomotor brain-computer interface', *J
Neural Eng*, 14: 046007.
Kelly, R. C., M. A. Smith, J. M. Samonds, A. Kohn, A. B. Bonds, J. A. Movshon, and T. S. Lee. 2007.
'Comparison of recordings from microelectrode arrays and single electrodes in the visual
cortex', *J Neurosci*, 27: 261-4.
Khanna, S. B., A. C. Snyder, and M. A. Smith. 2019. 'Distinct Sources of Variability Affect Eye
Movement Preparation', *J Neurosci*, 39: 4511-26.
Kim, K. H., and S. J. Kim. 2000. 'Neural spike sorting under nearly 0-dB signal-to-noise ratio using
nonlinear energy operator and artificial neural-network classifier', *IEEE Trans Biomed
Eng*, 47: 1406-11.
Kloosterman, F., S. P. Layton, Z. Chen, and M. A. Wilson. 2014. 'Bayesian decoding using
unsorted spikes in the rat hippocampus', *J Neurophysiol*, 111: 217-27.
Kohn, A., R. Coen-Cagli, I. Kanitscheider, and A. Pouget. 2016. 'Correlations and Neuronal
Population Information', *Annu Rev Neurosci*, 39: 237-56.
Koralek, A. C., X. Jin, J. D. Long, 2nd, R. M. Costa, and J. M. Carmena. 2012. 'Corticostriatal
plasticity is necessary for learning intentional neuroprosthetic skills', *Nature*, 483: 331-5.
Lee, JinHyung, David Carlson, Hooshmand Shokri, Weichi Yao, Georges Goetz, Espen Hagen,
Eleanor Batty, E. J. Chichilnisky, Gaute Einevoll, and Liam Paninski. 2017. 'YASS: Yet
Another Spike Sorter', *Advances in Neural Information Processing Systems 30 (NIPS
2017)*.

Lewicki, M. S. 1998. 'A review of methods for spike sorting: the detection and classification of
neural action potentials', *Network*, 9: R53-78.
Masse, N. Y., B. Jarosiewicz, J. D. Simeral, D. Bacher, S. D. Stavisky, S. S. Cash, E. M. Oakley, E.
Berhanu, E. Eskandar, G. Friehs, L. R. Hochberg, and J. P. Donoghue. 2014. 'Non-causal
spike filtering improves decoding of movement intention for intracortical BCIs', *J
Neurosci Methods*, 236: 58-67.
Meyers, E. M., D. J. Freedman, G. Kreiman, E. K. Miller, and T. Poggio. 2008. 'Dynamic
population coding of category information in inferior temporal and prefrontal cortex', *J
Neurophysiol*, 100: 1407-19.
Neto, J. P., G. Lopes, J. Frazao, J. Nogueira, P. Lacerda, P. Baiao, A. Aarts, A. Andrei, S. Musa, E.
Fortunato, P. Barquinha, and A. R. Kampff. 2016. 'Validating silicon polytrodes with
paired juxtacellular recordings: method and dataset', *J Neurophysiol*, 116: 892-903.
Nuyujukian, P., J. C. Kao, J. M. Fan, S. D. Stavisky, S. I. Ryu, and K. V. Shenoy. 2014. 'Performance
sustaining intracortical neural prostheses', *J Neural Eng*, 11: 066003.
Oby, E. R., S. Perel, P. T. Sadtler, D. A. Ruff, J. L. Mischel, D. F. Montez, M. R. Cohen, A. P. Batista,
and S. M. Chase. 2016. 'Extracellular voltage threshold settings can be tuned for optimal
encoding of movement and stimulus parameters', *J Neural Eng*, 13: 036009.
Pachitariu, Marius , Nicholas Steinmetz, Shabnam Kadir, Matteo Carandini, and Kenneth Harris.
2016. 'Fast and accurate spike sorting of high-channel count probes with KiloSort',
Advances in Neural Information Processing Systems 29 (NIPS 2016).
Parthasarathy, A., R. Herikstad, J. H. Bong, F. S. Medina, C. Libedinsky, and S. C. Yen. 2017.
'Mixed selectivity morphs population codes in prefrontal cortex', *Nat Neurosci*, 20:
1770-79.
Pedreira, Carlos, Juan Martinez, Matias J. Ison, and Rodrigo Quian Quiroga. 2012. 'How many
neurons can we see with current spike sorting algorithms?', *Journal of Neuroscience
Methods*, 211: 58-65.
Perge, J. A., M. L. Homer, W. Q. Malik, S. Cash, E. Eskandar, G. Friehs, J. P. Donoghue, and L. R.
Hochberg. 2013. 'Intra-day signal instabilities affect decoding performance in an
intracortical neural interface system', *J Neural Eng*, 10: 036004.
Perge, J. A., S. Zhang, W. Q. Malik, M. L. Homer, S. Cash, G. Friehs, E. N. Eskandar, J. P.
Donoghue, and L. R. Hochberg. 2014. 'Reliability of directional information in unsorted
spikes and local field potentials recorded in human motor cortex', *J Neural Eng*, 11:
046007.
Racz, M., C. Liber, E. Nemeth, R. B. Fiath, J. Rokai, I. Harmati, I. Ulbert, and G. Marton. 2019.
'Spike detection and sorting with deep learning', *J Neural Eng*.
Rey, H. G., C. Pedreira, and R. Quian Quiroga. 2015. 'Past, present and future of spike sorting
techniques', *Brain Res Bull*, 119: 106-17.
Rizzuto, D. S., A. N. Mamelak, W. W. Sutherling, I. Fineman, and R. A. Andersen. 2005. 'Spatial
selectivity in human ventrolateral prefrontal cortex', *Nat Neurosci*, 8: 415-7.
Rossant, C., S. N. Kadir, D. F. M. Goodman, J. Schulman, M. L. D. Hunter, A. B. Saleem, A.
Grosmark, M. Belluscio, G. H. Denfield, A. S. Ecker, A. S. Tolias, S. Solomon, G. Buzsaki,
M. Carandini, and K. D. Harris. 2016. 'Spike sorting for large, dense electrode arrays', *Nat
Neurosci*, 19: 634-41.

Sadtler, P. T., K. M. Quick, M. D. Golub, S. M. Chase, S. I. Ryu, E. C. Tyler-Kabara, B. M. Yu, and A.
P. Batista. 2014. 'Neural constraints on learning', *Nature*, 512: 423-6.
Sadtler, P. T., S. I. Ryu, E. C. Tyler-Kabara, B. M. Yu, and A. P. Batista. 2015. 'Brain-computer
interface control along instructed paths', *J Neural Eng*, 12: 016015.
Saif-Ur-Rehman, M., R. Lienkamper, Y. Parpaley, J. Wellmer, C. Liu, B. Lee, S. Kellis, R. A.
Andersen, I. Iossifidis, T. Glasmachers, and C. Klaes. 2019. 'SpikeDeeptector: A deep-
learning based method for detection of neural spiking activity', *J Neural Eng*, 16.
Santhanam, G., M. Sahani, S. Ryu, and K. Shenoy. 2004. 'An extensible infrastructure for fully
automated spike sorting during online experiments', *Conf Proc IEEE Eng Med Biol Soc*, 6:
4380-4.
Schafer, R. J., and T. Moore. 2011. 'Selective attention from voluntary control of neurons in
prefrontal cortex', *Science*, 332: 1568-71.
Shoham, S., M. R. Fellows, and R. A. Normann. 2003. 'Robust, automatic spike sorting using
mixtures of multivariate t-distributions', *J Neurosci Methods*, 127: 111-22.
Snyder, A. C., M. J. Morais, A. Kohn, and M. A. Smith. 2014. 'Correlations in V1 are reduced by
stimulation outside the receptive field', *J Neurosci*, 34: 11222-7.
Snyder, A. C., M. J. Morais, C. M. Willis, and M. A. Smith. 2015. 'Global network influences on
local functional connectivity', *Nat Neurosci*, 18: 736-43.
Snyder, A. C., and M. A. Smith. 2015. 'Stimulus-dependent spiking relationships with the EEG', *J
Neurophysiol*, 114: 1468-82.
Spaak, E., K. Watanabe, S. Funahashi, and M. G. Stokes. 2017. 'Stable and Dynamic Coding for
Working Memory in Primate Prefrontal Cortex', *J Neurosci*, 37: 6503-16.
Stark, E., and M. Abeles. 2007. 'Predicting movement from multiunit activity', *J Neurosci*, 27:
8387-94.
Todorova, S., P. Sadtler, A. Batista, S. Chase, and V. Ventura. 2014. 'To sort or not to sort: the
impact of spike-sorting on neural decoding performance', *J Neural Eng*, 11: 056005.
Tolias, A. S., A. S. Ecker, A. G. Siapas, A. Hoenselaar, G. A. Keliris, and N. K. Logothetis. 2007.
'Recording chronically from the same neurons in awake, behaving primates', *J
Neurophysiol*, 98: 3780-90.
Trautmann, E. M., S. D. Stavisky, S. Lahiri, K. C. Ames, M. T. Kaufman, D. J. O'Shea, S. Vyas, X.
Sun, S. I. Ryu, S. Ganguli, and K. V. Shenoy. 2019. 'Accurate Estimation of Neural
Population Dynamics without Spike Sorting', *Neuron*, 103: 292-308 e4.
Tremblay, S., G. Doucet, F. Pieper, A. Sachs, and J. Martinez-Trujillo. 2015. 'Single-Trial Decoding
of Visual Attention from Local Field Potentials in the Primate Lateral Prefrontal Cortex Is
Frequency-Dependent', *J Neurosci*, 35: 9038-49.
Velliste, M., S. Perel, M. C. Spalding, A. S. Whitford, and A. B. Schwartz. 2008. 'Cortical control of
a prosthetic arm for self-feeding', *Nature*, 453: 1098-101.
Ventura, V., and S. Todorova. 2015. 'A computationally efficient method for incorporating spike
waveform information into decoding algorithms', *Neural Comput*, 27: 1033-50.
Wang, D., Q. Zhang, Y. Li, Y. Wang, J. Zhu, S. Zhang, and X. Zheng. 2014. 'Long-term decoding
stability of local field potentials from silicon arrays in primate motor cortex during a 2D
center out task', *J Neural Eng*, 11: 036009.
Ward, M. P., P. Rajdev, C. Ellison, and P. P. Irazoqui. 2009. 'Toward a comparison of
microelectrodes for acute and chronic recordings', *Brain Res*, 1282: 183-200.

Wood, F., M. J. Black, C. Vargas-Irwin, M. Fellows, and J. P. Donoghue. 2004. 'On the variability
of manual spike sorting', *IEEE Trans Biomed Eng*, 51: 912-8.
882

Supplementary Figure 1. Weights for three sample hidden units (n1, n2, n3) of the neural network hidden layer and their outputs. To demonstrate how the network classified waveforms, we used 1000 example input waveforms from each of three different categories (bottom three panels: mean and standard deviation of the waveforms in each category). The first category included very spike-like waveforms (i.e. those that were assigned a P(spike) value between 0.95 and 1 by the network, green), the second included moderately spike-like waveforms (0.50 < P(spike) < 0.55, blue), and the third included noise (0<P(spike)<0.05, grey). To visualize the hidden layer, we selected three out of the 50 hidden units and plotted their weights (left panels, $W_{hidden\ layer}$). Each waveform was linearly scaled by the weight vector of units n1, n2, and n3 and summed (middle panels: mean and standard deviation of the scalar outputs of $W_{hidden\ layer}$ x waveform; waveform category indicated by bar color and column, and unit # indicated by row). The output of the hidden layer was passed through a ReLU non-linearity before being multiplied by an output weight (right, $W_{output\ layer}$). The resultant values were summed and passed through a sigmoid non-linearity to produce a P(spike) value (not shown).

Overall, the network's hidden units were difficult to characterize; however, we observed that certain hidden units tended to have a larger, positive response to very spike-like waveforms (e.g. n1 green bar) while others had a larger, positive response to noise waveforms (e.g. n3 grey bar). The positive $W_{output\ layer}$ for n1 would then weigh the final summed output towards a P(spike) of 1 and the negative $W_{output\ layer}$ for n3 would weigh the output towards a P(spike) of 0. Unlike n1 and n3, n2 had variable responses to different types of waveforms, indicating that not every unit had a well-defined spike or noise preference. Overall, we found that different units in the hidden layer focused on features that were associated with different types of spikes in the training data. Note that in the network, the contribution of bias values was not shown in this visualization.

Supplementary Figure 2. SNR metrics decreased as the array aged for Monkey Pe (blue) and Monkey Wa (orange). **(a)** SNR was computed for each channel on the array using the method described in Kelly et al. (2007). The median SNR of the array decreased over time in both subjects (Spearman's rank-order, Monkey Pe: ϱ = -0.77, p < 0.0001; Monkey Wa: ϱ = -0.72, p = 0.002). **(b)** SNR_{NAS} (i.e. the ratio of the percentage of waveforms with a P(spike) > 0.70 to the percentage of waveforms with a P(spike) < 0.02) served as an alternate measure of SNR as it was correlated with median SNR over time (Spearman's rank-order, Monkey Pe: ϱ = 0.78, p < 0.0001; Monkey Wa: ϱ = 0.75, p = 0.01).

Supplementary Figure 3. Change in percent decoding accuracy from that with threshold crossings (Δ % decoding accuracy) over time, as in Figure 5 except **(a)** using the maximum decoding accuracy for each session and **(b)** keeping the number of trials used to decode constant across all sessions. In (a) the maximum decoding accuracy across all γ thresholds greater than 0 on each session was used to show the best possible network performance if γ was chosen separately in each session (and tested in a cross-validated fashion). Δ % decoding accuracy was significantly greater than zero for both subjects across all sessions (2-tailed, Wilcoxon signed rank test, Monkey Pe: p < 0.0001; Monkey Wa: p = 0.01). There was a significant difference between the early array (0-50 days post implant) and the late array (> 50 days post implant) sessions in Monkey Wa, but not in Monkey Pe (2-tailed, Wilcoxon rank sum, Monkey Pe: p = 0.09; Monkey Wa: p = 0.01). In (b), decoding accuracy was computed for each session with 25 trials for Monkey Pe and 50 trials for Monkey Wa. The γ threshold was selected using the same method described for Fig. 4d. Δ % decoding accuracy again was greater than zero for both subjects across all sessions (2-tailed, Wilcoxon signed rank test, Monkey Pe: p < 0.0001; Monkey Wa: p = 0.002). Again, there was a significant difference between the early array (0-50 days post implant) and the late array (> 50 days post implant) sessions in Monkey Wa, but not in Monkey Pe (2-tailed, Wilcoxon rank sum, Monkey Pe: p = 0.68; Monkey Wa p = 0.001).

Supplementary Figure 4. Increasing the voltage threshold (V_T: the minimum voltage a waveform must cross to be included) did not improve decoding accuracy, but using the network classifications provided some benefit in most sessions. In lieu of increasing the RMS multiplier, which we did not store for our data, we increased the voltage thresholds (V_T) for each channel on a particular session by a factor between 1 and 2 (V_T multiplier). We only recorded threshold crossings in our data. A multiplier of 1 simply included all of our original threshold crossings, while a multiplier of 2 included only waveforms that crossed 2* V_T (the "new" threshold crossings). Waveforms that did not meet the new threshold were discarded. **(a,b)** Total percentage of waveforms removed at each V_T multiplier without using the network classifications ($\gamma = 0$, black line) and using the network classifications at a chosen γ threshold (blue line, Monkey Pe: $\gamma = 0.18$; orange line, Monkey Wa: $\gamma = 0.08$) for an example session in Monkey Pe and Monkey Wa. **(c,d)** Using the remaining waveforms after removing those that did not cross the new V_T, we computed decoding accuracy at each V_T multiplier without using the network classifications (black line) and after removing additional waveforms the network assigned P(spike) values below the chosen γ (blue and orange lines). Chance decoding was 12.5% (black dotted line). In both example sessions, increasing the V_T multiplier decreased decoding accuracy. **(e)** For each session, we normalized decoding accuracy with the chosen γ threshold (Monkey Pe: $\gamma = 0.18$; Monkey Wa: $\gamma = 0.08$) by the decoding accuracy without using the network classifications (i.e. the "new" threshold crossings) at each V_T multiplier. Then, we averaged across sessions recorded 0-50 days post-implant (early) and sessions recorded >50 days post-implant (late). Even at higher voltage thresholds, NAS improved decoding accuracy in both early and later sessions for Monkey Pe and in late sessions for Monkey Wa. In Monkey Wa's earlier sessions, using NAS did not substantially hurt or help decoding accuracy. These results were consistent with the trends observed in Figure 5.

Supplementary Figure 5. The network had a similar effect on decoding from V4 96-electrode Utah array implants in each animal as it did on decoding from the PFC array in the same sessions from the same animals (Monkey Pe- blue, Monkey Wa- orange). This analysis was done using the same steps as in Figure 5 except using waveforms from the V4 array instead of the PFC array. Monkey Wa did not have any usable late session (> 50 days post implant) data from the V4 array. As a result, only Monkey Pe was tested for trends over time.

(a) Percentage of waveforms with a P(spike) < 0.02 over time. A waveform with a P(spike) less than 0.02 was one that the network found very unlikely to be a spike. The percentage of these unlikely spike waveforms only slightly but significantly increased as Monkey Pe's array became older (Spearman's rank-order, $\varrho = 0.43$, $p = 0.01$). **(b)** Percentage of waveforms with a P(spike) > 0.70 over time. The percentage of waveforms that the network found to be strongly spike-like decreased as Monkey Pe's array became older ($\varrho = -0.48$, $p = 0.003$). The magnitude of these changes over time was much smaller in V4 compared to PFC. **(c)** Decoding accuracy with threshold crossings (i.e. $\gamma = 0$) decreased by a small amount as the array aged in Monkey Pe ($\varrho = -0.41$, $p = 0.01$). **(d)** Change in percent decoding accuracy using network classified spikes relative to decoding accuracy with threshold crossings (Δ % decoding accuracy). We computed a distribution of the maximum γ threshold (using the same method as in Figure 4c-d) for sessions that were 0-50 days post array implant and used the median to set the γ threshold before computing decoding accuracy for those sessions. We repeated this for sessions more than 50 days post array implant. In Monkey Pe, using NAS classifications improved decoding accuracy (2-tailed, Wilcoxon signed rank test, $p < 0.0001$) and in Monkey Wa, using the classifications neither hurt nor helped decoding significantly ($p = 0.81$). There was a significant difference between the early array (0-50 days post implant) and the late array (> 50 days post implant) sessions in Monkey Pe (2-tailed, Wilcoxon rank sum, $p = 0.0496$).

Thus, despite differences in the array quality between PFC and V4 (as demonstrated by the higher threshold crossing decoding accuracies in V4 compared to PFC in Fig. 5), using our network classifications still proved beneficial in one subject and had no significant impact on the other subject.

Supplementary Figure 6. Assigning waveforms classified as noise on each electrode to a new unit rather than discarding them did not improve decoding performance in most sessions for Monkey Pe (blue) or Monkey Wa (orange). In the main text analyses, any waveform classified as noise via our network or via spike-sorting was discarded. However, Todorova *et al.* (2014) found that creating a separate noise unit for the noise waveforms from each unit actually led to better decoding performance than discarding the noise. We sought to assess whether this result held for our data. **(a)** Using the manually spike-sorted classifications, we added a new unit to accompany each spike unit that contained all waveforms classified as noise (plotted on the y-axis). Percent decoding accuracy was worse with noise units for Monkey Pe (paired, 2-tailed, Wilcoxon signed rank test- $p < 0.0001$) and not significantly different for Monkey Wa ($p = 0.19$). **(b)** Similar to (a), except using NAS classifications. For each session, we discarded the noise units and found the γ threshold that resulted in the maximum decoding accuracy. We classified waveforms as spikes or noise using that threshold and then computed decoding accuracy with and without the noise units for each session (for the latter, the test set was independent from the set used to select the γ threshold). Discarding noise resulted in a higher decoding accuracy for most sessions in both subjects (Monkey Pe: $p < 0.0001$, Monkey W: $p = 0.049$). Thus, unlike Todorova *et al.* (2014), we did not find preserving the noise as separate units to be beneficial for decoding. In fact, the noise removed from most of the later recording sessions (>50 days post implant) was typically harmful for decoding.