Machine learning based detection of genetic and drug class variant impact on functionally conserved protein binding dynamics

Gregory A. Babbitt[1]*, Ernest P. Fokoue[3], Joshua R. Evans[1], Kyle I. Diller[1,2], Lily E. Adams[1]

[1]Thomas H. Gosnell School of Life Sciences, Rochester Institute of Technology, Rochester NY, USA 14623
[2]Golisano College for Computing and Information Science, Rochester NY, USA 14623
[3]Applied Statistics, Rochester Institute of Technology, Rochester NY, USA 14623

*email address for primary correspondence: gabsbi@rit.edu

Contact Information –Gregory A. Babbitt (gabsbi@rit.edu).

27 Abstract

The application of statistical methods to comparatively framed questions about protein dynamics can
potentially enable investigations of biomolecular function beyond the current sequence and structural
methods in bioinformatics. However, chaotic behavior in single protein trajectories requires statistical
inference be obtained from large ensembles of molecular dynamic (MD) simulations representing the
comparative functional states of a given protein. Meaningful interpretation of such a complex form of
big data poses serious challenges to users of MD. Here, we announce DROIDS v3.0, a molecular dynamic
(MD) method + software package for comparative protein dynamics, incorporating many new features
including maxDemon v1.0, a multi-method machine learning application that trains on large ensemble
comparisons of concerted protein motions in opposing functional states and deploys learned
classifications of these states onto newly generated protein dynamic simulations. Local canonical
correlations in learning patterns generated from self-similar MD runs are used to identify regions of
functionally conserved protein dynamics. Subsequent impacts of genetic and drug class variants on
conserved dynamics can also be analyzed by deploying the classifiers on variant MD runs and
quantifying how often these altered protein systems display the opposing functional states. Here, we
demonstrate statistical visualizations of complex changes in functional dynamics caused by temperature
changes, chemical mutations, and binding interactions with nucleic acids and small molecules. We
studied the impact of genetic variation on functionally conserved protein dynamics in ubiquitin and
TATA binding protein and find that our learning algorithms can identify conserved dynamics in new self-
similar simulations. We also report impacts to dynamics that correspond well with predicted disruptive
effects of a variety of genetic mutations. We studied the impact of drug class variation on the ATP
binding region of Hsp90, similarly identifying conserved dynamics and impacts that rank accordingly
with how closely different Hsp90 inhibitors mimic the natural ATP binding.

50 Keywords

51 Molecular dynamics, machine learning, molecular evolution, pharmaceuticals, genetic variation, binding
52 interaction

53 Statement of significance

We propose statistical methods as well as provide a user-friendly graphical interfaced software pipeline
for comparing simulations of the complex motions (i.e. dynamics) of proteins in different functional
states. We also provide both method and software to apply artificial intelligence (i.e. machine learning
methods) that enable the computer to recognize complex functional differences in protein dynamics on
new simulations and report them to the user. This method can identify dynamics important for protein
function, as well as to quantify how the motions of molecular variants differ from these important
functional dynamic states. This allows the impacts of different genetic backgrounds or drug classes to be
examined within the context of dynamic motions of the specific protein system under investigation.

Introduction

The physicist Richard Feynman is said to have once famously quipped, 'all biology is ultimately
due to the wiggling and jiggling of atoms'. Stated with more precision, Feynman's conjecture would
imply that all biological function at the molecular level can actually be understood by analyzing rapid
atom motions in biomolecular structures as they alter their functional state(s). Many decades later,
functional shifts in molecular dynamics are now being illuminated by structural and computational
biology. Examples of such functional dynamics include the destabilization of inter-residue contacts, in
both disease malfunction and normal signal activation, as well as stabilization of inter-residue contacts
during protein folding, the formation of larger complexes, and various other binding interactions to
small molecules. And while the functional role of rapid vibrations revealed by short term dynamic
simulations has been debated in the past, more recent empirical and computational studies have clearly
demonstrated that differences in both rapid and directed vibrations can drive longer term functional
conformational change (1, 2). From a broader perspective, if Feynman's conjecture is true, then the
specific details of a given protein systems biomolecular dynamics will represent a potentially large
source of latent variability in our functional understanding of the genome; a problem largely ignored by
the considerable amount of current analyses of static forms of 'omic' data (i.e. DNA sequence, transcript
level, and protein structure)(3). However, in the last decade, simultaneous advances in the development
of gaming graphics hardware and biomolecular force fields has elevated our ability to computationally
simulate molecular dynamics (MD) long enough to capture the most biologically relevant timescales for
protein function (4, 5) (i.e. ns to μs). And now, the application of proper statistical methods to
comparatively framed questions about protein dynamics can potentially enable meaningful comparisons
of large ensembles of shorter timed framed MD simulation (6). But despite the rich visual complexity of
data and movie images generated by MD software, the functional interpretation of these large complex
data sets created by modern MD simulations poses a serious challenge to current users, especially
where large ensembles of runs need to be collected and statistically compared. A potential solution to
this problem exists with the application of machine learning to the feature extraction and classification
of the dynamic differences between ensembles of MD runs representing the functional states of
biomolecular systems (e.g. before/after chemical mutation or binding interaction). In other words, the
high performance computation used to generate simulated protein motions for comparison can be
effectively partnered with high performance methods for optimally extracting and learning what the
underlying dynamic feature differences are that define different functional protein states. Although
machine learning has recently been applied to individual MD studies for a variety of specific tasks (7–9),
there is no current software platform for the general application of machine learning to comparative
protein dynamics.

In 2018, we released DROIDS v1.2 and v2.0 (Detecting Relative Outlier Impacts from molecular
Dynamic Simulation), a GPU accelerated software pipeline designed for calculating and visualizing
statistical comparisons of protein dynamics drawn from large repeated ensembles of short dynamic
simulations representing two protein states (6). This application allowed simple visual and statistical
comparison of protein MD ensembles set up in any way the user wanted to define them. Here, we
announce the release of DROIDS v3.0, which comprises multiple pipelines tailored for specific functional
comparisons. These include comparisons of different temperatures, different binding states (i.e. to DNA,
drugs, toxins or natural ligands), or divergent genetic/epigenetic mutant states. Many other new
improvements to DROIDS are listed below, however we also include a major new machine learning tool,
maxDemon v1.0, a multi-machine learning post-processing application that trains on the data
representing the normal functionally divergent dynamic states compared in DROIDS, and subsequently
identifies the effects on these learned dynamics upon the deployment of new MD simulations

representing genetic or drug class variants of interest. Thus, much like James Clerk Maxwell's mythical
creature (10), maxDemon derives important information from all atom resolution observation of
dynamic motion. The three primary features/aims of our newly expanded software is to (A) improve
user experience in comparative protein dynamics, (B) enable the local detection of functionally
conserved protein dynamics, and to (C) enable the assessment of the local dynamic impacts of both
genetic and drug class variants within the functional context of protein system of interest. Functionally
conserved dynamics are defined as 'repeated or self-similar and sequence-dependent dynamics'
discovered after training machine learners on the functional state ensembles derived with DROIDS.
Conserved dynamics are detected via significant canonical correlations in position specific learning
performance patterns after the deployment of learners on new MD simulation runs that were setup
identically to the dynamic state defined by the MD ensemble training sets. We expect that functionally
conserved dynamics will be sequence encoded and therefore should display a repeated position
dependent signature in our learned pattern profiles whenever MD runs are set up identically to MD
upon which learners were trained. Therefore, a significant local canonical correlation (i.e. Wilk's lambda)
between learning performance profiles of self-similar MD runs can be used to detect local regions of
conserved protein dynamics. By extension, mutational impacts of genetic or drug class variants on the
functionally conserved dynamics can be quantified by their effects that range significantly beyond that
observed in the self-similar runs. Thus when canonical correlations of variants differ significantly from
the self-correlation observed, according to a bootstrap or z-test, we plot the relative entropy or
magnitude of impact defining how the variant's dynamics differs from the self-similar dynamics of the
normal functioning protein. Because the machine learning algorithms are ultimately trained on MD data
representing this normal functioning state(s), this metric of impact is highly context dependent to how a
given mutation or drug impacts a specific protein. Thus, it potentially gives considerably more functional
relevance to results when compared to more general database-derived metrics of mutational tolerance
(e.g. SIFT, PolyPhen2 etc.).
In Table 1, we list five primary methodological pipelines in available in DROIDS 3.0+maxDemon
to address functional questions in comparative protein dynamics. In our results and discussion here, we
present data on four case studies of functional protein dynamics that include feature extraction and
classification of (A) a simple temperature shift in ubiquitin dynamics, (B) mutational tolerance in
ubiquitin dynamics, (C) mutation specific impacts of DNA binding of TATA binding protein, and (D)
comparison of binding dynamics of drug class variants that mimic ATP binding in Hsp90.

Materials and Methods

Overview

The machine learning-based detection of variant impacts on functional protein dynamics presented here
is outlined schematically in Figure 1. Our method/software leverages several important key concepts
when making valid comparisons between dynamics. The DROIDS method/software employs statistical
ensembling to make a robust comparison between protein dynamics in different functional states (6).
This is needed because of the inherent chaotic nature and unpredictability of single protein trajectory
projections. This is analogous to the many 'storm tracks' repeatedly modeled in order to gain confidence
in a weather forecast. The user can decide how large the MD ensembles need to be based upon the
stability of the protein under investigation. In the case studies presented here we used ensembles of
200 MD runs at 0.5 ns each for each of the two functional states (i.e. 400 runs). The dynamics is
summarized by calculation of root mean square fluctuations (rmsf) over constant time intervals, thus

allowing rmsf values to be comparable. We propose that rmsf is the most basic underlying functional
quantity to extract from MD simulation. When comparing rmsf, the user can choose to see and average
difference, or more preferably the Kullback-Leibler divergence (i.e. relative entropy) between the overall
statistical distributions of rmsf. The KL divergence provides a richer more informative view of dynamic
differences than simple averaging. While users can easily employ DROIDS to examine ensemble
differences between functional states, the application of this knowledge to new MD simulation is nearly
impossible due to the inherent complexity of the moving protein behavior. Our new software,
maxDemon, uses machine learning to essentially label or classify the differences learned by DROIDS
when applied to new MD runs. Learners are applied individually to each amino acid backbone rmsf
values allowing for single residue resolution in the results. Learners are also applied to user define time
slices of rmsf allowing for time resolution of classification of functional dynamic behaviors as well. The
learning performance is summarized by tallying the average classification (0 or 1) over all time slices for
each amino acid. Thus an average performance of 0.5 would indicate that the learners are not finding
the functional states defined by and trained by the initial DROIDS comparative analysis. Canonical
correlations in the positional performance plots are key in detecting sequence encoded functionally
conserved dynamics regions, as well as genetic and drug class variant impacts to these functional
regions as well. This is described with more formality below.

Upon launch, the DROIDS graphical user interface (GUI) will help the user write a control file for
required working path directories on their system (first use only) and then proceeds to a main GUI
outlining the various types of comparisons that can be generated (as detailed in Table 1) and the
number of GPU available on the system. The next step is provides a user-friendly GUI to control and
schedule Amber16/18 GPU-accelerated MD simulation to generate ensembles of short MD runs
representing two functional protein states wanting to be compared. These functional comparisons are
not limited, but would typically entail the impact of mutation (comparing dynamics before and after one
or more amino acid replacements), the impact of an environmental change (comparing two states of
temperature of solvent set up), or the impact of a molecular interaction (comparing bound to an
unbound state). The DROIDS GUI will lead users through the building of a structural alignment file using
UCSF Chimera's MatchMaker and Match-Align tools. This will be needed later by the graphics
components of DROIDS to make sure that only homologous regions of structures are being compared
and analyzed. In this application, where the user is primarily interested in genetic or drug class variant
impacts on an interactive signaling function, the typical training ensembles generated by DROIDS for
further analysis with maxDemon should represent the normal binding function of the wild-type protein
and therefore the bound vs unbound comparison would typically be used. A PDB file of the bound state
can be the starting point and an unbound PDB model can be saved after deleting chains in the original
file. If a small molecule ligand interaction is under study and requires application of an additional force
fields such as GAFF, than an additional file representing only the ligand should also be generated and
saved for preparation with antechamber software prior to building the solvent models using teLeAP. The
GUI will pop open the .bat files that control more details of the simulation setup allowing advanced
users to write more lines into the teLeAP modeling prep (e.g. to alter the water box dimensions, the
water model itself, or to add additional ions beyond simple charge neutralization). The user should read
all warnings provided to the terminal at this stage by the Amber software. Our GUI script will also
double check the sizes of the files generated at this stage and will supply a warning if teLeap failed
altogether to set up the complete model system for simulation. Upon successful setup the user can
launch all the MD runs from the GUI. The requested jobs are automatically scheduled to each GPU one

at a time by our software. When finished, the user can easily generate rmsf data by using the GUI to
setup and launch cpptraj software provided in Ambertools. Thus the total process from file preparation,
MD production and post-processing for DROIDS analysis by simply working down the buttons on each
GUI from top to bottom and subsequently following the directions on the main terminal. After MD
simulation and post-processing, DROIDS will take users to a second GUI for generating R plots and
analyses for statistically comparing the dynamics, and then to a third GIU for visualization and movie
generation. We refer users to our user manual and previous publication for more details. This third GUI
has buttons to optionally launch our new machine learning application maxDemon if users wish to go
beyond simple comparative protein dynamics and investigate novel simulations utilizing the DROIDS MD
ensembles as a training set for subsequent machine learning. Users can select any of seven different
machine learning classification algorithms including K-nearest neighbors, naïve Bayes, linear
discriminant analysis, quadratic discriminant analysis, random forest, adaptive boosting and support
vector machine (kernels include linear, tuned polynomial, laplace and tuned radial basis function). For
methodologically robust results, we generally recommend users select all of them.   For faster
processing, a minimum of three of the seven learning methods can be chosen. Currently, most methods
run on single CPU cores, however, the more CPU intensive methods of random forest and adaboost
algorithms are programmed to use all available CPU cores found on the system.

To detect functionally conserved dynamics after training on two MD ensembles representing a
query and reference functional state of a protein (e.g. bound and unbound), the machine learners are
deployed on two new MD simulations across space and time (i.e. fluctuations backbone atoms of
individual amino acids over subdivided time intervals) that are identical to the original query state. Any
sequence dependent or 'functionally conserved' dynamics can be recognized through a significant
canonical correlation in the profile of the overall learning performance along the amino acid positions
for the two similar state runs. In effect, this metric defines dynamics that are functionally conserved by
capturing a signal of significant self-similarity in dynamics that localizes to a specific part of the protein
backbone.

Eqn. 1 $$conserved_{dynamics} = significant\ (CC_{self})$$

The impacts of dissimilar states caused by altered amino acid sequence or different binding
partners can be subsequently assessed through their local effect on this canonical correlation (i.e.
conserved dynamics). Here, we introduce a metric of relative entropy relating the canonical correlations
in both the self-similar and altered state. In essence, this is a metric of the 'impact' of a given genetic or
drug class variant within the context of normal functioning dynamics. For example, when trained on a
natural binding interaction (e.g. DROIDS analysis comparing a DNA binding protein in its bound and
unbound states), novel MD simulations with a variety of amino acid replacements can be deployed to
see whether the learners can recognize the functional dynamics in the mutant forms. In this case,
functionally tolerated mutations will result in dynamics that do not vary outside of the normal bounds of
the self-similar runs, whereas functionally intolerant mutations will result in significant deviations from
self-similarity of motion.

Eqn. 2 $$variant_{impact} = CC_{self} * log\frac{CC_{variant}}{CC_{self}}$$

Variant impacts are only plotted when they differ significantly the self-similar MD runs according to a
simple Z test.

More detailed instructions to users are included with our DROIDS 3.0+maxDemon 1.0 user manual
available in the GitHub repository.

The main repository for DROIDS 3.0 and maxDemon 1.0 can be found here. Please follow the link to
"Releases" and download the latest release as .tar.gz or .zip file

https://github.com/gbabbitt/DROIDS-3.0-comparative-protein-dynamics

and DOI: 10.5281/zenodo.3358976 concurrent with this publication

https://zenodo.org/record/3358976#.XURVkOhKiiM

We also post various videos of examples using DROIDS, video tutorials, and ongoing projects here

https://www.youtube.com/channel/UCJTBqGq01pBCMDQikn566Kw

To enhance the user experience and scientific utility, DROIDS v3.0 offers many new features beyond
earlier major release versions 1.2 and 2.0.   These are summarized below.

-   New GUI organization directs users to specific comparative tasks/applications in Table 1
-   A new control file builder for managing path dependencies in Linux is included
-   Amber16/18 support has been beta tested and is defined via paths.ctl file
-   Single or dual GPU user options are available for faster analyses
-   Automated structure prep (dry and reduce) via pdb4amber is now included in the GUI. The
'reduce' variable is optional allowing users to either setup their own protonation states ahead of
DROIDS, or simply allow DROIDS to hydrogenate the input structures entirely.
-   Program/package dependency installer script named 'DROIDSinstaller.pl' is included. It will lead
users through all dependencies required after a fresh Linux build, including CUDA libraries and
tools required for Nvidia GPU accelerated Amber in the Linux environment
-   KL divergence (= relative entropy) definition of dFLUX is now included as an option providing a
richer color mapping of dFLUX in images and movies than the simple averaging algorithm
offered in earlier DROIDS versions

dFLUX collected as an angstrom average

$$dFLUX_{aa} = \left(\sum_{i=1}^{4} FLUX_{atom}\right)_{query} - \left(\sum_{i=1}^{4} FLUX_{atom}\right)_{reference}$$

$$dFLUX_{chain} = \sum_{i=1}^{L} |dFLUX_{aa}|$$

where L = number of structurally homologous amino acids in reference chain

i = 4 or avg atom flux on N, O, CA and C backbone atoms

dFLUX collected as symmetric KL divergence

$$dFLUX_{aa} = \left[\begin{array}{c} D_{KL}(FLUX_{query}|FLUX_{reference}) \\ + D_{KL}(FLUX_{reference}|FLUX_{query}) \end{array}\right] \Big/ 2$$

where

$$D_{KL}(FLUX_{query}|FLUX_{reference}) = \sum_i FLUX_{query}(i) log \frac{FLUX_{query}(i)}{FLUX_{reference}(i)}$$

$$D_{KL}(FLUX_{reference}|FLUX_{query}) = \sum_i FLUX_{reference}(i) log \frac{FLUX_{reference}(i)}{FLUX_{query}(i)}$$

and

i = 4 or avg atom flux on N, O, CA and C backbone atoms

-   Binding interaction analysis for both protein-DNA and protein-ligand systems is now offered
with dedicated GUI for these comparisons. Protein-ligand system setup includes QMMM
preprocessing in Antechamber and SQM.
-   LeAP control files for explicit solvent runs are now presented for advanced user modifications
(e.g. changing ion concentration, water model, water box dimension of volume).

-     Dedicated GUI allowing genetic mutation placement (on DNA or AA) are included for setting up
271   variants to analyze
272   -   Self-stability and temperature shift analysis has its own dedicated GUI, allowing users to copy
273   the input pdb file to compare MD ensembles generated on identical structures at the same of at
274   different temperatures
275   -   MaxDemon 1.0 - machine learning based detection of functionally conserved dynamic regions
276   -   MaxDemon 1.0 - machine learning based impact assessment of variants (genetic, structural or
277   binding)
278   -   Dynamic visualization and movie rendering of machine learning classification performance
279   -   Virtual reality and ChimeraX compatibility is also supported (additional information and
280   download code can be found here
281   https://cxtoolshed.rbvi.ucsf.edu/apps/moleculardynamicsviewer
282   https://github.com/kdiller713/ChimeraX_MolecularDynamicViewer

To demonstrate the performance and utility of DROIDS 3.0 + maxDemon 1.0, we ran the following four
comparative case studies using the PDB IDs mentioned below. Bound and unbound files were created by
deleting binding partners in UCSF Chimera and resaving PDBs (e.g. 3t0z_bound.pdb, 3t0z_unbound and
3t0z_ligand). Each MD run ensemble consisted of 200 production runs at 0.5ns each explicitly solvated
in a size 12 octahedral water box using TIP3P solvent model with constant temperature under an
Anderson thermostat. The models were charge neutralized with both Na+ and Cl- ions. The heating and
equilibration runs prior to production were 0.3ns and 10ns respectively. Prior to heating 2000 steps of
energy minimization were also performed.   All seven available machine learning classifiers were
trained on the functional MD ensembles and deployed upon new 5 ns production runs for each variant
analyzed.

Case study 1 (figure 2) – PDB ID = 1ubq – to analyze self-stability and effect of temperature shift in
ubiquitin

Case study 2 (figure 3)– PDB ID = 2oob – to analyze functional binding of ubiquitin to ubiquitin ligase and
impacts of several tolerance pre-classified genetic variants

Case study 3 (figure 4) – PDB ID = 1cdw – to analyze functional binding of TATA binding protein to DNA
and impacts of several genetic variants

Case study 4 (figure 5) – PDB ID = 3t0z – to analyze functional ATP binding in Hsp90 and subsequent
impacts of six inhibitor drug variants

302   Results and Discussion

To demonstrate the variety of comparative analyses that can be addressed with the new release of
DROIDS 3.0 and maxDemon 1.0, we chose four different case studies of comparative protein dynamics.
These included (A) an analysis of self-stability and temperature effects in single ubiquitin structure, (B) a
functional genetic variant analysis of ubiquitin and ubiquitin ligase binding interaction, (C) a functional
genetic variant analysis of DNA binding in TATA binding protein, and (D) a drug class variant analysis of
compounds targeting the Bergerat ATP binding region of Hsp90 heat shock protein.

Machine learning analysis of impacts due to simple environmental temperature shift

We first ran a null comparison as a 'sanity check' by running a query and reference ubiquitin (11)
MD at the same temperatures (both 300K) and same solvent conditions. The DROIDS analysis (Figure 2A-
C) showed identical atom fluctuation profiles along the backbone and a random dFLUX profile indicative
of nonsignificant differences due to small random local thermal differences in the training sets. The
machine learning classification plots on new MD runs vary randomly around 0.5 reflecting the fact that
the learning algorithms had no features to train on (Figure 2D). As expected, no significantly conserved
dynamics were identified either (Figure 2E). By contrast, a protein dynamic comparison run with a 50K
temperature difference (Figure 2 F-H) shows a much higher machine learner performance upon
deployment (i.e. 70-80% successful classification – Figure 2I). Because environmental temperature shifts
are not expected to reflect evolutionary conserved dynamics (i.e. are not position dependent), they
subsequently do not result in canonical correlations in the learning profiles (Figure J). Representative
time slices of the positional classifications in each of these experiments are shown in K and L resp and
indicate that our machine learning is capable of extracting and identifying simple differences in
dynamics due to temperature. Another interesting observation here was the slightly higher learning
performance of the simpler machine learning methods QDA and LDA over others at all sites in the
temperature shifted example. We interpret this to be related to the fact that underlying rmsf
distributions are probably Gaussian, a critical assumption of these two models, with unequal variances
caused by steric hindrances on the backbone. This would predict that QDA might outperform other
learners in this situation and it appears that it does. We note that where more complex functional
dynamics are concerned, the more sophisticated learning methods such as support vector machine and
adaboost often perform slightly better than others. However, we also note that these performance
differences are usually quite small and that all learning methods generally come to similar local
conclusions about functional dynamics. We examine machine learning performance regarding more
functional binding dynamics in ubiquitin.

Machine learning analysis of impacts of genetic variants on a functional protein binding interaction

To examine functional dynamics in ubiquitin, we conducted a DROIDS analysis comparing its two
functional states, bound and unbound to the ubiquitin associated binding (UBA) domain of ubiquitin
ligase (12)(Figure 3A-D). This binding domain is highly conserved among the many other proteins that
interact directly with ubiquitin. The binding interaction greatly reduces the atom fluctuation in ubiquitin
at 3 characteristic positions, two loop structures centered at LEU 8 and ALA 46 and a portion of beta
sheet at the C terminus (Figure 3C). These three regions also drive significant differences in dynamics
across the whole protein. In novel self-similar MD runs on the bound state, we successfully detect
significant canonical correlations indicating conserved dynamics in these three regions with a broad
expanse in conserved dynamics (Figure 3E and F) across the UBA region (Figure 3G). We tested a set of
24 mutations that included sites with the most and least tolerated effects on growth rate in vivo in yeast
according to a study by Roscoe et al. (13). In this study in vivo, nearly all mutations at E18 and G53 are
tolerated while nearly all mutations at K48 and R72 are not. Ultimately, the causes of tolerance in these
variants are not known, and do not necessarily invoke functional problems in dynamics. However, the
impacts that we did observed in simulation were on average twice as strong in the intolerant
backgrounds when compared to the mutation tolerant backgrounds. And, while we did not see large

differences in mutational impacts on dynamics between tolerated and non-tolerated mutant groups, the
24 mutations analyzed all show a general trend of dynamic impact falling outside of most of the
functional binding region (Figure 3H-K), suggesting that ubiquitin may have evolved a tertiary structure
that allosterically translates dynamic impacts to less functional regions of the protein. One interesting
exception to this rule was demonstrated by the very large impact of R72D, centered squarely in the
functionally conserved binding region of ubiquitin, and would obviously heavily disrupt electrostatic
charge interactions there as well.

Machine learning analysis of impacts of genetic variants on DNA binding interaction

TATA binding protein (TBP) is a general transcription factor that binds DNA upstream in most
highly regulated eukaryotic gene promoter regions (14). While relatively small, it is a mechanically
dynamic protein with a C-clamp like structure that highly distorts the rigid DNA double helix by inserting
four phenylalanine side-chains between base pairs. It is thought that this bending allows TBP to be more
rapidly released from the TATA element, as opposed to TATA-less promoters, subsequently allowing
more highly controlled regulatory responses in TATA box genes (15). Due to its obvious symmetry and
ability to impart large forces during binding, we thought that it would represent a good candidate for
comparison of its dynamics during its binding interaction with DNA. We conducted a DROIDS analysis
comparing human TBP (16) in its functionally bound and unbound states (Figure 4A-C). TBP exhibits a
characteristic large signature of dampening of atom fluctuation throughout its entire structure with
most pronounced effects in two loop regions that interact with the minor groove of DNA (arrows in
Figure 4A and 4C). Canonical correlations in new self-similar MD runs marking increased performance in
classification were observed in these regions (Figure 4D) along with corresponding regions of conserved
dynamics identified by significant Wilk's lamda (Figure 4E). Conserved dynamics from these loop areas
are connected through the chains in the beta sheet region of TBP spanning the DNA major groove
contact. Mutational impacts of four variants affecting the binding loop most proximal to the C terminal
exhibited followed our expectation of increasing impact ordering from R192Q, R192K, R192polyD, and
R192polyW (Figure 4G and 4H). The polyD and polyW mutations incorporated 5 sequential ASP or TRP
residues centered at R192, both causing the loop region to become more rigid (causing increased
negative dFLUX). We expected the strong functional binding affect observed across nearly all residues in
this system would make it relatively highly tolerant to single amino acid substitutions, even when
located in the most functional binding loop. In accordance with this idea, we found the most impactful
multiple mutation (i.e. R192polyW) significantly affected the dynamics of nearly 6 times more local
residues than the least impactful single substitution (i.e. R192Q).

Machine learning analysis of impacts of drug class variants targeting the ATP binding region of Hsp90

In contrast to TBP, we wanted to use our method to examine a small molecule binding
interaction in a protein with potentially more complex impacts on molecular dynamics. Hsp90 is a well-
known chaperone protein that assists the folding of many proteins and thereby mitigating many
environmental stresses in the cell. Hsp90 even capacitates the evolutionary process by allowing
potential phenotypic variation exhibited under stress to be hidden from natural selection until needed in
response to environmental change (17). Hsp90 contains a highly conserved N-terminal domain where
ATP binding and activation occurs. The binding of ATP physically changes motions in this region creating
a 'lid' that closed during ATP binding and open when conversion to ADP occurs. Due to the role of Hsp90

in stress mitigation in most tumors, it is a common drug target for ATP inhibitors in many cancer
therapies (18, 19). The amino acid residues that interact with ATP in this region are well known and the
inhibitor geldanamycin is known to mimic nearly all the local ATP contacts as well (20). Other more
modern inhibitors interact with the ATP binding pocket differently (19, 21, 22), so we thought that this
system would be a good candidate for comparative analysis of drug class variants.

We conducted a DROIDS analysis comparing the dynamics of Hsp90 chaperone, a common
drug target for inhibitors in many cancer therapies, in both its ATP bound and unbound states. The
binding of ATP was discovered to significantly destabilize three co-localized alpha helical regions of the
protein adjacent to and extending from the ATP binding site (Figure 5A-D). MaxDemon analysis
confirmed the dynamics of this region to be highly conserved in new MD runs (Figure 5D-G). We also
analyzed the impacts of the six drug class variants targeting the ATP site (20, 22, 21, 23, 24), but
interacting differently with residues in this region (Figure 5H). The contacts in the ATP binding site are
shown in Figure 5I. While the localized patterns of impacts of the drug variants were all quite similar to
ATP (Figure 5J), the drug variants that most closely mimicked the contacts of ATP (i.e. geldanamycin) had
far less impact on dynamics than variants that interacted very differently with the binding pocket (i.e.
benzamide SNX1321 and inhibitor FJ1(Figure H-I). We feel that this finding demonstrates that while it is
important to be able to target a druggable protein binding site (25), researchers should also consider
how these various chemicals might alter the natural dynamics of the system. In situations where a drug
might too closely mimic the dynamic effects of a natural activator like ATP, a hyperactivation response
might occur in non-tumor cells leading to secondary cancer (26–28). Alternatively, other situations may
require drug targeting that does not alter the natural dynamic behavior too much, potentially activating
proteolytic systems in the cell. Our software allows more detailed investigations of these potential
dynamic impacts of drug class variants.

Conclusion

We provide a well demonstrated method and user-friendly software pipeline for conducting statistically
sound comparative studies of large ensembles of comparative protein dynamics. The method/software
also now provides machine learning based extrapolations of effects on novel MD simulations
representing various functional variants of interest to the user. While there currently is at least one
other software allowing users to connect sequence-based evolutionary metrics to protein dynamics (29),
our method/software is unique in that regions of functional conservation are identified by analyzing
self-similar features of dynamics themselves rather than relying upon traditional sequence-based
approaches, which do not necessarily assume that a protein function has a strong dynamic component.
Therefore, by providing a systematic way of comparing protein dynamics at single residue resolution,
our method/software provides an important step beyond traditional bioinformatics, allowing
investigators to gain a much more biophysically-grounded view of functional and evolutionary change.
Another advantage to our method/software is that our functional impacts (i.e. mutational tolerance) are
defined solely within the context of protein dynamic system being simulated. This provides a much
deeper look into protein specific function than current genomic and proteomic database methods of
predicting mutational tolerance (30, 31) currently allow. As GPU technology continues to advance at a
rapid pace over the next few years, our method/software may have profound potential application to
the development of precision and personalized medicine, where understanding the detailed interaction
between genetic and drug class variants within the context of specific protein dynamic systems will be
greatly needed.

Supporting Material

The main repository for DROIDS 3.0 and maxDemon 1.0 can be found at the GitHub repository link
below. Please follow the link to "Releases" and download the latest release as .tar.gz or .zip file

https://github.com/gbabbitt/DROIDS-3.0-comparative-protein-dynamics

We also post various videos of examples using DROIDS, video tutorials, and ongoing projects here

https://www.youtube.com/channel/UCJTBqGq01pBCMDQikn566Kw

A 'live version' of the figures in this manuscript is also available on our YouTube channel.

Author Contribution

446 GAB and EPF conceived the project and method. All authors contributed to the code base. GAB and LEA
447 worked on beta testing and debugging.

Acknowledgements

450 We acknowledge the lab of Dr. Andre O. Hudson for beta testing our software during its early
451 development. We acknowledge Dr. Miranda Lynch and her colleagues at the Hauptman-Woodward
452 Medical Research Institute for many helpful comments.

References

1. Henzler-Wildman, K.A., M. Lei, V. Thai, S.J. Kerns, M. Karplus, and D. Kern. 2007. A hierarchy of
timescales in protein dynamics is linked to enzyme catalysis. Nature. 450: 913–916.

2. Niessen, K.A., M. Xu, A. Paciaroni, A. Orecchini, E.H. Snell, and A.G. Markelz. 2017. Moving in the
Right Direction: Protein Vibrations Steering Function. Biophys. J. 112: 933–942.

3. Babbitt, G.A., E.E. Coppola, M.A. Alawad, and A.O. Hudson. 2016. Can all heritable biology really be
reduced to a single dimension? Gene. 578: 162–168.

4. Götz, A.W., M.J. Williamson, D. Xu, D. Poole, S. Le Grand, and R.C. Walker. 2012. Routine
Microsecond Molecular Dynamics Simulations with AMBER on GPUs. 1. Generalized Born. J. Chem.
Theory Comput. 8: 1542–1555.

5. Salomon-Ferrer, R., A.W. Götz, D. Poole, S. Le Grand, and R.C. Walker. 2013. Routine Microsecond
Molecular Dynamics Simulations with AMBER on GPUs. 2. Explicit Solvent Particle Mesh Ewald. J.
Chem. Theory Comput. 9: 3878–3888.

6.   Babbitt, G.A., J.S. Mortensen, E.E. Coppola, L.E. Adams, and J.K. Liao. 2018. DROIDS 1.20: A GUI-
Based Pipeline for GPU-Accelerated Comparative Protein Dynamics. Biophys. J. 114: 1009–1017.

7.   Díaz, Ó., J.A.R. Dalton, and J. Giraldo. 2019. Artificial Intelligence: A Novel Approach for Drug
Discovery. Trends Pharmacol. Sci. .

8.   Plante, A., D.M. Shore, G. Morra, G. Khelashvili, and H. Weinstein. 2019. A Machine Learning
Approach for the Discovery of Ligand-Specific Functional Mechanisms of GPCRs. Mol. Basel Switz.
24.

9.   Terayama, K., H. Iwata, M. Araki, Y. Okuno, and K. Tsuda. 2018. Machine learning accelerates MD-
based binding pose prediction between ligands and proteins. Bioinforma. Oxf. Engl. 34: 770–778.

10.   Maxwell, J.C. 2001. Theory of Heat. 9 Reprint edition. Mineola, NY: Dover Publications.

11.   Vijay-Kumar, S., C.E. Bugg, and W.J. Cook. 1987. Structure of ubiquitin refined at 1.8 A
resolution. J. Mol. Biol. 194: 531–544.

12.   Peschard, P., G. Kozlov, T. Lin, I.A. Mirza, A.M. Berghuis, S. Lipkowitz, M. Park, and K. Gehring.
2007. Structural basis for ubiquitin-mediated dimerization and activation of the ubiquitin protein
ligase Cbl-b. Mol. Cell. 27: 474–485.

13.   Roscoe, B.P., K.M. Thayer, K.B. Zeldovich, D. Fushman, and D.N.A. Bolon. 2013. Analyses of the
effects of all ubiquitin point mutants on yeast growth rate. J. Mol. Biol. 425: 1363–1377.

14.   Kornberg, R.D. 2007. The molecular basis of eukaryotic transcription. Proc. Natl. Acad. Sci. U. S.
A. 104: 12955–12961.

15.   Tora, L., and H.T.M. Timmers. 2010. The TATA box regulates TATA-binding protein (TBP)
dynamics in vivo. Trends Biochem. Sci. 35: 309–314.

16.   Nikolov, D.B., H. Chen, E.D. Halay, A. Hoffman, R.G. Roeder, and S.K. Burley. 1996. Crystal
structure of a human TATA box-binding protein/TATA element complex. Proc. Natl. Acad. Sci. U. S.
A. 93: 4862–4867.

17.   Rutherford, S.L., and S. Lindquist. 1998. Hsp90 as a capacitor for morphological evolution.
Nature. 396: 336–342.

18.   Neckers, L., and P. Workman. 2012. Hsp90 Molecular Chaperone Inhibitors: Are We There Yet?
Clin. Cancer Res. 18: 64–76.

19.   Yuno, A., M.-J. Lee, S. Lee, Y. Tomita, D. Rekhtman, B. Moore, and J.B. Trepel. 2018. Clinical
Evaluation and Biomarker Profiling of Hsp90 Inhibitors. Methods Mol. Biol. Clifton NJ. 1709: 423–
441.

20.   Stebbins, C.E., A.A. Russo, C. Schneider, N. Rosen, F.U. Hartl, and N.P. Pavletich. 1997. Crystal
structure of an Hsp90-geldanamycin complex: targeting of a protein chaperone by an antitumor
agent. Cell. 89: 239–250.

21. Immormino, R.M., Y. Kang, G. Chiosis, and D.T. Gewirth. 2006. Structural and quantum chemical
studies of 8-aryl-sulfanyl adenine class Hsp90 inhibitors. J. Med. Chem. 49: 4953–4960.

22. Li, J., L. Sun, C. Xu, F. Yu, H. Zhou, Y. Zhao, J. Zhang, J. Cai, C. Mao, L. Tang, Y. Xu, and J. He. 2012.
Structure insights into mechanisms of ATP hydrolysis and the activation of human heat-shock
protein 90. Acta Biochim. Biophys. Sin. 44: 300–306.

23. Fadden, P., K.H. Huang, J.M. Veal, P.M. Steed, A.F. Barabasz, B. Foley, M. Hu, J.M. Partridge, J.
Rice, A. Scott, L.G. Dubois, T.A. Freed, M.A.R. Silinski, T.E. Barta, P.F. Hughes, A. Ommen, W. Ma,
E.D. Smith, A.W. Spangenberg, J. Eaves, G.J. Hanson, L. Hinkley, M. Jenks, M. Lewis, J. Otto, G.J.
Pronk, K. Verleysen, T.A. Haystead, and S.E. Hall. 2010. Application of chemoproteomics to drug
discovery: identification of a clinical candidate targeting hsp90. Chem. Biol. 17: 686–694.

24. Austin, C., S.N. Pettit, S.K. Magnolo, J. Sanvoisin, W. Chen, S.P. Wood, L.D. Freeman, R.J.
Pengelly, and D.E. Hughes. 2012. Fragment screening using capillary electrophoresis (CEfrag) for hit
identification of heat shock protein 90 ATPase inhibitors. J. Biomol. Screen. 17: 868–876.

25. Vajda, S., D. Beglov, A.E. Wakefield, M. Egbert, and A. Whitty. 2018. Cryptic binding sites on
proteins: definition, detection, and druggability. Curr. Opin. Chem. Biol. 44: 1–8.

26. Poulikakos, P.I., C. Zhang, G. Bollag, K.M. Shokat, and N. Rosen. 2010. RAF inhibitors
transactivate RAF dimers and ERK signalling in cells with wild-type BRAF. Nature. 464: 427–430.

27. Hatzivassiliou, G., K. Song, I. Yen, B.J. Brandhuber, D.J. Anderson, R. Alvarado, M.J.C. Ludlam, D.
Stokoe, S.L. Gloor, G. Vigers, T. Morales, I. Aliagas, B. Liu, S. Sideris, K.P. Hoeflich, B.S. Jaiswal, S.
Seshagiri, H. Koeppen, M. Belvin, L.S. Friedman, and S. Malek. 2010. RAF inhibitors prime wild-type
RAF to activate the MAPK pathway and enhance growth. Nature. 464: 431–435.

28. Cichowski, K., and P.A. Jänne. 2010. Drug discovery: inhibitors that activate. Nature. 464: 358–
359.

29. Bakan, A., A. Dutta, W. Mao, Y. Liu, C. Chennubhotla, T.R. Lezon, and I. Bahar. 2014. Evol and
ProDy for bridging protein sequence evolution and structural dynamics. Bioinformatics. 30: 2681–
2683.

30. Kumar, P., S. Henikoff, and P.C. Ng. 2009. Predicting the effects of coding non-synonymous
variants on protein function using the SIFT algorithm. Nat. Protoc. 4: 1073–1081.

31. Adzhubei, I., D.M. Jordan, and S.R. Sunyaev. 2013. Predicting functional effect of human
missense mutations using PolyPhen-2. Curr. Protoc. Hum. Genet. Chapter 7: Unit7.20.

537 Table 1. Common learner assisted comparative protein dynamic investigations enabled by

538 DROIDS 3.0 + maxDemon 1.0.

QUESTION	DROIDS 3.0 training comparison	Deployment of learners in maxDemon	Important notes
Measure dynamic tolerances of single protein to various genetic mutations	Two sets (ensembles) of MD on the same protein at the same temperature	MD run on one or more genetic mutant structures	Isolates MD impacts of mutation(s) from natural variability in self-similar dynamics
Measure dynamic tolerances of DNA binding interaction to genetic mutation(s)	MD ensembles comparing both the unbound and DNA bound protein	MD run on one or more unbound genetic mutant structures	Isolates MD impacts of mutation from natural binding function of the system
Measure dynamic tolerances of individual genetic differences to a given drug	MD ensembles comparing both the unbound and drug bound protein	MD run on one or more drug-bound genetic mutant structures	Isolates MD impacts of mutation from novel drug binding function of the system
Measure dynamic similarities of different drug candidates to natural ligand binding interaction	MD ensembles comparing both the unbound and ligand bound protein	MD run on one or more drug variant bound structures	Isolates MD impacts of drug candidates from the natural binding function of the ligand
Measure evolution of novel dynamics in paralog genes	MD ensembles comparing two ortholog proteins (i.e. same gene different species)	MD runs on one or more paralogs (i.e. duplicated genes in same species)	Isolates potential MD novelty in duplicated gene product from nonfunctional or neutral changes in different species

544 Figures

Figure 1. Schematic overview of DROIDS 3.0 + maxDemon 1.0 software for machine learning-based detection of variant impacts on functionally conserved protein dynamics. The pipeline starts with (A) generation of two large ensembles of molecular dynamic (MD) simulations that represent a functional comparison of protein states (e.g. mutation, binding or environmental change). The root mean square fluctuations (rmsf) of protein backbone atoms in these ensembles are comparatively analyzed/visualized (i.e. using DROIDS) and are also later used as pre-classified training data sets for machine learning (i.e. using maxDemon). Note: in the pictured DROIDS analysis of nucleosome shows overall dampening of rmsf in the histone core with maximal dampening where the histone tails cross the DNA helix (B) New MD simulations are generated on two structures self-similar to the query state of training as well as a list of functional variants, and (C) up to seven machine learning methods are employed to classify the MD in the self-similar and variant runs according to the functional comparison defined by the initial training step. (D) The relative efficiency of learning is defined by average value of classification (i.e. 0 or 1) over 50 frame time slices for each amino acid position and regions of functionally conserved dynamics are later identified by significant canonical correlations in this learning efficiency (i.e. Wilk's lamda) in self-similar MD runs. The impacts of variants are defined by relative entropy of variant MD compared to the MD in the self-similar runs and plotted when this entropy is significantly different from the variation in self-similarity (i.e. bootstrapped z-test). (E) A visual representation of the difference in local rmsf (dFLUX) is typically calculated using symmetric Kullback-Leibler (KL) divergence between the two distributions of rmsf in the training MD ensembles.

Figure 2. Analysis of environmental temperature change on non-functional ubiquitin dynamics.
DROIDS image and analysis of random ubiquitin dynamics compared at the same (A-E) and different (F-J)
temperatures. Note: blue color quantifies damped rmsf at temperature lowered by 50K. Note that
relative learning is much higher when a temperature difference is modeled (D and I resp), however, as
expected, neither comparison offers the machine learners a sequence-dependent profile by which to
establish a signal of conserved dynamics (E or J).   The learner classifications for the best performing
learner in this case (quadratic discriminant function: QDA) is shown imaged on the ubiquitin structure
over time in both the (K) random dynamics and (L) temperature dampened dynamics. (Movies of this
can be observed in supplemental file A)

Figure 3. Analysis of mutational impact and tolerance on functional ubiquitin dynamics. (A) DROIDS image and analysis of ubiquitin bound to the ubiquitin associated binding domain (UBA) of ubiquitin ligase. Note: blue color quantifies damped rmsf at binding interface. (i.e. negative dFLUX) also by the (B) respective rmsf profiles of bound and unbound training states and (C) the KL divergence or dFLUX profile colored by residue. Arrows indicate most prominent dampening of rmsf near loops at THR 9, ALA 46 and C terminus. (D) Significant differences in these rmsf profiles is determined by multiple-test corrected two sample KS test. (E) Local relative learning efficiency of each machine learning method in self-similar testing runs are shown color-coded by run and regions of functionally conserved dynamics, determined via significant local canonical correlation are shown in dark gray in both (F) traditional N to C terminal plot as well as (G) structural image. The mutational impacts of 24 genetic variants (H-K: six variants at each or four sites) are shown all demonstrating lack of impact in functionally conserved regions of the binding interaction.

Figure 4. Analysis of mutational impact and tolerance on DNA binding in Tata Binding Protein (TBP).
DROIDS image and analysis of TBP in DNA-bound and unbound states showing (A) colored TBP structure,
(B) respective rmsf profiles and (C) KL divergence (dFLUX) plot. Note: arrows indicate functional binding
loops in the DNA minor groove red color indicates dampened rmsf. maxDemon analysis (D-E) identifying
conserved dynamics supporting both minor groove binding loops and (F) connecting them through the
central region of the beta sheet in the main body of TBP closest to the DNA.   Mutational impacts of 4
genetic variants with increasing impact one of the functional loops are also shown (G) plotted and (H) on
the TBP structure. They are R192K, R192D, R192Q and polyW centered at R192 in 1cdw.pdb and and
position 161 (red arrow) in plots (Note: 31 position offset is due to DNA in the original file).

Figure 5. Analysis of drug class variant binding in the ATP-binding domain of Hsp90. DROIDS image and analysis of Hsp90 in ATP-bound and unbound states showing (A) colored Hsp90 structure, (B) respective rmsf profiles and (C) KL divergence (dFLUX) plot and (D) significant differences in dynamics determined via the KS test. Note: arrows and green color indicate regions where rmsf is amplified in response to ATP binding. maxDemon analysis (E-G) identifying conserved dynamics connecting the ATP binding pocket and region of amplified rmsf. (H) Mutational impacts of 6 drug class variants targeting the ATP binding pocket of Hsp90 are plotted and (I) ordered by number of differences in structural contacts within the binding pocket. (J) Mutational impacts of these variants are demonstrated to predominantly impact the functionally conserved region of amplified rmsf thus mimicking the dynamic effect of functional ATP binding.

642