Machine learning based detection of genetic and drug class variant impact on functionally conserved protein binding dynamics

Gregory A. Babbitt[1]*, Ernest P. Fokoue[3], Joshua R. Evans[1], Kyle I. Diller[1,2], Lily E. Adams[1]

[1]Thomas H. Gosnell School of Life Sciences, Rochester Institute of Technology, Rochester NY, USA 14623
[2]Golisano College for Computing and Information Science, Rochester NY, USA 14623
[3]Applied Statistics, Rochester Institute of Technology, Rochester NY, USA 14623

*email address for primary correspondence: gabsbi@rit.edu

Contact Information –Gregory A. Babbitt (gabsbi@rit.edu).

Abstract

The application of statistical methods to comparatively framed questions about protein dynamics can potentially enable investigations of biomolecular function beyond the current sequence and structural methods in bioinformatics. However, chaotic behavior in single protein trajectories requires statistical inference be obtained from large ensembles of molecular dynamic (MD) simulations representing the comparative functional states of a given protein. Meaningful interpretation of such a complex form of big data poses serious challenges to users of MD. Here, we announce DROIDS v3.0, a molecular dynamic (MD) method + software package for comparative protein dynamics, incorporating many new features including maxDemon v1.0, a multi-method machine learning application that trains on large ensemble comparisons of concerted protein motions in opposing functional states and deploys learned classifications of these states onto newly generated protein dynamic simulations. Local canonical correlations in learning patterns generated from self-similar MD runs are used to identify regions of functionally conserved protein dynamics. Subsequent impacts of genetic and drug class variants on conserved dynamics can also be analyzed by deploying the classifiers on variant MD runs and quantifying how often these altered protein systems display the opposing functional states. Here, we present several case studies of complex changes in functional protein dynamics caused by temperature, genetic mutation, and binding interaction with nucleic acids and small molecules. We studied the impact of genetic variation on functionally conserved protein dynamics in ubiquitin and TATA binding protein and demonstrate that our learning algorithm can properly identify regions of conserved dynamics. We also report impacts to dynamics that correspond well with predicted disruptive effects of a variety of genetic mutations. In addition, we studied the impact of drug class variation on the ATP binding region of Hsp90, similarly identifying conserved dynamics and impacts that rank accordingly with how closely various Hsp90 inhibitors mimic natural ATP binding.

Keywords

Molecular dynamics, machine learning, molecular evolution, pharmaceuticals, genetic variation, binding interaction

Statement of significance

We propose a statistical method as well as offer a user-friendly graphical interfaced software pipeline for comparing simulations of the complex motions (i.e. dynamics) of proteins in different functional states. We also provide both method and software to apply artificial intelligence (i.e. machine learning methods) that enable the computer to recognize complex functional differences in protein dynamics on new simulations and report them to the user. This method can identify dynamics important for protein function, as well as to quantify how the motions of molecular variants differ from these important functional dynamic states. For the first time, this method of analysis allows the impacts of different genetic backgrounds or drug classes to be examined within the context of functional motions of the specific protein system under investigation.

Introduction

The physicist Richard Feynman is said to have once famously quipped, 'all biology is ultimately due to the wiggling and jiggling of atoms'. Stated with more precision, Feynman's conjecture would imply that all biological function can ultimately be understood by analyzing rapid molecular motions in biomolecular structures as they alter or shift their functional state(s). Many decades later, these functional shifts in molecular dynamics are being illuminated by structural and computational biology. Examples of functionally altered dynamics include the destabilization of inter-residue contacts, in both disease malfunction and normal signal activation, as well as the stabilization of inter-residue contacts during protein folding, the formation of larger complexes, and various other binding interactions to small molecules. And while the functional role of rapid vibrations revealed by short term molecular dynamic (MD) simulations has been debated in the past, more recent empirical and computational studies have clearly demonstrated that differences in both rapid and directed vibrations can drive longer term functional conformational change (1, 2). From a broader perspective, if Feynman's conjecture is true, then the specific details of a given protein system's biomolecular dynamics will represent a potentially large source of latent variability in our functional understanding of the genome; a problem largely ignored by those disciplines currently generating the vast amounts of static forms of 'omic' type data (i.e. DNA sequence, transcript level, and protein structure)(3). However, in the last decade, simultaneous advances in the development of graphics hardware and biomolecular force fields has elevated our ability to computationally simulate MD long enough to capture ns to μs timescales for moderately-sized proteins (4, 5), and finally 'see' some of their functionally relevant motions. And now, the application of proper statistical comparisons of ensembles of short-timed framed MD simulation can potentially enable meaningful interpretations of comparative questions about protein dynamics (6). But due to the richly complex structure of data underlying the moving images generated by MD software, functional interpretation of modern MD simulations poses a serious challenge to current users, especially with comparatively-framed questions, where large ensembles of many production runs need to be generated and subsequently analyzed. A potential solution to this problem exists with the application of machine learning to the feature extraction and classification of the dynamic differences between ensembles of MD runs. These ensembles can be designed to represent pair-wise functional states of biomolecular systems (e.g. before/after chemical mutation or binding). Therefore, the high performance accelerated computation used to generate simulated protein motions for comparison can be effectively partnered with high performance methods for optimally extracting and learning the underlying dynamic feature differences defining the different functional states of proteins. Although machine learning has recently been applied to individual MD studies for a variety of specific tasks (7–9), there is no current software platform for the general application of machine learning to comparative protein dynamics.

In 2018, we released DROIDS v1.2 and v2.0 (Detecting Relative Outlier Impacts from molecular Dynamic Simulation), a GPU accelerated software pipeline designed for calculating and visualizing statistical comparisons of protein dynamics drawn from large repeated ensembles of short dynamic simulations representing two protein states (6). This application allowed simple visual and statistical comparison of protein MD ensembles set up in any way the user wanted to define them. Here, we announce the release of DROIDS v3.0, which now offers multiple pipelines tailored for specific functional comparisons of systems comprised of combinations of proteins, nucleic acids, and small ligand molecules. Comparisons can include different temperatures, different protein binding states (i.e. to DNA, drugs, toxins or natural ligands), or divergent genetic/epigenetic mutant states. We also include a major new machine learning tool, maxDemon v1.0, a multi-machine learning post-processing application for DROIDS that trains on the data representing the comparatively divergent functional dynamic states,

and subsequently identifies functionally conserved dynamics and genetic and/or drug class binding
variant effects when deployed on new MD simulations representing these variants of interest. Thus,
much like James Clerk Maxwell's mythical creature (10), maxDemon derives important information from
all atom resolution observation of dynamic motion. The three primary features/aims of our newly
expanded software is to (A) improve user experience in comparative protein dynamics, (B) enable the
local detection of functionally conserved protein dynamics, and to (C) enable the assessment of the local
dynamic impacts of both genetic and drug class variants within the functional context of protein system
of interest. Because the machine learning model we employ is trained on MD data representing normal
functioning dynamic states of a protein, this metric of impact is highly context dependent to how a given
mutation or drug impacts a specific protein. Thus, it potentially gives considerably more functional
relevance to the analysis of variants when compared to more general database-derived metrics of
mutational tolerance (e.g. SIFT, PolyPhen2 etc.). In Table 1, we list five primary methodological pipelines
in available in DROIDS 3.0+maxDemon to address functional questions in comparative protein dynamics.
In our results and discussion here, we present data on four case studies of functional protein dynamics
that include feature extraction and classification of (A) a simple temperature shift in ubiquitin dynamics,
(B) mutational tolerance in ubiquitin dynamics, (C) mutation specific impacts of DNA binding of TATA
binding protein, and (D) comparison of binding dynamics of drug class variants that mimic ATP binding in
Hsp90.

131   Materials and Methods

Overview of comparative dynamics and visualization with DROIDS v3.0

Our DROIDS method/software leverages several important key concepts when making comparisons
between MD. The method utilizes structural alignment to restrict comparison of dynamics between
individual homologous amino acids. The method also restricts comparison averaged over atoms
common to all amino acids (i.e. backbone C, N, O and C_α). The method also employs statistical
ensembling to make a robust comparison between protein dynamics in different functional states (6).
While this is computationally intensive, it is necessary because of the inherent chaotic nature and
unpredictability of single protein trajectory projections. This logic is analogous to the many 'storm
tracks' repeatedly modeled by meteorologists to gain statistical confidence in a weather forecast, where
an ensemble of model runs all with slightly different initial conditions has far more predictive power
than any single simulation. In DROIDS, the user can decide how large the MD ensembles need to be
based upon the inherent stability of the protein under investigation. Generally, an ensemble size of 200
to 300 MD runs at 0.5-1 ns will suffice for most proteins. The dynamics is summarized by calculation of
root mean square fluctuations (*rmsf*) over constant time intervals represented by a constant number of
image frames defined by the user (thus allowing *rmsf* values to be on comparable scales). The default
number of frames (*i*) in the software for a given time slice is n=50 representing 0.01 ns of simulation
time. The rmsf value is thus

$$rmsf = \frac{1}{4}\sum_{i=1}^{4}\sqrt{\frac{1}{n}*\sum_{j=1}^{n}\left(v_{jx}-w_x\right)^2 + \left(v_{jy}-w_y\right)^2\left(v_{jz}-w_z\right)^2}$$

where *v* represents the set of XYZ atom coordinates for *i* backbone atoms (C, N, O, and C_α) for a given
amino acid residue over *j* time points and *w* represents the reference coordinate structure at the
beginning of each MD production run for a given ensemble. Therefore, *rmsf* values as defined here
represent molecular dynamics at the resolution of a single amino acid, the same resolution at which fine
scale protein-level molecular evolution operates via amino acid replacement, insertion and deletion. The
rmsf is the most also basic underlying functional quantity to extract from MD simulation as its underpins
all hierarchical levels of motion (1). Two ensembles of *rmsf* values (a query set and a reference set) are
compared to calculate average delta *rmsf* or *dRMSF*. The user can choose to see the average angstrom
difference between sets of values, or more preferably the user can calculate the symmetric Kullback-
Leibler divergence (i.e. relative entropy) between the two empirical statistical distributions of *rmsf*. The
KL divergence generally provides a richer more informative view of dynamic differences with less loss of
information than simple averaging. Thus *dRMSF* comparing *rmsf* values for two ensembles of size *m* for
a given amino acid is

163
$$dRMSF_{avg} = \left(\sum_{i=1}^{m} rmsf\right)_{query} - \left(\sum_{i=1}^{m} rmsf\right)_{reference}$$

164   or

165
$$dRMSF_{KL} = \frac{1}{2} * \left[\left(\sum_{i=1}^{m} p(rmsf_{query}) * log\frac{p(rmsf_{query})}{p(rmsf_{reference})}\right)\right.$$
166
$$\left. + \left(\sum_{i=1}^{m} p(rmsf_{reference}) * log\frac{p(rmsf_{reference})}{p(rmsf_{query})}\right)\right]$$

The resulting dRMSF values are color mapped to either still structures or movie images of the dynamics
according to either 'temperature' scale where (+) dRMSF is red and (−) dRMSF is blue, or 'stoplight' scale
where (+) dRMSF is green and (−) dRMSF is red. On both scale neutral values are shaded towards white.

Functional classification of new MD simulation with maxDemon v1.0

While users can easily employ DROIDS 3.0 to examine ensemble differences between functional genetic
or binding states, the application of this knowledge to new MD simulation is nearly impossible due to
the inherent complexity of the moving protein behavior. Our new post-processing software, maxDemon
1.0, uses machine learning to label or classify the differences learned by a previous DROIDS
query/reference state comparison when applied to one or more new MD runs. The machine learning-
based detection of variant impacts on functional protein dynamics presented here is outlined
schematically in Figure 1. Similar to the statistics for comparative dynamics, the learning algorithms are
also applied individually to each amino acid backbone's ensemble of *rmsf* values allowing for single
residue resolution in the results. Learners are applied within the same user defined time slices of *rmsf*
allowing for visualization of time resolution of classification of functional dynamic behaviors as well. The
learning performance is summarized by tallying the average classification over all time slices for each
amino acid. Thus, an average performance of 0.5 would indicate that the learners are not finding the
functional states defined by and trained by the initial DROIDS comparative analysis. Canonical
correlations in the positional performance plots are key in detecting sequence encoded functionally

conserved dynamics regions, as well as genetic and drug class variant impacts to these functional
regions as well. This is described with more formality below.

Machine learning training and validation

189   The feature vectors (X) for machine learning are collections of *rmsf* values (x_i) labeled according
190   to a query (q) and reference state (r) defined by the DROIDS MD comparison (i.e. where labels y_i are *q =*
191   *1* and *r = 0*).

$$X = \{(x_i, y_i)\}_{i=1}^{N}$$

193   The length of the vector (N) is defined by the length of the MD production run chosen by the user and
194   the size of the ensemble of MD production runs taken. Thus if the user chooses an ensemble of 200 MD
195   production runs each at a time length of 0.5 ns (= 2500 frames) and uses the default time interval of 50
196   frames to calculate any given interval of *rmsf* then the resulting feature vector will contain 20,000 data
197   values for training (i.e. 10,000 values each for *q* and *r*).

198   Users create a 'stacked model' or meta-model containing up to seven different machine learning
classification algorithms including K-nearest neighbors, naïve Bayes, linear discriminant analysis,
quadratic discriminant analysis, random forest, adaptive boosting and support vector machine (kernels
options include tuned linear, polynomial, laplace and radial basis function). R packages employed here
are KNN, MASS, kernlab, randomForest and ada. We restricted machine learning to 'shallow' learning
methods due to the relatively small datasets created when resolving dynamics of protein systems to
short slices of time over single amino acids and also because of the robustness of the R packages when
applied sequentially over time and structural space. Therefore, we do not support implementation of
deep neural networks. For methodologically robust results on small proteins, we generally recommend
users select all seven available methods. As real features of dynamics should be detectable by any
method of learning, the agreement of classification obtained by the creation of a stacked model utilizing
different methods makes the learning less sensitive to methodological artifacts. Depending upon system
resources, users can choose to include or omit methods from four categories of learning (i.e. instance-
based = KNN, probabilistic = NB / LDA / QDA, black box = SVM, and ensemble learning = randomForest /
adaboost. Users will want to use as many as their system resources can handle, however for faster
processing, a minimum of three of the seven learning methods can be chosen. Currently, most methods
run on single CPU cores, however, the more CPU intensive methods of random forest and adaboost
algorithms are programmed to use all available CPU cores found on the system. Omitting SVM is
recommended for larger protein systems.

217   After learners are trained on the query and reference ensembles, they are validated on a new
MD run that matches the state of the reference MD runs during training. For example, when analyzing a
binding interaction where the reference ensemble of training runs are conducted in the unbound
protein state, a new run will be conducted in the unbound state and a line plot of the machine learning
performance (i.e. precision, recall and accuracy) will be generated for all positions on the protein. It
would be expected that if comparative differences in dynamics observed in the training set have a
genuine relation to function(s) defined during training, they will display repeated behavior in the new
reference run and be identified by the stacked learning model generating local peaks in learning
performance (i.e. accuracy) at functional regions (Figure 1D). Learner performance (*PERF*) for a given
machine learning method is defined as

$$PERF = \frac{TP + TN}{TP + TN + FP + FN} = \frac{TP + 0}{TP + 0 + FP + 0}$$

Where TP, TN, FP, and FN are true positive, true negative, false positive, and false negative
classifications resp. The zero value terms arise because the validation is conducted on simulation
representing just the reference state of the DROIDS comparison (where $y_i = 0$).   Therefore, accuracy,
and precision are algebraically collapsed to a single equivalent performance metric while recall is always
equal to 1.

Identifying regions of conserved dynamics

Functionally conserved dynamics are defined as 'repeated or self-similar and sequence-dependent
dynamics' discovered after training machine learners on the functional state ensembles derived with
DROIDS. Conserved dynamics are detected via significant canonical correlations in position specific
learning performance patterns after the deployment of learners on new MD simulation runs that were
setup identically to the reference dynamic state defined by the MD ensemble training set. We expect
that functionally conserved dynamics will be sequence encoded and therefore should display a repeated
position dependent signature in our learned pattern profiles whenever MD runs are set up identically to
MD upon which learners were trained. Therefore, a significant local canonical correlation (i.e. Wilk's
lambda) between learning performance profiles of self-similar MD runs can be used to detect local
regions of conserved protein dynamics.

To detect functionally conserved dynamics after training and validation, an additional new MD
run matching the functional reference state is created (i.e. matching the MD validation run). The
learning performance of this run is compared across all selected learners and across space and time (i.e.
fluctuations backbone atoms of individual amino acids over subdivided time intervals) to the same
results from the MD validation run using a canonical correlation analysis. Any sequence dependent or
'functionally conserved' dynamics can be recognized through a significant canonical correlation in the
profile of the overall learning performance along the amino acid positions for the two similar state runs.
In effect, this metric defines dynamics that are functionally conserved by capturing a signal of significant
self-similarity in dynamics that co-localizes to a specific part of the protein backbone.

$$conserved_{dynamics} = significant\ (CC_{self})$$

Significantly conserved regions calculated within a user defined sliding window (default value =20
residues with cutoff of $p<0.01$) can be plotted upon both the positional local correlational value profile
(i.e. R value) and the reference structure of the protein, colored in dark gray on a light background.

Variant impact assessment

By extension, mutational impacts of genetic or drug class variants on the functionally conserved
dynamics can be quantified by their effects that range significantly beyond that observed in the self-
similar reference runs. Thus when canonical correlations of variants differ significantly from the self-
correlation observed in functionally conserved regions, according to a bootstrap test, we can plot the
magnitude of impact defining how the variant's dynamics differs from the normal self-similar dynamics
of the in the conserved regions of the normal functioning protein. The impacts of dissimilar states
caused by altered amino acid sequence or different binding partners are assessed through their local
effect on this canonical correlation identifying conserved dynamics. We introduce a metric of relative

entropy relating the canonical correlations in both the self-similar and altered variant state. In essence,
this is a metric of the 'impact' of a given genetic or drug class variant within the context of normal
functioning dynamics. For example, when trained on a natural binding interaction (e.g. DROIDS analysis
comparing a DNA binding protein in its bound and unbound states), novel MD simulations with a variety
of amino acid replacements can be deployed to see whether the learners can still recognize the
functional dynamics in the mutant forms. In this case, functionally tolerated mutations will result in
functionally conserved dynamics that do not vary outside of ± 3 standard deviation bounds of the self-
similar runs, whereas functionally intolerant mutations will result in significant deviations from self-
similarity of motion. An overall impact of a genetic and/or drug class binding variant on the conserved
dynamic regions is calculated by

276
$$variant_{impact} = CC_{self} * log \frac{CC_{variant}}{CC_{self}}$$

Comparative plots of local variant impacts outside of the 3 standard deviation bound determined by the
validation run are able to be generated within a user defined sliding window.

Four example applications (case studies)

To demonstrate the performance and utility of DROIDS 3.0 + maxDemon 1.0, we ran the following four
comparative case studies using the PDB IDs mentioned below. Bound and unbound files were created by
deleting binding partners in UCSF Chimera and resaving PDBs (e.g. 3t0z_bound.pdb, 3t0z_unbound and
3t0z_ligand). Each MD run ensemble consisted of 200 production runs at 0.5ns each explicitly solvated
in a size 12 octahedral water box using TIP3P solvent model with constant temperature under an
Anderson thermostat. The models were charge neutralized with both Na+ and Cl- ions. The heating and
equilibration runs prior to production were 0.3ns and 10ns respectively. Prior to heating 2000 steps of
energy minimization were also performed.   All seven available machine learning classifiers were
trained on the functional MD ensembles and deployed upon new 5 ns production runs for each variant
analyzed.

Case study 1 (figure 2) – PDB ID = 1ubq – to analyze self-stability and effect of temperature shift in
ubiquitin

Case study 2 (figure 3)– PDB ID = 2oob – to analyze functional binding of ubiquitin to ubiquitin ligase and
impacts of several tolerance pre-classified genetic variants

Case study 3 (figure 4) – PDB ID = 1cdw – to analyze functional binding of TATA binding protein to DNA
and impacts of several genetic variants

Case study 4 (figure 5) – PDB ID = 3t0z – to analyze functional ATP binding in Hsp90 and subsequent
impacts of six inhibitor drug variants

Improvements and upgrades over previous versions

To enhance the user experience and scientific utility, DROIDS v3.0 offers many new features beyond
earlier major release versions 1.2 and 2.0.   These are summarized below.

-    New GUI organization directs users to specific comparative tasks/applications in Table 1
-    A new control file builder for managing path dependencies in Linux is included
-    Amber16/18 support has been beta tested and is defined via paths.ctl file

304	-	Single or dual GPU user options are available for faster analyses
305	-	Automated structure prep (dry and reduce) via pdb4amber is now included in the GUI. The
306		'reduce' variable is optional allowing users to either setup their own protonation states ahead of
307		DROIDS, or simply allow DROIDS to hydrogenate the input structures entirely.
308	-	Program/package dependency installer script named 'DROIDSinstaller.pl' is included. It will lead
309		users through all dependencies required after a fresh Linux build, including CUDA libraries and
310		tools required for Nvidia GPU accelerated Amber in the Linux environment
311	-	KL divergence (= relative entropy) definition of dFLUX is now included as an option providing a
312		richer color mapping of dFLUX in images and movies than the simple averaging algorithm
313		offered in earlier DROIDS versions
314	-	Binding interaction analysis for both protein-DNA and protein-ligand systems is now offered
315		with dedicated GUI for these comparisons. Protein-ligand system setup includes QMMM
316		preprocessing in Antechamber and SQM.
317	-	LeAP control files for explicit solvent runs are now presented for advanced user modifications
318		(e.g. changing ion concentration, water model, water box dimension of volume).
319	-	Dedicated GUI allowing genetic mutation placement (on DNA or AA) are included for setting up
320		variants to analyze
321	-	Self-stability and temperature shift analysis has its own dedicated GUI, allowing users to copy
322		the input pdb file to compare MD ensembles generated on identical structures at the same of at
323		different temperatures
324	-	MaxDemon 1.0 - machine learning based detection of functionally conserved dynamic regions
325	-	MaxDemon 1.0 - machine learning based impact assessment of variants (genetic, structural or
326		binding)
327	-	Dynamic visualization and movie rendering of machine learning classification performance
328	-	Virtual reality and ChimeraX compatibility is also supported (additional information and
329		download code can be found here
330		https://cxtoolshed.rbvi.ucsf.edu/apps/moleculardynamicsviewer
331		https://github.com/kdiller713/ChimeraX_MolecularDynamicViewer

Basic implementation of DROIDS and maxDemon

The first step of any DROIDS analysis is to find or create two homologous PDB file format structures that
represent the query and reference functional states of the protein system under investigation. Typically,
these would represent the same protein in a bound vs. unbound state, or in a mutant vs. wildtype state.
If the protein is interacting with a small ligand, and additional 'ligand only' PDB file should also be
created for subsequent quantum mechanical optimization and preparation by Ambertools antechamber
program. These files should be placed within the DROIDS download folder. Upon implementation via the
command 'perl DROIDS.pl' launched from terminal within the DROIDS folder, the DROIDS graphical user
interface (GUI) will help the user write a control file for required working path directories on their
system (first use only) and then proceeds to a main GUI outlining the various types of comparisons that
can be generated (as detailed in Table 1) and the number of GPU available on the system. The next step
is provides a user-friendly GUI to control and schedule Amber16/18 GPU-accelerated MD simulation to
generate ensembles of short MD runs representing two functional protein states wanting to be
compared. These functional comparisons are not limited, but would typically entail the impact of
mutation (comparing dynamics before and after one or more amino acid replacements), the impact of

an environmental change (comparing two states of temperature of solvent set up), or the impact of a
molecular interaction (comparing bound to an unbound state). The DROIDS GUI will lead users through
the building of a structural alignment file using UCSF Chimera's MatchMaker and Match-Align tools. This
will be needed later by the graphics components of DROIDS to make sure that only homologous regions
of structures are being compared and analyzed. In this application, where the user is primarily
interested in genetic or drug class variant impacts on an interactive signaling function, the typical
training ensembles generated by DROIDS for further analysis with maxDemon should represent the
normal binding function of the wild-type protein and therefore the bound vs unbound comparison
would typically be used. A PDB file of the bound state can be the starting point and an unbound PDB
model can be saved after deleting chains in the original file. If a small molecule ligand interaction is
under study and requires application of an additional force fields such as GAFF, than an additional file
representing only the ligand should also be generated and saved for preparation with antechamber
software prior to building the solvent models using teLeAP. The GUI will pop open the .bat files that
control more details of the simulation setup allowing advanced users to write more lines into the teLeAP
modeling prep (e.g. to alter the water box dimensions, the water model itself, or to add additional ions
beyond simple charge neutralization). The user should read all warnings provided to the terminal at this
stage by the Amber software. Our GUI script will also double check the sizes of the files generated at this
stage and will supply a warning if teLeap failed altogether to set up the complete model system for
simulation. Upon successful setup the user can launch all the MD runs from the GUI. The requested jobs
are automatically scheduled to each GPU one at a time by our software. When finished, the user can
easily generate rmsf data by using the GUI to setup and launch cpptraj software provided in Ambertools.
Thus the total process from file preparation, MD production and post-processing for DROIDS analysis by
simply working down the buttons on each GUI from top to bottom and subsequently following the
directions on the main terminal. After MD simulation and post-processing, DROIDS will take users to a
second GUI for generating R plots and analyses for statistically comparing the dynamics, and then to a
third GIU for visualization and movie generation. We refer users to our user manual and previous
publication for more details. This third GUI has buttons to optionally launch our new machine learning
application maxDemon if users wish to go beyond simple comparative protein dynamics and investigate
novel simulations utilizing the DROIDS MD ensembles as a training set for subsequent machine learning.

More detailed instructions to users are included with our DROIDS 3.0+maxDemon 1.0 user
manual available in the GitHub repository.

The main repository for DROIDS 3.0 and maxDemon 1.0 can be found here. Please follow the link to
"Releases" and download the latest release as .tar.gz or .zip file

https://github.com/gbabbitt/DROIDS-3.0-comparative-protein-dynamics

and DOI: 10.5281/zenodo.3358976 concurrent with this publication

https://zenodo.org/record/3358976#.XURVkOhKiiM

We also post various videos of examples using DROIDS, video tutorials, and ongoing projects here

https://www.youtube.com/channel/UCJTBqGq01pBCMDQikn566Kw

Results and Discussion

To demonstrate the variety of comparative analyses that can be addressed with the new release of
DROIDS 3.0 and maxDemon 1.0, we chose four different case studies of comparative protein dynamics.
These included (A) an analysis of self-stability and temperature effects in single ubiquitin structure, (B) a
functional genetic variant analysis of ubiquitin and ubiquitin ligase binding interaction, (C) a functional
genetic variant analysis of DNA binding in TATA binding protein, and (D) a drug class variant analysis of
compounds targeting the Bergerat ATP binding region of Hsp90 heat shock protein.

Machine learning analysis of impacts due to simple environmental temperature shift

We first ran a null comparison as a 'sanity check' by running a query and reference ubiquitin (11)
MD at the same temperatures (both 300K) and same solvent conditions. The DROIDS analysis (Figure 2A-
C) showed identical atom fluctuation profiles along the backbone and a random dFLUX profile indicative
of nonsignificant differences due to small random local thermal differences in the training sets. The
machine learning classification plots on new MD runs vary randomly around 0.5 reflecting the fact that
the learning algorithms had no features to train on (Figure 2D). As expected, no significantly conserved
dynamics were identified either (Figure 2E). By contrast, a protein dynamic comparison run with a 50K
temperature difference (Figure 2 F-H) shows a much higher machine learner performance upon
deployment (i.e. 70-80% successful classification – Figure 2I). Because environmental temperature shifts
are not expected to reflect evolutionary conserved dynamics (i.e. are not position dependent), they
subsequently do not result in canonical correlations in the learning profiles (Figure J). Representative
time slices of the positional classifications in each of these experiments are shown in K and L resp and
indicate that our machine learning is capable of extracting and identifying simple differences in
dynamics due to temperature. Another interesting observation here was the slightly higher learning
performance of the simpler machine learning methods QDA and LDA over others at all sites in the
temperature shifted example. We interpret this to be related to the fact that underlying rmsf
distributions are probably Gaussian, a critical assumption of these two models, with unequal variances
caused by steric hindrances on the backbone. This would predict that QDA might outperform other
learners in this situation and it appears that it does. We note that where more complex functional
dynamics are concerned, the more sophisticated learning methods such as support vector machine and
adaboost often perform slightly better than others. However, we also note that these performance
differences are usually quite small and that all learning methods generally come to similar local
conclusions about functional dynamics. We examine machine learning performance regarding more
functional binding dynamics in ubiquitin.

Machine learning analysis of impacts of genetic variants on a functional protein binding interaction

To examine functional dynamics in ubiquitin, we conducted a DROIDS analysis comparing its two
functional states, bound and unbound to the ubiquitin associated binding (UBA) domain of ubiquitin
ligase (12)(Figure 3A-D). This binding domain is highly conserved among the many other proteins that
interact directly with ubiquitin. The binding interaction greatly reduces the atom fluctuation in ubiquitin
at 3 characteristic positions, two loop structures centered at LEU 8 and ALA 46 and a portion of beta

sheet at the C terminus (Figure 3C). These three regions also drive significant differences in dynamics
across the whole protein. In novel self-similar MD runs on the bound state, we successfully detect
significant canonical correlations indicating conserved dynamics in these three regions with a broad
expanse in conserved dynamics (Figure 3E and F) across the UBA region (Figure 3G). We tested a set of
24 mutations that included sites with the most and least tolerated effects on growth rate in vivo in yeast
according to a study by Roscoe et al. (13). In this study in vivo, nearly all mutations at E18 and G53 are
tolerated while nearly all mutations at K48 and R72 are not. Ultimately, the causes of tolerance in these
variants are not known, and do not necessarily invoke functional problems in dynamics. However, the
impacts that we did observed in simulation were on average twice as strong in the intolerant
backgrounds when compared to the mutation tolerant backgrounds. And, while we did not see large
differences in the number of mutational impacts on dynamics between tolerated and non-tolerated
mutant groups, the 24 mutations analyzed all show a general trend of dynamic impact falling outside of
most of the functional binding region (Figure 3H-K), suggesting that ubiquitin may have evolved a
tertiary structure that allosterically translates dynamic impacts to less functional regions of the protein.
Some interesting exceptions to this rule were demonstrated by the very large impacts of K48L, K48W
and R72D, centered squarely in the functionally conserved binding regions of ubiquitin, and would
obviously heavily disrupt electrostatic charge interactions there as well.

Machine learning analysis of impacts of genetic variants on DNA binding interaction

TATA binding protein (TBP) is a general transcription factor that binds DNA upstream in most
highly regulated eukaryotic gene promoter regions (14). While relatively small, it is a mechanically
dynamic protein with a C-clamp like structure that highly distorts the rigid DNA double helix by inserting
four phenylalanine side-chains between base pairs. It is thought that this bending allows TBP to be more
rapidly released from the TATA element, as opposed to TATA-less promoters, subsequently allowing
more highly controlled regulatory responses in TATA box genes (15). Due to its obvious symmetry and
ability to impart large forces during binding, we thought that it would represent a good candidate for
comparison of its dynamics during its binding interaction with DNA. We conducted a DROIDS analysis
comparing human TBP (16) in its functionally bound and unbound states (Figure 4A-C). TBP exhibits a
characteristic large signature of dampening of atom fluctuation throughout its entire structure with
most pronounced effects in two loop regions that interact with the minor groove of DNA (arrows in
Figure 4A and 4C). Canonical correlations in new self-similar MD runs marking increased performance in
classification were observed in these regions (Figure 4D) along with corresponding regions of conserved
dynamics identified by significant Wilk's lamda (Figure 4E). Conserved dynamics from these loop areas
are connected through the chains in the beta sheet region of TBP spanning the DNA major groove
contact. Mutational impacts of four variants affecting the binding loop most proximal to the C terminal
exhibited followed our expectation of increasing impact ordering from R192Q, R192K, R192polyD, and
R192polyW (Figure 4G and 4H). The polyD and polyW mutations incorporated 5 sequential ASP or TRP
residues centered at R192, both causing the loop region to become more rigid (causing increased
negative dFLUX). We expected the strong functional binding affect observed across nearly all residues in
this system would make it relatively highly tolerant to single amino acid substitutions, even when
located in the most functional binding loop. In accordance with this idea, we found the most impactful
multiple mutation (i.e. R192polyW) significantly affected the dynamics of nearly 6 times more local
residues than the least impactful single substitution (i.e. R192Q).

Machine learning analysis of impacts of drug class variants targeting the ATP binding region of Hsp90

In contrast to TBP, we wanted to use our method to examine a small molecule binding
interaction in a protein with potentially more complex impacts on molecular dynamics. Hsp90 is a well-
known chaperone protein that assists the folding of many proteins and thereby mitigating many
environmental stresses in the cell. Hsp90 even capacitates the evolutionary process by allowing
potential phenotypic variation exhibited under stress to be hidden from natural selection until needed in
response to environmental change (17). Hsp90 contains a highly conserved N-terminal domain where
ATP binding and activation occurs. The binding of ATP physically changes motions in this region creating
a 'lid' that closed during ATP binding and open when conversion to ADP occurs. Due to the role of Hsp90
in stress mitigation in most tumors, it is a common drug target for ATP inhibitors in many cancer
therapies (18, 19). The amino acid residues that interact with ATP in this region are well known and the
inhibitor geldanamycin is known to mimic nearly all the local ATP contacts as well (20). Other more
modern inhibitors interact with the ATP binding pocket differently (19, 21, 22), so we thought that this
system would be a good candidate for comparative analysis of drug class variants.

We conducted a DROIDS analysis comparing the dynamics of Hsp90 chaperone, a common
drug target for inhibitors in many cancer therapies, in both its ATP bound and unbound states. The
binding of ATP was discovered to significantly destabilize three co-localized alpha helical regions of the
protein adjacent to and extending from the ATP binding site (Figure 5A-D). MaxDemon analysis
confirmed the dynamics of this region to be highly conserved in new MD runs (Figure 5D-G). We also
analyzed the impacts of the six drug class variants targeting the ATP site (20, 22, 21, 23, 24), but
interacting differently with residues in this region (Figure 5H). The contacts in the ATP binding site are
shown in Figure 5I. While the localized patterns of impacts of the drug variants were all quite similar to
ATP (Figure 5J), the drug variants that most closely mimicked the contacts of ATP (i.e. geldanamycin) had
far less impact on dynamics than variants that interacted very differently with the binding pocket (i.e.
benzamide SNX1321 and inhibitor FJ1(Figure H-I). We feel that this finding demonstrates that while it is
important to be able to target a druggable protein binding site (25), researchers should also consider
how these various chemicals might alter the natural dynamics of the system. In situations where a drug
might too closely mimic the dynamic effects of a natural activator like ATP, a hyperactivation response
might occur in non-tumor cells leading to secondary cancer (26–28). Alternatively, other situations may
require drug targeting that does not alter the natural dynamic behavior too much, potentially activating
proteolytic systems in the cell. Our software allows more detailed investigations of these potential
dynamic impacts of drug class variants.

Conclusion

We provide a well demonstrated method and user-friendly software pipeline for conducting statistically
sound comparative studies of large ensembles of comparative protein dynamics. The method/software
also now provides machine learning based extrapolations of effects on novel MD simulations
representing various functional variants of interest to the user. While there currently is at least one
other software allowing users to connect sequence-based evolutionary metrics to protein dynamics (29),
our method/software is unique in that regions of functional conservation are identified by analyzing
self-similar features of dynamics themselves rather than relying upon marrying dynamics to traditional
static sequence-based approaches, which do not necessarily assume that a protein function has a strong
dynamic component. By providing a systematic way of comparing protein dynamics at single residue

resolution, our method/software provides an important step beyond traditional bioinformatics, allowing
investigators to gain a much more biophysically-grounded view of functional and evolutionary change.
Another advantage to our method/software is that our functional impacts (i.e. mutational tolerance) are
defined solely within the context of protein dynamic system being simulated. This provides a much
deeper look into protein specific function than current genomic and proteomic database methods of
predicting mutational tolerance (30, 31) currently allow. As GPU technology continues to advance at a
rapid pace over the next few years, our method/software may have profound potential application to
the development of precision and personalized medicine, where understanding the detailed interaction
between genetic and drug class variants within the context of specific protein dynamic systems will be
greatly needed.

522 Supporting Material

The main repository for DROIDS 3.0 and maxDemon 1.0 can be found at the GitHub repository link
below. Please follow the link to "Releases" and download the latest release as .tar.gz or .zip file

https://github.com/gbabbitt/DROIDS-3.0-comparative-protein-dynamics

We also post various videos of examples using DROIDS, video tutorials, and ongoing projects here

https://www.youtube.com/channel/UCJTBqGq01pBCMDQikn566Kw

A 'live version' of the figures in this manuscript is also available on our YouTube channel.

530 Author Contribution

531 GAB and EPF conceived the project and method. All authors contributed to the code base. GAB and LEA
532 worked on beta testing and debugging.

534 Acknowledgements

535 We acknowledge the lab of Dr. Andre O. Hudson for beta testing our software during its early
536 development. We acknowledge Dr. Miranda Lynch and her colleagues at the Hauptman-Woodward
537 Medical Research Institute for many helpful comments.

539 References

1. Henzler-Wildman, K.A., M. Lei, V. Thai, S.J. Kerns, M. Karplus, and D. Kern. 2007. A hierarchy of
timescales in protein dynamics is linked to enzyme catalysis. Nature. 450: 913–916.

2. Niessen, K.A., M. Xu, A. Paciaroni, A. Orecchini, E.H. Snell, and A.G. Markelz. 2017. Moving in the
Right Direction: Protein Vibrations Steering Function. Biophys. J. 112: 933–942.

3. Babbitt, G.A., E.E. Coppola, M.A. Alawad, and A.O. Hudson. 2016. Can all heritable biology really be
reduced to a single dimension? Gene. 578: 162–168.

4. Götz, A.W., M.J. Williamson, D. Xu, D. Poole, S. Le Grand, and R.C. Walker. 2012. Routine
Microsecond Molecular Dynamics Simulations with AMBER on GPUs. 1. Generalized Born. J. Chem.
Theory Comput. 8: 1542–1555.

5. Salomon-Ferrer, R., A.W. Götz, D. Poole, S. Le Grand, and R.C. Walker. 2013. Routine Microsecond
Molecular Dynamics Simulations with AMBER on GPUs. 2. Explicit Solvent Particle Mesh Ewald. J.
Chem. Theory Comput. 9: 3878–3888.

6. Babbitt, G.A., J.S. Mortensen, E.E. Coppola, L.E. Adams, and J.K. Liao. 2018. DROIDS 1.20: A GUI-
Based Pipeline for GPU-Accelerated Comparative Protein Dynamics. Biophys. J. 114: 1009–1017.

7. Díaz, Ó., J.A.R. Dalton, and J. Giraldo. 2019. Artificial Intelligence: A Novel Approach for Drug
Discovery. Trends Pharmacol. Sci. .

8. Plante, A., D.M. Shore, G. Morra, G. Khelashvili, and H. Weinstein. 2019. A Machine Learning
Approach for the Discovery of Ligand-Specific Functional Mechanisms of GPCRs. Mol. Basel Switz.
24.

9. Terayama, K., H. Iwata, M. Araki, Y. Okuno, and K. Tsuda. 2018. Machine learning accelerates MD-
based binding pose prediction between ligands and proteins. Bioinforma. Oxf. Engl. 34: 770–778.

10. Maxwell, J.C. 2001. Theory of Heat. 9 Reprint edition. Mineola, NY: Dover Publications.

11. Vijay-Kumar, S., C.E. Bugg, and W.J. Cook. 1987. Structure of ubiquitin refined at 1.8 A
resolution. J. Mol. Biol. 194: 531–544.

12. Peschard, P., G. Kozlov, T. Lin, I.A. Mirza, A.M. Berghuis, S. Lipkowitz, M. Park, and K. Gehring.
2007. Structural basis for ubiquitin-mediated dimerization and activation of the ubiquitin protein
ligase Cbl-b. Mol. Cell. 27: 474–485.

13. Roscoe, B.P., K.M. Thayer, K.B. Zeldovich, D. Fushman, and D.N.A. Bolon. 2013. Analyses of the
effects of all ubiquitin point mutants on yeast growth rate. J. Mol. Biol. 425: 1363–1377.

14. Kornberg, R.D. 2007. The molecular basis of eukaryotic transcription. Proc. Natl. Acad. Sci. U. S.
A. 104: 12955–12961.

15. Tora, L., and H.T.M. Timmers. 2010. The TATA box regulates TATA-binding protein (TBP)
dynamics in vivo. Trends Biochem. Sci. 35: 309–314.

16. Nikolov, D.B., H. Chen, E.D. Halay, A. Hoffman, R.G. Roeder, and S.K. Burley. 1996. Crystal
structure of a human TATA box-binding protein/TATA element complex. Proc. Natl. Acad. Sci. U. S.
A. 93: 4862–4867.

17. Rutherford, S.L., and S. Lindquist. 1998. Hsp90 as a capacitor for morphological evolution.
Nature. 396: 336–342.

18.   Neckers, L., and P. Workman. 2012. Hsp90 Molecular Chaperone Inhibitors: Are We There Yet?
579   Clin. Cancer Res. 18: 64–76.

580   19.   Yuno, A., M.-J. Lee, S. Lee, Y. Tomita, D. Rekhtman, B. Moore, and J.B. Trepel. 2018. Clinical
581   Evaluation and Biomarker Profiling of Hsp90 Inhibitors. Methods Mol. Biol. Clifton NJ. 1709: 423–
582   441.

583   20.   Stebbins, C.E., A.A. Russo, C. Schneider, N. Rosen, F.U. Hartl, and N.P. Pavletich. 1997. Crystal
584   structure of an Hsp90-geldanamycin complex: targeting of a protein chaperone by an antitumor
585   agent. Cell. 89: 239–250.

586   21.   Immormino, R.M., Y. Kang, G. Chiosis, and D.T. Gewirth. 2006. Structural and quantum chemical
587   studies of 8-aryl-sulfanyl adenine class Hsp90 inhibitors. J. Med. Chem. 49: 4953–4960.

588   22.   Li, J., L. Sun, C. Xu, F. Yu, H. Zhou, Y. Zhao, J. Zhang, J. Cai, C. Mao, L. Tang, Y. Xu, and J. He. 2012.
589   Structure insights into mechanisms of ATP hydrolysis and the activation of human heat-shock
590   protein 90. Acta Biochim. Biophys. Sin. 44: 300–306.

591   23.   Fadden, P., K.H. Huang, J.M. Veal, P.M. Steed, A.F. Barabasz, B. Foley, M. Hu, J.M. Partridge, J.
592   Rice, A. Scott, L.G. Dubois, T.A. Freed, M.A.R. Silinski, T.E. Barta, P.F. Hughes, A. Ommen, W. Ma,
593   E.D. Smith, A.W. Spangenberg, J. Eaves, G.J. Hanson, L. Hinkley, M. Jenks, M. Lewis, J. Otto, G.J.
594   Pronk, K. Verleysen, T.A. Haystead, and S.E. Hall. 2010. Application of chemoproteomics to drug
595   discovery: identification of a clinical candidate targeting hsp90. Chem. Biol. 17: 686–694.

596   24.   Austin, C., S.N. Pettit, S.K. Magnolo, J. Sanvoisin, W. Chen, S.P. Wood, L.D. Freeman, R.J.
597   Pengelly, and D.E. Hughes. 2012. Fragment screening using capillary electrophoresis (CEfrag) for hit
598   identification of heat shock protein 90 ATPase inhibitors. J. Biomol. Screen. 17: 868–876.

599   25.   Vajda, S., D. Beglov, A.E. Wakefield, M. Egbert, and A. Whitty. 2018. Cryptic binding sites on
600   proteins: definition, detection, and druggability. Curr. Opin. Chem. Biol. 44: 1–8.

601   26.   Poulikakos, P.I., C. Zhang, G. Bollag, K.M. Shokat, and N. Rosen. 2010. RAF inhibitors
602   transactivate RAF dimers and ERK signalling in cells with wild-type BRAF. Nature. 464: 427–430.

603   27.   Hatzivassiliou, G., K. Song, I. Yen, B.J. Brandhuber, D.J. Anderson, R. Alvarado, M.J.C. Ludlam, D.
604   Stokoe, S.L. Gloor, G. Vigers, T. Morales, I. Aliagas, B. Liu, S. Sideris, K.P. Hoeflich, B.S. Jaiswal, S.
605   Seshagiri, H. Koeppen, M. Belvin, L.S. Friedman, and S. Malek. 2010. RAF inhibitors prime wild-type
606   RAF to activate the MAPK pathway and enhance growth. Nature. 464: 431–435.

607   28.   Cichowski, K., and P.A. Jänne. 2010. Drug discovery: inhibitors that activate. Nature. 464: 358–
608   359.

609   29.   Bakan, A., A. Dutta, W. Mao, Y. Liu, C. Chennubhotla, T.R. Lezon, and I. Bahar. 2014. Evol and
610   ProDy for bridging protein sequence evolution and structural dynamics. Bioinformatics. 30: 2681–
611   2683.

612   30.   Kumar, P., S. Henikoff, and P.C. Ng. 2009. Predicting the effects of coding non-synonymous
613   variants on protein function using the SIFT algorithm. Nat. Protoc. 4: 1073–1081.

614   31.   Adzhubei, I., D.M. Jordan, and S.R. Sunyaev. 2013. Predicting functional effect of human
615   missense mutations using PolyPhen-2. Curr. Protoc. Hum. Genet. Chapter 7: Unit7.20.

618   Table 1. Common learner assisted comparative protein dynamic investigations enabled by

619   DROIDS 3.0 + maxDemon 1.0.

QUESTION	DROIDS 3.0 training comparison	Deployment of learners in maxDemon	Important notes
Measure dynamic tolerances of single protein to various genetic mutations	Two sets (ensembles) of MD on the same protein at the same temperature	MD run on one or more genetic mutant structures	Isolates MD impacts of mutation(s) from natural variability in self-similar dynamics
Measure dynamic tolerances of DNA binding interaction to genetic mutation(s)	MD ensembles comparing both the unbound and DNA bound protein	MD run on one or more unbound genetic mutant structures	Isolates MD impacts of mutation from natural binding function of the system
Measure dynamic tolerances of individual genetic differences to a given drug	MD ensembles comparing both the unbound and drug bound protein	MD run on one or more drug-bound genetic mutant structures	Isolates MD impacts of mutation from novel drug binding function of the system
Measure dynamic similarities of different drug candidates to natural ligand binding interaction	MD ensembles comparing both the unbound and ligand bound protein	MD run on one or more drug variant bound structures	Isolates MD impacts of drug candidates from the natural binding function of the ligand
Measure evolution of novel dynamics in paralog genes	MD ensembles comparing two ortholog proteins (i.e. same gene different species)	MD runs on one or more paralogs (i.e. duplicated genes in same species)	Isolates potential MD novelty in duplicated gene product from nonfunctional or neutral changes in different species

624 Figures

Figure 1. Schematic overview of DROIDS 3.0 + maxDemon 1.0 software for machine learning-based detection of variant impacts on functionally conserved protein dynamics. The pipeline starts with (A) generation of two large ensembles of molecular dynamic (MD) simulations that represent a functional comparison of protein states (e.g. mutation, binding or environmental change). The root mean square fluctuations (rmsf) of protein backbone atoms in these ensembles are comparatively analyzed/visualized (i.e. using DROIDS) and are also later used as pre-classified training data sets for machine learning (i.e. using maxDemon). Note: in the pictured DROIDS analysis of nucleosome shows overall dampening of rmsf in the histone core with maximal dampening where the histone tails cross the DNA helix (B) New MD simulations are generated on two structures self-similar to the query state of training as well as a list of functional variants, and (C) up to seven machine learning methods are employed to classify the MD in the self-similar and variant runs according to the functional comparison defined by the initial training step. (D) The performance of learning is defined by average value of classification (i.e. 0 or 1) over 50 frame time slices for each amino acid position and regions of functionally conserved dynamics are later identified by significant canonical correlations in this learning efficiency (i.e. Wilk's lamda) in self-similar MD runs. The impacts of variants are defined by relative entropy of variant MD compared to the MD in the self-similar runs and plotted when this entropy is significantly different from the variation in self-similarity (i.e. bootstrapped z-test). (E) A visual representation of the difference in local rmsf (dFLUX) is typically calculated using symmetric Kullback-Leibler (KL) divergence between the two distributions of rmsf in the training MD ensembles.

Figure 2. Analysis of environmental temperature change on non-functional ubiquitin dynamics.
DROIDS image and analysis of random ubiquitin dynamics compared at the same (A-E) and different (F-J)
temperatures. Note: blue color quantifies damped rmsf at temperature lowered by 50K. Note that
performance is much higher when a temperature difference is modeled (D and I resp), however, as
expected, neither comparison offers the machine learners a sequence-dependent profile by which to
establish a signal of conserved dynamics (E or J).   The learner classifications for the best performing
learner in this case (quadratic discriminant function: QDA) is shown imaged on the ubiquitin structure
over time in both the (K) random dynamics and (L) temperature dampened dynamics. (Movies of this
can be observed in supplemental file A)

Figure 3. Analysis of mutational impact and tolerance on functional ubiquitin dynamics. (A) DROIDS image and analysis of ubiquitin bound to the ubiquitin associated binding domain (UBA) of ubiquitin ligase. Note: blue color quantifies damped rmsf at binding interface. (i.e. negative dFLUX) also by the (B) respective rmsf profiles of bound and unbound training states and (C) the KL divergence or dFLUX profile colored by residue. Arrows indicate most prominent dampening of rmsf near loops at THR 9, ALA 46 and C terminus. (D) Significant differences in these rmsf profiles is determined by multiple-test corrected two sample KS test. (E) Local learning performance of each machine learning method in self-similar testing runs are shown color-coded by run and regions of functionally conserved dynamics, determined via significant local canonical correlation are shown in dark gray in both (F) traditional N to C terminal plot as well as (G) structural image. The mutational impacts of 24 genetic variants (H-K: six variants at each or four sites) are shown all demonstrating lack of impact in functionally conserved regions of the binding interaction.

Figure 4. Analysis of mutational impact and tolerance on DNA binding in Tata Binding Protein (TBP).
DROIDS image and analysis of TBP in DNA-bound and unbound states showing (A) colored TBP structure,
(B) respective rmsf profiles and (C) KL divergence (dFLUX) plot. Note: arrows indicate functional binding
loops in the DNA minor groove red color indicates dampened rmsf. maxDemon analysis (D-E) identifying
conserved dynamics supporting both minor groove binding loops and (F) connecting them through the
central region of the beta sheet in the main body of TBP closest to the DNA.   Mutational impacts of 4
genetic variants with increasing impact one of the functional loops are also shown (G) plotted and (H) on
the TBP structure. They are R192K, R192D, R192Q and polyW centered at R192 in 1cdw.pdb and and
position 161 (red arrow) in plots (Note: 31 position offset is due to DNA in the original file).

I — Ligand contacts of drug binding variants on protein dynamics of Hsp90 in the ATP binding pocket

ligand	PDB	% sim	Val 186	Thr 184	Trp 162	Tyr 139	Phe 138	Lys 112	Alal 111	Leu 107	Asn 106	Asp 102	Met 98	Gly 97	Ile 96	Asp 93	Lys 58	Ala 55	Asp 54	Asn 51
ATP	3t0z	100	x				x				x		x	x		x		x		x
Geldanamycin	1yet	87.5		x			x	x			x			x		x		x		x
Inhibitor PU-H64	2fwy	75		x	x		x			x			x			x		x		x
Inhibitor PU-DZ8	2h55	75		x	x		x			x			x		x	x	x	x		x
Radicicol	4egk	62.5	x	x			x			x						x	x	x	x	x
Benzamide SNX-1321	3mnr	37.5		x	x	x				x		x			x	x	x	x		
Inhibitor FJ1	4hy6	0			x	x			x											

J — Impacts of drug binding variants on protein dynamics of Hsp90 that are significantly different than binding to ATP

Figure 5. Analysis of drug class variant binding in the ATP-binding domain of Hsp90. DROIDS image and analysis of Hsp90 in ATP-bound and unbound states showing (A) colored Hsp90 structure, (B) respective rmsf profiles and (C) KL divergence (dFLUX) plot and (D) significant differences in dynamics determined via the KS test. Note: arrows and green color indicate regions where rmsf is amplified in response to ATP binding. maxDemon analysis (E-G) identifying conserved dynamics connecting the ATP binding pocket and region of amplified rmsf. (H) Mutational impacts of 6 drug class variants targeting the ATP binding pocket of Hsp90 are plotted and (I) ordered by number of differences in structural contacts within the binding pocket. (J) Mutational impacts of these variants are demonstrated to predominantly impact the functionally conserved region of amplified rmsf thus mimicking the dynamic effect of functional ATP binding.