Title:

NeuroGPU: Accelerating multi-compartment, biophysically detailed neuron simulations on GPUs

Authors:

Roy Ben-Shalom[1,2], Nikhil S. Artherya[3], Alexander Ladd[3], Christopher Cross[1], Hersh Sanghevi[3],Kyung Geun Kim[3], Alon Korngreen[4,5], Kristofer E. Bouchard[6,7], Kevin J. Bender[1,2].

Affiliations:

1. Weill Institute for Neurosciences, Kavli Institute for Fundamental Neuroscience University of California, San Francisco, San Francisco CA, USA
2. Department of Neurology, University of California, San Francisco, San Francisco, CA, USA
3. Department of Electrical Engineering and Computer Science, University of California, Berkeley, Berkeley CA, USA
4. The Leslie and Susan Gonda Multidisciplinary Brain Research Center, Bar-Ilan University, Ramat-Gan Israel
5. The Mina and Everard Goodman Faculty of Life Sciences, Bar-Ilan University, Ramat-Gan Israel
6. Biological Systems and Engineering & Computational Research Divisions, Lawrence Berkeley National Lab, Berkeley, CA
7. Helen Wills Neuroscience Institute & Redwood Center for Theoretical Neuroscience, University of California, Berkeley, Berkeley, CA

Correspondence: roy.benshalom@ucsf.edu

Abstract:

The membrane potential of individual neurons depends on a large number of interacting biophysical processes operating on spatial-temporal scales spanning several orders of magnitude. The multi-scale nature of these processes dictates that accurate prediction of membrane potentials in specific neurons requires utilization of detailed simulations. Unfortunately, constraining parameters within biologically detailed neuron models can be difficult, leading to poor model fits. This obstacle can be overcome partially by numerical optimization or detailed exploration of parameter space. However, these processes, which currently rely on central processing unit (CPU) computation, often incur exponential increases in computing time for marginal improvements in model behavior. As a result, model quality is often compromised to accommodate compute resources. Here, we present a simulation environment, NeuroGPU, that takes advantage of the inherent parallelized structure of graphics processing unit (GPU) to accelerate neuronal simulation. NeuroGPU can simulate most of biologically detailed models 800x faster than traditional simulators when using multiple GPU cores, and even 10-200 times faster when implemented on relatively inexpensive GPU systems. We demonstrate the power of NeuoGPU through large-scale parameter exploration to reveal the response landscape of a neuron. Finally, we accelerate numerical optimization of biophysically detailed neuron models to achieve highly accurate fitting of models to simulation and experimental data. Thus, NeuroGPU enables the rapid simulation of multi-compartment, biophysically detailed neuron models on commonly used computing systems accessible by many scientists.

Introduction:

Electrical activity of single neurons is determined by the distribution of various ionic conductances arranged across complex morphologies (Mainen and Sejnowski, 1996a; Hausser et al., 2000; London and Häusser, 2005; Spruston, 2008; Hay et al., 2013; Alonso and Marder, 2019). Our understanding of single neurons has long relied on the ability to construct biophysically rigorous models of how neuronal membrane potential [Vm], and, hence, action potentials (APs, spikes) are generated from currents [I] flowing across the membrane and through the cell (Fig. 1) (Hodgkin and Huxley, 1952). Wilfrid Rall described the biophysical theory of how membrane potential of a single neuronal segment ('compartment') depends on the conductance (e.g., gNa) and voltage dependent flow of specific ionic species [e.g., sodium (Na) and potassium (K)], as well as passive properties of the membrane (i.e., capacitance) (Fig.1, top row) (Rall, 1962a). Using cable theory, Rall further described how to connect different compartments of a neuron, providing the foundation for modeling complex, spatially extended neuronal morphologies (Fig.1A) (Rall, 1962b). Concomitantly, the membrane channels that mediate a specific ionic current exhibits large diversity of genetically defined conductances (e.g., gNav1.2, gNav1.6, etc.,), indicating that individual compartments are, in reality, quite complex (Fig.1B). While just beginning to be appreciated at the time, we now know that ion channels have their own voltage dependent kinetics that are determined by the transition probabilities amongst various states of the channel subunits (Fig.1C) (Hille, 1984; Colquhoun and Hawkes, 1995). Finally, simulations of realistic neural network models require faithfully capturing the complexity of the individual neurons (Einevoll, et al., 2019). While the physical theories required to link these vastly disparate spatial-temporal scales exists, our ability to utilize them for basic understanding and clinical translation is impeded by the computational burden of the required simulations (Fig.1D, E).

Our predictive understanding of several neuronal cell classes has benefitted from the repeated refinement of compartmental models that describe their activity in health and disease. For example, neocortical pyramidal cells have been modeled extensively, providing insight into the effects of morphology on AP firing characteristics (Mainen and Sejnowski, 1996b; Hay et al., 2011; Almog and Korngreen, 2014), how synaptic input patterns affect spike output (Maršálek et al., 1997; Dlesmann et al., 1999; Destexhe et al., 2003) how APs initiate and propagate within axons (Kole et al., 2007, 2008; Shu et al., 2007; Hu et al., 2009; Hallermann et al., 2012; Cohen et al., 2020), and how neuronal activity is affected by alterations in ion channel function induced by genetic variation (Zamponi et al., 2010; Allen et al., 2014; Ben-Shalom et al., 2017; Spratt et al., 2019). Similar intensive studies have focused on other cell classes, including hippocampal

pyramidal cells (Mainen et al., 1996; Magee and Cook, 2000; Poirazi et al., 2003; Narayanan and

Johnston, 2008; Milstein et al., 2015)), cerebellar Purkinje cells (De Schutter and Bower, 1994;

Miyasho et al., 2001; Roth and Häusser, 2001), and midbrain dopaminergic neurons (Canavier,

1999; Canavier and Landry, 2006; Kuznetsova et al., 2010). In parallel with these advances in

modeling, there has recently been an enormous improvement in experimental approaches to

better understand the diversity of neuronal classes and their activity patterns. Within the general

group of neocortical pyramidal cells, for example, exists a wealth of diversity. This includes not

only differences in morphology and activity across laminae (Smith and Häusser, 2010; Deitcher

et al., 2017; Kanari et al., 2019), but also within laminae depending on genetic makeup or axonal

projection targets (Dembrow et al., 2010; Gee et al., 2012; Clarkson et al., 2017), or even within

what was thought to be a homogenous cell class within a single layer as one samples across a

large region of cortex (Fletcher and Williams, 2019).

Given the enormous complexity and vast spatio-temporal scales described above,

generating models that accurately recapitulate neuronal activity across the true range of diversity

present in nature can be a daunting task. Model fitting often requires one to tune individual

parameters to best match empirical observations. This process can be aided by iterative rounds

of parameter exploration and optimization that aim to minimize the differences between empirical

data targets and their associated models. These procedures can be computationally demanding

(Fig.1D-E). Indeed, each linear improvement in model accuracy requires an exponential increase

in computational resources (Nocedal and Wright, 2006; Gurkiewicz and Korngreen, 2007). Thus,

model optimization is often done on supercomputers that parallelize these computations across

massive number of central processing unit (CPU) cores. Unfortunately, the cost of constructing

and operating supercomputing centers is similarly massive. As such utilization of these resources

are typically restricted to large consortia, such as the Blue Brain Project (BBP) (Markram et al.,

2015) and the Allen Institute (Gouwens et al., 2018). For more restricted budgets, simulations

must typically be compromised in scale, complexity, or accuracy, thus negatively impacting results

(Almog and Korngreen, 2016).

In the past 10 years, graphics processing units (GPUs) have emerged as an alternative to

CPU-based hardware that may offer comparable levels of performance at substantially reduced

cost for some problems. GPUs utilize streaming multiprocessors with multiple simple cores that

allow for distributed, parallelized computing for relatively small chunks of data. With software

optimized GPUs, GPU-based computing can often outperform CPU-based applications in

processing speed and cost for some problems (Payne et al., 2010). Today, GPUs are being used

in scientific simulations, including molecular dynamics (Go et al., 2012; Salomon-Ferrer et al.,
2013) and climate modeling (Prein et al., 2015), and are the computational engine for most
modern artificial intelligence applications (Schmidhuber, 2015). In neuroscience, GPUs are
currently being used to accelerate complex imaging dataset processing (Eklund et al., 2013),
spiking neural network analysis (Fidjeland and Shanahan, 2010), clustering of activity from *in vivo*
extracellular electrophysiological experiments (Pachitariu et al., 2016), and simulations of single
ion channels (Ben-Shalom et al., 2012). Recently two platforms for neuronal biophysical
simulations with GPU support were developed: Arbor (Akar et al., 2019) and CoreNeuron
(Kumbhar et al., 2019). Both platforms focused on simulating large scale neuronal networks
comprised of detailed multi-compartmental models. Each approach has unique advantages and
disadvantages. For example, CoreNeuron supports previous NEURON models, but is not
implemented in CUDA, the fundamental operating language of NVIDIA's GPUs. As such, its ability
to accelerate model runtimes with GPUs is relatively modest. Arbor, instead, is implemented in
CUDA via an entirely new simulation environment. Thus, while it does harness the speedup
potential of GPUs, it is not clear how existing models, such as those found in ModelDB and the
BBP portal (McDougal et al., 2015; Ramaswamy et al., 2015), could be ported to Arbor, thus
impeding utilization.

Here, we describe NeuroGPU, a computational platform optimized to exploit GPU
architecture to dramatically accelerate simulation of mutli-compartmental neuronal models. Our
goal with NeuroGPU was different than that of CoreNeuron or Arbor. Rather than focusing on
neuronal network simulations, NeuroGPU is designed to optimize fitting of models that best
recapitulate empirical data derived from single neurons. To do so, we developed new approaches
to parallelize compartmental models, utilizing the GPU-based programming language CUDA to
optimize memory handling on GPUs. This resulted in simulation speedups of up to 200-fold on a
single GPU and up to 800-fold using a set of 4 GPUs. Building on our previous efforts (Ben-
Shalom et al., 2013), we developed an intuitive user interface that can import most compartmental
models implemented in NEURON (Carnevale and Hines, 2006) deposited at the ModelDB
(McDougal et al., 2017) or BBP portal (Ramaswamy et al., 2015). Further, we provide methods
to explore model parameter space to study how each parameter of the model contributes to its
voltage output. The runtimes of NeuroGPU enables us to sample the parameter space in a very
detailed manner, which were utilized here to reveal the response landscape of single neurons.
Finally, we provide an interface to use NeuroGPU for fitting models to experimental data with
evolutionary algorithms (DEAP and BluePyOpt) (Gagn, 2012; Van Geit et al., 2016). NeuroGPU

implemented such model optimization algorithms in minutes, rather than days, which had been

the previous benchmark (Hay et al., 2011; Almog and Korngreen, 2014). This enables the use of

more complex models that will better represent experimental data, as we demonstrate here in

both simulated and experimental data. NeuroGPU therefore provides an open-source platform for

neuronal simulation with increased speed and reduced cost, thus enabling the neuroscience

community to perform high quality biophysically detailed simulations.

Methods:

Hardware — NEURON and TitanXP-based simulations were run on a PC with Intel Core I7-7700K 4.2GHz with 16GB of RAM. Tesla V100-based simulations were run using the NVIDIA PSG cluster. Here, each simulation was run on a single node with Haswell or Skylake CPU cores. For multi-GPU simulations, we used cluster nodes with NVLINK (Li et al., 2019) between the GPUs to enable memory peer-access. Fitting models to experimental data was done on the Cori GPU cluster from the National Energy Research Scientific Computing Cent (NERSC) at Lawrence Berkeley National Labs. Cori GPU nodes includes 8 NVIDIA Tesla V100 and 20 Skylake CPU cores with total of 384GB memory.

Software — Simulations were performed in NEURON 7.6 and CUDA 10.1. All scripts were written in Python 3.7. All software is available at https://github.com/roybens/NeuroGPU.

Importing NEURON models — The python script extractmodel.py exports NEURON models to NeuroGPU. This script reads all simulation details from runModel.hoc, which is populated using the GUI (Fig. S1). NEURON models are described using either hoc or python scripts. The scripts include a morphology that can either be called as a separate file or constructed within the script (Fig S1B). The user must input a file containing model stimulation, which includes temporal aspects of the model and command currents delivered at a prescribed location. Furthermore, all free parameters, such as channel properties, must be described. These import components are translated into CUDA code, termed kernels, that can run on the GPU via the python script "extractmodel.py" (Fig S1C). This script first takes runModel.hoc and loads it into NEURON, not to run simulations, but rather to query NEURON for model properties needed for subsequent porting to NeuroGPU, including compartment names and the tri-diagonal matrix (F-Matrix or Hines Matrix) which holds the differential system for the voltages of the dendritic tree. Then, the script iterates over the .mod files in the directory, parses them and creates relevant kernels for each mechanism described. Mechanism kernels are written to the AllModels.cu in similar structure as described previously (Hines and Carnevale, 2000; Carnevale and Hines, 2006), iterating over all compartments defined in the model. A new hoc file is created to register mechanism values, which are stored in AllParams.csv and inserted in each compartment. After model parameter maps are determined, they are cataloged as part of ParamMappings.txt for reference for future reiterations of the same model, eliminating the need to reload NEURON. Finally, the script writes code translated to CUDA in NeuroGPU.cu and packages the application to run on either Windows or Unix. After compiling the code, an executable is created that reads the AllParams.csv and the stimulation and runs the model on the GPU.

Translating mechanisms to CUDA and memory assignment — Mechanisms in NEURON are
described by NMODL (.mod) files (Hines and Carnevale, 2000), which update the mechanism
states every simulation time step. This is done using three different procedures within NEURON
that initialize mechanisms (nrn_init), update currents that mechanisms affect (nrn_cur), and then
update mechanism states (nrn_state) (Carnevale and Hines, 2006). In NeuroGPU, CUDA kernels
are written for each of these procedures using .mod and .c files that are generated by NEURON
when running nrnivmodl. Kernels are saved and editable in AllModels.cu and AllModels.h.

CUDA is an extension of the C programming language that enables computation on the
GPU (Nvidia, 2018). CUDA kernels are procedures running on the GPU that can be invoked from
either the GPU or CPU. To invoke a kernel from the CPU, one must specify the number of parallel
threads used. Threads, which allow for parallelization on the GPU, are organized into blocks, with
each thread occupying a specific address within that block (idx.x) (Fig S2 C). GPUs are structured
to operate well when computing 32 parallel threads, a computing structure termed a warp (Nvidia,
2018). Therefore, we structured NeuroGPU to utilize 32 threads in the x dimension, corresponding
to individual morphological segments within the model. For a given model with more than 32
segments, individual threads are responsible for calculating every 32^{nd} segment. For example,
thread #1 would calculate segments 1, 33, 65, … 31N+1.

Complex neuronal models, including many described in the BBP portal, are memory
intensive (Hay et al., 2013; Ramaswamy et al., 2015). GPUs have several forms of memory that
have tradeoffs in terms of their size and relative speed that make them ideal for certain aspects
of model processing and impractical for others. GLOBAL memory is the largest physical memory
space available on the GPU but is relatively slow. Here, we use GLOBAL memory to store the
largest data structures associated with a given model, in part because they simply cannot be held
by other memory structures. SHARED memory is far faster, shared among the whole GPU block,
but limited to 48 kilobytes. This makes it ideal for storing the tridiagonal matrix, as this matrix is
the most accessed data structure within NeuroGPU. CONSTANT memory, which is a 64 kilobyte
block of fast, read-only memory, is used to hold constant data structures, including the order in
which the tri-diagonal matrix is solved in parallel (Ben-Shalom et al., 2013). Lastly,
REGISTER\LOCAL memory is the fastest memory available on the GPU but is limited to
maximum of 63 registers per thread and a total of 16 kilobytes of memory shared across the entire
block. It is used to store local variables necessary for the course of the simulation (Fig. S2C).

Extracting simulation properties from NEURON — NeuroGPU utilizes NEURON for simulation
pre-processing, including mechanism translation (which includes mathematical descriptions of
various ion channels, calcium diffusion characteristics, and other elements of neuronal function,
(Hines and Carnevale, 2000), a map for mechanism distribution across compartments
(ParamMappings.txt), and exporting the tri-diagonal matrix using fmatrix(). These are stored in
BasicConstSegP.csv. NEURON extracts all parameters for cable equations and mechanism
values within each compartment to AllParams.csv (Fig. S1). External stimulation delivery location,
intensity, and timecourse are written in stim.csv. Resting membrane potential and number of time
steps in the simulation are written in sim.csv.

Solving the tridiagonal matrix — Matrix solutions were performed using the branch-based
parallelism approach as described previously (Ben-Shalom et al., 2013), with morphology
analysis guiding iterative matrix computations. This analysis is done in extractmodel.py and the
data structures to solve the tri-diagonal in parallel is stored in BasicConstSegP.csv.

Benchmarking — All benchmarking was done compared to NEURON 7.6 running in a single
thread. The morphology was adjusted to have one segment per compartment in both NEURON
and NeuroGPU comparison. Simulation runtimes were compared without hard drive read/write
file steps, as these aspects depend more on hard drive properties than CPU/GPU comparisons.

Multi-compartmental models — NeuroGPU performance was tested with 4 different models:
1) A passive model, utilizing passive channels described in NEURON distribution pas.mod file.
These channels were distributed on both simple and complex morphologies (see Fig. S3A, D)
(Mainen and Sejnowski, 1996b). The simple morphology was based on the simple morphology
described in Mainen and Sejnowski, with compartments reduced to 32, as this is the minimum
number of compartments required for NeuroGPU-based simulations.
2) The Mainen and Sejnowski (1996) model, with channels distributed on the same complex and
simple morphologies. Channels are distributed as in (Mainen and Sejnowski, 1996b) (Fig. S4)
3) A pyramidal cell model from the Blue Brain Project portal (Ramaswamy et al., 2015) (Fig. 2).
BBP_PC refers to the model named L5_TTPC1_cADpyr232_1.
4) A chandelier cell model, termed BBP_CC, referring to L5_ChC_dNAC222_1. For this model,
the Kdshu2007.mod files were altered to run on NeuroGPU. Specifically, global variables were
removed from the neuron block and instead placed in the assigned block (Carnevale and
Hines, 2006) (Fig. 2).

Optimization algorithms — Two different genetic algorithm versions were used in this study.
For data related to Figure 4, the *eaMuPlusLambda* algorithm from the DEAP package was
implemented by modifying the varOR procedure to call NeuroGPU (Rainville et al., 2012).
Optimization was performed on the BBP_PC model. For each iteration, the algorithm began with
a new population of parameters with values randomly chosen with the range specified in Table 1.
The model was modified to accept new values from the optimization algorithm (similar changes
were necessary for parameter space exploration for Figure 3). Target data were generated using
the original parameters values described in Table 1. Optimization was targeted to reduce error
between target data and test data using both the interspike interval (ISI) and the root mean square
(RMS) of the voltage as the error function. Error was reduced to a single variable by weighting
these two variables as: 10*ISI + RMS.

For data related to Figure 5, the BluePyOpt (Van Geit et al., 2016) implementation of
Multiple Objective Optimization (MOO) was used. Experimental target data for these experiments
were from whole-cell current-clamp recordings from layer 5b thick tufted pyramidal cells in acute
slices from wild-type mouse prefrontal cortex (postnatal day 62) (Spratt et al., 2019). Optimization
was targeted to minimize the root mean square voltage error at each time point between empirical
data and model output as well as the following objectives, as defined in the electrophysiology
feature extraction library (eFEL) from the BBP (Moor et al., 2015): voltage_base, AP_amplitude,
voltage_after_stim, ISI_values, spike_half_width, and afterhyperpolarization_depth.
Electrophysiological data were fitted in models with morphology from L5_TTPC1_cADpyr232 Fig
(5A) or a reconstructed prefrontal cortex L5 thick tufted pyramidal neuron deposited at
neuroMorpho.org (Ascoli et al., 2007; Yin et al., 2018). The model parameters that were varied
for the S1 model and PFC model are described in Table 2 &3 respectively.

Profiling — To better understand why NeuroGPU accelerated some models more than others,
we used the NVIDIA profiler to monitor GPU utilization. Further, we tested two different memory
handling configurations to determine how best to utilize GPU parallel processing. In both cases,
the GPU is responsible for updating ionic currents from established mechanisms, solving the
tridiagonal matrix, and updating model states and voltages at each time step. In the first
configuration, termed SingleKernel, we computed all the time steps of each simulation in one
kernel on the GPU, largely because this would limit the amount of time performing the relatively
slow step of transferring memory between the GPU and CPU. In this case, the transfer is done
only once and during the simulation the GPU communicates with the CPU only to transfer voltages
reported at the recording electrode site. Alternatively, we also created a SplitKernel condition, in

which the simulation is split into many small kernels that are invoked every single time step. Data

are then registered back to the CPU and the next time step is run in serial. This approach may be

advantageous if memory transfer between the GPU and CPU is not the rate-limiting step.

Furthermore, in this case the GPU can also optimize computing timing by queueing certain steps

for execution while other memory is being transferred. We found that configuring NeuroGPU in

SingleKernel mode produced the fastest runtimes in all models tested (Table 4), and had higher

GPU utilization levels. This indicates that, for most models, memory transfer between GPU and

CPU is rate-limiting, and models run most efficiently when the majority of calculations are isolated

on the GPU. Nevertheless, the highest utilization values were ~10% in the SingleKernel

configuration (3.8% in SplitKernel), suggesting that additional memory optimizations could be

leveraged in future iterations of NeuroGPU.

Results:

Our goal for NeuroGPU was to develop user-friendly software for fitting compartmental
models to experimental data, with improved speed, using relatively low-cost hardware.
Furthermore, we sought to make NeuroGPU cross-compatible with NEURON, to allow one to
import models available on public databases, including ModelDB and the BBP portal. Toward that
end, we utilized the same basic structure as NEURON, including the use of *hoc* and *mod* files
that define all aspects of the compartmental model (Fig. S1). To increase simulation speed, we
focused primarily on parallelizing the most computationally intensive aspects of NEURON
simulations in GPU architecture. NEURON calculates the voltages of each segment of the model
by solving a system of differential equations that describes current flow in each compartment.
Within NEURON, this system of differential equations is represented within a tri-diagonal matrix
(Hines, 1984). Typically, matrix elements for neighboring compartments are solved in serial, as
current flow in one compartment is interdependent on flow in neighboring compartments. We and
others have previously developed methods to solve this tri-diagonal matrix in parallel across
GPUs, despite the interdependence of current flow across compartments (Fig. S2) (Hines, 1984;
Hines et al., 2008; Ben-Shalom et al., 2013). At that time, the method was implemented only for
classic Hodgkin-Huxley models with 3 parameters (gNa, gK, gLeak) (Ben-Shalom et al., 2013).
Here, we extended this method to support a wider range of models, including most models
available in ModelDB and the Blue Brain Project (BBP) repository. We implemented this in Python
and created an iPython Graphical User Interface (GUI) for easy use.

NeuroGPU Performance

To evaluate how NeuroGPU performs relative to NEURON, we benchmarked it for speed
and accuracy across different conditions, including CUDA implementation, hardware
configurations, and across a range of models. We first compared NeuroGPU performance with a
single GPU to NEURON implemented on a single CPU core. To benchmark speed, we evaluated
computing time for multiple instances of the same model. NeuroGPU was primarily evaluated on
recently developed models from the Blue Brain Project (BBP) portal (Hay et al., 2011; Markram
et al., 2015; Ramaswamy et al., 2015), but was also benchmarked on models with reduced
morphology or reduced numbers of voltage-gated channels or ligand-gated receptors to
determine how each of these aspects affects performance (Figs. S3-4). For BBP models, we

focused on two specific models: a layer 5 pyramidal neuron (Fig.2, top row: BBP_PC, see
Methods for specific model) and a layer 5 chandelier interneuron (Fig.2, bottom row: BBP_CC).
Models were interrogated with a range of stimulus intensities to determine relative differences
between NeuroGPU and NEURON (Fig. 2).

We first confirmed the quality of the simulations. Overall, NeuroGPU was able to replicate
NEURON simulations with high fidelity; however, small voltage differences were observed
between the two platforms in all models tested. These were most commonly observed when
voltage was changing rapidly between time steps (Fig. 2B-C, G-H), and were due to small
differences in timing that likely arise from different approaches to number rounding in GPUs vs
CPU architecture (Whitehead, 2011).

NEURON computation time scales linearly with the number of simulations, and, for
relatively small numbers of models (< 8), outperforms NeuroGPU (Fig.2, D,E,I,J). By contrast,
models implemented on GPUs scale linearly only after saturating all of the GPUs streaming
multiprocessors (Nvidia, 2018) (Fig.2, D,E,I,J). With NeuroGPU, processing times are quite
similar for any simulation incorporating fewer than 128 models, and begin to outpace NEURON
simulations when >8 simulations are run simultaneously. Relative gains in processing time were
noted when 8 to 16,384 models were run simultaneously. These gains were dependent on
hardware (Fig.2, E,I). For example, implementing NeuroGPU on an NVIDIA TitanXP GPU
resulted in 46.6-fold improvements in processing speed, while the same models run on an NVIDIA
Tesla V100 were 205.6-fold faster. It is worth noting that TitanXP hardware is relatively low cost
(<\$1099) and a very similar card (NVIDIA GTX-1080) can currently be purchased for less than
\$500. As such, significant improvements in processing speed can be obtained even with modestly
priced hardware. Additional returns can be gained from GPU tethering, as CUDA has been
recently updated to allow for memory sharing across GPUs. To evaluate this, we connected up
to 4 Tesla V100 GPUs together and measured speedup on both BBP models displayed in Figure
2. As expected, adding more GPUs increased the overall processing capacity, and we noted shifts
in the number of models that could be handled simultaneously before reaching maximum GPU
utilization (Fig. 2E, J). Furthermore, speedup was almost 3 orders of magnitude faster relative to
NEURON.

Exploring neuronal model parameter space

Parameter values (e.g. ion channels distributions) are correlated in a non-linear manner. This may
lead to situations where vastly different parameter combinations nevertheless produce similar
voltage outputs, at least for a limited set of stimuli (Prinz et al., 2004). The diversity of these
parameter sets can be limited by constraining the range over which a parameter can vary before
initiating model optimization, thus leading to more biologically realistic sets of parameters.
NeuroGPU may be ideal for parameter exploration within such ranges, as these types of
simulations require one to repeatedly model the same morphology with small differences in
constituent parameter values, a process that lends itself well to parallelization within GPUs.
Indeed, we predict that relative speedups would be identical to situations considered above (Fig.
2) and depend simply on the number of parameter sets used. To provide an example of parameter
space exploration, we examined neuronal output (i.e., number of action potentials) in the BBP_PC
model when co-varying the density of the axonal fast inactivating sodium channel and axonal
slow-inactivating potassium channel over a range of 0 to 10 and 0 to 20 S/cm^2, respectively.
Single traces from with different sodium and potassium conductances are shown in Figure 3A
and total spike output as function of these two channel densities is shown in Figure 3B. As
expected, increasing sodium conductance allowed models to generate more APs until sodium
conductance was so high that models entered depolarization block. Similarly, reducing potassium
conductance produced comparable results. Interestingly, certain combinations of sodium and
potassium conductance concentrations produced bursting phenotypes characterized by high-
frequency APs riding atop long-duration depolarizations. These presumably reflect parameter
ranges that then interact with other ion channels in the model (e.g., Ca_V3 of HCN channels) that
promote such burst dynamics.

Fitting models to surrogate and empirical data

With the ability to rapidly sample parameter space, NeuroGPU may be ideally suited to
accelerate model fitting to data, where a key constraint is the time needed to exhaustively sample
possible solutions. To test this, we implemented two different genetic optimization algorithms
within NeuroGPU. Initially we integrated the DEAP (Distributed Evolutionary Algorithms in Python)
package (Gagn, 2012) (Fig. 4). Genetic algorithm success lies in the balance between exploration
of the whole parameter space and the exploitation of specific areas that seem promising. For this,

large sample populations are ideal, as this allows for effective and broad parameter space

exploration. NeuroGPU is more efficient when many instances are running in parallel, allowing for

more effective application of genetic algorithms.

Genetic optimization was tested here by fitting model-generated voltages to a single

voltage epoch containing APs that was generated by the default values present in the BBP_PC

model. We focused first on such surrogate data, as the ground truth values for all parameters are

already known. As such, we can easily compare how well NeuroGPU performs in arriving at

similar values. Optimization began with different population sizes comprised of 100 to 10,000

individual parameter sets with random initial values (Fig. 4B). These populations were run in four

independent trials, each for 50 generations, and the difference between the naïve model and

ground-truth model was compressed to a single score value (see Methods). For these scores,

lower values indicate less difference between the two cases.

Scores improved for each of these populations, but the variance across trials and the

overall score were markedly affected by the population size, with score decreasing in a near-

linear fashion with each doubling of population size (Fig. 4C). These score improvements were

paralleled by a decrease in total processing time. For example, optimization with 10,000 individual

parameter sets ran 7.7x faster on NeuroGPU than NEURON (Fig. 4D; 10 vs 77 hours,

respectively). While these are significant improvements in simulation speed, they are relatively

modest compared to those observed in other conditions (Fig. 2), likely since the version of

NeuroGPU used here required NEURON to load the simulation and generate parameter values.

In the next section we present how eliminating calls to NEURON greatly increases speedup.

Given these promising results fitting surrogate data, we next asked whether similar

performance could be noted for empirical electrophysiological data. Therefore, we fitted the BBP

PC model to whole-cell current-clamp recordings of action potential activity from neurons in acute

mouse frontal cortex slices (Fig. 5A black traces). Models were implemented on two different

pyramidal cell morphologies from somatosensory (original BBP PC morphology; Fig. 5A) and

prefrontal cortex [from neuroMorpho.org; Fig. 5B (Ascoli et al., 2007; Yin et al., 2018)] to

determine whether morphology differentially affects optimization. We fitted the model to eight

voltage responses from varying stimulations to verify that the model is robust across stimulation

conditions (Fig. 5A, B). The optimization algorithm found values for the model's parameters that

resulted with good fits to both morphologies. Thus, models can be fitted to empirical data and new

morphologies by combining NeuroGPU with BluePyOpt.

Unlike single trace stimulations (Fig. 4), optimization to 8 separate traces required more

generations to obtain reasonable fits, which unfortunately increased processing time dramatically.

To reduce runtimes, we revised NeuroGPU by adding two final features. First, we eliminated

NEURON calls to the CPU entirely by generating a procedure that identifies the free parameters

of the model and modifies NeuroGPU's input, 'AllParams.csv', to new values without using

NEURON. Second, we used CPU multithreading scoring, which reduced the overall computation

time of each generation. With these improvements, runtimes were reduced for each iteration of

the optimization algorithm. Simulation of all 8 traces with 10,000 putative solutions required 60

seconds of processing time. This was followed by a 103 second period required for scoring for

each genetic algorithm generation. This latter aspect has been accelerated dramatically. On 8

CPUs, the same process requires 2891 seconds per generation. These speedups (48.2 fold in

simulation time) are close to the speedups of single simulations (Fig. 2D). With these

improvements, we were able to obtain models that fit well to experimental data using an 8 GPU

node running NeuroGPU in just 4 hours, a task that traditionally would require several days of

computation using a large cluster (Hay et al., 2011; Hill et al., 2011; Almog and Korngreen, 2014).

As such, NeuroGPU allow one the ability to develop more complex models and fit them to

empirical data in reasonable time frames (Fig. 1).

Discussion:

Detailed models of neurons are critical to our understanding of neuronal functioning.
However, the computational resources required of current software implementations of complex
neuronal models are prohibitive, typically requiring supercomputers. At best, this limits the
accuracy of results; at worst, it limits access to all but a select set of scientists. To address this
gap, based on our previous efforts (Ben-Shalom et al., 2013), we designed a user-friendly
environment that enables one to port multi-compartmental models for implementation with CUDA
to run simulations on GPUs. By taking advantage of parallel processing inherent to GPUs, we
were able to accelerate simulations dramatically—up to 2-3 orders of magnitude with multiple
GPUs. NeuroGPU was developed to be interoperable with NEURON, thereby allowing anyone
with expertise in the NEURON environment access to GPU-based acceleration. Towards this
goal, we developed a platform to easily port NEURON models from either ModelDB or the BBP
portal (Ramaswamy et al., 2015; McDougal et al., 2017) using a iPython notebook-based
graphical user interface (GUI). We further developed GUIs for creating stimulation protocols,
parameter exploration, and genetic optimization.

NeuroGPU addresses a major gap in currently implemented GPU-based simulation
environments. Two other neuronal simulations environments for multi-compartmental models
have been implemented using GPUs, CoreNeuron (Kumbhar et al., 2019) and Arbor (Akar et al.,
2019). These environments are designed primarily to accelerate large scale network simulations.
NeuroGPU, by contrast, is focused on greatly accelerating the simulation of single neurons with
complex, multi-compartment morphologies, critical for exploring the parameter space of single
models and optimizing such models to best fit empirical data.

Leveraging the acceleration of single-neuron simulations, NeuroGPU has expanded GUIs
for parameter exploration, which allows for rapid assessment of how changes in ion channel
density across compartments affects neuronal excitability (Fig. 3). This approach may be
particularly useful to generate testable hypotheses regarding channel distribution with
pharmacological manipulations (Keren et al., 2009; Almog and Korngreen, 2014; Mäki-Marttunen
et al., 2018), modulation of ion channels (Byczkowicz et al., 2019), or in disease states where ion
channel density is thought to be affected (Migliore and Migliore, 2012; Miceli et al., 2013; Ben-
Shalom et al., 2017; Spratt et al., 2019). Furthermore, one could generate a range of cells with
variable channel densities and confirm that their activity is physiologically realistic (e.g., Fig. 3, all
cases before generating depolarization block). These conditions could then be used as building
blocks for variable activity within neuronal networks (Prinz et al., 2003, 2004; Alonso and Marder,

2019). In addition to parameter exploration, NeuroGPU is designed for extensive model
optimization (Gagn, 2012; Van Geit et al., 2016). Fitting complex models to empirical data is
computationally expensive, often requiring days of compute time, even on large supercomputing
systems (Hay et al., 2011; Almog and Korngreen, 2014). Here, we show that NeuroGPU
accelerates model fitting processing times by 2-3 orders of magnitude (Fig. 4-5). This makes it
possible for individual labs to implement optimization algorithms with their own hardware. But
also, it opens the door to extremely high-speed model fitting, as NeuroGPU can be run easily on
GPU supercomputing systems, which inherently have exponentially more computational
resources compared than similarly kitted CPU systems.

Recent advances in genetic characterization and novel analysis methods have resulted in
characterization of diverse neuronal types with respect to their morphologies, projections, and
protein expression (Gouwens et al., 2019). However, these advancement lack detailed
biophysical models that can describe and simulate these neurons. In the BBP portal there are
~200 models that each is comprised of an m-type, which describes the morphology, and one of
11 e-types, which is a set of conductances that describes the electrical properties of the cell.
Currently, these e-types describe somewhat generalized activity patterns [e.g., neurons that fire
at high frequency without accommodation, or neurons that have stuttering firing patterns
(Markram et al., 2015)]. With NeuroGPU we can easily expand this repertoire of e-types, and
even replace generalizable e-types with models that recapitulate the activity of data obtained from
single neurons. This would improve network simulations, as single neurons would display
biologically accurate diversity within and across neuronal subtypes (e.g., Fig. 5B).

NeuroGPU accelerates compartmental modeling through parallelization of matrix
calculations. Solving the tridiagonal matrix is the most computationally demanding aspect of multi-
compartmental model simulations (Hines, 1984; Hines et al., 2008; Ben-Shalom et al., 2013).
Therefore, we took advantage of fast, on-GPU memory and controlled the timing of calculations
and memory transfers to optimize the use of computational resources (Volkov and Demmel, 2008;
Ben-Shalom et al., 2013; Nvidia, 2018). Resulting speedups depended primarily on neuronal
morphology, and in general we show that NeuroGPU offered the best improvements when
processing morphologically complex cases. Even in these cases, overall GPU utilization was
limited by execution dependencies, where one aspect of GPU processing could not proceed until
another aspect either transferred or processed its own memory. In the future, these dependencies
may be further reduced through either dynamic parallelization (Zhang et al., 2015) or by
increasing instruction level parallelism (ILP) (Volkov and Demmel, 2008). Nevertheless, the

current version of NeuroGPU accelerates single neuron compartmental simulations by several
orders of magnitude.

Future iterations of NeuroGPU may expand on the strengths and address limitations in
using GPUs for compartmental modeling. Ion channels are modeled typically with Markov-based
kinetics, or a simpler Markov approximation based on Hodgkin-Huxley type equations. NeuroGPU
currently supports Hodgkin-Huxley-based mechanisms only, as we found that implementation of
full Markov-based mechanisms on GPUs requires too much shared memory and reduces
performance drastically (Ben-Shalom et al., 2012). As with total GPU utilization, improvements in
memory handling may improve these cases. Furthermore, GPUs work best when the same
instructions are occurring simultaneously on multiple memory addresses. This makes them ideal
for iterating through models with identical morphologies and different channel distributions, but
less ideal for network models containing a diversity of neuron types. As an intermediate, one could
address this limitation by modeling networks containing discrete sets of neurons. For example, a
network could contain several compartmental morphology models that each support multiple
instances with different channel parameters, similar to the Ring model applied by Arbor (Akar et
al., 2019; Kumbhar et al., 2019).

NeuroGPU will help democratize multi-compartmental modeling. While NeuroGPU can
support simulations in large, tightly integrated systems using UNIX-based mutli-GPU
architectures, it also is ideal for individual laboratories running simulations on Windows-based
workstations with GPUs, which are becoming increasingly common. Indeed, a workstation with
total costs <$3000, when kitted with appropriate GPUs, can out-perform loosely inter connected
CPU-based clusters (i.e., with commodity inter-node connection hardware). This could help
broaden the use and utility of multi-compartmental modeling by bringing supercomputer-level
processing power to a large range of research settings.

Acknowledgments

We are grateful to Dr. Gilad Liberman who helped conceptualize this project. To the support and
advice of NVIDIA developers – Dr. Jonathan Lefman, Dr. Jonathan Bentz, Dr. Xuemeng Zhang
and Angela Chen in optimizing the CUDA code. To Maxwell Chen and Mathew Derango who
helped with code development. To NVIDIA Corporation for donating the GPUs used in this study.
To all the members of the Bender Lab for critically assessing this work. This research was
supported by NIH Grants F32 NS095580 (RBS), MH112729 (KJB), and DA035913 (KJB).

Figure 1: *Optimizing biophysical neuronal models increase with their complexity*

Biophysical neuronal model complexity depends on three factors (A-C) which determine computational costs required to simulate and fit models to empirical data (optimization) (D-E)

A: Morphological complexity: The abstraction of the neuronal morphology ranges from a point neuron, to a simplified morphology, and ultimately toward different methods to reconstruct neuronal morphology with high resolution.

B: Compartmental complexity: Compartmental models vary in complexity both in number of compartments and the content of each compartment. Top: Single compartment with basic, conductances required for spiking and a resting membrane potential. Middle: Multi-compartmental model where ion-channels are aggregated under several conductances e.g. all different voltage gated potassium channels are represented in a slow and fast inactivating channel (Korngreen and Sakmann, 2000). Bottom: High resolution morphology with detailed representation to all channels sub-types in each compartment.

C: Single-channel complexity: The overall conductance in compartmental models is formalized either with Hodgkin-Huxley equations or with Markov-based models. When fitting a model to empirical data, several parameters can be varied. Top: only the maximal conductance in a Hodgkin-Huxley formulation. Middle: coefficients added to Hodgkin-Huxley equations (time constants, voltage dependence). Bottom: In Markov-based channels the transition coefficients can be varied.

D: Optimizing a model (fitting model to data) depends on the complexity of the model and number of free parameters. When complexity and number of free parameters require compute times that exceed a few days, it becomes impractical to use high resolution models.

E: Developing tools to accelerate simulation and optimization time will enable us to use more complicated and biophysical relevant models.

Figure 2: NeuroGPU reduces simulation run-time of complex neurons by orders of magnitude without compromising accuracy

A: Morphology of a BBP portal layer 5 neocortical pyramidal cell (Ramaswamy et al., 2015). Dendrite in black, axon in red.

B: Top: injected current at the soma. Middle: NEURON voltage response as recorded at the soma. Cyan: NeuroGPU response as recorded at the soma. Bottom: difference in voltage between NEURON and NeuroGPU.

C: Top: APs generated per current injection intensity in the soma. Middle, bottom: Peak and average voltage difference between the voltage response in NEURON and NeuroGPU. Red circles denote examples in B.

D: Top: Runtimes for the model using the different architectures: black – NEURON, green – NeuroGPU on TitanXP, blue – NeuroGPU on TeslaV100. X-axis in log2 scale, Y-axis in log10 scale. Bottom: Speedup compared to NEURON.

E: Top: Runtime for the model on 1-4 GPUs (Tesla V100) on the same node. Bottom: Speedup compared to NEURON

F-J: Same as A-D, but for a model chandelier cell.

Figure 3: NeuroGPU enables rapid exploration of *parameter space in complex pyramidal neuron model*

A: Each point in the grid represents the number of APs in the relevant model. Points on the axis represent the varied conductances of Na_v and K_v at the axon in the range of [0,10] and [0,20] S/cm^2, respectively.

B: Example voltage responses for chosen models from A. Colors match to the corresponding model location.

Figure 4: NeuroGPU accelerates evolutionary optimization for fitting models to data

A: Voltage traces obtained from optimization (worst case from population of 100: red; best case from population of 10,000: cyan) compared to ground truth (black).

B: Optimizations examples using DEAP with different sizes of populations. Four Optimizations with different random starting population over 50 generations. Y axis is the error from the target voltage as described in the methods section. Lower values denote less error from target data.

C: Comparing runtimes for optimizations using NeuroGPU and NEURON (linearly extrapolated from 5 generations). Circles are color coded for population size as in A, and represent mean ± SEM.

D: Best score in each optimization in A. Circles and error bars as in C.

Figure 5: NeuroGPU fits BBP PC model to empirical data

A: Left: morphology of L5 thick-tufted pyramidal neuron from somatosensory cortex (Ramaswamy et al., 2015). Right: NeuroGPU fits (green traces) the L5 PC model to empirical data recorded from an L5 prefrontal cortex pyramidal neuron of a mouse (Black Traces) with different stimulus intensity 200-340pA (Spratt et al., 2019)

B: Left: Prefrontal-cortex layer 5 pyramidal neuron morphology (Ascoli et al., 2007; Yin et al., 2018). The morphology of BBP PC model was modified to that of the prefrontal neuron and fitted to the same data as in A.

C: Number of APs per 300 ms of step stimulation for different models of layer 5 pyramidal neuron. Note that both revised models overlap target data.

A   **NeuroGPU**
General Overview

Step	Action	Location
1	Import model	iPython
2	Translation	iPython
3	Execution	NeuroGPU

B

Import components	Source
Morphology and initial values for free parameters (hoc file)	ModelDB
Mechanisms (mod files)	ModelDB
Free parameters — channel properties — receptor properties — intrinsic properties (membrane, buffering, etc...)	User generated in iPython
Stimulation protocols — stimulus injection site	User generated in iPython

C   **Translation (extractModel.py)**

mod files hoc files	CUDA kernels — AllModels.cu — CudaStuff.cu
tri-diagonal matrix tri-diag. matrix indexes Mechanism map	Simulation constants — BasicConst.csv

Mechanism variables
Global variables
  (e.g., temperature,
   ion concentrations)
	Simulation variables
	— AllParams.csv

D   **Execution**

Supplemental Figure 1: *NeuroGPU overview and flowchart*

A: Overview of the general workflow in NeuroGPU: The user ports a model via the iPython GUI and customizes the simulation (panel B). NeuroGPU translates the model to CUDA code that can run on the GPU and compiles executable code.

B: Sources for model components: The morphology and model's properties are described in the hoc file. Additional mechanisms such as ion-channels are described in .mod files. The stimulation protocols can be either imported or can be generated with our provided GUI

C: Import to NeuroGPU is done by the extractModel.py script. It translates mod files to GPU kernels (see methods), which are written to AllModels.cu, and updates the course of the simulation at CudaStuff.cu. extractModel.py writes to the BasicConst.csv the tri-diagonal matrix and mechanism map, which indicates the mechanisms for each compartment. Finally, extractModel.py writes all the mechanism parameters to AllParams.csv.

D: After extractModel.py terminates, it creates NeuroGPU.exe. When NeuroGPU is invoked it reads the input files and runs the simulations for the different instances of the model and writes their voltages output to a file. When NeuroGPU is used for optimization, new instances of the models are created each iteration, and only AllParams.csv is updated via a python script.

Supplemental Figure 2: *NeuroGPU CUDA implementation*

A: NeuroGPU can be run on multiple GPUs; each GPU will run a separate grid of block/neurons (Nvidia, 2018).

B: Grids are distributed in blocks, with each block representing an instance of a model. The number of blocks in a grid is set by the number of model instances that will be simulated on an individual GPU.

C: A block is the basic simulation unit upon which 32 threads each update the memory in an ILP manner (see Methods). Global memory, which can be accessed by all blocks, stores mechanism parameters for every compartment. Constant memory, which is limited in size, stores the simulation constants such as the tri-diagonal matrix and the mechanism map.

Supplemental Figure 3: *Passive model simulations*

A: Simple morphology with artificial axon. This model contains passive channels (pas.mod) in all compartments.

B: Top: injected current at the soma Middle: NEURON voltage response as recorded at the soma. Blue: NeuroGPU response as recorded at the soma. Bottom: difference in voltage between NEURON and NeuroGPU.

C: Top: Runtimes for the model using the different architectures: black – NEURON, green – NeuroGPU on TitanXP, blue – NeuroGPU on TeslaV100. X-axis in log2 scale, Y-axis in log10 scale. Bottom: Speedup compared to NEURON.

D-F: Same as A-C, but for complex morphology from (Mainen and Sejnowski, 1996b).

Supplemental Figure 4: *Mainen and Sejnowski model neuron simulations*

A: Simple morphology with artificial axon and active and passive components distributed as in (Mainen and Sejnowski, 1996b)

B: Top: injected current at the soma. Middle: NEURON voltage response as recorded at the soma. Cyan: NeuroGPU response as recorded at the soma. Bottom: difference in voltage between NEURON and NeuroGPU.

C: Top: Runtimes for the model using the different architectures: black – NEURON, green – NeuroGPU on TitanXP, blue – NeuroGPU on TeslaV100. X-axis in log2 scale, Y-axis in log10 scale. Bottom: Speedup compared to NEURON.

D-F: Same as A-C, but for neocortical layer 5 pyramidal cell morphology, as in (Mainen and Sejnowski, 1996b).

G: In panel E, a relatively large voltage discrepancy of 6.6 mV was identified. This discrepancy occurred during the last AP within a burst and was due largely to a shift in the timing of this AP (Fig. 4G). Voltage differences are minimized by linearly interpolating the data 4-fold and advancing NeuroGPU simulation by ¼ time-step.

Table 1 – parameters varied in the BBP model for figure 4:

Parameter Name	Base value	Lower Bound	Upper Bound
gNaTa_tbar_NaTa_t	3.137968	0.3137968	31.37968
gNaTs2_tbar_NaTs2_t	0.983955	0.0983955	9.83955
gK_Tstbar_K_Tst	0.089259	0.0089259	0.89259
gIhbar_Ih	0.00008	0.000008	0.0008
gImbar_Im	0.000143	0.0000143	0.00143
gSKv3_1bar_SKv3_1	0.303472	0.0303472	3.03472

Table 2 - parameters varied in the BBP model for figure 5A:

Parameter Name	Base value	Lower Bound	Upper Bound
g_pas_all	0.0003	0.000003	0.003
e_pas_all	-75	-150	-50
gNaTa_tbar_NaTa_t_axonal	3.137968	0.3137968	31.37968
gK_Tstbar_K_Tst_axonal	0.089259	0.0089259	2.89259
gNap_Et2bar_Nap_Et2_axonal	0.006827	0.0006827	0.06827
gK_Pstbar_K_Pst_axonal	0.973538	0.0973538	9.73538
gSKv3_1bar_SKv3_1_axonal	1.021945	0.1021945	10.21945
gCa_LVAstbar_Ca_LVAst_axonal	0.008752	0.0008752	0.08752
gCa_HVAbar_Ca_HVA_axonal	0.00099	0.000099	0.0099
gSKv3_1bar_SKv3_1_somatic	0.303472	0.0303472	3.03472
gCa_HVAbar_Ca_HVA_somatic	0.000994	0.0000994	0.00994
gNaTs2_tbar_NaTs2_t_somatic	0.983955	0.0983955	9.83955
gCa_LVAstbar_Ca_LVAst_somatic	0.000333	0.0000333	0.0333
gIh_dend	0.00008	0.000007	0.009

Table 3 - parameters varied in the BBP model for figure 5B:

Parameter Name	Base value	Lower Bound	Upper Bound
g_pas_all	0.0003	0.000003	0.003
e_pas_all	-75	-150	-50
gNaTa_tbar_NaTa_t_axonal	3.137968	0.3137968	10.37968
gK_Tstbar_K_Tst_axonal	0.089259	0.0089259	2.89259
gNap_Et2bar_Nap_Et2_axonal	0.006827	0.0006827	0.06827
gK_Pstbar_K_Pst_axonal	0.973538	0.0973538	9.73538
gSKv3_1bar_SKv3_1_axonal	1.021945	0.1021945	10.21945
gCa_LVAstbar_Ca_LVAst_axonal	0.008752	0.0008752	0.08752
gCa_HVAbar_Ca_HVA_axonal	0.00099	0.000099	0.0099
gSKv3_1bar_SKv3_1_somatic	0.303472	0.0303472	3.03472
gCa_HVAbar_Ca_HVA_somatic	0.000994	0.0000994	0.00994
gNaTs2_tbar_NaTs2_t_somatic	0.983955	0.0983955	9.83955
gCa_LVAstbar_Ca_LVAst_somatic	0.000333	0.0000333	0.0333
gIh_dend	0.00008	0.0000008	0.08
gSK_E2bar_SK_E2_axon	0.007104	0.0007104	0.07104

Table 4:

Model	Morphology	SingleKernel		SplitKernel	
		Acceleration	Utilization	Acceleration	Utilization
Passive membrane	Soma & apical dendrite	95.8	0.30%	78.8	0.41%
	Pyramidal Cell	58.1	10%	55.2	3.62%
Mainen and Sejnowski	Soma & apical dendrite	153.1	10%	99.5	1%
	Pyramidal Cell	114.2	10%	111.8	3.80%
Blue Brain Project	Pyramidal Cell	93	10%	107	3.70%
	Chandelier Cell	205.6	10%	197.5	1.60%
Acceleration: fold increase in processing speed relative to single core CPU (MODEL)					
Utilization: Percent of time the GPU is being used					

References

Akar NA, Cumming B, Karakasis V, Küsters A, Klijn W, Peyser A, Yates S (2019) Arbor - A Morphologically-Detailed Neural Network Simulation Library for Contemporary High-Performance Computing Architectures. In: Proceedings - 27th Euromicro International Conference on Parallel, Distributed and Network-Based Processing, PDP 2019, pp 274–282.

Allen NM, Mannion M, Conroy J, Lynch SA, Shahwan A, Lynch B, King MD (2014) The variable phenotypes of KCNQ-related epilepsy. Epilepsia 55:e99–e105.

Almog M, Korngreen A (2014) A quantitative description of dendritic conductances and its application to dendritic excitation in layer 5 pyramidal neurons. J Neurosci 34:182–196.

Almog M, Korngreen A (2016) Is realistic neuronal modeling realistic? J Neurophysiol 2:jn.00360.2016.

Alonso LM, Marder E (2019) Visualization of currents in neural models with similar behavior and different conductance densities. Elife 8.

Ascoli GA, Donohue DE, Halavi M (2007) NeuroMorpho.Org: A central resource for neuronal morphologies. J Neurosci 27:9247–9251.

Ben-Shalom R, Aviv A, Razon B, Korngreen A (2012) Optimizing ion channel models using a parallel genetic algorithm on graphical processors. J Neurosci Methods 206:183–194.

Ben-Shalom R, Keeshen CM, Berrios KN, An JY, Sanders SJ, Bender KJ (2017) Opposing Effects on NaV1.2 Function Underlie Differences Between SCN2A Variants Observed in Individuals With Autism Spectrum Disorder or Infantile Seizures. Biol Psychiatry 82:224–232.

Ben-Shalom R, Liberman G, Korngreen A (2013) Accelerating compartmental modeling on a graphical processing unit. Front Neuroinform 7:4.

Byczkowicz N, Eshra A, Montanaro J, Trevisiol A, Hirrlinger J, Kole MHP, Shigemoto R, Hallermann S (2019) HCN channel-mediated neuromodulation can control action potential velocity and fidelity in central axons. Elife 8.

Canavier CC (1999) Sodium Dynamics Underlying Burst Firing and Putative Mechanisms for the Regulation of the Firing Pattern in Midbrain Dopamine Neurons: A Computational Approach.

Canavier CC, Landry RS (2006) An Increase in AMPA and a Decrease in SK Conductance Increase Burst Firing by Different Mechanisms in a Model of a Dopamine Neuron In Vivo. J Neurophysiol 96:2549–2563.

Carnevale NT, Hines ML (2006) The NEURON Book. Cambridge University Press.

Clarkson RL, Liptak AT, Gee SM, Sohal VS, Bender KJ (2017) D3 Receptors Regulate Excitability in a Unique Class of Prefrontal Pyramidal Cells. J Neurosci 37:5846–5860.

Cohen CCH, Popovic MA, Klooster J, Weil MT, Möbius W, Nave KA, Kole MHP (2020) Saltatory Conduction along Myelinated Axons Involves a Periaxonal Nanocircuit. Cell 180:311-322.e15.

Colquhoun D, Hawkes AG (1995) A Q-Matrix Cookbook. In: Single-Channel Recording, pp 589–633. Boston, MA: Springer US.

De Schutter E, Bower JM (1994) An active membrane model of the cerebellar Purkinje cell I.
Simulation of current clamps in slice. J Neurophysiol 71:375–400.

Deitcher Y, Eyal G, Kanari L, Verhoog MB, Atenekeng Kahou GA, Mansvelder HD, De Kock
CPJ, Segev I (2017) Comprehensive Morpho-Electrotonic Analysis Shows 2 Distinct
Classes of L2 and L3 Pyramidal Neurons in Human Temporal Cortex. Cereb Cortex
27:5398–5414.

Dembrow NC, Chitwood RA, Johnston D (2010) Projection-specific neuromodulation of medial
prefrontal cortex neurons. J Neurosci 30:16922–16937.

Eklund A, Dufort P, Forsberg D, LaConte SM (2013) Medical image processing on the GPU -
past, present and future. Med Image Anal 17:1073–1094.

Fidjeland AK, Shanahan MP (2010) Accelerated Simulation of Spiking Neural Networks Using
GPUs. Ijcnn'10:1–8.

Fletcher LN, Williams SR (2019) Neocortical Topology Governs the Dendritic Integrative
Capacity of Layer 5 Pyramidal Neurons. Neuron 101:76-90.e4.

Gagn C (2012) DEAP : Evolutionary Algorithms Made Easy. J Mach Learn Res 13:2171–2175.

Gee S, Ellwood I, Patel T, Luongo F, Deisseroth K, Sohal VS (2012) Synaptic activity unmasks
dopamine D2 receptor modulation of a specific class of layer V pyramidal neurons in
prefrontal cortex. J Neurosci 32:4959–4971.

Go AW, Williamson MJ, Xu D, Poole D, Grand S Le, Walker RC, Götz AW, Williamson MJ, Xu
D, Poole D, Le Grand S, Walker RC (2012) Routine microsecond molecular dynamics
simulations with AMBER on GPUs. 1. generalized born. J Chem Theory Comput 8:1542–
1555.

Gouwens NW, Berg J, Feng D, Sorensen SA, Zeng H, Hawrylycz MJ, Koch C, Arkhipov A
(2018) Systematic generation of biophysically detailed models for diverse cortical neuron
types. Nat Commun 9.

Gurkiewicz M, Korngreen A (2007) A Numerical Approach to Ion Channel Modelling Using
Whole-Cell Voltage-Clamp Recordings and a Genetic Algorithm. PLoS Comput Biol
3:e169.

Hallermann S, de Kock CPJ, Stuart GJ, Kole MHP (2012) State and location dependence of
action potential metabolic cost in cortical pyramidal neurons. Nat Neurosci 15:1007–1014.

Hausser M, Spruston N, Stuart GJ (2000) Diversity and dynamics of dendritic signaling. Science
(80-) 290:739–744.

Hay E, Hill S, Schürmann F, Markram H, Segev I (2011) Models of neocortical layer 5b
pyramidal cells capturing a wide range of dendritic and perisomatic active properties. PLoS
Comput Biol 7:e1002107.

Hay E, Schurmann F, Markram H, Segev I, Schürmann F, Markram H, Segev I (2013)
Preserving axosomatic spiking features despite diverse dendritic morphology. J
Neurophysiol 109:2972–2981.

Hill S, Markram H, Segev I, Druckmann S, Berger TK, Schu F (2011) Effective Stimuli for
Constructing Reliable Neuron Models. 7.

Hille B (1984) Ionic channels of excitable membranes, Third. Sunderland, Mass.: Sinauer

Associates.

Hines M (1984) Efficient computation of branched nerve equations. Int J Biomed Comput
15:69–76.

Hines ML, Carnevale NT (2000) Expanding NEURON's Repertoire of Mechanisms with
NMODL. Neural Comput 12:995–1007.

Hines ML, Eichner H, Schürmann F (2008) Neuron splitting in compute-bound parallel network
simulations enables runtime scaling with twice as many processors. J Comput Neurosci
25:203–210.

Hodgkin AL, Huxley AF (1952) A quantitative description of membrane current and its
application to conduction and excitation in nerve. Bull Math Biol 117:25–71; discussion 5-
23.

Hu W, Tian C, Li T, Yang M, Hou H, Shu Y (2009) Distinct contributions of Na(v)1.6 and
Na(v)1.2 in action potential initiation and backpropagation. Nat Neurosci 12:996–1002.

Kanari L, Ramaswamy S, Shi Y, Morand S, Meystre J, Perin R, Abdellah M, Wang Y, Hess K,
Markram H (2019) Objective Morphological Classification of Neocortical Pyramidal Cells.
Cereb Cortex 29:1719–1735.

Keren N, Bar-Yehuda D, Korngreen A (2009) Experimentally guided modelling of dendritic
excitability in rat neocortical pyramidal neurones. J Physiol 587:1413–1437.

Kole MHP, Ilschner SU, Kampa BM, Williams SR, Ruben PC, Stuart GJ (2008) Action potential
generation requires a high sodium channel density in the axon initial segment. Nat
Neurosci 11:178–186.

Kole MHPP, Letzkus JJ, Stuart GJ (2007) Axon initial segment Kv1 channels control axonal
action potential waveform and synaptic efficacy. Neuron 55:633–647.

Korngreen a, Sakmann B (2000) Voltage-gated K+ channels in layer 5 neocortical pyramidal
neurones from young rats: subtypes and gradients. J Physiol 525 Pt 3:621–639.

Kumbhar P, Hines M, Fouriaux J, Ovcharenko A, King J, Delalondre F, Schürmann F (2019)
CoreNEURON : An Optimized Compute Engine for the NEURON Simulator.

Kuznetsova AY, Huertas MA, Kuznetsov AS, Paladini CA, Canavier CC (2010) Regulation of
firing frequency in a computational model of a midbrain dopaminergic neuron. J Comput
Neurosci 28:389–403.

Li A, Song SL, Chen J, Li J, Liu X, Tallent N, Barker K (2019) Evaluating Modern GPU
Interconnect: PCIe, NVLink, NV-SLI, NVSwitch and GPUDirect.

London M, Häusser M (2005) DENDRITIC COMPUTATION. Annu Rev Neurosci 28:503–532.

Magee JC, Cook EP (2000) Somatic EPSP amplitude is independent of synapse location in
hippocampal pyramidal neurons. Nat Neurosci 3:895–903.

Mainen ZF, Carnevale NT, Zador AM, Claiborne BJ, Brown TH (1996) Electrotonic architecture
of hippocampal CA1 pyramidal neurons based on three-dimensional reconstructions. J
Neurophysiol 76:1904–1923.

Mainen ZF, Sejnowski TJ (1996a) Influence of dendritic structure on firing pattern in model
neocortical neurons. Nature 382:363–366 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/8684467.

Mainen ZF, Sejnowski TJ (1996b) Influence of dendritic structure on firing pattern in model
neocortical neurons. Nature 382:363–366.

Mäki-Marttunen T, Halnes G, Devor A, Metzner C, Dale AM, Andreassen OA, Einevoll GT
(2018) A stepwise neuron model fitting procedure designed for recordings with high spatial
resolution: Application to layer 5 pyramidal cells. J Neurosci Methods 293:264–283.

Markram H et al. (2015) Reconstruction and Simulation of Neocortical Microcircuitry. Cell
163:456–492.

McDougal R a., Morse TM, Hines ML, Shepherd GM (2015) ModelView for ModelDB: Online
Presentation of Model Structure. Neuroinformatics.

McDougal RA, Morse TM, Carnevale T, Marenco L, Wang R, Migliore M, Miller PL, Shepherd
GM, Hines ML (2017) Twenty years of ModelDB and beyond: building essential modeling
tools for the future of neuroscience. J Comput Neurosci 42:1–10.

Miceli F, Soldovieri MV, Ambrosino P, Barrese V, Migliore M, Cilio MR, Taglialatela M (2013)
Genotype–phenotype correlations in neonatal epilepsies caused by mutations in the
voltage sensor of K_v 7.2 potassium channel subunits. Proc Natl Acad Sci 110:4386–4391.

Migliore M, Migliore R (2012) Know Your Current Ih: Interaction with a Shunting Current
Explains the Puzzling Effects of Its Pharmacological or Pathological Modulations Attali B,
ed. PLoS One 7:e36867.

Milstein AD, Bloss EB, Apostolides PF, Vaidya SP, Dilly GA, Zemelman B V., Magee JC (2015)
Inhibitory Gating of Input Comparison in the CA1 Microcircuit. Neuron 87:1274–1289.

Miyasho T, Takagi H, Suzuki H, Watanabe S, Inoue M, Kudo Y, Miyakawa H (2001) Low-
threshold potassium channels and a low-threshold calcium channel regulate Ca2+ spike
firing in the dendrites of cerebellar Purkinje neurons: A modeling study. Brain Res
891:106–115.

Moor R, Geit W Van, (2015) BBP (2015) Electrophys Feature Extraction Library (eFEL).
GitHub Repos.

Narayanan R, Johnston D (2008) The h channel mediates location dependence and plasticity of
intrinsic phase response in rat hippocampal neurons. J Neurosci 28:5846–5860.

Nocedal J, Wright S (2006) Numerical optimization.

Nvidia C (2018) Cuda c programming guide, version 9.1. NVIDIA Corp.

Pachitariu M, Steinmetz N, Kadir S, Carandini M, D. HK (2016) Kilosort: realtime spike-sorting
for extracellular electrophysiology with hundreds of channels. bioRxiv:061481.

Payne JL, Sinnott-Armstrong NA, Moore JH (2010) Exploiting Graphics Processing Units for
Computational Biology and Bioinformatics. Interdiscip Sci 2:213–220.

Poirazi P, Brannon T, Mel BW (2003) Pyramidal neuron as two-layer neural network. Neuron
37:989–999.

Prein AF, Langhans W, Fosser G, Ferrone A, Ban N, Goergen K, Keller M, Tölle M, Gutjahr O,
Feser F, Brisson E, Kollet S, Schmidli J, Van Lipzig NPM, Leung R (2015) A review on
regional convection-permitting climate modeling: Demonstrations, prospects, and

challenges. Rev Geophys 53:323–361.

Prinz AA, Billimoria CP, Marder E (2003) Alternative to Hand-Tuning Conductance-Based
Models: Construction and Analysis of Databases of Model Neurons. J Neurophysiol
90:3998–4015.

Prinz AA, Bucher D, Marder E (2004) Similar network activity from disparate circuit parameters.
Nat Neurosci 7:1345–1352.

Rainville F De, Fortin F, Gardner M, Parizeau M, Gagné C (2012) DEAP : A Python Framework
for Evolutionary Algorithms. Companion proc Genet Evol Comput Conf:85–92.

Rall W (1962a) Theory of Physiological Properties of Dendrites. Ann N Y Acad Sci 96:1071–
1092.

Rall W (1962b) Electrophysiology of a Dendritic Neuron Model. Biophys J 2:145–167.

Ramaswamy S et al. (2015) The neocortical microcircuit collaboration portal: a resource for rat
somatosensory cortex. Front Neural Circuits 9:44.

Roth A, Häusser M (2001) Compartmental models of rat cerebellar Purkinje cells based on
simultaneous somatic and dendritic patch-clamp recordings. J Physiol 535:445–472.

Salomon-Ferrer R, Götz AW, Poole D, Le Grand S, Walker RC, Go AW, Poole D, Grand S Le,
Walker RC (2013) Routine microsecond molecular dynamics simulations with AMBER on
GPUs. 2. Explicit solvent particle mesh ewald. J Chem Theory Comput 9:3878–3888.

Schmidhuber J (2015) Deep Learning in neural networks: An overview. Neural Networks 61:85–
117.

Shu Y, Yu Y, Yang J, McCormick D a (2007) Selective control of cortical axonal spikes by a
slowly inactivating K+ current. Proc Natl Acad Sci U S A 104:11453–11458.

Smith SL, Häusser M (2010) Parallel processing of visual space by neighboring neurons in
mouse visual cortex. Nat Neurosci 13:1144–1149.

Spratt PWE, Ben-Shalom R, Keeshen CM, Burke KJ, Clarkson RL, Sanders SJ, Bender KJ
(2019) The Autism-Associated Gene Scn2a Contributes to Dendritic Excitability and
Synaptic Function in the Prefrontal Cortex. Neuron.

Spruston N (2008) Pyramidal neurons: Dendritic structure and synaptic integration. Nat Rev
Neurosci 9:206–221 Available at: https://www.nature.com/articles/nrn2286 [Accessed June
23, 2020].

Van Geit W, Gevaert M, Chindemi G, Rössert C, Courcol J-D, Muller E, Schürmann F, Segev I,
Markram H (2016) BluePyOpt: Leveraging open source software and cloud infrastructure to
optimise model parameters in neuroscience. arXiv 10:1–18.

Volkov V, Demmel JW (2008) Benchmarking GPUs to tune dense linear algebra. In: 2008 SC -
International Conference for High Performance Computing, Networking, Storage and
Analysis, pp 1–11. IEEE.

Whitehead N (2011) Precision & Performance: Floating Point and IEEE 754 Compliance
for NVIDIA GPUs.

Yin L, Zheng R, Ke W, He Q, Zhang Y, Li J, Wang B, Mi Z, Long Y sheng, Rasch MJ, Li T, Luan
G, Shu Y (2018) Autapses enhance bursting and coincidence detection in neocortical

pyramidal cells. Nat Commun 9:1–12.

Zamponi GW, Lory P, Perez-Reyes E (2010) Role of voltage-gated calcium channels in
epilepsy. Pflugers Arch Eur J Physiol 460:395–403 Available at:
https://idp.springer.com/authorize/casa?redirect_uri=https://link.springer.com/article/10.100
7/s00424-009-0772-
x&casa_token=w42m9NgEtgcAAAAA:mRvrqQi8F18ax7hUuXOhRian5voI0wG33bvVOj2Cg
JV86srCg7ISBBYP4SmpR_tqw-NCMpEI2Vc8fmW1cKk [Accessed June 30, 2020].

Zhang P, Holk E, Matty J, Misurda S, Zalewski M, Chu J, McMillan S, Lumsdaine A (2015)
Dynamic parallelism for simple and efficient GPU graph algorithms. In: Proceedings of the
5th Workshop on Irregular Applications Architectures and Algorithms - IA3 '15, pp 1–4.
New York, New York, USA: ACM Press.

876