Selective enhancement of object representations through multisensory integration

David A. Tovar*[1,2], Micah M. Murray[3-6] & Mark T. Wallace[1,2,6-9]

[1]*School of Medicine, Vanderbilt University, Nashville, Tennessee, 37240; United States*

[2]*Vanderbilt Brain Institute, Vanderbilt University, Nashville, Tennessee, 37240; United States*

[3]*The Laboratory for Investigative Neurophysiology (The LINE), Department of Radiology, Lausanne University Hospital and University of Lausanne (CHUV-UNIL), 1011 Lausanne, Switzerland*

[4]*Electroencephalography Brain Mapping Core, Center for Biomedical Imaging (CIBM) of Lausanne and Geneva, Lausanne, Switzerland*

[5]*Department of Ophthalmology, Fondation Asile des aveugles and University of Lausanne, Switzerland*

[6]*Department of Hearing and Speech Sciences, Vanderbilt University Medical Center, Nashville, Tennessee, 37240; United States*

[7]*Department of Psychology, Vanderbilt University, Nashville, Tennessee, 37240; United States*

[8]*Department of Psychiatry and Behavioral Sciences, Vanderbilt University Medical Center, Nashville, Tennessee, 37240; United States*

[9]*Department of Pharmacology, Vanderbilt University, Nashville, Tennessee, 37240; United States*

*Lead Contact and Correspondence: david.tovar@vanderbilt.edu

Keywords: Multisensory Integration, Representational Similarity Analysis, EEG, Decoding, Object Recognition

Objects are the fundamental building blocks of how we create a representation of the external world. One major distinction amongst objects is between those that are animate versus inanimate. Many objects are specified by more than a single sense, yet the nature by which multisensory objects are represented by the brain remains poorly understood. Using representational similarity analysis of human EEG signals, we show that the often-found processing advantages for animate objects are not evident in a multisensory context. Neural response decoding was found to be more strongly enhanced for inanimate objects, which were more weakly decoded under unisensory conditions. A distance-to-bound analysis provided critical links between EEG and behavior. Improved neural decoding for visual and audiovisual objects was associated with faster behavior, and decoding differences between visual and audiovisual objects predicted reaction time differences. Collectively, these findings show that object encoding is distinct under unisensory and multisensory conditions.

Introduction

The brain is constantly bombarded with sensory information from a host of different sources. In extracting relevant information that can guide behavior, choosing which sensory information is valuable and which should be discarded is critical. This feat can be accomplished through top-down processes such as attention (Corbetta, Miezin, Dobmeyer, Shulman, & Petersen, 1990; Posner, 1980) or may also be done in a more automatic fashion by using the stimulus features processed along each step of the feedforward processing cascade (Alais & Burr, 2004; Angelaki, Klier, & Snyder, 2009; Körding et al., 2007). In this bottom-up schema, some stimulus features may receive more weight than others given their ecological importance in guiding behavior or due to their regularity in the environment (Laws, 2000; Patten, Mannion, & Clifford, 2017). Furthermore, an emerging body of literature in audition and vision suggests that these biases in perceptual weighting may propagate to the level of object representations (Carlson, Ritchie, Kriegeskorte, Durvasula, & Ma, 2014; Murray, 2006; Ritchie, Tovar, & Carlson, 2015). Given that many objects in the world are specified not only on the basis of their unisensory features, but also by the fact that they are comprised of multisensory signals, an open question is how these multisensory cues are assembled in order to build object representations. Furthermore, provided that objects oftentimes share common characteristics separate from their low-level features, how

might potential biases in abstract object categories lead to differences in perceptual gains from multisensory integration?

One of the major categorical distinctions in the case of objects is that of animacy. In vision, animate objects have been found to offer substantial processing and perceptual advantages over inanimate objects, including being: categorized faster, more consciously perceived, and found faster in search tasks (Carlson et al., 2014; Jackson & Calvillo, 2013; Lindh, Sligte, Assecondi, Shapiro, & Charest, 2019; New, Cosmides, & Tooby, 2007; Ritchie et al., 2015). Auditory studies have similarly found faster categorization times for animate objects (Vogler & Titchener, 2011; Yuval-Greenberg & Deouell, 2009). This difference may be a remnant of an earlier evolutionary need to rapidly recognize and process living stimuli that could pose a threat or be a source of sustenance (Laws, 2000). Furthermore, many inanimate objects such as cars, trains, and cellphones have not existed long enough for the brain to have developed specialized brain areas to represent them. In contrast, a number of specialized areas have been identified for animate subcategories, such as faces in the fusiform face area (FFA), bodies in the extrastriate body area (EBA) and voices in the temporal voice areas (TVAs) (Belin, Zatorre, Lafaille, Ahad, & Pike, 2000; De Lucia, Clarke, & Murray, 2010; Downing, Jiang, Shuman, & Kanwisher, 2001; Kanwisher, McDermott, & Chun, 1997).

To study how perceptual differences in visual and auditory categories may influence their subsequent integration as audiovisual objects, it is helpful to be able to quantify the relationship among the different sensory modalities and stimuli within them. One way to quantify neural encoding differences and relationships between objects and modalities is representational similarity analysis (RSA) (Kriegeskorte, Mur, & Bandettini, 2008). In this analysis, neural response patterns to stimuli are used to build a representational space that quantifies the relationship between stimuli with representational distance between objects indicating the difference in their neural signatures. RSA has been used to show that both visual and auditory objects have a clear encoding distinction between animate and inanimate categories (Carlson et al., 2014; Carlson, Tovar, Alink, & Kriegeskorte, 2013; Cichy, Pantazis, & Oliva, 2014; Giordano, McAdams, Zatorre, Kriegeskorte, & Belin, 2013; Kriegeskorte, Mur, Ruff, & Kiani, 2008; Ritchie et al., 2015, Brandman et al., 2019; van den Hurk et al., 2017). In this framework,

a greater distance in representational space signifies that neural signals between stimuli are more distinct, while shorter distances signify that it is more difficult to distinguish the neural response differences between stimuli. Representational space can contract if stimuli are degraded (Grootswagers, Ritchie, Wardle, Heathcote, & Carlson, 2017) or expand in cases of increased attention (Nastase et al., 2017). Although RSA is increasingly used as a tool to study the neural structure of object representations, it has not been fully leveraged to examine these representations under conditions in which objects are often represented – as multisensory entities.

In this study, we used representational similarity analysis to study the nature of the neural representations for animate and inanimate objects presented in both the visual and auditory modalities, as well as the manner in which these representations change when objects are presented in a multisensory context. To this end, we presented subjects with auditory, visual and semantically congruent audiovisual animate and inanimate objects and had them perform a go/no-go animacy categorization task while recording high-density EEG. Our overarching hypothesis was the greater behavioral benefits would be seen for objects presented in a multisensory context, and that these benefits would be accompanied by greater changes in representational space. A secondary hypothesis was that given evidence that the benefits of multisensory integration increase when it is more difficult to process a stimulus using one modality alone, we would see greater benefits for inanimate objects, given their weaker unisensory encoding relative to animate objects.

Results
Behavior: Advantage for Animate Objects for Unisensory Presentations but not Audiovisual Presentations

1
2
Figure 1 Experiment Schematic. A Go/No-Go discrimination task of animate and inanimate
objects. The responses were counterbalanced such that the number of responses for animate and
inanimate objects was equivalent. The stimuli consisted of 96 visual line drawings and 96
environmental sounds of common animate and inanimate objects, as well semantically congruent
pairings of these objects. The sounds of animate object were non-verbal vocalizations. The
stimulus duration was 500ms with a variable inter-stimulus interval of 900-1500ms.
9

Subjects were shown 48 animate and 48 inanimate auditory, visual, and audiovisual objects

while they performed a go/no-go categorization task, as shown in Figure 1. We first examined

behavioral differences across sensory modalities and categories, as shown in Figure 2. Figure 2A

shows mean reaction times (RTs) for the go/no-go task across participants for the three sensory

conditions. RTs for the auditory condition were significantly slower than for the visual and

audiovisual conditions as established by the Wilcoxon signed rank test (p<0.001). Next, behavior

was split by animate and inanimate categories to investigate the effects of animacy on RTs.

Figure 2B shows that there are significantly (p<0.01) faster RTs for animate objects compared to

inanimate objects for the auditory and visual conditions, consistent with the results from previous

studies (Carlson et al., 2014; Murray, 2006; Vogler & Titchener, 2011; Yuval-Greenberg &

Deouell, 2009). However, this difference is not significant for the audiovisual condition.

To further investigate this surprising lack of a difference in audiovisual performance, we created

an index of sensory bias for each participant, operationalized as the difference in reaction times

to the auditory and visual stimuli, and correlated this bias score to audiovisual RTs on a subject-

by-subject basis using a Spearman correlation. Figure 2C shows that the only significant

correlation between sensory bias and audiovisual RTs was for inanimate objects. The positive

correlation indicates that subjects whose RTs for visual and auditory stimuli were more similar

had faster multisensory RTs.

Figure 2 Behavior: Advantage for Animate Objects for Unisensory Presentations but not
Audiovisual Presentations. (A) Reaction time (RT) results for each modality and (B) broken
down by animacy. Wilcoxon signed-rank test P values (* p<0.05, ** p<0.01, *** p<0.001)
above comparisons. (C) Subject sensory bias and audiovisual RT Spearman correlations across
subjects for all exemplars, only animate exemplars, and only inanimate exemplars. Sensory bias
is only significantly correlated to audiovisual RT for inanimate exemplars (p=0.01).

Representational Similarity Analysis: The Influence of Sensory Modality on Between and

Within Animacy Category Decoding

To investigate the neural correlates of the behavioral differences noted across conditions, we

used RSA (Figure 3A-3C). Specifically, we built representational dissimilarity matrices (RDM)

for each subject and modality over 1 millisecond intervals using linear discriminant analysis for

each exemplar pair. From each RDM, we explored the effect of sensory modality on the

distinction between animate and inanimate exemplars by calculating the mean pairwise decoding

for between category pairs (e.g., dog vs. bell, dog vs. cannon). As can be seen in figure 3D, prior

to stimulus onset, decoding is at chance levels (i.e., 50%), because the classifier does not have

any meaningful neural data that will distinguish between category pairs. However, shortly after

stimulus onset, decoding performance becomes significantly above chance (FDR corrected,

$p<0.025$) across all three modalities. The latency of the onset of these decoding differences,

defined as at least 20ms of sustained significant decoding (see Carlson, Tovar, Alink, &

Kriegeskorte, 2013), was 88ms for auditory, 95ms for visual, and 60ms for audiovisual stimulus

conditions. Visual and audiovisual decoding peaked at 163ms and 154ms, respectively, with

higher peak decoding of 60% for audiovisual presentations compared to 58% for visual

presentations. Decoding of auditory stimuli was comparatively poorer, peaking at 53% at 190ms.

Note that while there were differences in significant decoding onsets, caution should be taken

when comparing decoding onsets across conditions with different maximum decoding peaks (see

figure 14 in Grootswagers, Wardle, & Carlson, 2017). Collectively, the results of these decoding

analyses illustrate the temporal emergence of distinct neural representations for auditory, visual

and audiovisual objects.

To statistically compare decoding performance across modalities, we computed the mean

decoding for the interval spanning 50 to 600ms post-stimulus. Decoding for audiovisual stimuli

was significantly higher when compared with both visual and auditory decoding (Wilcoxon

signed rank test, $p<0.001$). Decoding for visual stimuli was higher than for auditory stimuli.

These modality focused RSA results suggest that the audiovisual presentation of an object

creates a more distinct representation between animate and inanimate objects when compared to

either of the corresponding unisensory presentations.

We further explored whether audiovisual presentations expanded exemplar distinctions within

animacy categories by calculating the mean within category pairwise decoding accuracies

(Figure 3E). In this analysis, onset latencies for significant decoding for auditory, visual, and

audiovisual stimuli were 89ms, 99ms, and 62ms, respectively. The corresponding peak decoding

latencies were 190ms, 140ms, and 152ms. The modality-specific comparisons for within-category decoding mirrored those seen for between-category decoding, with higher audiovisual decoding when compared with visual and auditory decoding, and higher visual decoding than auditory decoding (Wilcoxon signed rank test, p<0.001). A comparison of between-category decoding and within-category decoding demonstrated higher between-category decoding for visual and audiovisual stimulus presentations (Wilcoxon signed rank test, p<0.001) but no significant difference for auditory presentations (p>.05). In sum, when compared to unisensory presentations, audiovisual stimulus presentations not only expand the representational space between animacy categories, but also make exemplars within the animacy categories easier for a classifier to distinguish.

Figure 3 Representational Similarity Analysis: Sensory Modality Influences Between Animacy Category and Within Animacy Category Decoding. (A) RSA Schematic for pairwise decoding. Linear discriminate analysis with a 4-fold leave one-fold out cross validation was used for all exemplar pair combinations (B) Dissimilarity matrices for each of the modalities was built across time in 1 millisecond increments from pairwise exemplar classifications. (C) Mean between category and within category exemplar decoding accuracies were averaged across exemplars at each time point. (D-E) Resulting time series and summary bar plots for (D) between and (E) within categories for each of the modalities. Shaded area around lines indicates standard error across subjects. Asterisks indicate significant decoding above chance, corrected for multiple comparisons (Wilcoxon signed-rank test, FDR q = 0.025). Mean decoding across time (50ms to 600ms) for each modality with Wilcoxon signed-rank test P values (* p<0.05, ** p<0.01, *** p<0.001) above comparisons.

Category-Specific RSA: Audiovisual Presentations Selectively Enhance Inanimate Object Decoding

We further investigated representational space broken down by animacy categories to study the neural underpinnings for the observed reaction time differences between animate and inanimate categorization (Figure 4). Qualitatively, we noted that the decoding curves for animate and inanimate exemplars did not differ for auditory conditions (Figure 4A). However, this was not the case for visual exemplars, which appear to have higher decoding performance for animate exemplars when compared with inanimate exemplars. This distinction spanned the interval from approximately 100-200 ms after stimulus presentation (Figure 4B). Surprisingly, this difference is no longer apparent for audiovisual conditions. We quantified the difference between animacy categories by using the mean decoding performance during the stimulus period [50ms to 600ms]. This analysis confirmed that there was a significant animacy category difference, but only for the visual condition ($p<0.05$).

Since the audiovisual condition had overall higher within category pairwise decoding than the visual condition (Figure 3E), we probed whether the lack of an animate and inanimate within-category decoding difference for audiovisual presentations was due to visual inanimate objects incurring a special benefit from audiovisual presentation. Figure 4E shows the difference between audiovisual decoding and visual decoding for animate and inanimate exemplars. Notably, the difference is significantly above zero across several timepoints between 100-200 ms post stimulus onset for inanimate objects (Wilcoxon signed rank $p<0.025$, FDR corrected), but not for animate objects. Furthermore, a comparison of mean decoding performance difference across the 100-200 ms time period reveals a significant difference between animate and inanimate exemplars (Wilcoxon signed rank, $p=.001$). Together, these results suggest that audiovisual presentations may more strongly enhance the neural representations of inanimate objects when compared with animate objects.

Figure 4 Category-Specific RSA: Audiovisual Presentations Selectively Enhance Inanimate Object Decoding. (A-C) Audio, visual and audiovisual within category decoding for animate and inanimate exemplars. Asterisks indicate significant decoding above chance, corrected for multiple comparisons (Wilcoxon signed-rank test, FDR q = 0.025). (D) Mean decoding across time (50ms to 600ms) for each modality and category with Wilcoxon signed-rank test P values (* p<0.05, ** p<0.01, *** p<0.001) above comparisons. Shaded area around lines indicates standard error across subjects. (E) The audiovisual-visual within category decoding difference for animate and inanimate exemplars with asterisks indicating significant decoding differences above 0, corrected for multiple comparisons (Wilcoxon signed-rank test, FDR q = 0.025).

Representational Connectivity Analysis: Response Patterns between Areas in the Brain are Influenced by Object Category

Given that different sensory modalities and different object classes have been shown to engage different brain networks (Braga, Hellyer, Wise, & Leech, 2017; Hillebrandt, Friston, & Blakemore, 2014), we investigated whether the pairwise decoding differences we found using RSA would also be associated with differences in mean connectivity. To carry out this analysis, we constructed electrode specific representational dissimilarity matrices (RDMs) and performed Spearman correlations across all electrode combinations to calculate a mean representational connectivity measure between electrodes. The mean representational connectivity measure is an index of how similar the representational space is between electrodes. This value is driven by two factors: spatial proximity (i.e., neighboring electrodes will have higher connectivity) and

representational similarity due to stimulus features. We used the mean representational connectivity value prior to stimulus onset as our baseline, as neighboring electrodes will have shared signal even at rest (i.e. spatial autocorrelation). We found that the presentation of visual and audiovisual stimuli resulted in several timepoints that significantly diverged from baseline, and that these began at 107ms (Wilcoxon signed rank $p < 0.05$, FDR corrected), indicating increased representational connectivity across the electrodes following stimulus presentation. In contrast, significant timepoints were not found for the auditory condition. Similar to the RSA findings, we also found that the animate and inanimate category selectively affected connectivity measurements across the different sensory modalities. For auditory objects, connectivity rose significantly above baseline for animate exemplars at 380 ms without significantly rising above baseline inanimate exemplars. Likewise, for visual objects, mean connectivity for animate objects rose above baseline at 117 with no significant timepoints for inanimate exemplars. Overall, visual animate exemplars had a greater mean representational connectivity than inanimate exemplars over the entire stimulus period (Wilcoxon Signed Rank test, $p < 0.001$). In contrast, for audiovisual presentations, animate and inanimate categories did not demonstrate a mean difference over the stimulus period (Wilcoxon Signed Rank test, $p > .05$). In fact, despite a lack of an overall difference, inanimate objects diverge from baseline slightly earlier (i.e. 107 ms as opposed to 117 ms for animate objects). These results build off of the RSA analyses, and suggest that the presentation of objects in an audiovisual manner increase the representational connectivity when compared to when they are presented in a unisensory context, and furthermore that these connectivity measures increase to a greater extent for inanimate exemplars.

1
2
3
Figure 5: Representational Connectivity Analysis: Response Patterns between Areas in the
Brain are Influenced by Object Category. (A) Moving searchlight to create electrode specific
RDMs. The searchlight included the electrode of interest and every immediate surrounding
electrode to produce an electrode specific RDM for each modality. (B) Each electrode was
correlated in a pairwise fashion using a Spearman correlation. (C) This procedure was done for
all exemplars as well as within the animate and inanimate category along the timecourse (-100 to
600ms) to build time-resolved electrode similarity matrices of representational space. The mean
value of these matrices is the representational connectivity across all electrodes. (D-E)
Representational connectivity was measured (D) across modalities as well as (E) within the
animate and inanimate categories across modalities.
14
15
Distance-to-Bound Analysis: Behavior can be Predicted by Exemplar Distance to the
Decision Boundary in Representational Space
Having found both behavioral and neural differences between modality of presentation and
animacy categories, we next considered whether the two measures were associated with one
another. To do this, we computed the distance to the classifier decision boundary for all
exemplars and correlated these distances with behavioral performance (i.e., reaction times). A
negative correlation would denote that exemplars that are farthest away from the classifier
decision boundary are those that are most rapidly categorized. Indeed, Figure 6A shows a
significant negative Spearman correlation (Wilcoxon signed-rank test, FDR q = 0.025) between

representational distance and reaction time at several timepoints between 100-200 ms and

between 270-400 ms post-stimulus onset for both visual and audiovisual presentations. Auditory

presentations did not show any significant timepoints. Figure 6B shows the corresponding scatter

plot for the highest negative correlations in the 100-200 ms time window for visual and

audiovisual presentations. These plots show that for both visual and audiovisual presentations,

inanimate objects had slower categorization times than animate objects and were also closer to

the decision boundary. Additionally, consistent with our behavioral and RSA results, inanimate

exemplars appeared to show a greater shift along the reaction time and representational axes than

animate exemplars when comparing between visual and audiovisual scatter plots.

In Figure 6C, we quantified this observation by using a Spearman correlation to link the reaction

time difference for audiovisual versus visual exemplars with the representational difference for

animate and inanimate exemplars. A negative correlation denotes: 1) exemplars that were further

away from the decisional boundary for audiovisual presentations when compared with visual

presentations (positive AV-V distance value) are also the exemplars that demonstrated either

more of an audiovisual RT bias (positive AV-V RT value) or less of a visual bias (negative AV-

V RT value); and 2) exemplars that were further away from the decision boundary for visual

presentations when compared with audiovisual presentations (negative AV-V distance value) are

also the exemplars that demonstrated less of an audiovisual RT bias (positive AV-V RT value) or

more of a visual bias (negative AV-V RT value). We used a less conservative FDR q of 0.10 to

identify timepoints where representational distance differences show a marginally significant

correlation to reaction time differences. Using this criterion, we found several significant

timepoints between 100-200 ms and 370-450 ms post-stimulus for inanimate exemplars, but no

significant timepoints for animate exemplars. If we calculate the mean correlation across the

entire stimulus analysis epoch (50-600 ms post-stimulus) we find a significant negative

correlation for inanimate exemplars (Wilcoxon signed rank, r=-0.1661 p< 0.0001) but not for

animate exemplars (Wilcoxon signed rank, r=.0045 p=0.11). Figure 6D shows the corresponding

scatterplot with the highest negative correlation in the 100-200 ms window for visual and

audiovisual presentations at 163ms (same as figure 6B). Collectively, these results show

associations between neural decoding differences and behavioral performance differences

1   between audiovisual and visual stimulus presentations, but only when these stimuli are

2   inanimate.

4
5

Figure 6: Distance-to-Bound Analysis: Behavior can be predicted by Exemplar Distance to the
Decision Boundary in Representational Space. (A) Time-varying Spearman correlation
between mean exemplar representational distance from animacy discriminate bound and
respective average exemplar reaction time for each modality. Asterisks indicate a significant
spearman correlation below 0, corrected for multiple comparisons (Wilcoxon signed-rank test,
FDR q = 0.025). (B) Scatterplot for mean exemplar visual and audiovisual representational
distance and RT at a significant timepoint for both modalities.   (C) Time-varying Spearman
correlation between mean representational enhancement (Audiovisual-Visual distance) and mean
reaction time enhancement (Audiovisual-Visual RT). Note that asterisks in this plot only signify
a *marginally* significant spearman correlation below 0, corrected for multiple comparisons
(Wilcoxon signed-rank test, FDR q = 0.10). (D) Scatterplot for audiovisual representational and
RT enhancement at a marginally significant timepoint for inanimate exemplars.
18
19

Model Testing: Abstract Category Models Predicts Neural Activity Better than Low Level

Feature Models

To account for the potential contribution of low-level features to the neural RDMs, we

constructed contrast dissimilarity matrices for images and power spectral density dissimilarity

matrices for sounds as shown in Figure 7. The models were correlated to each subject's neural

RDM using a Spearman correlation, and tested for significance (FDR corrected, p<0.025) along

the time series ranging from 100 ms pre-stimulus to 600 ms post-stimulus. No significant

timepoint emerged from this analysis, suggesting that the neural RDMs are unlikely to be a result

of low-level stimulus features. In contrast, when we used an abstract model that ignored low

level features and instead separated stimuli based on object animacy category, we found a

significant correlation (FDR corrected, p<0.025) with the visual RDMs beginning at 118ms and

audiovisual RDMs at 106ms. The animacy model was not significantly correlated to the auditory

RDM, implying that the animacy distinction is not as prominent in audition.

Figure 7 Model Testing: Abstract Category Models Predicts Neural Activity Better than Low
Level Feature Models. (A) Category and low level visual and auditory feature models. The
animacy category model was constructed using a 0 for within animacy category exemplars and 1
for between animacy category exemplars. For the image contrast RDM, since all images were
black and white drawings, the contrast vector consisted of the intensity values of each image.
The power spectral density RDM was built using a Welch's power spectral density estimate and
converted to a single vector for each sound. Each RDM was then constructed by taking the
Spearman distance of each respective pairwise stimulus comparison. (B-D) Each model RDM
was then tested with the (B) Auditory, (C) Visual, (D) and Audiovisual time resolved RDMs on a
subject by subject basis. Shaded area around lines indicate standard error across subjects with

asterisks indicating a significant spearman correlation above 0, corrected for multiple comparisons (Wilcoxon signed-rank test, FDR q = 0.025).

Discussion

In this study, we leveraged the encoding bias that has been observed for animate objects over inanimate objects in vision and audition (Grootswagers, Ritchie, et al., 2017; Guerrero & Calvillo, 2016; Murray, 2006; Tzovara et al., 2012; Vogler & Titchener, 2011) to study how perceptual differences for visual and auditory object categories influence multisensory enhancement in audiovisual stimuli. We used behavioral measures and neural decoding, and the results provide additional support for previous findings that have shown perceptual advantages for animate objects over inanimate objects in both vision and audition (Grootswagers, Ritchie, et al., 2017; Guerrero & Calvillo, 2016; Murray, 2006; Tzovara et al., 2012; Vogler & Titchener, 2011). However, and somewhat surprisingly, we also found that the advantage for animacy was not evident when the objects are presented in a multisensory context (i.e., as audiovisual objects). Using representational similarity analysis, we show that this absence of a multisensory-mediated effect is evident despite an overall improvement in audiovisual neural decoding. Further analysis showed there was a greater enhancement for the decoding of inanimate objects under multisensory conditions, and that these objects are more weakly decoded when presented under visual only and audio only conditions. A distance to bound analysis provided critical links between neural decoding and behavioral performance. First, we found that improved neural decoding for visual and audiovisual objects was associated with faster reaction times in the animacy categorization task. Furthermore, the decoding differences between visual and audiovisual objects was also predictive of the reaction time differences between visual and audiovisual objects. Finally, a searchlight analysis and representational connectivity analysis showed that the presentation of objects in an audiovisual context may improve their encoding through increased representational connectivity between brain areas. Taken together, the results of our study provide new insights into the encoding of unisensory and multisensory objects, establishes critical links between neural activity and behavior in the context of object categorization, as well as explores potential mechanistic differences in multisensory integration for weakly and strongly encoded objects.

The reaction time bias for animate objects presented under both unisensory visual and auditory conditions is consistent with a number of previous studies (Grootswagers, Ritchie, et al., 2017; Guerrero & Calvillo, 2016; Murray, 2006; Tzovara et al., 2012; Vogler & Titchener, 2011). However, a small number of visual studies have reported a lack of bias for animate objects (Praß, Grimsen, König, & Fahle, 2013; VanRullen & Thorpe, 2001). The majority of these studies used visual stimuli with relatively small variability in their features, potentially explaining the discrepancy between studies. These studies and the effect of low-level features on categorization do, however point to the contribution stimulus features may have in the construction of higher-order categorical animate-inanimate distinctions in the brain.

While stimulus features clearly contribute to the formation of object categories, including the distinction between animate and inanimate objects, there is ample evidence that the animate-inanimate distinction transcends stimulus features and can be thought of as an abstract category distinction. The distinction is present for stimuli presented in both the visual and auditory modalities, suggesting that animacy is a general organizing principle. Furthermore, category-specific deficits in naming animate objects have been found in patients who have suffered brain damage (Capitani, Laiacona, Mahon, & Caramazza, 2003; Clarke et al., 2002; Kolinsky et al., 2002; VIgnolo, 1982; Vignolo, 2004; Warrington & Mccarthy, 1987). The category distinction is preserved across species; being present in both monkey inferotemporal (IT) cortex and human IT cortex. Furthermore, the use of carefully controlled stimuli that account for stimulus features have reinforced the categorical nature of animacy (Bracci, Ritchie, & de Beeck, 2017; Ritchie & Op De Beeck, 2018). Similarly, auditory studies have also provided evidence for animacy as an abstract category distinction (De Lucia et al., 2010; Giordano et al., 2013; Murray, 2006). In the current study, we corroborate these findings by showing a significant correlation between an animacy model and neural response patterns, but a lack of any correlation between low-level stimulus features such as visual contrast and auditory power spectrum with neural response patterns.

Given the frequently reported bias for animate objects presented in both visual and auditory contexts, it was somewhat surprising that the animacy advantage disappeared under conditions of multisensory presentation in our study. A similar reduction in animacy bias was observed in a

previous study that compared congruent audiovisual stimuli and auditory stimuli with visual

noise (Vogler & Titchener, 2011). One possible explanation for this lack of a multisensory

advantage for animate objects is that the brain may be preferentially integrating the visual and

auditory components of the more weakly encoded inanimate objects. In such a scenario, greater

multisensory integration for inanimate objects may serve to close the perceptual gap between

animate and inanimate objects. The presence of larger magnitudes of multisensory integration for

more weakly encoded stimuli is consistent with the concept of inverse effectiveness (Stein &

Meredith, 1993; Wallace, Ramachandran, & Stein, 2004). To test whether there were behavioral

differences in multisensory integration across categories, we examined our behavioral data for a

characteristic found in superior colliculus neurons: more balanced unisensory responses (i.e.

smaller differences between visual and auditory stimulus) yield the greatest multisensory

enhancement (Miller, Pluta, Stein, & Rowland, 2015). Behaviorally, if greater multisensory

integration occurs for inanimate objects, we would also expect a stronger relationship between

differences in unisensory reaction times and multisensory reaction times. In agreement, we found

that smaller RT differences between visual and auditory objects led to faster multisensory

reaction times for inanimate, but not for animate objects.

We subsequently set out to examine whether there was neural evidence in support of greater

audiovisual integration of inanimate objects. First, we used RSA and pairwise decoding

comparisons to show that audiovisual presentations of all objects had greater between-category

and within-category distances than their unisensory counterparts, suggesting a multisensory-

mediated enhancement in the distinction between animate and inanimate objects. Additionally,

audiovisual presentations had earlier decoding onsets and decoding peaks for both between-

category and within-category pairwise decoding. While the timing differences in decoding onsets

might be explained by differences in decoding magnitudes (Grootswagers, Wardle, et al., 2017),

the earlier decoding peak for audiovisual presentations does not have the same potential

confound. Overall, audiovisual presentations enhanced object encoding, consistent with findings

from recent studies (Brandman et al., 2019; Mercier & Cappe, 2019). Second, we specifically

investigated the behavioral bias we observed for animate objects. We found that only visual

presentations had statistically significant neural decoding differences between animate and

inanimate objects. Auditory decoding did not show the same bias we observed in behavior.

However, similar to behavior, the neural decoding bias was no longer present for audiovisual presentations. We determined that this reduction in visual bias was due to an overall enhancement in the decoding of inanimate objects.

While in large measure the neural decoding results generally complemented the behavioral results, we found that the neural decoding enhancement found for audiovisual presentations did not result in faster audiovisual reaction times. One possible explanation is that reaction times reached a performance floor for visual presentations, thus limiting the opportunity for audiovisual gain (Driver & Noesselt, 2008; Holmes, 2007). Another possibility is that the improved neural decoding results seen under audiovisual conditions is not a signal the brain is using for the task at hand (Grootswagers, Cichy, & Carlson, 2018). In other words, the added sensory information in audiovisual presentations provides the classifier with more information, but that information does not provide further value for the object categorization task. Moreover, the added information may not be of value for speeding reaction times but may be used for other aspects of the perceptual response not tapped in the current paradigm (e.g., response confidence).

In an effort to address these possibilities, we sought to directly link the neural results to the behavioral results at the exemplar level by using a distance to bound approach (Carlson et al., 2014; Grootswagers, Ritchie, et al., 2017; Ritchie et al., 2015). This approach is a data-driven way of determining the relationship between neural representational space and behavioral measures (i.e., reaction times). In this analysis, we found a significant relationship between visual and audiovisual decoding distances and reaction times during two distinct post-stimulus time epochs. One corresponded to peak decoding in our RSA analysis (i.e., 100-200 ms) and the other emerged approximately 150-200ms later. One plausible possibility is that these intervals represent periods of evidence accumulation in sensory areas and brain areas responsible for decision-making, respectively (Murray, Imber, Javitt, & Foxe, 2006; Tzovara et al., 2012). We next directly correlated multisensory neural decoding enhancements to reaction time improvements and found that only inanimate objects exhibited a significant relationship. Once again, these correlations were found in similar time periods.

To investigate the mechanism by which audiovisual presentations asymmetrically enhance the decoding of inanimate objects, we utilized representational connectivity analysis across all EEG sensors. Representational connectivity analysis has been previously used in more a limited way to assess how similar representations were between two brain areas (Kriegeskorte et al., 2008). In our analysis, we used a moving searchlight consisting of each electrode and its immediately surrounding neighbors to measure the different patterns of activity for each given stimulus. By doing so, we are able to use RCA as a tool to acquire a data driven measure of how similar response patterns are topographically across the brain. We predicted that animate and inanimate exemplars might demonstrate differences in connectivity measures, as previous studies have shown increased connectivity for biologically plausible motion over mechanical motion (Hillebrandt et al., 2014). Note that in this analysis neighboring electrodes will have shared signals simply due to proximity. Therefore, the importance of these connectivity measures is the *relative* difference between animate and inanimate categories. We found increased representational connectivity for animate objects when presented in vision and when compared with inanimate objects. However, much like for our RSA results, these connectivity differences were no longer present for when these objects were presented in an audiovisual context. Additionally, the connectivity increase for inanimate objects occurs within the 100-200 ms time epoch we have previously noted as the time period in which audiovisual presentations showed the greatest enhancement over visual presentations. One possible explanation for why connectivity measures disproportionately increase from visual to audiovisual presentations for inanimate objects is that there is increased audiovisual integration for inanimate objects relative to animate objects. This in turn leads to a greater spread of neural representation across brain areas. However, with the current analysis we cannot exclude the possibility that the increase in inanimate connectivity for audiovisual presentations may also be due a more localized spread within electrodes in close proximity.

In conclusion, our study introduces new insights into the brain's representation of sensory and multisensory information as it relates to object encoding. The greater neural encoding benefits for inanimate stimuli seen under audiovisual conditions compliments prior work, where sensory information was selectively removed from object stimuli, resulting in a selective contraction of the representational space of animate objects (Grootswagers, Ritchie, et al., 2017). Collectively,

these findings show that neural representational space and the encoding of objects is impacted by both semantic congruence and stimulus modality (stimulus combinations) in a dynamic fashion. Future directions of our current work include approaches to investigate the interplay between parametrically reducing neural encoding by degrading visual stimuli while simultaneously using audiovisual presentations to enhance neural encoding. Understanding the computational framework the brain uses to maximize the sensory information it captures across sensory systems has broad implications for how stimuli perturbations and sensory integration affects object encoding.

Methods

Participants

The experiment included 14 adults (9 men) aged 27± 4.2 years. All subjects had normal or corrected-to-normal vision and reported normal hearing. The study was conducted in accordance with the Declaration of Helsinki, and all subjects provided their informed consent to participate in the study. Each participant was compensated financially for their participation. The experimental procedures were approved by the Ethics Committee of the Vaudois University Hospital Center and University of Lausanne. One subject was removed due to poor signal quality with several artifacts present in the evoked potential response.

Stimuli

The experiment took place in a sound-attenuated chamber (Whisper room), where subjects were seated centrally in front of a 20" computer monitor (HP LP2065) and located ~ 140 cm away from them (visual angle of objects ~ 4°). The auditory stimuli were presented over insert earphones (Etymotic model: ER4S), and the volume was adjusted to a comfortable level (~62dB). The stimuli were presented and controlled by E-Prime 2.0, and all behavioral data were recorded in conjunction with a serial response box (Psychology Software Tools, Inc.; www.pstnet.com). The auditory stimuli included 48 animate and 48 inanimate sounds from a library of 500ms-duration sounds, used in previous studies and have been evaluated in regard to their acoustics and psychoacoustics as well as brain responses as a function of semantic category (De Lucia et al., 2010; Murray, 2006; Thelen, Cappe, & Murray, 2012) The visual stimuli were semantically congruent line drawings that were taken from a standardized set (Snodgrass & Vanderwart, 1980) or obtained from an online library (dgl.microsoft.com).

Experiment Design

Participants performed 10-13 experimental blocks (median 11 blocks) of a Go/No-Go task. Each

block contained 1 audio, visual, and audiovisual presentation for each of the 96 stimuli

exemplars, totaling 288 stimulus presentations per block. For half of the blocks subjects were

instructed to press a button when they perceived an animate object and for the other half when

they perceived an inanimate object. Animate and inanimate blocks were randomized for each

subject. Auditory, visual, and synchronous audiovisual stimuli were presented for 500ms,

followed by a randomized interstimulus interval (ISI) ranging from 900 to 1500ms, and

participants had to respond within this 1.4-2s window. Stimuli modality was randomized for

each trial (see Figure 1 for schematic). To control for motor confounds, the block instructions

alternated between indicating whether the stimuli was animate or inanimate (Grootswagers,

Wardle, et al., 2017). Reaction times and accuracy were measured for each response. Participants

did not receive feedback during the experiment.

EEG acquisition and preprocessing

Continuous EEG was acquired from 160 scalp electrodes (sampling rate at 1024 Hz) using a

Biosemi ActiveTwo system. Data preprocessing was performed offline using the Fieldtrip

toolbox (Oostenveld, Fries, Maris, & Schoffelen, 2011) in MATLAB. Data were filtered using a

Butterworth IIR filter with 1 Hz highpass, 60 Hz lowpass, and notch at 50Hz. All channels were

rereferenced to an average reference. Epochs were created for each stimulus presentation ranging

from -100ms to 600ms relative to stimulus onset. Each epoch was baseline corrected using the

prestimulus period. Artifact-contaminated trials were identified and removed following visual

inspection. On average 3.6± 4.7 trials were rejected. The resulting channel voltages at each time

point were used for the remainder of the analysis.

Representational Similarity Analysis

Following data preprocessing, we used CoSMoMVPA (Oosterhof, Connolly, & Haxby, 2016)

and custom scripts to perform cross-validated representational similarity analysis (RSA). We

used a linear discriminate classifier with 4-fold, leave one-fold out cross validation, for all

exemplar pair combinations across audio, visual, and audiovisual stimuli presentations. In this

procedure, trials are randomly assigned to one of four subsets of data. Three of the four subsets

(75% of the data) are then pooled together to train the classifier and then decoding accuracy is tested on the remaining subset (25% of the data). This procedure is repeated a total of four times, such that each of the subsets is tested at least once. Decoding results are reported in percent correct of classifications at each time point for each exemplar pair in the time series [-100ms 600ms]. This analysis was conducted independently to build representational dissimilarity matrices (RDM) for each subject and modality over 1 millisecond increments. The RDMs were then separated into animate exemplar pairwise comparisons, inanimate exemplar pairwise comparisons, and pairwise comparisons between categories. Using these comparison groupings, mean decoding accuracies were then calculated for each modality and subject. Significant above-chance accuracies were assessed using a non-parametric Wilcoxon signed rank test, FDR ($\square$=.025) corrected for multiple comparisons.

Representational Connectivity Analysis

To characterize connectivity changes for different modalities and object categories, we used a combination of a searchlight analysis and representational connectivity analysis (Kriegeskorte et al., 2008). Due to this analysis being computationally-intense, data was downsampled to 100 Hz. Electrode specific RDMs, using the same procedure describe for the RSA analysis, were built by using a moving searchlight which included the electrode of interest and every immediate adjacent electrode. Electrode-specific RDMs were then correlated to each other in pairwise fashion for each electrode combination using a Spearman correlation. Note that the searchlight will change sizes depending on the chosen electrode and searchlights will overlap for electrodes and thus there will be a baseline level of connectivity in neighboring electrodes. Therefore, all connectivity measurements were compared to baseline connectivity values prior to stimulus presentation. This procedure was done for all exemplars as well as within the animate and inanimate category along the timeseries [-100ms 600ms] to compute time-resolved representational connectivity measures.

Distance to Bound Analysis

To link neural representational space back to individual exemplar categorization times, we used a distance to bound analysis (for review see Ritchie & Carlson, 2016). Similar to RSA, this analysis represents individual exemplars as points in representational space. To decode animacy,

we apply linear discriminant analysis to the representational space, defining an optimal decision boundary that separates animate and inanimate exemplars. The distance to the boundary in representational space is then computed for each exemplar across timepoints along the timeseries [-100ms 600ms]. Next, we matched mean distance and the mean exemplar reaction time for each exemplar. We then performed a time-varying Spearman correlation between mean exemplar distance and mean exemplar reaction time for each modality.

Model Fitting

To account for low level visual features in our visual and auditory stimuli, we constructed model RDMs and calculated their partial correlations to the neural RDM. The low-level feature auditory RDM was constructed using a Welch's power spectral density (PSD) estimate for each of the 96 sounds. The resulting stimulus PSD was then organized into vectors and pairwise non-parametric spearman distance measurements were calculated for all exemplar pair combinations to form a model RDM. We then calculated the partial Spearman correlations between the PSD model RDM and the modality specific neural RDMs at each timepoint. An identical procedure was followed for the visual images, but instead of using PSD, image contrast was used. Note that since the images were black and white Snodgrass images, the contrast values will be equivalent to the image intensity values. In addition to these low-level feature models, we also constructed an abstract animacy category model. The animacy category model was constructed using a 0 to indicate no differences between stimuli pairs for within animacy category exemplars and a 1 to indicate complete dissimilarity for between category exemplars. This model was then also tested across modality specific neural RDMs.

Acknowledgements

This work was supported by a NIGMS of the National Institutes of Health (T32GM007347). MMM is supported by the Swiss National Science Foundation (n°169206), The Fondation Asile des aveulges (n°232933), and a grantor advised by Carigest SA. We are grateful to Céline Cappe for technical assistance during data acquisition and Tijl Grootswagers for helpful comments on earlier drafts of the manuscript.

Authors' information

Affiliations

Multisensory Research Laboratory, Vanderbilt University, Tennessee, USA. David A. Tovar &

Mark Wallace

Laboratory for Investigative Neurophysiology, University of Lausanne, Lausanne, Switzerland.

Micah Murray

Author's Contributions

D.A.T., M.M. and M.T.W conceptualized the study. M.M. collected the data. D.A.T.

preprocessed the data. D.A.T. performed the main data analyses and created all figures. D.A.T.,

M.M and M.T.W. wrote the initial draft of the paper. All authors revised the paper and approved

the final version of the manuscript.

Competing interests

Authors declare no conflicts of interest.

Corresponding author

Correspondence to David A. Tovar

References

Alais, D., & Burr, D. (2004). Ventriloquist Effect Results from Near-Optimal Bimodal
Integration. *Current Biology*, *14*(3), 257–262. https://doi.org/10.1016/S0960-
9822(04)00043-0
Angelaki, D. E., Klier, E. M., & Snyder, L. H. (2009). A Vestibular Sensation: Probabilistic
Approaches to Spatial Perception. *Neuron*, *64*(4), 448–461.
https://doi.org/10.1016/j.neuron.2009.11.010
Belin, P., Zatorre, R. J., Lafaille, P., Ahad, P., & Pike, B. (2000). Voice-selective areas in human
auditory cortex. *Nature*, *403*, 309–312.
Bracci, S., Ritchie, J. B., & de Beeck, H. O. (2017). On the partnership between neural
representations of object categories and visual features in the ventral visual pathway.
Neuropsychologia, *105*(June), 153–164.
https://doi.org/10.1016/j.neuropsychologia.2017.06.010
Braga, R. M., Hellyer, P. J., Wise, R. J. S., & Leech, R. (2017). Auditory and visual connectivity
gradients in frontoparietal cortex. *Human Brain Mapping*, *38*(1), 255–270.

https://doi.org/10.1002/hbm.23358

Brandman, T., Avancini, C., Leticevscaia, O., & Peelen, M. V. (2019). Auditory and Semantic Cues Facilitate Decoding of Visual Object Category in MEG. *Cerebral Cortex*, (June), 1–10. https://doi.org/10.1093/cercor/bhz110

Capitani, E., Laiacona, M., Mahon, B., & Caramazza, A. (2003). *What are the facts of semantic category-specific deficits? A critical review of the clinical evidence*. *Cognitive Neuropsychology* (Vol. 20). https://doi.org/10.1080/02643290244000266

Carlson, T. A., Ritchie, J. B., Kriegeskorte, N., Durvasula, S., & Ma, J. (2014). Reaction Time for Object Categorization Is Predicted by Representational Distance. *Journal of Cognitive Neuroscience*, *26*(1), 132–142. https://doi.org/10.1162/jocn_a_00476

Carlson, T., Tovar, D., Alink, A., & Kriegeskorte, N. (2013). Representational dynamics of object vision: The first 1000 ms. *Journal of Vision*, *13*(10), 1–19. https://doi.org/10.1167/13.10.1.doi

Cichy, R. M., Pantazis, D., & Oliva, A. (2014). Resolving human object recognition in space and time. *Nature Neuroscience*, *17*(3), 455–462. https://doi.org/10.1038/nn.3635

Clarke, S., Bellmann Thiran, A., Maeder, P., Adriani, M., Vernet, O., Regli, L., … Thiran, J. P. (2002). What and where in human audition: Selective deficits following focal hemispheric lesions. *Experimental Brain Research*, *147*(1), 8–15. https://doi.org/10.1007/s00221-002-1203-9

Corbetta, M., Miezin, F., Dobmeyer, S., Shulman, G., & Petersen, S. (1990). Attentional modulation of neural processing of shape, color, and velocity in humans. *Science*, *248*(4962), 1556–1559. https://doi.org/10.1126/science.2360050

De Lucia, M., Clarke, S., & Murray, M. M. (2010). A Temporal Hierarchy for Conspecific Vocalization Discrimination in Humans. *Journal of Neuroscience*, *30*(33), 11210–11221. https://doi.org/10.1523/JNEUROSCI.2239-10.2010

Downing, P. E., Jiang, Y., Shuman, M., & Kanwisher, N. (2001). A cortical area selective for visual processing of the human body. *Science*, *293*(5539), 2470–2473. https://doi.org/10.1126/science.1063414

Driver, J., & Noesselt, T. (2008). Multisensory Interplay Reveals Crossmodal Influences on "Sensory-Specific" Brain Regions, Neural Responses, and Judgments. *Neuron*, *57*(1), 11–23. https://doi.org/10.1016/j.neuron.2007.12.013

Giordano, B. L., McAdams, S., Zatorre, R. J., Kriegeskorte, N., & Belin, P. (2013). Abstract encoding of auditory objects in cortical activity patterns. *Cerebral Cortex*, *23*(9), 2025–2037. https://doi.org/10.1093/cercor/bhs162

Grootswagers, T., Cichy, R. M., & Carlson, T. A. (2018). Finding decodable information that can be read out in behaviour. *NeuroImage*, *179*(June), 252–262. https://doi.org/10.1016/j.neuroimage.2018.06.022

Grootswagers, T., Ritchie, J. B., Wardle, S. G., Heathcote, A., & Carlson, T. A. (2017). Asymmetric Compression of Representational Space for Object Animacy Categorization under Degraded Viewing Conditions. *Journal of Cognitive Neuroscience*, *29*(12), 1995–2010. https://doi.org/10.1162/jocn_a_01177

Grootswagers, T., Wardle, S. G., & Carlson, T. A. (2017). Decoding Dynamic Brain Patterns from Evoked Responses: A Tutorial on Multivariate Pattern Analysis Applied to Time Series Neuroimaging Data. *Journal of Cognitive Neuroscience*, *29*(4), 677–697. https://doi.org/10.1162/jocn_a_01068

Guerrero, G., & Calvillo, D. P. (2016). Animacy increases second target reporting in a rapid

serial visual presentation task. *Psychonomic Bulletin and Review*, *23*(6), 1832–1838. https://doi.org/10.3758/s13423-016-1040-7

Hillebrandt, H., Friston, K. J., & Blakemore, S. J. (2014). Effective connectivity during animacy perception - Dynamic causal modelling of Human Connectome Project data. *Scientific Reports*, *4*, 1–9. https://doi.org/10.1038/srep06240

Holmes, N. P. (2007). The law of inverse effectiveness in neurons and behaviour: Multisensory integration versus normal variability. *Neuropsychologia*, *45*(14), 3340–3345. https://doi.org/10.1016/j.neuropsychologia.2007.05.025

Jackson, R. E., & Calvillo, D. P. (2013). Evolutionary Psychology. *Evolutionary Psychology*, *11*(5), 1011–1026. https://doi.org/10.1177/147470491301100506

Kanwisher, N., McDermott, J., & Chun, M. M. (1997). The fusiform face area: a module in human extrastriate cortex specialized for face perception. *The Journal of Neuroscience : The Official Journal of the Society for Neuroscience*, *17*(11), 4302–4311. https://doi.org/10.1098/Rstb.2006.1934

Kolinsky, R., Fery, P., Messina, D., Peretz, I., Evinck, S., Ventura, P., & Morais, J. (2002). The fur of the crocodile and the mooing sheep: A study of a patient with a category-specific impairment for biological things. *Cognitive Neuropsychology*, *19*(4), 301–342. https://doi.org/10.1080/02643290143000196

Körding, K. P., Beierholm, U., Ma, W. J., Quartz, S., Tenenbaum, J. B., & Shams, L. (2007). Causal inference in multisensory perception. *PLoS ONE*, *2*(9). https://doi.org/10.1371/journal.pone.0000943

Kriegeskorte, N, Mur, M., Ruff, D., & Kiani, R. (2008). Matching categorical object representations in inferior temporal cortex of mand and monkey. *Neuron*, *60*(6), 1126–1141. https://doi.org/10.1016/j.neuron.2008.10.043.Matching

Kriegeskorte, Nikolaus, Mur, M., & Bandettini, P. A. (2008). Representational similarity analysis – connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*, *2*, 4. https://doi.org/10.3389/neuro.06.004.2008

Laws, K. R. (2000). Category-specific naming errors in normal subjects: The influence of evolution and experience. *Brain and Language*, *75*(1), 123–133. https://doi.org/10.1006/brln.2000.2348

Lindh, D., Sligte, I. G., Assecondi, S., Shapiro, K. L., & Charest, I. (2019). Conscious perception of natural images is constrained by category-related visual features. https://doi.org/10.1101/509927

Mercier, M. R., & Cappe, C. (2019). The interplay between multisensory integration and perceptual decision making, 1–26.

Miller, R. L., Pluta, S. R., Stein, B. E., & Rowland, B. A. (2015). Relative Unisensory Strength and Timing Predict Their Multisensory Product. *Journal of Neuroscience*, *35*(13), 5213–5220. https://doi.org/10.1523/jneurosci.4771-14.2015

Murray, M. M. (2006). Rapid Brain Discrimination of Sounds of Objects. *Journal of Neuroscience*, *26*(4), 1293–1302. https://doi.org/10.1523/JNEUROSCI.4511-05.2006

Murray, M. M., Imber, M. L., Javitt, D. C., & Foxe, J. J. (2006). Boundary Completion Is Automatic and Dissociable from Shape Discrimination. *Journal of Neuroscience*, *26*(46), 12043–12054. https://doi.org/10.1523/jneurosci.3225-06.2006

Nastase, S. A., Connolly, A. C., Oosterhof, N. N., Halchenko, Y. O., Guntupalli, J. S., Visconti, M., … Haxby, J. V. (2017). Attention Selectively Reshapes the Geometry of Distributed Semantic Representation. *Cerebral Cortex*, 1–15. https://doi.org/10.1093/cercor/bhx138

New, J., Cosmides, L., & Tooby, J. (2007). Category-specific attention for animals reflects ancestral priorities, not expertise. *Proceedings of the National Academy of Sciences*, *104*(42), 16598–16603. https://doi.org/10.1073/pnas.0703913104

Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J. M. (2011). FieldTrip: Open source software for advanced analysis of MEG, EEG, and invasive electrophysiological data. *Computational Intelligence and Neuroscience*, *2011*. https://doi.org/10.1155/2011/156869

Oosterhof, N. N., Connolly, A. C., & Haxby, J. V. (2016). CoSMoMVPA: Multi-Modal Multivariate Pattern Analysis of Neuroimaging Data in Matlab/GNU Octave. *Frontiers in Neuroinformatics*, *10*(July), 27. https://doi.org/10.3389/fninf.2016.00027

Patten, M. L., Mannion, D. J., & Clifford, C. W. G. (2017). Correlates of Perceptual Orientation Biases in Human Primary Visual Cortex. *The Journal of Neuroscience*, *37*(18), 4744–4750. https://doi.org/10.1523/jneurosci.3511-16.2017

Posner, M. I. (1980). Orienting of attention. *Quarterly Journal of Experimental Psychology*, *32*(1), 3–25. https://doi.org/10.1080/00335558008248231

Praß, M., Grimsen, C., König, M., & Fahle, M. (2013). Ultra Rapid Object Categorization: Effects of Level, Animacy and Context. *PLoS ONE*, *8*(6), 2–11. https://doi.org/10.1371/journal.pone.0068051

Ritchie, J. B., & Carlson, T. A. (2016). Neural decoding and "inner" psychophysics: A distance-to-bound approach for linking mind, brain, and behavior. *Frontiers in Neuroscience*, *10*(APR), 1–8. https://doi.org/10.3389/fnins.2016.00190

Ritchie, J. B., & Op De Beeck, H. (2018). Using neural distance to predict reaction time for categorizing the animacy, shape, and abstract properties of objects, 1–19. https://doi.org/10.1101/496539

Ritchie, J. B., Tovar, D. A., & Carlson, T. A. (2015). Emerging Object Representations in the Visual System Predict Reaction Times for Categorization. *PLoS Computational Biology*, *11*(6). https://doi.org/10.1371/journal.pcbi.1004316

Snodgrass, J. G., & Vanderwart, M. (1980). A Standardized Set of 260 Pictures : Norms for Name Agreement , Image Agreement , Familiarity , and Visual Complexity. *Journal of Experimental Psychology*, *6*(2), 174–215.

Stein, B. E., & Meredith, M. A. (1993). *The merging of the senses*. Cambridge, MA: The MIT Press.

Thelen, A., Cappe, C., & Murray, M. M. (2012). Electrical neuroimaging of memory discrimination based on single-trial multisensory learning. *NeuroImage*, *62*(3), 1478–1488. https://doi.org/10.1016/j.neuroimage.2012.05.027

Tzovara, A., Murray, M. M., Plomp, G., Herzog, M. H., Michel, C. M., & De Lucia, M. (2012). Decoding stimulus-related information from single-trial EEG responses based on voltage topographies. *Pattern Recognition*, *45*(6), 2109–2122. https://doi.org/10.1016/j.patcog.2011.04.007

van den Hurk, J., Van Baelen, M., & Op de Beeck, H. P. (2017). Development of visual category selectivity in ventral visual cortex does not require visual experience. *Proceedings of the National Academy of Sciences*, *114*(22), E4501–E4510. https://doi.org/10.1073/pnas.1612862114

VanRullen, R., & Thorpe, S. J. (2001). Is it a bird? Is it a plane? Ultra-rapid visual categorisation of natural and artifactual objects. *Perception*, *30*(6), 655–668. https://doi.org/10.1068/p3029

VIgnolo, L. (1982). Auditory agnosia. *Philosophical Transactions of the Royal Society B*, *298*, 49–57.

Vignolo, L. A. (2004). Music Agnosia and Auditory Agnosia. *Annals of the New York Academy of Sciences*, *999*(1), 50–57. https://doi.org/10.1196/annals.1284.005

Vogler, J. N., & Titchener, K. (2011). Cross-modal conflicts in object recognition: Determining the influence of object category. *Experimental Brain Research*, *214*(4), 597–605. https://doi.org/10.1007/s00221-011-2858-x

Wallace, M. T., Ramachandran, R., & Stein, B. E. (2004). A revised view of sensory cortical parcellation. *Proceedings of the National Academy of Sciences*, *101*(7), 2167–2172. https://doi.org/10.1073/pnas.0305697101

Warrington, E. K., & Mccarthy, R. A. (1987). Categories of knowledge: Further fractionations and an attempted integration. *Brain*, *110*(5), 1273–1296. https://doi.org/10.1093/brain/110.5.1273

Yuval-Greenberg, S., & Deouell, L. Y. (2009). The dog's meow: Asymmetrical interaction in cross-modal object recognition. *Experimental Brain Research*, *193*(4), 603–614. https://doi.org/10.1007/s00221-008-1664-6