Optimising network modelling methods for fMRI

Usama Pervaiz[a,1], Diego Vidaurre[b], Mark W. Woolrich[b], Stephen M. Smith[a]

[a]*Oxford Centre for Functional MRI of the Brain (FMRIB), Wellcome Centre for Integrative Neuroimaging, Nuffield Department of Clinical Neurosciences, University of Oxford, Oxford OX3 9DU, United Kingdom*
[b]*Oxford Centre for Human Brain Activity (OHBA), Wellcome Centre for Integrative Neuroimaging, Department of Psychiatry, University of Oxford, Oxford, OX3 7JX, United Kingdom*

Abstract

A major goal of neuroimaging studies is to develop predictive models to analyse the relationship between whole brain functional connectivity patterns and behavioural traits. However, there is no single widely-accepted standard pipeline for analyzing functional connectivity. The common procedure for designing functional connectivity based predictive models entails three main steps: parcellating the brain, estimating the interaction between defined parcels, and lastly, using these integrated associations between brain parcels as features fed to a classifier for predicting non-imaging variables e.g., behavioural traits, demographics, emotional measures, etc. There are also additional considerations when using correlation-based measures of functional connectivity, resulting in three supplementary steps: utilising Riemannian geometry tangent space parameterization to preserve the geometry of functional connectivity; penalizing the connectivity estimates with shrinkage approaches to handle excessive noise; and removing confounding variables from brain-behaviour data. These six steps are contingent on eachother, and to optimise a general framework one should ideally examine these various methods simultaneously. In this paper, we investigated strengths and short-comings, both independently and jointly, of the following measures: parcellation techniques of four kinds (categorized further depending upon number of parcels), five measures of functional connectivity, the decision of staying in the ambient space of connectivity matrices or in tangent space, the choice of applying shrinkage estimators, six alternative techniques for handling confounds and finally four novel classifiers. For performance evaluation, we have selected two of the largest datasets, UK Biobank and the Human Connectome Project resting state fMRI data, and have run more than 6000 assorted pipelines on total of ∼14000 individuals to determine the optimum pipeline.

Keywords: Functional Connectivity, Connectome, Netmat, Riemannian, Deep Learning, Convolutional Neural Networks

---

1. Introduction

It is valuable to understand large-scale networks of brain activity. Most of the literature is focused on recognizing brain networks that are spatially and temporally linked to a given task [1]. In this paper, we aim to explore brain networks measured from resting state functional magnetic resonance imaging (rfMRI). In contrast to task-based fMRI, during rfMRI the brain is not occupied by a pre-defined task. However, studies have shown that the brain activity at rest is not random [2], but is hierarchically organized in time and significantly correlated with behaviour [3].

The analysis of rfMRI data largely relies on estimates of functional connectivity. Functional connectivity is defined as the statistical association between time-series of anatomically distinct brain regions

---

[1]Corresponding Author: Usama Pervaiz: usama.pervaiz@ndcn.ox.ac.uk

[4], which in fMRI is typically calculated as zero-lag correlation. To simplify, if two brain regions have blood-oxygen-level-dependent (BOLD) signals that are correlated, it means they are functionally connected. Functional connectivity is dynamic- it can be observed to change over time [3]. Contrasting with this metric is static connectivity, which is an average of all dynamic connectivity states, and is thereby is less noisy. Static (or average) connectivity is also simpler to estimate and interpret, and is at this point in more common usage. The methodological research conducted in this article is purely based on exploring static functional connectivity.

A number of research studies have shown the utility of functional connectivity in identifying neuropsychiatric disorders such as Alzheimer's disease [6], depression [7], social anxiety disorder [8] autism spectrum disorder [9], Parkinson's disease [10] and schizophrenia [11]. Resting state functional connectivity also has been shown to correlate with emotional measures [12] and behavioral performance [13, 14]. Overall, functional connectivity is gaining visibility a salient tool for assessing functional brain organization and as an important biomarker for neurological disorders.

As the rfMRI scan is composed of thousands of voxels at each time-point per subject, this poses extreme challenges to working with raw voxel-wise time-series data. To avoid working in high dimensional space (and to increase interpretability and effective SNR), the standard processing procedure entails the determination of parcels which are defined over a group of voxels sharing similar timecourses. However, the method by which the brain is segmented into these different regions, or parcels, before estimating functional connectivity is far from standardized. Some of the existing parcellation techniques are based on mapping anatomical or functional atlases onto an individual's brain [16, 17, 18]. Other brain parcellation techniques are more data driven and attempt to derive parcels based upon common features within the data [19, 20, 21]. After parcellating the brain, the next step is estimating functional connectivity. Functional connectivity is conventionally estimated through taking a full (Pearson) correlation between brain parcels over time [15]. The use of full correlation in deriving these estimates however, has some drawbacks as this method does not distinguish direct vs. indirect pathways by which two brain regions may be connected [22]. Additionally, the utilization of this method results in numerous other limitations related to low SNR, primarily because of short scanning sessions. This paper provides a detailed account of several functional connectivity estimation techniques that may mitigate these challenges, which consequently can result in enhanced sensitivity in signal detection.

After derivation of brain parcels and functional connectivity estimates, there remains further decisions of how to optimally utilize these in conjunction with other data, such as behavioral metrics. The commonly followed procedure is to directly use elements of correlation-based functional connectivity estimates as features for regression or classification algorithms. This direct usage however has fallen subject to criticism, as correlation-based functional connectivity does not naturally form a Euclidean space [23, 24]. In this paper, we evaluate an arguably more principled approach to represent correlation-based functional connectivity using Riemannian geometry [23, 24]. This method is founded upon mathematical principles which involve manipulating correlation-based estimates in the tangential space of Riemannian manifold [26] where Euclidean geometry can be applied.

Additionally, there is also a concern of noise causing an increase in inter- and intra-subject variance in functional connectivity estimates. One method to alleviate this is to apply conventional regularisation techniques in the ambient space when functional connectivity is estimated. The other approach is to apply covariance shrinkage estimators [27] in the tangential space of Riemannian manifold. In this paper, we have evaluated the effects of covariance shrinkage techniques both in the ambient space and the tangent space (isotropic [28] and non-isotropic covariance shrinkage techniques [29]) on the prediction of individual

demographic and behavioural phenotypes. Moreover, we have assessed the performance of shrinkage approaches in following framework, (i) no shrinkage in the ambient space or the tangent space, (ii) shrinkage in the ambient space but no shrinkage in the tangent space, (iii) no shrinkage in the ambient space but shrinkage in the tangent space, and (iv) shrinkage approaches both in the ambient space and the tangent space.

To predict individual phenotypes from rfMRI data, the elements of the functional connectivity matrix, where each element represents the strength of connection between two parcels, can be used as input features for a machine learning classifier (or continuous variable predictor). In this paper, we compare the performance of a selection of existing state of art methods with several proposed deep learning based architectures. We also demonstrate a baseline application for using neural networks in brain functional connectivity modelling.

There is currently no general agreement on a single common pipeline for estimating and using functional connectivity. We aim to help with this situation by answering several major questions:

1. How should we parcellate the brain? Should this technique be data driven or based upon hard parcellation? How many parcels should we derive?
2. How should we estimate correlation-based functional connectivity? Should we remain with full, or partial correlation, or do we have better choices?
3. Should we preserve the geometry and shape of correlation-based functional connectivity elements within a Riemannian framework, and what would be the optimal way to do this?
4. Should we utilize covariance shrinkage estimators? Should shrinkage occur in ambient space of covariances or in tangent space?
5. How should we remove the effect of confounding variables in rfMRI?
6. Which classifier/predictor provides optimal prediction of age, sex and other non-imaging variables using these functional connectivity estimates? Is a deep learning approach of value?

The questions raised above may be treated as six steps to derive a framework for estimation and accurate usage of functional connectivity estimates. This paper will attempt to address the above questions in order to propose a comprehensive pipeline that takes into account several central methodological issues when estimating and using functional connectivity.

For performance evaluation of the different methods, we have chosen two rich datasets which contain both rfMRI and phenotypic data. The first is 13301 subjects from UK Biobank (UKB) [32] and other is 1003 healthy subjects from the Human Connectome project (HCP) [33]. Our assessment criteria are based on the prediction accuracy of age, sex, fluid intelligence and neuroticism score, using correlation-based functional connectivity estimates. To establish the most optimum and reliable pipeline, we have run more than 6000 combinations of different steps of methodology detailed below. This computation has involved thousands of hours of computing on both CPUs and GPUs. The overall methodology is summarized in Figure 1.

Figure 1: Flow chart summarizing the six major steps of the methodology framework for rfMRI analysis.

2. Methods

2.1. *Finding the best parcellation approach*

The standard procedure for parcellation entails the grouping of voxels sharing similar time-courses into parcels. A parcel can be any spatial region of the brain, associated with a single time course (found by averaging the spontaneous fluctuation over all voxels within the parcel). For our analyses, we considered the following spatial properties in parcels, 1) parcels may or may not be allowed to overlap, 2) parcels can have both positive and negative spatial weight, or be binary masks 3) parcels may be composed from multiple disconnected regions.

Following the above criteria, we estimated parcels (spatial maps and associated time-series) across the brain using four different methods. In the literature, parcels can also be referred as nodes, modes, networks or region of interests, but here for simplicity and continuity, we will only refer to them as parcels. We only consider rfMRI-driven parcellations, as there is plenty of existing evidence that these outperform parcellations derived from pre-defined structural atlases [34, 35, 36].

2.1.1. *Data-driven Parcellation: SHEN functional Parcels*

The simplest way to identify parcels is to extract time courses from pre-defined, labelled regions, which often come from anatomical atlases. For resting state studies, a preferred method is to use a functional brain atlas based on correlated BOLD signal, rather than anatomical distinctions [35]. In this study, we applied a functional brain atlas known as the SHEN parcellation [16] which covers the cortex, subcortex and cerebellum. To derive the SHEN atlas, a spectral clustering method was applied which ensured the functional homogeneity within each parcel [16]. SHEN parcellation is based on rfMRI data of 79 healthy normal volunteers and provides more coherent resting state time-course estimates when compared with anatomical atlases. The total number of parcels in SHEN parcellation is 268. SHEN is a volumetric parcellation, and for both UKB and HCP data, we used the preprocessed released data in standard volumetric

space after ICA FIX denoising [37].

2.1.2. *Data-driven Parcellation: YEO functional Parcels*

We applied another functional brain atlas known as the YEO parcellation [38]. The YEO parcellation is based on rfMRI data from 1489 subjects which were registered using surface-based alignment. To derive the YEO atlas, a gradient weighted Markov random field approach was employed which integrates local gradient and global similarity approaches. This ensured the parcels were functionally and connectionally homogeneous, and also agreed with the boundaries of certain cortical areas defined using histology and visuotopic fMRI. The YEO parcellation is available at multiple resolution levels, and we have applied the YEO parcellation where the total number of parcels is 100. The YEO parcellation is available both in volumetric and grayordinate space. For HCP data, we use the minimally-preprocessed released data in grayordinates, and for UKB data, we used the preprocessed released data in standard volumetric space.

2.1.3. *Data Driven Soft Parcellation: Spatially Independent Parcels*

We also applied a popular data-driven parcellation scheme called Group Independent Component Analysis, or GroupICA [30, 31] to our data. There are two popular variants of GroupICA, spatial ICA (sICA), which identifies spatially independent components, and temporal ICA (tICA) [39], which put restrictions on temporal dynamics. The parcels identified by tICA are coerced to have orthogonal time-series which therefore precludes further network analyses of the kind covered in this paper. Therefore, we opted for sICA and applied sICA by concatenating the time courses from all subjects and applying the ICA algorithm to the group data. The ICA parcels can be spatially overlapping and non-contiguous. The dimensionality (d) of sICA corresponds to the number of desired parcels. For HCP data, we applied sICA at d = 15, 50 and 200, and for UKB, d = 25 and 100. With UKB data, we disregarded four components from ICA 25, and 45 components from ICA 100 as they were judged to be artefacts. This left us with d = 21, and 55 for UKB. For HCP data we use the minimally-preprocessed released data, in grayordinates (cortical surface vertices and subcortical voxels), with ICA FIX denoising having been applied [37]. For UKB data, we used the preprocessed released data in standard volumetric space after ICA FIX denoising. (Future UKB data releases will include versions of the data transformed into grayordinate space).

2.1.4. *Data Driven Parcellation: Probabilistic Functional Parcels*

While ICA based approaches provide a choice between spatial or temporal independence, these approaches can be problematic as the brain is probably not perfectly segregated either in space or time, and they typically to do not have any modelling of between-subject variability. We applied another framework used for identifying large-scale probabilistic functional modes (PROFUMO) [40, 41] to identify parcels which are allowed to be correlated with each other in space and/or time, and which explicitly models between-subject variability in the parcels.. In contrast to the above methods, therefore, PROFUMO does not require parcels to be orthogonal or non-overlapping. We applied PROFUMO on the HCP for d = 50, but we are not yet able to apply PROFUMO on the UKB data due to prohibitive computational cost with the larger cohort.

2.2. *Finding the best correlation-based functional connectivity estimate method*

We extracted a timeseries signal for each subject, $X \in (\Re)^{T*d}$, where T corresponds to the number of timepoints and d correponds to the number of parcels for each subject. Functional connectivity estimates are also referred to in the literature as parcellated connectomes or netmats, but here we will refer to these estimates as functional connectivity. Table 1 lists symbols for the different correlation-based functional connectivity estimates we evaluated.

Term	Symbol
Empirical covariance	$\check{\Sigma}$
Full correlation	$\check{\Sigma}$
Precision matrix	$\hat{\Omega}$
Tikhonov precision matrix	$\bar{\Omega}$
Oracle approximate shrinkage precision matrix	$\dot{\Omega}$
Partial correlation	ρ
Any of above functional connectivity matrix	C
Any of above functional connectivity matrix in tangent space	$\vec{C}$

Table 1: The symbols used for various functional connectivity estimates in this paper.

2.2.1. *Estimating the Functional Connectivity*

Empirical Covariance: Functional connectivity is calculated by estimating the empirical (sample) covariance matrix of timeseries signal for each subject. The empirical covariance $\check{\Sigma}$ can be defined as:

$$\check{\Sigma} = 1/T(X - \bar{X})^t(X - \bar{X}) \tag{1}$$

Full Correlation: The full correlation coefficient, or Pearson's correlation coefficient can be defined in terms of covariance. Mathematically, full correlation $\check{\Sigma}$ is a standardized form of covariance. The value of correlation takes place between -1 and +1. Conversely, the value of covariance lies between $-\infty$ and $+\infty$.

Partial Correlation: Although commonly used, using full correlation to derive connectivity estimates is problematic, as it does not distinguish whether two parcels of brain are directly connected or indirectly connected through another parcel. To mitigate this, we define partial correlation, which is correlation between the time series of two parcels after adjusting for the time series of all other network parcels. Partial correlation is calculated from the inverse of the covariance matrix, also known as the precision matrix. We calculated inverse covariance using cholesky decomposition [42] as illustrated in Equation 2 . For this derivation, we first factorized $\check{\Sigma}$ into an upper triangular U that satisfies $\check{\Sigma} = U' * U$ and then calculated the precision matrix $\check{\Sigma}^{-1} = \Omega = w_{ij(MxM)}$. To convert precision into partial correlation ρ, there is a sign flip of the non-diagonal elements and also normalization as shown in Equation 3 where i and j are nodes.

$$\hat{\Omega} = \check{\Sigma}^{-1} = U^{-1}(U^{-1})^t \tag{2}$$

$$\rho = -\frac{w_{ij}}{\sqrt{w_{ii}w_{jj}}} \tag{3}$$

Tikhonov Partial Correlation: As partial correlation involves the calculation of the inverse of covariance matrix, this method becomes problematic when there are not considerably more timepoints than nodes. Several approaches based on regularization have been proposed in the literature to address this unstable matrix inversion problem. We implemented the Tikhonov regularization (also referred as L_2 ridge regression) [43] as shown in Equation 4. This equation involves the addition of a regularization term $\Gamma = \alpha I$, a multiple of the identity matrix. The scalar α is optimized here by minimizing the root mean square (RMS) distance between subject covariance matrices and their unregularized group average.

$$\bar{\Omega} = (\check{\Sigma} + \Gamma)^{-1} \tag{4}$$

Sparse Group Gaussian Graphical Modelling (SGGGM) Partial Correlation: Tikhnov regularization allows for a stable inversion for the covariance matrix; however, it uniformly shrinks off-diagonal

elements. Sparse Group Graphical Gaussian Modelling (SGGGM) [44] learns group-level connectivity in a data-driven way using an L_1 prior and regularization of each subject's connectivity towards the group mean using an L_2 prior. The advantage of SGGGM is that it supports intra-subject inverse covariance being similar, but not exactly the same as the group inverse covariance estimate in a similar manner to [45]. The inverse covariance, $\dot{\Omega}$, is calculated here using the regularization technique known as oracle approximating shrinkage (OAS), as described in the original paper [44], and is well regularized. SGGGM is posed as a regularized consensus optimization problem which can be solved using an alternating direction method of multipliers (ADMM) [46]. In Equation 5, $\|.\|$ corresponds to the Frobenius norm penalty, applied to the difference between the subjects' matrices and the group. $\| \dot{\Omega}^G \|_1$ is used for enforcing sparsity on the group prior and $tr(\check{\Sigma}^S \Omega^S) - logdet(\Omega^S)$ is the representation of each subject's own observation. Parameter λ_1 controls sparsity and λ_2 regulates the group consistency. We optimized these hyper-parameters (λ_1 and λ_2) by minimizing the distance between group mean connectivity estimated from half of the data-set and the un-regularized group mean using the other half of the data-set.

$$\underbrace{min}_{\dot{\Omega}^G>0, \dot{\Omega}^S>0} \lambda_1 \| \dot{\Omega}^G \|_1 + [tr(\check{\Sigma}^S \dot{\Omega}^S) - logdet(\dot{\Omega}^S)] + \lambda_2 \| \dot{\Omega}^S - \dot{\Omega}^G \|^2. \tag{5}$$

2.2.2. *Tangent Space Parameterization*

Covariance matrices by construction are symmetric and live in space of positive definitive (PD) matrices. The PD matrix is a symmetric matrix whose eigenvalues are all positive. The standard practice is to directly vectorize (unwrap) these covariance matrices and then feed them into a machine learning predictor, however there are a few downfalls to this practice. One issue is that PD matrices do not naturally form a Euclidean space, meaning mathematical operations like subtraction do not apply, if geometry is to be preserved (and the PD nature preserved). For example, the difference of two PD matrices does not correspond to the PD covariance matrix of a signal. $C_1, C_2 \in Sym^+_n \implies C_1 - C_2 \in Sym^+_n$ [23]. Another problem is that in the space of the positive definitive cone, where covariance matrices exist, elements of covariance are inter-correlated. This goes against the underlying assumption for some predictors, which assume features are uncorrelated. Lastly, these vectorized connectivity estimates do not follow a normal distribution, which violates the assumptions of some methods, like Linear Discriminant Analysis (LDA).

If we follow the geometry of PD matrices, we note that the space of PD matrices forms a differentiable manifold M. PD matrices therefore cannot directly be treated as an element of Euclidean space; therefore, to correctly apply mathematical formulations on these matrices, we utilise Riemannian geometry [25]. For each covariance matrix C in manifold M, we can define a scalar product in the associated tangent space (T) as MT_C. This tangent space is homomorphic to the manifold, and therefore we can approximate the Riemannian distance in the manifold by using Euclidean distance in the tangent space. This allows us to apply simple Euclidean mathematical operations in the tangent space without breaking the geometry of connectivity matrices. Moreover, many popular classification/prediction algorithms (for example, Neural Network, LDA and SVM) cannot be directly implemented to act in a Riemannian manifold. As the projected connectivity matrices in the tangent space are treated as Euclidean objects, such classification algorithms can be readily applied in the associated tangent space.

Another important consideration for the tangent space parametrization is that the projection requires a reference point in the manifold (this is the point where the tangent plane touches the manifold) that should be close to the subject's projected covariance matrix. If we have a different reference point for each subject, each subject's covariance matrix would be projected to a different tangent plane. To ensure that all projected covariance matrices lie in the same tangent plane, we must find a reference covariance matrix close to all subjects' covariance estimates. This reference covariance matrix could be an average

of the whole set of covariance matrices [48] and is referred to here as C_G. Following the logarithmic map for projecting any covariance matrix to its tangent plane [49], any covariance matrix C can be projected to tangent space as shown in Equation 6. Once the covariance matrices are in tangent space, they are no longer linked by the PD constraint, and hence these uncorrelated features are more useful for classifiers.

$$\vec{C} = log_m(C_G^{-1/2}CC_G^{-1/2}) \tag{6}$$

Reference Point in Tangent Space: C_G symbolizes the group reference estimate which may be estimated in different ways. The choice of reference PD matrix would normally be a group mean estimate as stated in Table 2. Euclidean mean is the average of all covariance matrices whereas harmonic mean is the reciprocal of the arithmetic mean of the reciprocals. Log Euclidean is the Euclidean mean of the logarithm of the covariance matrices. The Riemannian mean is introduced in [50] and can be computed in three iterative steps: (1) projecting connectivity estimates to the tangent space (initialized by using the arithmetic mean), (2) calculating the arithmetic mean in the tangent space, and (3) mapping the arithmetic mean back to the manifold. These three steps are repeated until convergence [24]. The Riemannian distance between two SPD matrices (A,B) can be defined as $\delta_R(C_A C_B) = \| \log(C_A^{-1} C_B) \|_F = [\sum_i log^2 \lambda_i]^{1/2}$, where λ_i are the eigen-values of $C_A^{-1} C_B$. The Kullback mean is the geometric mean between harmonic mean and arithmetic mean. It is not evident in the literature which mean would lead to better representation of the manifold and therefore, we considered all these alternatives for reference point estimation.

Reference Mean	Equation
Euclidean	$C_e = \frac{1}{N}\sum_i C_i$
Harmonic	$C_h = (\frac{1}{N}\sum_i C_i^{-1})^{-1}$
Log Euclidean	$C_{le} = \exp\left(\frac{1}{N}\sum_i \log C_i\right)$
Riemannian Mean	$C_r = \arg\min\left(\sum_i \delta_R(C_e C_i)^2\right)$
Kullback	$C_k = C_e^{1/2}\left(C_e^{-1/2}C_h C_e^{-1/2}\right)^\alpha C_e^{1/2}$

Table 2: Reference Mean Estimation. C_i denotes the functional connectivity matrix for subject i.

2.2.3. *Shrinkage in Tangent Space*

To further reduce estimation variability, we can apply regularization in the tangent space. The Ledoit-Wolf estimator shrinks the covariance towards a target matrix T as $\vec{C}_{LW} = (1 - \lambda)C + \lambda T$. In [28], the authors proposed shrinkage towards an identity matrix. A better alternative is to shrink towards the group mean covariance matrix. The Ledoit-Wolf shrinkage can also be applied in tangent space as shown in Equation 7.

$$\vec{C}_{LW} = (1 - \lambda)\vec{C} + \lambda C_G \tag{7}$$

This shrinkage is isotropic and therefore does not take into consideration the distribution of the population. Recently, another method called PoSCE was proposed [29] in which the population prior is not based on just the mean, but uses information from the probabilistic distribution of covariances. The prior dispersion is calculated as the mean outer product of the parametrized tangent space connectivity estimates as $\Lambda_o = \frac{1}{N-1}\sum_{i=1}^{N}\langle \vec{C}_i, \vec{C}_i \rangle$ and $\Lambda = \lambda I$ is likelihood covariance where λ is the shrinkage control parameter.

The shrunk covariance matrices in the tangent space can then be calculated as in Equation 8.

$$\vec{C}_{PoSCE} = (\Lambda^{-1} + \Lambda_o^{-1})^{-1}\Lambda^{-1}\vec{C} \tag{8}$$

These isotropic and non-isotropic shrinkage techniques could ideally be applied to any projected connectivity estimate (covariance, full correlation, partial correlation, Tikhonov partial correlation or SGGGM partial correlation) in the tangent space. Theoretically, Tikhonov partial correlation and SGGGM connectivity estimates are already well-regularized so they may not require any further shrinkage in the tangent space, but we have tested all possible variants in this study (regularization in the ambient space and then further regularization in the tangent space). Moreover, we have introduced concepts of three spaces as detailed below:

- **Ambient Space**: The estimated functional connectivity estimates (Section 2.2) were not projected into the tangent space. The classifier/predictor was directly applied to connectivity estimates in the ambient space.

- **Tangent Space**: The various functional connectivity estimates (covariance, full correlation, partial correlation, Tikhonov partial correlation or SGGGM partial correlation as defined in Section 2.2) were projected to tangent space following Section 2.2.2, but no shrinkage was applied in the tangent space. The classifier/predictor was applied on the parameterized tangent space connectivity estimates.

- **Tangent_Shrinkage Space**: The shrunk tangent space in which functional connectivity estimates were projected to tangent space and then shrinkage was applied in the tangent space (Section 2.2.3). In this case, the classifier/predictor was applied on the parameterized shrunk tangent space connectivity estimates. Most of the analyses carried out in this article are based on using PoSCE tangential space shrinkage, however Figure A.18 depicts results results comparing PoSCE shrinkage with Lediot-Wolf shrinkage in the tangent space.

2.3. *Finding the best classifier*

The last step is to use these covariance matrices as features to predict non-imaging variables.

Elastic Net: The first classifier we tested is Elastic Net [51], which is a classical regularized regression method that combines the penalties of lasso (L_1) and ridge (L_2) methods. L_1 encourages a sparser model (more zeros) but fails to accomplish group variable selection (where strongly correlated features are selected or discarded together). Alternatively, L_2 encourages the grouping effect and removes the limitation on the number of chosen variables but it does not achieve sparsity. L_2 is a reasonable approach to handle the ill-posed problems that result from extremely correlated features. Elastic net aims to overcome the limitations of both L_1 and L_2 penalties. The data matrix X is $s \times p$, where s is the number of subjects and p is the number of features, and y is the response vector, such as age or sex. The functional connectivity matrices are symmetric and only values above the diagonal need to be retained and vectorized, and hence $p = d(d\text{-}1)/2$, where d is number of parcels. We then applied univariate pre-feature selection, and only retained the top 50% features (based on correlation with the predictor). In Equation 9, $\|\cdot\|_1$ corresponds to the L_1 norm penalty and the quadratic part (the second term) is the is L_2 norm.

$$\hat{\beta} = \underset{\beta}{argmin}\| y - X\beta \|^2 + \lambda_2\| \beta \|^2 + \lambda_1 \| \beta \|_1 \tag{9}$$

BrainNetCNN: The second classifier, BrainNetCNN, is specifically developed to leverage the topological structure of networks [54]. It consists of edge-to-edge (E2E), edge-to-node (E2N) and node-to-graph (N2G) convolutional filters, which are all designed to analyze functional connectivity to predict the behavioral information. The main contribution of BrainNetCNN is using a cross shape filter (the dimension

of some of the filters are set to be $d * 1$ and others $1 * d$, whereas, the overall size of input connectivity matrix is d*d) instead of the traditional box shape filter. There are primarily three main layers used in this network, E2E, E2N and N2G layers. The E2E layer considers the weights of all the edges which share a node together. The output of the E2E layer is fed into the E2N layer. The E2N layer convolves the connectivity matrix with a 1D convolutional row filter, which results in a single output value for each node. Finally, the N2G graph layer is used, which is similar to the fully connected layer. The output features from N2G layer are then fed into a predictor to provide final prediction.

Recurrent Convolutional Neural Network: A Convolutional neural network (CNN) is a feed-forward network inspired by the brain's visual system; however, in comparing it with the brain, CNN lacks the recurrent connections which are abundant in the brain. Inspired by [52], we have designed a recurrent convolutional neural network (RCNN) by incorporating recurrent connections in each convolutional layer. The activities of RCNN evolve over time (the activity of each unit is modulated by the activities of its neighboring units), which provide the advantage of an increased receptive field, and results in a greater awareness of contextual information. We have implemented a 2D RCNN to extract features from functional connectivity matrices. The most important module of RCNN is the recurrent convolution layer (RCL). The architecture is shown in Figure A.26. The net input m_{ijk} at unit (i,j) on kth feature map is given by

$$z_{ijk} = (w_k^f)^T u^{(i,j)}(t) + (w_k^r)^T x^{(i,j)}(t-1) + b_k \qquad (10)$$

In Equation 10, $u^{(i,j)}(t)$ is the feed forward input, as in a CNN, while (w_k^f) is the vectorized feed forward weights. The second term of the equation arises because of the recurrent connections and $x^{(i,j)}(t-1)$ represents the recurrent input and $(w_k^r)^T$ is associated with recurrent weights. z_{ijk} will pass through the rectified linear activation function $f(z_{ijk})$ and then local response normalization (LRN) will be applied on it, which imitates lateral inhibition in cortex. In neurobiology, lateral inhibition refers to the capacity of an excited neuron to reduce the activity of its neighbors. Similarly here, feature maps will challenge each other for maximum representation.

Graph Convolutional Neural Network: The standard convolution is limited to data on a Euclidean grid; however, the graph convolutional neural network (GraphCNN) extends beyond traditional CNNs to handle data that is supported on a graph. GraphCNN exploits the Laplacian of the graph and is built on spectral filters, graph coarsening, and efficient pooling, which are all based on established tools in graph signal processing [53]. We followed the approach of [55] and constructed the graph $G = (V, E, A)$ where $d_x = |V|$ is the set of vertices, E is the edges and A is the adjacency matrix. GraphCNN takes input as a feature matrix $X = [x_1, ..., x_n]^T \in \mathbb{R}^{s \times d_x}$, where s is number of nodes and d is number of features for each node. In our case, each subject is represented by a node and corresponding features are computed by vectorizing the functional connectivity matrix. The other input to the GraphCNN is an adjacency matrix, $A \in \mathbb{R}^{d_x \times d_x}$ which is essentially a graph between features. We defined the adjacency matrix based on the similarity estimate between features. For constructing the graph, the Euclidean distance $d_{ij} = \|x_i - x_j\|_2$ was used as a distance function, a Gaussian kernel $a_{ij} = \exp(-d_{ij}^2/2\sigma^2)$ was applied and a k nearest neighbours graph was formulated.

*2.3.1. **Deconfounding the Data***

Many participant-related confounds exist in resting state data, which can corrupt associations between the imaging data and non-imaging data. Our main goal was to predict non-imaging variables based only on *pure* functional connectivity, hence we found it was crucial to minimize the impact of confounding variables. The basic confounds we controlled for were age, sex, ethnicity, weight, average head motion, brain size, intercranial volume, variables (x,y,z,table) related to bed position in scanner, imaging centre and confounds modelling slow date-related drift. We also included some non-linear effects, i.e., age^2, $sex \times age$,

$sex \times age^2$. We evaluated the effect of various deconfounding schemes on X, a predictor/data matrix (i.e, subjects' functional connectivity), and Y, a response vector (e.g, fluid intelligence). For X there are three possible strategies, (i) no deconfounding (X0), (ii) confound regression from data that is not contained within the cross-validation loop (X1), (iii) fold-wise confound regression (X2), following [56]. For Y, there are two options, (i) no deconfounding (Y0), or (ii) learning deconfounding regression weights from the training subset, and then applying these weights on the left-out validation subset (Y1). For example, deconfounded $\tilde{X}$ is calculated as $\tilde{X} = X - C\beta$ where C are confounds and β are regression weights. The β can be calculated as $\beta = C^+ X$, where C^+ is the pseudoinverse of the confounds.

2.4. *Imaging Data*

The rfMRI data of 13301 subjects from UKB and 1003 subjects from the HCP were used in this analysis. The pre-processing pipelines for UKB and HCP are described in [57] and [58] respectively, although the main steps can be summarized as (1) motion correction, (2) removal of structural artifacts with ICA (Independent Component Analysis and FMRIB's ICA-based X-noisefier (FIX), and (3) brain parcellation using any of the techniques covered in Section 2.1. The length of the scanning session for UKB is 6 minutes, and for HCP is 1 hour (4 sessions of 15 mins each). For UKB, we have 490 time-points and for HCP, we used data from all 4 sessions which gave us 4800 time points in total (1200 timepoints in each session).

2.5. *Non-Imaging Data*

Here, we have chosen four non-imaging variables: age, sex, fluid intelligence score and neuroticism score (the latter only for UKB), for following reasons:

Age: Improving prediction of age from brain data is of interest, to further clinical understanding of how age links to neurodevelopment and degeneration. For instance, comparing the discrepancy between an individual's chronological age and the age predicted from neuroimaging data can serve as a biomarker for several age-linked brain diseases [59]. Age can be accurately predicted from structural MRI data [63]; however, prediction of age from functional connectivity estimates is not as accurate. Nevertheless, this represents a non-imaging variable that can be predicted reasonably strongly (as opposed to fluid intelligence and neuroticism).

Sex: Sex classification through functional connectivity is comparatively accurate, and so this variable provides a valuable evaluation parameter to compare benchmark performance of different models.

Fluid Intelligence: Fluid intelligence refers to the ability to reason and to solve new problems independently of previously acquired knowledge [60]. It is highly related to professional and educational success and represents overall performance across a broad range of cognitive abilities. A number of recent studies have predicted fluid intelligence from functional connectivity [61], but due to measurement variability, correlations remain rather weak. However, more precise and novel methods for the estimation and use of functional connectivity could lead to better predictions, and provide a more precise understanding of how brain networks relate to cognitive abilities.

Neuroticism: Mental health is being assessed in a number of ways within UKB. Participants answer a 12-item neuroticism questionnaire as part of their baseline assessment. We used the algorithm employed in [62] to calculate the score of neuroticism for each subject.

3. Results

Figure 2 shows the prediction accuracy/correlation for non-imaging measures from functional connectivity estimates across different parcellation schemes (Section 2.1) and functional connectivity estimation

methods (Section 2.2). The results in Figure 2 were calculated by directly vectorizing the connectivity estimates without projection into tangent space. Elastic Net was used as a predictor with nested 5-fold cross-validation. The results illustrated in Figure 2 are a reduction of the full set of results, chosen to highlight the performance of methods employed in step 1 (brain parcellation) and step 2 (functional connectivity estimation) using the relatively robust Elastic Net as the predictor. The results shown in Figure 2 were calculated after removing the effect of confounds from data (deconfounding), and Figure A.15 shows prediction estimates without confound removal.

A reference point is required when projecting the functional connectivity estimates into tangent space. This reference mean binds each of the connectivity estimates into the same tangential plane. The results in Figure 3 shows the prediction correlation for fluid intelligence using different reference means. For each mean, functional connectivity estimates from all parcellation schemes (Section 2.1) were estimated by using all functional connectivity estimation methods (Section 2.2). The predictor employed here for fluid intelligence prediction was Elastic Net using nested 5 fold cross validation. For simplicity, only fluid intelligence prediction scores are displayed in Figure 3, as the prediction correlations for other non-imaging variables follows the same trend across various reference mean estimation techniques. The violin plots in Figure 3 shows the prediction variability over 4 different parcellation schemes and 5 measures of functional connectivity estimates in the tangent space. The results shown in Figure 3 were calculated after deconfounding, and Figure A.16 shows prediction estimates without deconfounding. Figure 4 illustrates how the prediction accuracy was modified by projecting connectivity estimates into the tangential plane. Again, we varied the parcellation schemes and functional connectivity estimation techniques, but fixed Elastic Net as the predictor. The results illustrated in Figure 4 are a reduction of the full set of results, chosen to highlight the performance of tangent space parameterization (Section 2.2.2). Moreover, the results shown in Figure 4 were calculated after deconfounding, and Figure A.17 shows prediction estimates without deconfounding.

Figure 5 compares the effect of applying shrinkage in the tangent space (Section 2.2.3). The shrinkage applied was non-isotropic shrinkage towards the population dispersion (PoSCE). Results here are based on functional connectivity estimates that have been projected in the tangential plane (Section 2.2.2). The violin plots in Figure 5 shows the prediction variability over 4 different parcellation schemes and 5 measures of functional connectivity estimates in the normal tangent space (no shrinkage) versus tangent_shrinkage space (PoSCE). (Section 2.2.3). Similarly to the previously displayed results, Elastic Net was used as the method for prediction of non-imaging measures. The Bland-Altman plot is shown in Figure 6 to describe agreement between shrinkage versus no shrinkage approaches. The Figure 5 and Figure 6 are precisely two different ways of visualizing the similar results. Figure A.18 compares the performance of isotropic (Ledoit-Wolf) versus non-isotropic (PoSCE) shrinkage in the tangent space and Figure A.19 compares the performance of isotropic (Ledoit-Wolf) versus no shrinkage strategy (projected functional connectivity estimates in the tangent space were directly fed to the predictor, and did not undergo any shrinkage). All the results displayed in Figure 5, 6, A.18 and A.19 are after deconfounding.

We compared various deconfounding strategies (Section 2.3.1), by varying ICA dimensionality (Section 2.1.3) and using Elastic Net as the predictor. Figure 7 shows the prediction correlations of fluid intelligence from functional connectivity estimates for each deconfounding strategy. The violin plots in Figure 7 shows the prediction variability over 4 different parcellation schemes, 5 measures of functional connectivity estimates and 3 different spaces (ambient space, tangent space and tangent_shrinkage space). Again, the results illustrated in Figure 7 are a reduction of the full set of results, chosen to highlight the performance of different deconfounding strategies. (Section 2.3)

Figure 2: The impact of various parcellation strategies and functional connectivity estimation methods on prediction power for non-imaging variables **after deconfounding**. [**A,B,C**] (**HCP Data**): A corresponds to the prediction accuracy for sex, and B and C correspond to prediction correlation (r) for fluid intelligence score and age respectively. [**D,E,F,G**] (**UKB Data**): D corresponds to the prediction accuracy for sex whereas E, F, and G correspond to the prediction correlation (r) for fluid intelligence scores, age, and neuroticism scores respectively. For HCP, the ICA based parcellation schemes are ICA_15D, ICA_50D and ICA_200D, and for UKB are ICA_21D and ICA_55D, where D = the number of parcels. For both HCP and UKB, SHEN parcellation was 268D, YEO was 100D, and PROFUMO was 50D (for HCP only).

Figure 3: The impact of various reference mean estimation techniques during tangent space parameterization on prediction of non-imaging variables **after deconfounding**. **[A] (HCP Data), [B] (UKB Data)** These figures show the prediction correlation for fluid intelligence scores when functional connectivity estimates are projected into tangent space, using different reference means. The violin plots represent the prediction variability over 4 different parcellation schemes and 5 measures of functional connectivity estimates in the tangent space.

Figure 8 compares the performance of different classifiers (Section 2.3) on the prediction between functional connectivity and non-imaging variables. Inputs included functional connectivity estimates (Section 2.2) both in ambient space (without tangent space projection) and tangent space (Section 2.2.2). Estimates with tangent space parameterization included estimates with and without PoSCE shrinkage (tangent space and tangent_shrinkage space). Therefore, the violin plots in Figure 8 shows the prediction variability over 4 different parcellation schemes, 5 measures of functional connectivity estimates and 3 different spaces (ambient space, tangent space and tangent_shrinkage space). Again, the results illustrated in Figure 8 are a reduction of the full set of results, chosen to highlight the performance of different classifiers/predictors (Section 2.3). The results in Figure 8 compared the performance of Elastic Net, 2D RCNN and BrainNetCNN (Section 2.3). We included GraphCNN initially, but dropped it due to consistently poor performance compared with the other models. Figure A.28 shows the comparative performance of GraphCNN and Elastic Net. The subset of results chosen for Figure A.28 were the ones where GraphCNN exhibited the best performance, although still underperforming in comparison to Elastic Net.

Figures 9 and 10 show the top ten methods in terms of predictive power, with strategies from different steps identified. The results shown in Figure 9 and 10 were calculated after deconfounding, and Figures A.20 and A.21 show prediction estimates without deconfounding. Figures 11, 12 and 13 show the combination of various techniques at different stages of the pipeline for fluid intelligence, sex, and age prediction respectively for both HCP and UKB data after deconfounding. Figures A.22, A.23, A.24 show similar results for fluid intelligence, sex and age prediction respectively but without deconfounding. In each of these figures, a few parameters were fixed across the different pipeline combinations (Euclidean mean as reference mean, non-isotropic shrinkage as shrinkage in tangent space). Figure A.25 provides results for the prediction of neuroticism score in UKB data, and results are displayed both before and after controlling for confounds.

All the results illustrated in this paper were using X1Y1 or X1Y0 deconfounding strategy (apart from Figure 7 where all six deconfounding strategies were employed). We have applied the X1Y1 deconfounding for age, fluid intelligence and neuroticism score prediction and X1Y0 for sex prediction (X1Y1 and X1Y0 are

Figure 4: The impact of tangent space parameterization on prediction power for non-imaging variables **after deconfounding**. **[A,B,C] (HCP Data), [D,E,F,G] (UKB Data):** The x-axis corresponds to prediction correlation/accuracy. The y-axis lists various functional connectivity estimates, such as "Covariance ICA_15D", which corresponds to ICA with 15D parcellation strategy and then estimating functional connectivity using empirical covariance. Likewise, "SGGGM PRO-FUMO" means first finding parcels with PROFUMO and then estimating functional connectivity using SGGGM. Euclidean mean is used as a reference mean for tangent space parameterization. The classifiers/predictors that did not converge do not contain the corresponding data point.

Figure 5: The impact of applying shrinkage in tangent space on prediction power **after deconfounding**. **[A] (HCP Data),** **[B] (UKB):** The y-axis depicts the prediction accuracy/correlation for different behavioural measures. The "Shrinkage" strategy means that non-isotropic PoSCE shrinkage was applied to connectivity estimates in tangent space before feeding to the predictor. "No Shrinkage" means that projected functional connectivity estimates in tangent space were directly fed to the predictor, and did not undergo PoSCE shrinkage. The violin plots show the prediction variability over 4 different parcellation schemes and 5 measures of functional connectivity estimates.

detailed in Section 2.3.1 and the reasoning for this is discussed in Section 4). Confounds (particularly head size and motion) are clearly a serious problem if not dealt with for fluid intelligence score prediction. Head size is positively correlated with fluid intelligence and head motion is negatively correlated. For neuroticism score prediction, the confounds which have the most effect on prediction power are age, table position, imaging-centre and date-drift related confounds. This could be because of non-linear interactions between imaging-centre/date-drift related confounds, age, table-position and neuroticism. For age, the crucial confound is head-motion (positively correlated with age), although other than head-motion, we did not find prediction was significantly affected by any confounds. For sex prediction, the crucial confounds are age, height, weight, head motion and head size. For fluid intelligence, neuroticism and age prediction, the deconfounded results are calculated after regressing out all the potential confounding variables. However, in case of sex prediction, for the deconfounded results, we regressed out all the confounds from data except head-size and body density related confounds. The rationale is that sex is a major casual factor for head-size, and head-size causes some confounding effects in the imaging. Regressing out head-size reduces the overall sex prediction accuracy but allows one to focus on the non-headsize sex effects in the imaging. However, one of the main goal in this work is to optimize functional connectivity estimation methods (i.e., allow maximum predictors to converge to make performance of different models comparable). Therefore, we didn't include head-size and body density related variables as confounds when predicting sex. Most of the results without removing the effect of confounds (i.e., higher prediction accuracy/correlation as compared to deconfounded results in the main text) are shown in the Inline supplementary material.

Figure 6: The impact of applying shrinkage in tangent space on prediction power **after deconfounding**. [A,B,C] **(HCP Data)**, [D,E,F,G] **(UKB Data):** The y-axis depicts the difference of two methods (no shrinkage - shrinkage) and x-axis depicts the mean of methods ((no shrinkage + shrinkage) /2).

Figure 7: The impact of deconfounding strategies on the prediction power. **[A] (HCP), [B] (UKB)** This figure shows the prediction correlation for fluid intelligence score for various ICA based parcellation techniques across the 6 possible deconfounding strategies that were tested. The violin plots show the prediction variability over 4 different parcellation schemes, 5 measures of functional connectivity estimates and 3 different spaces (ambient space, tangent space and tangent_shrinkage space). X is predictor matrix (i.e, subjects' functional connectivity), and Y, a response vector (e.g., fluid intelligence). The details of different deconfounding strategies are explained in Section 2.3.1.

Figure 8: The performance of different classifiers/predictors on prediction power with and without deconfounding. [**A,B,C**] (**HCP Data**), [**D,E,F,G**] (**UKB Data**): The prediction accuracy/correlation for different non-imaging measures is depicted on the y-axis. The violin plots show the prediction variability over 4 different parcellation schemes, 5 measures of functional connectivity estimates and 3 different spaces (ambient space, tangent space and tangent_shrinkage space).

Figure 9: The top performing five configurations for the prediction of each non-imaging variable by dataset **after deconfounding**. **[A,B,C] (HCP Data)** Each data point represents a different configuration strategy that may vary in terms of parcellation strategy, the functional connectivity estimation method, whether tangent space parameterization was employed, whether tangent space regularization was employed, and the predictor that was used. The first word indicates the parcellation strategy, and the second word refers to the functional connectivity estimation method. The third word refers to the geometry in which classifier is applied, ambient referring to non-tangential space and tangent referring to the projected covariance matrices in tangential space. If non-isotropic shrinkage was applied after projecting covariance matrices to tangential space, the fourth word will be "shrinkage". The last word indicates the type of classifier/predictor that was used.

Figure 10: The top performing five configurations for the prediction of each non-imaging variable by dataset **after de-confounding**. **[A,B,C,D] (UKB Data):** Each data point represents a different configuration strategy that may vary in terms of parcellation strategy, the functional connectivity estimation method, whether tangent space parameterization was employed, whether tangent space regularization was employed, and the predictor that was used. The first word indicates the parcellation strategy, and the second word refers to the functional connectivity estimation method. The third word refers to the geometry in which classifier is applied, ambient referring to non-tangential space and tangent referring to the projected covariance matrices in tangential space. If non-isotropic shrinkage was applied after projecting covariance matrices to tangential space, the fourth word will be "shrinkage". The last word indicates the type of classifier/predictor that was used.

Figure 11: This parallel coordinates plot provides a visualization of all possible combinations of options in the pipeline to predict fluid intelligence scores from functional connectivity **after deconfounding**. **[A] (HCP Data)**, **[B] (UKB Data)**: The lines are color-coded according to their prediction performance.

Figure 12: This parallel coordinates plot provides a visualization of all possible combinations of options in the pipeline to pipeline to predict sex from functional connectivity **after deconfounding**. **[A] (HCP Data), [B] (UKB Data):** The lines are color-coded according to their prediction performance.

Figure 13: This parallel coordinates plot provides a visualization of all possible combinations of options in the pipeline to pipeline to predict age from functional connectivity **after deconfounding**. **[A] (HCP Data)**, **[B] (UKB Data)**: The lines are color-coded according to their prediction performance.

4. Discussion

The best parcellation strategy: The data-driven parcellation techniques we explored for identification of brain parcels included sICA, PROFUMO, SHEN and YEO. PROFUMO yielded less predictive power than sICA identified parcels, as shown in Figure 2. This is consistent with results in [64], where PROFUMO network matrices tend to be quite empty, in part because of the fairly strong temporal independence between probabilistic functional modes. Using sICA, we investigated if the number of parcels (ICA dimensionality) affected the predictive power. Our results showed that increasing dimensionality leads to an increase in predictive power. However, higher predictive power using sICA could actually be attributable to cross-subject variations in the spatial configuration of functional brain regions that are represented as changes in functional connectivity [64]. Therefore, although PROFUMO yielded lower predictive power, it still may provide a *purer* estimate, as it should not contain as much potential confounding anatomical information. sICA also outperformed SHEN and YEO parcellations in terms of predictive power. SHEN and YEO parcellations can be affected if the reality is that of overlapping functional organisation, due to incorrect assumption of hard parcels leading to mixing of extracted time-series [65]; however, further detailed work is require to understand and address this issue.

The best functional connectivity estimation method: When functional connectivity estimates are left in ambient space, without projection into tangent space, our results revealed estimation using partial correlation yields higher predictive power than does estimation using full correlation or covariance. Using partial correlation results in the removal/weakening of a considerable number of marginal and negative connections. The marginal connections were most likely due to global effects or indirect connections. Hence, partial correlation also enhanced the sparsity in the functional connectivity matrix. Partial correlation involves the inversion of covariance matrix, and to stably invert the covariance matrix, regularization should be normally applied to the covariance matrices [36]. We employed Tikhonov regularization, as it is an efficient and stable method for estimation of a regularized partial correlation matrix. We found this method resulted in increased predictive power as compared to simple partial correlation (particularly for UKB, as duration of scanning session is shorter than with HCP). However, we found a more sophisticated, recent regularization method, SGGGM, provided the best predictive power. Through incorporation of group information when deriving intra-subject connectivity estimates, this method enables more accurately data-adaptive regularisation. This method produced the most robust predictions, although optimised tuning of the parameters of SGGGM (such as sparsity level and group consistency) is essential, as the performance of SGGGM is very sensitive to these parameters. Therefore, to find optimal values for these parameters, a comprehensive grid search strategy must be applied (and, for validity, this needs to be done within cross-validation).

Is tangent space parameterization important: To test how tangent space parameterization affects predictive power, we projected different functional connectivity estimates into tangent space. As functional connectivity matrices being projected in to tangent space should always be positive definitive, estimates containing values outside of the positive definitive manifold ideally require adjustment. Functional connectivity estimates through covariance or SGGGM are always positive definitive, therefore did not require additional processing. However, partial correlation and Tikhonov connectivity matrices are not always positive definitive. To adjust for these values, we calculated the eigen-decomposition of the matrix. Any eigenvalues close to zero were adjusted to a fixed, small non-zero value. Our results demonstrated that the performance of most functional connectivity estimation techniques were reasonably improved by projecting them into tangent space, as illustrated in Figure 4. These convincing results suggest the importance for future studies to consider the application of Riemannian geometry principles (e.g., tangent space parametrization) to functional connectivity estimates. When applied to different functional connectivity

estimation methods, we found tangent space parametrization increased the predictive ability of almost all estimation techniques. Our results however failed to delineate a single connectivity estimate that was best improved by this parameterization. Projection of these estimates into tangent space required a reference mean, and so we also compared the performance of different reference means. Specifically, we compared the performance of Euclidean, harmonic, log determinant, log Euclidean and Riemannian means as reference means for tangent space parameterization. In terms of prediction accuracy/correlation, our results demonstrate the Euclidean mean tends to have the most stability, as shown in Figure 3 (although the differences were not large between any of the reference mean methods). Therefore, we implemented tangent space parameterization using the Euclidean mean as a reference mean for proceeding analyses. The main advantage of tangent space parameterization is that it moved the functional connectivity estimates into a space where the following computations (e.g., prediction) could be done in a Euclidean framework with a corresponding boost in efficiency.

Regularization in tangent space: The functional connectivity estimates often have high estimation variability. After projecting functional connectivity estimates to tangent space, we evaluated three possible regularization strategies, (i) No shrinkage, (ii) applying the non-isotropic Population Shrinkage Covariance Estimator (PoSCE) shrinkage, (iii) applying isotropic Ledoit-Wolf shrinkage. We found that applying the PoSCE shrinkage technique as compared to no shrinkage approach slightly improved the performance for UKB data (as illustrated in Figure 5) in terms of prediction accuracy, but did not yield meaningful improvements for HCP data. However, our analyses also revealed that optimization of the shrinkage parameter in PoSCE was not straightforward. For PoSCE, we chose the shrinkage parameter which resulted in the strongest prediction for the non-imaging variables (within an appropriate cross-validation framework). We then compared non-isotropic PoSCE shrinkage to Ledoit-Wolf isotropic shrinkage, and found that PoSCE did not yield a meaningful advantage compared with Ledoit-Wolf shrinkage (as illustrated in Figure A.18). Lastly, we compared the isotropic Ledoit-Wolf shrinkage method with the no shrinkage approach, and found that applying simple Ledoit-Wolf shrinkage improved performance for HCP data, but did not significantly improve performance for UKB data (as illustrated in Figure A.19). These results imply that simple isotropic shrinkage is more suitable for less noisy data (e.g., HCP data) and aggressive PoSCE works well for data with comparatively high inter- and intra-subject variance (e.g., UKB data, as duration of scanning session is shorter than with HCP).

Regularization in the Ambient space vs. tangent space: We have evaluated the effects of Tikhonov and SGGGM regularization on functional connectivity estimates in the ambient space. Once the connectivity estimates are in the tangent space, we have further evaluated the choice of isotropic and non-isotropic shrinkage approaches. We have used these methods independently and jointly, in order to identify the optimum method. We have the following recommendations (based on the results in Figure 9 and 10): (i) Our results have demonstrated that if the data is less noisy (e.g., HCP data), it is more effective to regularize in the ambient space (i.e., Tikhonov or SGGGM) as compared to regularization in the tangent space (i.e., PoSCE). Moreover, it is not required to regularized both in the ambient space and the tangent space (this potentially could remove too much inter-subject variance), and (ii) If the data is comparably more noisy (e.g., UKB data), it is more feasible to regularize in the tangent space or to regularize both in the ambient space and the tangent space. For future studies, shrinkage in the tangent space could be added as an optional step that may possibly increase predictive power for noiser data.

Deconfounding: Many imaging studies fail to control for confounds in their analyses, which is problematic in providing replicable and interpretable results that are not attributable to extraneous variables. In our analyses, we found the optimal deconfounding strategy was X1Y1 (and X1Y0 in some cases). The reason we recommend X1Y1 over X2Y1 is because X2Y1 combination consists of performing fold-wise con-

found regression on the predictors X (the functional connectivity estimates), and fold-wise deconfounding the target variable Y. However, the deconfounding strategy X1Y1 (deconfounding X once, outside of cross-validation) is more aggressive than X2Y1 (X2Y1 is less aggressive as it used cross-validation to limit the parts of the confounds actually used). For some non-imaging target variables prediction (e.g., sex) there is no chance that confound variables would feed into them (e.g., sex could not be corrupted because of head motion or age). In such cases, it is recommended to deconfound only the imaging variables, X (i.e., functional connectivity estimates) and not to deconfound the target variable, Y (i.e., sex); therefore, X1Y0 (or X2Y0) deconfounding strategy should be used for such target variables. The pretext of supporting X1Y0 over X2YO is the same (X1Y0 is more aggressive as compared to X2Y0). Our analysis have revealed that X0Y1 (deconfounding only Y), also theoretically yields plausible results; however, for some cases (e.g., sex prediction), it is not applicable. Based on our analysis, we have the following recommendations, (i) deconfound both X and Y when there is a chance that confounds can corrupt both the imaging data and non-imaging data, such as fluid intelligence score or any given mental health variable, and (ii) deconfound only X when there is no chance of confounds feeding into target variable, such as sex prediction (otherwise, this could cause Berkson's paradox), and (iii) no deconfounding (X0Y0) is never an option for rfMRI studies.

The best classifier: Figure 8 illustrates the performance of different classifiers in combination with different parcellation and estimation techniques. Elastic Net is a simple regularized regression technique, whereas the other models tested are based on convolutional neural networks. The prediction of age, fluid intelligence and neuroticism is a continuous prediction task, whereas sex prediction is a binary classification problem. 2D RCNN consistently demonstrated the best performance for sex prediction (e.g., UKB data). 2D RCNN and Elastic Net were comparable for the prediction of fluid intelligence score (e.g., HCP data). For the prediction of neuroticism, our results demonstrated that ElasticNet provided the highest predictive power. Across the prediction of all variables, BrainNetCNN underperformed in comparison to other classifiers, although it is possible that further optimization of parameters could lead to higher accuracy. GraphCNN consistently underperformed in comparison with the other models (results presented in Figure A.28). It should be considered that we tested these deep learning architectures (2D RCNN, BrainNetCNN, and GraphCNN) for hundreds of different functional connectivity estimates, which impose practical limitations on our ability to tune hyper-parameters for each possible configuration. This indirectly suggests that only the most stable architecture will show consistent results across different connectivity estimates. Moreover, this suggests the most robust, off-the-shelf types of neural networks must minimize sensitivity to hyper-parameter tuning, to maximize generalizability and minimize over-fitting. Overall, we have demonstrated that a carefully designed 2D Recurrent Convolutional Network or BRAIN-NETCNN (top performing for fluid intelligence prediction in HCP data) can compete with (and in some cases outperform) a simpler regression model. These results contrast with [66], where kernel based regression (non-parametric classical machine learning algorithm [67]) demonstrated better performance than deep neural networks.

Comparison with Literature: Somewhat similar evaluations of various methods (in this problem domain) have previously been carried out in [68, 69]. In [68], authors proposed that matrix whitening transform and parallel transport could be utilized to project covariance matrices into a common tangent space and evaluated this method on twenty four healthy subjects. These former results build a foundation for estimation of functional connectivity using manifold operations, as higher prediction accuracy was achieved using tangent space parameterization. [69] evaluated different modelling choices and recommended a three stage pipeline: (i) ICA for brain parcellation, (ii) tangent space embedding for functional connectivity estimation and (iii) use of non-sparse models like SVM for non-imaging variables prediction. For brain parcellation, [69] applied a number of parcellation techniques that differed from our pipeline,

Figure 14: The recommended six steps of optimized functional connectivity modelling pipeline.

however also found that sICA yielded the best performance.

Lastly, we have applied deep learning architecture such as CNNs to analyze functional connectivity whereas [69] utilized traditional machine learning algorithms. Similarly to the last step of our pipeline, [66] compared the performance of three CNNs to kernel regression. The three CNNs tested included a generic fully-connected feedforward network, BrainNetCNN and Graph CNN. This study reported that CNNs did not outperform kernel regression across a wide range of behavioral and demographic measures. However, our results found that our proposed 2D RCNN (architecture illustrated in Figure A.26), which has not been previously evaluated against these methods, outperforms the regularized regression and existing CNNs for some tasks (e.g., Figure A.23).

There is another pipeline in the literature known as Connectome-based predictive modelling (CPM) [73] that is mainly comprised of three steps: (i) parcellating the brain using the SHEN functional atlas, (ii) estimating connectivity using full correlation, (iii) correlating each edge in the connectivity matrix with behavioral measures, selecting only the most correlated N edges, averaging across these N edges to give a single predictor value for each subject, and then fitting a linear model (e.g., robust regression, polynomial curve fitting) to predict non-imaging variables. Based on our findings, ICA and regularized partial correlation give better prediction over SHEN and full correlation respectively (as shown in Figure 2). For step 3, we compared performance of CPM predictive model with Elastic Net and found Elastic Net performs better than CPM (as shown in Figure A.27).

5. Conclusion

Our results have demonstrated that within data driven parcellation, ICA provides the most predictive power for non-imaging variables. For estimating functional connectivity, we have shown that regularized partial correlation like SGGGM or Tikhonov outperforms unregularized partial correlation or full correlation. To correctly apply mathematical formulations on functional connectivity estimates, it is recommended to take into account that these measures should ideally be worked with within the Riemannian manifold. To do so, Riemannian space is approximated with an associated tangent space and then functional connectivity estimates are mapped to the tangent space. We have reported in this paper that this tangent space parameterization results in a significant increase in predictive power of functional connectivity estimates, as previously shown in [68, 69]. Our results have also demonstrated that additional shrinkage is not necessarily required on well regularized connectivity estimates in tangent space; however, could be applied for noiser data. Lastly, we evaluated various classifiers for prediction of non-imaging variables from connectivity estimates and concluded that a carefully designed deep learning based architecture (2D RCNN) can be a valuable tool for analyzing functional connectivity. However, in some cases, simpler alternatives, such as ElasticNet still outperform deep learning algorithms, and, overall, our 2D RCNN and ElasticNet perform similarly.

6. Acknowledgements

Computation used the Oxford Biomedical Research Computing (BMRC) facility, a joint development between the Wellcome Centre for Human Genetics and the Big Data Institute supported by Health Data Research UK and the NIHR Oxford Biomedical Research Centre.

We are extremely grateful to all UK Biobank (Data Access Application 8107) and Human Connectome Project study participants, who generously donated their time to make this resource possible. UK Biobank (including the imaging enhancement) has been generously supported by the UK Medical Research Council and the Wellcome Trust. Human Connectome Project, WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16 NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research; and by the McDonnell Center for Systems Neuroscience at Washington University.

We additionally thanks Gael Varoquaux, Giles Colclough, Mehdi Rahim and Todd Constable for helpful discussions.

Lastly, U.P is funded by an MRC Mental Health Data Pathfinder award (PI Clare Mackay) MC_PC_17215. S.M.S and M.W.W receive support from the Wellcome Trust.

References

[1] Fox MD, Snyder AZ, Vincent JL, Corbetta M, Van Essen DC, Raichle ME. The human brain is intrinsically organized into dynamic, anticorrelated functional networks. Proceedings of the National Academy of Sciences. 2005 Jul 5;102(27):9673-8.

[2] De Luca MB, Beckmann CF, De Stefano N, Matthews PM, Smith SM. fMRI resting state networks define distinct modes of long-distance interactions in the human brain. Neuroimage. 2006 Feb 15;29(4):1359-67.

[3] Vidaurre D, Smith SM, Woolrich MW. Brain network dynamics are hierarchically organized in time. Proceedings of the National Academy of Sciences. 2017 Nov 28;114(48):12827-32.

[4] Rogers BP, Morgan VL, Newton AT, Gore JC. Assessing functional connectivity in the human brain by fMRI. Magnetic resonance imaging. 2007 Dec 1;25(10):1347-57.

[5] Hutchison RM, Womelsdorf T, Allen EA, Bandettini PA, Calhoun VD, Corbetta M, Della Penna S, Duyn JH, Glover GH, Gonzalez-Castillo J, Handwerker DA. Dynamic functional connectivity: promise, issues, and interpretations. Neuroimage. 2013 Oct 15;80:360-78.

[6] Greicius MD, Srivastava G, Reiss AL, Menon V. Default-mode network activity distinguishes Alzheimer's disease from healthy aging: evidence from functional MRI. Proceedings of the National Academy of Sciences. 2004 Mar 30;101(13):4637-42.

[7] Anand A, Li Y, Wang Y, Wu J, Gao S, Bukhari L, Mathews VP, Kalnin A, Lowe MJ. Activity and connectivity of brain mood regulating circuit in depression: a functional magnetic resonance study. Biological psychiatry. 2005 May 15;57(10):1079-88.

[8] Hahn A, Stein P, Windischberger C, Weissenbacher A, Spindelegger C, Moser E, Kasper S, Lanzenberger R. Reduced resting-state functional connectivity between amygdala and orbitofrontal cortex in social anxiety disorder. Neuroimage. 2011 Jun 1;56(3):881-9.

[9] Nair A, Treiber JM, Shukla DK, Shih P, Mller RA. Impaired thalamocortical connectivity in autism spectrum disorder: a study of functional and anatomical connectivity. Brain. 2013 Jun 1;136(6):1942-55.

[10] Hacker CD, Perlmutter JS, Criswell SR, Ances BM, Snyder AZ. Resting state functional connectivity of the striatum in Parkinsons disease. Brain. 2012 Nov 28;135(12):3699-711.

[11] Lynall ME, Bassett DS, Kerwin R, McKenna PJ, Kitzbichler M, Muller U, Bullmore E. Functional connectivity and brain networks in schizophrenia. Journal of Neuroscience. 2010 Jul 14;30(28):9477-87.

[12] Banks SJ, Eddy KT, Angstadt M, Nathan PJ, Phan KL. Amygdalafrontal connectivity during emotion regulation. Social cognitive and affective neuroscience. 2007 Dec 1;2(4):303-12.

[13] He BJ, Snyder AZ, Vincent JL, Epstein A, Shulman GL, Corbetta M. Breakdown of functional connectivity in frontoparietal networks underlies behavioral deficits in spatial neglect. Neuron. 2007 Mar 15;53(6):905-18.

[14] Kelly AC, Uddin LQ, Biswal BB, Castellanos FX, Milham MP. Competition between functional brain networks mediates behavioral variability. Neuroimage. 2008 Jan 1;39(1):527-37.

[15] Bastos AM, Schoffelen JM. A tutorial review of functional connectivity analysis methods and their interpretational pitfalls. Frontiers in systems neuroscience. 2016 Jan 8;9:175.

[16] Shen X, Tokoglu F, Papademetris X, Constable RT. Groupwise whole-brain parcellation from resting-state fMRI data for network node identification. Neuroimage. 2013 Nov 15;82:403-15.

[17] Desikan RS, Sgonne F, Fischl B, Quinn BT, Dickerson BC, Blacker D, Buckner RL, Dale AM, Maguire RP, Hyman BT, Albert MS. An automated labeling system for subdividing the human cerebral cortex on MRI scans into gyral based regions of interest. Neuroimage. 2006 Jul 1;31(3):968-80.

[18] Fischl B, Van Der Kouwe A, Destrieux C, Halgren E, Sgonne F, Salat DH, Busa E, Seidman LJ, Goldstein J, Kennedy D, Caviness V. Automatically parcellating the human cerebral cortex. Cerebral cortex. 2004 Jan 1;14(1):11-22.

[19] Honnorat N, Eavani H, Satterthwaite TD, Gur RE, Gur RC, Davatzikos C. GraSP: geodesic graph-based segmentation with shape priors for the functional parcellation of the cortex. Neuroimage. 2015 Feb 1;106:207-21.

[20] Parisot S, Glocker B, Schirmer MD, Rueckert D. GraMPa: Graph-based multi-modal parcellation of the cortex using fusion moves. InInternational Conference on Medical Image Computing and Computer-Assisted Intervention 2016 Oct 17 (pp. 148-156). Springer, Cham.

[21] Parisot S, Arslan S, Passerat-Palmbach J, Wells III WM, Rueckert D. Group-wise parcellation of the cortex through multi-scale spectral clustering. NeuroImage. 2016 Aug 1;136:68-83.

[22] Smith SM, Miller KL, Salimi-Khorshidi G, Webster M, Beckmann CF, Nichols TE, Ramsey JD, Woolrich MW. Network modelling methods for FMRI. Neuroimage. 2011 Jan 15;54(2):875-91.

[23] Varoquaux G, Baronnet F, Kleinschmidt A, Fillard P, Thirion B. Detection of brain functional-connectivity difference in post-stroke patients using group-level covariance modeling. InInternational Conference on Medical Image Computing and Computer-Assisted Intervention 2010 Sep 20 (pp. 200-208). Springer, Berlin, Heidelberg.

[24] Barachant A, Bonnet S, Congedo M, Jutten C. Classification of covariance matrices using a Riemannian-based kernel for BCI applications. Neurocomputing. 2013 Jul 18;112:172-8.

[25] Pennec X, Fillard P, Ayache N. A Riemannian framework for tensor computing. International Journal of computer vision. 2006 Jan 1;66(1):41-66.

[26] Ng B, Varoquaux G, Poline JB, Greicius M, Thirion B. Transport on Riemannian manifold for connectivity-based brain decoding. IEEE transactions on medical imaging. 2015 Aug 3;35(1):208-16.

[27] Chen Y, Wiesel A, Eldar YC, Hero AO. Shrinkage algorithms for MMSE covariance estimation. IEEE Transactions on Signal Processing. 2010 Oct;58(10):5016-29.

[28] Ledoit O, Wolf M. A well-conditioned estimator for large-dimensional covariance matrices. Journal of multivariate analysis. 2004 Feb 1;88(2):365-411.

[29] Rahim M, Thirion B, Varoquaux G. Population shrinkage of covariance (PoSCE) for better individual brain functional-connectivity estimation. Medical image analysis. 2019 Mar 15.

[30] Smith SM, Hyvrinen A, Varoquaux G, Miller KL, Beckmann CF. Group-PCA for very large fMRI datasets. NeuroImage. 2014 Nov 1;101:738-49.

[31] Beckmann CF, Smith SM. Probabilistic independent component analysis for functional magnetic resonance imaging. IEEE transactions on medical imaging. 2004 Feb;23(2):137-52.

[32] Miller KL, Alfaro-Almagro F, Bangerter NK, Thomas DL, Yacoub E, Xu J, Bartsch AJ, Jbabdi S, Sotiropoulos SN, Andersson JL, Griffanti L. Multimodal population brain imaging in the UK Biobank prospective epidemiological study. Nature neuroscience. 2016 Nov;19(11):1523.

[33] Van Essen DC, Smith SM, Barch DM, Behrens TE, Yacoub E, Ugurbil K, Wu-Minn HCP Consortium. The WU-Minn human connectome project: an overview. Neuroimage. 2013 Oct 15;80:62-79.

[34] SalaLlonch R, Smith SM, Woolrich M, Duff EP. Spatial parcellations, spectral filtering, and connectivity measures in fMRI: Optimizing for discrimination. Human brain mapping. 2019 Feb 1;40(2):407-19.

[35] Smith SM, Miller KL, Salimi-Khorshidi G, Webster M, Beckmann CF, Nichols TE, Ramsey JD, Woolrich MW. Network modelling methods for FMRI. Neuroimage. 2011 Jan 15;54(2):875-91.

[36] Thirion B, Varoquaux G, Dohmatob E, Poline JB. Which fMRI clustering gives good brain parcellations?. Frontiers in neuroscience. 2014 Jul 1;8:167.

[37] Salimi-Khorshidi G, Douaud G, Beckmann CF, Glasser MF, Griffanti L, Smith SM. Automatic denoising of functional MRI data: combining independent component analysis and hierarchical fusion of classifiers. Neuroimage. 2014 Apr 15;90:449-68.

[38] Schaefer A, Kong R, Gordon EM, Laumann TO, Zuo XN, Holmes AJ, Eickhoff SB, Yeo BT. Local-global parcellation of the human cerebral cortex from intrinsic functional connectivity MRI. Cerebral Cortex. 2017 Jul 18;28(9):3095-114.

[39] Smith SM, Miller KL, Moeller S, Xu J, Auerbach EJ, Woolrich MW, Beckmann CF, Jenkinson M, Andersson J, Glasser MF, Van Essen DC. Temporally-independent functional modes of spontaneous brain activity. Proceedings of the National Academy of Sciences. 2012 Feb 21;109(8):3131-6.

[40] Harrison SJ, Woolrich MW, Robinson EC, Glasser MF, Beckmann CF, Jenkinson M, Smith SM. Large-scale probabilistic functional modes from resting state fMRI. NeuroImage. 2015 Apr 1;109:217-31.

[41] https://www.biorxiv.org/content/10.1101/544817v1

[42] Krishnamoorthy A, Menon D. Matrix inversion using Cholesky decomposition. In2013 Signal Processing: Algorithms, Architectures, Arrangements, and Applications (SPA) 2013 Sep 26 (pp. 70-72). IEEE.

[43] Golub GH, Hansen PC, O'Leary DP. Tikhonov regularization and total least squares. SIAM Journal on Matrix Analysis and Applications. 1999;21(1):185-94.

[44] Ng B, Varoquaux G, Poline JB, Thirion B. A novel sparse group Gaussian graphical model for functional connectivity estimation. InInternational Conference on Information Processing in Medical Imaging 2013 Jun 28 (pp. 256-267). Springer, Berlin, Heidelberg.

[45] Colclough, G. L., Woolrich, M. W., Harrison, S. J., Rojas Lpez, P. A., Valdes-Sosa, P. A., Smith, S. M. (2018). Multi-subject hierarchical inverse covariance modelling improves estimation of functional brain networks. NeuroImage,

[46] Boyd S, Parikh N, Chu E, Peleato B, Eckstein J. Distributed optimization and statistical learning via the alternating direction method of multipliers. Foundations and Trends in Machine learning. 2011 Jul 26;3(1):1-22.

[47] Chen Y, Wiesel A, Eldar YC, Hero AO. Shrinkage algorithms for MMSE covariance estimation. IEEE Transactions on Signal Processing. 2010 Oct;58(10):5016-29

[48] Barachant A, Bonnet S, Congedo M, Jutten C. Multiclass braincomputer interface classification by Riemannian geometry. IEEE Transactions on Biomedical Engineering. 2011 Oct 14;59(4):920-8.

[49] Barachant A, Bonnet S, Congedo M, Jutten C. Classification of covariance matrices using a Riemannian-based kernel for BCI applications. Neurocomputing. 2013 Jul 18;112:172-8./.

[50] Moakher M. A differential geometric approach to the geometric mean of symmetric positive-definite matrices. SIAM Journal on Matrix Analysis and Applications. 2005;26(3):735-47.

[51] Zou H, Hastie T. Regularization and variable selection via the elastic net. Journal of the royal statistical society: series B (statistical methodology). 2005 Apr 1;67(2):301-20.

[52] Liang M, Hu X. Recurrent convolutional neural network for object recognition. InProceedings of the IEEE conference on computer vision and pattern recognition 2015 (pp. 3367-3375).

[53] Shuman DI, Narang SK, Frossard P, Ortega A, Vandergheynst P. The emerging field of signal processing on graphs: Extending high-dimensional data analysis to networks and other irregular domains. arXiv preprint arXiv:1211.0053. 2012 Oct 31.

[54] Kawahara J, Brown CJ, Miller SP, Booth BG, Chau V, Grunau RE, Zwicker JG, Hamarneh G. BrainNetCNN: convolutional neural networks for brain networks; towards predicting neurodevelopment. NeuroImage. 2017 Feb 1;146:1038-49.

[55] Defferrard M, Bresson X, Vandergheynst P. Convolutional neural networks on graphs with fast localized spectral filtering. InAdvances in neural information processing systems 2016 (pp. 3844-3852).

[56] Snoek L, Mileti S, Scholte HS. How to control for confounds in decoding analyses of neuroimaging data. NeuroImage. 2019 Jan 1;184:741-60.

[57] UKB Pre-processing pipeline, `http://biobank.ctsu.ox.ac.uk/crystal/crystal/docs/brain_mri.pdf`. Last accessed 18th August 2019

[58] HCP Pre-processing pipeline, `https://db.humanconnectome.org/megatrawl/HCP820_MegaTrawl_April2016.pdf`. Last accessed 18th August 2019

[59] Abbott A. A problem for our age. Nature. 2011 Jul 14;475(7355):S2.

[60] Jaeggi SM, Buschkuehl M, Jonides J, Perrig WJ. Improving fluid intelligence with training on working memory. Proceedings of the National Academy of Sciences. 2008 May 13;105(19):6829-33.

[61] He T, Kong R, Holmes A, Nguyen M, Sabuncu M, Eickhoff SB, Bzdok D, Feng J, Yeo BT. Do Deep Neural Networks Outperform Kernel Regression for Functional Connectivity Prediction of Behavior?. BioRxiv. 2018 Jan 1:473603.

[62] Neuroticism Score, `https://biobank.ctsu.ox.ac.uk/crystal/crystal/docs/MentalStatesDerivation.pdf`. Last accessed 18th August 2019

[63] Cole JH, Poudel RP, Tsagkrasoulis D, Caan MW, Steves C, Spector TD, Montana G. Predicting brain age with deep learning from raw imaging data results in a reliable and heritable biomarker. NeuroImage. 2017 Dec 1;163:115-24.

[64] Bijsterbosch JD, Woolrich MW, Glasser MF, Robinson EC, Beckmann CF, Van Essen DC, Harrison SJ, Smith SM. The relationship between spatial configuration and functional connectivity of brain regions. Elife. 2018 Feb 16;7:e32992.

[65] Bijsterbosch JD, Beckmann CF, Woolrich MW, Smith SM, Harrison SJ. The relationship between spatial configuration and functional connectivity of brain regions revisited. Elife. 2019 May 8;8:e44890.

[66] He T, Kong R, Holmes A, Nguyen M, Sabuncu M, Eickhoff SB, Bzdok D, Feng J, Yeo BT. Do Deep Neural Networks Outperform Kernel Regression for Functional Connectivity Prediction of Behavior?. BioRxiv. 2018 Jan 1:473603.

[67] Murphy KP. Machine learning: a probabilistic perspective. MIT press; 2012 Sep 7.

[68] Ng B, Varoquaux G, Poline JB, Greicius M, Thirion B. Transport on Riemannian manifold for connectivity-based brain decoding. IEEE transactions on medical imaging. 2015 Aug 3;35(1):208-16.

[69] Dadi K, Rahim M, Abraham A, Chyzhyk D, Milham M, Thirion B, Varoquaux G, Alzheimer's Disease Neuroimaging Initiative. Benchmarking functional connectome-based predictive models for resting-state fMRI. NeuroImage. 2019 Mar 2.

[70] Shirer WR, Ryali S, Rykhlevskaia E, Menon V, Greicius MD. Decoding subject-driven cognitive states with whole-brain connectivity patterns. Cerebral cortex. 2012 Jan 1;22(1):158-65.

[71] Hsieh CJ, Dhillon IS, Ravikumar PK, Sustik MA. Sparse inverse covariance matrix estimation using quadratic approximation. InAdvances in neural information processing systems 2011 (pp. 2330-2338).

[72] Suykens JA, Vandewalle J. Least squares support vector machine classifiers. Neural processing letters. 1999 Jun 1;9(3):293-300.

[73] Shen X, Finn ES, Scheinost D, Rosenberg MD, Chun MM, Papademetris X, Constable RT. Using connectome-based predictive modeling to predict individual behavior from brain connectivity. nature protocols. 2017 Mar;12(3):506.

Appendix A.   Inline Supplementary Figures

Figure A.15: The impact of various parcellation strategies and functional connectivity estimation methods on prediction power for non-imaging variables **without deconfounding**. [**A,B,C**] (**HCP Data**): A corresponds to the prediction accuracy for sex, and B and C correspond to prediction correlation (r) for fluid intelligence score and age respectively. [**D,E,F,G**] (**UKB Data**): D corresponds to the prediction accuracy for sex whereas E, F, and G correspond to the prediction correlation (r) for fluid intelligence scores, age, and neuroticism scores respectively. For HCP, the ICA based parcellation schemes are ICA_15D, ICA_50D and ICA_200D, and for UKB are ICA_21D and ICA_55D, where D = the number of parcels. For both HCP and UKB, SHEN parcellation was 268D, YEO was 100D, and PROFUMO was 50D (for HCP only).

Figure A.16: The impact of various reference mean estimation techniques during tangent space parameterization on prediction of non-imaging variables **without deconfounding**. **[A] (HCP Data), [B] (UKB Data)** These figures show the prediction correlation for fluid intelligence scores when functional connectivity estimates are projected into tangent space, using different reference means. The violin plot represents the prediction variability over 3 different parcellation schemes and 5 measures of functional connectivity estimates in the tangent space.

Figure A.17: The impact of tangent space parameterization on prediction power for non-imaging variables **without deconfounding**. **[A,B,C] (HCP Data), [D,E,F,G] (UKB Data):** The x-axis corresponds to prediction correlation/accuracy. The y-axis lists various functional connectivity estimates, such as "Covariance ICA_15D", which corresponds to ICA with 15D parcellation strategy and then estimating functional connectivity using empirical covariance. Likewise, "SGGGM PROFUMO" means first finding parcels with PROFUMO and then estimating functional connectivity using SGGGM. Euclidean mean is used as a reference mean for tangent space parameterization. The classifiers/predictors that did not converge do not contain the corresponding data point.

Figure A.18: The impact of isotropic versus non-isotropic shrinkage in tangent space on prediction power for non-imaging variables **after deconfounding**. **[A] (HCP Data), [B](UKB)**: The y-axis depicts the prediction accuracy/correlation for different non-imaging measures. Isotropic Shrinkage means that Ledoit-Wolf shrinkage was applied to projected functional connectivity estimates in tangent space before they were fed to a predictor. The Non-Isotropic Shrinkage strategy means that PoSCE shrinkage was applied to connectivity estimates in tangent space before they were fed to a predictor.

Figure A.19: The impact of applying isotropic shrinkage in tangent space on prediction power after deconfounding. **[A] (HCP Data), [B](UKB)**: The y-axis depicts the prediction accuracy/correlation for different non-imaging measures. Isotropic Shrinkage means that Ledoit-Wolf shrinkage was applied to projected functional connectivity estimates in tangent space before they were fed to a predictor. "No Shrinkage" means that projected functional connectivity estimates in tangent space were directly fed to the predictor, and did not undergo Ledoit-Wolf shrinkage.

Figure A.20: The top performing five configurations for the prediction of each non-imaging variable by dataset **without deconfounding**. **[A,B,C] (HCP Data)** Each data point represents a different configuration strategy that may vary in terms of parcellation strategy, the functional connectivity estimation method, whether tangent space parameterization was employed, whether tangent space regularization was employed, and the predictor that was used. The first word indicates the parcellation strategy, and the second word refers to the functional connectivity estimation method. The third word refers to the geometry in which classifier is applied, ambient referring to non-tangential space and tangent referring to the projected covariance matrices in tangential space. If non-isotropic shrinkage was applied after projecting covariance matrices to tangential space, the fourth word will be "shrinkage". The last word indicates the type of classifier/predictor that was used.

Figure A.21: The top performing five configurations for the prediction of each non-imaging variable by dataset **without deconfounding**. [A,B,C,D] (UKB Data): Each data point represents a different configuration strategy that may vary in terms of parcellation strategy, the functional connectivity estimation method, whether tangent space parameterization was employed, whether tangent space regularization was employed, and the predictor that was used. The first word indicates the parcellation strategy, and the second word refers to the functional connectivity estimation method. The third word refers to the geometry in which classifier is applied, ambient referring to non-tangential space and tangent referring to the projected covariance matrices in tangential space. If non-isotropic shrinkage was applied after projecting covariance matrices to tangential space, the fourth word will be "shrinkage". The last word indicates the type of classifier/predictor that was used.

Figure A.22: This parallel coordinates plot provides a visualization of all possible combinations of options in the pipeline to predict fluid intelligence scores from functional connectivity **without deconfounding**. **[A] (HCP Data)**, **[B] (UKB Data)**: The lines are color-coded according to their prediction performance.

Figure A.23: This parallel coordinates plot provides a visualization of all possible combinations of options in the pipeline to pipeline to predict sex from functional connectivity **without deconfounding**. **[A] (HCP Data), [B] (UKB Data):** The lines are color-coded according to their prediction performance.

Figure A.24: This parallel coordinates plot provides a visualization of all possible combinations of options in the pipeline to pipeline to predict age from functional connectivity **without deconfounding**. **[A] (HCP Data), [B] (UKB Data):** The lines are color-coded according to their prediction performance.

Figure A.25: This parallel coordinates plot provides a visualization of all possible combinations of options in the pipeline to predict neuroticism score from functional connectivity. [**A**] shows the result before confounds removal and [**B**] shows the result after regressing out the confounds.

Figure A.26: The proposed architecture of 2D RCNN. A recurrent block is unfolded on the right for T = 3 time steps. At T = 0, it is only a feed-forward network with a single residual block. At T = 4, it has depth of 4 with additional recurrent connections. Each residual block is further composed of addition, batch normalization, convolution and activation layers.

Comparison with Connectome-based Predictive Modelling (CPM)

Parcellation: SHEN
Functional Connectivity Estimation: Full
Tangent Space Parameterization: No
Tangent Space Shrinkage: No
Predictor: CPM model vs Elastic Net

Parcellation: ICA_50
Functional Connectivity Estimation: Full
Tangent Space Parameterization: No
Tangent Space Shrinkage: No
Predictor: CPM model vs Elastic Net

Figure A.27: The comparison of Elastic Net and CPM prediction performance. CPM predictor is based on a model that averages connectivity edges from a subset of all edges.

Comparison with GraphCNN

Parcellation: PROFUMO
Functional Connectivity: Covariance/Full
Tangent Space Parameterization: Yes
Tangent Space Shrinkage: No
Predictor: GraphCNN vs Elastic Net

Parcellation: PROFUMO
Functional Connectivity: Covariance/Full
Tangent Space Parameterization: Yes
Tangent Space Shrinkage: Yes
Predictor: GraphCNN vs Elastic Net

Figure A.28: The comparison of Elastic Net and GraphCNN prediction performance. We have chosen a subset (e.g., parcellation (PROFUMO), functional connectivity estimation (Full/Covariance)) from all available configurations to illustrate the performance of GraphCNN.