1

Electrophysiological correlates of the flexible allocation of visual working memory resources

Christine Salahub[1*], Holly A. Lockhart[1], Blaire Dube[2], Naseem Al-Aidroos[2], and Stephen M. Emrich[1]

[1]Department of Psychology, Brock University
St. Catharines, Ontario, Canada

[2] Department of Psychology, University of Guelph
Guelph, Ontario, Canada

Word Count
Methods: 2,760
Main Text: 4,652

*Corresponding Author: Christine Salahub, christine.salahub@brocku.ca, Department of Psychology, Brock University, 1812 Sir Isaac Brock Way, L2S 3A1, St. Catharines, Ontario, Canada

Author Contributions: C.S., H.A.L., N.A., and S.M.E conceived of the experimental designs. C.S., H.A.L., and S.M.E. analyzed the data; C.S., H.A.L., and B.D. collected the data. C.S. and S.M.E. took the lead in preparing the manuscript. All authors discussed the interpretation of results and contributed to the final manuscript.

Acknowledgements: This work was supported by NSERC grants (#435945 and #458707) awarded to S.M.E., and NSERC PGS-D scholarships awarded to C.S. and H.A.L. We thank Joey Capozza (experiment programming/data collection), Thomas Nelson (experiment programming), and Brenda de Wit (data collection).

1   Abstract

Efficiently allocating capacity-limited cognitive resources is critical to guiding behavior

effectively. Although previous research has suggested that distractors are blocked from

memory access, recent work proposes a more flexible attentional filter that acts based

on item priority. Here, we investigated the electrophysiological correlates of flexible

attentional prioritization by manipulating the distribution of memory resources amongst

items. Across three experiments, we found that the contralateral delay activity (CDA), a

component typically associated with visual working memory (VWM) load, was affected

by both memory load and resource allocation. This allocation occurred as early as

during attentional selection, as indicated by the N2pc. Additionally, CDA amplitude was

well described when fit with a continuous power law function with load and resources

together, more so than when fit with either alone. Together, these findings suggest that

ERP markers of attentional selection and memory maintenance track attentional

prioritization in addition to VWM load.

More likely than not, it is much easier for you to recall the names of the

characters from the last television show that you watched than what you were wearing

while you watched it. This bias in memory is in part due to the fact that what we allocate

more attention to is remembered with greater detail[1]. Indeed, numerous studies of long-

term memory have established that attention prioritizes relevant information to be

encoded into memory[2–4]. Attention also affects the maintenance and quality of

information stored over shorter periods of time, such as in visual working memory[5–7]

(VWM). In fact, given that VWM is limited in capacity, several models of VWM have

suggested that attention may play a critical role in determining what information gains

access to these finite storage resources[8–11].

One potential mechanism through which attention may drive working memory

performance is by filtering out irrelevant distractors[12]. Filtering efficiency has been

quantified using measurements of electrophysiological brain activity related to working

memory storage, specifically an event-related potential (ERP) called the contralateral

delay activity[13–16] (CDA). CDA amplitude increases with the number of items stored in

VWM, saturating as memory load increases beyond a few items[17]. Interestingly, when

distractors are presented alongside targets in a memory display, lower-capacity

individuals exhibit larger CDA amplitudes than those with higher capacities, reflecting

the fact that they have encoded and stored more distractors in memory[16]. This finding

has been taken as evidence that poor filtering efficiency, resulting in unnecessary

storage, is a critical determinant of VWM capacity.

Several recent studies have demonstrated that it is also possible to bias

attentional resources toward and away from certain items in a flexible manner,

independent of the need to filter out irrelevant distractor items. This bias can be induced

by associating certain stimuli with monetary incentives, or by simply varying instructions

indicating the probability that an item will be probed on any given trial[7]. For example,

spatial cues[18] or feature-based cues[19] can be used to change the likelihood that a given

item will be probed. In this way, the proportion of attentional resources allocated to any

given memory item can continuously vary anywhere between 0 and 100%.

In these past studies[18,19], it was found that working memory performance (i.e.,

raw error = 1/ precision) was best predicted by the likelihood that an item would be

probed on a given trial, independent of the overall memory load. These findings support

the idea that attentional resources can be continuously allocated across items, even

when they are of very low priority. Importantly, this relationship between probe likelihood

and memory precision, which followed a power law, could also account for changes in

performance across loads; for example, the change in precision from one to two items

was consistent with each item only receiving half as many attentional resources. This

framework suggests that attention does more than just restrict or grant access to VWM;

rather, it also flexibly distributes resources amongst memory items based on their

respective priorities. In other words, how attention is allocated between targets is as

important to memory performance as whether or not it is allocated to distractors[20].

If attention can be flexibly allocated across items in VWM, how might this be

reflected by neural measures of attention and VWM maintenance? There is evidence

that the CDA is well-described by a saturation model, which predicts a continuous

increase in CDA amplitude that saturates as set size becomes larger, instead of

increasing discretely and plateauing at memory capacity[17]. This finding suggests that

the CDA, much like VWM performance, may be more flexibly affected by memory load

than previously thought. Yet, it is currently unknown whether the CDA is also flexibly

affected by the prioritization of memory items instead of, or in addition to, changes in

memory load.

Prioritization could also be tracked by ERP components that precede memory

maintenance, such as attentional selection and suppression. That is, one way that

flexible prioritization could be accomplished is through the specific up-weighting of goal-

relevant over irrelevant information (as opposed to down-weighting of goal-irrelevant

information). Attentional selection can be tracked by the N2pc, a lateralized component

which specifically reflects the enhancement of an item[21–23]. Alternatively, it could be that

prioritization is accomplished through the active suppression or down-weighting of goal

irrelevant information. This can be measured by the distractor positivity (P_D): a

lateralized component that is observed when distractors are presented laterally in the

stimulus display[24–27]. These two components can thus be used to disentangle the

underlying mechanisms of prioritization: whether through selective enhancement of

relevant information (N2pc) or suppression of irrelevant information (P_D).

Consequently, to determine the effect of resource allocation on the CDA, as well

as whether prioritization is driven by selective enhancement of high-priority items or

inhibition of low-priority items, we conducted three experiments in which the allocation

of memory resources across items was manipulated in a continuous-report delayed-

recall task. For these experiments, we use the term *memory load* to refer to the number

of items with greater than zero percent likelihood of being probed. We use the terms

resource allocation or *probability* to refer to the likelihood that one item, or a set of

items, will be probed. In Experiment 1, we examined how changes in resource

allocation amongst memory items influenced the CDA in comparison to the typical effect

of memory load. To do this, participants were asked to remember the colors of four

laterally presented items that were either equally likely to be probed, or where a spatial

cue indicated that one item was more likely to be probed than the others. Thus, while

participants should always be allocating 100% of memory resources to these items, how

the resources are distributed across items varied. In Experiments 2 and 3, we took

advantage of an attribute of the CDA, N2pc, and P_D – that these components are only

sensitive to laterally presented stimuli and not stimuli presented on the vertical midline –

to separately manipulate the effects of memory load and resource allocation on the

CDA. In Experiment 2, two items were presented laterally and two vertically, and a

featural cue indicated whether the lateral or vertical items were more likely to be probed.

Thus, this design allowed us to manipulate the proportion of memory resources

specifically allocated to lateral items. In Experiment 3, we tested whether the CDA

reflects the allocation of memory resources even in the absence of prioritization cues.

To do so, we manipulated the total number of items to-be-remembered (four or six),

while systematically changing the number of items presented laterally. In this way, we

could simultaneously manipulate lateral memory load and proportion of memory

resources allocated to the lateral items.

Methods

Participants

All participants gave written informed consent of the procedures as approved by

a university ethics review board. Participants received partial course credit or paid

remuneration ($15/hour) for participating. Consistent with prior research[15,16,28], we

aimed for a sample size of 20 participants (right handed, normal-color vision, no history

of mental illness). To reach these targets a total of 30 participants were run in

Experiment 1, 33 in Experiment 2, and 28 in Experiment 3. Data were replaced if > 35%

of trials were removed due to EEG artifacts (10 in Experiment 1, 6 in Experiment 2, and

4 in Experiment 3). Additionally, in Experiments 2 and 3 data were replaced if average

residual HEOG activity was > 4 µV (6 in Experiment 2 and 4 in Experiment 3; see

Electrophysiological Recording and Analysis). Distinct samples (N = 20) were used for

each experiment *(*Exp 1*: M*$_{age}$ = 22.0, *SD*$_{age}$ = 3.0, 10 male; Exp 2: *M*$_{age}$ = 22.6, *SD*$_{age}$ =

4.2, 9 male; Exp 3: *M*$_{age}$ = 21.6, *SD*$_{age}$ = 3.9, 3 male).

Stimuli and Procedures

All tasks were completed on a Windows PC with a 41-cm NEC MultiSync LCD

2090UXi computer monitor (1600 x 1200 pixels, 60 Hz refresh rate) in a private testing

room. Stimuli were rendered using Psychopy v1.90.3 (Peirce, 2007) and presented on a

grey background (RGB = 128 128 128) with a central fixation dot (radius of 0.3° visual

angle). Viewing distance was approximately 57 cm (no chin rest was used). In all

experiments, participants first completed a standard change detection task [29]. However,

these data are not included in the analyses below.

The colors for the squares in the continuous report VWM tasks were chosen

pseudo-randomly from a 360-degree isoluminant color wheel (CIE L*a*b* color space, [L

= 70, a = -6, b = 14, radius = 49]), which was calibrated to the testing monitor using a

chroma meter (Konica Minolta CS-100A; Konica Minolta Sensing Americas, Inc.,

Ramsey, New Jersey). On every trial the memory stimuli colors were separated by at

least 30 degrees on the color wheel.

Experiment 1.

Visual working memory task with spatial-based prioritization cues (Figure

2A).

Each trial began with a centrally presented arrow (3° x 3°, 200 ms), indicating

which half of the screen contained the target stimuli. Next, a fixation screen was

presented for a random interval (200 – 500 ms) followed by the memory array

consisting of four squares on both sides of the screen (1° x 1°, 4° from fixation,

separated by 1°, 150 ms). One or four of the laterally presented squares appeared with

a horizontal spatial line cue (2° long x 1° wide, 2° from fixation) depending on the

condition (both sides of the screen included a cue to balance visual input). At the

beginning of each block, participants were given instructions on the cue-validity (i.e., the

probability the cued item would be probed). There were three conditions: In the 1-

Cue/100%-Valid condition, the one cued item would always be the target; In the 4-

Cues/100%-Valid condition, all four items could potentially be the target, resulting in

approximately 25% of memory resources being allocated toward each item; In the 1-

Cue/50%-Valid condition, the one cued item would be probed on 50% of trials and any

of the remaining three items would be probed on the other 50%.

Following the memory array, a fixation dot was presented for 900 ms followed by

the response screen, wherein a colour wheel (diameter of 7°) appeared around the

task-relevant lateral stimuli. Black outlines appeared at the same locations as the

memory array (line width of 1 pixel), with one outline bolded (line width of 3 pixels)

indicating the target location for the color response. Participants made their choice by

clicking on the color wheel with the mouse. As the mouse was moved around the color

wheel, the probed square outline was filled with the presently selected color.

There were a total of 960 trials: 240 in both the 1-Cue/100%-Valid and 4-

Cues/100%-Valid Conditions, and 480 in the 1-Cue/50%-Valid condition, which allowed

for 240 valid trials, split equally between the left and right sides of the screen. One

participant's data consisted of only 840 trials due to a recording error. Participants were

given a self-paced break every 25 trials.

Experiment 2.

Luminance matching task.

In both Experiments 2 and 3 participants first completed a subjective luminance-

matching task in which a staircase method was used to match the brightness of 12

colors from the color wheel with a grey color. These individual luminance-matched

greys were used as placeholder colors in both experiments (see Supplemental

Materials for more information).

Visual working memory task with feature-based prioritization cues (Figure

3A).

After pressing any key, trials began by a written cue (1.5° tall, 800 ms) indicating

the likelihood that the color of a shape (square or circle) would be probed on that trial

(100% or 75% valid). There were two cue instructions, such that it was either 100% or

75% likely that the color of a certain shape would be tested. Cued shape was

counterbalanced across participants. These cues led to an implicit probability for the

non-cued shape. For example, if it were 100% likely that the color of a square would be

probed, then there was a 0% chance that a circle would be probed

Next, there was a jittered fixation screen (500 – 1,000 ms) followed by the

memory array (200 ms) consisting of 8 shapes. Four shapes were always presented

laterally (two left and two right) and four vertically (two top and two bottom; 3° from

fixation to center of the cluster). Two shapes within a cluster were presented 1.2° apart

vertically (center to center). There were always two colored squares (1° x 1°, black

outline width of 1 pixel) and two colored circles (diameter of 1°) presented. If colored

squares were presented laterally, then colored circles were presented vertically and vice

versa. The remaining four items were filled with the subjectively luminance-matched

grey and were always the un-cued shape. Shapes were presented in all possible

position configurations equally (16 unique positions).

After the memory array was presented, there was a delay screen with a fixation

dot (900 ms). The response screen (similar to Experiment 1) was unspeeded. The

probed shape was chosen pseudo-randomly from the top or bottom shape in a cluster,

depending on the probability cue. Every 50 trials participants were presented with a

break screen. All participants received 20 practice trials.

There were a total of four conditions that varied by the probability that the color of

the shape presented on the lateral would be probed at test: 100%, 75%, 25%, and 0%.

Participants completed a total of 816 trials (100% lateral: 200, 0% lateral: 200, 75%

lateral: 208, 25% lateral: 208). One participant completed 806 trials due to a

programming error, and another completed 807 trials due to an interruption to the

recording session.

Experiment 3.

Visual working memory task with lateralized resource and load

manipulation (Figure 5A).

Participants were instructed to remember the colors of all of the squares in the

memory array, and that each square was equally likely to be probed. Each trial began

with a jittered fixation screen (500 –1,500 ms) followed by the lateralized memory array

(200 ms). There were three conditions defined by the proportion of memory resources

allocated toward the lateral items. 1) Load 4 with three colored squares presented in a

vertical cluster to the left or right of fixation (1° x 1°, black outline width of 1 pixel, 1.2°

apart center-to-center, 3° from fixation to center of the group of squares) and one

colored square presented vertically. This condition reflects 75% of attention to the

lateral while maintaining a total of 4 items in memory. 2) Load 4 with one square

presented laterally and three squares on the vertical, resulting in 25% lateral attention.

3) Load 6 with three squares presented laterally and 3 vertically, resulting in 50% of

attention to the lateral. For all memory arrays there were an equivalent number of

luminance-matched grey squares presented opposite to the colored squares. Counter-

balancing of stimuli positions was the same as in Experiment 2.

Next, there was a 900 ms delay period consisting of a fixation screen followed by

the probe screen (same as in Experiment 2). Participants were then given feedback

after their response (800 ms), where 'Correct' was considered within 40° on the target

color. Participants completed a total of 900 trials, 300 of each condition

counterbalanced across the 16 possible position combinations. There were 12 practice

trials and self-paced breaks were given every 50 trials.

EEG Recording and Pre-Processing

All EEG pre-processing was done in MATLAB with the EEGLAB[30] (Version

14.0.0b), and ERPLAB[31] (Version 6.1.2) toolboxes. EEG was DC recorded at a 512 Hz

sampling rate from a 64 Ag/AgCl electrode cap placed at the standard 10-20 sites[32].

The signal was online referenced to the common mode sense (CMS) and the driven

right leg (DRL) electrodes. Data were re-referenced off-line to the average of the

mastoids, baseline corrected to -200 ms before memory array onset, and filtered with a

40-Hz low-pass and 0.1-Hz high-pass Butterworth filter (slope: 12dB/octave). For

illustrative purposes only, data were low-pass filtered at 30-Hz. Data were epoched

between -200 and 1,050 (Experiment 1) or -200 and 1,100 ms (Experiment 2) ms, time-

locked to the memory array.

Artifact rejection.

Horizontal electro-oculogram (HEOG) was recorded from bipolar external

electrodes placed laterally beside the eyes. Vertical electro-oculogram (VEOG) was

recorded as the difference between external electrodes placed below the eyes and FP1

or FP2. Participants were instructed not to blink or move their eyes from the start of

each trial to the appearance of the response screen. We used an automated artifact-

rejection procedure to remove trials with VEOG activity greater than ±80 µV or HEOG

activity greater than ±32 µV (using a step function) between stimuli onset and the end of

the trial. We also removed trials in which the voltage over posterior channels (P1/2,

P3/4, P5/6, P7/8, P9/10, PO3/O4, PO8/O7, and O1/2) was ± 100 µV. In the final sample

an average of 21.4% of trials rejected in Experiment 1, (SD = 10.4%), 11.6% in

Experiment 2 (*SD* = 7.8%), and 13.3% in Experiment 3 (*SD* = 10.1%). Across studies,

each participant had more than 100 trials in each ERP condition bin.

In Experiments 2 and 3 we also replaced participants whose average residual

HEOG activity (relative to the side of the lateralized memory array) was greater than 4

µV between memory array onset and the end of the epoch. On average across

conditions, the absolute residual HEOG was 1.61 µV (*SD* = 1.02 µV) in Experiment 2

and 1.61 µV (*SD* = 1.00 µV) in Experiment 3. This means that the deviation in lateral

eye movements was less than ± 0.1° relative to the location of the lateralized memory

array in both experiments, and that the estimated voltage propagation was overall less

than 0.1 µV at posterior electrodes[33–35].

Data Analysis

Behavioral data.

Performance was assessed using the trial-by-trial raw response error (i.e., the

difference in degrees between the color of the probed item and the participant's

response) and was computed using the standard deviation of response errors. Lower

values reflect more precise responding. We predicted that as the amount of memory

resources provided to an item increased, error would decrease, following a power-

law[18,19,36]. To test this, we fitted the behavioral data across all experiments to a power-

law function:

$$y \propto ax^{-k}$$

Bayesian information criterion (BIC) values were computed to compare model

fits. Raw error values were calculated using custom scripts in MATLAB. Goodness of fit

was computed using nonlinear least squares regression in MATLAB's Curve-Fitting

Toolbox using a bisquare robust fitting procedure with the group data averaged across

conditions. Degrees of freedom-adjusted-R^2 and root mean square error (*RMSE*) values

are also reported.

ERP data.

Difference waves were calculated as contralateral minus ipsilateral activity in

each condition. In Experiment 1, laterality was determined in reference to the pre-cued

side of the screen. In Experiments 2 and 3, laterality was determined in reference to the

side of the screen on which the colored lateral items were presented.

We measured difference wave activity at five posterior electrode pairs: P3/4,

P7/8, PO7/O8, PO3/O4, and O1/2[37]. Across all experiments, there was no significant

Condition x Channel interaction for any of the ERP components (*F*s < 2.24, *p*s > .055,

η^2_ps < .106). Therefore, we averaged activity across these electrode sites for all ERP

measurements.

For each ERP component of interest, we ran a repeated-measures ANOVA on

the mean condition amplitudes. Follow-up linear contrasts and fits were completed in

Experiments 2 and 3 for the N2pc and CDA. Greenhouse-Geisser corrected degrees of

freedom and *p* values are reported. Two-tailed post-hoc t-tests were Bonferroni-

corrected. Cohen's d is reported where appropriate. Bayesian repeated-measures

ANOVAs and post-hoc tests are reported where applicable (r scale prior width of 0.5,

default Cauchy prior centered on 0, 10,000 Monte Carlo samples). Bayes factors (BF_{10})

are presented as the marginal likelihood for the alternative model compared to the null

model[38]. Statistical analyses were completed using JASP Version 0.8.4[39], MATLAB

R2017a, and R version 3.5.1[40] in RStudio version 1.1.456[41].

CDA.

In all experiments, the CDA was measured for each condition and participant as

the mean amplitude during the delay period from 400 ms post-stimuli offset to the end of

the trial[42,43] (Experiment 1: 1,050 ms; Experiments 2 and 3: 1,100 ms).

N2pc.

An N2pc was only observed in Experiment 2 and was measured from 200 – 300

ms post-stimuli onset[44–47]. To determine whether individuals were selecting the higher

priority items any faster than the lower priority items, we also measured the negative

50% fractional area latency of the N2pc between 200 – 300 ms for each participant and

condition [48].

P_D.

We predicted there to be a P_D in Experiment 2 exclusively, as this was the only

task in which there were systematically lateralized distractors. In Experiment 2, we

measured the P_D as the positively signed area from 250 – 400 ms[49,50]. Because the

positively signed area is biased away from zero, we used a nonparametric permutation

approach developed by Sawaki and colleagues[51] to determine the presence of the P_D.

This method estimates the area of the waveform above zero that would be expected by

noise alone, which can then be compared to the observed area of the grand-average P_D

in each condition.

The *p* values for the permutation tests were estimated using the following formula

with 1,000 permutations[33]:

$$p = \frac{\text{Number of permuted areas} \geq \text{observed area}}{\text{Total number of simulated permutations}}$$

EEG and behavior correlations.

In Experiment 2, we predicted a correlation between ERPs and behavior, such

that as N2pc /CDA amplitudes increased, responses would become more precise. To

examine this, we ran a repeated measures correlation analysis using the *rmcorr*

package in R[52]. Each participant provided three data points for the 100%, 75%, and

25% lateral memory resource conditions. We obtained the repeated measures

correlation coefficient between raw error for all trials in each condition and the mean

amplitude of the N2pc and the mean amplitude of the CDA.

Modelling CDA data.

In Experiments 2 and 3, to examine whether the CDA increased continuously

relative to load and resource allocation, we fitted the CDA amplitudes to a power-law

(we obtained an identical pattern of results using a saturation model[17], although with

worse overall fits). Mean CDA amplitudes were fit to three different models: 1) CDA

amplitude was compared to lateral memory load alone; 2) CDA amplitude was

compared to the proportion of resources allocated to the lateral items; 3) CDA amplitude

was compared to a weighted-product of the number of lateral items held in VWM and

the amount of memory resources allocated to them. The weighted-product values were

calculated by the following formula:

18   % of lateral resources × number of lateral items

For example, in Experiment 2 when it was 25% likely that a lateral item would be

probed, then 25% × 2 items were stored in memory, resulting in a weighted score of 0.5.

The weighted-product values for each condition in Experiment 2 were: 0, 0.5, 1.5, and

2. In Experiment 3, the lateralization procedure influenced the amount of memory

resources allocated toward the lateral items (i.e., when 3 of 6 items were presented

laterally, 50% of memory resources were allocated toward those items: 3 × 50% = 1.5).

Therefore, there were 3 weighted-product values: 0.25, 2.25, and 1.5. In total, there

were 7 data points across the two studies. Model fits were completed using the Curve

Fitting Toolbox in MATLAB and custom MATLAB scripts to calculate BIC values to

compare model fits.

6   **Results**

7   **Behavioral: Experiments 1 - 3**

8   Because we manipulated proportion of memory resources per item across all

experiments, and were interested in how behavior changed as a function of resource

allocation, behavioural results were collapsed across all three experiments.

To compare how performance changed as a function of resource allocation, all

data points were fitted to a power law function. Consistent with past findings[18,19], this

provided a good fit (Figure 1), with the model accounting for around 79% of the variance

in the data, adjusted-R^2 = .788, *RMSE* = 6.263. These results demonstrate that the

proportion of memory resources allocated to an individual item was highly predictive of

behavioral precision for that item. Moreover, percent of memory resources allocated to

an item better predicted behavioral precision than memory load alone: adjusted-R^2 =

.431, *RMSE* = 10.97, Δ*BIC* = 9.71. Thus, regardless of the behavioural manipulation

(i.e., spatial cues; feature-based cues; memory load), error is strongly predicted by the

percentage of resources allocated.

Figure 1. Standard deviation of raw response error by percent memory resources in each experiment, fit with a power law. Dashed grey lines represent fits performed on the 95% confidence interval of the condition means.

ERPs

Experiment 1

In Experiment 1, we sought to examine how the prioritization of some items over others affected the CDA. Four lateral memory items were always presented, and spatial cues indicated the number of items to be remembered, as well as the likelihood of a given item to be probed. Based on past demonstrations that the CDA primarily reflects VWM load, we should observe a larger CDA amplitude in the 4-Cues/100%-Valid condition than the 1-Cue/100%-Valid condition; remembering four items results in a larger CDA than remembering a single item. What remains an open question is how the CDA changes when resources are distributed unequally across the four memory items. Thus, comparing the 4-Cues/100%-Valid condition to the 1-Cue/50%-Valid condition provides an initial test of how resource allocation affects CDA amplitude.

CDA.

The spatial prioritization cues influenced CDA amplitude (Figure 2B; main effect

of Condition, $F(2,38) = 5.83$, $p = .006$, $\eta^2_p = .235$, $BF_{10} = 6.98$). Consistent with a

memory load effect, there was a more negative CDA amplitude when all four items were

cued ($M = -0.545$ μV, $SD = 0.659$ μV), than when one item was cued at 100% validity

($M = -0.168$, $SD = 0.698$ μV), $t(19) = 3.43$, $p_{bonf} = .008$, d = 0.767, $BF_{10} = 14.943$. CDA

amplitude in the 1-Cue/50%-Valid condition ($M = -0.285$ μV, $SD = 0.522$ μV) was not

significantly different from the 1-Cue/100%-Valid condition, $t(19) = 0.981$, $p_{bonf} = 1$, d =

0.219, $BF_{10} = 0.355$, or from the 4-Cues/100%-Valid condition, $t(19) = 2.377$, $p_{bonf} =$

.084, d = 0.532, $BF_{10} = 2.196$. While the CDA amplitude in the 1-Cue/50%-Valid

condition was numerically smaller than in the 4-Cues/100%-Valid condition, this

difference was not born out in the inferential statistics. Instead, the CDA amplitude in

the 1-Cue/50%-Valid condition appeared to be in between the amplitudes of the other

conditions (i.e., between holding one and four items in memory).

Figure 2. A) Task schematic of Experiment 1. Each trial began with a lateralization cue followed
by a jittered ITI consisting of a fixation dot. Conditions were blocked and cue probability
instructions provided at the beginning of each block. After a delay, participants made a
response to the probed square on the color wheel with the mouse. B) Grand average difference
waveform (N = 20) at the average of 5 posterior channel pairs, time-locked to stimuli onset.
Positive is plotted up. Filtered at 30 Hz for visualization purposes only.
7

Experiment 2

In Experiment 1 we replicated the typical effect of memory load on CDA

amplitude and the behavioral effect of resource allocation on memory precision.

However, the effects of resource allocation on CDA amplitude were less clear, as both

high and low probability items were presented together laterally, resulting in a mixed

electrophysiological signal. To better isolate the effects of prioritization on CDA

amplitude, in Experiment 2 we separated the items in the memory array along the

horizontal and vertical midlines by employing feature-based cues. Specifically, all

memory arrays comprised two items presented laterally, and two presented on the

vertical midline, with the lateral items either 100%, 75%, 25%, or 0% likely to be probed,

depending on the shape of those items. Because lateralized ERP components are only

sensitive to laterally presented stimuli, we could systematically manipulate the

proportion of lateral memory resources and thus its effect on the N2pc, P_D, and CDA.

N2pc.

The different cueing levels influenced the amplitude of the N2pc (Figure 3B; main

effect of Condition, $F(3,57) = 8.11$, $p < .001$, $\eta^2_p = .299$, $BF_{10} = 176.69$). Overall N2pc

amplitude was more negative when the item was 100% (*M* = -0.331 µV, *SD* = 0.783 µV)

likely to be probed than when it was 0% likely to be probed (*M* = 0.172 µV, *SD* = 0.646

µV), $t(19) = 3.582$, $p_{bonf} = .012$, d = 0.801, $BF_{10} = 20.173$. The N2pc was also larger

when the lateral item was 75% likely (*M* = -0.262 µV, *SD* = 0.791 µV) compared to 0%

likely to be probed, $t(19) = 3.643$, $p_{bonf} = .010$, d = 0.815, $BF_{10} = 22.741$. There was no

significant difference between N2pc amplitude in the 75% and 25% ($M = 0.032$ µV, SD

= 0.615 µV) conditions or any other condition, ps > .065, ds < 0.634, BFs$_{10}$ < 4.86.

However, the overall N2pc amplitude did become linearly more negative as item priority

increased, adjusted-R^2 = .983, $RMSE$ = .0315, linear contrast: $t(19) = 4.81$, $p < .001$,

suggesting that individuals could flexibly allocate their attention toward an item

depending on how important it was to the trial. Interestingly, fractional area latency did

not differ between conditions, $F(1.814, 29.027) = 1.698$, $p = .202$, $\eta^2_p = .096$, $BF_{10} =$

.435. Therefore, participants were not selecting high probability items any faster than

low probability items.

P$_D$.

Permutation tests indicated that the positive area of the grand average waveform

between 250 – 400 ms was not significantly different from noise in any of the conditions,

100%: $p = .529$, 75%: $p = .30$, 25%: $p = .306$, 0%: $p = .087$. Although the P$_D$ was not

significant, it could be that priority still had an influence on its amplitude. There was a

small but non-significant effect of priority on the positive area of the P$_D$, $F(1.84, 34.96) =$

2.95, $p = .070$, $\eta^2_p = .134$, $BF_{10} = 1.36$. Therefore, there was little evidence of active

attentional suppression in this task.

CDA.

Similar to the N2pc, priority affected the amplitude of the CDA (main effect of

Condition, $F(2.09,39.74) = 7.43$, $p = .002$, $\eta^2_p = .281$, $BF_{10} = 251.951$). More information

was stored in VWM when the item was 100% likely to be probed ($M = -0.696$ µV, $SD =$

0.809 µV) than 0% ($M = -0.028$ µV, $SD = 0.382$ µV), $t(19) = 3.323$, $p_{bonf} = .021$, d =

0.743, BF_{10} = 12.198. Similarly, the CDA was more negative in the 100% condition than

the 25% condition (M = -0.042 μV, SD = 0.347 μV), $t(19)$ = -3.118, p_{bonf} = .034, d = -

0.697, BF_{10} = 8.249. When an item was 75% likely to be probed, the CDA amplitude (M

= -0.618 μV, SD = 0.792 μV) was marginally more negative than in the 25% and 0%

conditions, ts < 2.87, p_{bonfs} < .075, ds < 0.641, BFs_{10} > 4.30. No other post-hoc

comparisons were significant, ts < 0.133, p_{bonfs} = 1, ds < 0.104, BFs_{10} < 0.235.

However, similar to the N2pc, CDA amplitude was linearly related to priority, adjusted-

R^2 = .906, $RMSE$ = .1106, linear contrast: $t(19)$ = 4.36, p < .001. Therefore, the more

likely an item was to be probed, the more information about that item was stored in

VWM as tracked by the CDA.

Figure 3. A) Task schematic of Experiment 2. Each trial began with a feature-based cue
followed by a jittered ITI consisting of a fixation dot. In this example, it was 100% likely that the
color of a circle would be probed. The stimulus display consisted of 2 colored shapes on the
lateral and 2 on the vertical. In the present example, if squares were presented on the lateral,
0% of memory resources should be allocated toward them. If circles were presented on the

1   lateral, 100% should be allocated. After a delay, participants made a response to the probed
2   shape on the color wheel with the mouse. B) Grand average difference waveform (N = 20) at
3   the average of 5 posterior channel pairs, time-locked to stimuli onset. Positive is plotted up.
4   Filtered at 30 Hz for visualization purposes only.
5
N2pc and CDA amplitudes predict behavioral precision.

To examine whether memory resource-related changes in N2pc and CDA

amplitudes predicted changes to VWM response error, a repeated-measures correlation

was performed between mean amplitude and response error across three lateral

resource conditions (25%, 75%, and 100%). It was found that attention, as measured by

the N2pc, toward the lateral shapes predicted how precisely the color of the probed

shape was reported, $r_{rm}(39) = 0.549$, 95% CI = [.282, .737], p = < .001 (Figure 4A).

There was also a correlation between raw error and mean amplitude of the CDA, $r_{rm}(39)$

= 0.444, 95% CI = [0.150, 0.666], p = .004 (Figure 4B). These findings indicate more

precise reports of the probed color were associated with larger neural responses related

to attentional enhancement (N2pc) and memory maintenance (CDA).

1   *Figure 4.* Repeated-measures correlations plots. Each colored line is the fit for three data points
2   from each individual participant from the 100%, 75%, and 25% lateral likelihood conditions. A)
3   Correlation between N2pc mean amplitude and standard deviation (SD) of raw response error.
4   Lower SD indicates more precise responding. B) Correlation between CDA mean amplitude and
5   SD of response error.
6
Experiment 3

Experiment 2 provided evidence that attentional prioritization not only affects the

behavioral precision in a delayed-recall task, it is also associated with a proportional

increase in the amplitude of ERP components associated with attentional enhancement

(N2pc) and memory maintenance (CDA). Interestingly, previous studies have found that

the effect of load on behavioral precision is identical to those of prioritization; thus,

splitting resources across two items results in similar memory precision as an item with

50% cue validity[18]. Consequently, to test whether the CDA similarly reflects resource

allocation in the absence of prioritization cues we manipulated how many items were

presented laterally, and how many vertically. There were three conditions: one item

lateral and three vertical (Load 4, 25% lateral), three items lateral and one vertical (Load

4, 75% lateral), and three items lateral and three items vertical (Load 6, 50% lateral).

Thus, these last two conditions had the same lateral memory load and a change in the

proportion of memory resources allocated to those items. Comparing across these three

conditions allowed us to examine how both lateral memory load and the proportion of

lateral memory resources affected the CDA, independent of cueing effects.

CDA.

CDA amplitude was affected by Condition (Figure 5B), $F(2,38) = 7.60$, $p = .002$,

$\eta^2_p = .286$, $BF_{10} = 24.313$, such that the amplitude was more negative when 75% of

memory resources were allocated to three lateral items ($M = -0.775$ µV, $SD = 0.637$ µV)

than when 25% were allocated to one lateral item ($M = -0.252$ µV, $SD = 0.541$ µV), $t(19)$

= 3.401, p_{bonf} = .009, d = 0.760, BF_{10} = 14.168. When 50% of memory resources were

allocated to three lateral items (*M* = -0.565 µV, *SD* = .595 µV), the CDA amplitude was

not different from either of the other two conditions, *t*s < 2.27, *p*s > .105, ds < 0.508,

BFs_{10} < 1.83. Although participants were holding three lateral items in memory in this

condition, the CDA amplitude was not significantly different from when only one lateral

item was in memory (in contrast to when three lateral items were held in memory with

75% of memory resources). Additionally, CDA amplitude was linearly related to the

proportion of lateral resources, adjusted-R^2 = .9067, *RMSE* = .0963, t(19) = 3.4, *p* =

.009, such that amplitude became more negative as the amount of resources increased.

Together, these findings suggest that even in the absence of prioritization cues, the

CDA may reflect a combination of memory load *and* the amount of attention/memory

resources allocated toward these items.

Figure 5. A) Task schematic of Experiment 3. Participants were told to remember the colors of
all of the squares. Each trial began with a jittered ITI consisting of a fixation dot. There were 3
conditions differing in overall memory load (4 or 6) and by how many items were presented on
the lateral (1 or 3). After a delay, participants made a response to the probed shape on the color
wheel with the mouse. B) Grand average difference waveform (N = 20) at the average of 5
posterior channel pairs, time-locked to stimuli onset. Positive is plotted up. Filtered at 30 Hz for
visualization purposes only.
8
CDA amplitude continuously reflects both VWM load and resource allocation

Across three experiments, the manipulation of resource allocation – whether by

spatial cues, feature-based cues, or memory load – affected the amplitude of the CDA.

Although these effects were sometimes small, they are consistent with previous

behavioral findings (also observed here) that the magnitude of the effect on memory

performance depends on the magnitude of the change in resource allocation. However,

although small changes in resource allocation may only produce small effects, these

effects tend to follow a predictable pattern along a continuous power-law in behavioral

studies[18]. Thus, it is possible that the effect of resource allocation on ERP measures of

memory maintenance should similarly follow a continuous pattern, wherein the

amplitude of the CDA changes with the proportion of resources allocated to laterally-

presented items. It is also possible that, although resource allocation is a better

predictor of memory performance than load alone, CDA amplitude may reflect a mixture

of signals that combine effects of load *and* resource allocation. To examine this

prediction, we tested whether the CDA amplitudes observed in Experiments 2 and 3

(which involved the same stimulus displays) were best described by one of three

models: one in which CDA amplitude was predicted by load alone, another with

resource allocation alone, and a model using a scaled combination of memory load and

resource allocation (see Methods).

When CDA amplitudes were compared to memory load alone (Figure 6A), the

model only accounted for 65% of the variance in the data, adjusted-R^2 = 0.653, *RMSE* =

0.255, BIC = -14.44. This was similar when CDA amplitudes were fit with proportion of

memory resources alone (Figure 6B), adjusted-R^2 = 0.647, *RMSE* = 0.257, BIC = -

18.64. However, when fitting CDA amplitude to the weighted sum of both memory load

and proportion memory resources, we observed the best fit (Figure 6C), adjusted-R^2 =

0.737, *RMSE* = 0.222, BIC = -21.28. This demonstrates that the amplitude of the CDA

follows a predictable continuous function that is affected both by the number of lateral

items to be remembered, and by the proportion of total resources allocated to those

items.

● Experiment 2   ● Experiment 3

Figure 6. Power-law models and fits. Dotted lines represent 95% CIs of the model fit. Black dots
represent condition means from Experiment 2 and red dots from Experiment 3. A) Fit between
CDA mean amplitude and lateral memory load. B) Fit between CDA amplitude and proportion
lateral memory resources. C) Fit between CDA amplitude and number of items scaled for both
memory load and memory resources.
17
18   **General Discussion**

In the current study, we sought to examine the effect of attentional prioritization

on the CDA, as well use attention-related ERPs to determine whether prioritization was

driven by selective enhancement or suppression. In Experiment 1, we found that the

CDA amplitude is somewhat reduced when prioritizing one item over others than when

all items are prioritized equally. In Experiment 2, we implemented a stronger

manipulation of resource allocation using a systematic lateralization procedure[26,51],

demonstrating that the CDA tracked overall proportion of memory resources allotted.

Additionally, we found that the N2pc was also reflective of priority, providing evidence

that the allocation of neural resources toward to-be remembered items occurs via

attentional enhancement. Moreover, both N2pc and CDA amplitudes correlated with

individuals' behavioral precision in this task, demonstrating that both components can

be used to predict how well individuals are able to recall a memory item. Finally, in

Experiment 3 we manipulated the proportion of memory resources that should be

allocated to lateral items by controlling the relative proportion of memory array items

presented laterally. Consistent with the first two experiments, we found that CDA

amplitude tracked the proportion of memory resources that should have been allocated

toward the lateral items in the stimulus display.

When comparing across Experiments 2 and 3, we also found that CDA

amplitudes were best predicted by a weighted sum of memory load and resources. This

relationship followed a continuous power law, similar to previous behavioral

findings[7,18,19]. Importantly, these model fits showed that when accounting for both load

and memory resources there was a better fit than when considering only load or

resources in isolation. This novel finding points to the CDA as a proxy of more than

memory load alone, suggesting that this component may also reflect the total amount of

memory resources allocated to each item, and therefore, the fidelity of those

representations.

One potential argument against the resource allocation interpretation is that

instead of flexibly distributing resources across all items in the display, individuals were

selectively encoding items in the display depending on the likelihood that they would

become the target (i.e. preferentially encoding the higher priority items). One argument

against this interpretation comes from the absence of timing differences in the N2pc in

Experiment 2. Previous studies have shown that in visual search tasks, high-probability

targets are selected first, resulting in an earlier N2pc[47,53]. Based on this logic, one would

expect that participants might select the higher-priority items first, resulting in a change

in the onset of the lateral N2pc depending on whether the high-priority items were

presented on the lateral or vertical midline. That is, if participants were encoding more

high-priority items, these items should be selected first (consistent with high-probability

targets in search tasks). In contrast to this hypothesis, there was no difference in the

timing of the N2pc across conditions in Experiment 2, suggesting that all items were

being attended to at the same time, regardless of their priority.

In addition, the findings of Experiment 3 demonstrate that resource allocation

affects the CDA amplitude even in the absence of explicit prioritization cues. That is,

even though all items were equally likely to be probed, the CDA amplitude towards

three lateral items was reduced when resources had to be spread across additional

vertical items. It is possible that participants could decide to encode only a subset of

items on each trial. However, rather than being a confound specific to a resource

allocation interpretation, fluctuations in CDA amplitude across trials is likely a feature of

all CDA measurements[42], as changes in the number of items and amount of information

encoded may occur due to spontaneous fluctuations in attention[5,54,55], or top-down

strategies[56,57]. In other words, although the experiments presented here may include

some measure of strategic differences in resource allocation across trials, *spontaneous*

changes in resource allocation across trials, as opposed to the systematic changes

across conditions demonstrated here, may be a feature of past CDA studies that has

been previously unexplored.

There are several implications that arise from these findings. First, the CDA has

frequently been used to estimate the number of items stored in memory, such that it has

been used as a proxy for filtering efficiency[16,58]. However, we show that the CDA at

least in part reflects flexible prioritization and allocation of memory resources towards

to-be remembered items. Therefore, it is possible that studies that have used the CDA

as an all-or-none marker of WM filtering may be over- or under-estimating the number

of items that individuals have stored in memory, without accounting for resource

allocation.

The results also speak to the role of attentional enhancement in prioritization. In

Experiment 2 we found that the N2pc, but not the P_D, tracked the priority of the

lateralized stimuli, while also predicting the behavioural precision of memory report. This

suggests that when using feature-based cues, participants relied on up-weighting

relevant information depending on their respective priorities, in comparison to down-

weighting irrelevant information using active suppression. This is consistent with

previous findings which found that when given a pre-cue that indicated to participants to

up or down-regulate memory encoding processes, it was only possible to up-regulate

processing to benefit performance[3]. Additionally, it has been found that when using

reward to prioritize items, only target selection was impacted and not distractor

suppression[59].

Our finding is also consistent with a recent study that suggests the N2pc reflects

enhancement of items at the spatial focus of attention, instead of an overall attentional

shift toward the lateral[60]. Interestingly, we did not find attention-related components in

Experiments 1 and 3, pointing to the importance of having a pre-cue to be able to

allocate attention accordingly, suggesting perhaps that resource allocation may occur

later in the presence of simultaneous spatial cues (Experiment 1) or no cues

(Experiment 3). Future studies should further examine the N2pc as a potential marker of

the flexible allocation of neural resources for attentional enhancement according to item

priority.

Our findings also stress the importance of flexible attentional control in

prioritization, which may be a limiting factor in overall VWM capacity and performance.

Namely, previous work has focused on the link between unnecessary memory storage

of distractors and VWM capacity[61,62]. However, a reanalysis of these data found that

attentional control processes involved in filtering distractors better predicted memory

capacity than unnecessary storage itself[20]. These attentional control processes are

thought to arise from the bilateral prefrontal cortex and left basal ganglia[61,62]. Thus,

while future studies should investigate the role of frontal-related ERP components to

VWM resource allocation, our findings that the N2pc amplitude changes as a function of

priority and predicts behavioural precision provide further evidence that attentional

enhancement driven by top-down attentional control may be critical to determining VWM

performance.

Although previous studies have established a clear link between filtering ability

and VWM performance, our findings suggest that the role of attention in VWM

performance goes beyond filtering distractors. Consequently, one limitation of the

filtering account is that the effect can only be observed when there are distractors

present in the display. It is known, however, that memory performance differs amongst

individuals even when the display consists only of targets (i.e. capacity effects).

Therefore, a full account of working memory performance should require a mechanism

wherein resources are allocated amongst items when they are all relevant to the task[11].

The results of Experiment 3 speak to the existence of such a mechanism, as even in the

absence of prioritization (or filtering) cues, the CDA still best reflected the overall

proportion of resources allocated toward the lateral items. This was of course also

influenced by how many items were being held in memory, as demonstrated by the

model fit of CDA amplitude with resources and load together. However, a full account of

VWM performance will need to understand the control mechanisms that select and

prioritize targets, in addition to (or irrespective of) the requirement to filter distractors.

Finally, the current results provide with some information about the neural origins

of the CDA. The finding that the CDA follows a power-law when fit with both resources

and memory load is consistent with the saturation model of delay period activity

proposed by Bays[17]. In this model, as input increases, neuronal activity also increases.

However, as the input becomes large, it produces a smaller increment in neuronal

activity[17]. This results in activity saturating at some maximum level. Although the power-

law examined here tests a similar pattern, the current experiments did not test a large

enough range of set sizes to delineate between capacity-limited models and limitless

models. Moreover, it could be that prioritization is only possible within a limited range of

stored items. Regardless, the results of the experiments presented here indicate the

need to consider resource allocation in addition to overall load in neural and behavioral

models of VWM.

References

1. Chun, M. M. & Turk-Browne, N. B. Interactions between attention and memory. *Current Opinion in Neurobiology* **17**, 177–184 (2007).

2. deBettencourt, M. T., Norman, K. A. & Turk-Browne, N. B. Forgetting from lapses of sustained attention. *Psychon Bull Rev* **25**, 605–611 (2017).

3. Sundby, C. S., Woodman, G. F. & Fukuda, K. Electrophysiological and behavioral evidence for attentional up-regulation, but not down-regulation, when encoding pictures into long-term memory. *Mem Cogn* (2018). doi:10.3758/s13421-018-0871-z

4. Turk-Browne, N. B., Golomb, J. D. & Chun, M. M. Complementary attentional components of successful memory encoding. *NeuroImage* **66**, 553–562 (2013).

5. Adam, K. C. S., Mance, I., Fukuda, K. & Vogel, E. K. The contribution of attentional lapses to individual differences in visual working memory capacity. *Journal of Cognitive Neuroscience* **27**, 1601–1616 (2015).

6. Fukuda, K. & Vogel, E. K. Individual differences in recovery time from attentional capture. *Psychological Science* **22**, 361–368 (2011).

7. Klyszejko, Z., Rahmati, M. & Curtis, C. E. Attentional priority determines working memory precision. *Vision Research* **105**, 70–76 (2014).

8. Awh, Vogel, E. K. & Oh, S.-H. Interactions between attention and working memory. *Neuroscience* **139**, 201–208 (2006).

9. Cowan, N. *et al.* On the capacity of attention: Its estimation and its role in working memory and cognitive aptitudes. *Cogn Psychol* **51**, 42–100 (2005).

10. Engle, R. W. Working memory capacity as executive attention. *Curr Dir Psychol Sci* **11**, 19–23 (2002).

11. Fukuda, K., Woodman, G. F. & Vogel, E. K. Individual differences in visual working memory capacity: Contributions of attentional control to storage. *Mechanisms of Sensory Working Memory: Attention and Perfomance XXV* 105 (2015).

12. Cowan, N. & Morey, C. C. Visual working memory depends on attentional filtering. *Trends in Cognitive Sciences* **10**, 139–141 (2006).

13. Luck, S. J. & Vogel, E. K. Visual working memory capacity: From psychophysics and neurobiology to individual differences. *Trends in Cognitive Sciences* 391 (2013). doi:10.1016/j.tics.2013.06.006

14. McCollough, A. W., Machizawa, M. G. & Vogel, E. K. Electrophysiological measures of maintaining representations in visual working memory. *Cortex* **43**, 77–94 (2007).

15. Vogel, E. K. & Machizawa, M. G. Neural activity predicts individual differences in visual working memory capacity. *Nature* **428**, 748–751 (2004).

16. Vogel, E. K., McCollough, A. W. & Machizawa, M. G. Neural measures reveal individual differences in controlling access to working memory. *Nature* **438**, 500–503 (2005).

17. Bays, P. M. Reassessing the evidence for capacity limits in neural signals related to working memory. *Cereb Cortex* **28**, 1432–1438 (2018).

18. Emrich, S. M., Lockhart, H. A. & Al-Aidroos, N. Attention mediates the flexible allocation of visual working memory resources. *J Exp Psychol Hum Percept Perform* **43**, 1454–1465 (2017).

19. Dube, B., Emrich, S. M. & Al-Aidroos, N. More than a filter: Feature-based attention regulates the distribution of visual working memory resources. *J Exp Psychol Hum Percept Perform* **43**, 1843–1854 (2017).

20. Emrich, S. M. & Busseri, M. A. Re-evaluating the relationships among filtering activity, unnecessary storage, and visual working memory capacity. *Cogn Affect Behav Neurosci* **15**, 589–597 (2015).

21. Eimer. The N2pc component as an indicator of attentional selectivity. *ELECTROENCEPHALOGRAPHY AND CLINICAL NEUROPHYSIOLOGY* **99**, 225–234 (1996).

22. Hickey, C., McDonald, J. J. & Theeuwes, J. Electrophysiological evidence of the capture of visual attention. *Journal of Cognitive Neuroscience* **18**, 604–613 (2006).

23. Hickey, C., Zoest, W. van & Theeuwes, J. The time course of exogenous and endogenous control of covert attention. *Exp Brain Res* **201**, 789–796 (2010).

24. Burra, N. & Kerzel, D. The distractor positivity (Pd) signals lowering of attentional priority: Evidence from event-related potentials and individual differences. *Psychophysiol* **51**, 685–696 (2014).

25. Gaspar, J. M. & McDonald, J. J. Suppression of salient objects prevents distraction in visual search. *J. Neurosci.* **34**, 5658–5666 (2014).

26. Hickey, C., Di Lollo, V. & McDonald, J. J. Electrophysiological indices of target and distractor processing in visual search. *Journal of Cognitive Neuroscience* **21**, 760–775 (2008).

27. Sawaki, R. & Luck, S. J. Active suppression after involuntary capture of attention. *Psychon Bull Rev* **20**, 296–301 (2013).

28. Fukuda, K., Kang, M.-S. & Woodman, G. F. Distinct neural mechanisms for spatially lateralized and spatially global visual working memory representations. *Journal of Neurophysiology* **116**, 1715–1727 (2016).

29. Luck, S. J. & Vogel, E. K. The capacity of visual working memory for features and conjunctions. *Nature* **390**, 279–281 (1997).

30. Delorme, A. & Makeig, S. EEGLAB: An open source toolbox for analysis of single-trial EEG dynamics including independent component analysis. *J. Neurosci. Methods* **134**, 9–21 (2004).

31. Lopez-Calderon, J. & Luck, S. J. ERPLAB: An open-source toolbox for the analysis of event-related potentials. *Front Hum Neurosci* **8**, (2014).

32. *BioSemi ActiveTwo System Amsterdam, The Netherlands*.

33. Gaspelin, N. & Luck, S. J. Combined electrophysiological and behavioral evidence for the suppression of salient distractors. *Journal of Cognitive Neuroscience* **30**, 1265–1280 (2018).

34. Lins, O. G., Picton, T. W., Berg, P. & Scherg, M. Ocular artifacts in EEG and event-related potentials I: Scalp topography. *Brain Topogr* **6**, 51–63 (1993).

35. McDonald, J. J. & Ward, L. M. Spatial relevance determines facilitatory and inhibitory effects of auditory covert spatial orienting. *Journal of Experimental Psychology: Human Perception and Performance* **25**, 1234 (1999).

36. Bays, P. M. & Husain, M. Dynamic shifts of limited working memory resources in human vision. *Science* **321**, 851–854 (2008).

37. Hakim, N., Adam, K. C. S., Gunseli, E., Awh, E. & Vogel, E. K. Dissecting the neural focus of attention reveals distinct processes for spatial attention and object-based storage in visual working memory. *Psychol Sci* **30**, 526–540 (2019).

38. van Doorn, J. *et al.* The JASP guidelines for conducting and reporting a bayesian analysis. *PsyArXiv* (2019). doi:10.31234/osf.io/yqxfr

39. JASP Team. *JASP*. (2018).

40. R Core Team. *R: A language and environment for statistical computing.* (2017).

41. RStudio Team. *RStudio: Integrated Development for R*. (2015).

42. Adam, K. C. S., Robison, M. K. & Vogel, E. K. Contralateral delay activity tracks fluctuations in working memory performance. *Journal of Cognitive Neuroscience* **30**, 1229–1240 (2018).

43. Ikkai, A., McCollough, A. & Vogel, E. Contralateral delay activity provides a neural measure of the number of representations in visual working memory. *JOURNAL OF NEUROPHYSIOLOGY* **103**, 1963–1968 (2010).

44. Kiss, M., Velzen, J. V. & Eimer, M. The N2pc component and its links to attention shifts and spatially selective visual processing. *Psychophysiology* **45**, 240–249 (2008).

45. Luck, S. J. & Hillyard, S. A. Spatial filtering during visual search: Evidence from human electrophysiology. *Journal of Experimental Psychology: Human Perception and Performance* **20**, 1000–1014 (1994).

46. Mazza, V., Turatto, M. & Caramazza, A. Attention selection, distractor suppression and N2pc. *Cortex* **45**, 879–890 (2009).

47. Woodman, G. F. & Luck, S. J. Electrophysiological measurement of rapid shifts of attention during visual search. *Nature* **400**, 867 (1999).

48. Luck, S. J. *An introduction to the event-related potential technique*. (MIT press, 2014).

49. Feldmann-Wüstefeld, T. & Vogel, E. K. Neural evidence for the contribution of active suppression during working memory filtering. *Cereb Cortex* (2018). doi:10.1093/cercor/bhx336

50. Gaspar, J. M., Christie, G. J., Prime, D. J., Jolicœur, P. & McDonald, J. J. Inability to suppress salient distractors predicts low visual working memory capacity. *Proceedings of the National Academy of Sciences* **113**, 3693–3698 (2016).

51. Sawaki, R., Geng, J. J. & Luck, S. J. A common neural mechanism for preventing and terminating the allocation of attention. *J. Neurosci.* **32**, 10725–10736 (2012).

52. Bakdash, J. Z. & Marusich, L. R. Repeated measures correlation. *Front Psychol* **8**, (2017).

53. Woodman, G. F. & Luck, S. J. Serial deployment of attention during visual search. *Journal of Experimental Psychology: Human Perception and Performance* **29**, 121–138 (2003).

54. deBettencourt, M. T., Keene, P. A., Awh, E. & Vogel, E. K. Real-time triggering reveals concurrent lapses of attention and working memory. *Nature Human Behaviour* 1 (2019). doi:10.1038/s41562-019-0606-6

55. van den Berg, R., Shin, H., Chou, W.-C., George, R. & Ma, W. J. Variability in encoding precision accounts for visual short-term memory limitations. *Proc. Natl. Acad. Sci. U.S.A.* **109**, 8780–8785 (2012).

56. Cusack, R., Lehmann, M., Veldsman, M. & Mitchell, D. J. Encoding strategy and not visual working memory capacity correlates with intelligence. *Psychonomic Bulletin & Review* **16**, 641–647 (2009).

57. Linke, A. c., Vicente-Grabovetsky, A., Mitchell, D. j. & Cusack, R. Encoding strategy accounts for individual differences in change detection measures of VSTM. *Neuropsychologia* **49**, 1476–1486 (2011).

58. Awh, E. & Vogel, E. K. The bouncer in the brain. *Nature neuroscience* **11**, 5–6 (2008).

59. Hickey, C., Chelazzi, L. & Theeuwes, J. Reward has a residual impact on target selection

in visual search, but not on the suppression of distractors. *Visual Cognition* **19**, 117–128

(2011).

60. Zivony, A., Allon, A. S., Luria, R. & Lamy, D. Dissociating between the N2pc and

attentional shifting: An attentional blink study. *Neuropsychologia* **121**, 153–163 (2018).

61. Liesefeld, A. M., Liesefeld, H. R. & Zimmer, H. D. Intercommunication between prefrontal

and posterior brain regions for protecting visual working memory from distractor

interference. *Psychol Sci* **25**, 325–333 (2014).

62. McNab, F. & Klingberg, T. Prefrontal cortex and basal ganglia control access to working

memory. *Nat Neurosci* **11**, 103–107 (2008).