Spatial Patterns for Discriminative Estimation (SP♠DE)

A. Llera[1,2,5], R. Chauvin[1,2], P. Mulders[1,2,3], J. Naaijen[,1,2], M. Mennes[1,2], C. F. Beckmann[1,2,4]

1- Donders Institute for Brain, Cognition and Behavior, Centre for Cognitive Neuroimaging, 6500 GL, Nijmegen, The Netherlands.

2- Department of Cognitive Neuroscience, Radboud University Medical Centre, 6525 EN, Nijmegen, The Netherlands.

3- Department of Psychiatry, Radboud University Medical Centre, 6500 HB, Nijmegen, The Netherlands.

4- Oxford Centre for Functional Magnetic Resonance Imaging of the Brain (FMRIB), University of Oxford, Oxford, OX3 9DU, U.K.

5- Karakter, Child and Adolescent Psychiatry, University Center, 6525 GC Nijmegen, The Netherlands.

Abstract

Functional connectivity between brain regions is modulated by cognitive states or experimental conditions.
Such connectivity variations can be appreciated in covariance or correlation matrices obtained from fMRI data.
A multivariate methodology that can capture fMRI connectivity maps in light of different experimental
conditions would be of primary importance to learn about the specific roles of the different brain areas
involved in the observed connectivity variations. Here we adapt, extend, and evaluate a supervised
dimensionality reduction model to fMRI data that provides a full multivariate characterization by achieving
optimal discriminative linear spatial filters in terms of variance and provides interpretable spatial maps directly
reflecting the brain areas involved in the accounted connectivity changes[1,2]. We demonstrate the strength of
such approach for fMRI data by using data from the Human connectome project to show that the model
provides close to perfect discrimination between different fMRI tasks at low dimensionality. Additionally, the
straightforward interpretability of the model is demonstrated by the obtained linear filters relating to
anatomical areas well known to be involved on each considered fMRI task, and by testing the robustness of
both, discriminatory and spatial reproducibility, with respect to the number of subjects and of the fMRI time-
points considered. We additionally show that such an approach can provide a complementary/alternative view
to traditional task fMRI analyses by looking at changes in the covariance structure as a substitute to changes in
the mean signal as the general linear model (GLM) analyses. We use 2-back and 0-back working memory task
fMRI data from the Human connectome project to show that, at the group level, SPADE discovers connectivity
changes in memory related areas during the 2-back periods, while attention network areas are involved during
the 0-back task periods. We conclude that SPADE is a robust tool to investigate brain connectivity alterations
across induced cognitive changes and has the potential to be used in pathological or pharmacological cohort
studies. A publicly available toolbox is provided to facilitate the end use and further development of this
methodology able to extract Spatial Patterns for Discriminative Estimation (SP♠DE).

Introduction

Functional magnetic resonance imaging (fMRI) is the primary tool used to investigate how the brain (re)acts
under different mental states and the biological underpinnings of brain disorders. Most commonly, these state
or group-differences are investigated using generalized linear models (GLM) [3] to detect brain regions that
differentiate between experimental conditions. The GLM is for example the standard tool used to analyze task
fMRI data incorporating a temporal model for the induced brain activity [4] that allows obtaining a supervised
voxel-wise characterization of changes in the blood-oxygen-level dependent (BOLD) response [3]. Yet, while
powerful and straightforward to interpret, the GLM has two crucial disadvantages. Foremost, while fMRI data
is multivariate in nature, the GLM is applied as a mass univariate approach (i.e., independently to each voxel in
the brain) and does not take into account interactions between different regional effects. Second, it ignores the
variance in the data by looking at single mean BOLD changes across conditions. To overcome these issues, one
can use multivariate models that allow studying the second order interactions between different brain areas [5,6].
Although these models overcome some of the issues with univariate modelling, they are not specifically
tailored for state/group characterization. Further inclusion into models for state/group identification, i.e.

regression or classification, can provide strong discrimination but complicates the interpretation of the results.
Consequently, to improve interpretability of results obtained from analyzing multivariate fMRI data while
optimizing discrimination between two conditions or groups of fMRI time-series, it would be beneficial to use a
multivariate approach to extract brain patterns that maximize discriminative properties. To that end we
consider a model to extract Spatial Patterns for Discriminative Estimation (SP♠DE). SPADE is a covariance
based discriminative approach that provides optimal linear discriminative filters in terms of variance[1]. Although
the basics of the approach are commonly used in EEG-based brain-computer interfaces [2,7], its application for
fMRI data is challenging since it requires a large number of observations to compute well-posed covariance
matrices. Nevertheless, we introduced preliminary results in [8] and further work has been done since then by
applying it to cohorts of neurodevelopmental disorders [9–12]. Recently we have also considered it to study the
effect of stress induction [13]. Although recent advances in data acquisition and large-scale data collection allow
collecting a large number of observations in relatively short time periods, this is not yet the standard, especially
in clinical acquisitions. To partially overcome this issue we expand the original methodology formulation [1] by
using a regularized version of the covariance matrices[14] and by embedding the process into a novel
permutation testing statistical approach for model order selection; note here that, according to [15], the model
order selection step is of primary importance for the proper interpretation of the spatial maps associated with
the learned spatial filters.

Here, we make use of high-quality fMRI data from the Human Connectome Project (HCP) [16,17] to uncover and
evaluate the potential power of the method for discriminative estimation on fMRI data. We consider resting
state, motor, and working memory task fMRI data from 1063 subjects and demonstrate that we are able to
learn low-dimensional representations of the data that provide close to perfect discrimination between the
different mental states. The availability of these simple and well-known tasks allows to validate that the
learned filters are robust and specific to brain areas well-known to be involved during their respective
paradigms [15,18], validating the spatial interpretation of the obtained results on fMRI data. Further, the highly
temporally sampled fMRI data of the HCP allows also considering the classification and spatial associations'
robustness as a function of the number of subjects and time points included. Herewith, we can identify the
scenarios in which the current approach is useful to address general questions using fMRI.
74

Methods

Dataset & preprocessing

In this work we use resting state and task fMRI data from the Human Connectome Project (HCP) [16,17]. For each
subject, we consider the motor task (MT), the working memory task (WM), and the first of the two available
resting state sessions (RS). We use the HCP1200 release which includes data from 1200 subjects and only
consider data from subjects for whom all three data modalities (RS, MT and WM) were available resulting in a
total of 1063 subjects. In all cases we used the fully preprocessed data in MNI152 space as delivered in the
HCP1200 release. For the full preprocessing details we refer the reader to [19].

Spatial Patterns for Discriminative Estimation (SP♠DE)

SPADE indexes connectivity changes from two sets of fMRI data using the simultaneous diagonalization of two
covariance matrices (Fukunaga, 1990); full analytical details are provided in the supplementary material.
Although ideally one would like to compute full brain spatial covariance matrices, this is not computationally
achievable yet due to memory constraints, and a spatial dimensionality reduction must be performed in order
to apply the algorithm to fMRI data. For each subject and for each of the three considered fMRI data modalities
we performed a spatial dimensionality reduction into 165 regions of interest (ROI) from a functional
parcellation [20] by extracting the mean time-series across the voxels in each ROI. Each ROI time-series was then
independently demeaned and divided by its standard deviation before further processing.

Then, considering such ROI time-series gathered under two different fMRI modalities (e.g., resting state versus
working memory task fMRI), we compute a regularized covariance matrix[14] per subject and condition and
average then across subjects to obtain a unique covariance matrix per modality; these two average covariance
matrices are then used to estimate their simultaneous diagonalization[1]. This results in a set of discriminative

linear spatial filters that optimally separate the two initial modalities in terms of variance. We address the
model order selection, i.e. the number of spatial filters selected to optimize discrimination, using permutation
testing. Briefly, we select the filters that explain significantly more variance for a given condition than the
variance obtained when randomizing the data across conditions. Full details are provided in the supplementary
material. An important feature of the SPADE model is that connectivity changes can be summarized for each
basis vector as a unique spatial map that provides a spatial weight for each ROI. This results in a
straightforward interpretation of the relevant changes in connectivity. Since the simultaneous diagonalization
assumes no implicit noise model, the estimated basis vectors cannot be directly interpreted back to the brain,
and the interpretable associated spatial maps are obtained using structural coefficients [15,18]. Brief details are
provided in the supplementary material and for a more extensive explanation we refer the reader to [15]. Note
that since for a proper spatial interpretation the noise model is estimated from the selected relevant filters[15],
the model order selection we introduce here is of most importance to obtain a proper interpretation of the
resulting spatial filters.

For the remainder of the paper we will denote the full process involving spatial dimensionality reduction of two
fMRI data modalities, spatial covariance regularization, simultaneous diagonalization, model order estimation
by permutation testing, and estimation of the associated interpretable spatial maps [15] as SPADE. To facilitate
the end use application of these tools to the community, a toolbox providing full automatized estimation will
be made publicly available through Git-Hub upon publication.

SPADE evaluations

We use the resting state (RS), motor task (MT) and working memory task (WM) fMRI data from the HCP sample
and apply the introduced SPADE methodology to find brain connectivity differences between each pair of fMRI
modalities independently: RS vs MT, RS vs WM and MT vs WM. To quantify the quality of the learned filters we
perform a discriminative analysis to distinguish between fMRI modalities using a ten-fold cross validation
approach for each of the three scenarios (RS vs MT, RS vs WM and MT vs WM) independently. At each fold,
SPADE discriminative filters are learned from the covariance matrices of the two selected modalities using data
from 90% of the subjects and the number of filters is selected using permutation testing. Then we compute the
projection of these subjects' data into the newly learned basis, compute the logarithmic variance of the
resulting time-series as features, and use them to train a Linear Discriminant Analysis (LDA) classifier [21] to
distinguish between the two included modalities (e.g. RS vs MT). The filters are then used to project the
remaining unseen data (~10% subjects) and extract the log-variance of these projections as features to test the
classifier quality. Each classifier is evaluated using the accuracy which we define as the percentage of correctly
classified samples. For comparison we also evaluate the results obtained using a linear support vector machine
(SVM) classifier in the full covariance space, i.e. feature space of dimension (165*166)/2= 13695. We visually
evaluate the spatial extent of the SPADE linear filters using structural coefficients for visualization of the
associated spatial maps [15,18]. Finally, we consider the effect of a reduced number of subjects and temporal
observations in the performance of the model. For each considered number of subjects (N) and time-points (T),
we performed 100 different realizations of the SPADE analyses, where at each realization a subset of N subjects
was selected randomly and the temporal down-sampling was performed by selecting T equally temporally
spaced samples from the full original fMRI time-series i.e. simulating higher TR acquisitions.

In addition, we perform a secondary evaluation where we apply the SPADE model to a scenario previously
studied using a GLM analysis. Using the WM task data from the HCP sample, we compared the 0-back memory
task periods to the 2-back memory task periods at the group level using the SPADE approach. As with the
previous evaluations, in this case we also test the discrimination power using 10-fold cross-validation and
report the spatial maps associated to the top four spatial maps for comparison to the results presented in [22].

Results

To illustrate the discriminative performance of the SPADE methodology, Figure 1 presents two-dimensional
representations of fMRI data obtained using the SPADE model. For each comparison between two fMRI
modalities, we plotted one random fold from the ten-fold-cross-validation used to evaluate discrimination and
divide the data into training and testing datasets. Note that by construction, the first and the last SPADE filters

maximize variance for one class while minimizing it for the other one. Consequently, the discriminative power
of the algorithm usually comes from the combination of pairs of filters at both extremes of the eigen-spectrum.
In the first row we can appreciate, for each of the three comparisons, a very clear two-dimensional separation
between the training features obtained by combining the two extreme SPADE filters. The second row clearly
shows the generalization ability of the SPADE model on the test-set data. We observed that in all cases the
classification using uniquely one pair of filters (two-dimensional feature space) is very high, between 98.6% and
99.76% respectively; exact statistics are provided in the second column of Table 1.
152

153
Figure 1: Two-dimensional fMRI data representations obtained using SPADE. The columns represent three different comparisons, MT vs RS,
WM vs RS and WM vs MT task fMRI respectively. In the first row we present the logarithmic variance of the training fMRI data projected
onto the first and last SPADE filters learned to discriminate each pair of fMRI modalities as indicated in the figure legends. Dots represent
subjects and blue and black color encode the two different fMRI tasks considered on each scenario. In all three cases we can see that the
training set is correctly separated in two visually distinguishable sets. In the second row we represent the learned two-dimensional training
feature distributions presented in the first row as two Gaussian densities, and visualize the logarithmic variance of the testing fMRI data
projections into the new basis as color coded diamonds. Appreciate the generalization ability of the SPADE model that provides an optimal
two-dimensional classification space.

However, to fully evaluate the discriminative performance of the SPADE model we applied model order
selection via permutation testing and selected filters at significance Bonferroni corrected level p<0.05/165 =
3.3x10^-4 (see previous section and supplementary material for complete details). Although in practice the
dimensionality was computed on each fold independently, for illustration we provide the exact set of filters
selected when using the full sample at each comparison in Table 1 column 'SPADE selected filters'. On each of
the three comparisons the classification performance obtained using SPADE at the dimensionality selected
using the permutation testing strategy is presented in Table 1 column 'SPADE accuracy'. For comparison we
also provide the classification results obtained using a SVM in the full covariance space in the last column of
Table 1. Although the mean improvement with respect to the two-dimensional scenario or the SVM is relatively
small, the improvement it is clearly notable in the reduced standard deviation of the results across folds. These
results highlight that the top filters are the most relevant for discrimination but using the model order selection
generalizes better across folds. Further, the comparison with the SVM provides remarkable results, especially in
light of the reduced dimension in which SPADE classification is performed and the linear nature of the SPADE
filters that allow for a straightforward spatial interpretation.
176
177

Comparison	SPADE-2D accuracy	SPADE Selected filters	SPADE accuracy	SVM accuracy
RT vs MT	98.64 (0.95) %	1-6 and 155-165	99.3 (2*10^-3) %	98.9 (0.37) %
RT vs WM	99.34 (0.33) %	1-2 and 152-165	99.77 (6*10^-5) %	99.8 (0.40) %
WM vs MT	99.76 (0.46) %	1-4 and 153-165	99.63 (2*10^-4) %	99.58 (0.35) %
mean	99.24 (0.58) %		99.56 (1.3*10^-3) %	99.42 (0.37) %

Table 1: Summary results of the SPADE analyses. The second row presents results when comparing resting state (RT) with motor task (MT)
fMRI, the third row shows RT with working memory (WM) task fMRI, and the forth row compares WM and MT fMRI. The fifth row shows
the mean results across the three comparisons. The second column (SPADE 2-D) presents the classification results when discriminating
each pair of fMRI modalities using a SPADE two-dimensional projection of the data. The column 'SPADE selected filters' shows the eigen-
spectrum location of the filters selected by the model order selection. The column 'SPADE accuracy' shows the classification results
obtained using the model order selection and the column 'SVM accuracy' shows the results obtained using a SVM in full covariance space
(i.e. feature space of dimension (165*166)/2= 13695).

To evaluate the spatial distributions of the filters associated to the discriminative results reported, Figure 2
summarizes the spatial maps obtained in all three comparisons; the full set of maps will be uploaded as
supplementary material. Since each fold provides slightly different discriminative filters, for visual validation we
performed SPADE analyses including all subjects in the learning phase. The obtained spatial filters were then
transformed into interpretable spatial maps [15,18].

When looking at differences between resting state and motor task [23], in Figure 2 A) we observe that areas
synchronizing to maximize variance for the motor task (left side, filters 1 and 2) involve bilateral supplementary
motor cortex, caudate and operculum in the first filter, while primary motor cortex and contralateral cerebellar
cortex involvement is present in the second filter. Areas identified by these filters are well known to be related
to motor preparation, execution and control [24,25]. On the other side of the spectrum (right side, filters 164 and
165) we find the filters maximizing variance for resting state data while minimizing it for motor task data. The
last filter (#165) involves sensory motor cortex, bilateral dorso-lateral PFC (attention network), cerebellum and
several temporal areas including the temporal gyrus and temporal pole. On the other side, the penultimate
filter (#164) resembles the default mode network (DMN), anterior cingulate cortex and thalamus.

When looking at the differences between resting state and working memory task, in Figure 2 B) we observe
that the areas synchronizing to maximize variance for the working memory task in the first filter involve areas
well known to working memory performance [26,27] as visual and precuneus area, similar to the dorsal pathway,
and temporal-occipital areas, as present in the ventral pathway [28,29]. Filter number two involves areas similar to
number one but includes bilateral hippocampus and thalamus and more temporal areas. On the other side of
the eigen-spectrum, we find that the last filter (#165) involves the anterior cingulate cortex, cerebellum, frontal
pole, thalamus, middle temporal gyrus and temporal pole, frontal opercula. Further, the penultimate filter
(#164) involves again the DMN and the thalamus. We observe that the filters relating to increased variance
during rest (Figure 2A and 2B) are in both cases informing about a stronger involvement of default mode
network (DMN) related areas during the resting state and are extremely similar in both independent analyses
(Figure 2 A and B right sides), showing the consistency of the SPADE algorithm.

Figure 2: A) Resting state vs. motor task. B) Resting state vs. working memory task. C) Working memory vs. motor task fMRI. For each of the three scenarios we present a summary of the spatial maps associated with the discriminative spatial filters. On the left side we present filters 1 and 2, which maximize variance for A) motor, B) memory and C) memory. On the right side we present filters 165 and 164, which maximize variance for A) resting state, B) resting state and C) motor task. For visualization the value of the maps is converted to pseudo-z-statistics and thresholded at Z=1.6.

When looking at the differences between working memory and motor task (Figure 2 C), we observe that the spatial maps obtained are also very closely related to the ones that differentiated the tasks from the resting state; in particular, filters maximizing for WM (Figure 2 C, filters 1 and 2) resemble the ones maximizing variance for WM with respect to resting state (Figure 2 B filters 1 and 2); and filters maximizing variance for MT (Figure 2 C, filters 164 and 165) exhibit a similar spatial distribution to the ones maximizing variance for MT with respect to resting state (Figure 2 A filters 1 and 2). These results show that the filters extracted for each

modality involve areas well known to be required for the particular task performed and are highly specific since
they can be obtained independently of the other covariance structure considered.

For the three considered comparisons, Figure 3 presents the mean and standard deviation of the classification
performance results (top and bottom rows respectively) obtained over 100 random subjects subsets selections
as a function of the number of subjects and of fMRI time points included (see section Methods for details).
Clearly more subjects and longer scanning sessions provide stronger discriminability as shown by a higher
accuracy and a lower standard deviation in these numerical experiments. However, we appreciate that in all
cases above 100 subjects and a reasonable amount of time points (200 as a reference) are enough to reach
high accuracy and a low standard deviation. Using 50 subjects still provides high accuracy in most cases but at a
higher standard deviation cost. Dropping the number of subjects to 20 clearly decreases the model
performance even when considering a high temporal sampling.

Figure 3: Top row presents the mean classification performance for the three comparisons indicated on each figure title, each as a function
of the number of fMRI time samples (y-axis) and the number of subjects (x-axis). The bottom row shows the standard deviation around the
classification accuracy presented in the top row.

The numerical results presented in figure 3 are interesting when the goal of a study is to discriminate between
two groups. However, our main aim is to motivate SPADE as a tool that allows learning about the hidden brain
processes that drive changes on brain functional connectivity as a function of cognitive changes. In figure 4 we
consider the reproducibility of the spatial maps obtained through SPADE as a function of time points and
number of subjects, for the MT vs WM case. The results for the other two scenarios, RT vs Wm and MT vs WM,
are provided as supplementary material, subsection 'spatial reproducibility'. Each subfigure shows the mean
correlation matrix between the significant spatial maps obtained from SPADE in the full sample (N=1063) and
the spatial maps obtained at each of the 100 SPADE analyses on each subset of subjects, for the number of
subjects indicated on each subfigure title (N) and the number of time-points indicated in the y-axis (T). The
standard deviation across each entry of these matrices is shown in figure 5. The size of these matrices equals
the number of significant selected filters indicated in Table 1. At the sub-sampled realizations, the analyses
were performed at the same dimensionality than the full analyses, and the filters are not reordered to match
the original order, showing the robustness in the order of their recovery at all the sub-samples. Consequently,
the top left corner and bottom right corner of each subfigure relates to the spatial reproducibility of the two
most discriminative filters, the associated to the first and the last filters learned through SPADE. Although these
two filters can be expected to be reproduced considering just 50 subjects, figure 4 shows that increasing the
number of subjects really boosts spatial reproducibility. Note for example that considering N=50 and T=240 we
are able to recover the last filter and several top filters, and when considering approximately double number of
time-points, N=460, or even more, N=568, we can slightly increase reproducibility; such reproducibility
improvement is less than the obtained by doubling the number of subjects, i.e. N=100, T=240. A similar effect

can be found globally and it becomes clearer when considering the standard deviation around these results as
presented in Figure 5. Increasing number of subjects provides stronger signal to noise ratio than increasing
number of time-points. This simply means that the group effect will be easier found with more subjects,
independently of the better single subject connectivity estimation through more fMRI samples. Although such
results might seem a truism, it is a desirable characteristic of any robust method. Further, figures 4 and 5 show
that although the mean spatial reproducibility for the top and bottom filters is very high when considering 100
subjects, we need to get to 200 subjects to strongly reduce the standard deviation. They also suggest that
increasing the number of time-points above 350 does not provide clearly improved mean correlation
reproducibility. Although the standard deviation around these mean values also decreases with higher T, such
a decrease in standard deviation is negligible for the top and bottom filters.

272
273 Figure 4: SPADE spatial maps reproducibility for RT vs MT. Each subfigure shows the mean correlation matrix between the significant
274 spatial maps using the full sample (N=1063) and the ones obtained for N and T as indicated on each row and column. The mean is
275 computed over 100 random selections of subjects (see Methods section for details). The size of each correlation matrix equals the number
276 of significant selected filters as indicated in Table 1 and are accordingly ordered, with the top left corner and bottom right corner relating
277 to the spatial reproducibility of the most important filters, the first (#1) and the last (#165) ones.

280
Figure 5: Standard deviation of SPADE spatial maps reproducibility for RT vs MT. Each subfigure shows the element wise standard deviation
around the correspondent mean correlation value from the matrices shown in figure 4. The standard deviation is computed over 100
random selections of subjects (see Methods section for details).

In addition to the previously described comparisons, we performed another validation of the model by
considering an analysis where we use the WM task fMRI data and compare the 2-back working memory task to
the 0-back working memory task. A common approach to this type of data is a traditional example of task fMRI
data analysis where conditions are compared by means of a GLM analysis, and the results of such analyses in
this same dataset have been previously reported in [22]. In this study, increased activation in the lateral-
prefrontal and dorsal parietal cortex was associated with 2-back vs. 0-back working memory task differences.
Table 2 shows the classification of the 10-fold cross validation results for discrimination of the 0-back and the
2-back working memory tasks. We appreciate that a two-dimensional SPADE projection already provides a very
high accuracy to identify which level of memory loading the task required (2nd column). Such low dimensional
representation already provides higher discrimination than the obtained using a SVM in full covariance space
(5th column). Further, in this scenario the two main filters provide a discrimination accuracy very close to the
one obtained using all selected discriminant filters (3rd and 4th columns).

Comparison	SPADE-2D accuracy	SPADE Selected filters	SPADE accuracy	SVM accuracy
0 vs 2-back	93.9 (0.016) %	1-10 and 163-165	94.4 (0.015) %	91.3(0.018)%

Table 2: Summary results of the SPADE analyses in 2-back vs. 0-back working memory. The second column (SPADE 2-D) presents the
classification results when discriminating each pair of fMRI modalities using a SPADE two-dimensional projection of the data. The column
'SPADE selected filters' shows the eigen-spectrum location of the filters selected by the model order selection. The column 'SPADE
accuracy' shows the classification results obtained using the model order selection and the column 'SVM accuracy' shows the results
obtained using an SVM in full covariance space (i.e. feature space of dimension (165*166)/2= 13695).

In Figure 6 we present a summary of the spatial maps learned using the SPADE model. The filter providing the
most variance for the 2-back task, i.e. filter 1, involves left thalamus and hippocampus, bilateral putamen and
caudate, temporal pole and language areas. The next filter providing most variance for the 2-back task, i.e.
filter 2, involves left thalamus, bilateral hippocampus, brainstem, cingulate and paracingulate gyrus, bilateral
inferior frontal gyrus and left inferior temporal gyrus. On the other side of the eigen-spectrum, the filter
maximizing variance for the 0-back task, i.e. filter 165, involves brainstem, cingulate gyrus, left thalamus,
frontal pole and temporal gyrus and the next strongest filter for the 0-back task, i.e. filter 164, includes bilateral
thalamus, brainstem, cingulate gyrus, frontal pole and motor cortex. Summarizing, the networks identified for
the 2-back task involve areas purely related to working memory task while the 0-back task involves areas more
related to the attention and salience network. This clearly reflects that the 2-back task involves stronger
memory processing than the 0-back case which involves sustained attention.

Figure 6: Spatial maps obtained using SPADE to compare the 2-back against 0-back working memory fMRI task data. Left side: filters 1 and
2 show the filters maximizing variance for 2-back memory task. Right side: filters 164 and 165 show the filters maximizing variance for 0-
back memory task.

In general these presented results show some overlap with [22]. More specifically, some areas of filters 1 and 2
are present in both analyses. However, SPADE also reveals additional discriminative areas not found by the
direct univariate analysis, including for example the striatum or the superior frontal gyrus.

Discussion

In this work we showed that we can achieve optimal linear filtering of fMRI data by applying an initial spatial
dimensionality reduction followed by simultaneous diagonalization of covariance matrices [1,2]. We used a
regularized version of the covariance matrices [14], introduced a permutation strategy for model order selection,
i.e. how many spatial filters optimize discrimination, and we denote the fully developed model as SPADE
(Spatial Patterns for Discriminative Estimation). We validated the use of this strategy by using the high-quality
HCP data from 1063 subjects. The presented analyses illustrate the power of SPADE filters for discrimination of

fMRI data, and although accurate classification can be achieved also using (for example) an SVM in a high-
dimensional space (full covariance space), the power of the presented model is the intuitive interpretation of
the results that are summarized as a small set of spatial maps that can be used to further develop our
understanding of brain function. Contrary to the SVM, SPADE provides simple features that discriminate
between the compared conditions and which we can easily visualize back to brain space. This is certainly a big
advantage with respect to discrimination in full covariance, correlation/partial correlation space where the
interacting factors between different spatial nodes make the interpretation more difficult.

Our analyses revealed a strong specificity of the spatial distribution of different fMRI modalities across the
three considered modalities (rest, motor and working memory). Each of the discriminative spatial maps
obtained through SPADE reflects brain areas well-known to be relevant for a particular modality, reflecting for
example that a stronger engagement of the DMN is recorded during rest than during task fMRI. In the working
memory tasks, filters reveal independent effects for the ventral-dorsal pathways; the sensory integration is
represented in one filter and the higher-order memory storage and utilization in another filter. Indeed, these
two pathways start by sending sensory information to the parietal and temporal areas, characterizing spatial
versus categorical features related to the items to memorize. Both connect to the temporo-medial structure
(TMS) via specific connectivity to the parahippocampus, enthorinal cortex, before converging on the
hippocampus [30]. The TMS then connects through the temporal pole to the (prefrontal, pole) frontal and
(anterior) cingulate to store and use the information. Regarding working memory, we observe the phonological
loop with both Wernicke and Broca areas [31–33]. SPADE is extracting differentiating filters out of these networks,
demonstrating the existence of independent dynamics that can be the subject of further studies.

Ultimately, the SPADE model can extract regions of connectivity variation, obtained across different scenarios
using fMRI data. We have shown its ability when using big data by demonstrating that it is able to pick up on
areas relevant to each fMRI scenario but also by showing its close to optimal discrimination between
representative fMRI experiments. We consider that the model order estimation, as well as the classification
generalization of the model, can be used as a proxy of the specificity of the resulting spatial maps. As a
consequence, the quality of the spatial maps reported here for interpretation is very high. Clearly, this occurs
due to the strong differences in paradigms that we differentiate; for example, resting state from motor task
fMRI. Further, the presented extended numerical analyses identify the robustness of the results to the number
of subjects and temporal sampling of the fMRI and can serve as a reference to identify which scenarios can be
addressed though this methodology. Although high classification accuracy and a low standard deviation can be
achieved using around 100 subjects, getting strongly reproducible spatial maps with low standard deviation
was only achieved using 200 or more subjects. We observed that one side of the eigen-spectrum achieved
higher spatial reproducibility with less data than the other side. A solution to this fact, that is part of current
research, could be to learn these last filters as top filters of a new simultaneous diagonalization where the
input covariance matrices to the algorithm are used in a reversed order.

To show the performance of SPADE to discriminate even between relatively similar paradigms, we applied it to
compare 2-back working memory from 0-back working memory task fMRI data. We showed that the 2-back
task involves areas well known to be involved in working memory while the 0-back did not involve for example
the hippocampus, but instead, the identified networks involved areas related to the salient and attention
networks, as the frontal pole or the dorsal anterior cingulate gyrus. In comparing our results with those
presented in [22], we note that our analysis point to connectivity changes between 2 and 0-back task at areas
known to be involved in working memory tasks that were not clearly identified using the GLM approach in [22].
This is not a surprising result since both analyses are looking at different statistics in the data; while [22] reports
changes in the mean fMRI signal across conditions through a GLM analyses, the findings we report using SPADE
refer to changes in covariation between brain areas. Consequently, although the results are different, the
analysis we present here and that in [22] are not exclusive but rather complementary, with both having their
advantages and limitations: while for memory reasons we cannot yet compute the SPADE solutions at the full
brain, with a voxel-wise resolution, the computational load of performing the SPADE decomposition itself is
much lower than that of a typical GLM. As an example of the computational advantage of the SPADE model we
observe that after computing the ROI time-series for the 1063 subjects included in this study the computation
of the full SPADE spatial maps took less than two minutes using a standard laptop.

Although working full brain voxel-wise would be optimal, it is to date computationally intractable and our
choice of working in a parcellated full brain [20] could be replaced by working in a resting state network space or
even voxel-wise when restricted to an anatomical ROI that might be relevant for a particular investigation. Here
we considered a parcellated full brain for ease of results interpretation and visual validation. Further, since the
simultaneous diagonalization introduced by [1] can be used for any pair of symmetric positive definite matrices,
and given the growing neuroimaging interest in working with partial correlation matrices, we considered the
extension of the SPADE algorithm to partial correlation matrices and observe that it did not improve in
discrimination with respect to the original formulation. Nevertheless we believe that such an approach
warrants more thorough investigation in cases where the initial spatial dimensionality reduction results in more
highly correlated data, for example when using an ICA based strategy [5] or a small spatially continuous ROI; note
here that in these two scenarios, although the methodology is identical, the interpretation changes drastically
since the filters will relate to resting state networks directly or voxels being involved, respectively. An extra
flexibility of the presented model is the possibility of extension to multi-class versions by using combinations of
binary problems or with approximations to multiple simultaneous diagonalizations [34]. Another research
direction we are investigating for this model includes the study of subject-wise deviation from group functional
connectivity as a strategy to address normative modelling [35] on functional connectomes, or to get subject
dependent co-varying networks loadings that would allow SPADE to complement the GLM results at the single
subject level on task data. A final relevant line of research we consider is the non-trivial extension of SPADE to
full brain. Although this is challenging due to the high spatial resolution of fMRI data, and the strong spatial
correlation in the functional data, solving this limitation would make SPADE a very strong and specific model to
be applied in even more relevant scenarios, including voxel-wise task data analyses.

To conclude, the SPADE model is able to capture and summarize the brain nodes involved in network
covariation changes induced by fMRI experimental manipulation. As introduced here, the SPADE model can be
used to address questions of potential interest to diverse scientific and industrial communities.

Acknowledgements

The research leading to these results has received funding from the developing Human Connectome Project
through a Synergy Grant by the European Research Council under the European Union's Seventh Framework
Programme (FP/2007-2013), ERC Grant Agreement no. 319456. We further gratefully acknowledge support
from the Netherlands Organization for Scientific Research (NWO) through VENI grant to J.N.
(V1.Veni.194.032) and through VIDI grant to CFB (864.12.003). We also gratefully acknowledge funding from
the Wellcome Trust UK Strategic Award (098369/Z/12/Z).

Data were provided [in part] by the Human Connectome Project, WU-Minn Consortium (Principal Investigators:
David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16 NIH Institutes and Centers that
support the NIH Blueprint for Neuroscience Research; and by the McDonnell Center for Systems Neuroscience
at Washington University.

SUPLEMENTARY MATERIAL (SM)

Discriminative simultaneous covariance diagonalization.

Consider two sets of time-series, X and Y, measured at the same spatial locations during two different states of
the system being measured, and define the spatial covariance matrices of each of these series as C_X and C_Y.
Usually, the unsupervised simultaneous diagonalization of both covariances is achieved through a generalized
eigenvalue decomposition, involving a whitening transformation of one of the covariance structures (e.g C_X),
combined with a further rotation to also diagonalize the other covariance (C_Y). A different approach was
introduced in [1] where the whitening transformation is performed with respect to the sum of both covariances
$C := C_X + C_Y$; such whitening can be summarized by two matrices, a rotation W and a scaling diagonal matrix P,
such that $I = P^T W^T C W P$. Individually applying these transformations to C_X and C_Y, one obtains two (non-diagonal)
matrices $K_X = P^T W^T C_X W P$ and $K_Y = P^T W^T C_Y W P$. Performing now the eigenvalue decomposition of (for example) K_Y
we obtain matrices Z_Y and diagonal D_Y such that $Z_Y K_Y Z_Y^T = D_Y$. Defining $V := W P Z_Y$, we have that $V^T C_X V = I - D_Y$ and
$V^T C_Y V = D_Y$. This means that V defines a basis for the data that diagonalizes simultaneously C_X and C_Y and, and by

construction, the sum of the variances of the projections of data X and Y into each of the new basis vectors
adds to one; consequently, for basis directions where the projection of X has large variance (i.e. close to one),
the projection of Y must have low variance (i.e. close to zero), and vice versa. The algorithmic imposition to
maximize variance for one class and minimize it for the other one, makes of this process a supervised
multivariate dimensionality reduction model, and the new learned basis is formed of spatial filters that provide
optimal linear discrimination in terms of variance of the projected data (Blankertz et al., 2011). Note that for
implementation purposes it all reduces to solving a generalized eigenvalue problem which can be easily
accomplished using most software platforms, for example using the matlab command eig (C_x, C) or the python
command scipy.linalg.eigh(C_x,C,eigvals_only=False)). In the recent literature, the process described in [1] is
commonly used as a feature extractor for EEG based brain computer interfaces [2,7] and the features extracted
for discrimination are usually the logarithmic of the variance of the projected data; by construction of the
algorithm the most discriminative dimensions are the associated with the extreme eigenvectors since towards
the center of the eigen-spectrum the variances for both conditions tend to be close to ½. In practice, for
discrimination purposes the dimension is usually reduced to a few pairs of extreme eigenvectors and a low
dimensional linear classifier suffices [7].

Interpretation of the linear filters

449 Since the simultaneous diagonalization assumes no implicit noise model, the spatial filters learned, i.e. the
450 columns of V (V_k) cannot be directly interpreted and the interpretable spatial maps (A_k) are obtained from
451 $A=C_{X|Y}VC_S^{-1}$ [15,18], where X|Y denotes the spatially concatenated X and Y data, and S the data projected to the
452 new basis V, i.e. S= V^T(X|Y). For completeness we note here that X|Y = AS + e, where e denotes the residual of
453 the approximation X|Y = AS and for a more detailed description we refer the reader to [15,18].

Model order estimation

Although for classification purposes the SPADE model order selection is not critical due to the latter integration
of a classifier, for interpretation purposes we are required to select which filters provide significant connectivity
covariation information. To that end we address for the first time the model order estimation on this model by
permutation testing to find a robust estimation of which filters explain more variance for a modality than for
the other one with respect to a null distribution obtained by permutation. To that end a p-value is computed
for each basis vector (column of V, V_k) by comparing the absolute difference between the variances of the data
projections, Abs(Var(V'_k*X)- Var(V'_k*Y)), with a distribution of values obtained when the simultaneous
diagonalization new basis (V) is computed using randomized groups of covariances. In the dataset set used in
the main text the randomization is achieved by permuting half of the subject's covariance matrices across
different fMRI modalities.

Spatial reproducibility

478 Figure S1: SPADE spatial maps reproducibility for RT vs WM. Each subfigure shows the mean correlation matrix between the significant
479 spatial maps using the full sample (N=1063) and the ones obtained for N and T as indicated on each row and column. The mean is
480 computed over 100 random selections of subjects (see section Methods for details). The size of each correlation matrix equals the number
481 of significant selected filters as indicated in Table 1 and are accordingly ordered, with the top left corner and bottom right corner relating
482 to the spatial reproducibility of the most important filters, the first (#1) and the last (#165) ones.

Figure S2: SPADE spatial maps reproducibility for MT vs WM. Each subfigure shows the mean correlation matrix between the significant spatial maps using the full sample (N=1063) and the ones obtained for N and T as indicated on each row and column. The mean is computed over 100 random selections of subjects (see section Methods for details). The size of each correlation matrix equals the number of significant selected filters as indicated in Table 1 and are accordingly ordered, with the top left corner and bottom right corner relating to the spatial reproducibility of the most important filters, the first (#1) and the last (#165) ones.

References

1. Fukunaga, K. *Introduction to Statistical Pattern Recognition. Pattern Recognition* **22,** (1990).

2. Ramoser, H., Müller-Gerking, J. & Pfurtscheller, G. Optimal spatial filtering of single trial EEG during imagined hand movement. *IEEE Trans. Rehabil. Eng.* **8,** 441–446 (2000).

3. Friston, K., Holmes, A. & Worsley, K. Statistical parametric maps in functional imaging: a general linear approach. *Hum. Brain Mapp.* (1994).

4. Aguirre, G. K. & Detre, J. A. Experimental Design and the Relative Sensitivity of BOLD and Perfusion fMRI. **500,** 488–500 (2002).

5. Beckmann, C. F. & Smith, S. M. Probabilistic independent component analysis for functional magnetic resonance imaging. *IEEE Trans Med Imaging* **23(2),** 137–152 (2004).

6. Beckmann, C. F. & Smith, S. M. Tensorial extensions of independent component analysis for multisubject FMRI analysis. **25,** 294–311 (2005).

7. Blankertz, B., Lemm, S., Treder, M., Haufe, S. & Müller, K. R. Single-trial analysis and classification of

504  ERP components - A tutorial. *Neuroimage* **56,** 814–825 (2011).

505 8. A. Llera, R. Chauvyn, P. Mulders, M. Mennes, C. F. B. Rest vs Task fMRI connectivity: a simultaneous
506  covariance diagonalization approach. in *23-th Organization for Human Brain Mapping (OHBM)* (2017).
507  doi:10.13140/RG.2.2.11971.09765

508 9. Subbaraju, V., Belathur, M. & Sundaram, S. Identifying differences in brain activities and an accurate
509  detection of autism spectrum disorder using resting state functional-magnetic resonance imaging : A
510  spatial filtering approach. *Med. Image Anal.* **35,** 375–389 (2017).

511 10. Subbaraju, V. Identification of lateralized compensatory neural activities within the social brain due to
512  autism spectrum disorder in adolescent males. **47,** 631–642 (2018).

513 11. Aradhya, A. M. S., Subbara, V., Sundaram, S. & Sundarara, N. Regularized Spatial Filtering Method (R-
514  SFM) for detection of Attention Deficit Hyperactivity Disorder (ADHD) from resting-state functional
515  Magnetic Resonance Imaging (rs-fMRI). 5541–5544 (2018).

516 12. Itani, S. & Thanou, D. Combining Anatomical and Functional Networks for Neuropathology
517  Identification : A Case Study on Autism Spectrum Disorder.

518 13. Zhang, W. *et al.* Discriminating stress from rest based on resting-state connectivity of the human brain:
519  A supervised machine-learning study. *Hum. Brain Mapp.* **(In Press),** (2020).

520 14. Lotte, F. & Guan, C. Regularizing common spatial patterns to improve BCI designs: Unified theory and
521  new algorithms. *IEEE Trans. Biomed. Eng.* **58,** 355–362 (2011).

522 15. Haufe, S. *et al.* On the interpretation of weight vectors of linear models in multivariate neuroimaging.
523  *Neuroimage* **87,** 96–110 (2014).

524 16. Van Essen, D. C. *et al.* The WU-Minn Human Connectome Project: An overview. *Neuroimage* **80,** 62–79
525  (2013).

526 17. Elam, J. S. & Van Essen, P. D. Human Connectome Project. in *Encyclopedia of Computational
527  Neuroscience* 1–4 (2013).

528 18. Parra, L. C., Spence, C. D., Gerson, A. D. & Sajda, P. Recipes for the linear analysis of EEG. *Neuroimage*
529  **28,** 326–341 (2005).

530 19. Van Essen, D. C. *et al.* The Human Connectome Project: A data acquisition perspective. *NeuroImage* **62,**
531  2222–2231 (2012).

532 20. van Oort, E. S. B. *et al.* Functional parcellation using time courses of instantaneous connectivity.
533  *Neuroimage* **170,** 31–40 (2018).

534 21. Bishop, C. M. *Pattern Recognition and Machine Learning. Pattern Recognition* **4,** (2006).

535 22. Barch, D. M. *et al.* NeuroImage Function in the human connectome : Task-fMRI and individual
536  differences in behavior. *Neuroimage* **80,** 169–189 (2013).

537 23. Cole, M. W., Ito, T., Bassett, D. S. & Schultz, D. H. Activity flow over resting-state networks shapes
538  cognitive task activations. *Nat. Neurosci.* **19,** 1718–1726 (2016).

539 24. Sahyoun, C., Floyer-Lea, A., Johansen-Berg, H. & Matthews, P. . Towards an understanding of gait
540  control: brain activation during the anticipation, preparation and execution of foot movements.
541  *Neuroimage* **21,** 568–575 (2004).

542 25. Smith, S. M. *et al.* Correspondence of the brain's functional architecture during activation and rest.
543  *Proc. Natl. Acad. Sci.* **106,** 13040–13045 (2009).

544 26. Owen, A. M., McMillan, K. M., Laird, A. R. & Bullmore, E. N-back working memory paradigm: A meta-
545  analysis of normative functional neuroimaging studies. *Hum. Brain Mapp.* **25,** 46–59 (2005).

546 27. Soto, D., Rotshtein, P. & Kanai, R. Parietal structure and function explain human variation in working
547  memory biases of visual attention. *Neuroimage* **89,** 289–296 (2014).

28. Takahashi, E., Ohki, K. & Kim, D. S. Dissociation and convergence of the dorsal and ventral visual
working memory streams in the human prefrontal cortex. *Neuroimage* **65,** 488–498 (2013).

29. Haak, K. V. & Beckmann, C. F. Objective analysis of the topological organization of the human cortical
visual connectome suggests three visual pathways. *Cortex* **98,** 73–83 (2018).

30. Fernandez-Ruiz, A. & Oliva, A. Distributed Representation of 'What' and 'Where' Information in the
Parahippocampal Region. *J. Neurosci.* **36,** 8286–8288 (2016).

31. Müller, N. G. & Knight, R. T. The functional neuroanatomy of working memory: Contributions of human
brain lesion studies. *Neuroscience* **139,** 51–58 (2006).

32. Baddeley, A. Working memory: Looking back and looking forward. *Nat. Rev. Neurosci.* **4,** 829–839
(2003).

33. Baddeley, A. The episodic buffer: A new component of working memory? *Trends Cogn. Sci.* **4,** 417–423
(2000).

34. Grosse-wentrup, M., Member, S. & Buss, M. Multi-class Common Spatial Patterns and. **55,** 1–10 (2008).

35. Marquand, A. F., Rezek, I., Buitelaar, J. & Beckmann, C. F. Archival Report Understanding Heterogeneity
in Clinical Cohorts Using Normative Models : Beyond Case-Control Studies. *Biol. Psychiatry* **80,** 552–561
(2016).

565