Hippocampal subfields integrate information about past temporal and cognitive contexts

Halle R. Dimsdale-Zucker, Maria E. Montchal, Zachariah M. Reagh, Shao-Fang Wang, Laura A. Libby, Charan Ranganath

Abstract. The hippocampus plays a critical role in supporting episodic memory. Although we know that temporal context is a defining feature of episodic memory, we understand relatively little about how this information may be represented by the hippocampus. Research in rodents has suggested that the hippocampus represents temporal information on an absolute scale or in terms of relative temporal intervals, but cognitive models of memory have argued that temporal context in episodic memory is a consequence of changes in cognitive states and experiences. Here, we combined high-resolution fMRI imaging with voxel pattern similarity analyses to answer the question of how human hippocampal subfields represent retrieved information about cognitive states and the time at which a past event took place. As participants recollected previously presented items, activity patterns in the CA23DG subregion carried information about prior cognitive states, along with coarse-grained information about when the item was previously encountered. These findings are consistent with the idea that CA23DG supports temporal context in episodic memory by encoding an integrated representation of discrete and gradually-changing cognitive states.

Introduction. Converging evidence suggests that the hippocampus plays a critical role in memory for events and their episodic details (Eichenbaum, Yonelinas, & Ranganath, 2007; Scoville & Milner, 1957; Vargha-Khadem et al., 1997). For a memory to be considered episodic, it must be associated with a particular moment in time, or temporal context (Reiff & Scheerer, 1959; Tulving, 1983). Consistent with its integral role in

episodic memory, studies in rodents (Allen, Salz, McKenzie, & Fortin, 2016; Cai et al.,

2016; Kraus et al., 2015; Kraus, Robinson, White, Eichenbaum, & Hasselmo, 2013;

Salz et al., 2016), non-human primates (Naya, Chen, Yang, & Suzuki, 2017), and

humans (Dimsdale-Zucker, Ritchey, Ekstrom, Yonelinas, & Ranganath, 2018; Hsieh,

Gruber, Jenkins, & Ranganath, 2014; Jenkins & Ranganath, 2010, 2016; Tubridy &

Davachi, 2011) have shown that the hippocampus represents information about time.

At present, there are at least two major accounts of how this might happen. One

possibility is that the hippocampus maintains a continuously varying representation of

temporal context, possibly via internally generated cell assembly sequences (Buzsáki &

Llinás, 2017; Levy, 1996; Rodriguez & Levy, 2001; Wallenstein, Eichenbaum, &

Hasselmo, 1998). Consistent with this idea, results from single-unit recording studies in

rodents have suggested that cell populations in the hippocampus can faithfully

represent temporal relationships across both short (Kraus et al., 2015, 2013;

MacDonald, Lepage, Eden, & Eichenbaum, 2011; Salz et al., 2016) and longer (Cai et

al., 2016; Mankin, Diehl, Sparks, Leutgeb, & Leutgeb, 2015; Mankin et al., 2012; Ziv et

al., 2013) intervals. Another possibly complementary account comes from cognitive

theories of episodic memory that operationalize temporal context in terms of changes in

cognitive *states* or experiences (Estes, 1955; Howard & Kahana, 2002). Although

temporal context models generally assume that representations of temporal context

change gradually, these models also predict that context can abruptly change to reflect

one's current cognitive state (Lohnas, Polyn, & Kahana, 2015; Polyn, Norman, &

Kahana, 2009).

The extent to which the human hippocampus represents cognitive states and

temporal context is unclear, and there is reason to think that different hippocampal

subfields might make distinct contributions (Dimsdale-Zucker et al., 2018). For instance,

some models emphasize the role of area CA1 in encoding of temporal context (e.g.,

(Kesner & Rolls, 2015) others emphasize the importance of the dentate gyrus and CA3

(Levy, 1996; Lisman, 1999; Wallenstein et al., 1998), and some recent evidence has

suggested that area CA2 may be disproportionately important (Mankin et al., 2015).

Thus, this leaves open the question of whether temporal information may be

differentially represented by hippocampus subfields.

Here, we used high-resolution functional magnetic resonance imaging (fMRI) to

clarify whether or how the hippocampus encodes temporal and cognitive contexts

during episodic memory retrieval. We also examined contributions of medial temporal

cortical regions, as, for instance, parahippocampal cortex is known to be important for

representing contextual information (Davachi, 2006; Diana, Yonelinas, & Ranganath,

2007). We scanned participants while they recollected objects that were studied in

sequentially-organized lists, and used voxel pattern similarity (PS) analyses (Dimsdale-

Zucker & Ranganath, 2018; Kriegeskorte, Mur, & Bandettini, 2008) to examine whether

patterns of activity in hippocampal subfields at the time of retrieval carried information

about temporal and cognitive contexts instantiated at encoding.

Method.

Participants. 32 participants were recruited from the community and were

compensated $50 for their time. This study was approved by the Institutional Review

Board at the University of California, Davis. Four participants were excluded due to

missing behavioral data, two participants were excluded for excessive motion that

prevented tracing of hippocampal subfields, one participant was excluded due to an

experimenter error at data collection that resulted in the incorrect stimuli being seen,

and one participant was excluded because they only had one run of usable data after

discarding motion-contaminated and data-collection contaminated runs. The results

below reflect data from 24 remaining participants (Mage = 22.85 years, SD = 3.06

years, Nfemale = 13). One of these 24 participants was excluded from behavioral

cognitive and temporal context analyses due to partially missing data; since the brain

imaging data for this participant were complete and did not depend on this behavior

being recorded, they were included in all other analyses.

Encoding. Participants viewed eight 36-item lists of still pictures of everyday

objects (e.g., contact lens case, french fries; http://cvcl.mit.edu/mm/uniqueObjects.html;

see Figure 1). Object assignment to list and presentation order of objects within a list

were uniquely randomized for each participant via the Matlab randperm function. To

encourage participants to learn temporal relationships amongst items in a list (Palombo,

Di Lascio, Howard, & Verfaellie, 2019), each list was presented three times in a mini-

block before subjects saw items from the next list (e.g., 1, 1, 1, 2, 2, 2...8, 8, 8). Mini-

blocks were separated with a self-paced break. Presentation order of objects within a

list was identical for all three list presentations.

Objects remained on the screen for 2.5 seconds (timing and presentation

parameters were controlled via Presentation [Neurobehavioral Systems, Inc., Berkeley,

CA, www.neurobs.com]) while the participant made a yes/no button response to an

orienting question (cognitive context). To manipulate cognitive context, each object was

associated with one of four questions: Would this item fit in a refrigerator?, Would this

item fit in a bathtub?, Would you find this item in a convenience store?, Would you find

this item in a supermarket?. Each of the four questions was presented equally often in

each block, and question/object pairs remained the same across all three list

presentations. Participants were instructed that this was a decision-making task and

that there would be some repetition but to concentrate on doing the task. Participants

were not aware that memory for these questions would be tested later, thus the learning

of question and temporal context information was incidental.

Scanned object recognition. While in the MRI scanner, participants saw each

of the 288 old objects from encoding as well as 72 new objects presented one at a time

for 2.5 seconds with a jittered ITI ranging from 2-15 seconds (mean ITI jitter = 6

seconds). Objects were divided into 6 runs (60 trials per run). Object order within a run

was pseudo-randomized such that objects with the same encoding question always had

at least one intervening object (e.g., fridge, convenience store, bathtub, fridge,

supermarket, fridge, etc.) to help minimize encoding context reinstatement biases on PS

results (see Multivariate Results below). Proximity of objects from encoding mini-blocks

(1-8) was not considered in the pseudo-randomization.

While in the scanner, participants were instructed to indicate via button press

whether or not they remembered the object on a 4-point scale: 1=new, 2=familiar (old

but no remembered details), 3=remembered non-temporal details (e.g., the encoding

question, something about the object itself, or an association they made with the

object), 4=remembered temporal detail (e.g., in what list or when they had seen the

object during encoding). Responses for remembered judgments were collapsed into a

single response bin for behavioral and fMRI analyses.

Source memory: Cognitive context. After completing MRI scanning,

participants returned to the lab where they completed a cognitive context source

memory task. In this phase, participants saw all 288 studied objects from encoding and

were asked to indicate which encoding question (fridge/bathtub/convenience

store/grocery store) had been associated with the object. Objects were presented

across four blocks of 72 trials each. Within each block, there were an equal number of

objects from each encoding mini-block (1-8). Presentation order of objects was uniquely

randomized by participant within each source memory block. Objects appeared on the

screen until the participant had made their source memory judgment. There was no

opportunity to guess or skip objects.

Source memory: Temporal context. After completing the cognitive context

source memory test, participants again saw the 288 old objects from encoding and this

time were asked to indicate in which mini-block (1-8) the object had appeared. Objects

were again divided across four blocks of 72 trials with a different randomization order

than was used in the task context source memory test. Objects remained on the screen

until the participant had made their response. There was no opportunity to guess or skip

temporal context judgments.

fMRI acquisition and pre-processing. Scans were acquired on a Siemens

Skyra 3T scanner with a 32 channel head coil. Two sets of structural images were

acquired to enable subfield segmentation: A T1-weighted magnetization prepared rapid

acquisition gradient echo (MP-RAGE) pulse sequence image (1 mm isotropic voxels),

and a high-resolution T2-weighted image (TR = 4200 ms; TE= 93 ms; field of view =

200 mm^2; flip angle = 139°; bandwidth = 199 Hz/pixel; voxel size = 0.4 x 0.4 x 1.9 mm;

58 coronal slices acquired perpendicular to the long-axis of the hippocampus). High-

resolution functional (T2*) images were acquired using a multiband gradient echo planar

(EPI) imaging sequence (TR = 2010 ms; TE = 25 ms; field of view = 216 mm; image

matrix = 144 x 152; flip angle = 79°; bandwidth = 1240 Hx/pixel; partial phase Fourier =

6/8; parallel imaging = GRAPPA acceleration factor 2 with 72 reference lines; multiband

factor = 2; 52 oblique axial slices acquired parallel to the long-axis of the hippocampus

slices; voxel size = 1.5 mm isotropic).

SPM8 (http://www.fil.ion.ucl.ac.uk/spm/) was used for image pre-processing.

Functional EPI images were realigned to the first image and resliced. No slice timing

correction was performed due to the acquisition of multiple simultaneous slices with the

multiband sequence (capabilities to handle multiband timing do not exist in SPM8). Co-

registration between the native-space ROIs defined in T2 space and the functional

images was done with SPM's Coregister: Estimate and Reslice procedure. This

procedure uses a linear normalized mutual information cost-function between a

reference (mean functional) image and source (T2) image to compute and apply a

voxel-by-voxel affine transformation matrix. This transformation matrix was then applied

to the subfield ROIs that had been defined in T2 space (see *ROI segmentation*) to bring

them into register with the functional images. The T1 image was co-registered to the

mean EPI. Then, nonlinear spatial normalization parameters were derived by

segmenting the coregistered T1 image. Quality assurance included identifying suspect

timepoints via custom code (https://github.com/memobc/memolab-fmri-qa) defined as

time-points in excess of 0.5 mm frame displacement (based on (Power, Barnes, Snyder,

Schlaggar, & Petersen, 2012) or 1.5% global mean signal change (based on ARTRepair

recommendations, (Mazaika, Whitfield-Gabrieli, & Cooper, 2005)). Runs were excluded

if the frame displacement exceeded the voxel size. As reported earlier, three

participants were excluded for motion in excess of these thresholds; of the 24 subjects

included in the analyses, 9 had runs excluded based on these thresholds (mean

number of removed runs = 0.92, SD = 1.38; ranging from 0-4 runs).

Pattern similarity analyses. PS analyses were conducted on beta maps

generated from unsmoothed data in native subject space. Following the least squares

separate procedure described by Mumford (2012), single trial models were generated to

estimate the unique beta map for every trial in a run (N=60). Within each single trial

model, the first regressor modeled the trial of interest with a stick function, the second

regressor modeled all other trials in that run, six regressors were used to capture

motion, and any additional spike regressors as identified by our QA scripts were used to

capture additional residual variance. Voxel-wise patterns of hemodynamic activity were

separately extracted for each ROI from the single trial beta images. To ensure robust

ability to detect differences in PS, we required temporal signal-to-noise ratios (TSNR) in

a region to be above 20 (approximately 2 standard deviations below the mean global

TSNR of 50.4). This required the removal of entorhinal cortex and its subregions (mean

TSNR ranged between 10-20), despite its compelling role in the representation of

temporal context (Bellmund, Deuker, & Doeller, 2019; Montchal, Reagh, & Yassa, 2019)

Within each ROI, correlations (Pearson's r) were computed between these trial-

wise betas to yield a trial-by-trial correlation matrix that related each voxel's signal on a

trial to all other trials across all runs. We restricted comparisons to those trials for which

participants made a correct "remember" response (during MRI scanning). Correlation

values were z-transformed prior to statistical analysis. Statistical analyses tested for

differences in correlations between trial pairs on the basis of encoding context (cognitive

context: same vs. different encoding question; temporal context: same vs. different

encoding list, or similar vs. different list half). To more accurately characterize both

within- and across-subject error variance (Baayen, Davidson, & Bates, 2008; Clark,

1973; Dixon, 2008; Jaeger, 2008; Mumford & Poldrack, 2007; Singmann & Kellen, in

press), we implemented a mixed-modelling approach to evaluate statistical significance

with the *lme4* packing in R (Bates, Mächler, Bolker, & Walker, 2014); for a similar

approach, see (Dimsdale-Zucker et al., 2018). Only between-run correlations were used

to maximize the number of possible trial pairs without mixing within- and between-run

correlations. Trial pairs of interest were extracted from these trial-by-trial correlation

matrices.

All relevant code (https://github.com/hallez/tempcon_pub), a reproducible

compute environment (https://doi.org/10.24433/CO.0129473.v1), and relevant data

(https://osf.io/qfcjg/) are available online.

ROI definition. Hippocampal subfields were defined following the procedure

reported in (Dimsdale-Zucker et al., 2018). In short, the ASHS automated segmentation

procedure was used to delineate subfields in subject-native space (Yushkevich et al.,

2010). We restricted our analyses to hippocampal body where discriminating subfields

is most agreed upon. Medial temporal lobe cortical regions were manually-traced (see

the Libby and Ranganath protocol in (Yushkevich et al., 2015)). In accordance with prior

findings suggesting functional distinctions between anterior and posterior

parahippocampal gyrus (Aminoff, Gronau, & Bar, 2007; Baldassano, Beck, & Fei-Fei,

2013; Baldassano, Esteva, Fei-Fei, & Beck, 2016), we subdivided parahippocampal

cortex one slice posterior to the wing of the ambient cistern (Frankó, Insausti, Artacho-

Pérula, Insausti, & Chavoix, 2014).

215
Figure 1. Task structure. During the encoding phase, each participant studied lists of
36 objects that were each randomly paired with one of four encoding questions ("Would
this item fit in a fridge?", "Would this item fit in a bathtub?", "Would you find this item in a

supermarket?", "Would you find this item in a convenience store?"). Each list was
repeated three times in a row to promote learning of the temporal relationships amongst
the items. Objects appeared in the same order and with the same question (cognitive
context) across all repetitions. High-resolution functional magnetic resonance brain
imaging (fMRI) was used to examine hippocampal activity patterns during a recognition
memory test for these objects, allowing us to examine activity pattern similarity as a
function of whether pairs of items were encoded within the same or similar temporal
contexts (i.e., studied in the same list or temporally proximal lists), and/or the same
cognitive context (i.e., associated encoding question)
228
Results.

Behavioral results. During MRI scanning participants performed a recognition

memory test requiring judgments as to whether each item was recognized on the basis

of recollection of specific item and source information from the study phase (see

Method). Pattern similarity analyses were restricted to correctly remembered items.

Correct remember judgments were the most common response (mean hit rate =

0.69, SD = 0.19), and, for these items, participants showed high accuracy at

remembering the associated encoding task context (mean hit rate = 0.71, SD = 0.12).

Memory for the exact ("same") temporal context (list 1-8) was poor (mean hit rate =

0.18, SD = 0.03), but, we reasoned that, even if participants were unable to recall the

exact list identity, they might have memory for the "similar" temporal context associated

with each item. We therefore re-scored each trial according to whether the participant

could accurately determine whether it was presented in the "similar" (first half (lists 1-4)

or the second half (lists 5-8)) versus "different" (across halves, i.e., list 1/list5, list 1/list 6,

etc.) temporal context of the encoding phase. On this metric, memory for similar

temporal context (mean hit rate for list half = 0.59, SD = 0.04) was reliably greater than

chance of 0.5, t(22) = 8.74, *p* < 0.001. Thus, although participants did not have access

to the precise list in which an item had been studied, they were able to retrieve

information about the item's temporal context at a coarse level.

fMRI results: Hippocampal Subfields We next tested whether activity patterns

in the hippocampal subfields (CA1, CA23DG, subiculum) during memory retrieval

carried information about the context in which the item was previously encountered.

Specifically, we examined voxel PS during retrieval as a function of whether pairs of

trials shared a temporal (defined either as same list vs. different list [*same* temporal

context] or as same half of the experiment vs. different halves of the experiment [*similar*

temporal context]) and/or cognitive (i.e., same encoding task vs. different encoding task)

context when the items were originally learned.

We first considered when items came from the "same" temporal encoding context

(same vs. different list). No hippocampal subfield varied its PS at retrieval with respect

to the same temporal context (all $X^2 < 0.5$, all ps > 0.40). In CA23DG, we found that PS

was higher during retrieval of items associated with the same cognitive context

compared to items associated with different cognitive contexts ($X^2(1) = 4.63$, $p^{perm1000} =$

0.031). No other subfield varied its PS at retrieval with respect to cognitive context alone

(all $X^2 < 0.3$, all ps > 0.55) nor the combination of temporal and cognitive context (all X^2

< 0.80, all ps > 0.30).

We next considered whether PS might depend on whether items shared a

"similar" temporal context at encoding (same vs. different half of the encoding phase).

PS levels did not vary by similar temporal context alone ($X^2(1) = 0.08$, $p^{perm1000} = 0.815$).

Thus, PS levels were not modulated by same or similar temporal context alone. In

CA23DG, we found that PS was higher during retrieval of items that were associated

with the same cognitive context than for items that were associated with different

cognitive contexts ($X^2(1) = 4.68$, $p^{perm1000} = 0.037$; see Figure 2). Thus, irrespective of

how we defined temporal context (same, similar), PS in CA23DG was higher for items

that were associated with the same cognitive context. This effect was qualified by a

significant similar temporal by cognitive context interaction ($X^2(1) = 8.11$, $p^{perm1000} =$

0.008), such that the effect of cognitive context was larger for items that were in similar

temporal contexts (same half) than for items that were in different temporal contexts

(different half) particularly when these items shared the same cognitive context.

In CA1, PS levels did not vary by similar temporal context ($X^2(1) = 2.42$, $p^{perm1000}$

$= 0.122$), cognitive context ($X^2(1) = 0.08$, $p^{perm1000} = 0.757$), nor when we considered

both temporal and cognitive context ($X^2(1) = 0.84$, $p^{perm1000} = 0.329$). In subiculum, PS

levels did not vary by similar temporal context ($X^2(1) = 0.11$, $p^{perm1000} = 0.751$) or

cognitive context ($X^2(1) = 0.27$, $p^{perm1000} = 0.622$), however, we found that PS was

marginally higher for items that were studied relative to the same question but studied in

different list halves as compared to all other conditions ($X^2(1) = 2.91$, $p^{perm1000} = 0.082$).

Figure 2. Pattern similarity values in CA23DG during memory retrieval carry information about temporal and cognitive encoding contexts. A. Mean pattern similarity scores, with scatter of individual subject observations for the combination of different encoding contexts. B. Differences between same/different list half ("similar" temporal context), same/different question (cognitive context), and the interaction of temporal and cognitive context ([same question, same list half – different question, same list half] – [same question, different list half – different question, different list half). C. Permuted chi-square values to determine significance of cognitive-by-temporal interaction.

fMRI Results: Medial Temporal Lobe (MTL) Neocortical Areas

Our next analyses investigated activity in MTL regions outside of the hippocampus. Previous work has suggested that regions in parahippocampal cortex (PHC) should process information about cognitive context (Diana, Yonelinas, & Ranganath, 2012, 2013; F. Wang & Diana, 2017). In anterior PHC (aPHC), we observed an interaction between cognitive context, same temporal context, and hemisphere ($X^2(3) = 8.91$, $p^{perm1000} = 0.037$). Looking across hemispheres, PS levels only varied reliably in left aPHC on the basis of cognitive context ($X^2(1) = 7.89$, $p^{perm1000}$

= 0.007). We found no other significant effects involving same temporal context (all X^2 <

0.7, all ps > 0.4), nor the combination of same temporal and cognitive context (all X^2 <

1.2, all ps > 0.2) in either hemisphere. PS in posterior PHC (pPHC) was marginally

greater for items in the different as compared to same temporal context ($X^2(1) = 3.75$,

$p^{perm1000} = 0.055$), but did not vary on the basis of cognitive context alone ($X^2(1) = 1.22$,

$p^{perm1000} = 0.263$). This marginal effect of same temporal context in pPHC was qualified

by a significant same temporal context by cognitive context interaction ($X^2(1) = 8.18$,

$p^{perm1000} = 0.002$). PS levels in PRC did not vary by temporal encoding context ($X^2(1) =$

0.001, $p^{perm1000} = 0.981$), cognitive context ($X^2(1) = 0.51$, $p^{perm1000} = 0.497$), nor the

combination of temporal and cognitive context ($X^2(1) = 0.82$, $p^{perm1000} = 0.354$).

We next considered whether PS in MTL neocortical areas might depend on

whether items shared a similar temporal context at encoding. In aPHC, we observed an

interaction between cognitive context, similar temporal context, and hemisphere ($X^2(1) =$

9.17, $p^{perm1000} = 0.028$). This reflects the fact that in left aPHC, voxel PS was greater for

items studied relative to different cognitive contexts ($X^2(1) = 7.96$, $p^{perm1000} = 0.006$), as

well as for items from different temporal contexts ($X^2(1) = 5.75$, $p^{perm1000} = 0.015$), but

did not vary based on the combination of cognitive and temporal context ($X^2(1) = 0.88$,

$p^{perm1000} = 0.349$). In right aPHC, voxel PS did not carry information about an item's

cognitive context ($X^2(1) = 0.75$, $p^{perm1000} = 0.372$) or temporal ($X^2(1) = 1.49$, $p^{perm1000} =$

0.226) context, nor their combination ($X^2(1) = 0.27$, $p^{perm1000} = 0.60$). PS levels did not

reliably vary for cognitive context (all X^2 < 1.2, all ps > 0.25), similar temporal context (all

X^2 < 0.30, all ps > 0.60), nor the combination of cognitive and temporal context (all X^2 <

1.9, all ps > 0.25) in either pPHC or PRC.

Discussion.

The goal of the present study was to test the extent to which the hippocampus represents absolute temporal information and information about particular cognitive states during recollection of past events. Although cognitive states typically fluctuate over time in a continuous manner, the design of our experiment allowed us to examine the influence of these two aspects of context separately. We found that, during recollection of a study item, CA23DG activity patterns carried information about the cognitive context associated with that item during the study phase. Additionally, cognitive context information evident in CA23DG activity patterns varied over a coarse timescale, such that pattern similarity was highest for pairs of items that were associated with similar temporal and cognitive contexts. Collectively, these findings demonstrate that the hippocampus represents information about past events in a manner that is consistent with temporal context models (Howard & Kahana, 2002; Norman, Detre, & Polyn, 2008; Polyn et al., 2009; Sederberg, Howard, & Kahana, 2008).

We have long understood that context is central for recall (Clewett & Davachi, 2017; Davachi & DuBrow, 2015; Zacks & Swallow, 2007) and recollection-based recognition (Eichenbaum et al., 2007), but we do not yet understand how *temporal* context may be encoded in the brain. These representations of temporal and cognitive state contexts seem to rely on the hippocampus (Eichenbaum, 2017; Ranganath, 2019). In the hippocampus, one candidate mechanism is the coordinated firing of self-organized cell assemblies, or time cells (Lisman & Jensen, 2013; Y. Wang, Romani, Lustig, Leonardo, & Pastalkova, 2015). These cells can track how long an animal has

been running on a treadmill where distance, speed, and duration of run time can be

decorrelated (Kraus et al., 2015, 2013; Salz et al., 2016), code for meaningful gaps or

pauses (MacDonald et al., 2011), and represent ordered sequences and experiences

even during rest periods (Pastalkova, Itskov, Amarasingham, & Buzsáki, 2008).

Hippocampal ensembles also drift in their representations of space when recorded

across days, thus it seems that they can encode both fine and coarse temporal

information (Mankin et al., 2015, 2012; Rubin, Geva, Sheintuch, & Ziv, 2015; Ziv et al.,

2013). These findings provide evidence for the idea that hippocampal neurons may

encode information about temporal intervals or the passage of time. That said, available

evidence indicates that hippocampal time cells are highly sensitive to changes in task

context. In one such demonstration, immobilized rats learned to maintain information

about specific odors across a delay period (MacDonald et al., 2013). Results showed

that different cell assemblies encoded temporal intervals across the delay period

depending on the odor that was to be maintained. In other words, changes in the task

context led to substantial changes in the neural ensembles that encoded temporal

information during the task.

In the present study, we found evidence for the idea that information about

cognitive states (i.e., specific task contexts) was carried in hippocampal activity patterns

during recollection, and that these patterns also carried relatively coarse-grained

information about the temporal context in which the recollected item was initially

encountered (see also (DuBrow, Rouhani, Niv, & Norman, 2017) for evidence that

contexts can drift slowly). This is consistent with the scale of temporal information

participants had access to behaviorally; they were poor at retrieving the exact list an

item had been in but had access to information about in which half of the study lists it

had occurred. These findings are generally in line with what would be predicted by

cognitive models of the representation of temporal context in episodic memory. Initial

theories operationalized temporal context as random fluctuations in cognitive states

over time (Estes, 1955), and subsequent theories have incorporated the assumption

that temporal context also reflects a time-weighted average of recently processed items

and experiences (Howard & Kahana, 2002; Norman et al., 2008; Sederberg et al.,

2008). These models would predict that activity patterns during memory retrieval should

reflect information about the temporal context associated with each study item (e.g.,

Manning et al., 2011; Deuker et al., 2016; Nielson et al., 2015). The Context

Maintenance and Retrieval (CMR) model goes farther by incorporating information

about the current task or cognitive state into the temporal context representation. CMR

predicts that if there are abrupt changes in one's cognitive state (e.g., a change in the

task that one is performing), items that are temporally proximal can actually have

distinct contextual associations (Polyn et al., 2009). Thus, the CMR model predicts that,

during memory retrieval, reinstatement of temporal context should reflect a conjunction

of task-related information and information that reflects elapsed time, similar to what

was observed in CA23DG. Though CMR most explicitly incorporates semantic

relationships into the temporal context model, we suggest that contextual associations

associated with task or cognitive states likely tap into a similar mechanism. Moreover,

the model suggests that changing tasks during encoding would break up the temporal

context representation during encoding of each list. This prediction is consistent with the

fact that we did not see evidence of high pattern similarity across items within the same

list, and instead only saw representation of temporal information across coarser

timescales.

At a broader level, our findings converge with results from a number of recent

studies showing that hippocampal activity patterns carry information that generalizes

across events that share common elements (Horner, Bisby, Bush, Lin, & Burgess, 2015;

Schlichting & Preston, 2015). Here, we found that activity patterns in the CA23DG

subregion generalize across items that shared both temporal and task context. Other

findings, however, suggest that hippocampal representations can amplify differences

between overlapping experiences (Chanales, Oza, Favila, & Kuhl, 2017; Libby, Reagh,

Bouffard, Ragland, & Ranganath, 2018; Ritvo, Turk-Browne, & Norman, 2019; Yassa &

Stark, 2011). In one recent study, for instance, we found that CA23DG activity patterns

during memory retrieval were more different for across pairs of items that were

associated with the same episodic context (i.e., objects seen within the same movie)

than across pairs of items that were associated with different contexts. The findings of

Dimsdale-Zucker et al. (2018), considered alongside the present results, raise an

important question: When does CA23DG assign similar or distinct representations to

overlapping events?

To answer this question, it may be informative to consider the conflicting role of

shared context in facilitating inter-item relationships (Sederberg, Miller, Howard, &

Kahana, 2010) while diminishing item distinctiveness (El-Kalliny et al., 2019). During

recognition memory tests, people are generally more likely to recollect events that were

distinctive than events that were overwhelmingly similar to one another (Hunt, 1995). If

CA23DG represents information about one's cognitive state during an event, then we

would expect that this area would be most likely to support successful recollection when

those representations are distinctive. In the present study, changes in the encoding task

encouraged participants to shift cognitive states abruptly across items within a list. By

attending to the task context, a participant could form distinctive memories for the

different items that were in the same list. In our previous study (Dimsdale-Zucker et al.,

2018), however, participants studied lists of items presented in virtual reality videos that

depicted navigation through two homes. Thus, the environmental context was

overwhelmingly similar across items in the same list, and the cognitive context was not

explicitly controlled (i.e., cognitive context likely tracked with environments and the

passage of time). To successfully encode items from the study phase, participants

needed to form representations that highlighted the distinctive aspects of each item in

the list in order to overcome contextual interference at the time of retrieval (Park, Arndt,

& Reder, 2006). We therefore propose that, by binding information about items with

information about cognitive contexts, CA23DG can support successful retrieval of

overlapping memories that would otherwise be difficult to disambiguate (Yassa &

Reagh, 2013).

Our findings also highlight the relative paucity of direct access to memory for

temporal context at retrieval. Behavioral measures of memory for temporal context

show clustered recall; that is, items studied nearer in time to one another are more likely

to be recalled close together (Kahana, 1996). These findings suggest that, during

episodic memory retrieval, people may be mentally transported back to a past cognitive

state (Manning, Polyn, Baltuch, Litt, & Kahana, 2011; Tulving, 1983). Yet, when people

are explicitly asked about temporal order information, they often cannot produce reliable

estimates (Jenkins & Ranganath, 2010). In the present study, we also found that

participants had little explicit access to an item's temporal encoding context. When

asked to choose in which of eight lists an item had been studied, participants were

essentially at chance. This is not surprising because temporal context models only

suggest that memories for temporally proximal events should be associated with similar

context representations, but retrieval of context information would not automatically

enable a person to determine the exact time at which a previous item was encountered.

There is considerable evidence to suggest that people rely on heuristics strategies in

order to roughly reconstruct the time at which an event took place (Friedman, 1993). In

our study, this might have been more challenging because, as we have stated above,

changes in cognitive context within a list most likely disrupted the continuity of temporal

context representations (for a related finding, see (Polyn et al., 2009)).

In addition to the hippocampus, medial temporal lobe cortical regions have also

been implicated in representing context. A substantial body of work has suggested a

particular role for parahippocampal cortex in supporting representations of context

(Davachi, 2006; Diana et al., 2007, 2013; Hsieh et al., 2014; Tubridy & Davachi, 2011;

F. Wang & Diana, 2017). In line with these findings, we also saw that parahippocampal

cortex carried information about cognitive and temporal contexts. Recent work has also

suggested a role for lateral entorhinal cortex in absolute representations of time

(Bellmund et al., 2019; Montchal et al., 2019; Sugar & Moser, 2019). Unfortunately, we

could not assess whether lateral entorhinal cortex represented elapsed time because

our scanning protocol was not optimized for entorhinal cortex coverage, and the

temporal signal-to-noise ratio was therefore insufficient. Thus, it is possible that in this

task where participants had access to both a sense of ongoing time and fluctuating

cognitive states, hippocampus and entorhinal cortex could play complementary roles.

Taken together, we have shown that that activity patterns in the CA23DG region

of the human hippocampus reflected an integrated representation of cognitive and

coarse temporal contexts. This finding can help explain how we represent continuously

unfolding episodes in a changing world. Outside of the laboratory, we are constantly

multitasking between competing goals and responsibilities. The hippocampus, and,

specifically CA23DG, may allow us to differentiate between experiences that are

associated with different tasks while preserving the temporal flow between experiences.

472
473

474   **References**

475   Allen, T. A., Salz, D. M., McKenzie, S., & Fortin, N. J. (2016). Nonspatial Sequence Coding in CA1

476   Neurons. *The Journal of Neuroscience*, *36*(5), 1547–1563.

477   https://doi.org/10.1523/JNEUROSCI.2874-15.2016

478   Aminoff, E., Gronau, N., & Bar, M. (2007). The parahippocampal cortex mediates spatial and

479   nonspatial associations. *Cerebral Cortex (New York, N.Y.: 1991)*, *17*(7), 1493–1503.

480   https://doi.org/10.1093/cercor/bhl078

481   Baayen, R. H., Davidson, D. J., & Bates, D. M. (2008). Mixed-effects modeling with crossed

482   random effects for subjects and items. *Journal of Memory and Language*, *59*(4), 390–

483   412. https://doi.org/10.1016/j.jml.2007.12.005

484   Baldassano, C., Beck, D. M., & Fei-Fei, L. (2013). Differential connectivity within the

485   Parahippocampal Place Area. *NeuroImage*, *75*, 228–237.

486   https://doi.org/10.1016/j.neuroimage.2013.02.073

487   Baldassano, C., Esteva, A., Fei-Fei, L., & Beck, D. M. (2016). Two Distinct Scene-Processing

488   Networks Connecting Vision and Memory. *ENeuro*, *3*(5), ENEURO.0178-16.2016.

489   https://doi.org/10.1523/ENEURO.0178-16.2016

490   Bates, D., Mächler, M., Bolker, B., & Walker, S. (2014). Fitting Linear Mixed-Effects Models using

491   lme4. *10.18637/Jss.V067.I01*, 1–48.

492   Bellmund, J. L., Deuker, L., & Doeller, C. F. (2019). Mapping sequence structure in the human

493   lateral entorhinal cortex. *ELife*, *8*, e45333. https://doi.org/10.7554/eLife.45333

494   Buzsáki, G., & Llinás, R. (2017). Space and time in the brain. *Science (New York, N.Y.)*, *358*(6362),

495   482–485. https://doi.org/10.1126/science.aan8869

Cai, D. J., Aharoni, D., Shuman, T., Shobe, J., Biane, J., Song, W., … Silva, A. J. (2016). A shared

neural ensemble links distinct contextual memories encoded close in time. *Nature*,

534(7605), 115–118. https://doi.org/10.1038/nature17955

Chanales, A. J. H., Oza, A., Favila, S. E., & Kuhl, B. A. (2017). Overlap among Spatial Memories

Triggers Repulsion of Hippocampal Representations. *Current Biology: CB*, *27*(15), 2307-

2317.e5. https://doi.org/10.1016/j.cub.2017.06.057

Clark, H. H. (1973). The language-as-fixed-effect fallacy: A critique of language statistics in

psychological research. *Journal of Verbal Learning and Verbal Behavior*, *12*(4), 335–359.

https://doi.org/10.1016/S0022-5371(73)80014-3

Clewett, D., & Davachi, L. (2017). The ebb and flow of experience determines the temporal

structure of memory. *Current Opinion in Behavioral Sciences*, *17*, 186–193.

https://doi.org/10.1016/j.cobeha.2017.08.013

Davachi, L. (2006). Item, context and relational episodic encoding in humans. *Current Opinion in*

Neurobiology, *16*(6), 693–700. https://doi.org/10.1016/j.conb.2006.10.012

Davachi, L., & DuBrow, S. (2015). How the hippocampus preserves order: the role of prediction

and context. *Trends in Cognitive Sciences*, *19*(2), 92–99.

https://doi.org/10.1016/j.tics.2014.12.004

Diana, R. A., Yonelinas, A. P., & Ranganath, C. (2007). Imaging recollection and familiarity in the

medial temporal lobe: a three-component model. *Trends in Cognitive Sciences*, *11*(9),

379–386. https://doi.org/10.1016/j.tics.2007.08.001

Diana, R. A., Yonelinas, A. P., & Ranganath, C. (2012). Adaptation to cognitive context and item

information in the medial temporal lobes. *Neuropsychologia*, *50*(13), 3062–3069.

https://doi.org/10.1016/j.neuropsychologia.2012.07.035

Diana, R. A., Yonelinas, A. P., & Ranganath, C. (2013). Parahippocampal cortex activation during

context reinstatement predicts item recollection. *Journal of Experimental Psychology.*

General, *142*(4), 1287–1297. https://doi.org/10.1037/a0034029

Dimsdale-Zucker, H. R., & Ranganath, C. (2018). Representational Similarity Analyses: A

Practical Guide for Functional MRI Applications. In D. Manahan-Vaughan (Ed.),

Handbook of in Vivo Neural Plasticity Techniques. Elsevier.

Dimsdale-Zucker, H. R., Ritchey, M., Ekstrom, A. D., Yonelinas, A. P., & Ranganath, C. (2018).

CA1 and CA3 differentially support spontaneous retrieval of episodic contexts within

human hippocampal subfields. *Nature Communications*, *9*(1), 294.

https://doi.org/10.1038/s41467-017-02752-1

Dixon, P. (2008). Models of accuracy in repeated-measures designs. *Journal of Memory and*

Language, *59*(4), 447–456. https://doi.org/10.1016/j.jml.2007.11.004

DuBrow, S., Rouhani, N., Niv, Y., & Norman, K. A. (2017). Does mental context drift or shift?

Current Opinion in Behavioral Sciences, *17*(Supplement C), 141–146.

https://doi.org/10.1016/j.cobeha.2017.08.003

Eichenbaum, H. (2017). On the Integration of Space, Time, and Memory. *Neuron*, *95*(5), 1007–

1018. https://doi.org/10.1016/j.neuron.2017.06.036

Eichenbaum, H., Yonelinas, A. P., & Ranganath, C. (2007). The medial temporal lobe and

recognition memory. *Annual Review of Neuroscience*, *30*, 123–152.

https://doi.org/10.1146/annurev.neuro.30.051606.094328

El-Kalliny, M. M., Wittig, J. H., Sheehan, T. C., Sreekumar, V., Inati, S. K., & Zaghloul, K. A. (2019).

Changing temporal context in human temporal lobe promotes memory of distinct

episodes. *Nature Communications*, *10*(1), 203. https://doi.org/10.1038/s41467-018-

08189-4

Estes, W. K. (1955). Statistical theory of distributional phenomena in learning. *Psychological*

Review, *62*(5), 369–377. https://doi.org/10.1037/h0046888

Frankó, E., Insausti, A. M., Artacho-Pérula, E., Insausti, R., & Chavoix, C. (2014). Identification of

the human medial temporal lobe regions on magnetic resonance images: Human Medial

Temporal Lobe Landmarks. *Human Brain Mapping*, *35*(1), 248–256.

https://doi.org/10.1002/hbm.22170

Friedman, W. J. (1993). Memory for the time of past events. *Psychological Bulletin*, *113*(1), 44–

66. https://doi.org/10.1037/0033-2909.113.1.44

Horner, A. J., Bisby, J. A., Bush, D., Lin, W.-J., & Burgess, N. (2015). Evidence for holistic episodic

recollection via hippocampal pattern completion. *Nature Communications*, *6*, 7462.

https://doi.org/10.1038/ncomms8462

Howard, M. W., & Kahana, M. J. (2002). A Distributed Representation of Temporal Context.

Journal of Mathematical Psychology, *46*(3), 269–299.

https://doi.org/10.1006/jmps.2001.1388

557 Hsieh, L.-T., Gruber, M. J., Jenkins, L. J., & Ranganath, C. (2014). Hippocampal activity patterns

558   carry information about objects in temporal context. *Neuron*, *81*(5), 1165–1178.

559   https://doi.org/10.1016/j.neuron.2014.01.015

560 Hunt, R. R. (1995). The subtlety of distinctiveness: What von Restorff really did. *Psychonomic*

561   *Bulletin & Review*, *2*(1), 105–112. https://doi.org/10.3758/BF03214414

562 Jaeger, T. F. (2008). Categorical Data Analysis: Away from ANOVAs (transformation or not) and

563   towards Logit Mixed Models. *Journal of Memory and Language*, *59*(4), 434–446.

564   https://doi.org/10.1016/j.jml.2007.11.007

565 Jenkins, L. J., & Ranganath, C. (2010). Prefrontal and medial temporal lobe activity at encoding

566   predicts temporal context memory. *The Journal of Neuroscience: The Official Journal of*

567   *the Society for Neuroscience*, *30*(46), 15558–15565.

568   https://doi.org/10.1523/JNEUROSCI.1337-10.2010

569 Jenkins, L. J., & Ranganath, C. (2016). Distinct neural mechanisms for remembering when an

570   event occurred. *Hippocampus*, *26*(5), 554–559. https://doi.org/10.1002/hipo.22571

571 Kahana, M. J. (1996). Associative retrieval processes in free recall. *Memory & Cognition*, *24*(1),

572   103–109. https://doi.org/10.3758/BF03197276

573 Kesner, R. P., & Rolls, E. T. (2015). A computational theory of hippocampal function, and tests of

574   the theory: new developments. *Neuroscience and Biobehavioral Reviews*, *48*, 92–147.

575   https://doi.org/10.1016/j.neubiorev.2014.11.009

576 Kraus, B. J., Brandon, M. P., Robinson, R. J., Connerney, M. A., Hasselmo, M. E., & Eichenbaum,

577   H. (2015). During Running in Place, Grid Cells Integrate Elapsed Time and Distance Run.

578   *Neuron*, *88*(3), 578–589. https://doi.org/10.1016/j.neuron.2015.09.031

Kraus, B. J., Robinson, R. J., White, J. A., Eichenbaum, H., & Hasselmo, M. E. (2013).

Hippocampal "time cells": time versus path integration. *Neuron*, *78*(6), 1090–1101.

https://doi.org/10.1016/j.neuron.2013.04.015

Kriegeskorte, N., Mur, M., & Bandettini, P. (2008). Representational Similarity Analysis -

Connecting the Branches of Systems Neuroscience. *Frontiers in Systems Neuroscience*, *2*.

https://doi.org/10.3389/neuro.06.004.2008

Levy, W. B. (1996). A sequence predicting CA3 is a flexible associator that learns and uses

context to solve hippocampal-like tasks. *Hippocampus*, *6*(6), 579–590.

https://doi.org/10.1002/(SICI)1098-1063(1996)6:6<579::AID-HIPO3>3.0.CO;2-C

Libby, L. A., Reagh, Z. M., Bouffard, N. R., Ragland, J. D., & Ranganath, C. (2018). The

Hippocampus Generalizes across Memories that Share Item and Context Information.

Journal of Cognitive Neuroscience, 1–12. https://doi.org/10.1162/jocn_a_01345

Lisman, J. E. (1999). Relating Hippocampal Circuitry to Function. *Neuron*, *22*(2), 233–242.

https://doi.org/10.1016/S0896-6273(00)81085-5

Lisman, J. E., & Jensen, O. (2013). The θ-γ neural code. *Neuron*, *77*(6), 1002–1016.

https://doi.org/10.1016/j.neuron.2013.03.007

Lohnas, L. J., Polyn, S. M., & Kahana, M. J. (2015). Expanding the scope of memory search:

Modeling intralist and interlist effects in free recall. *Psychological Review*, *122*(2), 337–

363. https://doi.org/10.1037/a0039036

MacDonald, C. J., Lepage, K. Q., Eden, U. T., & Eichenbaum, H. (2011). Hippocampal "time cells"

bridge the gap in memory for discontiguous events. *Neuron*, *71*(4), 737–749.

https://doi.org/10.1016/j.neuron.2011.07.012

Mankin, E. A., Diehl, G. W., Sparks, F. T., Leutgeb, S., & Leutgeb, J. K. (2015). Hippocampal CA2

activity patterns change over time to a larger extent than between spatial contexts.

Neuron, *85*(1), 190–201. https://doi.org/10.1016/j.neuron.2014.12.001

Mankin, E. A., Sparks, F. T., Slayyeh, B., Sutherland, R. J., Leutgeb, S., & Leutgeb, J. K. (2012).

Neuronal code for extended time in the hippocampus. *Proceedings of the National*

Academy of Sciences of the United States of America, *109*(47), 19462–19467.

https://doi.org/10.1073/pnas.1214107109

Manning, J. R., Polyn, S. M., Baltuch, G. H., Litt, B., & Kahana, M. J. (2011). Oscillatory patterns

in temporal lobe reveal context reinstatement during memory search. *Proceedings of*

the National Academy of Sciences, *108*(31), 12893–12897.

https://doi.org/10.1073/pnas.1015174108

Mazaika, P., Whitfield-Gabrieli, S., & Cooper, J. C. (2005). *Detection and repair of transient*

artifacts in fMRI data. Poster presented at the Human Brain Mapping.

Montchal, M. E., Reagh, Z. M., & Yassa, M. A. (2019). Precise temporal memories are supported

by the lateral entorhinal cortex in humans. *Nature Neuroscience*, *22*(2), 284.

https://doi.org/10.1038/s41593-018-0303-1

Mumford, J. A., & Poldrack, R. A. (2007). Modeling group fMRI data. *Social Cognitive and*

Affective Neuroscience, *2*(3), 251–257. https://doi.org/10.1093/scan/nsm019

Mumford, J. A., Turner, B. O., Ashby, F. G., & Poldrack, R. A. (2012). Deconvolving BOLD

activation in event-related designs for multivoxel pattern classification analyses.

NeuroImage, *59*(3), 2636–2643. https://doi.org/10.1016/j.neuroimage.2011.08.076

Naya, Y., Chen, H., Yang, C., & Suzuki, W. A. (2017). Contributions of primate prefrontal cortex

and medial temporal lobe to temporal-order memory. *Proceedings of the National*

Academy of Sciences, *114*(51), 13555–13560. https://doi.org/10.1073/pnas.1712711114

Norman, K. A., Detre, G., & Polyn, S. M. (2008). Computational models of episodic memory. In

The Cambridge handbook of computational psychology (pp. 189–225).

https://doi.org/10.1017/CBO9780511816772.011

Palombo, D. J., Di Lascio, J. M., Howard, M. W., & Verfaellie, M. (2019). Medial Temporal Lobe

Amnesia Is Associated with a Deficit in Recovering Temporal Context. *Journal of*

Cognitive Neuroscience, *31*(2), 236–248. https://doi.org/10.1162/jocn_a_01344

Pastalkova, E., Itskov, V., Amarasingham, A., & Buzsáki, G. (2008). Internally generated cell

assembly sequences in the rat hippocampus. *Science (New York, N.Y.)*, *321*(5894), 1322–

1327. https://doi.org/10.1126/science.1159775

Polyn, S. M., Norman, K. A., & Kahana, M. J. (2009). A context maintenance and retrieval model

of organizational processes in free recall. *Psychological Review*, *116*(1), 129–156.

https://doi.org/10.1037/a0014420

Power, J. D., Barnes, K. A., Snyder, A. Z., Schlaggar, B. L., & Petersen, S. E. (2012). Spurious but

systematic correlations in functional connectivity MRI networks arise from subject

motion. *NeuroImage*, *59*(3), 2142–2154.

https://doi.org/10.1016/j.neuroimage.2011.10.018

Ranganath, C. (2019). Time, memory, and the legacy of Howard Eichenbaum. *Hippocampus*,

29(3), 146–161. https://doi.org/10.1002/hipo.23007

Reiff, R., & Scheerer, M. (1959). *Memory and hypnotic age regression; developmental aspects of*

cognitive function explored through hypnosis. New York: International Universities Press.

Ritvo, V. J. H., Turk-Browne, N. B., & Norman, K. A. (2019). Nonmonotonic Plasticity: How

Memory Retrieval Drives Learning. *Trends in Cognitive Sciences*.

https://doi.org/10.1016/j.tics.2019.06.007

Rodriguez, P., & Levy, W. B. (2001). A model of hippocampal activity in trace conditioning:

Where's the trace? *Behavioral Neuroscience*, *115*(6), 1224–1238.

https://doi.org/10.1037/0735-7044.115.6.1224

Rubin, A., Geva, N., Sheintuch, L., & Ziv, Y. (2015). Hippocampal ensemble dynamics timestamp

events in long-term memory. *ELife*, *4*. https://doi.org/10.7554/eLife.12247

Salz, D. M., Tiganj, Z., Khasnabish, S., Kohley, A., Sheehan, D., Howard, M. W., & Eichenbaum, H.

(2016). Time Cells in Hippocampal Area CA3. *The Journal of Neuroscience*, *36*(28), 7476–

7484. https://doi.org/10.1523/JNEUROSCI.0087-16.2016

Schlichting, M. L., & Preston, A. R. (2015). Memory integration: neural mechanisms and

implications for behavior. *Current Opinion in Behavioral Sciences*, *1*, 1–8.

https://doi.org/10.1016/j.cobeha.2014.07.005

Scoville, W. B., & Milner, B. (1957). Loss of recent memory after bilateral hippocampal lesions.

Journal of Neurology, Neurosurgery, and Psychiatry, *20*(1), 11–21.

Sederberg, P. B., Howard, M. W., & Kahana, M. J. (2008). A context-based theory of recency and

contiguity in free recall. *Psychological Review*, *115*(4), 893–912.

https://doi.org/10.1037/a0013396

Sederberg, P. B., Miller, J. F., Howard, M. W., & Kahana, M. J. (2010). The temporal contiguity

effect predicts episodic memory performance. *Memory & Cognition*, *38*(6), 689–699.

https://doi.org/10.3758/MC.38.6.689

Singmann, H., & Kellen, D. (in press). An introduction to mixed models for experimental

psychology. In D. H. Spieler & E. Schumacher, *New Methods in Neuroscience and*

Cognitive Psychology. Psychology Press.

Sugar, J., & Moser, M.-B. (2019). Episodic memory: Neuronal codes for what, where, and when.

Hippocampus, *0*(0). https://doi.org/10.1002/hipo.23132

Tubridy, S., & Davachi, L. (2011). Medial temporal lobe contributions to episodic sequence

encoding. *Cerebral Cortex (New York, N.Y.: 1991)*, *21*(2), 272–280.

https://doi.org/10.1093/cercor/bhq092

Tulving, E. (1983). *Elements of episodic memory*. New York: Oxford University Press.

Vargha-Khadem, F., Gadian, D. G., Watkins, K. E., Connelly, A., Paesschen, W. V., & Mishkin, M.

(1997). Differential Effects of Early Hippocampal Pathology on Episodic and Semantic

Memory. *Science*, *277*(5324), 376–380. https://doi.org/10.1126/science.277.5324.376

Wallenstein, G. V., Eichenbaum, H., & Hasselmo, M. E. (1998). The hippocampus as an

associator of discontiguous events. *Trends in Neurosciences*, *21*(8), 317–323.

Wang, F., & Diana, R. A. (2017). Neural correlates of temporal context retrieval for abstract

scrambled phrases: Reducing narrative and familiarity-based strategies. *Brain Research*,

1655, 128–137. https://doi.org/10.1016/j.brainres.2016.11.017

Wang, Y., Romani, S., Lustig, B., Leonardo, A., & Pastalkova, E. (2015). Theta sequences are

essential for internally generated hippocampal firing fields. *Nature Neuroscience*, *18*(2),

282–288. https://doi.org/10.1038/nn.3904

Yassa, M. A., & Stark, C. E. L. (2011). Pattern separation in the hippocampus. *Trends in*

Neurosciences, *34*(10), 515–525. https://doi.org/10.1016/j.tins.2011.06.006

Yushkevich, P. A., Amaral, R. S. C., Augustinack, J. C., Bender, A. R., Bernstein, J. D., Boccardi, M.,

… Hippocampal Subfields Group (HSG). (2015). Quantitative comparison of 21 protocols

for labeling hippocampal subfields and parahippocampal subregions in in vivo MRI:

towards a harmonized segmentation protocol. *NeuroImage*, *111*, 526–541.

https://doi.org/10.1016/j.neuroimage.2015.01.004

Yushkevich, P. A., Wang, H., Pluta, J., Das, S. R., Craige, C., Avants, B. B., … Mueller, S. (2010).

Nearly Automatic Segmentation of Hippocampal Subfields in In Vivo Focal T2-Weighted

MRI. *NeuroImage*, *53*(4), 1208–1224.

https://doi.org/10.1016/j.neuroimage.2010.06.040

Zacks, J. M., & Swallow, K. M. (2007). EVENT SEGMENTATION. *Current Directions in*

Psychological Science, *16*(2), 80–84. https://doi.org/10.1111/j.1467-8721.2007.00480.x

Ziv, Y., Burns, L. D., Cocker, E. D., Hamel, E. O., Ghosh, K. K., Kitch, L. J., … Schnitzer, M. J. (2013).

Long-term dynamics of CA1 hippocampal place codes. *Nature Neuroscience*, *16*(3), 264–

266. https://doi.org/10.1038/nn.3329