Hippocampal subfields integrate information about past temporal and cognitive contexts

Halle R. Dimsdale-Zucker, Maria E. Montchal, Zachariah M. Reagh, Shao-Fang Wang, Laura A. Libby, Charan Ranganath

Abstract. The hippocampus plays a critical role in supporting episodic memory. Although we know that temporal context is a defining feature of episodic memory, we understand relatively little about how this information may be represented by the hippocampus. Research in rodents has suggested that the hippocampus represents temporal information on an absolute scale or in terms of relative temporal intervals, but cognitive models of memory have argued that temporal context in episodic memory is a consequence of changes in cognitive states and experiences. Here, we combined high-resolution fMRI imaging with voxel pattern similarity analyses to answer the question of how human hippocampal subfields represent retrieved information about cognitive states and the time at which a past event took place. As participants recollected previously presented items, activity patterns in the CA23DG subregion carried information about prior cognitive states, along with coarse-grained information about when the item was previously encountered. These findings are consistent with the idea that CA23DG supports temporal context in episodic memory by encoding an integrated representation of discrete and gradually-changing cognitive states.

Introduction. Converging evidence suggests that the hippocampus plays a critical role in memory for events and their episodic details (Eichenbaum et al., 2007; Scoville & Milner, 1957; Vargha-Khadem et al., 1997). For a memory to be considered episodic, it must be associated with a particular moment in time, or temporal context (Reiff & Scheerer, 1959; Tulving, 1983). Consistent with its integral role in episodic memory,

studies in rodents (Allen et al., 2016; Cai et al., 2016; Kraus et al., 2013, 2015; Salz et

al., 2016), non-human primates (Naya et al., 2017), and humans (Dimsdale-Zucker et

al., 2018; Hsieh et al., 2014; Jenkins & Ranganath, 2010, 2016; Thavabalasingam et al.,

2018; Tubridy & Davachi, 2011) have shown that the hippocampus represents

information about time.

At present, there are at least two major accounts of how this might happen. One

possibility is that the hippocampus maintains a continuously varying representation of

temporal context, possibly via internally generated cell assembly sequences (Buzsáki &

Llinás, 2017; Levy, 1996; Rodriguez & Levy, 2001; Wallenstein et al., 1998). Consistent

with this idea, results from single-unit recording studies in rodents have suggested that

cell populations in the hippocampus can faithfully represent temporal relationships

across both short (Kraus et al., 2013, 2015; MacDonald et al., 2011; Salz et al., 2016)

and longer (Cai et al., 2016; Mankin et al., 2012, 2015; Ziv et al., 2013) intervals.

Another possibly complementary account comes from cognitive theories of episodic

memory that operationalize temporal context in terms of changes in cognitive *states* or

experiences (Estes, 1955; Howard & Kahana, 2002). Although temporal context models

generally assume that representations of temporal context change gradually, these

models also predict that context can abruptly change to reflect one's current cognitive

state (Lohnas et al., 2015; Polyn et al., 2009). The current study was designed to

adjudicate between the possibility that neural representations are sensitive to the actual

passage of time or that they are sensitive to the concomitant fluctuations in mental state

that lead to the perception of time. A third possibility, uniquely observable by using

representational similarity analysis, is that neural representations actually track the

conjunction of slowly drifting temporal features along with continuously varying cognitive

states.

Much of the existing human work into temporal coding has considered the

hippocampus as a single functional unit (DuBrow & Davachi, 2016; Ezzyat & Davachi,

2014; Hsieh et al., 2014; Thavabalasingam et al., 2018; Tubridy & Davachi, 2011).

However, there is reason to think that different hippocampal subfields might make

distinct contributions (Dimsdale-Zucker et al., 2018) in representing cognitive states and

temporal contexts. For instance, some models emphasize the role of area CA1 in

encoding of temporal context (e.g., (Kesner & Rolls, 2015) others emphasize the

importance of the dentate gyrus and CA3 (Levy, 1996; Lisman, 1999; Wallenstein et al.,

1998), and some recent evidence has suggested that area CA2 may be

disproportionately important (Mankin et al., 2015). For the purposes of the current study,

we were interested in characterizing whether the hippocampus represented temporal

contexts as absolute temporal signals or in relation to variations in cognitive states.

Given the extant evidence that multiple subfields can represent temporal contexts, this

leaves open the question of whether different subfields represent temporal information

in different ways.

Here, we used high-resolution functional magnetic resonance imaging (fMRI) to

clarify whether or how the hippocampus encodes temporal and cognitive contexts

during episodic memory retrieval. We also examined contributions of medial temporal

cortical regions, as, for instance, parahippocampal cortex is known to be important for

representing contextual information (Davachi, 2006; Diana et al., 2007). We scanned

participants while they recollected objects that were studied in sequentially-organized

lists, and used voxel pattern similarity (PS) analyses (Dimsdale-Zucker & Ranganath,

2018; Kriegeskorte et al., 2008) to examine whether patterns of activity in hippocampal

subfields at the time of retrieval carried information about temporal and cognitive

contexts instantiated at encoding. In order to adjudicate between context models that

propose slowly drifting signal versus those that predict the possibility of rapid changes

concurrent with modulation of cognitive state, we embedded both 'drifting' and 'shifting'

(DuBrow et al., 2017) manipulations of context in the current paradigm.

Method.

Participants. 32 participants were recruited from the community and were

compensated $50 for their time. This study was approved by the Institutional Review

Board at the University of California, Davis. Four participants were excluded due to

missing behavioral data, two participants were excluded for excessive motion that

prevented tracing of hippocampal subfields, one participant was excluded due to an

experimenter error at data collection that resulted in the incorrect stimuli being seen,

and one participant was excluded because they only had one run of usable data after

discarding motion-contaminated and data-collection contaminated runs. The results

below reflect data from 24 remaining participants (Mage = 22.85 years, SD = 3.06

years, Nfemale = 13). One of these 24 participants was excluded from behavioral

cognitive and temporal context analyses due to partially missing data; since the brain

imaging data for this participant were complete and did not depend on this behavior

being recorded, they were included in all other analyses.

Encoding. Participants viewed eight 36-item lists of still pictures of everyday

objects (e.g., contact lens case, french fries; http://cvcl.mit.edu/mm/uniqueObjects.html;

see Figure 1). Object assignment to list and presentation order of objects within a list

were uniquely randomized for each participant via the Matlab randperm function. To

encourage participants to learn temporal relationships amongst items in a list (Palombo

et al., 2019), each list was presented three times in a mini-block before subjects saw

items from the next list (e.g., 1, 1, 1, 2, 2, 2...8, 8, 8). A label with a list number (e.g.,

"List 1") appeared at the beginning of each list prior to seeing any objects. Mini-blocks

were separated with a self-paced break. Presentation order of objects within a list was

identical for all three list presentations.

Objects remained on the screen for 2.5 seconds (timing and presentation

parameters were controlled via Presentation [Neurobehavioral Systems, Inc., Berkeley,

CA, www.neurobs.com]) while the participant made a yes/no button response to an

orienting question (cognitive context). To manipulate cognitive context, each object was

associated with one of four questions: Would this item fit in a refrigerator?, Would this

item fit in a bathtub?, Would you find this item in a convenience store?, Would you find

this item in a supermarket?. Each of the four questions was presented equally often in

each block, and question/object pairs remained the same across all three list

presentations. Participants were instructed that this was a decision-making task and

that there would be some repetition but to concentrate on doing the task. Participants

were not aware that memory for these questions would be tested later, thus the learning

of question and temporal context information was incidental. Grouping items into lists

was meant to capture slowly drifting cognitive state signals. We reasoned that items

studied near in time would be related by slow, ongoing fluctuations that co-varied across

presentation of the items. A similar temporal grouping strategy has been used

previously to encourage connections between items in this fashion (Palombo et al.,

2019). In addition, to target continuously varying representations, we affiliated each item

with a question. Previous work has shown that interspersing questions throughout the

encoding phase can result in fast, shifting variations in context that are aligned to

changes in cognitive state (Polyn et al., 2009).

Scanned object recognition. While in the MRI scanner, participants saw each

of the 288 old objects from encoding as well as 72 new objects presented one at a time

for 2.5 seconds with a jittered ITI ranging from 2-15 seconds (mean ITI jitter = 6

seconds). Objects were divided into 6 runs (60 trials per run). Object order within a run

was pseudo-randomized such that objects with the same encoding question always had

at least one intervening object (e.g., fridge, convenience store, bathtub, fridge,

supermarket, fridge, etc.) to help minimize encoding context reinstatement biases on PS

results (see Multivariate Results below). Proximity of objects from encoding mini-blocks

(1-8) was not considered in the pseudo-randomization.

While in the scanner, participants were instructed to indicate via button press

whether or not they remembered the object on a 4-point scale: 1=new, 2=familiar (old

but no remembered details), 3=remembered non-temporal details (e.g., the encoding

question, something about the object itself, or an association they made with the

object), 4=remembered temporal detail (e.g., in what list or when they had seen the

object during encoding). Responses for remembered judgments were collapsed into a

single response bin for behavioral and fMRI analyses.

Source memory: Cognitive context. After completing MRI scanning,

participants returned to the lab where they completed a cognitive context source

memory task. In this phase, participants saw all 288 studied objects from encoding and

were asked to indicate which encoding question (fridge/bathtub/convenience

store/grocery store) had been associated with the object. Objects were presented

across four blocks of 72 trials each. Within each block, there were an equal number of

objects from each encoding mini-block (1-8). Presentation order of objects was uniquely

randomized by participant within each source memory block. Objects appeared on the

screen until the participant had made their source memory judgment. There was no

opportunity to guess or skip objects.

Source memory: Temporal context. After completing the cognitive context

source memory test, participants again saw the 288 old objects from encoding and this

time were asked to indicate in which mini-block (1-8) the object had appeared. Objects

were presented centrally on the screen and a number line displaying the numeric

options 1-8 appeared below. Participants were told to use the numbers at the top of the

keypad to make their response. Objects were again divided across four blocks of 72

trials with a different randomization order than was used in the task context source

memory test. Objects remained on the screen until the participant had made their

response. There was no opportunity to guess or skip temporal context judgments.

encoding (unscanned)

encoding question

fridge?

bathtub?

supermarket?

convenienece store?

convenienece store?

bathtub?

supermarket?

supermarket?

bathtub?

supermarket?

fridge?

convenienece store?

list 1 repetition 1   list 1 repetition 2   list 1 repetition 3

list 2 repetition 1   list 2 repetition 2   list 2 repetition 3

list 8 repetition 1   list 8 repetition 2   list 8 repetition 3

object recognition (fMRI)

same cognitive context   different temporal context

pattern similarity analysis

similar temporal context   same temporal context

Figure 1. Task structure. During the encoding phase, each participant studied lists of 36 objects that were each randomly paired with one of four encoding questions ("Would this item fit in a fridge?", "Would this item fit in a bathtub?", "Would you find this item in a supermarket?", "Would you find this item in a convenience store?"). Each list was repeated three times in a row to promote learning of the temporal relationships amongst the items. Objects appeared in the same order and with the same question (cognitive context) across all repetitions. High-resolution functional magnetic resonance brain imaging (fMRI) was used to examine hippocampal activity patterns during a recognition memory test for these objects, allowing us to examine activity pattern similarity as a function of whether pairs of items were encoded within the same or similar temporal contexts (i.e., studied in the same list or temporally proximal lists), and/or the same cognitive context (i.e., associated encoding question).

fMRI acquisition and pre-processing. Scans were acquired on a Siemens

Skyra 3T scanner with a 32 channel head coil. Two sets of structural images were

acquired to enable subfield segmentation: A T1-weighted magnetization prepared rapid

acquisition gradient echo (MP-RAGE) pulse sequence image (1 mm isotropic voxels),

and a high-resolution T2-weighted image (TR = 4200 ms; TE= 93 ms; field of view =

200 mm^2; flip angle = 139°; bandwidth = 199 Hz/pixel; voxel size = 0.4 x 0.4 x 1.9 mm;

58 coronal slices acquired perpendicular to the long-axis of the hippocampus). High-

resolution functional (T2*) images were acquired using a multiband gradient echo planar

(EPI) imaging sequence (TR = 2010 ms; TE = 25 ms; field of view = 216 mm; image

matrix = 144 x 152; flip angle = 79°; bandwidth = 1240 Hx/pixel; partial phase Fourier =

6/8; parallel imaging = GRAPPA acceleration factor 2 with 72 reference lines; multiband

factor = 2; 52 oblique axial slices acquired parallel to the long-axis of the hippocampus

slices; voxel size = 1.5 mm isotropic).

SPM8 (http://www.fil.ion.ucl.ac.uk/spm/) was used for image pre-processing.

Functional EPI images were realigned to the first image and resliced. No slice timing

correction was performed due to the acquisition of multiple simultaneous slices with the

multiband sequence (capabilities to handle multiband timing do not exist in SPM8). Co-

registration between the native-space ROIs defined in T2 space and the functional

images was done with SPM's Coregister: Estimate and Reslice procedure. This

procedure uses a linear normalized mutual information cost-function between a

reference (mean functional) image and source (T2) image to compute and apply a

voxel-by-voxel affine transformation matrix. This transformation matrix was then applied

to the subfield ROIs that had been defined in T2 space (see *ROI segmentation*) to bring

them into register with the functional images. The T1 image was co-registered to the

mean EPI. Then, nonlinear spatial normalization parameters were derived by

segmenting the coregistered T1 image. Quality assurance included identifying suspect

timepoints via custom code (https://github.com/memobc/memolab-fmri-qa) defined as

time-points in excess of 0.5 mm frame displacement (based on (Power et al., 2012) or

1.5% global mean signal change (based on ARTRepair recommendations, (Mazaika et

al., 2005)). Runs were excluded if the frame displacement exceeded the voxel size. As

reported earlier, three participants were excluded for motion in excess of these

thresholds; of the 24 subjects included in the analyses, 9 had runs excluded based on

these thresholds (mean number of removed runs = 0.92, SD = 1.38; ranging from 0-4

runs).

Pattern similarity analyses. PS analyses were conducted on beta maps

generated from unsmoothed data in native subject space. Following the least squares

separate procedure described by Mumford (2012), single trial models were generated to

estimate the unique beta map for every trial in a run (N=60). Within each single trial

model, the first regressor modeled the trial of interest with a stick function, the second

regressor modeled all other trials in that run, six regressors were used to capture

motion, and any additional spike regressors as identified by our QA scripts were used to

capture additional residual variance. Voxel-wise patterns of hemodynamic activity were

separately extracted for each ROI from the single trial beta images. To ensure robust

ability to detect differences in PS, we required temporal signal-to-noise ratios (TSNR) in

a region to be above 20 (approximately 2 standard deviations below the mean global

TSNR of 50.4). This required the removal of entorhinal cortex and its subregions (mean

TSNR ranged between 10-20), despite its compelling role in the representation of

temporal context (Bellmund et al., 2019; Montchal et al., 2019)

Within each ROI, correlations (Pearson's r) were computed between these trial-

wise betas to yield a trial-by-trial correlation matrix that related each voxel's signal on a

trial to all other trials across all runs. We restricted comparisons to those trials for which

participants made a correct "remember" response (during MRI scanning). Trials were

sorted on the basis of encoding context (cognitive, temporal), however source memory

for these contexts was not taken into consideration. Correlation values were z-

transformed prior to statistical analysis. Statistical analyses tested for differences in

correlations between trial pairs on the basis of encoding context (cognitive context:

same vs. different encoding question; temporal context: same vs. different encoding list,

or similar vs. different list half). To more accurately characterize both within- and across-

subject error variance (Baayen et al., 2008; Clark, 1973; Dixon, 2008; Jaeger, 2008;

Mumford & Poldrack, 2007; Singmann & Kellen, in press), we implemented a mixed-

modelling approach to evaluate statistical significance with the *lme4* packing in R (Bates

et al., 2014); for a similar approach, see (Dimsdale-Zucker et al., 2018). We used an

alpha of $p < 0.05$ and performed permutation testing for all of the pattern similarity

results reported in the manuscript. Only between-run correlations were used to

maximize the number of possible trial pairs without mixing within- and between-run

correlations. Trial pairs of interest were extracted from these trial-by-trial correlation

matrices.

All relevant code (https://github.com/hallez/tempcon_pub), a reproducible

compute environment (https://doi.org/10.24433/CO.0129473.v1), and relevant data

(https://osf.io/qfcjg/) are available online.

ROI definition. Hippocampal subfields were defined following the procedure

reported in (Dimsdale-Zucker et al., 2018; see Figure 2). In short, the ASHS automated

segmentation procedure was used to delineate subfields in subject-native space

(Yushkevich et al., 2010). We restricted our analyses to hippocampal body where

discriminating subfields is most agreed upon. Medial temporal lobe cortical regions were

manually-traced (see the Libby and Ranganath protocol in (Yushkevich et al., 2015)). In

accordance with prior findings suggesting functional distinctions between anterior and

posterior parahippocampal gyrus (Aminoff et al., 2007; Baldassano et al., 2013, 2016),

we subdivided parahippocampal cortex one slice posterior to the wing of the ambient

cistern (Frankó et al., 2014).

anterior ⟶ posterior

Figure 2. Top: Segmentations of hippocampal subfields (Cornu Ammonis [CA] 1, a
combined CA2/3 and dentate gyrus [CA23DG] region, and subiculum [SUB]) as well as
cortical medial temporal lobe regions (perirhinal cortex [PRC], anterior parahippocampal
cortex [aPHC], and posterior parahippocampal cortex [pPHC]). Segmentations are
depicted for a representative subject in the coronal plane of a T2 image. Slices move
from anterior to posterior from left-to-right. Bottom: Segmentations following reslicing to
functional (EPI) space displayed on a mean functional image from the same subject.
262
Results.

Behavioral results. During MRI scanning participants performed a recognition

memory test requiring judgments as to whether each item was recognized on the basis

of recollection of specific item and source information from the study phase (see

Method). Pattern similarity analyses were restricted to correctly remembered items. On

average, this yielded 200 trials (SD = 51.9; minimum trials = 71; maximum trials = 282)

from which we constructed all possible trial pairs and then compared activity patterns

(see fMRI Results).

Correct remember judgments were the most common response (mean hit rate =

0.69, SD = 0.19), and, for these items, participants showed high accuracy at

remembering the associated encoding task context (mean hit rate = 0.71, SD = 0.12).

Memory for the exact ("same") temporal context (list 1-8) was poor (mean hit rate =

0.18, SD = 0.03), but, we reasoned that, even if participants were unable to recall the

exact list identity, they might have memory for the "similar" temporal context associated

with each item. We therefore re-scored each trial according to whether the participant

could accurately determine whether it was presented in the "similar" (first half (lists 1-4)

or the second half (lists 5-8)) versus "different" (across halves, i.e., list 1/list5, list 1/list 6,

etc.) temporal context of the encoding phase. On this metric, memory for similar

temporal context (mean hit rate for list half = 0.59, SD = 0.04) was reliably greater than

chance of 0.5, t(22) = 8.74, *p* < 0.001. Thus, although participants did not have access

to the precise list in which an item had been studied, they were able to retrieve

information about the item's temporal context at a coarse level.

fMRI results: Hippocampal Subfields We next tested whether activity patterns

in the hippocampal subfields (CA1, CA23DG, subiculum) during memory retrieval

carried information about the context in which the item was previously encountered.

Specifically, we examined voxel PS during retrieval as a function of whether pairs of

trials shared a temporal (defined either as same list vs. different list [*same* temporal

context] or as same half of the experiment vs. different halves of the experiment [*similar*

temporal context]) and/or cognitive (i.e., same encoding task vs. different encoding task)

context when the items were originally learned.

We first considered when items came from the "same" temporal encoding context

(same vs. different list). No hippocampal subfield varied its PS at retrieval with respect

to the same temporal context (all X^2 < 0.5, all *p*s > 0.40). In CA23DG, we found that PS

was higher during retrieval of items associated with the same cognitive context

compared to items associated with different cognitive contexts ($X^2(1)$ = 4.63, $p^{perm1000}$ =

0.031). No other subfield varied its PS at retrieval with respect to cognitive context alone

(all X^2 < 0.3, all *p*s > 0.55) nor the combination of temporal and cognitive context (all X^2

< 0.80, all *p*s > 0.30).

We next considered whether PS might depend on whether items shared a

"similar" temporal context at encoding (same vs. different half of the encoding phase).

This was intended to give us a coarser measure of temporal context. The choice of list

half was informed by the fact that participants were behaviorally able to discriminate

coarse temporal context reliably greater than chance. PS levels did not vary by similar

temporal context alone ($X^2(1) = 0.08$, $p^{perm1000} = 0.815$). Thus, PS levels were not

modulated by same or similar temporal context alone. In CA23DG, we found that PS

was higher during retrieval of items that were associated with the same cognitive

context than for items that were associated with different cognitive contexts ($X^2(1) =$

4.68, $p^{perm1000} = 0.037$; see Figure 3). Thus, irrespective of how we defined temporal

context (same, similar), PS in CA23DG was higher for items that were associated with

the same cognitive context. This effect was qualified by a significant similar temporal by

cognitive context interaction ($X^2(1) = 8.11$, $p^{perm1000} = 0.008$), such that the effect of

cognitive context was larger for items that were in similar temporal contexts (same half)

than for items that were in different temporal contexts (different half) particularly when

these items shared the same cognitive context.

In CA1, PS levels did not vary by similar temporal context ($X^2(1) = 2.42$, $p^{perm1000}$

$= 0.122$), cognitive context ($X^2(1) = 0.08$, $p^{perm1000} = 0.757$), nor when we considered

both temporal and cognitive context ($X^2(1) = 0.84$, $p^{perm1000} = 0.329$). In subiculum, PS

levels did not vary by similar temporal context ($X^2(1) = 0.11$, $p^{perm1000} = 0.751$) or

cognitive context ($X^2(1) = 0.27$, $p^{perm1000} = 0.622$), however, we found that PS was

marginally higher for items that were studied relative to the same question but studied in

different list halves as compared to all other conditions ($X^2(1) = 2.91$, $p^{perm1000} = 0.082$).

Figure 3. Pattern similarity values in CA23DG during memory retrieval carry information about temporal and cognitive encoding contexts. A. Mean pattern similarity scores, with scatter of individual subject observations for the combination of different encoding contexts. B. Differences between same/different list half ("similar" temporal context), same/different question (cognitive context), and the interaction of temporal and cognitive context ([same question, same list half – different question, same list half] – [same question, different list half – different question, different list half). C. Permuted chi-square values to determine significance of cognitive-by-temporal interaction.

fMRI Results: Medial Temporal Lobe (MTL) Neocortical Areas

Our next analyses investigated activity in MTL regions outside of the hippocampus. Previous work has suggested that regions in parahippocampal cortex (PHC) should process information about cognitive context (Diana et al., 2012, 2013; F. Wang & Diana, 2017). We first considered items from the same temporal encoding context (same versus different list). In aPHC, we found that PS with higher during retrieval of items associated with the same temporal encoding context (same list) as compared to items associated with different temporal contexts ($X^2(1) = 4.79$, $p^{perm1000} =$

0.024, Supplemental Figure 1). No other neocortical regions varied their PS with respect

to the same temporal context (all $X^2 < 2.90$, all ps > 0.06). In aPHC, we also found that

PS was higher during retrieval of items associated with the same cognitive context

compared to items associated with different cognitive contexts ($X^2(1) = 5.92$, $p^{perm1000} =$

0.012, Supplemental Figure 2). There was a trend in the same direction (greater PS for

same versus different cognitive context) in PRC ($X^2(1) = 3.53$, $p^{perm1000} = 0.054$). PS in

pPHC did not vary with respect to cognitive context alone ($X^2(1) = 0.64$, $p^{perm1000} =$

0.44). In pPHC there was an interaction such that PS was greater for items that shared

a temporal context as well as a cognitive context but was lower when these items did

not share a cognitive context ($X^2(1) = 9.44$, $p^{perm1000} = 0.004$, Figure 4). No other regions

modulated their PS based on the combination of same temporal and cognitive contexts

(all $X^2 < 1$, all ps > 0.3).

Supplemental Figure 1. Pattern similarity values in aPHC during memory retrieval carry information about the same temporal encoding context. A. Mean pattern similarity scores, with scatter of individual subject observations for same/different encoding context (list). B. Differences between same/different list (temporal context), same/different question (cognitive context), and the interaction of temporal and cognitive context ([same question, same list – different question, same list] – [same question, different list – different question, different list]). C. Permuted chi-square values to determine significance of same temporal context.

Supplemental Figure 2. Pattern similarity values in aPHC during memory retrieval
carry information about the cognitive encoding context. A. Mean pattern similarity
scores, with scatter of individual subject observations for same/different encoding
question (cognitive context). B. Differences between same/different list (temporal
context), same/different question (cognitive context), and the interaction of temporal and
cognitive context ([same question, same list – different question, same list] – [same
question, different list – different question, different list]). C. Permuted chi-square values
to determine significance of cognitive context.

Figure 4. Pattern similarity values in pPHC during memory retrieval carry information about temporal and cognitive encoding contexts. A. Mean pattern similarities scores, with scatter of individual subject observations for the combination of different encoding contexts. B. Differences between same/different list (temporal context), same/different question (cognitive context), and the interaction of temporal and cognitive context ([same question, same list – different question, same list] – [same question, different list – different question, different list]). C. Permuted chi-square values to determine significance of cognitive-by-temporal interaction.

We next considered whether PS in MTL neocortical areas might depend on whether items shared a similar temporal context at encoding. In aPHC, we found that PS was higher during retrieval of items associated with a different temporal context as compared to items with similar temporal encoding contexts ($X^2(1) = 7.39$, $p^{perm1000} = 0.003$, Supplemental Figure 3). No other neocortical regions varied their PS with respect to similar temporal context (all $X^2 < 2.2$, all ps > 0.13). In aPHC, we also found that PS was higher during retrieval of items associated with the same cognitive context compared to items associated with different cognitive contexts ($X^2(1) = 5.83$, $p^{perm1000} =$

0.013, Supplemental Figure 4). There was a trend in the same direction (greater PS for

same versus different cognitive context) in PRC ($X^2(1) = 3.55$, $p^{perm1000} = 0.051$). PS in

pPHC did not vary with respect to cognitive context alone ($X^2(1) = 0.68$, $p^{perm1000} =$

0.41). In pPHC there was an interaction such that the effect of cognitive context was

larger for items that were in similar temporal contexts (same half) than for items that

were in different temporal contexts (different half) particularly when these items shared

the same cognitive context ($X^2(1) = 4.67$, $p^{perm1000} = 0.029$, Figure 5). No other regions

modulated their PS based on the combination of similar temporal and cognitive contexts

(all $X^2 < 1.5$, all ps > 0.20).

403
Supplemental Figure 3. Pattern similarity values in aPHC during memory retrieval
carry information about the similar temporal encoding context. A. Mean pattern similarity
scores, with scatter of individual subject observations for similar temporal contexts (list
half). Although pattern similarity values were very close in magnitude, there was a small

but reliable effect such that pattern similarity values for items studied in different list
halves were greater than for items in the same half of lists. B. Differences between
same/different list half (temporal context), same/different question (cognitive context),
and the interaction of temporal and cognitive context ([same question, same list half –
different question, same list half] – [same question, different list half – different question,
different list half]). C. Permuted chi-square values to determine significance of similar
temporal context.
415

416
Supplemental Figure 4. Pattern similarity values in aPHC during memory retrieval
carry information about the cognitive encoding context. A. Mean pattern similarity
scores, with scatter of individual subject observations for same/different encoding
question (cognitive context). B. Differences between same/different list half (temporal
context), same/different question (cognitive context), and the interaction of temporal and
cognitive context ([same question, same list half – different question, same list half] –
[same question, different list half – different question, different list half]). C. Permuted
chi-square values to determine significance of cognitive context.
425

Figure 5. Pattern similarity values in pPHC during memory retrieval carry information about similar temporal and cognitive encoding contexts. A. Mean pattern similarities scores, with scatter of individual subject observations for the combination of different encoding contexts. B. Differences between same/different list half (temporal context), same/different question (cognitive context), and the interaction of temporal and cognitive context ([same question, same list half – different question, same list half] – [same question, different list half – different question, different list half]). C. Permuted chi-square values to determine significance of cognitive-by-similar temporal interaction.

Discussion.

The goal of the present study was to test the extent to which the hippocampus represents absolute temporal information and information about particular cognitive states during recollection of past events. Although cognitive states typically fluctuate over time in a continuous manner, the design of our experiment allowed us to examine the influence of these two aspects of context separately. We found that, during recollection of a study item, CA23DG activity patterns carried information about the cognitive context associated with that item during the study phase. Additionally,

cognitive context information evident in CA23DG activity patterns varied over a coarse

timescale, such that pattern similarity was highest for pairs of items that were

associated with similar temporal and cognitive contexts. Collectively, these findings

demonstrate that the hippocampus represents information about past events in a

manner that is consistent with temporal context models (Howard et al., 2014; Howard &

Kahana, 2002; Manning, 2019; Norman et al., 2008; Polyn et al., 2009; Ranganath,

2019; Sederberg et al., 2008; Shankar & Howard, 2010, 2012).

We have long understood that context is central for recall (Clewett & Davachi,

2017; Davachi & DuBrow, 2015; Zacks & Swallow, 2007) and recollection-based

recognition (Eichenbaum et al., 2007), but we do not yet understand how *temporal*

context may be encoded in the brain. These representations of temporal and cognitive

state contexts seem to rely on the hippocampus (Eichenbaum, 2017; Ranganath, 2019).

In the hippocampus, one candidate mechanism is the coordinated firing of self-

organized cell assemblies, or time cells (Lisman & Jensen, 2013; Y. Wang et al., 2015).

These cells can track how long an animal has been running on a treadmill where

distance, speed, and duration of run time can be decorrelated (Kraus et al., 2013, 2015;

Salz et al., 2016), code for meaningful gaps or pauses (MacDonald et al., 2011), and

represent ordered sequences and experiences even during rest periods (Pastalkova et

al., 2008). Hippocampal ensembles also drift in their representations of space when

recorded across days, thus it seems that they can encode both fine and coarse

temporal information (Mankin et al., 2012, 2015; Rubin et al., 2015; Ziv et al., 2013).

These findings provide evidence for the idea that hippocampal neurons may encode

information about temporal intervals or the passage of time. That said, available

evidence indicates that hippocampal time cells are highly sensitive to changes in task

context. In one such demonstration, immobilized rats learned to maintain information

about specific odors across a delay period (MacDonald et al., 2013). Results showed

that different cell assemblies encoded temporal intervals across the delay period

depending on the odor that was to be maintained. In other words, changes in the task

context led to substantial changes in the neural ensembles that encoded temporal

information during the task.

In the present study, we found evidence for the idea that information about

cognitive states (i.e., specific task contexts) was carried in hippocampal activity patterns

during recollection, and that these patterns also carried relatively coarse-grained

information about the temporal context in which the recollected item was initially

encountered (see also (DuBrow et al., 2017) for evidence that contexts can drift slowly).

This is consistent with the scale of temporal information participants had access to

behaviorally; they were poor at retrieving the exact list an item had been in but had

access to information about in which half of the study lists it had occurred. These

findings are generally in line with what would be predicted by cognitive models of the

representation of temporal context in episodic memory. Initial theories operationalized

temporal context as random fluctuations in cognitive states over time (Estes, 1955), and

subsequent theories have incorporated the assumption that temporal context also

reflects a time-weighted average of recently processed items and experiences (Howard

& Kahana, 2002; Norman et al., 2008; Sederberg et al., 2008). These models would

predict that activity patterns during memory retrieval should reflect information about the

temporal context associated with each study item (e.g., Manning et al., 2011; Deuker et

al., 2016; Nielson et al., 2015). The Context Maintenance and Retrieval (CMR) model

goes farther by incorporating information about the current task or cognitive state into

the temporal context representation. CMR predicts that if there are abrupt changes in

one's cognitive state (e.g., a change in the task that one is performing), items that are

temporally proximal can actually have distinct contextual associations (Polyn et al.,

2009). Thus, the CMR model predicts that, during memory retrieval, reinstatement of

temporal context should reflect a conjunction of task-related information and information

that reflects elapsed time, similar to what was observed in CA23DG and pPHC. Though

CMR most explicitly incorporates semantic relationships into the temporal context

model, we suggest that contextual associations associated with task or cognitive states

likely tap into a similar mechanism. Moreover, the model suggests that changing tasks

during encoding would break up the temporal context representation during encoding of

each list. This prediction is consistent with the fact that we did not see evidence of high

pattern similarity across items within the same list, and instead only saw representation

of temporal information across coarser timescales.

At a broader level, our findings converge with results from a number of recent

studies showing that hippocampal activity patterns carry information that generalizes

across events that share common elements (Horner et al., 2015; Schlichting & Preston,

2015). Here, we found that activity patterns in the CA23DG subregion generalize across

items that shared both temporal and task context. Other findings, however, suggest that

hippocampal representations can amplify differences between overlapping experiences

(Chanales et al., 2017; Libby et al., 2018; Ritvo et al., 2019; Yassa & Stark, 2011). One

potential cause of the divergence of results in CA23DG across studies is that human

functional imaging aggregates patterns across CA3 and DG due to current limitations of

fMRI (Chen et al., 2011; Copara et al., 2014; Dimsdale-Zucker et al., 2018; Ekstrom et

al., 2009; LaRocque et al., 2013; Stokes et al., 2015) CA3 and DG have separately

been tied to pattern completion (Guzowski et al., 2004; Kesner & Rolls, 2015; Treves &

Rolls, 1994; Vazdarjanova & Guzowski, 2004; Yassa & Stark, 2011) and separation

(Hasselmo & Wyble, 1997; Kesner & Rolls, 2015; Redish, 1999; Yassa & Stark, 2011).

Thus, it may be the case that by averaging their activity patterns together, we are

blurring the true underlying signal. Though this methodological caveat could explain

some patterns of results, we suggest that differences in the cognitive demands of the

tasks used may also be relevant to consider. A further complication is that there may be

divergence in function along the proximal/distal axis of CA3 itself suggesting that even

CA3 alone has the computational circuitry to perform both pattern separation and

completion operations (Lee et al., 2020).

In one recent study, for instance, we found that CA23DG activity patterns during

memory retrieval were more different for across pairs of items that were associated with

the same episodic context (i.e., objects seen within the same movie) than across pairs

of items that were associated with different contexts. In addition, a recent report using

ultra-high resolution fMRI that could isolate CA3 from DG found evidence for greater

reinstatement of encoding activity patterns in CA3 when retrieving items associated with

coherent, as compared to partially-overlapping, events (Grande et al., 2019). The

findings of Dimsdale-Zucker et al. (2018), considered alongside the present results,

raise an important question: When does CA23DG assign similar or distinct

representations to overlapping events?

To answer this question, it may be informative to consider the conflicting role of

shared context in facilitating inter-item relationships (Sederberg et al., 2010) while

diminishing item distinctiveness (El-Kalliny et al., 2019). During recognition memory

tests, people are generally more likely to recollect events that were distinctive than

events that were overwhelmingly similar to one another (Hunt, 1995). If CA23DG

represents information about one's cognitive state during an event, then we would

expect that this area would be most likely to support successful recollection when those

representations are distinctive. In the present study, changes in the encoding task

encouraged participants to shift cognitive states abruptly across items within a list. By

attending to the task context, a participant could form distinctive memories for the

different items that were in the same list. In our previous study (Dimsdale-Zucker et al.,

2018), however, participants studied lists of items presented in virtual reality videos that

depicted navigation through two homes. Thus, the environmental context was

overwhelmingly similar across items in the same list, and the cognitive context was not

explicitly controlled (i.e., cognitive context likely tracked with environments and the

passage of time). To successfully encode items from the study phase, participants

needed to form representations that highlighted the distinctive aspects of each item in

the list in order to overcome contextual interference at the time of retrieval (Park, Arndt,

& Reder, 2006). We therefore propose that, by binding information about items with

information about cognitive contexts, CA23DG can support successful retrieval of

overlapping memories that would otherwise be difficult to disambiguate (Yassa &

Reagh, 2013).

Our findings also highlight the relative paucity of direct access to memory for

temporal context at retrieval. Behavioral measures of memory for temporal context

show clustered recall; that is, items studied nearer in time to one another are more likely

to be recalled close together (Kahana, 1996). These findings suggest that, during

episodic memory retrieval, people may be mentally transported back to a past cognitive

state (Manning et al., 2011; Tulving, 1983). Yet, when people are explicitly asked about

temporal order information, they often cannot produce reliable estimates (Jenkins &

Ranganath, 2010). In the present study, we also found that participants had little explicit

access to an item's temporal encoding context. When asked to choose in which of eight

lists an item had been studied, participants were essentially at chance. This is not

surprising because temporal context models only suggest that memories for temporally

proximal events should be associated with similar context representations, but retrieval

of context information would not automatically enable a person to determine the exact

time at which a previous item was encountered. There is considerable evidence to

suggest that people rely on heuristics strategies in order to roughly reconstruct the time

at which an event took place (Friedman, 1993). In our study, this might have been more

challenging because, as we have stated above, changes in cognitive context within a

list most likely disrupted the continuity of temporal context representations (for a related

finding, see (Polyn et al., 2009)).

In addition to the hippocampus, medial temporal lobe cortical regions have also

been implicated in representing context. A substantial body of work has suggested a

particular role for parahippocampal cortex in supporting representations of context

(Davachi, 2006; Diana et al., 2007, 2013; Hsieh et al., 2014; Tubridy & Davachi, 2011;

F. Wang & Diana, 2017). In line with these findings, we also saw that parahippocampal

cortex carried information about cognitive and temporal contexts as well as their

conjunction both for same and similar temporal contexts. Recent work has also

suggested a role for lateral entorhinal cortex in absolute representations of time

(Bellmund et al., 2019; Montchal et al., 2019; Sugar & Moser, 2019). Unfortunately, we

could not assess whether lateral entorhinal cortex represented elapsed time because

our scanning protocol was not optimized for entorhinal cortex coverage, and the

temporal signal-to-noise ratio was therefore insufficient. Thus, it is possible that in this

task where participants had access to both a sense of ongoing time and fluctuating

cognitive states, hippocampus and entorhinal cortex could play complementary roles.

Taken together, we have shown that activity patterns in the CA23DG region of

the human hippocampus reflected an integrated representation of cognitive and coarse

temporal contexts. This finding can help explain how we represent continuously

unfolding episodes in a changing world. Outside of the laboratory, we are constantly

multitasking between competing goals and responsibilities. The hippocampus, and,

specifically CA23DG, may allow us to differentiate between experiences that are

associated with different tasks while preserving the temporal flow between experiences.

598
599

References

Allen, T. A., Salz, D. M., McKenzie, S., & Fortin, N. J. (2016). Nonspatial Sequence Coding in CA1

Neurons. *The Journal of Neuroscience*, *36*(5), 1547–1563.

https://doi.org/10.1523/JNEUROSCI.2874-15.2016

Aminoff, E., Gronau, N., & Bar, M. (2007). The parahippocampal cortex mediates spatial and

nonspatial associations. *Cerebral Cortex (New York, N.Y.: 1991)*, *17*(7), 1493–1503.

https://doi.org/10.1093/cercor/bhl078

Baayen, R. H., Davidson, D. J., & Bates, D. M. (2008). Mixed-effects modeling with crossed

random effects for subjects and items. *Journal of Memory and Language*, *59*(4), 390–

412. https://doi.org/10.1016/j.jml.2007.12.005

Baldassano, C., Beck, D. M., & Fei-Fei, L. (2013). Differential connectivity within the

Parahippocampal Place Area. *NeuroImage*, *75*, 228–237.

https://doi.org/10.1016/j.neuroimage.2013.02.073

Baldassano, C., Esteva, A., Fei-Fei, L., & Beck, D. M. (2016). Two Distinct Scene-Processing

Networks Connecting Vision and Memory. *ENeuro*, *3*(5), ENEURO.0178-16.2016.

https://doi.org/10.1523/ENEURO.0178-16.2016

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2014). Fitting Linear Mixed-Effects Models using

lme4. *10.18637/Jss.V067.I01*, 1–48.

Bellmund, J. L., Deuker, L., & Doeller, C. F. (2019). Mapping sequence structure in the human

lateral entorhinal cortex. *ELife*, *8*, e45333. https://doi.org/10.7554/eLife.45333

Buzsáki, G., & Llinás, R. (2017). Space and time in the brain. *Science (New York, N.Y.)*, *358*(6362),

482–485. https://doi.org/10.1126/science.aan8869

Cai, D. J., Aharoni, D., Shuman, T., Shobe, J., Biane, J., Song, W., Wei, B., Veshkini, M., La-Vu, M.,

Lou, J., Flores, S. E., Kim, I., Sano, Y., Zhou, M., Baumgaertel, K., Lavi, A., Kamata, M.,

Tuszynski, M., Mayford, M., … Silva, A. J. (2016). A shared neural ensemble links distinct

contextual memories encoded close in time. *Nature*, *534*(7605), 115–118.

https://doi.org/10.1038/nature17955

Chanales, A. J. H., Oza, A., Favila, S. E., & Kuhl, B. A. (2017). Overlap among Spatial Memories

Triggers Repulsion of Hippocampal Representations. *Current Biology: CB*, *27*(15), 2307-

2317.e5. https://doi.org/10.1016/j.cub.2017.06.057

Chen, J., Olsen, R. K., Preston, A. R., Glover, G. H., & Wagner, A. D. (2011). Associative retrieval

processes in the human medial temporal lobe: Hippocampal retrieval success and CA1

mismatch detection. *Learning & Memory*, *18*(8), 523–528.

https://doi.org/10.1101/lm.2135211

Clark, H. H. (1973). The language-as-fixed-effect fallacy: A critique of language statistics in

psychological research. *Journal of Verbal Learning and Verbal Behavior*, *12*(4), 335–359.

https://doi.org/10.1016/S0022-5371(73)80014-3

Clewett, D., & Davachi, L. (2017). The ebb and flow of experience determines the temporal

structure of memory. *Current Opinion in Behavioral Sciences*, *17*, 186–193.

https://doi.org/10.1016/j.cobeha.2017.08.013

Copara, M. S., Hassan, A. S., Kyle, C. T., Libby, L. A., Ranganath, C., & Ekstrom, A. D. (2014).

Complementary Roles of Human Hippocampal Subregions during Retrieval of

Spatiotemporal Context. *The Journal of Neuroscience*, *34*(20), 6834–6842.

https://doi.org/10.1523/JNEUROSCI.5341-13.2014

Davachi, L. (2006). Item, context and relational episodic encoding in humans. *Current Opinion in*

Neurobiology, *16*(6), 693–700. https://doi.org/10.1016/j.conb.2006.10.012

Davachi, L., & DuBrow, S. (2015). How the hippocampus preserves order: The role of prediction

and context. *Trends in Cognitive Sciences*, *19*(2), 92–99.

https://doi.org/10.1016/j.tics.2014.12.004

Diana, R. A., Yonelinas, A. P., & Ranganath, C. (2007). Imaging recollection and familiarity in the

medial temporal lobe: A three-component model. *Trends in Cognitive Sciences*, *11*(9),

379–386. https://doi.org/10.1016/j.tics.2007.08.001

Diana, R. A., Yonelinas, A. P., & Ranganath, C. (2012). Adaptation to cognitive context and item

information in the medial temporal lobes. *Neuropsychologia*, *50*(13), 3062–3069.

https://doi.org/10.1016/j.neuropsychologia.2012.07.035

Diana, R. A., Yonelinas, A. P., & Ranganath, C. (2013). Parahippocampal cortex activation during

context reinstatement predicts item recollection. *Journal of Experimental Psychology.*

General, *142*(4), 1287–1297. https://doi.org/10.1037/a0034029

Dimsdale-Zucker, H. R., & Ranganath, C. (2018). Representational Similarity Analyses: A

Practical Guide for Functional MRI Applications. In D. Manahan-Vaughan (Ed.),

Handbook of in Vivo Neural Plasticity Techniques. Elsevier.

Dimsdale-Zucker, H. R., Ritchey, M., Ekstrom, A. D., Yonelinas, A. P., & Ranganath, C. (2018).

CA1 and CA3 differentially support spontaneous retrieval of episodic contexts within

human hippocampal subfields. *Nature Communications*, *9*(1), 294.

https://doi.org/10.1038/s41467-017-02752-1

Dixon, P. (2008). Models of accuracy in repeated-measures designs. *Journal of Memory and*

Language, *59*(4), 447–456. https://doi.org/10.1016/j.jml.2007.11.004

DuBrow, S., & Davachi, L. (2016). Temporal binding within and across events. *Neurobiology of*

Learning and Memory, *134 Pt A*, 107–114. https://doi.org/10.1016/j.nlm.2016.07.011

DuBrow, S., Rouhani, N., Niv, Y., & Norman, K. A. (2017). Does mental context drift or shift?

Current Opinion in Behavioral Sciences, *17*(Supplement C), 141–146.

https://doi.org/10.1016/j.cobeha.2017.08.003

Eichenbaum, H. (2017). On the Integration of Space, Time, and Memory. *Neuron*, *95*(5), 1007–

1018. https://doi.org/10.1016/j.neuron.2017.06.036

Eichenbaum, H., Yonelinas, A. P., & Ranganath, C. (2007). The medial temporal lobe and

recognition memory. *Annual Review of Neuroscience*, *30*, 123–152.

https://doi.org/10.1146/annurev.neuro.30.051606.094328

Ekstrom, A. D., Bazih, A. J., Suthana, N. A., Al-Hakim, R., Ogura, K., Zeineh, M., Burggren, A. C., &

Bookheimer, S. Y. (2009). Advances in high-resolution imaging and computational

unfolding of the human hippocampus. *NeuroImage*, *47*(1), 42–49.

https://doi.org/10.1016/j.neuroimage.2009.03.017

El-Kalliny, M. M., Wittig, J. H., Sheehan, T. C., Sreekumar, V., Inati, S. K., & Zaghloul, K. A. (2019).

Changing temporal context in human temporal lobe promotes memory of distinct

episodes. *Nature Communications*, *10*(1), 203. https://doi.org/10.1038/s41467-018-

08189-4

Estes, W. K. (1955). Statistical theory of distributional phenomena in learning. *Psychological*

Review, *62*(5), 369–377. https://doi.org/10.1037/h0046888

Ezzyat, Y., & Davachi, L. (2014). Similarity Breeds Proximity: Pattern Similarity within and across

Contexts Is Related to Later Mnemonic Judgments of Temporal Proximity. *Neuron*,

81(5), 1179–1189. https://doi.org/10.1016/j.neuron.2014.01.042

Frankó, E., Insausti, A. M., Artacho-Pérula, E., Insausti, R., & Chavoix, C. (2014). Identification of

the human medial temporal lobe regions on magnetic resonance images: Human Medial

Temporal Lobe Landmarks. *Human Brain Mapping*, *35*(1), 248–256.

https://doi.org/10.1002/hbm.22170

Friedman, W. J. (1993). Memory for the time of past events. *Psychological Bulletin*, *113*(1), 44–

66. https://doi.org/10.1037/0033-2909.113.1.44

Grande, X., Berron, D., Horner, A. J., Bisby, J. A., Düzel, E., & Burgess, N. (2019). Holistic

Recollection via Pattern Completion Involves Hippocampal Subfield CA3. *Journal of*

Neuroscience, *39*(41), 8100–8111. https://doi.org/10.1523/JNEUROSCI.0722-19.2019

Guzowski, J. F., Knierim, J. J., & Moser, E. I. (2004). Ensemble Dynamics of Hippocampal Regions

CA3 and CA1. *Neuron*, *44*(4), 581–584. https://doi.org/10.1016/j.neuron.2004.11.003

Hasselmo, M. E., & Wyble, B. P. (1997). Free recall and recognition in a network model of the

hippocampus: Simulating effects of scopolamine on human memory function.

Behavioural Brain Research, *89*(1–2), 1–34.

Horner, A. J., Bisby, J. A., Bush, D., Lin, W.-J., & Burgess, N. (2015). Evidence for holistic episodic

recollection via hippocampal pattern completion. *Nature Communications*, *6*, 7462.

https://doi.org/10.1038/ncomms8462

Howard, M. W., & Kahana, M. J. (2002). A Distributed Representation of Temporal Context.

Journal of Mathematical Psychology, *46*(3), 269–299.

https://doi.org/10.1006/jmps.2001.1388

Howard, M. W., MacDonald, C. J., Tiganj, Z., Shankar, K. H., Du, Q., Hasselmo, M. E., &

Eichenbaum, H. (2014). A Unified Mathematical Framework for Coding Time, Space, and

Sequences in the Hippocampal Region. *The Journal of Neuroscience*, *34*(13), 4692–4707.

https://doi.org/10.1523/JNEUROSCI.5808-12.2014

Hsieh, L.-T., Gruber, M. J., Jenkins, L. J., & Ranganath, C. (2014). Hippocampal activity patterns

carry information about objects in temporal context. *Neuron*, *81*(5), 1165–1178.

https://doi.org/10.1016/j.neuron.2014.01.015

Hunt, R. R. (1995). The subtlety of distinctiveness: What von Restorff really did. *Psychonomic*

Bulletin & Review, *2*(1), 105–112. https://doi.org/10.3758/BF03214414

Jaeger, T. F. (2008). Categorical Data Analysis: Away from ANOVAs (transformation or not) and

towards Logit Mixed Models. *Journal of Memory and Language*, *59*(4), 434–446.

https://doi.org/10.1016/j.jml.2007.11.007

Jenkins, L. J., & Ranganath, C. (2010). Prefrontal and medial temporal lobe activity at encoding

predicts temporal context memory. *The Journal of Neuroscience: The Official Journal of*

the Society for Neuroscience, *30*(46), 15558–15565.

https://doi.org/10.1523/JNEUROSCI.1337-10.2010

Jenkins, L. J., & Ranganath, C. (2016). Distinct neural mechanisms for remembering when an

event occurred. *Hippocampus*, *26*(5), 554–559. https://doi.org/10.1002/hipo.22571

Kahana, M. J. (1996). Associative retrieval processes in free recall. *Memory & Cognition*, *24*(1),

103–109. https://doi.org/10.3758/BF03197276

Kesner, R. P., & Rolls, E. T. (2015). A computational theory of hippocampal function, and tests of

the theory: New developments. *Neuroscience and Biobehavioral Reviews*, *48*, 92–147.

https://doi.org/10.1016/j.neubiorev.2014.11.009

Kraus, B. J., Brandon, M. P., Robinson, R. J., Connerney, M. A., Hasselmo, M. E., & Eichenbaum,

H. (2015). During Running in Place, Grid Cells Integrate Elapsed Time and Distance Run.

Neuron, *88*(3), 578–589. https://doi.org/10.1016/j.neuron.2015.09.031

Kraus, B. J., Robinson, R. J., White, J. A., Eichenbaum, H., & Hasselmo, M. E. (2013).

Hippocampal "time cells": Time versus path integration. *Neuron*, *78*(6), 1090–1101.

https://doi.org/10.1016/j.neuron.2013.04.015

Kriegeskorte, N., Mur, M., & Bandettini, P. (2008). Representational Similarity Analysis—

Connecting the Branches of Systems Neuroscience. *Frontiers in Systems Neuroscience*, *2*.

https://doi.org/10.3389/neuro.06.004.2008

LaRocque, K. F., Smith, M. E., Carr, V. A., Witthoft, N., Grill-Spector, K., & Wagner, A. D. (2013).

Global similarity and pattern separation in the human medial temporal lobe predict

subsequent memory. *The Journal of Neuroscience: The Official Journal of the Society for*

Neuroscience, *33*(13), 5466–5474. https://doi.org/10.1523/JNEUROSCI.4293-12.2013

Lee, H., GoodSmith, D., & Knierim, J. J. (2020). Parallel processing streams in the hippocampus.

Current Opinion in Neurobiology, *64*, 127–134.

https://doi.org/10.1016/j.conb.2020.03.004

Levy, W. B. (1996). A sequence predicting CA3 is a flexible associator that learns and uses

context to solve hippocampal-like tasks. *Hippocampus*, *6*(6), 579–590.

https://doi.org/10.1002/(SICI)1098-1063(1996)6:6<579::AID-HIPO3>3.0.CO;2-C

Libby, L. A., Reagh, Z. M., Bouffard, N. R., Ragland, J. D., & Ranganath, C. (2018). The

Hippocampus Generalizes across Memories that Share Item and Context Information.

Journal of Cognitive Neuroscience, 1–12. https://doi.org/10.1162/jocn_a_01345

Lisman, J. E. (1999). Relating Hippocampal Circuitry to Function. *Neuron*, *22*(2), 233–242.

https://doi.org/10.1016/S0896-6273(00)81085-5

Lisman, J. E., & Jensen, O. (2013). The θ-γ neural code. *Neuron*, *77*(6), 1002–1016.

https://doi.org/10.1016/j.neuron.2013.03.007

Lohnas, L. J., Polyn, S. M., & Kahana, M. J. (2015). Expanding the scope of memory search:

Modeling intralist and interlist effects in free recall. *Psychological Review*, *122*(2), 337–

363. https://doi.org/10.1037/a0039036

MacDonald, C. J., Lepage, K. Q., Eden, U. T., & Eichenbaum, H. (2011). Hippocampal "time cells"

bridge the gap in memory for discontiguous events. *Neuron*, *71*(4), 737–749.

https://doi.org/10.1016/j.neuron.2011.07.012

Mankin, E. A., Diehl, G. W., Sparks, F. T., Leutgeb, S., & Leutgeb, J. K. (2015). Hippocampal CA2

activity patterns change over time to a larger extent than between spatial contexts.

Neuron, *85*(1), 190–201. https://doi.org/10.1016/j.neuron.2014.12.001

Mankin, E. A., Sparks, F. T., Slayyeh, B., Sutherland, R. J., Leutgeb, S., & Leutgeb, J. K. (2012).

Neuronal code for extended time in the hippocampus. *Proceedings of the National*

770  *Academy of Sciences of the United States of America*, *109*(47), 19462–19467.

771   https://doi.org/10.1073/pnas.1214107109

772 Manning, J. R. (2019). *Episodic memory: Mental time travel or a quantum `memory wave'*

773   *function?* [Preprint]. PsyArXiv. https://doi.org/10.31234/osf.io/6zjwb

774 Manning, J. R., Polyn, S. M., Baltuch, G. H., Litt, B., & Kahana, M. J. (2011). Oscillatory patterns

775   in temporal lobe reveal context reinstatement during memory search. *Proceedings of*

776   *the National Academy of Sciences*, *108*(31), 12893–12897.

777   https://doi.org/10.1073/pnas.1015174108

778 Mazaika, P., Whitfield-Gabrieli, S., & Cooper, J. C. (2005). *Detection and repair of transient*

779   *artifacts in fMRI data* [Poster]. Human Brain Mapping.

780 Montchal, M. E., Reagh, Z. M., & Yassa, M. A. (2019). Precise temporal memories are supported

781   by the lateral entorhinal cortex in humans. *Nature Neuroscience*, *22*(2), 284.

782   https://doi.org/10.1038/s41593-018-0303-1

783 Mumford, J. A., & Poldrack, R. A. (2007). Modeling group fMRI data. *Social Cognitive and*

784   *Affective Neuroscience*, *2*(3), 251–257. https://doi.org/10.1093/scan/nsm019

785 Mumford, J. A., Turner, B. O., Ashby, F. G., & Poldrack, R. A. (2012). Deconvolving BOLD

786   activation in event-related designs for multivoxel pattern classification analyses.

787   *NeuroImage*, *59*(3), 2636–2643. https://doi.org/10.1016/j.neuroimage.2011.08.076

788 Naya, Y., Chen, H., Yang, C., & Suzuki, W. A. (2017). Contributions of primate prefrontal cortex

789   and medial temporal lobe to temporal-order memory. *Proceedings of the National*

790   *Academy of Sciences*, *114*(51), 13555–13560. https://doi.org/10.1073/pnas.1712711114

Norman, K. A., Detre, G., & Polyn, S. M. (2008). Computational models of episodic memory. In

The Cambridge handbook of computational psychology (pp. 189–225). Cambridge

University Press. https://doi.org/10.1017/CBO9780511816772.011

Palombo, D. J., Di Lascio, J. M., Howard, M. W., & Verfaellie, M. (2019). Medial Temporal Lobe

Amnesia Is Associated with a Deficit in Recovering Temporal Context. *Journal of*

Cognitive Neuroscience, *31*(2), 236–248. https://doi.org/10.1162/jocn_a_01344

Pastalkova, E., Itskov, V., Amarasingham, A., & Buzsáki, G. (2008). Internally generated cell

assembly sequences in the rat hippocampus. *Science (New York, N.Y.)*, *321*(5894), 1322–

1327. https://doi.org/10.1126/science.1159775

Polyn, S. M., Norman, K. A., & Kahana, M. J. (2009). A context maintenance and retrieval model

of organizational processes in free recall. *Psychological Review*, *116*(1), 129–156.

https://doi.org/10.1037/a0014420

Power, J. D., Barnes, K. A., Snyder, A. Z., Schlaggar, B. L., & Petersen, S. E. (2012). Spurious but

systematic correlations in functional connectivity MRI networks arise from subject

motion. *NeuroImage*, *59*(3), 2142–2154.

https://doi.org/10.1016/j.neuroimage.2011.10.018

Ranganath, C. (2019). Time, memory, and the legacy of Howard Eichenbaum. *Hippocampus*,

29(3), 146–161. https://doi.org/10.1002/hipo.23007

Redish, A. D. (1999). *Beyond the Cognitive Map*. MIT Press.

https://mitpress.mit.edu/books/beyond-cognitive-map

Reiff, R., & Scheerer, M. (1959). *Memory and hypnotic age regression; developmental aspects of*

cognitive function explored through hypnosis. International Universities Press.

Ritvo, V. J. H., Turk-Browne, N. B., & Norman, K. A. (2019). Nonmonotonic Plasticity: How

Memory Retrieval Drives Learning. *Trends in Cognitive Sciences*.

https://doi.org/10.1016/j.tics.2019.06.007

Rodriguez, P., & Levy, W. B. (2001). A model of hippocampal activity in trace conditioning:

Where's the trace? *Behavioral Neuroscience*, *115*(6), 1224–1238.

https://doi.org/10.1037/0735-7044.115.6.1224

Rubin, A., Geva, N., Sheintuch, L., & Ziv, Y. (2015). Hippocampal ensemble dynamics timestamp

events in long-term memory. *ELife*, *4*. https://doi.org/10.7554/eLife.12247

Salz, D. M., Tiganj, Z., Khasnabish, S., Kohley, A., Sheehan, D., Howard, M. W., & Eichenbaum, H.

(2016). Time Cells in Hippocampal Area CA3. *The Journal of Neuroscience*, *36*(28), 7476–

7484. https://doi.org/10.1523/JNEUROSCI.0087-16.2016

Schlichting, M. L., & Preston, A. R. (2015). Memory integration: Neural mechanisms and

implications for behavior. *Current Opinion in Behavioral Sciences*, *1*, 1–8.

https://doi.org/10.1016/j.cobeha.2014.07.005

Scoville, W. B., & Milner, B. (1957). Loss of recent memory after bilateral hippocampal lesions.

Journal of Neurology, Neurosurgery, and Psychiatry, *20*(1), 11–21.

Sederberg, P. B., Howard, M. W., & Kahana, M. J. (2008). A context-based theory of recency and

contiguity in free recall. *Psychological Review*, *115*(4), 893–912.

https://doi.org/10.1037/a0013396

Sederberg, P. B., Miller, J. F., Howard, M. W., & Kahana, M. J. (2010). The temporal contiguity

effect predicts episodic memory performance. *Memory & Cognition*, *38*(6), 689–699.

https://doi.org/10.3758/MC.38.6.689

Shankar, K. H., & Howard, M. W. (2010). Timing using temporal context. *Brain Research*, *1365*,

3–17. https://doi.org/10.1016/j.brainres.2010.07.045

Shankar, K. H., & Howard, M. W. (2012). A scale-invariant internal representation of time.

Neural Computation, *24*(1), 134–193. https://doi.org/10.1162/NECO_a_00212

Singmann, H., & Kellen, D. (in press). An introduction to mixed models for experimental

psychology. In D. H. Spieler & E. Schumacher, *New Methods in Neuroscience and*

Cognitive Psychology. Psychology Press.

Stokes, J., Kyle, C., & Ekstrom, A. D. (2015). Complementary roles of human hippocampal

subfields in differentiation and integration of spatial context. *Journal of Cognitive*

Neuroscience, *27*(3), 546–559. https://doi.org/10.1162/jocn_a_00736

Sugar, J., & Moser, M.-B. (2019). Episodic memory: Neuronal codes for what, where, and when.

Hippocampus, *0*(0). https://doi.org/10.1002/hipo.23132

Thavabalasingam, S., O'Neil, E. B., & Lee, A. C. H. (2018). Multivoxel pattern similarity suggests

the integration of temporal duration in hippocampal event sequence representations.

NeuroImage, *178*, 136–146. https://doi.org/10.1016/j.neuroimage.2018.05.036

Treves, A., & Rolls, E. T. (1994). Computational analysis of the role of the hippocampus in

memory. *Hippocampus*, *4*(3), 374–391. https://doi.org/10.1002/hipo.450040319

Tubridy, S., & Davachi, L. (2011). Medial temporal lobe contributions to episodic sequence

encoding. *Cerebral Cortex (New York, N.Y.: 1991)*, *21*(2), 272–280.

https://doi.org/10.1093/cercor/bhq092

Tulving, E. (1983). *Elements of episodic memory*. Oxford University Press.

Vargha-Khadem, F., Gadian, D. G., Watkins, K. E., Connelly, A., Paesschen, W. V., & Mishkin, M.

(1997). Differential Effects of Early Hippocampal Pathology on Episodic and Semantic

Memory. *Science*, *277*(5324), 376–380. https://doi.org/10.1126/science.277.5324.376

Vazdarjanova, A., & Guzowski, J. F. (2004). Differences in hippocampal neuronal population

responses to modifications of an environmental context: Evidence for distinct, yet

complementary, functions of CA3 and CA1 ensembles. *The Journal of Neuroscience: The*

Official Journal of the Society for Neuroscience, *24*(29), 6489–6496.

https://doi.org/10.1523/JNEUROSCI.0350-04.2004

Wallenstein, G. V., Eichenbaum, H., & Hasselmo, M. E. (1998). The hippocampus as an

associator of discontiguous events. *Trends in Neurosciences*, *21*(8), 317–323.

Wang, F., & Diana, R. A. (2017). Neural correlates of temporal context retrieval for abstract

scrambled phrases: Reducing narrative and familiarity-based strategies. *Brain Research*,

1655, 128–137. https://doi.org/10.1016/j.brainres.2016.11.017

Wang, Y., Romani, S., Lustig, B., Leonardo, A., & Pastalkova, E. (2015). Theta sequences are

essential for internally generated hippocampal firing fields. *Nature Neuroscience*, *18*(2),

282–288. https://doi.org/10.1038/nn.3904

Yassa, M. A., & Stark, C. E. L. (2011). Pattern separation in the hippocampus. *Trends in*

Neurosciences, *34*(10), 515–525. https://doi.org/10.1016/j.tins.2011.06.006

Yushkevich, P. A., Amaral, R. S. C., Augustinack, J. C., Bender, A. R., Bernstein, J. D., Boccardi, M.,

Bocchetta, M., Burggren, A. C., Carr, V. A., Chakravarty, M. M., Chételat, G., Daugherty,

A. M., Davachi, L., Ding, S.-L., Ekstrom, A., Geerlings, M. I., Hassan, A., Huang, Y., Iglesias,

J. E., … Hippocampal Subfields Group (HSG). (2015). Quantitative comparison of 21

protocols for labeling hippocampal subfields and parahippocampal subregions in in vivo

MRI: Towards a harmonized segmentation protocol. *NeuroImage*, *111*, 526–541.

https://doi.org/10.1016/j.neuroimage.2015.01.004

Yushkevich, P. A., Wang, H., Pluta, J., Das, S. R., Craige, C., Avants, B. B., Weiner, M. W., &

Mueller, S. (2010). Nearly Automatic Segmentation of Hippocampal Subfields in In Vivo

Focal T2-Weighted MRI. *NeuroImage*, *53*(4), 1208–1224.

https://doi.org/10.1016/j.neuroimage.2010.06.040

Zacks, J. M., & Swallow, K. M. (2007). EVENT SEGMENTATION. *Current Directions in*

Psychological Science, *16*(2), 80–84. https://doi.org/10.1111/j.1467-8721.2007.00480.x

Ziv, Y., Burns, L. D., Cocker, E. D., Hamel, E. O., Ghosh, K. K., Kitch, L. J., Gamal, A. E., & Schnitzer,

M. J. (2013). Long-term dynamics of CA1 hippocampal place codes. *Nature*

Neuroscience, *16*(3), 264–266. https://doi.org/10.1038/nn.3329