Creating Artificial Human Genomes Using Generative Models

Authors: Burak Yelmen[1,2,*], Aurélien Decelle[3], Linda Ongaro[1,2], Davide Marnetto[1], Corentin Tallec[3], Francesco Montinaro[1,4], Cyril Furtlehner[3], Luca Pagani[1,5], Flora Jay[3,*]

Affiliations:

1 Institute of Genomics, University of Tartu, Estonia

2 Institute of Molecular and Cell Biology, University of Tartu, Estonia

3 Laboratoire de Recherche en Informatique, CNRS UMR 8623, Université Paris-Sud,

Université Paris-Saclay, Orsay, France

4 Department of Zoology, University of Oxford, UK

5 APE Lab, Department of Biology, University of Padova, Italy

[*]to whom correspondence should be addressed: burakyelmen@gmail.com, flora.jay@lri.fr

Abstract

Generative models have shown breakthroughs in a wide spectrum of domains due to recent advancements in machine learning algorithms and increased computational power. Despite these impressive achievements, the ability of generative models to create realistic synthetic data is still under-exploited in genetics and absent from population genetics.

Yet a known limitation of this field is the reduced access to many genetic databases due to concerns about violations of individual privacy, although they would provide a rich resource for data mining and integration towards advancing genetic studies. Here we demonstrate that we can train deep generative adversarial networks (GANs) and restricted Boltzmann machines (RBMs) to learn the high dimensional distributions of real genomic datasets and create artificial genomes (AGs). Additionally, we ensure none to little privacy loss while generating high quality AGs. To illustrate the promising outcomes of our method, we show that augmenting reference panels with AGs improves imputation quality for low frequency alleles. In summary, AGs have the potential to become valuable assets in genetic studies by providing high quality anonymous substitutes for private databases.

Introduction

Availability of genetic data has increased tremendously due to advances in sequencing technologies and reduced costs (Mardis 2017). The vast amount of human genetic data is used in a wide range of fields, from medicine to evolution. Despite the advances, cost is still a limiting factor and more data is always welcomed, especially in population genetics and genome-wide association studies (GWAS) which usually require substantial amounts of samples. Partially related to the costs but also to the research bias toward studying populations of European ancestry, many autochthonous populations are under-represented in genetic databases, diminishing the extent of the resolution in many studies (Cann 2002; Popejoy and Fullerton 2016; Mallick et al. 2016; Sirugo et al. 2019). Additionally, a huge portion of the data held by government institutions and private companies is considered sensitive and not easily accessible due to privacy issues, exhibiting yet another barrier for scientific work. A class of machine learning methods called generative models might provide a suitable solution to these problems.

Generative models are used in unsupervised machine learning to discover intrinsic properties of data and produce new data points based on those. In the last decade, generative models have been studied and applied in many domains of machine learning (Libbrecht and Noble 2015; Zhang et al. 2017; Rolnick and Dyer 2019). There have also been a few applications in the genetics field (Davidsen et al. 2019; Liu et al. 2019). Among the various generative approaches, we focus on two of them in this study, generative adversarial networks (GANs) and restricted Boltzmann machines (RBMs). GANs are generative neural networks which are capable of learning complex data distributions in a variety of domains (Goodfellow et al. 2014). A GAN consists of two neural networks, a generator and a discriminator, which compete in a zero-sum game (Supplementary Figure 1). During training, the generator produces new instances while the discriminator evaluates their authenticity. The training objective consists in learning the data distribution in a way such that the new instances created by the generator cannot be distinguished from true data by the discriminator. Since their first introduction, there have been many successful applications of GANs, ranging from generating high quality, realistic imagery to gap filling in texts (Ledig et al. 2017;

Fedus et al. 2018). GANs are currently the state-of-the-art models for generating
realistic images (Brock et al. 2018).

A restricted Boltzmann machine, initially called Harmonium is another generative
model which is a type of neural network capable of learning probability distributions
through input data (Smolensky 1986; Teh and Hinton 2001). RBMs are two layer neural
networks consisting of an input (visible) layer and a hidden layer (Supplementary
Figure 2). The learning procedure for the RBM consists in maximizing the likelihood
function over the visible variables of the model. This procedure is done by adjusting
the weights such that the correlations between the visible and hidden variables on both
the dataset and sampled configurations from the RBM converge. Then RBM models
recreate data in an unsupervised manner through many forward and backward passes
between these two layers (Gibbs sampling), corresponding to sampling from the
learned distribution. The output of the hidden layer goes through an activation function,
which in return becomes the input for the hidden layer. Although mostly overshadowed
by recently introduced approaches such as GANs or Variational Autoencoders
(Kingma and Welling 2013), RBMs have been used effectively for different tasks (such
as collaborative filtering for recommender systems, image or document classification)
and are the main components of deep belief networks (Hinton and Salakhutdinov 2006;
Hinton 2007; Larochelle and Bengio 2008).

Here we propose and compare a prototype GAN model along with an RBM model to
create Artificial Genomes (AGs) which can mimic real genomes and capture population
structure along with other characteristics of real genomes. We envision two main
applications of our generative methods: (i) improving the performance of genomic
tasks such as imputation, ancestry reconstruction, GWAS studies, by augmenting
genomic panels with AGs serving as proxies for private datasets, (ii) demonstrating
that a proper encoding of the genomic data can be learned and possibly used as a
starting input of various inference tasks by combining this encoding with recent neural
network-based tools for the reconstruction of recombination, demography or selection
(Sheehan and Song 2016; Adrion et al. 2019; Flagel et al. 2019).

Results

Reconstructing genome wide population structure:

Initially we created AGs with GAN, RBM, and two simple generative models for comparison: a Bernoulli and a Markov chain model (see Materials & Methods) using 2504 individuals (5008 haplotypes) from 1000 Genomes data (1000 Genomes Project Consortium et al. 2015), spanning 805 SNPs from all chromosomes which reflect a high proportion of the population structure present in the whole dataset (Colonna et al. 2014). Both GAN and RBM models seem to capture a good portion of the population structure present in 1000 Genomes data while the other two models could only produce instances centered around 0 on principal component analysis (PCA) space (Figure 1). All major modes, corresponding to African, European and Asian genomes, seem to be well represented in AGs produced by GAN and RBM models. Uniform manifold approximation and projection (UMAP) mapping results also correlate with the performed PCA (Supplementary Figure 3). We additionally checked the distribution of pairwise differences of haploid genomes to see how different AGs are from real genomes (Supplementary Figure 4). Both RBM and GAN models seem to have highly similar distributions to the distribution of pairwise differences of the real genomes within themselves. Especially RBM excels at acquiring the real peaks, indicating a high similarity with real genomes. Since GANs and RBMs show an excellent performance for this use case, we further explored other characteristics using only these two models.

Figure 1. The six first axes of a PCA applied to real (gray) and artificial genomes (AGs) generated via Bernoulli (green), Markov chain (purple), GAN (blue) and RBM (red) models. There are 5000 haplotypes for each AG dataset and 5008 (2504 genomes) for the real dataset from 1000 Genomes spanning 805 informative SNPs. See Materials & Methods for detailed explanation of the generation procedures.

Furthermore, similarly to tSNE and UMAP, RBMs perform a non-linear dimension reduction of the data and provides a suitable representation of a genomic dataset as a by-product based on the non-linear feature space associated to the hidden layer (Supplementary Text). As Diaz-Papkovich et al (Diaz-Papkovich et al. 2019), we found that the RBM representation differs from the linear PCA ones. Here we plot the representation corresponding to the selected RBM model and exhibit its rapid evolution through training (Supplementary Figure 5).

Supplementary Figure 5 shows that African, East Asian, and to a lesser extent, European populations stand out on the two first components. The Finnish are slightly isolated from the other European (similar to Peruvian from American) populations on the first components. South Asians are located at the center separated from Europeans, partially overlapping with American populations, and stand out at dimension 5 and higher. Interestingly when screening the hidden node activations, we observed that different populations or groups activate different hidden nodes, each one

representing a specific combination of SNPs, thereby confirming that the hidden layer
provides a meaningful encoding of the data (Supplementary Figure 6).

Reconstructing local high-density haplotype structure:
To evaluate if high quality artificial dense genome sequences can also be created by
the generative models, we applied the GAN and RBM methods to a 10K SNP region
using (i) the same individuals from 1000 Genomes data and (ii) 1000 Estonian
individuals from the high coverage Estonian Biobank (Leitsalu et al. 2015) to generate
artificial genomes. PCA results of AGs spanning consecutive 10K SNPs show that both
GAN and RBM models can still capture the relatively toned-down population structure
(Supplementary Figure 7) as well as the overall distribution of pairwise distances
(Supplementary Figure 8). Looking at the allele frequency comparison between real
and artificial genomes, we see that especially GAN performs poorly for low frequency
alleles, due to a lack of representation of these alleles in the AGs (Supplementary
Figure 9). On the other hand, the distribution of the distance of real genomes to the
closest AG neighbour show that GAN model, although slightly underfitting, outperforms
RBM model, for which an excess of small distances points towards slight overfitting
(Supplementary Figure 10).

Additionally, we performed linkage disequilibrium (LD) analyses comparing artificial
and real genomes to assess how successfully the AGs imitate short and long range
correlations between SNPs. Pairwise LD matrices for real and artificial genomes all
show a similar block pattern demonstrating that GAN and RBM accurately captured
the overall structure with SNPs having higher linkage in specific regions (Figure 2a).
However plotting LD as a function of the SNP distance showed that all models capture
weaker correlation, with RBM outperforming the GAN model perhaps due to its
overfitting characteristic (Figure 2b). To further determine the haplotypic integrity of
AGs, we performed ChromoPainter (Lawson et al. 2012) and Haplostrips (Marnetto
and Huerta-Sánchez 2017) analyses on AGs created using Estonians as the training
data. It was visually impossible to distinguish the difference between real and artificial
genomes in terms of local haplotypic structure with Haplostrips (Supplementary Figure
11). However, majority of the AGs produced via GAN model displayed fractured
chunks when painted against 1000 Genomes individuals whereas RBM AGs were
nearly indistinguishable from real genomes (Supplementary Figure 12).

Figure 2. Linkage disequilibrium (LD) analyses on real and artificial Estonian
genomes. a) Correlation (r2) matrices of SNPs. Lower triangular parts are SNP
pairwise correlation in real genomes and upper triangular parts are SNP pairwise
correlation in artificial genomes. b) LD as a function of SNP distance. Pairwise SNP
distances were stratified into 50 bins and for each distance bin the correlation was
averaged over all pairs of SNPs belonging to the bin.

a.

b.

180
181

After demonstrating that our models generated realistic AGs according to the
described summary statistics, we investigated further whether they respected privacy
by measuring the extent of overfitting. We calculated two metrics of resemblance and
privacy, the nearest neighbour adversarial accuracy (AA_{TS}) and privacy loss presented
in a recent study (Yale et al. 2019). AA_{TS} score measures whether two datasets were
generated by the same distribution based on the distances between all data points and
their nearest neighbours in each set. When applied to artificial and real datasets, a
score between 0.5 and 1 indicates underfitting, between 0 and 0.5 overfitting (and likely
privacy loss), and exactly 0.5 indicates that the datasets are indistinguishable. By using
an additional real test set, it is also possible to calculate a privacy loss score that is
positive in case of information leakage, negative otherwise, and approximately ranges
from -0.5 to 0.5. Computed on our generated data, both scores support haplotypic
pairwise difference results confirming the underfitting nature of GAN AGs and slight
overfitting nature of RBM AGs with a risk of privacy leakage for the latter (Figure 3a
and 3b).

Since it has been shown in previous studies that imputation scores can be improved
using additional population specific reference panels (Gurdasani et al. 2015; Mitt et al.
2017), as a possible future use case, we tried imputing real Estonian genomes using
1000 Genomes reference panel and additional artificial reference panels with Impute2
software (Howie et al. 2011). Both combined RBM AG and combined GAN AG panels
outperformed 1000 Genomes panel for the lowest MAF bin (for MAF < 0.05, 0.015 and
0.024 improvement respectively) which had 5926 SNPs out of 9230 total (Figure 3b).
Also mean info metric over all SNPs was 0.009 and 0.015 higher for combined RBM
and GAN panels respectively, compared to the panel with only 1000 Genomes
samples. However, aside from the lowest MAF bin, 1000 Genomes panel
outperformed both concatenated panels for all the higher bins. This might be a
manifestation of haplotypic deformities in AGs, that might have disrupted the
imputation algorithm.

211
212

Figure 3. a) Nearest neighbour adversarial accuracy (AA$_{TS}$) of artificial genomes generated from Estonian Biobank. Black line indicates the optimum value whereas values below the line indicate overfitting and values above the line indicate underfitting. **b)** Privacy loss. Positive values indicate information leakage, hence overfitting. **c)** Imputation evaluation of three different reference panels based on Impute2 software's info metric. Imputation was performed on 8678 Estonian individuals (which were not used in training of GAN and RBM models) using only 1000 Genomes panel (gray), combined 1000 Genomes and GAN artificial genomes panel (blue) and combined 1000 Genomes and RBM artificial genomes panel (red). SNPs were divided into 10 strata, from 0.05 to 0.1, after which mean info metric values were calculated for each stratum. Bars in the zoomed section show the standard error of mean.

Linking genotypes with phenotypes:

We then explored the possibility of creating AGs with unphased genotype data and recreating phenotype-genotype associations using generative models. As a proof of concept, we created GAN AGs via training on 1925 Estonian individuals with 5000 SNPs using unphased genotypes instead of haplotypes. There was an additional column in this dataset representing eye color (blue or brown). This region encompasses rs12913832 SNP which is highly associated with eye color (Han et al. 2008; Eriksson et al. 2010; Zhang et al. 2013). In our real genomes dataset, nearly 96% of the individuals possessing at least one ancestral allele A have brown eye color. The AGs were able to reproduce the same genotypic-phenotypic association with a ratio of 80% with the same allele A. Similarly, 97% of all blue-eyed individuals have the both derived alleles (G) whereas the same percentage is 88% in GAN AGs. There are no blue-eyed individuals who have both ancestral alleles in the real dataset but this number is 9 out 1925 in GAN AGs (Supplementary Table 1). We weren't able to create RBM AGs for this dataset.

Discussion

In this study, we applied generative models to produce artificial genomes and evaluated their characteristics. To the best of our knowledge, this is the first application of GAN and RBM models in this context, displaying overall promising applicability. We showed that population structure and frequency-based features of real populations can successfully be preserved in AGs created using GAN and RBM models. Furthermore, both models can be applied to sparse or dense SNP data given a large enough number of training individuals. Our different trials showed that the minimum required number of individuals for training is highly variable, possibly correlated with the diversity among individuals (data not shown). Since haplotype data is more informative, we created haplotypes for the analyses but we also demonstrated that the models can be applied to genotype data too, by simply combining two haplotypes if the training data is not phased (see Materials & Methods). In addition, we showed that it is possible to generate AGs with simple phenotypic traits through genotype data (see Results). Even though there were only two simple classes, blue and brown eye color phenotypes, generative models can be improved in the future to hold the capability to produce artificial datasets combining AGs with multiple phenotypes.

One major drawback of the proposed models is that, due to computational limitations, they cannot yet be used to create whole artificial genomes but rather snippets or sequential dense chunks. Although parallel computing might be a solution, this might further disrupt the haplotype structure in AGs. Instead, adapting convolutional GANs for AG generation might be another possible solution in the future (Radford et al. 2016). Another problem arose due to rare alleles, especially for the GAN model. We showed that nearly half of the alleles become fixed in the GAN AGs in the 10K SNP dataset, whereas RBM AGs seem to capture more of the rare alleles present in real genomes (Supplementary Figure 13). A known issue in GAN training is mode collapse (Salimans et al. 2016). Mode collapse happens when the generator fails to cover the full support of the data distribution. This failure case could explain the inability of GANs to generate rare alleles. For some applications relying on rare alleles, GAN models less sensitive to mode dropping would be a promising alternative (Arjovsky et al. 2017; Lucas et al. 2018).

An important use case for the AGs in the future might be creating publicly available
versions of private genome banks. Through enhancements in scientific knowledge and
technology, genetic data becomes more and more sensitive in terms of privacy. AGs
might offer a versatile solution to this delicate issue in the future by protecting the
anonymity of real individuals. Our results showed that GAN AGs seem to be
underfitting while RBM AGs seem to be overfitting based on distribution of minimum
distance to the closest neighbour (Supplementary Figure 10) and AA_{TS} scores (Figure
3a), although this can be investigated further by integrating AA_{TS} scores within our
models as a criterion for early stopping in training (before the networks start overfitting).
In the context of the privacy issue, GAN AGs have a slight advantage since underfitting
is preferable. More distant AGs would hypothetically be harder to be traced back to the
original genomes. We also tested the sensitivity of the AA_{TS} score and privacy loss
(Supplementary Figure 14). It appears that both scores are affected very slightly when
we add only a few real genomes to the AG dataset from the training set. Therefore,
more sensitive measurement techniques should be developed in the future for better
assessment of generated AGs. Additionally, even though we did not detect exact
copies of real genomes in AG sets created either by RBM or GAN models, it is a very
complicated task to determine if the generated samples can be traced back to the
originals. Reliable measurements need to be developed in the future to assure
complete anonymity of AGs to their source.
294
Imputation results demonstrated promising outcomes especially for population specific
low frequency alleles. However, imputation with both RBM and GAN AGs integrated
reference panels showed slight decrease of info metric for higher frequency alleles
compared to only 1000 Genomes panel (Figure 3c). We initially speculated that this
might be related to the disturbance in haplotypic structure and therefore, tried to filter
AGs based on chunk counts from ChromoPainter results, preserving only AGs which
are below the average chunk count of real genomes. The reason behind this was to
preserve most real-alike AGs with undisturbed chunks. Even with this filtering, slight
decrease in higher MAF bins was still present (data not shown). Yet results of
implementation with AGs for low frequency alleles and without AGs for high frequency
ones could be combined to achieve best performance. In terms of imputation, future
improved models can become practically very useful, largely for GWAS studies in
which imputation is a common application to increase resolution. Different generative

models such as MaskGAN (Fedus et al. 2018) which demonstrated good results in text
gap filling might also be adapted for genetic imputation. RBM is possibly another option
to be used as an imputation tool directly by itself, since once the weights have been
learned, it is possible to fix a subset of the visible variables and to compute the average
values of the unobserved ones by sampling the probability distribution (in fact, it is
even easier than sampling entirely new configurations since the fixed subset of
variables will accelerate the convergence of the sampling algorithm).

As an additional feature, training an RBM to model the data distribution gives access
to a latent encoding of data points, providing a potentially easier to use representation
of data (Supplementary Figure 5). Future works could augment our current GAN model
to also provide an encoding mechanism, in the spirit of (Dumoulin et al. 2016 Jun 2),
(Chen et al. 2016) or (Donahue et al. 2016). These interpretable representations of the
data are expected to be more relevant for downstream tasks (Chen et al. 2016) and
could be used as a starting point for various population genetics analyses such as
demographic and selection inference, or yet unknown tasks.

Although there are some current limitations, generative models will most likely become
prominent for genetics in the near future with many promising applications. In this work,
we demonstrated the first possible implementations and use of AGs in the forthcoming
field which we would like to name artificial genomics.

Materials & Methods

Data:

We used 2504 individual genomes from 1000 Genomes Project (1000 Genomes Project Consortium 2015) and 1000 individuals from Estonian Biobank (Leitsalu et al. 2015) to create artificial genomes (AGs). Additional 2000 Estonians were used as a test dataset. Another Estonian dataset consisting of 8678 individuals which were not used in training were used for imputation. Analyses were applied to a highly differentiated 805 SNP range selected as a subset from (Colonna et al. 2014) and a dense 10000 SNP range from chromosome 15. We also used a narrowed down version of the same region from chromosome 15 with 5000 SNPs with an additional eye color column for unphased genotype data using another 1925 Estonians as training dataset. In this set, 958 of the Estonian samples have brown (encoded as 1) and 967 have blue eyes (encoded as 0). In the data format we used, rows are individuals/haplotypes (instances) and columns are positions/SNPs (features). Each allele at each position is represented either by 0 or 1. In the case of phased data (haplotypes), each column is one position whereas in the case of unphased data, each two column corresponds to a single position with alleles from two chromosomes.

GAN Model:

We used python-3.6, Keras 2.2.4 deep learning library with TensorFlow backend (Chollet 2015), pandas 0.23.4 (McKinney 2010) and numpy 1.16.4 (Oliphant 2007) for the GAN code. Generator of the GAN model we present consists of an input layer with the size of the latent vector size 600, one hidden layer with size proportional to the number of SNPs as SNP_number/1.2 rounded, another hidden layer with size proportional to the number of SNPs as SNP_number/1.1 rounded and an output layer with the size of the number of SNPs. The latent vector was set with numpy.random.normal function setting the mean of the distribution as 0 and the standard deviation as 1. The discriminator consists of an input layer with the size of the number of SNPs, one hidden layer with size proportional to the number of SNPs as SNP_number/2 rounded, another hidden layer with size proportional to the number of SNPs as SNP_number /3 rounded and an output layer of size 1. All layer outputs except for output layers have LeakyReLU activation functions with leaky_alpha parameter 0.01 and L2 regularization parameter 0.0001. The generator output layer

activation function is tanh and discriminator output layer activation function is sigmoid.
Both discriminator and combined GAN were compiled with Adam optimization
algorithm with binary cross entropy loss function. We set the discriminator learning rate
as 0.0008 and combined GAN learning rate as 0.0001. For 5000 SNP data, the
discriminator learning rate was 0.00008 and combined GAN learning rate was 0.00001.
Training to test dataset ratio was 3:1. We used batch size of 32 and trained all datasets
up to 20000 epochs. We stopped training based on coherent PCA results of AGs with
real genomes. During each batch, when only the discriminator is trained, we applied
smoothing to the real labels (1) by vectoral addition of random uniform distribution via
numpy.random.uniform with lower bound 0 and upper bound 0.1. Elements of the
generated outputs were rounded to 0 or 1 with numpy.rint function.
373
RBM Model:
The RBM was coded in Julia (Bezanson et al. 2017), and all the algorithm for the
training has been done by the authors. The part of the algorithm involving linear algebra
used the standard package provided by Julia. Two versions of the RBM were
considered. In both versions, the visible nodes were encoded using Bernoulli random
variables {0,1}, and the size of the visible layer was the same size as the considered
input. Two different types of hidden layers were considered. First with a sigmoid
activation function (hence having discrete {0,1} hidden variables), second with ReLu
(Rectified Linear unit) activations in which case the hidden variables were positive and
continuous (there are distributed according to a truncated gaussian distribution when
conditioning on the values of the visible variables). Results with sigmoid activation
function were worse compared to ReLu so we used ReLu for all the analyses
(Supplementary Figure 15). The number of hidden nodes considered for the
experiment was Nh=100 for the 805 SNP dataset and Nh=500 for the 10k one. There
is no canonical way of fixing the number of hidden nodes, in practice we checked that
the number of eigenvalues learnt by the model was smaller than the number of hidden
nodes, and that by adding more hidden nodes no improvement were observed during
the learning. The learning in general is quite stable, in order to have a smooth learning
curve, the learning rate was set between 0.001 and 0.0001 and we used batch size of
32. The negative term of the gradient of the likelihood function was approximated using
the PCDk method (Brügge et al. 2013), with k=10 and 100 of persistent chains. As a

stopping criterion, we looked at when the AA_{TS} score converges to the ideal value of
0.5 when sampling the learned distribution.

Bernoulli Distribution Model:

We used python-3.6, pandas 0.23.4 and numpy 1.16.4 for the Bernoulli distribution
model code. Each allele at a given position was randomly drawn given the derived
allele frequency in the real population.

Markov Chain Model:

We used python-3.6, pandas 0.23.4 and numpy 1.16.4 for the Markov chain model
code. Allele at the initial position was set by drawing from a Bernoulli distribution
parameterized with the real frequency. Each sequence window consisting of a given
number of positions was determined by the probability of the previous sequence
window. After the initial position, window size increased incrementally up to the given
window size.

Chromosome Painting:

We compared the haplotype sharing distribution between real and artificial
chromosomes through ChromoPainter (Lawson et al. 2012). In detail, we have painted
100 randomly selected "real" and "artificial" Estonians (recipients) against all the 1000
Genome Project phased data (donors). The nuisance parameters -n (348.57) and -M
(0.00027), were estimated running 10 iterations of the expectation-maximization
algorithm on a subset of 3,800 donor haplotypes.

Haplostrips:

We used Haplostrips (Marnetto and Huerta-Sánchez 2017) to visualize the haplotype
structure of real and artificial genomes. We extracted 500 individuals from each sample
set (Real, GAN synthetics, RBM synthetics) and considered them as different
populations. Black dots represent derived alleles, white ancestral. The plotted SNPs
were filtered for a population specific minor allele frequency >5%; haplotypes were
clustered and sorted for distance against the consensus haplotype from the real set.
See the application article for further details about the method.

Acknowledgements

This work was supported by the European Union through the European Regional Development Fund (Project No. 2014-2020.4.01.16-0024, MOBTT53: LP, DM, BY; Project No. 2014-2020.4.01.16-0030: LO, FM); the Estonian Research Council grant PUT (PRG243): LP; Laboratoire de Recherche en Informatique: FJ, AD, CT, CF.

References

1000 Genomes Project Consortium, Auton A, Brooks LD, Durbin RM, Garrison EP, Kang HM, Korbel JO, Marchini JL, McCarthy S, McVean GA, et al. 2015. A global reference for human genetic variation. Nature. 526(7571):68–74. doi:10.1038/nature15393.

Adrion JR, Galloway JG, Kern AD. 2019. Inferring the landscape of recombination using recurrent neural networks. bioRxiv. doi:10.1101/662247.

Arjovsky M, Chintala S, Bottou L. 2017. Wasserstein generative adversarial networks. In: 34th International Conference on Machine Learning, ICML 2017.

Bezanson J, Edelman A, Karpinski S, Shah VB. 2017. Julia: A fresh approach to numerical computing. SIAM Rev. doi:10.1137/141000671.

Brock A, Donahue J, Simonyan K. 2018 Sep 28. Large Scale GAN Training for High Fidelity Natural Image Synthesis. http://arxiv.org/abs/1809.11096.

Cann HM. 2002. A Human Genome Diversity Cell Line Panel. Science (80-). doi:10.1126/science.296.5566.261b.

Chen X, Duan Y, Houthooft R, Schulman J, Sutskever I, Abbeel P. 2016. InfoGAN: Interpretable representation learning by information maximizing generative adversarial nets. In: Advances in Neural Information Processing Systems.

Chollet F. 2015. Keras: Deep Learning library for Theano and TensorFlow. GitHub Repos.

Colonna V, Ayub Q, Chen Y, Pagani L, Luisi P, Pybus M, Garrison E, Xue Y, Tyler-Smith C, Abecasis GR, et al. 2014. Human genomic regions with exceptionally high levels of population differentiation identified from 911 whole-genome sequences. Genome Biol. doi:10.1186/gb-2014-15-6-r88.

Davidsen K, Olson BJ, DeWitt WS, Feng J, Harkins E, Bradley P, Matsen FA. 2019. Deep generative models for T cell receptor protein sequences. Elife. 8. doi:10.7554/eLife.46935. https://elifesciences.org/articles/46935.

Diaz-Papkovich A, Anderson-Trocme L, Gravel S. 2019. Revealing multi-scale population structure in large cohorts. bioRxiv. doi:10.1101/423632.

Donahue J, Krähenbühl P, Darrell T. 2016 May 31. Adversarial Feature Learning. http://arxiv.org/abs/1605.09782.

Dumoulin V, Belghazi I, Poole B, Mastropietro O, Lamb A, Arjovsky M, Courville A. 2016 Jun 2. Adversarially Learned Inference. http://arxiv.org/abs/1606.00704.

Eriksson N, Macpherson JM, Tung JY, Hon LS, Naughton B, Saxonov S, Avey L, Wojcicki A, Pe'er I, Mountain J. 2010. Web-based, participant-driven studies yield novel genetic associations for common traits. PLoS Genet. doi:10.1371/journal.pgen.1000993.

Fedus W, Goodfellow I, Dai AM. 2018 Jan 23. MaskGAN: Better Text Generation via Filling in the______. http://arxiv.org/abs/1801.07736.

Flagel L, Brandvain Y, Schrider DR. 2019. The unreasonable effectiveness of convolutional neural networks in population genetic inference. Mol Biol Evol. doi:10.1093/molbev/msy224.

Goodfellow I, Pouget-Abadie J, Mirza M. 2014. Generative Adversarial Networks

(GANs) - Tutorial. Neural Inf Process Syst.

Gurdasani D, Carstensen T, Tekola-Ayele F, Pagani L, Tachmazidou I, Hatzikotoulas K, Karthikeyan S, Iles L, Pollard MO, Choudhury A, et al. 2015. The African Genome Variation Project shapes medical genetics in Africa. Nature. doi:10.1038/nature13997.

Han J, Kraft P, Nan H, Guo Q, Chen C, Qureshi A, Hankinson SE, Hu FB, Duffy DL, Zhen ZZ, et al. 2008. A genome-wide association study identifies novel alleles associated with hair color and skin pigmentation. PLoS Genet. doi:10.1371/journal.pgen.1000074.

Hinton GE. 2007. Learning multiple layers of representation. Trends Cogn Sci. doi:10.1016/j.tics.2007.09.004.

Hinton GE, Salakhutdinov RR. 2006. Reducing the dimensionality of data with neural networks. Science (80-). doi:10.1126/science.1127647.

Howie B, Marchini J, Stephens M. 2011. Genotype imputation with thousands of genomes. G3 Genes, Genomes, Genet. doi:10.1534/g3.111.001198.

Kingma DP, Welling M. 2013 Dec 20. Auto-Encoding Variational Bayes. http://arxiv.org/abs/1312.6114.

Larochelle H, Bengio Y. 2008. Classification using discriminative restricted boltzmann machines. In: Proceedings of the 25th International Conference on Machine Learning.

Lawson DJ, Hellenthal G, Myers S, Falush D. 2012. Inference of population structure using dense haplotype data. PLoS Genet. 8(1):11–17. doi:10.1371/journal.pgen.1002453.

Ledig C, Theis L, Huszár F, Caballero J, Cunningham A, Acosta A, Aitken A, Tejani A, Totz J, Wang Z, et al. 2017. Photo-realistic single image super-resolution using a generative adversarial network. In: Proceedings - 30th IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017.

Leitsalu L, Haller T, Esko T, Tammesoo ML, Alavere H, Snieder H, Perola M, Ng PC, Mägi R, Milani L, et al. 2015. Cohort profile: Estonian biobank of the Estonian genome center, university of Tartu. Int J Epidemiol. doi:10.1093/ije/dyt268.

Libbrecht MW, Noble WS. 2015. Machine learning applications in genetics and genomics. Nat Rev Genet. doi:10.1038/nrg3920.

Liu Q, Lv H, Jiang R. 2019. HicGAN infers super resolution Hi-C data with generative adversarial networks. In: Bioinformatics. Vol. 35. Oxford University Press. p. i99–i107.

Lucas T, Tallec C, Verbeek J, Ollivier Y. 2018. Mixed batches and symmetric discriminators for GAN training. In: 35th International Conference on Machine Learning, ICML 2018.

Mallick S, Li H, Lipson M, Mathieson I, Gymrek M, Racimo F, Zhao M, Chennagiri N, Nordenfelt S, Tandon A, et al. 2016. The Simons Genome Diversity Project: 300 genomes from 142 diverse populations. Nature. doi:10.1038/nature18964.

Mardis ER. 2017. DNA sequencing technologies: 2006-2016. Nat Protoc. doi:10.1038/nprot.2016.182.

Marnetto D, Huerta-Sánchez E. 2017. Haplostrips: revealing population structure

through haplotype visualization. Methods Ecol Evol. 8(10):1389–1392. doi:10.1111/2041-210X.12747.

McKinney W. 2010. Data Structures for Statistical Computing in Python. In: Proceedings of the 9th Python in Science Conference.

Mitt M, Kals M, Pärn K, Gabriel SB, Lander ES, Palotie A, Ripatti S, Morris AP, Metspalu A, Esko T, et al. 2017. Improved imputation accuracy of rare and low-frequency variants using population-specific high-coverage WGS-based imputation reference panel. Eur J Hum Genet. doi:10.1038/ejhg.2017.51.

Oliphant TE. 2007. SciPy: Open source scientific tools for Python. Comput Sci Eng.

Popejoy AB, Fullerton SM. 2016. Genomics is failing on diversity. Nature. doi:10.1038/538161a.

Radford A, Metz L, Chintala S. 2016. Unsupervised Representation learning with Deep Convolutional GANs. Int Conf Learn Represent. doi:10.1051/0004-6361/201527329.

Rolnick D, Dyer EL. 2019. Generative models and abstractions for large-scale neuroanatomy datasets. Curr Opin Neurobiol. doi:10.1016/j.conb.2019.02.005.

Salimans T, Goodfellow I, Zaremba W, Cheung V, Radford A, Chen X. 2016. Improved techniques for training GANs. In: Advances in Neural Information Processing Systems.

Sheehan S, Song YS. 2016. Deep Learning for Population Genetic Inference. PLoS Comput Biol. 12(3):1–28. doi:10.1371/journal.pcbi.1004845.

Sirugo G, Williams SM, Tishkoff SA. 2019. The Missing Diversity in Human Genetic Studies. Cell. doi:10.1016/j.cell.2019.02.048.

Smolensky P. 1986. Information processing in dynamical systems: Foundations of harmony theory. In: Parallel Distributed Processing Explorations in the Microstructure of Cognition.

Teh YW, Hinton GE. 2001. Rate-coded restricted boltzmann machines for face recognition. In: Advances in Neural Information Processing Systems.

Yale A, Dash S, Dutta R, Guyon I, Pavao A, Bennett K. 2019 Apr 24. Privacy Preserving Synthetic Health Data. https://hal.inria.fr/hal-02160496/.

Zhang H, Xu T, Li H, Zhang S, Wang X, Huang X, Metaxas D. 2017. StackGAN: Text to Photo-Realistic Image Synthesis with Stacked Generative Adversarial Networks. In: Proceedings of the IEEE International Conference on Computer Vision.

Zhang M, Song F, Liang L, Nan H, Zhang J, Liu H, Wang LE, Wei Q, Lee JE, Amos CI, et al. 2013. Genome-wide association studies identify several new loci associated with pigmentation traits and skin cancer risk in European Americans. Hum Mol Genet. doi:10.1093/hmg/ddt142.