1

Anticipatory Control of Momentum for Bipedal Walking on Uneven Terrain

Osman Darici[1*], Hakan Temeltas[2], Arthur D. Kuo[1,3]

[1]Faculty of Kinesiology and [3]Biomedical Engineering Program, University of Calgary, Calgary,

Alberta, Canada

[2]Istanbul Technical University, Control and Automation Engineering, Istanbul, Turkey

*Corresponding author: osman.darici1@ucalgary.ca

Abstract

Humans and other walking bipeds often encounter and compensate for uneven terrain. They

might, for example, regulate the body's momentum when stepping on stones to cross a stream.

We examined what to do and how far to look, as a simple optimal control problem, where

forward momentum is controlled to compensate for a step change in terrain height and regain

steady gait with no loss of time or distance compared to nominal walking. We modeled planar,

human-like walking with pendulum-like legs, and found the most economical control to be quite

stereotypical. It starts by gaining momentum several footfalls ahead of an upward step, in

anticipation of the momentum lost atop that step, and then ends with another speed-up to

regain momentum thereafter. A similar pattern can be scaled to a variety conditions, including

both upward or downward steps, yet allow for considerably reduced overall energy and peak

power demands, compared to compensation without anticipation. A measure of "persistence

time" helps describe how momentum is retained between steps, and how far ahead to plan.

Anticipatory control of momentum can help to economically negotiate uneven terrain.

Introduction

Humans and other bipeds often encounter uneven terrain in walking environments. Even the act

of stepping between curb and sidewalk can perturb otherwise steady walking and cause a loss of

stability and forward speed. Although gait may be restored with feedback control, there may be

advantages to anticipating the upcoming disturbance, for example through vision or other

imaging, and performing compensations before stepping on it. Although it may seem

advantageous to anticipate ahead of time, it is unknown how far ahead to look, what actions to

take, and at what cost to restore nominal gait. A simple modeling analysis can yield insight on

how best to anticipate and compensate for a terrain disturbance.

Anticipation offers a potential advantage in time. Whereas a feedback response cannot be

initiated until a disturbance has been physically encountered, anticipatory control can be

initiated immediately upon its (visual) detection. It can thus distribute control actions both before

and after the disturbance, and potentially compensate more economically or with less actuator

effort. A simple example is the running long jump, which builds up more momentum and yields

a longer jump than can be gained from a static, standing position. Similar benefits might apply to

traversal of a minor terrain disturbance, with appropriate anticipation and planning.

We will address anticipation and integration as a simple optimization problem (Fig. 1). One

simplification is to consider only a single disturbance in terrain height ("up-step" or "down-step").

Many a person has experienced a stumble or fall from a small, unexpected disturbance, as has

many a bipedal robot. In fact, an up- or down-step is often used as a test of a robot's robustness

to uneven terrain[1,2]. An additional simplification is to consider a minimal, sagittal plane model of

bipedal walking, in which momentum is carried by a pendulum-like stance leg, and additional

degrees of freedom for the swing leg or lateral motions are ignored (or controlled by lower-level

feedback loops). Pendulum-like, underactuated locomotion describes some aspects of human

walking e.g.[3,4], and that of a number of robot models[5–7] and physical machines[8–12].

Underactuation implies that energy change occurs little during stance, but substantially with a

relatively rigid swing leg's collision with ground[13–15], as part of the "step-to-step transition"[16]. The

energy and momentum losses from collision, and the positive work done to offset these losses,

are key to the optimization solutions.

The proposed optimization modulates forward momentum to mitigate the effects of a single

terrain height disturbance (an "up-step" or "down-step"). The goals will be to regain a nominal

walking gait without falling down, and without loss of time, so that the biped will eventually be

at an appointed time and position, as if had always been on level terrain. Of course, there may

be some demands on overall or peak work of muscles or actuators, and so these will be minimized

or evaluated as part of the optimization. Here we present the dynamics of a simple model (Fig.

1), followed by an optimization formulation to address these questions. This is then followed by

a series of simple observations regarding how to anticipate and recover from a terrain

disturbance.

a. Walking over a step

step height b ↑   ←step→ length S

b. Model

c. Level nominal walking

d. Step at $i=0$
Pre-emptive push-off   Late push-off

e. Compensation over N steps

N steps (shift by m)

Figure 1. Simple model of walking over a single up- (or down-) step. (**a**) Body center of mass (COM) is a point mass carried atop stance leg acting as an inverted pendulum, encountering step of height b. (**b**) Model has mass M at pelvis, massless legs of length L, gravitational acceleration g, and fixed step length S, with inter-leg angle 2α. Stance leg angle is measured with angle θ as shown. (**c**) Level nominal walking has step-to-step transition where COM velocity is redirected from forward-and-downward v_i^- to forward-and-upward v_i^+, with active, impulsive trailing leg push-off (PO), followed by inelastic, impulsive, leading leg collision (CO). (**d**) Up-step occurs on step $i = 0$, with two cases: pre-emptive and late push-off, which both perform positive work (u_0 and u_0^+, respectively) but earlier or later than collision. (**e**) Optimization is to modulate N push-offs to minimize their total work while accommodating the up-step in the same time as level walking at speed V. The N steps are nominally centered on the up-step for equal anticipation and recovery, but may be shifted by m steps relative to obstacle. Up-step heights have positive b; down-steps negative b.

Results

We found that encountering an up-step without any compensation results in a considerable loss

of time. The lost time may then be regained by speeding up from nominal walking, but even the

optimal speed-up places considerable demands on overall work and peak actuator power. We

then found that the optimal compensation is instead to anticipate and adjust forward

momentum or speed in a transient period starting before and ending after the up-step. Results

show that a single compensation pattern can be scaled to characterize optimal strategies for

different walking speeds and step heights, including down-steps.

Uncompensated transient response resembles exponential decay and is described by

persistence time

The benchmark for optimal compensation strategies is the effect of a completely uncompensated

up-step. Uncompensated control means that only the nominal, pre-emptive push-off is applied[17]

($u_i = U$), without any modulation. The transient response resembles an exponential decay,

starting with an immediate loss of speed at the up-step, followed by an approximately

exponential response over subsequent discrete steps (step index i; equation 2). We found the

persistence time to characterize how compensations scale over a wide range of walking speeds

and disturbances.

There is considerable advantage to pushing off onto the up-step pre-emptively. If the up-step can

be anticipated only enough to allow push-off to occur before the collision, it can greatly reduce

the immediate loss of speed compared to a late push-off[17]. For a sample up-step of modest

height, loss of speed is about 80% less ($b = 0.025L$; see Fig. 2a) and time loss is 82.7% less ($b =$

$0.025L$; see Fig. 2b). Continuing with nominal push-offs after the up-step, both cases experience

a similar type of exponential decay in speed error, and therefore an asymptotic return to nominal

walking (Fig. 2b). But pre-emptive push-off reduces the total time loss by 82% compared to late

push-off (for $b =0.025L$), even if push-off magnitude is not actively modulated. Thus, even a

short-range ability to detect an upcoming obstacle can be helpful, if it allows for an unmodulated

but still pre-emptive push-off.

The eventual total time loss also increases sharply with up-step height (Fig. 2c). This is because

the potential energy of the up-step comes at the expense of the model's kinetic energy, and

therefore speed. In fact, the potential energy gained at mid-stance, atop the up-step, must not

exceed the kinetic energy available immediately after push-off (see velocity v_0^+; equations 2 and

7). As a result, a faster nominal walking speed is relatively less sensitive to up-step (compare

different speeds in Fig. 2c).

Figure 2. Effect of an uncompensated up-step. (**a**) Speed fluctuations vs. time, for an up-step at time 0 with constant push-off. Model experiences transient disturbance from nominal speed due to up-step, with smaller effect if push-off occurs pre-emptively as opposed to late. Each dot (filled symbol) indicates a discrete step, with speed v_i sampled at mid-stance (see Fig. 1e). (**b**) Cumulative time gain vs. time shows accumulating effect of speed loss, with asymptote towards a total time loss (negative time gain). (**c**) Total time gain vs. up-step height b for various nominal walking speeds, with greater bumps causing greater loss of time, and smaller effect for faster nominal speeds. Also shown are effects of late push-off (unfilled symbols). Up-step height $b = 0.025L$, nominal mid-stance velocity $V = 0.44g^{-0.5}L^{0.5}$. Conditions are equivalent to a human walking at 1.5 m/s, encountering an up-step of 2.5 cm.

The transient response's decay (Fig. 2a) is well characterized by persistence time (detailed in Methods). For the nominal gait, the persistence time is about 2.61 steps, equivalent to about 1.39 seconds or 2.06 m for nominal, human-like walking. This equivalently yields a 90% settling time of about 5.7 steps following a disturbance.

Time may be gained from steady-state walking with a (costly) burst of speed

Given the total time lost from a disturbance, a naïve compensation is simply to regain that time with an isolated time gain, meaning a separate burst of speed from nominal, level walking. The appropriate amount of time t_{gain} could be gained either well before or well after nominal speed is disrupted. In either case, the time is to be gained within a burst of N fast steps, starting and ending at the nominal steady-state speed V, while minimizing total push-off work.

The optimal solution is a burst of speed that smoothly rises to a single peak, and then decreases back to nominal, with a roughly time-symmetric profile (Fig. 3 top). The corresponding push-off

sequence (Fig. 3 top) is neither smooth nor symmetric. The peak push-off work occurs on the

initial compensation step, with considerably greater magnitude than nominal, about 1.78 times

greater to regain time lost from a sample up-step ($b = 0.075L$; $N = 9$). The succeeding push-

offs—save the final one—decrease rapidly and then level off above normal, as time is recouped.

The final compensatory push-off is actually below nominal, to enable speed-matching for the

final conditions. This asymmetric push-off profile nonetheless contributes to a rather smooth

accumulation of time gain, resembling a ramp function with rounded corners (Fig. 3 top).

Figure 3. Optimal strategies to gain time during level walking, separate from any disturbance, for (top row:) varying
amounts of time t_{gain}, and (bottom row:) varying number of steps N. Each row, from left to right: Speed fluctuations
vs. time, push-off work vs. time, and cumulative time gain vs. time, relative to nominal (each step denoted by filled
symbol). Parameter values are $N = 9$ steps for top row, $t_{\text{gain}} = 0.5$ for bottom row. Filled dots indicate steps.
Unfilled dots denote large push-offs that entail momentary aerial phases or even running for several steps; maximum
time gain thresholds to avoid such cases are shown in (top most right).

These effects are amplified as more time is gained (Fig. 3 top). The greater the t_{gain} (at fixed N),

the greater both the peak speed and peak push-off. Of course, time may be gained more easily

over a greater number of compensation steps. The more steps N over which time is gained, the

shallower the peak in walking speed, the lower the peak push-off, and the more gradual the gain,

with less time gained per step (Fig. 3 bottom). Conversely, gaining time over very few steps entails

a sharp peak in both speed and push-off (Fig. 3 bottom). In terms of both overall and peak amount

push-off work, there is great advantage to spreading a time gain over as many steps as possible

(Fig. 3 bottom).

Another issue with gaining time is the limitations of a walking gait. A sufficiently large push-off

may cause the model to lose ground contact (or leap) into a momentary aerial phase prior to

collision (see equation 2), particularly for the first push-offs of the compensation (Fig. 3 top). This

might resemble a straight-legged run for a few steps. If such leaping were disallowed, the

maximum time that could be gained would be equivalent to about 2.86 nominal step times (T).

In addition, large enough time gains can call for speeds that exceed the limits to pendulum-like

walking, where it would be necessary to break into a run. A simple indicator of running is when

the downward, centripetal COM acceleration requires greater force than body weight, $v_i \geq$

$1\ g^{0.5}L^{0.53}$. We did not explicitly model running in our analysis, and instead noted which steps or

time gains would exceed the thresholds for maintaining a pure walking gait.

The primary issue is the number of steps over which time is to be gained. For fewer steps or more

time gain, there are substantial penalties with regard to peaks in walking speed, peak and overall

work, and the potential need for aerial phases. Conversely, increasing N or decreasing t_{gain}

reduces these penalties substantially. For relatively large N, the speed and push-off profiles

become increasingly constant (Fig. 3 bottom), so that the primary cost is dominated by the work

for steady walking at an elevated speed. In the limit, the extra work needed to gain time is simply

inversely proportional to N. If time needs to be gained, whether due to a disturbance or a change

in task goals, it should ideally be distributed across as many steps as possible.

Optimal strategy for an up-step: Speed up, lose speed, speed up

Optimization reveals that the ideal compensation strategy should actually overlap with the up-

step. Performing optimization for a wide range of number of compensation steps, a near-

optimum may be achieved with a relatively small N, with little advantage to taking more steps.

Moreover, these N steps should optimally be centered about the up-step, with $m = 0$. The best

strategy is not to gain time separately from the disturbance, but to modulate push-offs in

anticipation of it, and to continue doing so after encountering it. Here we describe the optimal

strategies in terms of speed or momentum fluctuations, push-off modulation, and cumulative

time gain.

Figure 4. Optimal strategies to compensate for an up-step, for (top row) varying number of steps N, and (bottom
row) varying step height b. Each row, from left to right: Speed v_i vs. time, push-off work vs. time, and cumulative
time gain vs. time. In top row, step height is fixed ($b = 0.075L$), and optimal solutions shown are for linearized
model, superimposed on nonlinear model solutions (dashed lines). In bottom row, both up- and down-step (positive

1 and negative b, respectively) solutions are shown for linearized model; $N = 9$. Optimal strategies are all centered
2 about the up-step ($m = 0$).
3

The key to reducing overall work is to ramp up speed (momentum) in a few steps immediately
preceding the disturbance (Fig. 4 top), pushing off hardest when stepping onto it. This anticipates
a sharp loss in speed atop the up-step, followed by a gradual return to nominal speed, with
approximately two-fold symmetric profile: symmetric in time about the up-step, and in speed
about nominal speed profile. The associated push-offs increase to a high peak centered on the
up-step itself (u_0), and otherwise remain close to nominal for all but a few steps surrounding that
step. The push-off profile is also approximately symmetric in time about the up-step, with the
exception of the Nth push-off, which serves a special purpose of matching the final boundary
conditions. In terms of cumulative time, the strategy reserves the few final steps to gain time in
anticipation of the time lost on and after the up-step. We found little difference to using
linearized vs. nonlinear dynamics (solid vs. dashed lines, respectively in Fig. 4 top), and therefore
use linearized dynamics for following analyses.

The compensations increase in magnitude with fewer compensatory steps (Fig. 4 top) or larger
up-step heights (Fig. 4 bottom). The extreme case is the minimum possible steps, $N = 2$, which
generally call for a large speed-up and a large peak push-off. Not surprisingly, the amplitudes of
both speed and push-off profiles increase with bump height. Moreover, the profiles scale
approximately linearly for small b. But regardless of the number of steps and the height to be
gained, the optimal compensation largely occurs within $\pm 2T_{\text{persist}}$ of the up-step.

What drives the optimal strategy is the unique opportunity afforded by the up-step. The model's
only energy losses are in collisions between leg and ground, and the collision onto the up-step
can be reduced substantially with an appropriately large push-off. This push-off (u_0) supplies
work that can help make up for the potential energy gain of the up-step, as well as an increase in
speed that can help make up for the large amount of time lost atop the up-step. In addition,
pushing off harder also reduces the succeeding collision loss. Such a reduction can also occur by
pushing off harder on level terrain, but this also increases walking speed, which is not generally

economical. But compensating for an up-step already requires speed to be elevated at some

point to gain time and accelerating up to and including the up-step causes a reduction in collision

for several steps, especially $i = 0$. Collision losses are also briefly reduced for a few following

steps, as still more acceleration is needed to regain nominal speed. The economy of accelerating

is further illustrated by optimal compensations for many steps (e.g. see Fig. 4 top, $N = 19$),

where the model actually gains slight advantage by slowing down slightly before the rapid speed-

up prior to the up-step.

We additionally observe that the optimal compensation for a down-step (Fig. 4 bottom), largely

mirrors that for an up-step. The actions largely scale with step height, so that negative heights

(down-steps, $b < 0$) entail slowing down rather than speeding up ahead of the disturbance and

reducing push-offs instead of increasing. Similarly, the cumulative time change is also nearly

opposite to an up-step, except with time being deliberately lost instead of gained, in anticipation

of the kinetic energy gained from stepping down. This scaling effect occurs about the nominal

speed, push-off, or time gain, and is not quite linear, owing to the nonlinear dynamics (equations

2 & 9). Nevertheless, scaling of compensation with step height b serves to roughly describe the

optimal solution for both up- and down-steps. Down-step strategies will be examined further in

another section below.

Earlier or later compensations are more costly

The optimality of centering the compensation about the up-step is illustrated by the costs of

doing otherwise (Fig. 5). Shifting the compensation earlier or later ($m < 0$ or $m > 0$, respectively)

and optimizing for each case, reveals increasing costs for total push-off work (Fig. 5a) and peak

push-off work (Fig. 5b).

There is still more cost if the compensation occurs entirely before or after the disturbance.

Compensating early with no overlap ($m < -\frac{(N+1)}{2}$) is essentially equivalent to a completely

separate time gain (Fig. 3), with an equivalent higher cost. Compensating later ($m > \frac{(N+1)}{2}$) also

tends toward the same higher cost, albeit with a longer transition. This is due to the transient

response after the disturbance, in which the total time loss accumulates over several persistence

times τ. Beginning the compensation during the transient therefore means that less time is to be

regained, and so the overall work cost only gradually increases towards an asymptote (Fig. 5a),

namely the cost for gaining time separately. The peak push-off also tends toward its

corresponding asymptote (Fig. 5b), albeit with elevated costs in some cases. But these transition

cases only reinforce the notion that the optimal compensation should distribute the

compensatory steps evenly before and after the up-step.

A large number of steps is not necessary to obtain near-optimal total work or peak push-off work.

Although both costs (Fig. 5c and d) decrease with greater N, the returns diminish rapidly. For

example, taking the minimum of two compensatory steps only takes about 12% more extra work

than for nine ($N = 9; b = 0.075L$). Beyond about two persistence times ($2T_{\text{persist}}$), the costs are

nearly indistinguishable. There is little to be gained from looking more than a few steps ahead.

The optimal strategy has considerable advantages over an isolated time gain. For the sample

case, the overall work is roughly half that for a completely separate time gain (compare minimum

with asymptote in Fig. 5a). There is also a high cost penalty for failing to anticipate the up-step at

all, and starting the compensation after a late push-off[17]. A similar but smaller advantage is

observed in peak push-off. However, there is a special case of a compensation that ends just

before the up-step ($m = -(N + 1)/2$ in Fig. 5b), where peak push-off is reduced, albeit at a slight

cost in total work.

It is interesting to note that the optimal strategy is generally less costly than the potential energy

of the up-step itself. One might expect a cost equal to the work for level nominal walking, plus

the work needed to lift the body up the step. But the optimal strategy actually gains advantage

from pushing off harder on the up-step, due to a lower collision loss as potential energy is gained.

In the sample case (Fig. 5), the overall added cost is about 58.5% of the potential energy gain,

and the peak push-off is about 71.5%.

a. Total extra work: Vary compensation timing

b. Peak push-off work: Vary compensation timing

c. Total extra work: Vary N

d. Peak push-off work: Vary N

Figure 5. Costs for optimal compensation strategies, as a function of compensation timing (shifting by m relative to up-step, see Fig. 1) and the number of compensation steps (N). (**a**) Total extra work vs. m, for N compensatory steps ($N = 9$, $b = 0.075L$). Total extra work is defined as the work in excess of N nominal steps. Filled symbols indicate cost for each m, lighter horizontal lines indicate compensation range of N steps. (**b**) Peak push-off work vs. m. (**c**) Total extra work vs. N, and (**d**) Peak push-off work vs. N for optimal compensation centered about up-step ($m = 0$). Also shown is the cost of an isolated time gain from nominal walking (Fig. 3), to regain time lost from an equivalent up-step ($b = 0.075L$, $t_{\text{gain}} = 2.48 \, g^{-0.5} L^{0.5}$) with no compensation. In (**a**) and (**b**), minima for both total and peak work occur at $m = 0$, where compensatory steps are distributed equally before and after the disturbance. Both costs also decrease for greater N. Also shown in (**a**) is the optimal strategy for recovering from an unanticipated up-step with a late push-off on the up-step.

Optimal strategies are self-similar despite parameter variations

The optimal strategies have similar speed profiles even for varied speed and step length (Fig. 6). Varying average step length while average walking speed fixed, it is apparent that longer steps call for compensations of similar shape, albeit in fewer steps and with reduced amplitude (Fig. 6a). This is accompanied by a reduction in persistence time with longer steps. The speed profiles are also similar to each other when increasing speed while keeping step length fixed (Fig. 6b),

although the amplitudes decrease, and persistence times increase. Thus, for a wide range of

parameter values, the compensation strategy always calls for speed up ahead of an up-step,

losing speed atop the up-step, and then recovering speed for several steps after it.

All of these effects may be summarized in terms of persistence time. Whether varying speed or

step length, the optimal compensation maintains approximately the same profile (albeit varying

amplitude) and takes place within about $\pm 2T_{\mathrm{persist}}$. In fact, including all parameter variations

considered thus far (e.g., number of steps, step height), the speed fluctuation profiles are nearly

the same when plotted in terms of persistence time (Fig. 6c). Persistence time is helpful for

summarizing the combined effects of a discrete, once-per-step collision, and the continuous-time

dynamics of the pendulum-like stance leg. It also plays a large role in the optimal compensation,

whether stepping up or down, or walking at a range of speeds and step lengths.

Figure 6. Effect of parameter variations on optimal strategies. (**a**) Optimal speed fluctuations for varying step length
(via leg angle α; constant average speed). (**b**) Optimal speed fluctuations for varying speed (via step frequency;
constant leg angle α). In both (**a**) and (**b**), $b = 0.075L$ and $N = 9$. (**c**) Speed fluctuations for all parameter variations
considered thus far, scaled by persistence time. Superimposed are variations in number of steps N (Fig. 4 top), step
height b (Fig. 4(bottom row), step length, and speed. All amplitudes are plotted relative to respective nominal speed,
and have been normalized to unity positive peak. Speed fluctuations for negative step heights are shown negated
to facilitate comparison.

Up- and down-step strategies are related due to time-symmetry

The optimal strategy to compensate for a down-step is a simple time-reversal of the up-step

strategy (Fig. 4 bottom). The speed profile for the down-step ($b < 0$) is the same as for the up-

step except with time running backwards. In fact, the push-off profile for a down-step is the same

as the time-reversed up-step profile, except using the up-step collisions as the down-step push-

offs. Similarly, the cumulative time gain is reversed in time, where down-step time loss is

equivalent to up-step time gain.

Time-reversal symmetry is explained by two basic principles. First, the walking dynamics have

time-symmetry. The push-off and collision impulses act the same and differ only in which leg they

apply to (trailing and leading leg, respectively), and in the order of execution. As a result, the

same dynamics may be played forward or backward in time, and the model either walks to the

right (as viewed from the side, Fig. 1), or to the left, respectively. For example, the push-off profile

for a down-step (e.g., $b = -0.05L$ in Fig. 4 bottom) may be flipped about the (vertical) work axis

(at $t = 0$) to yield the collision profile for an equivalent up-step ($b = 0.05L$).

The second principle is that minimizing push-offs and minimizing collision magnitudes yield the

same solution. This is because the boundary conditions enforced here call for nominal level

walking at the same speed, and thus no difference in kinetic energy between start and end. The

only energy difference is in the potential energy of the step (Mgb). The only energy sources and

sinks are the push-offs and collisions, and so the sum of all push-offs and collisions must equal

the potential energy, which is fixed for a given optimization problem. In addition, push-offs can

only perform positive work, and collisions negative work. Any solution that minimizes total push-

offs must therefore also minimize the total collision magnitudes.

Next is to apply time-symmetric dynamics to the optimization. The optimal strategy to traverse

an up-step with minimal push-off work (e.g., Fig. 4 top) may be played in reverse, to yield the

optimal strategy to traverse a down-step with minimal collision work magnitude. But minimizing

collision magnitude is the same as minimizing push-off, and so the same strategy, whether played

forward or backward in time, minimizes the respective push-offs for either direction.

Discussion

We explored the optimal strategy for anticipating and compensating for a single up- (or down-)

step on otherwise flat terrain. The uncompensated effect of the disturbance was characterized

in terms of a transient response with a loss of time and forward momentum, followed by an

asymptotic return to nominal walking. For planned tasks, it may be desirable to regain the lost

time, which was examined in two cases: one where time is regained by speeding up level walking,

and the other, optimal case, where the compensatory steps are distributed both before and after

the step. The analysis yields several conclusions regarding optimal compensations.

We found that there is a consistent pattern to optimally compensating for an up-step. It starts

several steps before the disturbance, with a smooth ramp-up in speed (or momentum) and push-

off that both peak just before contacting the up-step (Fig. 4 top, $i = 0$). This anticipates and pre-

compensates for the speed and time lost atop that step. This is followed by a recovery after the

disturbance, with another increase in speed (and decrease in push-off) over the same number of

steps. A similar pattern applies regardless of the number of compensation steps, the up-step

height, the walking speed, or the step length (see Fig. 6), but with appropriate scaling. For

example, the pattern's timing scales largely in accordance with the persistence time, which is

determined by the speed and step length (equation 10). The pattern's amplitude also scales, for

different heights (including down-steps), speeds, or step lengths, but relatively little with the

number of compensation steps. In fact, although there is always an advantage to taking more

steps, there is rather little advantage beyond $N = 3$ steps.

This strategy is also clearly superior to gaining time separately during level walking. For example,

the optimal compensation in five steps requires 51.3% less total extra work and 8.5% less peak

work ($N = 5, b = 0.075L$; see Fig. 5), while also having less sensitivity to the number of

compensation steps. This is because a time gain is largely a matter of walking faster, which entails

greater collision losses and therefore requires more positive push-off work. But the transient

introduced by the up-step allows opportunity to reduce some collision losses, particularly on the

up-step itself, as well as during the accelerations that occur both before and after it. Less energy

is lost to collisions when either accelerating or stepping upward, and the optimal compensation

takes full advantage of such opportunities.

The variations in optimal compensation are quite consistent with each other, in terms of

persistence time. Although the optimal compensation calls for varying push-off, it is nonetheless

heavily influenced by the effort cost for altering the uncompensated dynamics. This is evident

from the consistent similarity between compensations as a function of up-step height, number

of compensation steps, and nominal walking speed and step length (Fig. 6c). As a result, a general

rule of thumb is that the optimal compensation largely occurs within ±2 persistence times of the

up-step, and even the uncompensated transient response dies out within about 2 persistence

times following the up-step.

These results help to reinforce the benefits of looking ahead. Vision (or other imaging) is certainly

critical for spatial path planning, for example to determine feasible paths to avoid obstacles. But

the dynamics of legged locomotion are such that planning can also be performed dynamically, in

terms of momentum trajectories. Knowledge of upcoming terrain variations can allow not only

for economy, but also for surmounting obstacles that might otherwise exceed actuator

limitations. By properly leveraging these dynamics, our results show how it is possible to

surmount an up-step with less loss of time, less overall work, and reduced peak push-off

compared to the up-step's gravitational potential energy.

This has potential implications for control of legged robots. Perhaps the most straightforward

control for robots, and also the most important for stability, is state feedback control. Controlled

stability toward a reference gait might automatically regulate walking speed toward a nominal

reference value. However, state feedback would not normally be expected to make up for lost

time, unless time were included as an explicit goal, and perhaps included as an explicit state

(internal to the feedback controller). Feedback also responds after a disturbance, and would

therefore have to regain time already lost, which cannot be optimally economical (see separate

time gain, Fig. 3). In contrast, look-ahead would allow for feedforward compensation, and could

achieve near-optimal performance given at least two persistence times (or distances) of

foresight. Although such compensation could be stored as a scalable trajectory (e.g., Fig. 6c), an

alternative would simply be a model predictive control[18], where an optimal plan is continually

regenerated with a receding horizon, perhaps placed at least several persistence times ahead.

This might be compatible with other types of optimization methods already employed for some

legged robots[19–22].

Our analysis may suggest how humans negotiate small obstacles. Humans rely on vision to

identify curbs or height discrepancies in a sidewalk, and the resulting compensations may do

more than simply prevent tripping. It is possible that humans speed up prior to a stepping up a

curb, and perhaps slow down prior to stepping down a curb[23]. They appear to look several steps

ahead[24] and make quick, dynamically sensible decisions. Moreover, they appear to control not

only speed but also foot placement, while taking into account actuator limitations. It is unknown

how humans actually plan their momentum or whether they control it optimally. The optimal

strategies considered here might serve as a reference for comparison to humans.

The compensation strategies examined here are focused on pendulum-like walking. Our step-to-

step transition analysis treats the leg as relatively straight when it contacts ground. This may

apply well to relatively small up-steps, but not to larger ones. Humans normally flex the swing

knee at mid-stance, in part to gain ground clearance, and then extend again prior to ground

contact[25]. But swing knee extension does not seem to apply for larger inclines or typical stairs,

where there may be less forward momentum. Compensation strategies might be different for

larger up-steps, and especially for less pendulum-like gaits.

The present analysis has a number of additional limitations. Our model is a drastic simplification

of bipedal walking, without the ability to adjust step length or width. It also focuses mainly

impulsive step-to-step transitions, without modulation of the duration and time course of the

actual forces applied over a finite time. Indeed, there are insufficient degrees of freedom to

predict the multi-joint actions of more realistic legs, with multiple actuators whose individual

limitations may inform the appropriate compensation strategies. The model is also confined to

dynamical planning of push-offs and speed, assuming that the spatial path is already determined.

An improved model could allow for three-dimensional stepping[26,27] with multiple joints that allow

for leg compliance[28] and finite-duration step-to-step transitions, and might combine spatial and

dynamical planning into a single optimization problem. Such an optimization would be far more

complex, but perhaps within the realm of practical possibility.

Despite these limitations, there may be some general conclusions that may yet apply to more

complex models. Even with additional degrees of freedom, walking is often dominated by

forward momentum, and the step-to-step transition may dissipate significant energy, which must

then be restored with active work. It may therefore be advantageous to counter a step height

disturbance by gaining momentum several steps beforehand and continuing the compensation

past the disturbance for several steps thereafter. Furthermore, the appropriate compensation

range may described by a measure such as persistence time. Without planning, compensations

for uneven terrain may come with a relatively high cost in overall work, peak actuator demands,

and/or number of compensation steps. There may be considerable advantage to applying

optimization to the dynamics of legged locomotion, particularly on uneven terrain.

Methods

Model of walking

The walking model has rigid, pendulum-like legs whose ground collisions dominate the energetics

(Fig. 1a). It has a point-mass pelvis of mass M, atop massless legs taking fixed-length steps (Fig.

1b). The stance leg behaves like an underactuated, inverted pendulum during single support,

punctuated by the "step-to-step transition" to redirect the center-of-mass (COM) velocity

between steps[14]. This is accomplished with an active push-off along the trailing leg, followed

immediately by an inelastic heel-strike collision along the leading leg, both modeled as ideal

impulses in immediate succession (Fig. 1c). A full walking step therefore starts with a push-off

then a collision and followed by pendular stance phase that ends just before the next leg contacts

ground. Middle stance (mid-stance) is defined as the instant that the stance leg is upright within

the stance phase. When the terrain disturbance is encountered (Fig. 1d), we consider cases

where push-off occurs pre-emptively or late, relative to collision. In the optimal case (Fig. 1e),

terrain variations are sensed in advance, and pre-emptive push-offs are to be planned. We

previously examined a similar model[17], and found that failure to anticipate and perform push-off

pre-emptively, for example on uneven terrain, results in considerably poorer economy.

The model dynamics are briefly summarized as follows (detailed previously[17]): Each step has

index i with the disturbance located at $i = 0$ (Fig. 1d). Negative i therefore refer to the

preparatory steps beforehand, and positive to recovery steps thereafter. Each step begins just

before the step-to-step transition, with COM velocity v_i^- directed forward and downward as

dictated by the preceding step's stance phase. The ideal step-to-step transition starts with pre-

emptive push-off work u_i (in units of mass-normalized work) performed impulsively along the

trailing leg to redirect the COM velocity. Applying impulse-momentum (and normalizing by body

mass) yields an intermediate velocity of magnitude v_i^0,

$$v_i^0 = \sqrt{(v_i^-)^2 + 2u_i} \ . \tag{1}$$

19 This is followed immediately by the heel-strike collision along the leading leg, to yield post-

20 collision velocity v_i^+. Again applying impulse-momentum,

$$v_i^+ = v_i^- \cos 2\alpha + \sqrt{2u_i} \sin 2\alpha \ . \tag{2}$$

The single stance phase follows the step-to-step transition, and is modeled as an underactuated,

simple inverted pendulum. As a discrete measure of overall forward momentum, we use the mid-

stance velocity v_i (no superscript; see Fig. 1e), sampled when the leg is vertical and the COM

velocity is purely forward.

We treat steady, level walking as the nominal condition (Fig. 1c). Each begins and ends at the

same speed $v_i^- = v_i^+$. The nominal push-off work u_i offsets the collision work, so that [14],

4
$$u_i = \frac{1}{2}(v_i^-)^2 \tan^2 \alpha. \tag{3}$$

6   The up- or down-step disturbs steady walking (Fig. 1d). Its height b (positive for up-steps,

7   negative for down-steps) causes the preceding step ($i = -1$) to end with different leg angles

8   from nominal. For simplicity, we will typically refer to up-steps alone, and treat down-steps as a

9   straightforward generalization there-of, unless otherwise discussed. For a given height b and step

10   length S, we define the angular disturbance as δ_i,

12
$$\delta_0 = \sin^{-1}\frac{b}{S}, \; \delta_i = 0 \text{ for } i \neq 0 , \tag{4}$$

where the angle is zero for all non-disturbance steps.

We expect that it is helpful to detect the up-step ahead of time, to allow push-off to occur pre-

emptively, that is, before the collision. Pre-emptive push-off is more economical both on the level

[14] and on the up-step[17], because it reduces the subsequent collision loss. If the up-step is

completely unanticipated, the push-off might occur late. If so, the leading leg collision first

redirects COM velocity along a new pendular arc. We refer to the work of a late push-off as u_0^+

(with the plus sign '+' indicating the post-collision timing), performed impulsively to increase

speed along that new arc:

24
$$\text{Late push-off: } v_0^+ = \sqrt{(v_0^- \cos 2\alpha)^2 + 2u_0^+} \text{ for } i = 0 . \tag{5}$$

We treat the late push-off as of nominal amount, as if the nominal energy were stored elastically

as observed in humans[29,30], but released late. The next step will then have substantially reduced

speed v_0^+ and slower step time τ_0.

The inverted pendulum stance phase follows the step-to-step transition. The step time τ_i is

defined as the time for the stance leg angle θ to move from initial to final angles ($\alpha + \delta_i$ and

$-\alpha + \delta_{i+1}$, respectively). Using the linearized dynamics,

5
$$\tau_i = \log \frac{\alpha - \delta_{i+1} + \sqrt{\left(v_i^+\right)^2 - 2\alpha(\delta_i + \delta_{i+1}) + \delta_{i+1}^2 - \delta_i^2}}{v_i^+ - \alpha - \delta_i}. \tag{6}$$

7 Solving the equation of motion with the step time, the velocity at end of stance v_{i+1}^-, or

8 equivalently the beginning of the next step-to-step transition can be found as:

10
$$v_{i+1}^- = \frac{1}{2}\left(e^{-\tau_i}(v_i^+ - \alpha - \delta_i) + e^{\tau_i}(v_i^+ + \alpha + \delta_i)\right). \tag{7}$$

We chose nominal parameters to correspond to typical human walking. A person with leg length

L of 1 m may typically walk at 1.5 m/s, with step length of 0.79 m and step time of 0.53 s (from

anecdotal observations). Using dynamic similarity, parameters and results may be expressed in

terms of body mass M, gravitational acceleration g, and L as base units. The corresponding

model parameters are angle $\alpha = 0.41$, push-off $U = 0.0342\ MgL$, step time $T = 1.66\ g^{-0.5}L^{0.5}$,

and pre-collision speed $V^* = 0.601\ g^{0.5}L^{0.5}$, where capital letters indicate nominal values for u_i,

τ_i, and v_i^-, respectively. We also refer to a nominal speed $V = 0.44\ g^{0.5}L^{0.5}$ for mid-stance

speed v_i. We considered a range of up-step heights, for example $b = 0.075L$, equivalent to

about 7.5 cm for a human.

Although most of this study relied on the linearized dynamics of equations (6-7), we also

performed a subset of simulations with fully nonlinear dynamics to test the accuracy of this

approximation (Fig. 4).

Optimal Control Formulation

We used optimization to determine the push-off sequence that modulates momentum to most

economically negotiate a single disturbance. The objective was to minimize the total positive

work of N consecutive push-offs of amount u_i, subject to constraints to depart from and then

regain nominal walking with no loss of time or speed compared to steady, level gait. The timing

of this compensation was found to affect overall economy and was therefore explored by shifting

the N modulated steps earlier or later relative to the disturbance. The optimal strategies were

explored with parameter variations in compensatory steps N, step height b, nominal speed V,

and compensation timing m.

The N compensatory steps were nominally centered about the up-step. It is convenient to

consider odd N, so that the single up-step at $i = 0$ is surrounded by an equal amount of

anticipatory steps before, and recovery steps after. The parameter m (Fig. 1e) shifts these steps

later ($m > 0$) or earlier ($m < 0$). Again for odd N, the compensation steps range from "start" $=$

$-\frac{N-1}{2} + m$ to "end" $= \frac{N-1}{2} + m$. The speed constraint states that walking speed begins at and

returns to nominal, level walking. The time constraint requires that the total time for stepping

onto and recovering from the uneven terrain, be equal to the nominal time to walk the same

number of level steps.

The optimal policy π (sequence of push-offs $u_{\text{start}}, \dots, u_{\text{end}}$, all constrained to be non-negative)

is:

$$\pi^* = \arg\min_{\pi} \sum_{i=\text{start}}^{\text{end}} u_i \tag{8}$$

20   Subject to:

22   Initial speed: $v_{\text{start}}^{-} = V^*$

24   Final speed: $v_{\text{end}}^{+} = V^*$

26   Time: $\sum_{i=\text{start}}^{\text{end}} \tau_i = N \cdot T$

1   Dynamics: Step-to-step transition equation (2)

2   Stance phase equation (6), equation (7)

We next define a persistence time for the hybrid dynamics of discrete step-to-step transitions

and continuous-time pendulum dynamics. On level ground and with unmodulated push-offs,

walking speed converges exponentially toward nominal with each discrete step. The step-to-step

eigenvalue $\cos 2\alpha$ (about 0.68 for nominal gait; equation 2) determines this convergence. This

may be combined with the continuous-time step period T to yield an overall decay with time

constant T_{persist}:

$$\frac{\Delta v_{i+1}}{\Delta v_i} = \cos 2\alpha = e^{-\frac{T}{T_{\text{persist}}}} \tag{9}$$

where Δv_i refers to the deviation from nominal mid-stance speed at step i. Solving for

persistence time,

$$T_{\text{persist}} = -\frac{T}{\log_e \cos 2\alpha}\ . \tag{10}$$

An analogous persistence distance may be found by dividing T_{persist} by nominal speed.

Persistence time (or distance) may be interpreted as the time (or distance) required for a

disturbance response to decay to $e^{-1} \approx 37\%$ of its peak amplitude. It helps to place an

expectation on optimal recovery from a disturbance. With active control of push-off, it is of

course possible to change the disturbance response substantially. But when optimizing for work

or energy, we do not expect the response to be far faster than uncompensated, because that

would entail a high effort cost. Nor do we expect the response to be slower than the

uncompensated case, which is already stable. We therefore expect that optimal compensation

responses should be somewhat faster than uncompensated and should therefore decay within

no more than a few persistence times.

References

1. Hobbelen, D. G. E. & Wisse, M. A disturbance rejection measure for limit cycle walkers: The
gait sensitivity norm. *IEEE Trans. Robot.* **23**, 1213–1224 (2007).
2. Park, H. W., Sreenath, K., Ramezani, A. & Grizzle, J. W. Switching control design for
accommodating large step-down disturbances in bipedal robot walking. in *2012 IEEE*
International Conference on Robotics and Automation, ICRA 2012 45–50 (Institute of
Electrical and Electronics Engineers Inc., 2012). doi:10.1109/ICRA.2012.6225056
3. Alexander, R. M. Energy-saving mechanisms in walking and running. *J. Exp. Biol.* **160**, 55–69
(1991).
4. Kuo, A. D., Donelan, J. M. & Ruina, A. Energetic consequences of walking like an inverted
pendulum: step-to-step transitions. *Exerc Sport Sci Rev* **33**, 88–97 (2005).
5. Byl, K. & Tedrake, R. Approximate optimal control of the compass gait on rough terrain. in
IEEE International Conference on Robotics and Automation, 2008, 1258–1263 (2008).
6. Manchester, I. R., Mettin, U., Iida, F. & Tedrake, R. Stable Dynamic Walking over Uneven
Terrain. *Int J Rob Res* **30**, 265–279 (2011).
7. Saglam, C. O. & Byl, K. Quantifying and optimizing robustness of bipedal walking gaits on
rough terrain. in *Robotics Research* 235–251 (Springer, 2018).
8. Bhounsule, P. A., Cortell, J. & Ruina, A. Design and control of ranger: an energy-efficient,
dynamic walking robot. in *Adaptive Mobile Robotics* 441–448 (WORLD SCIENTIFIC, 2012).
doi:10.1142/9789814415958_0057
9. Collins, S., Ruina, A., Tedrake, R. & Wisse, M. Efficient bipedal robots based on passive-
dynamic walkers. *Science* **307**, 1082–1085 (2005).
10. Manchester, I. R., Mettin, U., Iida, F. & Tedrake, R. Stable dynamic walking over rough
terrain: theory and experiment. in *IN PROCEEDINGS OF THE INTERNATIONAL SYMPOSIUM*
ON ROBOTICS RESEARCH (ISRR2009 (2009).
11. Westervelt, E. R., Grizzle, J. W. & Koditschek, D. E. Hybrid zero dynamics of planar biped
walkers. *IEEE Trans. Autom. Control* **48**, 42–56 (2003).
12. Wisse, M. Three additions to passive dynamic walking: actuation, an upper body, and 3d
stability. *Int J Humanoid Robot.* **2**, 459–478 (2005).
13. Garcia, M., Chatterjee, A., Ruina, A. & Coleman, M. The simplest walking model: Stability,
complexity, and scaling. *ASME J. Biomech. Eng.* **120**, 281–288 (1998).
14. Kuo, A. D. Energetics of actively powered locomotion using the simplest walking model. *J.*
Biomech. Eng. **124**, 113–20 (2002).
15. McGeer, T. Passive dynamic walking. *Int. J. Robot. Res.* **9**, 62–82 (1990).
16. Donelan, J. M., Kram, R. & Kuo, A. D. Mechanical work for step-to-step transitions is a major
determinant of the metabolic cost of human walking. *J. Exp. Biol.* **205**, 3717–27 (2002).
17. Darici, O., Temeltas, H. & Kuo, A. D. Optimal regulation of bipedal walking speed despite an
unexpected bump in the road. *PLOS ONE* **13**, e0204205 (2018).
18. Mayne, D. Q. Model predictive control: Recent developments and future promise.
Automatica **50**, 2967–2986 (2014).
19. Wieber, P. Trajectory Free Linear Model Predictive Control for Stable Walking in the
Presence of Strong Perturbations. in *2006 6th IEEE-RAS International Conference on*
Humanoid Robots 137–142 (2006). doi:10.1109/ICHR.2006.321375

20. Dimitrov, D., Wieber, P., Ferreau, H. J. & Diehl, M. On the implementation of model predictive control for on-line walking pattern generation. in *2008 IEEE International Conference on Robotics and Automation* 2685–2690 (2008). doi:10.1109/ROBOT.2008.4543617

21. Farshidian, F., Jelavic, E., Satapathy, A., Giftthaler, M. & Buchli, J. Real-time motion planning of legged robots: A model predictive control approach. in *2017 IEEE-RAS 17th International Conference on Humanoid Robotics (Humanoids)* 577–584 (2017). doi:10.1109/HUMANOIDS.2017.8246930

22. Posa, M., Kuindersma, S. & Tedrake, R. Optimization and stabilization of trajectories for constrained dynamical systems. in *2016 IEEE International Conference on Robotics and Automation (ICRA)* 1366–1373 (2016). doi:10.1109/ICRA.2016.7487270

23. Darici, O., Temeltas, H. & Kuo, A. D. Anticipatory speed changes for optimal human walking on uneven terrain. in *XXVI Congress of the International Society of Biomechanics* (2017).

24. Matthis, J. S. & Fajen, B. R. Humans exploit the biomechanics of bipedal gait during visually guided walking over complex terrain. *Proc. Biol. Sci.* **280**, 20130700 (2013).

25. Wu, A. R. & Kuo, A. D. Determinants of preferred ground clearance during swing phase of human walking. *J. Exp. Biol.* jeb.137356 (2016). doi:10.1242/jeb.137356

26. Grizzle, J. W., Chevallereau, C., Sinnet, R. W. & Ames, A. D. Models, feedback control, and open problems of 3D bipedal robotic walking. *Automatica* **50**, 1955–1988 (2014).

27. Rebula, J. R., Ojeda, L. V., Adamczyk, P. G. & Kuo, A. D. The stabilizing properties of foot yaw in human walking. *J. Biomech.* **53**, 1–8 (2017).

28. Geyer, H., Seyfarth, A. & Blickhan, R. Compliant leg behaviour explains basic dynamics of walking and running. *Proc. R. Soc. B-Biol. Sci.* **273**, 2861–2867 (2006).

29. Fukunaga, T. *et al.* In vivo behaviour of human muscle tendon during walking. *Proc. Biol. Sci.* **268**, 229–233 (2001).

30. Zelik, K. E., Huang, T.-W. P., Adamczyk, P. G. & Kuo, A. D. The role of series ankle elasticity in bipedal walking. *J. Theor. Biol.* **346**, 75–85 (2014).

Acknowledgements

This work is supported by NSF DGE 0718128, the ONR ETOWL program, NIH AG030815, the Dr. Benno Nigg Research Chair (University of Calgary), and NSERC (Natural Sciences and Engineering Research Council of Canada) Discovery program and Canada Research Chair (Tier 1) program.

Author Contributions

O.D. performed the simulations and generated the figures. O.D. and A.D.K. wrote the manuscript. A.D.K. also revised the manuscript and the figures. H.T. reviewed the manuscript.

Additional Information

Competing Interests: The authors declare no competing interests.

Figure Legends

Figure 1. Simple model of walking over a single up- (or down-) step. (**a**) Body center of mass (COM) is a point mass

carried atop stance leg acting as an inverted pendulum, encountering step of height b. (**b**) Model has mass M at

pelvis, with massless legs of length L, gravitational acceleration g, and a fixed step length S, also described by inter-

leg angle 2α. Stance leg angle is measured with angle θ as shown. (**c**) Level nominal step-to-step transition, where

COM velocity is redirected from forward-and-downward v_i^- to forward-and-upward v_i^+, first with active, impulsive

trailing leg push-off (PO), followed by inelastic, impulsive, leading leg collision (CO). (**d**) The up-step occurs on step

$i = 0$, with two cases: pre-emptive and late push-off, which both perform positive work (u_0 and u_0^+, respectively)

but earlier or later than collision. (**e**) Optimization is performed to modulate N push-offs to minimize their total work

while accommodating the up-step and taking the same time as nominal, level walking at speed V. The N steps are

nominally centered on the up-step for equal anticipation and recovery. We also consider cases where the

compensatory steps are shifted by m steps relative to obstacle. Up-steps are denoted by $b > 0$; down-steps by $b <$

0.

Figure 2. Effect of an uncompensated up-step. (**a**) Speed fluctuations vs. time, for an up-step at time 0 with constant

push-off. Model experiences transient disturbance from nominal speed due to up-step, with smaller effect if push-

off occurs pre-emptively as opposed to late. Each dot (filled symbol) indicates a discrete step, with speed v_i sampled

at mid-stance (see Fig. 1e). (**b**) Cumulative time gain vs. time shows accumulating effect of speed loss, with

asymptote towards a total time loss (negative time gain). (**c**) Total time gain vs. up-step height b for various nominal

walking speeds, with greater bumps causing greater loss of time, and smaller effect for faster nominal speeds. Also

shown are effects of late push-off (unfilled symbols). Up-step height $b = 0.025L$, nominal mid-stance velocity $V =$

$0.44g^{-0.5}L^{0.5}$. Conditions are equivalent to a human walking at 1.5 m/s, encountering an up-step of 2.5 cm.

Figure 3. Optimal strategies to gain time during level walking, separate from any disturbance, for (top row:) varying

amounts of time t_{gain}, and (bottom row:) varying number of steps N. Each row, from left to right: Speed fluctuations

vs. time, push-off work vs. time, and cumulative time gain vs. time, relative to nominal (each step denoted by filled

symbol). Parameter values are $N = 9$ steps for top row, $t_{\text{gain}} = 0.5$ for bottom row. Filled dot symbols indicate

steps. Unfilled symbols denote large push-offs that entail momentary aerial phases or even running for several steps;

maximum time gain thresholds to avoid such cases are shown in (top most right).

Figure 4. Optimal strategies to compensate for an up-step, for (top row) varying number of steps N, and (bottom

row) varying step height b. Each row, from left to right: Speed v_i vs. time, push-off work vs. time, and cumulative

time gain vs. time. In top row, step height is fixed ($b = 0.075L$), and optimal solutions shown are for linearized

model, superimposed on nonlinear model solutions (dashed lines). In bottom row, both up- and down-step (positive

and negative b, respectively) solutions are shown for linearized model; $N = 9$. Optimal strategies are all centered

about the up-step ($m = 0$).

Figure 5. Costs for optimal compensation strategies, as a function of compensation timing (shifting by m relative to

up-step, see Fig. 1) and the number of compensation steps (N). (**a**) Total extra work vs. m, for N compensatory steps

($N = 9$, $b = 0.075L$). Total extra work is defined as the work in excess of N nominal steps. Filled symbols indicate

cost for each m, lighter horizontal lines indicate compensation range of N steps. (**b**) Peak push-off work vs. m. (**c**)

Total extra work vs. N, and (**d**) Peak push-off work vs. N for optimal compensation centered about up-step ($m = 0$).

Also shown is the cost of an isolated time gain from nominal walking (Fig. 3), to regain time lost from an equivalent

up-step ($b = 0.075L$, $t_{\text{gain}} = 2.48\ g^{-0.5}L^{0.5}$) with no compensation. In (**a**) and (**b**), minima for both total and peak

work occur at $m = 0$, where compensatory steps are distributed equally before and after the disturbance. Both costs

also decrease for greater N. Also shown in (**a**) is the optimal strategy for recovering from an unanticipated up-step

with a late push-off on the up-step.

Figure 6. Effect of parameter variations on optimal strategies. (**a**) Optimal speed fluctuations for varying step length

(via leg angle α; constant average speed). (**b**) Optimal speed fluctuations for varying speed (via step frequency;

constant leg angle α). In both (**a**) and (**b**), $b = 0.075L$ and $N = 9$. (**c**) Speed fluctuations for all parameter variations

considered thus far, scaled by persistence time. Superimposed are variations in number of steps N (Fig. 4 top), step

height b (Fig. 4 bottom), step length, and speed. All amplitudes are plotted relative to respective nominal speed, and

have been normalized to unity positive peak. Speed fluctuations for negative step heights are shown negated to

facilitate comparison.