# ConnectedReads: machine-learning optimized long-range

genome analysis workflow for next-generation sequencing

Chung-Tsai Su[1,*], Sid Weng[1], Yun-Lung Li[1], and Ming-Tai Chang[1]

1. ATGENOMIX INC.

*Corresponding author: chungtsai.su@atgenomix.com

# Abstract

Current human genome sequencing assays in both clinical and research settings

primarily utilize short-read sequencing and apply resequencing pipelines to

detect genetic variants. However, theses mapping-based data analysis pipelines

remains a considerable challenge due to an incomplete reference genome,

mapping errors and high sequence divergence. To overcome this challenge, we

propose an efficient and effective whole-read assembly workflow with

unsupervised graph mining algorithms on an Apache Spark large-scale data

processing platform called ConnectedReads. By fully utilizing short-read data

information, ConnectedReads is able to generate assembled contigs and then

benefit downstream pipelines to provide higher-resolution SV discovery than

that provided by other methods, especially in high diversity against reference

and N-gap regions of reference. Furthermore, we demonstrate a cost-effective

approach by leveraging ConnectedReads to investigate all spectra of genetic

changes in population-scale studies.

# Background

Whole-genome sequencing (WGS) is increasingly used in biomedical research,

clinical, and personalized medicine applications to identify disease- and drug-

associated genetic variants in humans, all with the goal of advancing precision

medicine (*1*). At present, next-generation sequencing (NGS, also called short-

read sequencing (SRS)) is a well-established technology used to generate

whole-genome data due to its high throughput and low cost (*2*). Resequencing,

especially of human samples, is one of the popular applications of NGS. This

process maps raw reads against a reference genome and determines all kinds of

genomic variations, including single nucleotide polymorphisms (SNPs) and

indels as well as genetic rearrangements and copy-number variants (CNVs) (*3*).

However, a fundamental flaw in the resequencing pipeline is that it ignores the

correlation between sequence reads; thus, resequencing does not fully and

properly utilize sequence data and may generate inconsistent alignments, which make variant calling, especially structural variant (SV) calling, more complicated (*4, 5*). Since the human reference genome is incomplete and contains many low-complexity regions, assembling sequence reads without reference bias would be a proper way to overcome the above challenges. Nonetheless, assembly-based approaches for WGS data suffer from several computational challenges, such as high computing resource requirements and long turnaround times.

In this article, we propose an efficient whole-read assembly workflow with unsupervised graph mining algorithms on an Apache Spark large-scale big data processing platform called ConnectedReads. By leveraging the in-memory cluster computing framework of Apache Spark (*6*), ConnectedReads takes less than 20 hours to process 30-fold human WGS data and generates corresponding long assembled contigs for downstream analysis, such as read mapping, variant calling or phasing. The spec. of cluster and the execution time for each step of ConnectedReads are described in the method session. To evaluate the data correctness of ConnectedReads, we use 68 high-confidence

insertions in the NA12878 sample detected by svclassify (*7*). To demonstrate

the influence of reference incompleteness, mapping error and high sequence

divergence on NGS data analysis, three public available samples from different

populations are used. Through ConnectedReads, we are able to investigate

unique non-reference insertions (UNIs) and non-repetitive, non-reference

(NRNR) sequences from population datasets (*8, 9*). Furthermore, high

resolution for SVs are provided by leveraging ConnectedReads, especially on

breakpoints of insertions. In conclusion, ConnectedReads optimizes NGS reads

to generate long assembled contigs, not only reducing mapping error but also

benefit the downstream data analysis pipelines.

# Results

# Data preparation

To exemplify the challenges of WGS data analysis mentioned above and assess

the utility of ConnectedReads, three WGS datasets from three different ethnic

groups were selected from publicly available databases, as listed in Table 1,

including NA12878 of European ancestry, NA24694 of Asian ancestry, and

NA19240 of African ancestry. In addition, the samples were around 30X and sequenced by three different Illumina platforms, namely, the NovaSeq 6000 (NA12878), HiSeq 2500 (NA24694), and HiSeq X Ten (NA19240) platforms. Therefore, we believe that these datasets are representative of the majority of WGS data on cohort datasets and national bio-bank projects.

**Table 1.** Description of WGS datasets

| Sample | Platform | Coverage | Read Length | Description | Source |
|--------|----------|----------|-------------|-------------|--------|
| NA12878 | NovaSeq 6000 | 30X (313,716,127 read pairs) | 151 | HG001 (Population: CEU) | *a |
| NA24694 | HiSeq 2500 | 30X (311,220,694 read pairs) | 148 | HG006, Father of The Han Chinese GIAB Trio | *b |
| NA19240 | HigSeq X Ten | 35X (376,862,646 read pairs) | 151 | Yoruba(Nigeria) (Population: YRI) | *c |

Data sources:

[a] https://www.ebi.ac.uk/ena/data/view/ERR2438055

[b] https://www.ncbi.nlm.nih.gov/sra/SRX1388455

[c] https://www.ncbi.nlm.nih.gov/sra/SRX4637790

# Evaluations

The results for the datasets in Table 1 obtained by applying the ConnectedReads workflow with default settings are listed in Table 2. Comparing to SRS data in Table 1, ConnectedReads is clearly able to reduce the number of contigs and

total base pairs by more than 96% and 87%, respectively. Take NA12878 for examples, 313, 716, 127 read pairs with length of 151 are transformed to 16,348,524 contigs (Reduction rate: 97.4%). In addition, the total BPs is reduced from 94,742,270,354 on SRS to 10,466,069,046 on ConnectedReads (Reduction Rate: 88.9%). Since ConnectedReads generates assembled contigs based on paired-end or barcode information, any two contigs would not be assembled together without sufficient supports for paired-end information or overlaps. Although ConnectedReads aims to construct more accurate assembled contigs rather than longer ones without haplotypes, it is usually able to construct several contigs of more than 30 Kbps. In addition, there are 1,402,511, 1,224,389 and 2,082,886 contigs of >=1 Kbps for NA12878, NA24694 and NA19240, respectively. Furthermore, the length of contigs is strongly correlated with coverage and read length. The deeper the coverage is, the longer the contigs that can be generated are.

**Table 2.** Description of the contigs of three datasets generated by

ConnectedReads.

| Sample | NA12878 | NA24694 | NA19240 |
|---|---|---|---|
| Number of contigs | 16,348,524 | 18,900,370 | 18,261,647 |
| Total base pairs (bps) | 10,466,069,046 | 9,925,886,082 | 14,093,570,587 |
| Average length | 640 | 525 | 772 |
| Longest contig | 37,619 | 33,904 | 32,145 |
| # of singletons (<=151) | 8,351,671 | 11,305,117 | 8,355,394 |
| >=1 Kbps | 2,899,483 | 2,470,630 | 4,487,568 |
| >=2 Kbps | 1,402,551 | 1,224,389 | 2,082,886 |
| >=5 Kbps | 263,878 | 256,178 | 277,357 |

ConnectedReads offers two advantages for downstream analysis. One is

mapping recovery, and the other is SV detectability. Both of these advantages

are described comprehensively by the following experimental results and case

studies.

First, mapping recovery is the best way to demonstrate the advantage of

ConnectedReads. According to the evolution of NGS technology in recent years,

longer reads can reduce two kinds of mapping errors, namely, false mapping

and uncovered regions based on the reference genome (*10*). However, it is hard

to determine whether a mapping record is falsely aligned because of several

complicated situations, such as sequencing errors, an incomplete reference

genome, high sequence divergence and SVs (*5*). Therefore, the recovery rate is

a proper measurement for evaluating the performance of ConnectedReads and

SRS. Mapping recovery means all of positions on human reference is not

mapped by any SRS data but able to be covered by ConnectedReads data. For

example, the uncovered regions of the reference genome means that there is no

short reads mapped by using Genome Analysis Toolkit (GATK) Best Practices

(i.e., BWA-MEM) but contigs of ConnectedReads are mapped on some of the

regions by using minimap2 (*11*). These regions are called as mapping recovery.

In terms of NA12878 mapping recovery, as illustrated in 0, there is a 15%-90%

recovery rate for each chromosome on hg38 (excluding chrY). For example,

chr1 has 319,018 uncovered bps with SRS, but 135,253 bps (42.4%) can be

recovered by ConnectedReads. The best recovery rate (89.6%) is on chr21, and

the worst recovery rate (15.4%) is on chr17. Large regions are often recovered

when large deletions occur. Overall, ConnectedReads is able to reconstruct the

mapping information for uncovered regions in the reference genome by using

SRS data, and it may be the best candidate complementary to Illumina short-

read data.

Second, SV detection remains a challenge in SRS (*12*). Using ConnectedReads

technology will significantly mitigate this challenge because ConnectedReads

has the similar advantage as long-read sequencing (LRS) from Nanopore and

PacBio. The longer the read is, the more correct the mapping result is and the

more easily SVs can be detected. Fig. 2 shows the numbers of insertions and

deletions identified in NA12878. The statistical method is simply based on a

CIGAR string generated by minimap2. When the threshold of mapping quality

(MAPQ) is increased, fewer insertions and detections are identified. Since

several alignment records with an MAPQ of 0 were falsely mapped in our

investigation, the threshold of MAPQ was set to 1 in the following experiments

to balance the precision and sensitivity of SV detection. In addition, several

recent studies have revealed that every human genome has approximately

20,000 SVs that span at least 10 million bps (*13, 14*). ConnectedReads identifies

21,855 SVs, and the number of SVs is similar to that obtained in previous

studies (*13, 14*).

Furthermore, an interesting phenomenon on Fig. 3 is observed when the

insertions and deletions shown in Fig. 2 are sorted by length. Based on the 1000

Genomes Project and several studies (*15, 16*), the number of SVs decreases as

the length of the SVs increases. Therefore, the majority of the SVs are small

indels (<50 bps). Then, the trend of the distribution slightly decreases as the

length of the SVs increases, except for the peak at 250-300 bps. The reason is

due to abundant Alu elements whose body lengths are approximately 280 bases

(*17*). In addition, several studies have reported this phenomenon when using

PacBio LRS (*13*). Therefore, ConnectedReads is able to complement SRS in not

only mapping recovery but also SV detection.

# Comparison against a high-confidence truth set

If ConnectedReads generates a mis-assembled contig, then it should be observed via

the CIGAR string after applying any read mapping tools. For example, two unrelated

unitigs are assembled together, the contig usually is marked as large soft- or hard-

clipping in its CIGAR string. In addition, insertions and deletions in the CIGAR string are

the candidates should be investigated in the evaluation process. To evaluate the data

correctness of ConnectedReads, the SV dataset collected by svclassify (*7*) is used.

Since insertions are more difficult to be detected by most of existing SV callers

than deletions, the 68 high-confidence insertions from svclassify are chosen as

the insertion dataset in this paper. In this paper, we develop a naïve Insertion

Caller, named CIGAR-based Insertion Caller for ConnectedReads (CCC-INS),

which is based on CIGAR string generated by minimap2 with default settings.

Additionally, two well-known variant callers are selected for performance

evaluation: pbsv for PacBio LRS and FermiKit (18) for Illumina SRS. Both

FermiKit and ConnectedReads adopt assembly-based approaches to prevent

reference bias. The results for the insertion benchmark data are listed in Table

3. PacBio LRS data are usually able to cover the whole region of most SVs, so

pbsv achieves a 91.2% detection rate. However, FermiKit detects only 28

insertions since it aims to construct the complete sequence for each insertion.

Since most WGS samples are sequenced by SRS and have a coverage of

approximately 30X, it is quite difficult to reconstruct the complete sequence

(including novel insertions) through any computational approaches. Therefore,

we adjusts the naïve insertion caller CCC-INS to relax the criterion of detection

in three levels, including completely constructed (CC), partially constructed

(PC), and potentially detectable (PD). The CCC-INS$^{CC+PC}$ caller has a strict

criterion because it is based on both completely constructed and partially

constructed insertions. The CCC-INS$^{CC+PC+PD}$ caller has a lenient criterion

because it accommodates all three levels of detection. As shown in Table 3, CCC-

INS$^{CC+PC}$ and CCC-INS$^{CC+PC+PD}$ achieve 86.8% and 95.6% detection rates,

respectively, indicating that using ConnectedReads is able to achieve the same

level of performance as PacBio LRS. Therefore, the above experimental results

give us confidence to investigate SVs in population-scale data.

**Table 3.**    Long insertion dataset in NA12878 from svclassify

| Method | Detection rate (%) | Number of insertions with complete sequences |
|---|---|---|
| pbsv (PacBio)* | 91.2 | 62 |
| FermiKit | 41.2 | 28 |
| CCC-INS$^{CC+PC}$ | 86.8 | 32 |
| CCC-INS$^{CC+PC+PD}$ | 95.6 | 32 |

*The result of pbsv from NIST's Genome in a Bottle (GIAB) project is available at ftp://ftp-

trace.ncbi.nlm.nih.gov/giab/ftp/data/NA12878/analysis/PacBio_pbsv_05212019/HG001_GRCh38.pbs

v.vcf.gz

Therefore, leveraging ConnectedReads is competent at SV detection, especially

for insertions. Then, the next question that we are interested in is how many

unique SVs exist in each population. According to Kehr's findings (in Table S4

of (9)), there are 372 SVs in all Icelanders. After removing redundant SVs and

merging adjacent SVs, 248 distinct SVs are represented as the second set of SV

dataset in this paper. We are eager to know whether these 248 SVs are unique

to Icelanders or shared by all populations. Therefore, the three samples from

different continents shown in Table 1 are processed by ConnectedReads, and

then minimap2 is used to generate alignment records for their ConnectedReads

contigs. Then, we manually evaluate whether the 248 SVs exist in the three

samples and the results are listed in Table 4. More than 95% of the common

SVs in all Icelanders are also found in the three different populations, and only

one SV cannot be found in any of the three given samples. It is obvious that

most common SVs in Icelanders are not unique to Icelanders. Furthermore,

approximately 40 SVs should not be classified as SVs in the given samples

because they are composed of several adjacent small variants and incorrectly

detected as SVs. More details will be discussed in the next section. It is believed

that ConnectedReads provides us with higher resolution to observe SVs than

some of SV calling tools.

**Table 4.**     The common SV dataset from all Icelanders.

| Sample | Race | Detected | | Undetected | |
|---|---|---|---|---|---|
| | | SV | Multiple small variants | Not found | Uncovered |
| NA12878 | Caucasian | 204 | 39 | 2 | 3 |
| NA24694 | Asian | 198 | 40 | 2 | 8 |
| NA19240 | African | 205 | 39 | 1 | 3 |

# Discussion

# Accuracy of insertion length

In the above section, ConnectedReads not only was complementary to the resequencing pipeline of SRS in terms of uncovered regions but also was able to benefit SV discovery, especially for long insertions. ConnectedReads and PacBio adopt HG38, but svclassify uses HG19. For comparison, the insertions provided by Spiral Genetics are converted from HG19 to HG38 by using UCSC LiftOver. Then, all of SVs from different source or methods are comparable since they are based on the same genome coordinate. As shown in Table 3, at least 85% of long insertions can be detected by using ConnectedReads followed by minimap2 and CCC-INS, and 32 insertions are completely constructed. As shown in Fig. 4, most of the insertions identified by ConnectedReads are almost

the same as those identified by Spiral Genetics and PacBio. 24 of 32 insertions

identified from ConnectedReads have identical lengths with PacBio. In addition,

the remaining insertions have only slight differences. Therefore,

ConnectedReads with SRS can construct complete and accurate insertion

sequences as well as PacBio LRS can.

# Granularity of SV detection

Another interesting phenomenon shown in Table 4 caught our attention.

Although common SVs in Icelanders exist in different populations,

approximately 40 of the SVs should not be classified as SVs ($\geq$ 50 bps) because

they are composed of multiple adjacent small variants, as illustrated in Fig. 5.

Fig. 5(a) and Fig. 5(b) contain only 13 SNPs and 13 deletions spanning 60 bps

and 80 bps, respectively. When several adjacent variants occur in any

individual, most mapping tools have limited information with which to

correctly arrange reads with dense adjacent variants and then straightforwardly

choose to either employ soft-/hard-clipping or categorize them as unmapped.

This limitation will somehow guide most variant callers to identify these regions

as SVs. ConnectedReads can prevent such false mapping and help variant

callers detect the adjacent variants correctly and precisely.

Furthermore, ConnectedReads is able to mitigate the impact on downstream

analysis due to the incomplete human reference genome. The most recent

human genome still has many ambiguous areas (N-gaps), and they are mainly

located in centromeres and telomeres. Fig. 6 illustrates that two ambiguous

gaps can be assembled by using ConnectedReads and that the sequences are

totally identical among the three individuals from different populations. This

finding gives us strong confidence that most humans might have the same

sequence in the two N-gap regions. By randomly selecting two Chinese adults,

the occurrence of identical sequences in the N-gap regions is confirmed by

Sanger sequencing, as performed by a Clinical Laboratory Improvement

Amendments (CLIA)-certificated laboratory. The length of the ambiguous

region in Fig. 6(a) should be corrected from 382 to 223 bps. In addition, the

length of ambiguous regions in Fig. 6(b) should be shortened from 45 to 31.

Based on these cases, leveraging ConnectedReads on cohort-scale WGS dataset

is able to provide a cost-effective approach with which to complete the human reference genome.

# Correctness of reconstructed contigs

The next topic for the evaluation of ConnectedReads is correctness. To comprehensively investigate the data correctness of contigs constructed by ConnectedReads, all of imperfect matched sequences should be considered because any wrong constructed contigs should not be perfectly aligned to reference genome. Therefore, insertion sequences, soft-clipped sequences and unmapped contigs are selected and then identified as being from *Homo sapiens* or just chimeric DNA sequences resulting from false reconstruction. Take NA12878 for example, there are 37 insertions, 384 soft-clipped and 411 unmapped contigs by removing sequences with a length < 1,000 bps. By using BLAST to find any homologous sequences in the National Center for Biotechnology Information (NCBI) non-redundant sequence (nr) database, each sequence can be identified as human or not. As shown in Fig. 7, 35.1%, 46.6% and 37.7% of the insertions, soft-clipped sequences and unmapped contigs are identical to *Homo sapiens* DNA sequences in the nr database. As

the threshold of similarity is continuously lowered, more evidence can be found

to support the sequence assembly correctness of ConnectedReads. However,

there are six sequences without any support when the threshold is set to 20%.

Two of the contigs have low-complexity content, and two are matched to several

entries but with less than 10% support. The last two unmapped contigs

(CONTIG-8337086 and CONTIG-15793805) are more than 10 Kbps in length.

CONTIG-15793805 covers all of CONTIG-8337086 in reverse-complement

mode, so CONTIG-15793805 is represented for evaluation. In Fig. 8, CONTIG-

15793805 is almost fully covered by several long *Homo sapiens* sequences, and

some of these sequences are highly overlapped (at the position of 3000-3500

and 7000-7700). Therefore, the results give us more confident that these non-

reference contigs constructed by ConnectedReads should be from *Homo*

*sapiens*. Although more effort on verifying data correctness is emerging and

expected, we believe that ConnectedReads achieves high data correctness based

on the above findings.

# 1 Translocation-based insertions

Another way to evaluate the data correctness of ConnectedReads is to check

whether there is any translocation. If any two unrelated sequences are

incorrectly assembled together, it will cause a fake translocation event, in which

a contig is mapped to multiple chromosomes. Table 5 lists the 13,686 contigs

with multiple alignment records on two chromosomes in sample NA12878.

**Table 5.**      Translocation-based insertions in NA12878.

| Item | Number |
| --- | --- |
| Number of contigs mapped on at least two chromosomes | 13,686 |
| Number of contigs after removing singletons | 2,075 |
| Number of qualified contigs | 71 |
| Number of high-confidence translocation groups | 22 |
| Number of translocation-based insertions | 8 |

Generally speaking, a translocation-based insertion should have at least three

breakpoints (two for translocation sequences and one for insertion) on genome

reference, so it's difficult to find a single contig with three breakpoints. If a

breakpoint for insertion is mapped in only one contig (named as singleton), it

won't be a candidate for translocation-based insertions. After removing

singletons and filtering out the contigs with low mapping quality (MAPQ < 60),

71 qualitied contigs are represented by 22 translocation groups.

Interestingly, eight translocation groups have one clear breakpoint on one chromosome but two breakpoints on another chromosome. Those translocation-based insertions can be observed from the VCF of NA12878 generated by pbsv. As shown in Fig. 9(a), for example, CONTIG-6374680 and CONTIG-1880453 have identical breakpoints at chr3:110694547. However, CONTIG-6374680 and CONTIG-1880453 have their own breakpoints at chr1:108952231 and chr1:108952660, respectively. Thus, in NA12878, the 430-bp sequence in intron 1 of CLCC1 is inserted at chr3:110694547. Fig. 9(b) also shows that the 697-bp sequence in exon 10 of BTBD7 is inserted into intron 1 of SLC2A5. These translocation groups are called translocation-based insertions. ConnectedReads proposes a naïve way to investigate these translocation-based insertions. In summary, ConnectedReads not only constructs genome sequences precisely but also facilitates SV detection by mitigating reference mapping bias.

# Conclusions

NGS data analysis remain a considerable challenge due to an incomplete reference genome, mapping errors and high sequence divergence. By leveraging

ConnectedReads, SRS is able to be constructed from short reads to long assembled contigs. Using ConnectedReads not only prevents mapping errors but also facilitates SV discovery. In addition, ConnectedReads are able to mitigate the influence on reference incompleteness. In summary, ConnectedReads can serve as an NGS gateway for facilitating downstream data analysis, such as false positive prevention, SV detection, and haplotype identification.

# Materials and methods

## Workflow

ConnectedReads leverages Apache Spark (*6*), a distributed in-memory computing framework, to accelerate its whole workflow, as illustrated in Fig. 10. To fully utilize the power of the distributed framework, the preprocessing step involves splitting a large compressed file into several small files and then uploading those files into the Hadoop distributed file system (HDFS) since most of the WGS samples exist in two separate FASTQ files in GZIP format. First, we adopt Apache Adam (*19*), as shown in Fig. 10(a), to transform data

from FASTQ format to column-based Parquet format for data parallel access.

To facilitate data processing in the following steps, we extend Adam to not only

encode paired-end information and barcodes into the read name column but

also place all reads in different subfolders based on their sequencing quality and

sequence complexity. Then, we propose a distributed suffix tree algorithm with

supervised graph mining on Spark to mitigate the influence of improper string

graph construction due to sequencing errors. Using an outlier detection

algorithm on a suffix tree, the process in Fig. 10(b) can be configured as a highly

sensitive error detector for low-coverage regions. After that, we are able to

adopt the parallel string graph construction shown in Fig. 10(c) to represent the

relation of each qualified read and the read overlaps by suffix-prefix

information. More details are available in our previous paper (*20*). Based on

the string graph, we propose the parallel haplotype-sensitive assembly (HSA)

depicted in Fig. 10(d) to construct assembled contigs; the detailed procedure of

this module will be described in the next session. For example, these generated

contigs (Fig. 10) include (i) heterozygous SNPs, (ii) heterozygous deletions, (iii)

heterozygous insertions and (iv) homozygous SNPs. In summary,

ConnectedReads transforms noisy short reads with low quality and sequencing errors to long assembled and qualified contigs.

# Parallel HSA

ConnectedReads adopts a string graph, a lossless data representation that is fundamental for many de novo assemblers based on the overlap-layout-consensus paradigm (*21, 22*), to represent the overlaps of each read. Here, we propose a Spark-based HSA based on a string graph. By leveraging GraphFrame, HSA is able to perform efficient and scalable graph traversal operations and supervised graph mining algorithms on Apache Spark. Before introducing the detailed algorithms of HSA, we formally define the notations of the sequencing data and string graph that we will use in the following sections.

## Definitions and notation

Let $G(V, E)$ be a directed graph and $S, T \subseteq V$. We define $V = \{v_1, v_2, ..., v_k\}$ and $E(S, T)$ to be the set of edges going from $S$ to $T$, i.e.,

$$|V| = k \text{ and } E(S, T) = \{ e_{ij} \in E : v_i \in S, v_j \in T \text{ and } i < j \leq k \}.$$

Definition 1.  Let $R$ be the set of short reads and $R^{RC}$ be the reverse complement

set of $R$. $G$ and $G^{RC}$ are the string graphs based on $R$ and $R^{RC}$, respectively.

If $e_{ij}$ exists in $G$ and $i, j \in R$, then $e_{mn}$ also exists in $G^{RC}$ and $m, n \in R^{RC}$ such

that $m$ and $n$ are the reverse complements of $j$ and $i$, respectively.

We define $G^{EXT}(V, E)$ to be the expanded graph of vertices $V \in R \cup R^{RC}$ and

edges $E$ to be the set of edges in either $G$ or $G^{RC}$.

**Definition 2.**  Let $IN(v_i)$ and $OUT(v_i)$ be the number of in-degree and out-

degree edges of $v_i$, respectively. We define a vertex $v_i$ to be

9           **Singleton** if $IN(v_i) = 0$ and $OUT(v_i) = 0$;

**Start(S)** if $IN(v_i) = 0$ and $OUT(v_i) = 1$;

**Terminator(T)** if $IN(v_i) = 1$ and $OUT(v_i) = 0$;

**Bridge(B)** if $IN(v_i) = 1$ and $OUT(v_i) = 1$;

and **Ambiguity(A)** if $IN(v_i) \neq 1$ or $OUT(v_i) \neq 1$.

**Definition 3.**  We define the priority order of the vertex labels to be **T** > **S** >

**B** and **A**.

This means that **B** could be relabeled as **S** or **T**. Once a vertex becomes **T**, it will

always be **T** regardless of what the graph property propagation is.

To keep the depth information in FASTQ format, a new quality encoding function is proposed.

Definition 4. Let $L$ and $N$ be the numbers of layers for quality and depth, respectively. $L*N$ should be 42 if Phred33 is adopted. Let $Q[i]$ and $D[i]$ be the quality and depth of the $i$-th base of the given contig, respectively. We define the quality encoding function $Encoder_Q[i]$ and the depth encoding function $Encoder_D[i]$ to be

$$Encoder_Q[i] = \left\lfloor \frac{|Q[i] - ord("!")|}{N} \right\rfloor * N$$

$$Encoder_D[i] = \begin{cases} 0 & if\ D[i] == 1 \\ 1 & if\ 2 \leq D[i] < 4 \\ 2 & if\ 4 \leq D[i] < 7 \\ 3 & if\ 7 \leq D[i] < 11 \\ & \cdots \\ N-1 & if\ D[i] \geq 200 \end{cases}$$

In addition, we define the quality-depth (QD)-encoding function $Encoder_{QD}[i]$ to be

$$Encoder_{QD}[i] = chr(Encoder_Q[i] + Encoder_D[i] + ord("!"))$$

## System flow

In Fig. 11, HSA makes use of five modules, namely, (a) string graph expansion, (b) vertex connectivity classification, (c) the Start-Bridge-Terminator (S-B-T)

traversal algorithm, (d) the ploidy-based routing algorithm and (e) the triplet

traversal algorithm. To simplify the following graph traversal algorithms, each

vertex and its reverse complement should be separated in a string graph. This

means that the string graph $G$ generated by Fig. 10(c) should first be expanded

by Definition 1 and named $G^{EXT}$, which contains $G$ and $G^{RC}$. For that reason, Fig.

11(a) generates the expanded string graph with all reads and their reverse

complements. After removing all singletons in $G^{EXT}$, the remaining vertices will

be classified by the vertex connectivity classification module shown in Fig. 11(b)

into four classes, which are defined in Definition 2: start (**S**), bridge (**B**),

terminator (**T**) and ambiguity (**A**). To generate assembled contigs, the graph

traversal/pairing algorithms shown in Fig. 11(c-e) are proposed based on the

above properties of vertices and described comprehensively in the next section.

## Graph mining algorithms

ConnectedReads leverages Apache Spark and its derived packages to propose

three efficient and scalable graph algorithms for large graphical datasets, i.e.,

string graphs. Spark GraphFrame is a powerful tool for performing distributed

computations with large graphical datasets. In addition, Spark Dataset is a

type-safe interface that provides the benefits of resilient distributed datasets (RDDs) and Spark SQL optimization. By leveraging GraphFrame and Dataset, we propose several Spark-based graph traversal/routing algorithms for HSA with high performance and scalability.

From our observations of NGS sequencing data, two challenges must be overcome if we want to enhance the performance of graph operation for HSA. The first challenge in the string graph involves long diameters, and the second challenge is how to properly connect the vertices with multiple in-/out-degrees. Taking NA12878 as an example, more than 90% of the vertices are **B,** and the longest diameter from **S** to **T** is more than 500. This means that the traversal algorithm must perform the propagation operation in at least 500 iterations from one vertex (**S**) to another vertex (**T**). For most graph frameworks, the performance of a graph algorithm is strongly related to the number of iterations for its traversal operation. Here, we propose the S-B-T traversal algorithm, shown in Fig. 11(c), to connect all vertices from **S** to **T** via all adjacent **B**s. By following Definition 3, the data preprocessing flow for the expanded string graph is applied, as illustrated in Fig. 12. First, all vertices before and after any

vertex **A** should be relabeled as **T** and **S**, respectively. To overcome the long-

diameter problem, the mechanism used to relabel **B** to **T** by customized random

selection is applied to shorten the diameter of the given graph, and then, the

terminator-intensive propagated string graph is acquired. Based on the

terminator-intensive graph, the S-B-T traversal algorithm, which integrates a

belief propagation algorithm with iterative graph merging, is able to

theoretically reduce the time complexity from $O(N)$ to $O(\sqrt{N})$ ($N$: the number

of iterations for graph propagation).

When each simple routing path (i.e., **S** to **T** via **B**s) is completely traversed and

merged into a single vertex in the new graph, the majority of the vertices have

multiple in-/out-degrees. Therefore, we have to solve the second challenge -

how to select a proper routing path in the multiple-in-/out-degree graph. Many

useful indicators enable us to perform correct routing, such as read pairs,

barcodes and read overlaps. The pseudo code of the ploidy-based pairing

algorithm shown in Fig. 11(d) is as follows:

```
16  def ploidy_based_pairing(G: GraphFrame for string graph, N: int for ploidy) {
17      Candidates = ∅
18      Vₐ = all of As in G
19      for each v ∈ Vₐ {
20          Iᵥ = the set of vertices point to v
```

```
1        Oᵥ = the set of vertices pointed by v
2        Dᵥ = de_noise(Iᵥ, v)
3        T = ∅
4        for each u ∈ Dᵥ {
5           (t, s) = find_best_matching(u, v, Oᵥ)              #t: triple ; s: score
6           if s ≥ MIN_THRESHOLD then
7              add (t, s) into T
8           }
9        sort T by score
10       add the top N triples from T into Candidates
11    }
12    return Candidates
13  }
```

To mitigate false assembly due to sequencing errors, the function **de_noise()**

is used to remove the noisy vertices in $I_v$ by using a naïve clustering algorithm

based on the read-pair information in this paper. In addition, the function

**find_best_matching()** adopts a tripartite clustering algorithm based

primarily on the number of supports from read-pair information in ($u$, $v$), ($u$,

$O_v$) and ($v$, $O_v$) to find the best combination for sequence assembly. Using the

ploidy-based pairing algorithm, we obtain sufficient information to overcome

the second challenge and then apply the triplet traversal algorithm shown in

Fig. 11(e) to construct the assembled contigs by traversing the aggregated graph

from each **S** to **T** via the triple set generated by the ploidy-based pairing

algorithm. The triplet traversal algorithm involves almost the same procedures

as the S-B-T traversal algorithm, except for the linkage of vertexes. In summary,

HSA leverages Apache Spark to efficiently generate assembled contigs from a

large string graph.

# Performance

Here, sample NA12878 is processed by ConnectedReads on our Spark cluster.

It takes approximately 18 hours for the 30X WGS sample; the detailed

performance of ConnectedReads is described in Table 6.

**Table 6.**     Execution time for NA12878

| Module | Time (hours) | # Executors | # Cores per executor |
|---|---|---|---|
| (a) Parallel data transformation | 1.9 | 9 | 17 |
| (b) Parallel error correction | 8.1 | 15 | 8 |
| (c) Parallel string graph construction | 4.3 | 9 | 17 |
| (d) Parallel haplotype-sensitive assembly | 4.0 | 9 | 17 |
| Data export from HDFS to local disk | 0.05 | 9 | 4 |
| Total | 18.3 | | |

*There are 9 computing nodes (each node has two E502650 v4 with 512 GB of memory)

# QD encoder/decoder

Since ConnectedReads not only connects reads with their overlaps but also

aggregates identical reads, the size of ConnectedReads contigs will be reduced

by at least 90% in comparison with that of contigs from short-read data.

However, the downstream analysis tools might not work well due to the loss of

depth information. We have to take the depth information into consideration

and keep the output compatible with FASTQ format. Therefore, the QD encoder

and decoder are proposed based on Definition 4 to mitigate the impact on

information loss. The mechanism of the QD-encoding function is quite flexible,

allowing it to fit most use cases. For example, if the depth information is more

critical than quality, (L, N) = (3, 14) is the best choice. Fig. 13 provides an

example to demonstrate how the QD encoder transforms short reads into

ConnectedReads contigs. The data reduction rate is approximately 77% (from

144 characters to 33 characters in both sequence and quality). In addition, Fig.

14 shows the result of applying the QD-decoding function. The recovery rate in

terms of sequences and quality is 95.8% (138/144) and 47.3% (71/144),

respectively. Therefore, ConnectedReads provides an efficient QD-decoding

tool for some use cases that heavily leverages depth information.

## Availability of data and materials

16   Data: The raw sequencing data discussed in this manuscript are deposited on

17   the European Bioinformatics Institute (EBI) and NCBI websites. NA12878 is

available from https://www.ebi.ac.uk/ena/data/view/ERR2438055; NA24694

and NA19240 are available from

https://www.ncbi.nlm.nih.gov/sra/SRX1388455 and

https://www.ncbi.nlm.nih.gov/sra/SRX4637790, respectively.

Codes: The source code and scripts for the ConnectedReads workflow and the

related experiments discussed in this paper are available at

https://github.com/atgenomix/connectedreads.

# References

1.  E. D. Esplin, L. Oei, M. P. Snyder, Personalized sequencing and the future of medicine: discovery, diagnosis and defeat of disease. *Pharmacogenomics* **15**, 1771-1790 (2014).
2.  C. S. Ku, D. N. Cooper, B. Iacopetta, D. H. Roukos, Integrating next-generation sequencing into the diagnostic testing of inherited cancer predisposition. *Clin Genet* **83**, 2-6 (2013).
3.  S. P. Pfeifer, From next-generation resequencing reads to a high-quality variant data set. *Heredity (Edinb)* **118**, 111-124 (2017).
4.  H. Li, Toward better understanding of artifacts in variant calling from high-coverage samples. *Bioinformatics* **30**, 2843-2851 (2014).
5.  H. Li, Exploring single-sample SNP and INDEL calling with whole-genome de novo assembly. *Bioinformatics* **28**, 1838-1844 (2012).
6.  S. e. a. Gupta, in *VLSI Design*. (16th International Conference on IEEE, 2003).
7.  H. Parikh *et al.*, svclassify: a method to establish benchmark structural variant calls. *BMC Genomics* **17**, 64 (2016).
8.  K. H. Y. Wong, M. Levy-Sakin, P. Y. Kwok, De novo human genome assemblies reveal spectrum of alternative haplotypes in diverse populations. *Nat Commun* **9**, 3040 (2018).

9.  B. Kehr *et al.*, Diversity in non-repetitive human sequences not found in the reference genome. *Nat Genet* **49**, 588-593 (2017).

10. A. Hatem, D. Bozdag, A. E. Toland, U. V. Catalyurek, Benchmarking short sequence mapping tools. *BMC Bioinformatics* **14**, 184 (2013).

11. H. Li, Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics* **34**, 3094-3100 (2018).

12. D. L. Cameron, L. Di Stefano, A. T. Papenfuss, Comprehensive evaluation and characterisation of short read general-purpose structural variant calling software. *Nat Commun* **10**, 3240 (2019).

13. L. Shi *et al.*, Long-read sequencing and de novo assembly of a Chinese genome. *Nat Commun* **7**, 12065 (2016).

14. J. D. Merker *et al.*, Long-read genome sequencing identifies causal structural variation in a Mendelian disease. *Genet Med* **20**, 159-163 (2018).

15. P. H. Sudmant *et al.*, An integrated map of structural variation in 2,504 human genomes. *Nature* **526**, 75-81 (2015).

16. J. Molnar *et al.*, The genome of the chicken DT40 bursal lymphoma cell line. *G3 (Bethesda)* **4**, 2231-2240 (2014).

17. P. Deininger, Alu elements: know the SINEs. *Genome Biol* **12**, 236 (2011).

18. H. Li, FermiKit: assembly-based variant calling for Illumina resequencing data. *Bioinformatics* **31**, 3694-3696 (2015).

19. M. a. N. Massie, Frank and Hartl, Christopher and Kozanitis, Christos and Schumacher, Andre and Joseph, Anthony D and Patterson, David A, paper presented at the UCB/EECS-2013-207, EECS Department, University of California, Berkeley,   2013.

20. M.-T. C. Chung-Tsai Su, Yun-Chian Cheng, Yun-Lung Li, Yao-Ting Wang, GraphSeq: Accelerating String Graph Construction for De Novo Assembly on Spark.   (2016).

21. J. T. Simpson, R. Durbin, Efficient de novo assembly of large genomes using compressed data structures. *Genome Res* **22**, 549-556 (2012).

22. P. Bonizzoni, G. D. Vedova, Y. Pirola, M. Previtali, R. Rizzi, FSG: Fast String Graph Construction for De Novo Assembly. *J Comput Biol* **24**, 953-968 (2017).

# Acknowledgements

We are grateful to Prof. Chen Chia-Hsiang and his team for supporting the Sanger sequencing validation. In addition, Cheng Yun-Chian and Prof. Chen Chien-Yu assisted in algorithm design in the early stage. The results presented in the paper are based on the data generated by the Atgenomix Seqslab Cloud platform.

## Funding

The research was supported by Atgenomix Inc.

# Author information

## Affiliations

Atgenomix Inc., Taiwan, R.O.C.

Chung-Tsai Su, Sid Weng, Yun-Lung Li & Ming-Tai Chang

## Contributions

CS, SW, YL and MC developed the algorithms and implemented the tools for data transformation and error correction. CS developed the algorithms and

implemented the tools for string graph construction. CS and SW developed the

algorithms and implemented the tools for haplotype-sensitive assembly. CS

collected the sequencing data and carried out the benchmarks based on the

sequencing dataset. CS carried out the experiments, developed the structural

variant caller and carried out the related experiments. CS prepared the

manuscript with input from all other authors. All authors read and approved

the final manuscript.

## Corresponding author

Correspondence to Chung-Tsai Su

# Ethics declarations

## Ethics approval and consent to participate

This article is a preprint version and can be accessed on https://www.biorxiv.org/content/10.1101/776807v1. This article is not published nor is under publication elsewhere.

## Consent for publication

Not applicable.

# Competing interests

C.S., S.W., Y.L. and M.C. are employees of Atgenomix Inc. The authors declare

no other potential conflict of interest.

2   **Fig. 1.**   Mapping recovery of NA12878 (short reads vs. ConnectedReads).

3      BWA and minimap2 are adopted for the short-read data and

4      ConnectedReads contigs, respectively. Recovery Rate = # recovered / (#

5      recovered + # uncovered).

2 **Fig. 2.** Number of SV vs. MAPQ (NA12878). The priority order used for

3 counting is insertion > deletion > soft-/hard-clipped sequence. Any two

4 SVs will be merged if their distance is less than 50 bps. This means that if

5 one insertion and one deletion are encountered in the same location, only

6 one insertion is counted.

2   **Fig. 3.**   SV length distribution of NA12878. The peak at a length of 251-300

3       is attributed primarily from Alu elements.

2    **Fig. 4.**   Comparison of insertion lengths among three approaches (genome

3       coordinates are based on hg38). (a) Spiral Genetics vs. ConnectedReads,

4       (b) PacBio vs. ConnectedReads. The gray dashed line is the 1:1 line. The

5       green and blue dashed lines in (a) and (b), respectively, represent the

6       moving average of the comparison.

(a) Multiple SNPs

(b) Multiple deletions

**Fig. 5.** Examples of NRNR sequences (multiple small variants). (a) Thirteen

adjacent SNPs in the intron of SRGAP1. (b) Thirteen adjacent deletions in

the intron of BICC1.

(a) N-gap near centromere of chr1

(b) N-gap near centromere of chr20

**Fig. 6.**  The contigs from three individuals cross the entire N-gap regions

near the centromere of chromosome 1 and 20. Based on the alignment

result, the sequences in the N-gap are identical among the three

individuals. (a) The genomic location of IGV is chr1:124,977,874-

124,978,413 of HG38. (b) The genomic location of IGV is

chr20:29,447,807-29,447,908 of HG38.

2 **Fig. 7.** Distribution of BLAST queries for non-reference sequences identified

3 by ConnectedReads. (a) From insertions, (b) from soft-clipped sequences

and (c) from unmapped contigs. The x-axis shows the similarity of the

query results by BLAST. NUI means that the matched result is annotated

as a non-reference unique insertion. *Homo sapiens* means that the

matched result is from *Homo sapiens* or Human BAC.

**Fig. 8.**  BLAST result for CONTIG-15793805. Six long *Homo sapiens* contigs

are identified with low E-values. Since some of them overlap, the

alignment result gives us strong confidence in the data correctness of

ConnectedReads.

(a) Insertion sequence from CLCC1 intron 1

(b) Insertion sequence from BTBD7 exon 10

2  **Fig. 9.**  Examples of translocation-based insertions. (a) The 429-bp sequence

3  from intron 1 of CLCC1 is inserted at chr3:110,694,547. (b) The 697-bp

4  sequence from exon 10 of BTBD7 is inserted into intron 1 of SLC2A5.

**Fig. 10.** Workflow of ConnectedReads. (a) Parallel data transformation. (b)

3      Parallel error correction. (c) Parallel string graph construction. (d)

4      Parallel haplotype-sensitive assembly (HSA).

2 **Fig. 11.** Parallel haplotype-sensitive assembly (HSA). (a) String graph

3 expansion. (b) Vertex connectivity classification. (c) S-B-T traversal

4 algorithm. (d) Ploidy-based paired algorithm. (e) Triplet traversal

5 algorithm.

2    **Fig. 12.** An example to demonstrate the graph preprocessing workflow for the

3    S-B-T traversal algorithm. (a) Expanded string graph. (b) Propagated

4    string graph. (c) Terminator-intensive propagated string graph.

| | Sequence | Quality |
|---|---|---|
| Short Reads<br>(144 nucleotides) | R1 GGCGTCTATATCTCG<br>R2 GCGTCTATATCTCG<br>R3 TCTATATCTCGGC<br>R4 TCTATATCTCGGCTC<br>R5 CTATATCTCGGCTCT<br>R6 TATCTCGGCTCTAGG<br>R7 CTCGGCTCTAGGC<br>R8 CTCGGCTCTAGGCCC<br>R9 GCTCTAGGCCCTCAT<br>R10 TAGGCCCTCATTTT | R1 JJJJIIIGGGJJJA,<br>R2 AJJJJHHHHI09,,<br>R3 JJJJJJJJJJJJJ0<br>R4 AJJJJJJ../../..<br>R5 JJJJJJJJJJJEEDD<br>R6 AJJJEEEEEEBBB<<<br>R7 JJJJJJJAAJJJJ<br>R8 AJJJJEEEGGG<=..<br>R9 JIIJIJIJIIJJAAA<br>R10 JJJJJJJ+(((((( |
| ConnectedReads<br>(33 nucleotides) | GGCGTCTATATCTCGGCTCTAGGCCCTCATTTT | =>>>@AAABBBDDDDCCBBBAAA@??>>>>!!! |

2 **Fig. 13.** An example application of the QD encoder (taking (L, N) = (3, 14) as

3 an example).

| | Sequence | Quality |
|---|---|---|
| Encoded Data | GGCGTCTATATCTCGGCTCTAGGCCCTCATTTT | =>>>@AAABBBDDDDCCBBBAAA@??>>>>!!! |
| Decoded Data | R1 GGCGTCTATATCTCG<br>R2  GCGTCTATATCTCGG<br>R3    TCTATATCTCGGCTC<br>R4    TCTATATCTCGGCTC<br>R5   CTATATCTCGGCTCT<br>R6     TATCTCGGCTCTAGG<br>R7      CTCGGCTCTAGGCCC<br>R8      CTCGGCTCTAGGCCC<br>R9        AGGCCCTCATTTT<br>R10       AGGCCCTCATTTT | R1 JJJJJJJJJJJJJJJ<br>R2  JJJJJJJJJJJJJJJ<br>R3    JJJJJJJJJJJJJJJ<br>R4    JJJJJJJJJJJJJJJ<br>R5   JJJJJJJJJJJJJJJ<br>R6     JJJJJJJJJJJJJJJ<br>R7      JJJJJJJJJJJJJJJ<br>R8      JJJJJJJJJJJJJJJ<br>R9        JJJJJJJJJJ!!!<br>R10       JJJJJJJJJJ!!! |

3   **Fig. 14.** An example application of the QD decoder (taking (L, N) = (3, 14)

4      and read length = 15 as an example).