Title: Quantifying geographic accessibility to improve efficiency of entomological monitoring.

Authors: Joshua Longbottom[1, 2,] Ana Krause[1], Stephen J. Torr[1], Michelle C. Stanton[1, 2]

Author Affiliation:
[1]Department of Vector Biology, Liverpool School of Tropical Medicine, Liverpool, L3 5QA
[2]Centre for Health Informatics, Computing and Statistics, Lancaster Medical School, Lancaster University,
Lancaster, LA1 4YW

Corresponding author:
Mr Joshua Longbottom
Department of Vector Biology,
Liverpool School of Tropical Medicine,
Liverpool, L3 5QAUK
Email: joshua.longbottom@lstmed.ac.uk

ORCIDs:
Joshua Longbottom: https://orcid.org/0000-0002-4151-9031
Ana Krause: https://orcid.org/0000-0002-9665-5102
Stephen J. Torr: https://orcid.org/0000-0001-9550-4030
Michelle C. Stanton: https://orcid.org/0000-0002-1754-4894

Abstract:
Background
Vector-borne diseases are important causes of mortality and morbidity in humans and livestock,
particularly for poorer communities and countries in the tropics. Large-scale programs against these
diseases, for example malaria, dengue and African trypanosomiasis, include vector control, and
assessing the impact of this intervention requires frequent and extensive monitoring of disease vector
abundance. Such monitoring can be expensive, especially in the later stages of a successful program
where numbers of vectors and cases are low.
Methodology/Principal Findings
We developed a system that allows the identification of monitoring sites where pre-intervention
densities of vectors are predicted to be high, and travel cost to sites is low, highlighting the most
efficient locations for longitudinal monitoring. Using remotely sensed imagery and an image
classification algorithm, we mapped landscape resistance associated with on- and off-road travel for
every gridded location (3m and 0.5m grid cells) within Koboko district, Uganda. We combine the
accessibility surface with pre-existing estimates of tsetse abundance and propose a stratified sampling
approach to determine the most efficient locations for longitudinal data collection. Our modelled
predictions were validated against empirical measurements of travel-time and existing maps of road
networks. We applied this approach in northern Uganda where a large-scale vector control program is
being implemented to control human African trypanosomiasis, a neglected tropical disease (NTD)
caused by trypanosomes transmitted by tsetse flies. Our accessibility surfaces indicate a high
performance when compared to empirical data, with remote sensing identifying a further ~70% of roads
than existing networks.
Conclusions/Significance
By integrating such estimates with predictions of tsetse abundance, we propose a methodology to
determine the optimal placement of sentinel monitoring sites for evaluating control programme

efficacy, moving from a nuanced, ad-hoc approach incorporating intuition, knowledge of vector ecology
and local knowledge of geographic accessibility, to a reproducible, quantifiable one.
50

Author Summary
Assessing the impact of vector control programmes requires longitudinal measurements of the
abundance of insect vectors within intervention areas. Such monitoring can be expensive, especially in
the later stages of a successful program where numbers of vectors and cases of disease are low. Efficient
monitoring involves a prior selection of monitoring sites that are easy to reach and produce rich
information on vector abundance. Here, we used image classification and cost-distance algorithms to
produce estimates of accessibility within Koboko district, Uganda, where vector control is contributing
to the elimination of sleeping sickness, a neglected tropical disease (NTD). We combine an accessibility
surface with pre-existing estimates of tsetse abundance and propose a stratified sampling approach to
determine locations which are associated with low cost (lowest travel time) and potential for
longitudinal data collection (high pre-intervention abundance). Our method could be adapted for use in
the planning and monitoring of tsetse- and other vector-control programmes. By providing methods to
ensure that vector control programmes operate at maximum efficiency, we can ensure that the limited
funding associated with some of these NTDs has the largest impact.

Keywords: Accessibility, Entomology, Remote sensing, Resistance, Vector control

67
Introduction
Vector-borne diseases (VBDs) are important causes of mortality and morbidity in humans and livestock,
particularly for poorer communities and countries in the tropics, accounting for an estimated 17% of the
global burden of all infectious diseases (1). The control of VBDs, or their elimination as a public health
problem, is dependent upon effective vector management, which includes pre-intervention surveys and
subsequent longitudinal monitoring of vector abundance to assess the effectiveness of an intervention.
Such monitoring is an important component of the overall costs of control.
75
To improve the efficiency of vector control programs, there is a requirement to identify optimal
locations for longitudinal monitoring site placement. Ideally, these sites should be in locations that
maximise information on the distribution and density of vectors while minimising costs of obtaining
these data. In practice, most vector surveillance is opportunistic and lacks a rigorous framework (2). A
more rational method would involve combining information on vector abundance with estimates of
geographical accessibility, to identify sites across operational areas where pre-intervention catches are
high and sampling costs are low. Towards this goal, we examined the utility of remotely sensed (RS) data
to produce contemporary estimates of geographic accessibility to entomological sampling sites, using
sleeping sickness control as an example application.
85
Sleeping sickness control as an example application
Human African trypanosomiasis (HAT) is a neglected tropical disease (NTD) affecting remote areas of
sub-Saharan Africa. The disease, also termed 'sleeping sickness', is caused by the protozoan parasite
Trypanosoma brucei with two sub-species, *T.b.gambiense* and *T.b.rhodesiense*, causing Gambian (gHAT)
and Rhodesian (rHAT) human African trypanosomiasis respectively. The burden of the Gambian form of
the disease, for which humans are the main hosts, is >10 times that of the Rhodesian form, with annual
reported cases being in the region of 2-3,000 (3). The World Health Organization (WHO) has targeted
the elimination of gHAT as a "public health problem" by 2020, which is defined as a 90% reduction in
areas reporting >1 case in 10 000 compared to 2000–2004, and <2000 annually reported cases globally
(4). Several countries appear to be on track to achieve this target (5). Uganda is unique in that it is the

only country where both gHAT and rHAT occur, albeit within different local level zones (6, 7). Vector
control forms an important part of Uganda's efforts against both forms of HAT (8, 9).
98
The important vectors of gHAT are Palpalis-group species of tsetse, which concentrate in riverine
vegetation where, consequently, interventions are focused. In Uganda, tsetse control is being achieved
through the deployment of Tiny Targets, small (20 x 50 cm) panels of insecticide-treated material which
are deployed at 50-100m intervals along rivers (9, 10). Prior work produced estimates of tsetse
abundance across Northern Uganda, identifying locations of high pre-intervention abundance (11),
which has informed the identification of operational control areas.
105
Methods to quantify accessibility largely involve cost-distance analyses, which have been widely used
within the field of public health in analyses mapping accessibility to healthcare (12-15). Such analyses
require an input surface of landscape friction ('resistance') – estimates of associated travel cost for
gridded cells within a Cartesian plane. The cost-distance analysis identifies the cumulative cost of
traversing each cell based on the given resistance surface and an origin location – opting to traverse
through cells associated with the lowest resistance values. The use of accessibility mapping in the
planning and implementation of control programmes for vector-borne disease is novel and has the
potential to improve the efficiency of monitoring VBD interventions.
114
In this paper, we use remotely sensed (RS) satellite data to derive a contemporary road network within
Koboko district, Northern Uganda, where an existing tsetse control programme is in operation. To
obtain a road network within this district, we compare the utility of RS data at two differing spatial
resolutions (one source characterising locations within the district as 3 × 3m grid cells on a Cartesian
plane, and another as 0.5 × 0.5m grid cells) (16, 17), and an existing open source dataset detailing road
locations (18). Image classification algorithms, specifically maximum likelihood estimators were used to
detect dirt and tarmac roads within the RS imagery (19). Ground truth tracking (GPS) data detailing
motorbike speeds along roads within the district were used to assign on-road travel costs to each grid
cell. We used published estimates of time taken to traverse through different densities of vegetation to
assign resistance values to off-road grid cells (20, 21). Resistance surfaces were validated using withheld
ground-truth tracking data, comparing observed and predicted travel times within a linear regression.
The resulting resistance surfaces were used within a least-cost path algorithm to identify cumulative
costs to locations of high tsetse abundance (11). We apply a stratified sampling approach to determine
locations which are associated with low cost (lowest travel time) and potential for rich longitudinal data
collection (high pre-intervention abundance).
130
Here, by combining field data on travel time along varying road types and remotely sensed imagery, we
describe the process of producing a high-resolution accessibility surface. By integrating such estimates
with predictions of tsetse abundance, we propose a methodology to determine the optimal placement
of sentinel monitoring sites for evaluating the efficacy of a tsetse control programme, moving from a
nuanced, ad-hoc approach incorporating intuition, knowledge of vector ecology and local knowledge of
geographic accessibility to a reproducible, quantifiable one. The work described here is presented in the
context of tsetse control, but the methods used are applicable to a wide range of vector-borne diseases.
138
Materials and Methods
Study area: The focal area of this study was Koboko District, located within the West Nile Region of
Uganda. The West Nile region consists of eight districts, with current and planned intervention initiatives
(i.e. the Tiny Target programme), operating in seven. Koboko district covers roughly 860km^2 and has a
population of 229,200 people (22). Between 2000 and 2018, 14.6% (620/4235) of gHAT cases reported

from Uganda occurred in Koboko, but the incidence of gHAT is in decline as a consequence of an
integrated programme of screening and treatment of the human population and, more recently, vector
control (23). A map showing the location of existing, and planned intervention areas within West Nile
Region is provided as Fig. S1, highlighting the position of Koboko within these intervention districts.
148
Field methodology and data collection: To obtain data informing variation in speeds along road class,
technicians making routine visits to traps within Koboko were provided with GPS devices. The recording
of GPS tracks was performed during three time periods in the dry season: May-June 2017, February-
April 2018, and December 2018-January 2019. Trap attendants within Koboko operate using motorbikes;
therefore, observed speeds were representative of motorbike-based travel. Devices were configured to
record track points at ~15-second intervals.
155
Obtaining remotely sensed satellite data: To compare the effect of different spatial resolutions of
satellite data on the ability to identify roads, we used two differing sources of remotely sensed imagery.
Imagery obtained from PlanetScope™ satellites, captured on February 12[th], 2018 were utilised.
PlanetScope™ imagery is provided at a 3m × 3m resolution, and includes the following four spectral
bands: blue (455 − 515 nm), green (500 − 590 nm), red (455 − 515 nm), and near infrared (780 − 860 nm)
(16, 24). PlanetScope™ data are freely accessibly through an education and research program account.
Data captured through the Pléiades-1A satellite, available at a 0.5m × 0.5m resolution and captured on
27[th] December 2016 were used to represent high-spatial resolution imagery (25). Imagery captured on
this date was the most contemporary data available. The Pléiades-1A imagery similarly consists of the
same four spectral bands as PlanetScope™. Data obtained by Pléiades-1A is available by request through
Airbus (previously known as the European Aeronautic Defence and Space Company) (17).
167
168   **GPS data review and cleaning:** To calculate travel speeds, the time-difference between subsequent
169   points within a track and the Euclidean distance between these points were used within the following
170   formula (Equation 1):
171
172   Where x_i represents the GPS coordinate of point i, t_i represents the time recorded for point i and $|| \cdot ||$
173   represents the Euclidean distance:

$$speed = \frac{||x_i - x_j||}{|t_i - t_j|}$$

174   (Eq. 1)
175   Recorded points with a speed <1km/hr were assumed to be stationary points (based on average walking
176   speeds (26)), and were removed from the track dataset. Similarly, we removed data points for which the
177   speed exceeded 150 km/hr (93.2 mph) as these were likely to be artefacts created due to errors with
178   location positioning and are not representative of true travel speed.
179
Open street map validation: To determine the accuracy of currently available open source data,
OpenStreetMap (OSM) geolocated roads, and roads visible within 0.5m and 3m satellite data were
compared. Shapefiles detailing mapped roads hosted by OSM were retrieved from Geofabrik OSM Data
Extracts on March 3[rd], 2018, to align with the dates during which field-obtained tracking data were
collected (18). A 1 km × 1km fishnet constructed for Koboko district was used to produce a random
sample of 25 grid squares for manual digitisation. The digitisation process consisted of tracing over
visible roads and tracks, as seen in the 0.5m resolution imagery (metric one), or as seen in the 3m
resolution imagery (metric two). The length of digitized road obtained from each of the three sources
was calculated in metres.
189

Remote sensing image preparation: In total, 14 scenes covering an area of 745.8 km^2 were downloaded
from Planet.com. To produce one complete surface, overlapping scenes were merged using ArcGIS
(version 10.4), and the composite image was cropped to district boundaries. Imagery obtained from
Pléiades-1A (0.5m) were provided as a pre-prepared mosaic.

Image classification: To aid image classification, image segmentation utilising a mean-shift approach
was first performed within ArcGIS (version 10.4). Mean-shift segmentation is a process that identifies
segments in imagery by grouping adjacent pixels that have similar spectral characteristics; a detailed
introduction and theory related to mean-shift segmentation algorithms can be found within Demirović
2019 (27). We utilised the "*Segment Mean Shift*" tool within the "*Spatial Analyst Toolbox*" in ArcGIS,
with the following default parameters: spectral detail = 15.5, spatial detail = 15, minimum segment size
(in pixels) = 20. Following mean-shift segmentation, we applied a maximum likelihood (ML) classification
algorithm using an equal *a priori* probability weighting to identify the class in which each cell had the
highest probability of being a member. The ML classification algorithm considers both the variances and
covariances of pixels assigned to 'classes' (groups of pixels relating to a specific type of land-cover, in
this instance), selected within a signature training file (19). Under the assumption that the distribution
of a class sample is normal, each class was characterized by the mean vector and the covariance matrix.
Given these characteristics, for each cell value within the remotely sensed imagery, the statistical
probability of a cell belonging to each class is calculated and an appropriate classification is assigned
(19). We opted to use the following classes within this analysis: dirt road and/or track, tarmac road,
dense vegetation (for example: woodlands, forest, bushwood and shrubwood), grassland (for example:
grassland, meadow, steppe and savannah) and barren land. Signature files for use in the ML
classification were produced by manually tracing and assigning pixels within the remotely sensed
imagery to one of the five classes described above. Classification was performed using the "*Train
Maximum Likelihood Classifier*" tool within the "*Spatial Analyst Toolbox*" in ArcGIS. To account for "salt
and pepper" speckling effects representative of potentially misclassified and/or isolated cells, we
performed post-classification processing. This processing stage included filtering to remove isolated cells
(28), smoothing to smooth rugged class boundaries (29), and generalizing to reclassify small regions of
isolated cells (30). Post-classification cleaning was performed in ArcGIS.

Classification validation: A total of 500 accuracy assessment points were randomly generated for each
classified surface (i.e. 3m × 3m and 0.5m × 0.5m imagery). A step-by-step comparison was then made for
each randomly selected point, noting the algorithm-derived class and the manually assigned (ground-
truth) class. Utilising this information, a confusion matrix was constructed for each image source.
Accuracy was calculated with respect to both omission and commission rates, where omission refers to
instances where a feature (point) is omitted from the evaluated category, and commission refers to
instances where a feature is incorrectly assigned to the category being evaluated.

Road network update: Using the outputs from the image classification process, the GPS tracking data,
and available OSM data, two contemporary road networks (one per remotely sensed data source) were
produced. Cleaned, field-obtained tracking points were used to inform estimates of average travel
speeds along selected roads as follows. Tracking points were converted to polylines, consisting of line
segments constructed from five trailing points. These segments were assigned a mean observed speed
by calculating the Euclidean distance of each segment and incorporating start and end times. These
segments were then rasterised, resulting cells were stacked, and overlapping cells resulting from
replicate trips across all tracking days were averaged. This produced a surface indicating the average
observed speed for each cell. Tracks obtained during December 2018 were withheld from this network
and were used for validation (see below). A surface detailing urban and rural locations (31) was used to

categorise roads as being within urban or rural areas. This classification was paired with the Ugandan Traffic and Road Safety Act detailing maximum speed limits based on roads within urban/built-up areas and rural areas. Characterising roads by these features imply a legal maximum speed for each road representative of true travel speeds. Classified urban and classified rural cells were assigned the speeds given in Table 1, as informed by the official Traffic and Road Safety Act 2004 (32) and the Highway code (33).

Table 1. Assigned travel speeds to roads lacking ground-obtained tracking data.

Road type	Speed (km/h)	
	Built-up area	Rural area
Paved	50	100
Gravel/dirt	50	80

Normalized Difference Vegetation Index analysis: As the majority of mapped roads do not lead directly to a river or tributary, trap attendants are required to traverse off-road in order to reach suitable habitats for trap placement. We therefore aimed to characterise the cost associated with off-road travel within our analysis. Utilising the two differing imagery sources, two separate NDVI surfaces were generated (Equation 2). During the NDVI calculation, output values were normalised to range between -1.0 and 1.0, representing greenness. Generally, output NDVI values ≤0 represent waterbodies including lakes and major rivers; values between 0.1 and 0.2 represent barren land, including areas of rock, sand, or snow; values between 0.2 and 0.3 represent shrub and grassland (areas of moderate vegetation), and values between 0.3 and 0.8 represent areas of dense vegetation (for example temperate and tropical rainforest) (34, 35).

Where NIR represents the near infrared band, and R represents the red band within the RS imagery:

$$NDVI = \frac{(NIR - R)}{(NIR + R)}$$

(Eq. 2)

Assigning off-road resistance values: Resistance values are values associated with a specific cost to traverse through a cell (time, in seconds). For this study, off-road resistance values were assigned utilising the NDVI outputs, with cost values ranging based on indicative terrain. Locations which contain dense vegetation are generally slower to navigate and therefore cells representative of these areas were associated with a higher resistance value; conversely, cells which represent areas with little to no vegetation were presumed to be easier to traverse and were assigned a lower resistance value. Average off-road walking speeds for differing terrains were obtained from published literature (20, 21) (Table 2).

Table 2. Resistance values (cell crossing time) associated with off-road travel.

NDVI value	Off road walking speed (km/h)	Off road walking speed (m/s)	Cell crossing time (t_i)	
			0.5 × 0.5m	3m × 3m
≤0	Essentially impassable	Essentially impassable	200	200
0.1-0.2	3.5	0.97	0.73	4.37
0.2-0.3	2.48	0.69	1.03	6.14
0.3-0.8	1.49	0.41	1.73	10.34

Resistance surface and cost-distance analysis: The updated road networks, featuring a cell crossing time based on assigned speeds (representative of on-road resistance), were combined with their

respective NDVI resistance surface. To validate the generated surfaces, we used field-obtained tracking
data (obtained December 2018) withheld from the road network construction. Sixty-three segments
along the withheld tracks were used to create validation points. Using the resistance surface, the travel
time from the start to the end point of each segment was generated utilising a least-cost path algorithm
within QGIS 3.4.4 (36), plugin "*Least-Cost Path*" (produced by FlowMap Group (37)). The specific
algorithm implemented is referred to as Dijkstra's algorithm, and is an approach utilising graph theory to
identify the shortest path between two nodes; the algorithm is described in detail in Dijkstra 1959 (38).
A linear regression model was then fitted to the observed travel time data with predicted travel time
being included as the only covariate to quantify the relationship between the two measures. The ability
of the predicted travel time to each validation point to accurately predict the observed travel time was
used to detect an association between the two, and to provide a means of adjusting the generated
surface values if necessary. The accuracy of each resistance surface was defined by the coefficient p-
values, and by root-mean-square error (RMSE). Utilising these resistance surfaces, two separate cost-
distance analyses were performed (one per spatial resolution), each using the location of our district
entomologist's base as the origin. The cost-distance analysis again implemented Dijkstra's algorithm,
calculating the cumulative cost of travel from the origin to each grid cell in the resistance surface.
289
Identifying optimal sentinel site placement: We performed a spatially stratified sampling approach to
aid the identification of 104 least-cost, high abundance locations per 25km^2 for sentinel site placement.
Firstly, we produced a fishnet consisting of 5 km × 5 km grid squares across Koboko district, and assigned
each grid square a sequential stratum identification number (see Fig. S2 for strata distribution). For each
strata within the proposed intervention area, we ranked each cell by their predicted tsetse abundance
values (11), and by their predicted travel time from the origin – as obtained from the cost-distance
output. To account for spatial clustering, and to ensure a more even spatial distribution of sentinel sites,
we retained the cell with the highest predicted abundance and lowest associated cost per 50m × 50m
area. We calculated the cumulative rank for each cell within the de-clustered dataset, where predicted
abundance values were ranked from high to low, and accessibility values ranked from low to high. We
retained two locations (paired sites) with the lowest cumulative rank per sampled strata, with these
locations being identified as the optimal placement for sentinel monitoring sites.
302
Utilising the travelling salesperson problem (TSP) to identify the optimal route: Once the optimal
location of monitoring sites was identified, we applied the travelling salesperson problem (TSP) to
identify the most efficient order in which to visit each site. The TSP is an optimisation problem in which
the following question is addressed: "Given a list of cities and distances between each pair of cities,
what is the shortest possible route that visits each city and returns to the origin city?"(39). We adapt this
problem to answer "Given a list of monitoring locations and travel times between each pair of locations,
what is the shortest possible route that visits each monitoring site and returns to the origin location?".
We solve this through the implementation of "Concorde's algorithm" (39), through the TSP package in R
(40). First, the 3 × 3m friction surface was converted into a transition matrix through use of the
"*transition*" function in the gdistance R package (41). Second, the pairwise distances between each site
was calculated to produce a distance matrix, through use of the "*costDistance*" function in the gdistance
package. We then implemented the TSP using the function "*TSP*" and the distance matrix, and solved
the TSP with "*solve_TSP*"; both functions are from the TSP R package. By following the route identified
by solving the TSP, and incorporating 30-minute stays at each pair of sites to deploy traps and/or collect
samples, we group sites into 'clusters' which are feasible to visit within a 5-hour sampling day.
318

Results

GPS data collection: To inform estimates of on-road travel cost for each 3m × 3m and 0.5m × 0.5m cell within Koboko district, Northern Uganda, we obtained tracking data during three periods: May-June 2017, February-April 2018, and December 2018-January 2019. Tracks collected between May 2017 - April 2018 were used to inform road speeds, and tracks collected between December 2018-January 2019 were withheld for validating the resistance surfaces (Fig. S3).

OpenStreetMap accuracy assessment: Analyses evaluating the accuracy of an existing, community-driven, open-source road network (from OpenStreetMap), indicate that at least one road exists within the OpenStreetMap (OSM) dataset for 17 out of 25 randomly sampled 1km^2 grid squares across Koboko district (mean road length = 1.97 km). Only one out of 25 grid squares contained no visible roads across sources (i.e. 0.5m imagery, 3m imagery, and OSM). When comparing total road length visible in 3 × 3m imagery with that charted by OSM, the two sources show close agreement (97.43% similarity [total road length across 25km^2], paired t-Test p = 0.91), however, when comparing the 0.5 × 0.5m imagery and the OSM dataset, only 28.16% of digitised roads are charted by OSM (paired t-Test p < 0.001, Fig. 1, Table S1, Fig. S4). This section of the analysis provided the rationale for the classification of 0.5m imagery, with the inclusion potentially capturing up to 71% more roads than OSM within the study area.

Fig. 1. Example of composite images of digitised road networks within Koboko district. Purple roads represent roads visible in 0.5m imagery (17), as digitised in this study; black roads represent roads visible in 3m imagery (24), as digitised in this study, and light blue roads represent roads available within the OSM dataset (18). The overlap of all three colours indicate areas of consistency across sources.

Image classification: Classification of two differing sources of remotely sensed imagery (0.5 × 0.5m and 3 × 3m) yielded varying accuracies across classes, and across spatial resolutions, with accuracy values ranging from 38% to 89% for dirt roads and 5% to 84% for tarmac roads for 3m and 0.5m imagery respectively (Table 3; Fig. 2). Overall image classification accuracy, considering all five classes utilised (dirt road and/or track, tarmac road, dense vegetation, grassland and barren land), ranged from 53% (3m) to 78% (0.5m), with 0.5m imagery proving to be more effective at identifying both dirt and tarmac roads than the 3m imagery.

Fig. 2. Confusion matrices for the classification of each surface (Left: 3m, Right: 0.5m). Diagonal squares (bottom left to top right) indicate the percentage of correctly classified cells per class.

Table 3. Maximum likelihood classification (MLC) accuracy assessment validation values for each class. Values represent the percentage of correctly classified cells (classified *vs* ground truth) for the five classes of interest.

Class	3m imagery			0.5m imagery		
	Correct	Incorrect	Accuracy (%)	Correct	Incorrect	Accuracy (%)
Dirt road and/or track	38	62	38.00	97	11	89.81
Tarmac road	5	95	5.00	84	16	84.00
Dense vegetation	91	9	91.00	95	5	95.00
Grassland	65	34	65.65	80	20	80.00
Barren land	70	30	70.00	38	54	41.30
Overall	**269**	**230**	**53.91**	**394**	**106**	**78.80**

Resistance surface and cost-distance analysis: The accuracy of the resistance surfaces was assessed by
investigating the relationship between observed travel times and predicted travel times using withheld
field-obtained GPS tracks and a linear regression. Predicted values produced utilising the 3m resistance
surface have a much closer alignment with ground truth (observed) values, root-mean-square error
(RMSE) = 3.93 (3m) than the 0.5m resistance surface (RMSE = 6.01). In separate regressions with
validation data from both surfaces, we identify that there is a significant association between observed
and predicted values ($p < 0.001$ (0.5m) and $p < 0.001$ (3m)), indicating a high performance of each
surface, with the 3m surface showing a stronger relationship with less variability ($R^2 = 0.66$ vs
$R^2 = 0.49$, 3m and 0.5m respectively). Summaries of resistance surface validation are provided within
Fig. S5 and Table 4. Output cost-distance surfaces detailing the travel time from the location of our field
station to each gridded cell within Koboko district are provided as Fig.3.
368
369 **Table 4.** Model summaries for resistance surface validation. Summary statistics from four separate
370 linear regressions are provided.
371

	3m resistance surface		0.5m resistance surface	
	Training data	Validation data	Training data	Validation data
p-value	< 0.001	< 0.001	< 0.001	< 0.001
Coefficient	1.10	0.59	0.78	0.34
RMSE	1.11	3.93	0.85	6.01
R^2	0.93	0.66	0.95	0.49

372
373 **Fig. 3.** Cost-distance surfaces. Figures show the cumulative travel time from the field site origin (black
374 point), to each subsequent cell within the surface. Left: 3m cost-distance surface, Right: 0.5m cost-
375 distance surface. This figure was generated using ArcGIS version 10.4 (42), and products derived in this
376 study from image classification of Planet (3m)(24) and Airbus (0.5m)(17) satellite imagery.
377
Identification of optimal sentinel site placement: Utilising the 3m cost-distance surface and a predictive
surface of tsetse abundance (11), we identified the optimal placement of 104 sentinel sites within the
current intervention area (52 paired locations) (Fig. 4). Such sites are positioned within the most easily
accessible, high abundant locations for 26 unique 5 x 5 km strata across the intervention area. Optimal
sentinel-site placement identifies locations with abundance values ranging from 0.04- 19.57 (mean =
5.21) flies per cell, and locations which are within 5.55 - 151.81 (mean = 68.42) minutes from the field
station location.
385
386 **Fig. 4.** Optimal placement of sentinel sites (max two sites per grid square [25km^2]) within Koboko
387 district. Location of optimal sites visualised alongside the 3m accessibility surface (this study) and tsetse
388 abundance surface (11), dashed lines represent the 5 x 5km sampling strata used to allocate optimal
389 sites. This figure was generated using ArcGIS version 10.4 (42).
390
Identification of the optimal route: Utilising the coordinates of the 52 paired monitoring site locations,
derived above, we implemented the traveling salesperson problem (TSP) to identify the optimal route in
which to visit these sites. The result of the TSP is shown as Fig. 5. Based on the assumption that the
field-team will spend up to 5 hours sampling per day, incorporating travel times, we grouped sites to
identify sampling clusters to visit per day. We show that a sampling period of four days is required to
ensure that all sample locations are visited.
397

398 **Fig. 5.** Left: Optimal route in which to sample the identified sentinel sites within Koboko district. Right:
399 Clusters of sentinel sites are identified by enforcing a maximum sampling and travel period of 5-hours
400 within Koboko district. This figure was generated using ArcGIS version 10.4 (42).
401

Discussion
This analysis investigated the ability of high-resolution satellite imagery to inform estimates of
accessibility to entomological sampling sites, using tsetse control as an example application. We started
by scrutinising the completeness of an existing open source road network for Koboko district, Uganda,
comparing charted roads with those obtainable from manual digitisation of remotely sensed (RS)
imagery at two differing spatial resolutions. Results from this section of the analysis indicate that, for
this region of Uganda, roads visible within 3m imagery matched 97.43% of roads identified in
OpenStreetMap (OSM) (paired t-Test $p = 0.91$) (Fig. 1, Table S1). Comparing roads visible within 0.5m RS
imagery, and those charted by OSM, yields 28.16% consistency across sources (paired t-Test $p < 0.001$)
(Table S1).
412

As data published on OSM is the result of community contributions incorporating local knowledge, data
coverage is often inconsistent. The recent establishment of several refugee camps across the West Nile
Region has resulted in increased road mapping efforts within this area, which explains the high levels of
coverage seen here (43). OpenStreetMap completeness varies globally and the analyses we have
developed will be particularly useful in places where OSM and standard sources of information on road
networks are scant (44).
419

Part of our analysis aimed to infer the effect of including spatially disaggregated data on estimates of
accessibility, detailing whether the extra information obtainable from 0.5m imagery produces refined
estimates. The results of a maximum likelihood classification algorithm indicate a high ability to identify
roads and associated features within the 0.5m imagery, mirroring that seen by manual digitisation
(Table 3; Fig. 2). Results from image classification also indicate that the spatial detail available within 3m
imagery is too coarse to classify roads in this district accurately (38% and 5% accuracy for dirt and
tarmac roads respectively). This result is to be expected as the majority of roads within Koboko district
rarely exceed a width of 3m, resulting in decreased visibility; narrow roads are likely to be common
across large parts of rural Africa (45). The utility of 3m imagery may be greater in more developed areas,
where roads exceed 3m in width.
430

Despite a higher image classification accuracy and a better model fit to training data, the 0.5m
resistance surface appears to under-perform when presented with withheld GPS tracking data
compared to the 3m resistance surface (Table 4, Fig. S5). Both resistance surfaces show a significant
linear relationship between observed and predicted values, however, the 3m resistance surface has a
lower root-mean-square error (3.93 *vs* 6.01 respectively). This under-performance may be due to the
increased number of roads within the 0.5m resistance surface, and some of the assumptions made
regarding travel along roads of differing class. While we have used the best possible information
available to us, there will invariably be additional factors that may affect how accessible a location is.
Should, in practice, a location be more difficult to access than predicted using our approach, an
alternative location will be selected based both on the outcome of this approach and field-based
information. We envisage this process to be somewhat iterative, with new GPS data collected during the
first visit to a proposed monitoring site. This new data may be used to improve surface validation and
refine some of the assumptions made during the approach described here. When using the surfaces to
identify optimal placement of sentinel-sites, the relative travel-time to each cell is as informative as the

actual travel-time. Despite varying RMSEs, the significant relationship between predicted and observed
travel times, support the utility of the generated surfaces.
447
By combining the generated 3m accessibility surface (Fig. 3) with previously published estimates of
tsetse-abundance (11), we provide a novel framework for the identification of efficient locations in
which to place sentinel-monitoring sites (Fig. 4). Previous methods to inform the placement of sentinel-
monitoring sites have been based on intuition, incorporating knowledge of tsetse ecology and local
knowledge of roads within an intervention area. Here, we further quantify this process, providing a
more robust approach that can be applied to a range of vector-borne diseases. The movement from a
nuanced, ad-hoc process to an evidence-based one will allow for a more efficient assessment of tsetse
control programmes. Although we have provided a quantifiable approach for prioritising spatial
sampling of disease vectors, we are aware that knowledge of additional country and context specific
factors such as varying vector behaviours and geographic accessibility are invaluable for designing and
implementing an effective monitoring program. Such approaches should be tailored for the vector,
disease, and country of interest, with the work described here providing a framework from which to
build. Local knowledge can still be useful in the design and implementation of this approach, potentially
when identifying changes in accessibility (such as the creation or disuse of roads), or through refinement
of selected sites. The application of the methods used here to the context of intervention monitoring
and assessment is novel, and the refinement of results has several cost-effective implications as vector
control expands to other areas within the region.
465
The distribution and abundance of disease vectors dynamically change in response to variations in biotic
and abiotic conditions (46, 47). The methodology described here is receptive to new surfaces detailing
expanding or decreasing species ranges, however our approach is focused on identifying static
monitoring sites based off conditions at the time of implementation of the intervention. Periodic
updates to OSM data may be used to generate contemporary geographic accessibility surfaces reflecting
the creation of new road networks or the disuse of others. Although this methodology has the potential
for dynamic updates, we are aware that our approach requires a technical understanding of GIS and
remote sensing, factors which may prevent uptake and application in developing countries outside of
the framework of internationally supported programs. These factors may be addressed through capacity
strengthening programmes, where GIS skills can be integrated as part of the curriculum.
476
Several important vector-borne NTDs have been targeted for elimination as a public-health problem by
2020 within the WHO NTD roadmap (4). Unfortunately, however, the burden of numerous VBDs will
continue beyond the ambitious 2020 target (48-50). As evident within the WHO roadmap, both disease
and vector surveillance form large components of most elimination strategies; however, the Strategic
and Technical Advisory Group (STAG) for NTDs also recognise the need for a better understanding of the
economic aspects of NTD control. By providing methods to ensure that vector control programmes
operate at maximum efficiency, we can ensure that the limited funding associated with some of these
NTDs has the largest impact.
485
Although this analysis does not serve as an economic evaluation of methods to assess control
programme efficacy, previous work has shown that vehicle running and travel costs are within the top
five associated costs of running a tsetse control programme (51, 52), with staff salaries being the most
expensive element. By strategically placing sentinel-monitoring sites in locations that are associated
with a low accessibility cost, programmes can reduce costs associated with travel (e.g., fuel,
maintenance) and staff expenses, with current costs of tsetse monitoring being ~9.0\$/km^2/year (10.6%
of tsetse control programme budgets) (52). The accessibility surface may also contribute toward cost-

effective planning of pre-intervention surveys, which are responsible for roughly 6% of control program
budgets (52). Furthermore, by informing the positioning of these sites by additional metrics, such as pre-
intervention abundance, we identify locations that may provide more accurate evaluations of control
efficacy. Further research should be performed to evaluate the precise economic gains of this approach.
497
498 Accessibility, in general, is a very sought-after metric and the methodology applied here, although
499 currently restricted to one district in Northern Uganda and limited to the purpose of identifying
500 accessible tsetse monitoring sites, could inform other accessibility analyses within the area such as
501 access to HAT diagnostic centres, and may be applied to a range of vector-borne diseases.
502

Acknowledgements:
JL is funded by a Medical Research Council Scholarship (Award no. 1964851). SJT is funded by grants
from the Bill & Melinda Gates Foundation (OPP1104516), the Biotechnology and Biological Sciences
Research Council, the Department for International Development, The Economic and Social Science
Research Council, The Natural Environment Research Council and the Defence, Science and Technology
Laboratory, under the Zoonosis and Emerging and Livestock Systems (ZELS) programme (Grant no.
BB/L019035/1). The Bill & Melinda Gates Foundation grant OPP1104516 also supports MCS. MCS
acknowledges additional funding from the Medical Research Council (MR/M014975/1). The funders had
no role in study design, data collection and analysis, decision to publish or preparation of the
manuscript. The authors declare no conflicts of interest. The authors wish to thank Dr Simon Wagstaff
and Mr Andrew Bennett for providing the computational resources to perform this analysis.
514

515 **Author contributions:**
516 SJT, MCS and JL conceived and planned the study. JL and AK were involved in field study design and data
517 collection. JL wrote all computer code and designed and performed the analysis. JL wrote the first draft
518 of the manuscript, and all authors contributed toward subsequent revisions. All authors gave final
519 approval for publication.
520

521 **Data Availability:**
522 Due to file hosting limitations, both the 0.5m resolution and 3m resolution resistance surfaces are
523 available upon request from the authors. Code used to generate and validate the resistance surfaces can
524 be found as Supplementary File 2.
525

References:
1.   World Health Organization. Vector-borne diseases 2017 [Available from:
https://www.who.int/en/news-room/fact-sheets/detail/vector-borne-diseases.
2.   Sedda L, Lucas ER, Djogbenou LS, Edi AVC, Egyr-Yawson A, Kabula BI, et al. Improved spatial
ecological sampling using open data and standardization: an example from malaria mosquito
surveillance. bioRxiv. 2018:465963.
3.   Franco JR, Cecchi G, Priotto G, Paone M, Diarra A, Grout L, et al. Monitoring the elimination of
human African trypanosomiasis: Update to 2014. PLoS Negl Trop Dis. 2017;11(5):e0005585.
4.   World Health Organization. Accelerating work to overcome neglected tropical diseases: a
roadmap for implementation. Geneva; 2012.
5.   Moloo A. Eliminating sleeping sickness as a public health problem is on track 2017 [Available
from: http://www.who.int/trypanosomiasis_african/news/HAT_elimination_on_track/en/.
6.   Picozzi K, Fèvre E, Odiit M, Carrington M, Eisler MC, Maudlin I, et al. Sleeping sickness in Uganda:
a thin line between two fatal diseases. BMJ. 2005;331(7527):1238-41.

7.   Berrang-Ford L, Odiit M, Maiso F, Waltner-Toews D, McDermott J. Sleeping sickness in Uganda:
revisiting current and historical distributions. Afr Health Sci. 2006;6(4):223-31.
8.   Welburn SC, Coleman PG, Maudlin I, Fevre EM, Odiit M, Eisler MC. Crisis, what crisis? Control of
Rhodesian sleeping sickness. Trends in parasitology. 2006;22(3):123-8.
9.   Tirados I, Esterhuizen J, Kovacic V, Mangwiro TNC, Vale GA, Hastings I, et al. Tsetse control and
Gambian sleeping sckness; implications for control strategy. PLoS Negl Trop Dis. 2015;9(8):e0003822.
10.   Lehane M, Alfaroukh I, Bucheton B, Camara M, Harris A, Kaba D, et al. Tsetse control and the
elimination of Gambian sleeping sickness. PLoS Negl Trop Dis. 2016;10(4):e0004437.
11.   Stanton MC, Esterhuizen J, Tirados I, Betts H, Torr SJ. The development of high resolution maps
of tsetse abundance to guide interventions against human African trypanosomiasis in northern Uganda.
Parasit Vectors. 2018;11(1):340.
12.   Juran S, Broer PN, Klug SJ, Snow RC, Okiro EA, Ouma PO, et al. Geospatial mapping of access to
timely essential surgery in sub-Saharan Africa. BMJ Glob Health. 2018;3(4):e000875.
13.   Agbenyo F, Marshall Nunbogu A, Dongzagla A. Accessibility mapping of health facilities in rural
Ghana. J Transp Health. 2017;6:73-83.
14.   Ouma PO, Maina J, Thuranira PN, Macharia PM, Alegana VA, English M, et al. Access to
emergency hospital care provided by the public sector in sub-Saharan Africa in 2015: a geocoded
inventory and spatial analysis. Lancet Glob Health. 2018;6(3):e342-e50.
15.   Delamater PL, Messina JP, Shortridge AM, Grady SC. Measuring geographic access to health
care: raster and network-based methods. International journal of health geographics. 2012;11(1):15-.
16.   Planet. Planet imagery product specification: PlanetScope & RapidEye. 2016.
17.   Airbus. Satellite Data 2019 [Available from: https://www.intelligence-airbusds.com/en/8289-
imagery-services.
18.   OpenStreetMap contributors. Geofabrik OpenStreetMap Data Extracts. 2018.
19.   ESRI. ArcMap 10.3: Spatial Analyst Toolbox: How Maximum Likelihood Classification works 2016
[Available from: http://desktop.arcgis.com/en/arcmap/10.3/tools/spatial-analyst-toolbox/how-
maximum-likelihood-classification-works.htm.
20.   Houben RM, Van Boeckel TP, Mwinuka V, Mzumara P, Branson K, Linard C, et al. Monitoring the
impact of decentralised chronic care services on patient travel time in rural Africa - methods and results
in Northern Malawi. International journal of health geographics. 2012;11:49.
21.   Soule RG, Goldman RF. Terrain coefficients for energy cost prediction. J Appl Physiol.
1972;32(5):706-8.
22.   Uganda Bureau of Statistics. Projections of demographic trends in Uganda 2007-2017. Kampala,
Uganda: Uganda Bureau of Statistics,; 2016.
23.   World Health Organization. Global Health Observatory data repository: Human African
Trypanosomiasis: World Health Organization; 2019 [Available from:
http://apps.who.int/gho/data/node.main.A1635?lang=en.
24.   Planet. Planet Explorer 2018 [Available from:
https://www.planet.com/explorer/#/mosaic/global_monthly_2018_04_mosaic.
25.   ASTRIUM. Pléiades Imagery - User Guide. 2012.
26.   Bohannon RW. Comfortable and maximum walking speed of adults aged 20—79 years:
reference values and determinants. Age Ageing. 1997;26(1):15-9.
27.   Demirović D. An Implementation of the Mean Shift Algorithm. Image Processing On Line.
2019;9:251-68.
28.   ESRI. Filtering classified output 2019 [Available from:
https://desktop.arcgis.com/en/arcmap/latest/extensions/spatial-analyst/image-classification/filtering-
classified-output.htm.

29.   ESRI. Smoothing class boundaries and clumping classified output 2019 [Available from:
https://desktop.arcgis.com/en/arcmap/latest/extensions/spatial-analyst/image-
classification/smoothing-class-boundaries-and-clumping-classified-output.htm.
30.   ESRI. Generalizing classified output by removing small isolated regions 2019 [Available from:
https://desktop.arcgis.com/en/arcmap/latest/extensions/spatial-analyst/image-
classification/generalizing-classified-output-by-removing-small-isolated-regions.htm.
31.   Facebook Connectivity Lab, Center for International Earth Science Information Network - CIESIN
- Columbia University. High Resolution Settlement Layer. 2016.
32.   Traffic and Road Safety Act (Uganda). The Traffic and Road Safety (Speed Limits) Regulations,
2004.; 2004. Contract No.: Section 131(k) of the Traffic and Road Safety Act, Cap. 361.
33.   Ministry of Works and Transport. The Highway Code. Uganda; 2009.
34.   Sellers PJ. Canopy reflectance, photosynthesis and transpiration. Int J Remote Sens.
1985;6(8):1335-72.
35.   Ranga B. Myneni, Forrest G. Hall, Piers J. Sellers, Marshak A. The interpretation of spectral
vegetation indexes. IEEE Trans Geosci Remote Sens. 1995;33(2):481-6.
36.   QGIS Development Team. QGIS Geographic Information System version 3.4.4. Open Source
Geospatial Foundation Project. http://qgisosgeoorg. 2019.
37.   FlowMap Group. QGIS Python Plugins Repository: Least-Cost Path
(https://github.com/Gooong/LeastCostPath) 2019 [Available from:
https://plugins.qgis.org/plugins/leastcostpath/.
38.   Dijkstra EW. A note on two problems in connexion with graphs. Numerische Mathematik.
1959;1:269–71.
39.   Applegate D, Cook W, Rohe A. Chained Lin-Kernighan for Large Traveling Salesman Problems.
INFORMS Journal on Computing. 2003;15(1):82-92.
40.   Hahsler M, Hornik K. TSP Infrastructure for the Traveling Salesperson Problem. Journal of
Statistical Software; Vol 1, Issue 2 (2008). 2007.
41.   van Etten J. gdistance: Distances and Routes on Geographical Grids. R package version 1.2-2.
2018 [Available from: https://CRAN.R-project.org/package=gdistance.
42.   ESRI. ArcGIS Desktop: Release 10.4.1. Redlands, CA: Environmental Systems Research Institute.;
2011.
43.   Geoffrey Kateregga. Community mapping for refugees in Uganda 2018 [updated 19th March
2019. Available from: https://2018.stateofthemap.org/slides/T037-
Community_Mapping_for_Refugees_in_Uganda.pdf.
44.   Barrington-Leigh C, Millard-Ball A. The world's user-generated road map is more than 80%
complete. PLoS One. 2017;12(8):e0180698.
45.   Riverson J, Gaviria J, Thriscutt S. Rural Roads in Sub-Saharan Africa: Lessons from World Bank
Experience. Washington, D.C.; 1991.
46.   Burkett-Cadena ND, McClure CJW, Estep LK, Eubanks MD. Hosts or habitats: What drives the
spatial distribution of mosquitoes? Ecosphere. 2013;4(2):art30.
47.   Smith DL, Dushoff J, McKenzie FE. The Risk of a Mosquito-Borne Infectionin a Heterogeneous
Environment. PLOS Biology. 2004;2(11):e368.
48.   Ferguson NM. Challenges and opportunities in controlling mosquito-borne infections. Nature.
2018;559(7715):490-7.
49.   Hotez PJ, Basáñez M-G, Acosta-Serrano A, Grillet ME. Venezuela and its rising vector-borne
neglected diseases. PLoS Negl Trop Dis. 2017;11(6):e0005423.
50.   Mackey TK, Liang BA, Cuomo R, Hafen R, Brouwer KC, Lee DE. Emerging and reemerging
neglected tropical diseases: a review of key characteristics, risk factors, and the policy and innovation
environment. Clin Microbiol Rev. 2014;27(4):949-79.

51.   Muhanguzi D, Okello WO, Kabasa JD, Waiswa C, Welburn SC, Shaw AP. Cost analysis of options
for management of African animal trypanosomiasis using interventions targeted at cattle in Tororo
district; south-eastern Uganda. Parasit Vectors. 2015;8:387.
52.   Shaw APM, Tirados I, Mangwiro CTN, Esterhuizen J, Lehane MJ, Torr SJ, et al. Costs of using "Tiny
Targets" to control *Glossina fuscipes fuscipes*, a vector of Gambiense sleeping sickness in Arua district of
Uganda. PLoS Negl Trop Dis. 2015;9(3):e0003624.

Travel time (minutes)

240+

● Koboko origin

Travel time (minutes)

120+

● Koboko origin

Travel time
High
Low

Tsetse abundance
High
Low

Strata

● Optimal sentinel site

Monitoring clusters
— 1
— 2
— 3
— 4

▲ Koboko origin
--- TSP route
• Optimal monitoring sites