1   A Suboptimal Model Explained the Spatiotemporal Control of Human Eye Movements in

2   Visual Search

3   Yunhui Zhou[1], Yuguo Yu[1,2*]

[1] School of Life Sciences, Fudan University, Shanghai 200433, P.R. China

[2] Human Phenome Institute, Institutes of Brain Science, Institute of Science and Technology

for Brain-Inspired Intelligence, Fudan University, Shanghai 200433, P.R. China.

[*] Correspondence should be addressed to:

Yuguo Yu, Ph.D.

Institute of Science and Technology for Brain-Inspired Intelligence, Fudan University,

Shanghai 200433, China. Email: yuyuguo@fudan.edu.cn

Author contributions: Y.Y. supervised the research, Y.Z. and Y.Y. designed the research,

Y.Z. performed the research, wrote the analysis tools and analysed the data, Y.Z. and Y.Y.

wrote the paper.

Conflict of Interest: The authors declare no competing financial interests.

18   **Abstract**

To search for the visual target, humans perform high-speed eye movements across

spatial locations. However, the efficiency of human search strategy is still controversial.

Previous studies showed that humans can optimally integrate information across fixations

and determine the next fixation location. However, such a model ignored the temporal

control of eye movement and the limited memory capacity of human brain. Here, we

measured the temporal course of human visibility map and recorded the eye movements of

human subjects performing a visual search task. We further built a continuous-time eye

movement model which mimics human eye behaviors well. The model suggested that

humans determined fixation location suboptimally compared to the Bayesian optimal

searcher due to saccadic bias, and predicted the visual memory capacity was around 8

fixations, which is consistent with some previous experimental studies. The saccadic bias

suggests that humans may control eye movements by both heuristics and current task

demands. This mixed control strategy may have adaptive advantages compared to an optimal

searcher considering the limitations of the human brain energetics and statistics of the natural

environment.

Introduction

For animals with foveated retina, efficient visual search is important for survival, and

requires close-to-optimal planning of eye movement both in space and time. Currently, there

are conflicting evidence on whether human can make spatially optimal eye movements.

Najemnik & Geisler [1–3] have shown that humans can perform close to optimal models in a

multi-saccade visual search task, but other studies indicated that human may rely more on

suboptimal heuristics rather than calculating and planning optimal eye movement for a

specific task [4–6]. Optimally planning eye movements has the advantage of analyzing the

environment at a faster speed, but following simple heuristics also has the advantage of

conserving computational power, so in reality human may trade off in between. Besides, the

ideal searchers have unlimited visual memory [1,3], so it is impossible that human strictly

follows the optimal search rule. We therefore reconsider the question of how optimal do

humans search, and ask if a visual search model with more biological limitations can perform

more closely to humans.

Moreover, there is a surprising lack of consideration of time in visual search models.

For example, the Target Acquisition Model does not explain fixation duration [7,8]; the ideal

searchers assume each fixation last for 250 ms [1,3]; and the Guided Search model assumes

fixation duration is 200 – 250 ms [9]. We found only one model that considered fixation

times [10], but the model did not explicitly model how information accumulates over time,

and only explained the mean fixation duration. However, for visual tasks like reading and

free viewing, there are models that fully capture the fixation duration distribution by

simulating the stochastic information accumulation process [11–14]. Although such

stochastic accumulation process has been observed in electrophysiological recordings [15],

the accumulation process in these models are usually artificial rather than based on

experiment data. What's more, eye movement models of scene viewing do not actually

acquire information from the stimulus, instead they simply fit eye movement metrics *per se*

by image features, so it is unknown whether these models can actually perform visual search

with human-level performance. To bridge the gap, we believe that a model of visual search

that fully explains the spatiotemporal control of eye movements should combine the merits

from existing models of both visual search and scene viewing.

In this research, we experimentally measured the accumulation of visual information

by the brief stimulus exposure method. The data was then used to formulate a drift-diffusion

process that decides saccade timing. Combined with the ideal search theory, we proposed a

continuous-time optimal searcher that determines both fixation location and fixation

duration. We found that human participants do not follow the optimal search strategy. Then,

we derived a suboptimal model with a constraint on the saccade amplitude and memory

capacity that better agrees with participants' eye movement statistics compared to the

continuous-time ideal searcher.

72   **Results**

Selecting Target Contrast

The stimulus image was a Gabor target (6 cycle/degree, 0.3 degrees in diameter)

embedded in a circular naturalistic background noise image (15 degrees in diameter, root-

mean-squared (RMS) contrast 0.2) (Figure 1A). To normalized the task difficulty across

participants, we first measured the relationship between foveal target visibility and target

RMS contrast. The participants' correct response rate can be well fitted by a Weibull

psychometric function given the target RMS contrast (Fig 1B). Visibility was positively

related to the target RMS contrast and can be described by Equation 2 (Fig 1C). For each

participant, we selected the target RMS contrast that made visibility equals to 3.0 (Fig 1C).

The selected value ranged from 0.111 to 0.125, with a mean value of 0.121.

Temporal Course of Target Visibility and the Evidence Accumulation Model

We then measured how target visibility changed over time within one fixation across

the visual field by a brief stimulus presentation experiment. The target visibility first

increased as a function of time, and then reached stable peak values after stimulus onset (Fig

1D and Fig 1E). The steady-state foveal visibility was approximately 3.14, which was close

to the predefined value of 3.0. The rising speed of visibility varies across the visual field. In

the foveal region, the visibility peaked rapidly within the initial 100 ms; however, the

peripheral regions rose slower and had lower peak visibility levels (Fig 1E). Notably, at just

2.25° (30% of the image radius) away from the fovea, the target visibility peaked after

approximately 400 ms (Fig 1E). Therefore, the participants identified targets faster in the

fovea and much slower in the peripheral regions.

To mathematically describe the change of visibility over time, we formulated an

evidence accumulation model constrained by the measured visibility. The model integrated

random independent samples over time in a leaky manner, i.e. earlier samples were given

lower weight. Leaky integration seems necessary because otherwise visibility can be

arbitrary high given enough samples (S1 Text). The integration produced a drift-diffusion

process. The drift direction depends on target's presence at the location, and at each time

point, the variability of accumulated information is constrained by the measured visibility.

After fitting the model parameters by experiment data, we could analytically describe the

change of visibility at any location in the visual field (Equations 3-5, Fig 1D, Fig 1E). The

evidence accumulation model allowed us to analytically calculate the change of target

location's probability over time, and the variability allowed us to capture the distribution of

fixation duration as shown in the following section.

Because the visibility map was measured with the target location cue in the detection

task, one may question the validity of using it in the visual search task when there is no target

cue. We measured the visibility map without a target location cue in another group of 4

participants (Figure S4 in S4 Text) and found that the optimal search performance was much

slower than the participants' performance (Figure S5 in S4 Text). Therefore, in theory, a

visibility map measured without a target location cue does not allow human-level search

performance.

Participants' Spatial Control of Fixation was Inconsistent with the ELM Searcher

Next, we performed a visual search experiment with the same stimulus images to

record participants' eye movement data. To model eye movements control both in space and

time, we combined the evidence accumulation model and the entropy-limit-minimization

(ELM) searcher [1] into a continuous-time ELM (CTELM) searcher.

We first re-examined whether the distribution of the fixation location, saccade

amplitude, and saccade direction could be predicted by the ELM rule. The participants'

fixation density was doughnut shaped, with fewer fixations in the central part of the image

and more fixations at the outer part (Fig 3A). However, there was a fixation "hotspot"

located slightly above the image center. The "hotspot" was actually caused by the first

saccade from a single participant. Because the stimulus images were statistically symmetric

around the center, we choose to focus more on the overall feature of the distribution instead

of the local variation. This doughnut-shaped distribution of fixation locations could be

generated by both the ELM and CTELM searcher (Fig 3A); however, an important difference

emerged when we split the distribution by fixation order. While the distribution of fixation

distances from the image center was relatively stable as the search progressed for the human

searcher, the two models progressively fixated at the outer part of the image (Fig 3C). The

fit to the participants' fixation distance decreased as the search progressed (Fig 3B).

For the saccade amplitude, the participants' distribution was different from the two

optimal searchers' distribution (BC = 0.898 for ELM and BC = 0.900 for CTELM), because

the two optimal searchers generated more long saccades than the participants did (Fig 4A).

The difference was present as early as the third saccade (Fig 4C), and the disparity between

the models' and humans' distributions increased as the search progressed (Fig 4B).

For the saccade direction, the participants preferred to make horizontal and vertical

saccades over saccades of oblique directions, whereas the ELM and CTELM searcher

showed a weak preference of the vertical saccades (Fig 5A). The difference is larger in the

first saccade and after 15 saccades (Fig 5B, Fig 5C). The participants' first saccade was very

biased to the upward direction (-90°) and generated the fixation hotspot located above the

image center. This was the behavior of a single participant; for simplicity of the model, we

chose to ignore this variation. Taken together, our data reveal that participants used a

different search strategy than the ELM rule.

CTELM Searcher Constrained by Memory and Saccadic Bias Explained Participants'

Spatial Control of Fixation

Because the participants actually searched quite fast (2 fixations slower than the ELM

searcher on median, as shown below) and the overall fixation density could already be

captured by the ELM rule, it is possible that the participants' strategy did not deviate

excessively from this rule. Considering that the human brain may be subject to various

limitations, we tested whether a CTELM searcher constrained by a few limitations

(constraint-CTLEM searcher) better explained the participants' data.

To make the model's saccade amplitude distribution better agree with the

participants' data, we applied a penalty function when calculating the expected information

gain of the next fixation (Equations 13 and 14). However, this limitation alone cannot

prevent the model from gradually fixating toward the outer edge of the image. This is

because the ELM and CTELM searchers tended to avoid examined locations that became

larger around the image center as the search progressed. This implied that the perfect

memory of all previous fixations in the ELM and CTELM searcher may be the cause of this

problem, and the human brain does not have an unlimited memory capacity.

Therefore, we vary the constraint-CTELM searcher's memory capacity and examined

how eye movement metrics fit to participants' data as the search progressed. Fig 6 shows

that the distribution of fixation distances was indeed sensitive to memory capacity, and the

matching to the experimental data peaked when the memory capacity was 8 fixations. The

fixation duration and saccade amplitude were less sensitive; however, the fit also peaked at

approximately 8 fixations (Fig 6). Therefore, we choose a memory capacity of 8 fixations to

be the optimal capacity. When the five free parameters in the constraint-CTELM searcher

were re-fit with this capacity, the relationship displayed in Fig 6 did not change.

With a memory capacity of 8 fixations, the constraint-CTELM searcher's fixation

density was still doughnut shaped but had more fixations around the center of the image (Fig

3A). The model's fixation distance distribution was relatively stable after the third fixation

and consistently fit the participants' data (Fig 3B, Fig 3C). The saccade amplitude

distribution of the constraint-CTELM searcher was similar to the participants (BC = 0.967).

There was still a noticeable discrepancy, as the constraint-CTELM searcher made more short

saccades than human participants, but importantly, the fit of the saccade amplitude to the

participants' data remained stable as the search progressed (Fig 4B). For the saccade

direction, the constraint-CTELM searcher performed similar to the ELM and CTELM

searcher (Fig 5A) because we did not introduce the direction bias. However, the fit of the

saccade direction as search progressed was slightly better than the CTELM and ELM

searcher after the 15th saccade (Fig 5B).

Taken together, the participants' saccadic bias and limited memory were at least

partial causes of the suboptimal searching behavior. The eye movement model agreed with

the participants' data better when these limitations were considered.

CTLEM and Constraint-CTELM Searcher Explained Participants' Overall Fixation

Duration

Both the CTELM and constraint-CTELM searcher generated similar overall

distributions of fixation durations compared to the participants (BC = 0.996 for both models,

Fig 7A); however, both models could not fit the first fixation duration's distribution very

well (Fig 7B, Fig 7C). The fitting of the fixation duration as the search progressed was

worse for the CTELM searcher than the constraint-CTELM searcher, especially after the 14th

fixation (Fig 7B). This was not because the CTELM searcher was unable to produce

sufficient trials with more than 14 fixations, as we obtained more data for up to 18 fixations

from the CTELM searcher compared to the participants for calculating the histogram. Taken

together, both models generated similar overall fixation duration distributions; however, they

could only partially explain the participants' changes in fixation duration as the search

progressed.

Constraint-CTELM Searcher Better Explained Participants' Search Performance

With the appropriate choice of target detection threshold TH_{targ}, the three models'

correct response rate (ELM: 88.0%, CTELM: 87.6%, and constraint-CTELM: 87.5%) was

similar to the participants' correct response rate (87.9%). All three models needed a lower

median number of fixations (7 fixations) to find the target compared to the participants (9

fixations). The participants' distribution of fixation numbers had a larger tail (maximum of

164 fixations) than the ELM (maximum of 40 fixations) and CTELM (maximum of 35

fixations) searchers; however, this distribution can be captured by the constraint-CTELM

searcher (maximum of 176 fixations) (Fig 8A).

The constraint-CTELM searchers show a similar degradation of performance to

participants when the target was located more than 5° from the image center, whereas the

ELM and CTELM searcher performed much better due to the unlimited memory (Fig 8B, Fig

8C). However, the constraint-CTELM searcher was unable to capture the participants'

search inefficiency when the target was less than 3° away from the image center (Fig 8B, Fig

8C); thus, there may be other factors limiting the participants' performance. Taken together,

the constraint-CTELM searcher explained the participants' search inefficiency better than the

CTELM and ELM searcher.

CTELM and constraint-CTELM Searcher Detect Target More Reliably Than the ELM Searcher

An unexpected discovery worth noting was that the CTELM and constraint-CTELM

searcher, on average, performed significantly better than the ELM searcher when the target

was less than 3° from the image center (Fig 8C, Table S2). Importantly, if the target

appeared at the image center, the CTELM and constraint-CTELM searcher could detect the

target within the first fixation for 97% of the trials, while the ELM searcher achieved this for

only 53% of the trials. The reason was not that the former two models on average fixated

longer than 250 ms (which the ELM searcher assumed) in the first few fixations (Fig 7C),

because a modified-ELM searcher considering the change of average fixation duration still

performed worse when the target was close to the image center (Figure S6 in S5 Text, Table

S3). The actual reason was that the ELM searcher only considered posterior probability at

exactly 250 ms after the fixation onset, while the CTELM and constraint-CTELM considered

the whole diffusion process. The posterior probability could first rise above the threshold but

drop below it at 250 ms, and in this case the ELM searcher would fail to detect the target, but

the CTELM searcher would not. Fig 9 shows that for any target detection threshold, the

CTELM searcher always detects the target located at the screen center within the first

fixation better than the ELM searcher. Therefore, the better performance of CTELM

searcher actually showed the importance of using a continuous-time eye movement model

rather than a model with fixed fixation duration.

233   **Discussion**

In this research, we first proposed the CTELM searcher, which optimally controls eye

movements both in space and time. We showed that the participants' search strategies were

suboptimal. However, by biasing the model's saccade amplitude and limiting the model's

memory capacity to 8 fixations, we obtain a model that closely matched human eye

movement statistics in visual search. Compared to previous studies, our model no longer

uses artificial evidence accumulation process, agrees with human behavior better, and is

more biologically realistic as it considers limitations in memory. The importance of

modelling the full accumulation process rather than assuming a constant fixation duration

was shown in the better performance of the constraint-CTELM searcher than the ELM

searcher when the target was closed to image center.

Temporal Course of Visual Processing

An interesting result from the detection task is that central vision processed

information faster than peripheral vision. The result agrees with previous findings that scene

gist recognition depends more on central vision during the initial 100 ms of viewing [16]. At

the neuronal level, the initial central advantage is consistent with earlier finding that the

discriminability of neural activities for high contrast gratings peaked rapidly 100 ms after

stimulus onset [17], but what makes peripheral vision be slower in our task remains

ambiguous. A recent neurophysiological study showed that neurons in the anterior part of

inferior temporal cortex responded later to objects presented at peripheral than central visual

field [18], but the exact neural mechanisms leading to this phenomenon is still unknown.

One possible reason was that the discriminability of neural activities for suboptimal gratings

could peaked much slower [17], and that peripheral vision generally tunes for lower spatial

frequencies. From the perspective of our evidence accumulation model, it is possible that the

visual system shortens the integration time at central vision to achieve a faster response speed

but lengthens the integration time at the peripheral region to compensate for the low signal-

to-noise ratio.

The Control of Fixation Duration

Recently, the "mixed control" hypothesis of fixation duration has received

experimental support [19–21] and was adopted in eye movement models of scene viewing

[11,12]. This hypothesis states that fixation duration is controlled by an autonomous timer

and modulated by processing demand from the current fixation. The constraint-CTELM

searcher used a similar control strategy. The autonomous timer and modulation from the

current fixation were implemented as the collapsing bound and the drift-diffusion process,

respectively. Fixation will be prolonged if the model cannot determine whether the current

fixation location has a target because the probability value at the fixation location will not

decrease sufficiently quickly. The introduction of a collapsing boundary may seem arbitrary,

but its existence, though still controversial, has received certain experimental support

[22,23], and it allows human to trade off accuracy for speed if the current visual information

remains ambiguous about target location.

The constraint-CTELM searcher's inability to reproduce the participants' first

fixation duration suggests that the participants initialized the search differently than the

model. Participants could initiate a saccade plan before the trial starts, so they could make

the first saccade earlier; whereas the model had to collect sufficient information before the

first saccade. This may also explain why the participants' average search performance was

inferior when the target was near the image center, because efficient saccade planning

requires sufficient time to plan [24].

Suboptimal Human Eye Movements

The participants' spatial control of eye movements was suboptimal and showed

prominent bias. Considering the importance of vision for survival, finding the possible cause

and evolutionary advantage of this suboptimal behavior is crucial to understanding human

vision strategies in the real world.

First, the participants preferred short saccades, whereas the ELM and CTELM

searcher made more long saccades. The preference is also shown in other visual tasks [25].

Interestingly, the preference for short saccades does not affect the median search step

performance, as shown by the constraint-CTELM searcher. Favoring short saccades may

have adaptive advantages not captured in the current visual search task and models. For

example, for random, nondestructive searching, Levy flights (which favors short flights) can

optimized the number of targets being found per unit distance traveled [26]. Besides, human

saccades are not accurate, and making short saccades may also help to avoid subsequent

corrective saccades because the saccade landing accuracy decreased for longer saccades

[27,28]. Another possible advantage is that the short saccade occupies a shorter flight time;

thus, the disruption of the visual image during the saccade can be minimized [29,30].

Second, as reported in other studies [31,32], participants preferred horizontal and

vertical saccades over saccades of oblique directions. Because the search images were

statistically radially symmetric, the preference could not be generated by image features.

One possible cause of the horizontal preference may be the higher cone density in horizontal

regions of the retina [33]. Indeed, both our data and the visibility map measured by

Najemnik & Geisler [1] showed horizontal enhancement, though the enhancement was

weaker in our data. Najemnik & Geisler [1] showed that the ELM rule could generate the

horizontal saccade bias when the horizontal enhancement of the visibility map was

prominent; however, our results from the three models showed that the horizontal saccade

bias could not be generated when the horizontal enhancement of the visibility map was weak.

Another possible cause of both the horizontal and vertical bias is that the human eye

movements have been adapted to the statistics of the natural environment. Due to the Earth's

gravity, edges in natural scenes are more likely to lie in the horizontal and vertical directions,

and there is often more power in the horizontal and vertical directions than in the oblique

directions [34]. For the human brain, which has limited energy and computational resources,

fixating along the horizontal and vertical edges may have a higher chance of catching

important visual information.

Many studies have shown that human eye movements are suboptimal when optimally

performing a task requiring effortful computation and careful planning [4–6]. Considering

the saccadic bias, we think that the control of the saccade amplitude and saccade direction

may use a similar "mixed control" strategy as for fixation durations. Evolution and early life

experiences may have provided good heuristics when selecting the saccade direction and

amplitude; however, specific demands from the current visual task can further modify these

metrics. The advantage of this strategy is that the computational cost of saccade target

selection may be further reduced to selecting a few random numbers, as even the relatively

efficient ELM rule requires convolving two maps across the visual field in every fixation.

The heuristics may be good enough but not strictly optimal for a particular task. This may

explain why participants searched quite fast but were slower than the optimal model in our

visual search task.

Memory Capacity of Visual Search

Another novel feature in the constraint-CTELM searcher is the limitation of the

memory capacity when integrating information across multiple fixations. This is another

cause of suboptimal behavior and may explain why participants sometimes made more than

100 fixations before finding the target. However, it is interesting that adding a memory

limitation did not change the median number of fixations to find the target compared to the

model with unlimited memory; thus, this may allow humans to reserve memory resources

and energy while maintaining high search performance.

The type of short-term memory that we modeled is most similar to the fragile visual

short-term memory (FVSTM). FVSTM is thought to be an intermediate stage between

iconic visual memory and visual working memory. It has a high capacity of approximately

5-15 items, lasts for at least 4 seconds [35] and has been shown to be tied to the location of

the original visual stimulus [36], making it particularly suitable for integrating information

across multiple fixations to generate a posterior probability map. However, the exact

memory capacity in visual search tasks remains controversial. There are reports indicating

that visual search has a memory of $3 - 4$ items [37], $7 - 9$ items [38,39], and more than 10

items [40]. The predicted memory capacity of 8 fixations of the constraint-CTELM searcher

lies within the range of these reported results and thus may serve as additional evidence in

this debate. However, the exact memory capacity requires future investigations and may

serve as a test of our model.

Limitations of current study

Although the constraint-CTELM searcher explained a range of behavioral data of

visual search, it is still a simple model and does not fully reflect the complexities of the

visual system. First, accurately measure the target visibility is challenging, because the 2IFC

task may not reproduce the actual attention deployment and pre-saccadic enhancement of

visual processing [41] happened in visual search, and introduced perceptual learning at

measured locations. Second, humans may plan multiple fixations ahead during a fixation

[42–44], whereas our model only plans one fixation ahead. Third, the implementation of

memory is still relatively simple. The model either kept information from a fixation or

completely forgot it, whereas human brain memory may gradually decay over time [45,46].

In addition, multiple types of memory may be involved in visual search [47,48].

Participants also had some eye movement features that the constraint-CTELM

searcher could not reproduce. First, the model made more short saccades than did

participants. Many short saccades were made when the target's posterior probability at the

current fixation location was high but not higher than the target detection threshold. In this

case, the model tended to saccade to a nearby location and then saccade back to confirm

whether the target was indeed there. Second, as discussed above, participants terminate the

first fixation earlier than the model, and thus, they may initialize a trial differently.

Nonetheless, we believe that our model can be a starting point for a more complete eye

movement model in the future.

Materials and Methods

Participants

367   Seven student volunteers (4 males and 3 females, age range 19-26 years) participated

368   in the experiment for monetary compensation. One subject was the author (Y.Z). All

369   participants had normal or corrected-to-normal vision. This study was approved and

370   supervised by the Ethics Committee of the School of Life Sciences at Fudan University, and

371   written informed consent was obtained from all participants.

Apparatus

Stimuli were presented on a 24.5-inch BenQ ZOWIE XL2540 LCD monitor at a

resolution of 1920×1080 and a refresh rate of 240 Hz. Participants were seated 70 cm in

front of the display with their heads fixed by a forehead and chin rest. Stimuli were

generated and presented using MATLAB R2017b (MathWorks) and the Psychophysics

Toolbox extensions version 3.0.15 [49–51] running on a Windows 7 (Microsoft) machine.

Eye movements of both eyes were recorded at 2000 Hz with a TRACKPixx3 eye-tracker

(Vpixx Technologies, Canada).

Experiment Design and Statistical Analysis

381   **Target and background image.** The target was a six cycle-per-degree Gabor with a

diameter of 0.3 degrees, oriented 45 degrees counterclockwise from the vertical, and

windowed by a symmetrical raised cosine (half-height width was one cycle of the Gabor).

The background image was a circular naturalistic noise image (whose statistics follow a $1/f$

power spectrum) placed at the center of the screen with a diameter of 15 degrees and root-

mean-squared (RMS) contrast of 0.2 (Fig 1A). The RMS contrast is defined as the standard

deviation of the pixel gray value divided by the mean gray value. The area outside the

background image was set to the mean gray value of the image (0.5). The background

images used in each trial of detection task and visual search task were randomly picked from

a database of 1000 independently generated images.

391   **Eye-tracker calibration.** During each laboratory visit, participants first performed a

392 13-point calibration routine. The outer edge of the 13 points formed a square that covered the

393 circular search area. We repeated the calibration until the average test-retest measurement

394 error of both eyes fell below 0.5°. Recalibration of the eye-tracker was performed whenever

395 the eye-tracking accuracy failed to meet the requirements of the experiment (described

396 below).

397   **Detection task**. The detection experiment contained two sections. In the first section,

we measured the relationship between foveal target visibility and target RMS contrast and

selected the target contrast level that made the foveal visibility equal to 3. Each participant

therefore had a unique target contrast and was used for all subsequent experiments. The goal

was to normalize the target detection difficulty across participants. Before the start of each

trial, a black cross and stroked circle appeared at the center of the screen, indicating the

fixation location and target location. The remaining display area was set to a 0.5 gray value.

Participants began a trial by fixating within 1° from the screen center and pressing a button.

The cross and circle then disappeared for 200−400 ms (chosen randomly), followed by two

250 ms intervals of the stimulus image separated by a 500 ms gray interval. The two

stimulus intervals had the same noise background image; however, a randomly chosen

stimulus had a target at the screen center. The participants then chose the interval that

contained the target with a keyboard. A trial was aborted if the participant fixated more than

1° away from the screen center at any time during the trial. This section contained 4−5

levels of target contrast (depending on the participant's pace), and each level included 200

trials. Trials with different target contrasts were randomly interleaved. We chose the

appropriate target contrast levels (ranging from 0.03 to 0.12) by a pilot experiment for each

participant to avoid floor or ceiling effects.

In the second section, we measured the relationship between the stimulus presentation

time and target visibility along four cardinal directions in the search field. For each

participant, the target RMS contrast was the value obtained from section one. There were

two versions of experiment in this section. Four participants participated in the first version,

four participated in the second version, with one participant (the author Y.Z) participated in

both. The procedure was the same as in section one except that we varied both the stimulus

duration and target location. In the first version of experiment, participants were required to

fixate at the screen center and decide which of the two stimulus intervals contained the target

at the cued location. The experiment contained five blocks (four cardinal directions plus the

screen center). For each block, we chose 3−4 different target locations (except when the

target was at the screen center) and 4−5 levels of stimulus presentation time. The target was

located 0−6.75° (0−90% of the image radius) away from the screen center. In the second

version of experiment, the target location cue was not shown, and in each trial, target location

was randomly chosen from all possible locations in the first version of experiment. When the

target appeared at the screen center, the stimulus duration was chosen from 4 to 200 ms, and

each level was tested for 100 trials. When the target appeared at peripheral locations, the

stimulus duration was chosen from 50 to 700 ms, and each combination of stimulus length

and target location was tested for 50 trials. In the main text we report data from the four

participants in first version of the experiment. Data from the second version was reported in

S4 Text.

The entire detection task contained approximately 5000 trials. Participants finished

these trials by multiple laboratory visits within two months. Before the start of the formal

experiment, participants practiced with approximately 100 trials to stabilize their

performance. Participants received feedback about their performance during practice trials

but did not receive feedback during the formal experiment.

Visual search task. In this experiment, participants were asked to search for the

target within the background noise image as fast as possible while trying to maximize the

response accuracy. The target locations were sampled uniformly inside the search area, and

participants were informed about this feature. Participants began each trial by fixating within

1° of the screen center and pressing a button. Then, the search images appeared and waited

for participants' responses. There was no upper limit on the waiting time. When the

participants found the target, they fixated at the target and pressed a key on the keyboard.

The final fixation location and the target's true location were then shown on the screen. If

the distance between these two locations was less than 1°, we labeled the response as correct.

Participants were asked to report if they had found the correct target location but the response

was judged as incorrect. In this case we would recalibrate the eye tracker. Participants

performed 200−330 (mean = 235) visual search trials depending on their pace and available

time.

Selecting target RMS contrast. We first calculated the hit rate and correct rejection

rate of each target contrast level from behavior data in section one of the detection tasks. The

hit (or correct rejection) rate was defined as the number of trials that target appeared in the

first (or second) interval, and the participant made a correct response, divided by the total

number of trials that target appeared in the first (or second) interval. The relationships

between the hit/correct rejection rate and target RMS contrast c were then separately fit with

a Weibull function:

460
$$f(c) = 0.5 + 0.5 \times \left\{ 1 - \exp\left[-\left(\frac{c}{c_T} \right)^s \right] \right\} \quad (1)$$

461   The threshold parameter c_T and steepness parameter s were estimated by maximum-

462   likelihood methods implemented in the Palamedes Toolbox [52]. The relationship between

463   the foveal target visibility and target RMS contrast could then be estimated by signal

464   detection theory [53]:

465
$$d'(c) = \frac{z\left[f_H(c) \right] - z\left[1 - f_{CR}(c) \right]}{\sqrt{2}} \quad (2)$$

Here, $z(x)$ is the inverse standard normal cumulative distribution function. $f_H(c)$ and $f_{CR}(c)$

are the estimated hit and correct rejection rates given by Equation 1. We could then obtain

the target contrast level that made $d'(c) = 3$.

Fitting the temporal course of the visibility map. Behavior data from different

participants in the second section of the detection task were first pooled together. Target

visibility at each location for each level of stimulus duration was then calculated by Equation

2. The relationship between the visibility d', target location (x,y) relative to the fixation

location, and stimulus duration t were then fit by the following equations:

474
$$d'(x, y, t) = a(x, y) \cdot \sqrt{\frac{1 - \exp\left[-k(x, y) \cdot t\right]}{k(x, y) \cdot \left\{1 + \exp\left[-k(x, y) \cdot t\right]\right\}}} \tag{3}$$

475
$$a(x, y) = p_1 \cdot \exp\left(-p_2 \cdot \sqrt{x^2 + p_5 \cdot y^2}\right) \tag{4}$$

476
$$k(x, y) = p_3 \cdot \exp\left(-p_4 \cdot \sqrt{x^2 + p_5 \cdot y^2}\right) \tag{5}$$

The parameters p_1, p_2, p_3, p_4, p_5 in these equations were estimated by minimizing the

MSE between the calculated and measured visibility data using the GlobalSearch algorithm

in the Global Optimization Toolbox of MATLAB. The derivation of these equations is

shown in the S1 Text.

Eye-tracking data analysis. Eye-tracking data were analyzed by the EYE-EEG

extension [54] of the EEGLAB toolbox [55]. Only the data from the dominate eye

(determined by a hole-in-the-card test) were analyzed. All participants were right-eye

dominant. We used the algorithm described by Nyström & Holmqvist (2010) with default

parameters to classify eye movements into saccades and fixations. In the main text we report

data from the four participants in first version of detection task. Across these participants,

the algorithm identified 15,201 fixations and 16,269 saccades. However, we visually

inspected the data and excluded 12 fixations (.08%) and 15 saccades (.09%) that originated

from recording noise. The data from another four participants in the second version of

detection task was reported in S4 Text. The algorithm by Nyström & Holmqvist excludes

fixations interrupted by blinks or noise; therefore, the number of detected fixation events was

smaller than the number of detected saccade events.

When summarizing fixation metrics, we did not include the last fixations (when a

response was made) for fixation duration to avoid the effects of the participants' motion on

the fixation duration. When collecting fixation locations, we did not include the initial

fixations because, in all the trials, the search started from the screen center. We did not

further remove any saccades when summarizing the saccade metrics.

The Entropy Limit Minimization (ELM) Searcher

We used the ELM searcher [1] as our baseline model. This searcher selects a fixation

location to maximize the expected information gain of the next fixation (equation 11 below).

The ELM searcher greatly reduces the computational burden compared to the Bayesian ideal

searcher while maintaining a similar search performance [1,3] and has received

electrophysiological support [57]. The model can only fixate at 400 locations uniformly

sampled inside the search field (Fig 2B). We set the fixation duration to 250 ms and

evaluated the visibility map using Equations 3-5. The model terminates the search whenever

the posterior probability of the target being at the current fixation location exceeds a

threshold TH_{targ}. The value of TH_{targ} was chosen to make the model's correct response rate

comparable to the participants' data.

The Continuous-time ELM (CTELM) Searcher

We propose the CTELM searcher, which extends the ELM searcher to account for the

distribution of fixation durations. A schematic diagram of the CTELM searcher is shown in

Fig 2A and will be described in the following sections.

Temporal Course of Evidence Accumulation. The accumulation of visual evidence

over time should be derived according to the change in target visibility over time. In brief,

we formulate a drift-diffusion process W_t at each location with the following properties:

(1) At any time t, W_t follows a normal distribution.

(2) At any time t, the expectation and standard deviation obeys $E[W_t] = -E[W_t{'}]$ and

$SD(W_t) = SD(W_t{'})$, where W_t is generated by target plus noise, and $W_t{'}$ is generated by only

noise at this location.

(3) At any time t, $2E[W_t]/SD(W_t)$ equals the target visibility $d{'}$ measured at this

location. This is the definition of $d{'}$ in signal detection theory [53].

In practice, we calculate W_t as the leaky integration of independent normal random

variables ΔW generated within each time interval Δt. If the target appears at this location,

ΔW follows the $N(\Delta t, \sigma^2 \Delta t)$ distribution; otherwise, $N(-\Delta t, \sigma^2 \Delta t)$. The visibility of the target

at this location is then controlled by the parameter σ.

In the S1 Text, we show that if ΔW are integrated perfectly over time, the visibility at

any location will approach infinity given an infinite viewing time. This is impossible in

reality. Therefore, we assume that the weight w of previous evidence decays exponentially

with a speed parameter k over time:

530
$$w(t) = \exp(-k \cdot t) \tag{6}$$

531   The total accumulated evidence W_i at the i^{th} timestep can then be calculated as

532
$$\begin{cases} W_0 = 0 \\ W_i = \Delta W + W_{i-1} \cdot w(\Delta t) \end{cases} \tag{7}$$

In Figure S2 of S1 Text, we show that the values of the parameters k and σ depend on

the queried position (x,y) relative to the fixation location. The value of k is calculated by

Equation 5. The parameter σ is calculated by $\sigma = 4 / \sqrt{2}a$, and the value of a is calculated by

Equation 4.

Calculating Target's Posterior Probability Map. At each time step, the posterior

probability of target being at the i^{th} ($i = 1 \cdots n$, $n = 400$) location can be calculated from the

accumulated evidence from the current and previous fixations by Bayesian theory:

540
$$P_{i,T_F} = P\left(i \mid \mathbf{W}_{L_1,T_1}, \cdots, \mathbf{W}_{L_F,T_F}\right) = \frac{P\left(\mathbf{W}_{L_1,T_1}, \cdots, \mathbf{W}_{L_F,T_F} \mid i\right) p(i)}{\sum_{j=1}^{n}\left[P\left(\mathbf{W}_{L_1,T_1}, \cdots, \mathbf{W}_{L_F,T_F} \mid j\right) p(j)\right]} \tag{8}$$

Here, the fixations are indexed by $1 \cdots F$, and L_F and T_F represent the location and duration of

the F_{th} fixation, respectively. $p(i) = 1/n$ is the prior probability of the target being at location

i. The vector $\mathbf{W}_{L_F,T_F} = \left(W_{1,L_F,T_F}, \cdots, W_{n,L_F,T_F}\right)$ is the accumulated evidence by time T_F of the F_{th}

fixation at all locations. Equation 8 implies that the CTELM searcher has perfect memory

across fixations.

Assuming that visual information is independently accumulated at each location

during each fixation, Equation 8 can be simplified to (see the S2 Text for details):

548
$$P_{i,T_F} = \frac{p(i) \cdot \exp\left[\sum_{f=1}^{F} \frac{a_{i,L_f}^2 \cdot W_{i,L_f,T_f}}{2 + 2\exp\left(-T_f \cdot k_{i,L_f}\right)}\right]}{\sum_{j=1}^{n}\left\{p(j) \cdot \exp\left[\sum_{f=1}^{F} \frac{a_{j,L_f}^2 \cdot W_{j,L_f,T_f}}{2 + 2\exp\left(-T_f \cdot k_{j,L_f}\right)}\right]\right\}} \tag{9}$$

Here, a_{i,L_f} and k_{i,L_f} refer to the parameters a and k in Equations 4 and 5 at location i

during fixation f. By applying Equation 9 to all target locations at each time step, we can

calculate the change in the posterior probability map of the target location over time.

Decision on Saccade Timing. In the model, saccades are triggered randomly in two

different ways according to their relative frequency. The majority (97%) of saccades (normal

saccades) are triggered by a decision process concerning whether the current fixation location

contains the target. The first saccade in a trial is always a normal saccade. If the probability

of the target being at the current fixation location is lower than a threshold, the model makes

a saccade decision. We implemented the saccade threshold $TH_{sac}(t)$ as a "collapsing bound",

similar to certain decision-making models [22,58–60]:

$$\log_{10}\left[TH_{sac}(t)\right] = q_1 \cdot \exp\left[-\left(\frac{t}{q_2}\right)^{q_3}\right] \tag{10}$$

Here, q_1, q_2, q_3 (q_1, $q_3 < 0$, $q_2 > 0$) are parameters whose values are estimated by fitting to

distributions of fixation durations from experimental data. If the next saccade is also a

normal saccade, a new saccade decision process at the next fixation location starts

immediately after a saccade decision is made. Although the model controls the fixation

duration by foveal analysis, saccade timing is not independent from the peripheral analysis.

This is because the fixation duration is controlled by the posterior probability, and, at any

time, the posterior probability at all locations sums to one. If the target is very likely to

present at a peripheral location, this will lower the probability that the target is at the current

fixation location and will terminate the current fixation earlier.

In addition to normal saccades, a small group of low-latency saccades can be

generated by fast subcortical response through superior colliculus [61]. In the model, we set

the frequency of low-latency saccades to 3% according to the frequency of express saccades

in an overlap task [62]. The latency (in seconds) is directly drawn from a gamma distribution

with shape parameter 8 and scale parameter 6.9×10^{-4}, plus a delay of 0.03 seconds. This

latency follows a distribution with mean = 85 ms, 5% percentile = 58 ms, and 95% percentile

= 121 ms, which roughly falls in the 80-120 ms range of express saccade latency [63]. If the

next saccade is a normal saccade, a new saccade decision process at the next fixation location

starts immediately before the delay of 0.03 seconds.

In the model, the delay from the retina to the visual cortex (eye-brain lag) is set to

0.06 seconds [64], and the delay from a normal saccade decision being made to the eye

starting to move (saccade lag) is set to 0.03 seconds [65]. At the start of a new fixation, the

model continues to accumulate information from the previous fixation until the arrival of

new information after the eye-brain lag. We do not consider the duration of a saccade itself

(a saccade is finished instantly) because of saccadic masking [29].

Decision on Saccade Target. As in the ELM searcher, we select the location that

maximizes the expected information gain of the next fixation to be the saccade target:

586
$$L_{f+1} = \arg\max_{L_{f+1}} \left\{ H_{L_f} - \mathrm{E}\left[H_{L_{f+1}} \right] \right\} = \arg\max_{L_{f+1}} \left[\frac{1}{2} \sum_{i=1}^{n} \left(P_{i,T_f} \cdot d_{i,L_{f+1}}'^2 \right) \right] \qquad (11)$$

Here, H_{L_f} is the entropy of the target location at the current fixation, and $\mathrm{E}\left[H_{L_{f+1}} \right]$ is the

expected entropy of the target location if the next fixation location is L_{f+1}.

The deviation of Equation 11 has been shown by Najemnik and Geisler [1], and

requires $d_{i,L_{f+1}}'$ to be a fixed value. However, in the model, $d_{i,L_{f+1}}'$ changes with time. As a

simplification, we set the expected duration of the next fixation to be 0.25 seconds when

evaluating Equation 11. We ran Monte Carlo simulations and found that the expected

information gain calculated in this way had a high Pearson correlation (mean = 0.952, min =

0.912, and max = 0.968) with the actual information gain (Figure S3 in S3 Text).

Decision on Target Location. The search stops whenever the posterior probability at

the current fixation location exceeds a target detection threshold TH_{targ}, and the model sets

the current fixation location as the target location. The value of TH_{targ} was chosen to make

the model's correct response rate comparable to the participants' data.

The Constraint-CTELM searcher

The constraint-CTELM searcher is a suboptimal searcher built to achieve a better fit

to the experimental data. The schematic diagram is the same as the CTELM searcher (Fig

2A); however, we constrained its saccade amplitude distribution and the number of previous

fixations when calculating the posterior probability of the target location.

Decision on Saccade Target. We used a penalty function $H(L_f, L_{f+1}, f)$ to modify the

expected information gain across the search field before selecting the maximum:

$$L_{f+1} = \arg\max_{L_{f+1}} \left[H\left(L_f, L_{f+1}, f\right) \cdot \frac{1}{2} \sum_{i=1}^{n} \left(P_{i,T_f} \cdot d_{i,L_{f+1}}^{'2} \right) \right] \qquad (12)$$

$$H\left(L_f, L_{f+1}, f\right) = \exp\left[-\frac{D\left(L_f, L_{f+1}\right)}{m_1 \cdot g(f)} \right] - \exp\left[-\frac{D\left(L_f, L_{f+1}\right)}{m_2} \right] \qquad (13)$$

$$g(f) = \begin{cases} 2, & f = 1 \\ 1 + 2/(f-1), & f \geq 2 \end{cases} \qquad (14)$$

where $D(L_f, L_{f+1})$ is the Euclidean distance between the current and next potential fixation

location, and m_1 and m_2 are free parameters ($m_1 > m_2$). Equation 13 suppresses the

probability of both short and long saccades to fit the distribution of the saccade amplitude

from human data. Equation 14 further fine tunes the parameter m_1 according the index of the

current fixation. The forms of Equations 13 and 14 were selected by hand.

Memory Capacity. For simplicity, we set the memory of the model to be all-or-none,

that is, the model either retains complete information from a fixation or completely forgets it.

A model with a memory capacity of M can only integrate information from the past $M-1$

fixations plus the current fixation. The posterior probability target being at location i could

be calculated as (see S2 Text for the derivation of this formula):

619
$$
P_{i,T_F} = \frac{p(i) \cdot \exp\left[\sum_{f=\min(1,F-M+1)}^{F} \frac{a_{i,L_f}^2 \cdot W_{i,L_f,T_f}}{2 + 2\exp\left(-T_f \cdot k_{i,L_f}\right)} \right]}{\sum_{j=1}^{n_0}\left\{ p(j) \cdot \exp\left[\sum_{f=\min(1,F-M+1)}^{F} \frac{a_{j,L_f}^2 \cdot W_{j,L_f,T_f}}{2 + 2\exp\left(-T_f \cdot k_{j,L_f}\right)} \right] \right\}}
\tag{15}
$$

To find the appropriate memory capacity, we first fit the free parameters with

unlimited memory in the model and then evaluated the model with various memory

capacities. We calculated the Bhattacharyya coefficients (BC) of the fixation duration

distribution, saccade amplitude distribution, and distribution of fixation distance from the

image center for each of the initial 20 fixations and saccades using Equation 18 and then

averaged across the ordinal positions. This allowed us to evaluate how the model fit the data

over time. We then chose the memory capacity that best fit the data and refit the five free

parameters in Equations 10 and 13.

Fitting Model Parameters

Table S1 shows a summary of the parameters used in the ELM, CTELM, and

constraint-CTLEM searcher. The ELM searcher does not have free parameters that control

the eye movement statistics.

For the CTELM searcher, there are three free parameters in Equation 10 that control

the distribution of the fixation duration. The remaining parameters were estimated from

experimental data and fixed when fitting the free parameters. The values of the free

parameters were estimated by genetic algorithm [66] that minimized the sum of the

Bhattacharyya distance (DB) between the simulated and experimental histograms of the

fixation duration (T_{sim}, T_{exp}):

638
$$Loss = DB\left(T_{sim}, T_{exp}\right) \tag{16}$$

639 where the $DB(H_1, H_2)$ of the two histograms H_1 and H_2 is defined as

640
$$DB\left(H_1, H_2\right) = -\ln\left[BC\left(H_1, H_2\right)\right] \tag{17}$$

641
$$BC\left(H_1, H_2\right) = \sum_{i=1}^{N} \sqrt{H_1(i) \cdot H_2(i)} \tag{18}$$

Here, N represents the number of bins in the two histograms. The histogram should be

calculated as probability. The genetic algorithm was implemented in the Global

Optimization toolbox of MATLAB. We set the population size to 150 and max generations

to 25, leaving the other parameters unchanged. For each parameter sample in the population,

the model was run for 1000 times to obtain the histogram of fixation durations. We used the

Multicore package (https://www.mathworks.com/matlabcentral/fileexchange/13775-

multicore-parallel-processing-on-multiple-cores) to run the genetic algorithm on multiple

computers. A single fitting session took approximately 5 hours to run on a cluster of 14

computers.

For the constraint-CTELM searcher, we fit the five free parameters (Equations 10 and

13) by the genetic algorithm. The cost function is the sum of the Bhattacharyya distance

(DB) between the simulated and experimental histograms of the fixation duration (T_{sim}, T_{exp})

and saccade amplitude (A_{sim}, A_{exp}):

655
$$Loss = DB\left(T_{sim}, T_{exp}\right) + DB\left(A_{sim}, A_{exp}\right) \tag{19}$$

We set the population size to 250 and max generations to 25, leaving the other

parameters unchanged. For each parameter sample in the population, the model was run

1000 times to obtain the histograms of the fixation durations and saccade amplitudes.

Simulating Visual Search

The three models were evaluated for 10000 trials to obtain eye movement statistics.

We randomly rotate the 400 potential target locations around the image center before each

trial to obtain a smooth distribution of fixation locations. The target locations were randomly

selected with equal probability in each trial.

To obtain the relationship between target eccentricity and number of fixations needed

to find the target, we set the target to appear more frequently around image center during the

simulation, so that roughly equal number of trials could be obtained when grouping

simulation trials according to target eccentricity. The three models were evaluated for 10000

trials to obtain eye movement statistics

To obtain the relationship between memory capacity and the model's eye movement

metrics, we first assumed unlimited memory capacity in the constraint-CTELM searcher, and

fit the five free parameters (equation 10, 13) according to participants' data. We then

evaluated the model with memory capacity of 2, 4, $\cdots$, 14 and infinite fixations for 10000

times each. The TH_{targ} value was set to 0.97. For the simulation result belonging to each

capacity, we calculated the histograms of fixation duration, fixation distance and saccade

amplitude of the initial 21 fixations and 20 saccades. Then for each of the above three eye

movement metrics, we calculated the BC value between histograms of simulation and

experiment data corresponding to the same fixation or saccade index. Thus, for each

memory capacity value, we obtained 21 BC values of fixation duration, 20 BC values of

fixation distance, and 20 BC values of saccade amplitude. Finally, for each eye movement

metrics, we averaged the BC values across the fixation or saccade index.

To compare the target detection probability within the first fixation when the target

was at screen center between the ELM searcher and CTELM searcher, we simulated the first

fixation of the CTELM searcher for 10000 times. The fixation duration was set to be 250

ms. The target was identified if the posterior probability at screen center exceed the target

detection threshold at any time within the 250 ms. The target detection threshold was varied

between 0.01 to 1, and for each threshold value, we calculated the proportion of trials in

which the target was identified.

When we summarized the eye movement metrics, we did not include the last fixations

for the fixation duration, nor did we include the initial fixations for the fixation location. We

used BC to quantify the similarity between the histograms of the model's and humans' eye

movement metrics. When the histograms are calculated as probabilities and have the same

number of bins, BC has a maximum value of 1 if the two histograms are completely the same

and a minimum value of 0 if the two histograms have no overlap.

Statistical Analysis

To compare the fixation number between the CTELM searcher (or constraint-

CTELM searcher) to the ELM searcher, we first grouped the trials according to target

eccentricity by 0.5° step. The average fixation number of the two models belonging to the

same group were compared by two tailed two sample t-test with unequal variance assumption

(the "ttest2" function in MATLAB with option 'Vartype' set to 'unequal'). Though t-test

assumes the samples to be normally distributed, the test is robust with respect to violation in

normality if the sample size is large. In our case we could obtain 498 to 692 (mean = 610)

simulation trials for each group of eccentricity of each model, so the test should still be

effective even if the data is not normally distributed.

Data and Code Accessibility

The experiment and simulation results, the code for analyzing eye-tracking data and

visual search models are available on Open Science Framework at https://osf.io/ypcwx/.

Questions should be directed to the corresponding author.

Acknowledgments

This work was supported by the National Natural Science Foundation of China

(81761128011), the Shanghai Municipal Science and Technology 795 Major Project (No.

2018SHZDZX01) and ZJLab, the program for the Professor of Special Appointment (Eastern

Scholar) at Shanghai Institutions of Higher Learning. We thank Professor Zhaoping Li for

her advice on the manuscript.

Supporting Information

S1 Text. Temporal Course of Evidence Accumulation and Deviation of Visibility Map

Function.

S2 Text. Calculation of the Posterior Probability Map.

S3 Text. Validation of the ELM Rule.

S4 Text. Visibility Map without Target Location Cue.

S5 Text. ELM Searcher Considering the Change of Fixation Duration as Search Progressed.

S1 Table. Parameters used in the three visual search models.

S2 Table. Details of statistical test to compare fixation number between the models.

S3 Table. Details of statistical test to compare fixation number between the models.

Fig 1. Stimulus image and results of the detection task. **A:** The stimulus image was a 1/*f*

noise image (15° diameter, root-mean-squared (RMS) contrast 0.2) with an embedded target.

The target was a 6 cycle/degree Gabor grating with a diameter of 0.3 degrees, oriented 45°

counterclockwise from the vertical and windowed by a symmetrical raised cosine (half-

height width of one cycle). The area outside the image was set to the mean gray value of the

image (0.5, not shown here). **B and C:** Detection rate (B) and foveal target visibility (C) as a

function of the target RMS contrast of the four participants. Dots are raw data; different

colors (or gray values) represent different participants. In B, the curves are the Weibull

function fit to the dots. In C, the curves are calculated from Weibull functions fit to hit rates

and the correct rejection rate of the raw data (Equation 1). The intersection between the

dashed line ($d' = 3.0$) and the curves is the target RMS contrast that we chose for each

participant. This target contrast was used for all subsequent experiments. **D:** Target visibility

map after different stimulus exposure times in the detection task. The dots are raw data

merged from all participants. The surface is the visibility map function (Equations 3-5) fit to

the raw data. Not all locations were tested in these exposure times; thus, the number of black

dots may differ in each subplot. Hori/Vert: horizontal/vertical dimension of the search field.

Fixation location locates at the center of horizontal and vertical axis. **E:** Temporal course of

target visibility at four cardinal directions (shown in four subplots) relative to the fixation

location. Each marker represents raw data measured at different relative eccentricities (shown

in the legend) merged from all participants. The curves are Equation 3 fitted to the raw data

measured at each location. The eccentricity values in the legend are normalized with respect

to the radius of the search field. The data measured at the fixation location (eccentricity =

0.0) are shown in every subplot. For clarity, not all measured locations are shown here. See

Figure S1 in S1 Text for the complete data.

Fig 2. **A:** Schematic diagram of the continuous-time entropy limit minimization (CTELM)

and constraint-CTELM searchers. **B:** Locations of the 400 positions (black dots) where the

model can fixate. The dashed circle indicates the boundary of the search area. We generated

these positions by simulating 400 dots repelling each other. The repelling force was

proportional to the inverse sixth power of the distance between two dots. One dot was fixed

at the image center and served as the starting position of the visual search.

Fig 3. Fixation location distribution of participants and three searchers. **A:** The gray scale

represents the relative proportion of fixations located at the displayed location, where lighter

means higher density. The relative proportions were obtained by smoothing the scatterplot of

the fixation locations by a Gaussian window with a standard deviation of 0.35 degrees (15

pixels) and then scaling so that the maximum value in each subplot equals one. **B:**

Bhattacharyya coefficient between models' and participants' distributions of fixation

distances from the image center of the initial 20 fixations after the first saccade. Dots

represent raw data, curves represent quadratic functions ($y = \beta_1 x^2 + \beta_1 x + \beta_3$) fitted to the

dots. R^2 = 0.87, 0.88 and 0.23 for ELM (blue), CTELM (green), and constraint-CTELM

(magenta) searcher, respectively. **C:** Fixation distance distribution selected within the initial

20 fixations after the first saccade. Bars represent participants' data, and lines of different

color represent the model shown in legend at the bottom.

Fig 4. Saccade amplitude distribution of the participants and the three searchers. **A:** Saccade

amplitude histogram of all saccades. **B:** Bhattacharyya coefficient between the models' and

participants' saccade amplitude distribution of the initial 20 saccades. Dots represent raw

data, curves represent quadratic functions ($y = \beta_1 x^2 + \beta_1 x + \beta_3$) fitted to the dots. $R^2 = 0.92$,

0.92 and 0.44 for ELM (blue), CTELM (green), and constraint-CTELM (magenta) searcher,

respectively. **C:** Saccade amplitude distribution selected within the initial 20 saccades. Bars

represent participants' data, and lines of different color represent the model shown in legend

of panel A.

Fig 5. Saccade direction distribution of the participants and the three searchers. The

rightward saccade is 0°, and the downward saccade is 90°. **A:** Saccade direction histogram of

all saccades. **B:** Bhattacharyya coefficient between the models' and participants' saccade

direction distribution of the initial 20 saccades. Dots represent raw data, curves represent

quadratic functions ($y = \beta_1 x^2 + \beta_1 x + \beta_3$) fitted to the dots excluding the first saccade. R^2 =

0.90, 0.96 and 0.96 for ELM (blue), CTELM (green), and constraint-CTELM (magenta)

searcher, respectively. **C:** Saccade direction distribution selected within the initial 20

saccades. Bars represent participants' data, and lines of different color represent the model

shown in legend of panel A.

Fig 6. Effect of memory capacity on the average Bhattacharyya coefficients between the

sequential fixation duration distribution, saccade amplitude distribution, and the distribution

of the fixation distance to the screen center of the simulated data and experimental data. The

black line represents constraint-CTELM searcher whose parameters were fit with an

unlimited memory capacity. The gray line represents parameters fit with a memory capacity

of 8 fixations. Each dot is the mean of the Bhattacharyya coefficients separately calculated

for each of the initial 20 fixations/saccades. "Inf" in the X axis represents the unlimited

memory capacity.

Fig 7. Fixation duration distribution of the participants and the three searchers. **A:** Fixation

duration distribution of all fixations, except the last fixation during which the participants and

the models made a response. **B:** Bhattacharyya coefficient between the models' and

participants' fixation duration distributions of the initial 20 fixations. Dots represent raw

data, curves represent quadratic functions fitted to the dots excluding the first fixation. R^2 =

0.77 and 0.52 for CTELM (green) and constraint-CTELM (magenta) searcher respectively.

C: Fixation duration distribution selected within the initial 20 fixations. Bars represent

participants' data, and lines of different color represent the model shown in legend of panel

A. The entropy limit minimization (ELM) searcher is not shown here because it did not

consider fixation duration.

Fig 8. Participants and the three models' search performances. **A:** The distribution of the

number of fixations needed to find the target. **B and C:** Median (B) and mean (C) number of

fixations to detect the target as a function of the median target eccentricity from the image

center. In panel (B) and (C) each data point of the three models represents the median or

average fixation number of 498 to 692 (mean = 610) simulation trials. The two bottom lines

in panel (C) represent eccentricity range where the average fixation numbers of the CTELM

(upper, green) and constraint-CTELM (lower, magenta) searcher were significantly (p <

0.01) lower than the ELM searcher. We used the two-sample t-test assuming unequal

variance to compare each pair of data points. The exact p-values are shown in Table S2.

Fig 9. The probability of detecting the target at screen center during the first fixation as a

function of target detection threshold of the ELM and CTELM searchers. The ELM searcher

compared posterior probability at fixation location (also the screen center) to target detection

threshold only once at exactly 250 ms. In the CTELM searcher, the fixation duration was

also set to be 250 ms, but the target was detected if the posterior probability at fixation

location drifted above the detection threshold at any time within 250 ms.

References

1.   Najemnik J, Geisler WS. Simple summation rule for optimal fixation selection in
visual search. Vision Res. 2009;49(10):1286–94.

2.   Najemnik J, Geisler WS. Eye movement statistics in humans are consistent with an
optimal search strategy. J Vis. 2008;8(3):4.

3.   Najemnik J, Geisler WS. Optimal eye movement strategies in visual search. Nature.
2005;434(7031):387–91.

4.   Araujo C, Kowler E, Pavel M. Eye movements during visual search : the costs of
choosing the optimal path. Vision Res. 2001;41(25–26):3613–25.

5.   Nowakowska A, Clarke ADF, Hunt AR. Human visual search behaviour is far from
ideal. Proc R Soc B Biol Sci. 2017;284(1849):1–6.

6.   Morvan C, Maloney LT. Human visual search does not maximize the post-saccadic
probability of identifying targets. PLoS Comput Biol. 2012;8(2):e1002342.

7.   Zelinsky GJ. A Theory of Eye Movements During Target Acquisition. Psychol Rev.
2008;115(4):787–835.

8.   Zelinsky GJ. TAM: Explaining off-object fixations and central fixation tendencies as
effects of population averaging during search. Vis cogn. 2012;20(4–5):515–45.

9.   Wolfe JM, Gancarz G. Guided search 3.0: A model of visual search catches up with
jay enoch 40 years later. In: Basic and Clinical Applications of Vision Science. 1997.
p. 189–92.

10.   Halverson T, Hornof AJ. A computational model of active vision for visual search in
human-computer interaction. Human-Computer Interact. 2011;26(4):285–314.

11.   Nuthmann A, Smith TJ, Engbert R, Henderson JM. CRISP: A Computational Model

of Fixation Durations in Scene Viewing. Psychol Rev. 2010;117(2):382–405.

12. Trukenbrod HA, Engbert R. ICAT: A computational model for the adaptive control of

fixation durations. Psychon Bull Rev. 2014;21(4):907–34.

13. Tatler BW, Brockmole JR, Carpenter RHS. Latest: A model of saccadic decisions in

space and time. Psychol Rev. 2017;124(3):267–300.

14. Engbert R, Nuthmann A, Richter EM, Kliegl R. Swift: A dynamical model of saccade

generation during reading. Psychol Rev. 2005;112(4):777–813.

15. Roitman JD, Shadlen MN. Response of neurons in the lateral intraparietal area during

a combined visual discrimination reaction time task. J Neurosci. 2002;22(21):9475–

89.

16. Larson AM, Freeman TE, Ringer R V., Loschky LC. The spatiotemporal dynamics of

scene gist recognition. J Exp Psychol Hum Percept Perform. 2014;40(2):471–87.

17. Müller JR, Metha AB, Krauskopf J, Lennie P. Information conveyed by onset

transients in responses of striate cortical neurons. J Neurosci. 2001;21(17):6978–90.

18. Obara K, O'Hashi K, Tanifuji M. Mechanisms for shaping receptive field in monkey

area TE. J Neurophysiol. 2017;118(4):2448–57.

19. Henderson JM, Pierce GL. Eye movements during scene viewing: Evidence for mixed

control of fixation durations. Psychon Bull Rev. 2008;15(3):566–73.

20. Utrecht U. Crowding degrades saccadic search performance. Vision Res.

2006;46(3):417–25.

21. Walshe RC, Nuthmann A. Asymmetrical control of fixation durations in scene

viewing. Vision Res [Internet]. 2014;100:38–46. Available from:

http://dx.doi.org/10.1016/j.visres.2014.03.012

22.   Thura D, Beauregard-Racine J, Fradet C-W, Cisek P. Decision making by urgency

gating: theory and experimental support. J Neurophysiol. 2012;108(11):2912–30.

23.   Drugowitsch J, Moreno-Bote RN, Churchland AK, Shadlen MN, Pouget A. The cost

of accumulating evidence in perceptual decision making. J Neurosci.

2012;32(11):3612–28.

24.   Ghahghaei S, Verghese P. Efficient saccade planning requires time and clear choices.

Vision Res [Internet]. 2015;113:125–36. Available from:

http://dx.doi.org/10.1016/j.visres.2015.05.006

25.   Tatler BW, Vincent BT. The prominence of behavioural biases in eye guidance. Vis

cogn. 2009;17(6–7):1029–54.

26.   Rosa S, Conservacion A De, Acg G, Costa ICM De, Especies R, Rica DC, et al.

Optimizing the success of random searches. Nature. 1999;401(October):911–4.

27.   Abrams RA, Meyer DE, Kornblum S. Speed and Accuracy of Saccadic Eye

Movements : Characteristics of Impulse Variability in the Oculomotor System. J Exp

Psychol Hum Percept Perform. 1989;15(3):529–43.

28.   Kerr PW, Reddix MD. Eye Movement Control During Reading : I . The Location of

Initial Eye Fixations on Words. Vision Res. 1988;28(10):1107–18.

29.   Bridgeman B, Hendry D, Stark L. Failure to detect displacement of the visual world

during saccadic eye movements. Vision Res. 1975;15(6):719–22.

30.   Collewijn H, Erkelens CJ, Steinman RM. Binocular co-ordination of human vertical

saccadic eye movements. J Physiol. 1988;404(1):183–97.

31.   Van Renswoude DR, Johnson SP, Raijmakers MEJ, Visser I. Do infants have the

horizontal bias? Infant Behav Dev. 2016;44:38–48.

32. Foulsham T, Kingstone A, Underwood G. Turning the world around: Patterns in

saccade direction vary with picture orientation. Vision Res. 2008;48(17):1777–90.

33. Curcio CA, Sloan KR, Kalina RE, Hendrickson AE. Human photoreceptor

topography. J Comp Neurol. 1990;292(4):497–523.

34. Torralba A, Oliva A. Statistics of natural image categories. In: Network: Computation

in Neural Systems. 2003. p. 391–412.

35. Sligte IG, Scholte HS, Lamme VAF. Are there multiple visual short-term memory

stores? PLoS One. 2008;3(2):e1699.

36. Report B. Fragile visual short-term memory is an object-based and location-specific

store. Psychon Bull Rev. 2013;20(4):732–9.

37. McCarley JS, Wang RF, Kramer AF, Irwin DE, Peterson MS. How much memory

does oculomotor search have? Psychol Sci [Internet]. 2003;14(5):422–6. Available

from: http://www.ncbi.nlm.nih.gov/pubmed/12930471

38. Kaunitz LN, Rowe EG, Tsuchiya N. Large Capacity of Conscious Access for

Incidental Memories in Natural Scenes. Psychol Sci. 2016;27(9):1266–77.

39. Beck MR, Peterson MS, Vomela M. Memory for where, but not what, is used during

visual search. J Exp Psychol Hum Percept Perform. 2006;32(2):235–50.

40. Dickinson CA, Zelinsky GJ. Memory for the search path: Evidence for a high-capacity

representation of search history. Vision Res. 2007;47(13):1745–55.

41. Rolfs M, Carrasco M. Rapid Simultaneous Enhancement of Visual Sensitivity and

Perceived Contrast during Saccade Preparation. J Neurosci. 2012;32(40):13744–52.

42. Hoppe D, Rothkopf CA. Multi-step planning of eye movements in visual search. Sci

Rep [Internet]. 2019;9(1):1–12. Available from: http://dx.doi.org/10.1038/s41598-018-

37536-0

43.   De Vries JP, Hooge ITC, Verstraten FAJ. Saccades Toward the Target Are Planned as

Sequences Rather Than as Single Steps. Psychol Sci. 2014;25(1):215–23.

44.   Caspi A, Beutter BR, Eckstein MP. The time course of visual information accrual

guiding eye movement decisions. Proc Natl Acad Sci. 2004;101(35):13086–90.

45.   Hesse C, Franz VH. Grasping remembered objects: Exponential decay of the visual

memory. Vision Res [Internet]. 2010;50(24):2642–50. Available from:

http://dx.doi.org/10.1016/j.visres.2010.07.026

46.   Ricker TJ, Vergauwe E, Cowan N. Decay theory of immediate memory: From Brown

(1958) to today (2014). Q J Exp Psychol [Internet]. 2016;69(10):1969–95. Available

from: http://dx.doi.org/10.1080/17470218.2014.914546

47.   Van der Stigchel S, Hollingworth A. Visuospatial Working Memory as a Fundamental

Component of the Eye Movement System. Curr Dir Psychol Sci. 2018;27(2):136–43.

48.   Peterson MS, Beck MR, Vomela M. Visual search is guided by prospective and

retrospective memory. Percept Psychophys. 2007;69(1):123–35.

49.   Brainard DH. The Psychophysics Toolbox. Spat Vis. 1997;10(4):433–6.

50.   Pelli DG. The VideoToolbox software for visual psychophysics: Transforming

numbers into movies. Spat Vis. 1997;10(4):437–42.

51.   Kleiner M, Brainard D PD. "What's new in Psychtoolbox-3?" Perception 36 ECVP

Abstract Supplement. Perception. 2007;36(14):1–16.

52.   Prins N, Kingdom FAA. Applying the model-comparison approach to test specific

research hypotheses in psychophysical research using the Palamedes toolbox. Front

Psychol. 2018;9(JUL):1250.

53.   Macmillan NA, Creelman CD. Comparison (Two-Distribution) Designs for

952   Discrimination. In: Detection Theory: A User's Guide. 2005. p. 165–85.

953   54.   Dimigen O, Sommer W, Hohlfeld A, Jacobs AM, Kliegl R. Coregistration of eye

954   movements and EEG in natural reading: Analyses and review. J Exp Psychol Gen.

955   2011;140(4):552–72.

956   55.   Delorme A, Makeig S. EEGLAB: an open source toolbox for analysis of single-trial

957   EEG dynamics including independent component analysis. J Neurosci Methods

958   [Internet]. 2004;134(1):9–21. Available from:

959   http://www.ncbi.nlm.nih.gov/pubmed/15102499

960   56.   Nyström M, Holmqvist K. An adaptive algorithm for fixation, saccade, and glissade

961   detection in eyetracking data. Behav Res Methods. 2010;42(1):188–204.

962   57.   Horan M, Daddaoua N, Gottlieb JP. Parietal neurons encode instrumental sampling

963   based on decision uncertainty. Nat Neurosci [Internet]. 2019;22(August):1327–35.

964   Available from: http://dx.doi.org/10.1038/s41593-019-0440-1

965   58.   Ratcliff R, Frank MJ. Reinforcement-based decision making in corticostriatal circuits:

966   Mutual constraints by neurocomputational and diffusion models. Vol. 24, Neural

967   Computation. 2012. p. 1186–229.

968   59.   Gluth S, Rieskamp J, Buchel C. Deciding When to Decide: Time-Variant Sequential

969   Sampling Models Explain the Emergence of Value-Based Decisions in the Human

970   Brain. J Neurosci. 2012;32(31):10686–98.

971   60.   Zhang S, Lee MD, Vandekerckhove J, Maris G, Wagenmakers EJ. Time-varying

972   boundaries for diffusion models of decision making and response time. Front Psychol.

973   2014;5(DEC):1364.

974   61.   Schiller PH, Sandell JH, Maunsell JH. The effect of frontal eye field and superior

975   colliculus lesions on saccadic latencies in the rhesus monkey. J Neurophysiol

976   [Internet]. 1987;57(4):1033–49. Available from:

977   https://doi.org/10.1152/jn.1987.57.4.1033

978   62.   Munoz DP, Broughton JR, Goldring JE, Armstrong IT. Age-related performance of

979   human subjects on saccadic eye movement tasks. Exp Brain Res. 1998;121(4):391–

980   400.

981   63.   Fischer B, Ramsperger E. Human express saccades: effects of randomization and daily

982   practice. Exp Brain Res. 1986;64(3):569–78.

983   64.   Nowak LG, Bullier J. The Timing of Information Transfer in the Visual System. In:

984   Rockland KS, Kaas JH, Peters A, editors. Extrastriate Cortex in Primates [Internet].

985   Boston, MA: Springer US; 1997. p. 205–41. Available from:

986   https://doi.org/10.1007/978-1-4757-9625-4_5

987   65.   Bruce CJ, Goldberg ME, Bushnell MC, Stanton GB. Primate frontal eye fields. II.

988   Physiological and anatomical correlates of electrically evoked eye movements. J

989   Neurophysiol [Internet]. 2017;54(3):714–34. Available from:

990   https://doi.org/10.1152/jn.1985.54.3.714

991   66.   Goldberg DE. Genetic algorithms in search, optimization, and machine learning. 1st

992   ed. Vol. 27, Choice Reviews Online. Boston, MA, USA: Addison-Wesley Longman

993   Publishing Co., Inc.; 2013. 27-0936-27–0936 p.