1   Human Visual Search Follows Suboptimal Bayesian Strategy Revealed by a Spatiotemporal

2   Computational Model

3   Yunhui Zhou, Yuguo Yu[*]

State Key Laboratory of Medical Neurobiology, School of Life Science and Human

Phenome Institute, Institutes of Brain Science, Institute of Science and Technology for Brain-

Inspired Intelligence, Fudan University, Shanghai, China

[*] Correspondence author

Email: yuyuguo@fudan.edu.cn (YY)

Short title: A continuous-time visual search model

Author contributions: Y.Y. supervised the research, Y.Z. and Y.Y. designed the research,

Y.Z. performed the research, wrote the analysis tools and analysed the data, Y.Z. and Y.Y.

wrote the paper.

Conflict of Interest: The authors declare no competing financial interests.

18   **Abstract**

Humans perform sequences of eye movements to search for a target in complex

environment, but the efficiency of human search strategy is still controversial. Previous

studies showed that humans can optimally integrate information across fixations and

determine the next fixation location. However, their models ignored the temporal control of

eye movement, ignored the limited human memory capacity, and the model prediction did

not agree with details of human eye movement metrics well. Here, we measured the

temporal course of human visibility map and recorded the eye movements of human subjects

performing a visual search task. We further built a continuous-time eye movement model

which considered saccadic inaccuracy, saccadic bias, and memory constraints in the visual

system. This model agreed with many spatial and temporal properties of human eye

movements, and showed several similar statistical dependencies between successive eye

movements. In addition, our model also predicted that the human saccade decision is shaped

by a memory capacity of around 8 recent fixations. These results suggest that human visual

search strategy is not strictly optimal in the sense of fully utilizing the visibility map, but

instead tries to balance between search performance and the costs to perform the task.

Author Summary

During visual search, how do humans determine when and where to make eye

movement is an important unsolved issue. Previous studies suggested that human can

optimally use the visibility map to determine fixation locations, but we found that such

model didn't agree with details of human eye movement metrics because it ignored several

realistic biological limitations of human brain functions, and couldn't explain the temporal

control of eye movements. Instead, we showed that considering the temporal course of

visual processing and several constrains of the visual system could greatly improve the

prediction on the spatiotemporal properties of human eye movement while only slightly

affected the search performance in terms of median fixation numbers. Therefore, humans

may not use the visibility map in a strictly optimal sense, but tried to balance between search

performance and the costs to perform the task.

Introduction

For animals with foveated retina, efficient visual search is important for survival, and requires close-to-optimal planning of eye movement both in space and time. Currently, there are conflict evidences on whether human can make spatially optimal eye movements. The Bayesian ideal searcher and the closely-related entropy-limit-minimization (ELM) model are two important optimal eye movement models of multi-saccade visual search task, and previous studies have shown that humans' search performance and eye movement statistics were consistent with these optimal models [1–3]. However, other studies have indicated that human may rely more on suboptimal strategy rather than calculating and planning optimal eye movement for a specific task [4–7]. What's more, despite the claim that human eye movement strategy was close to optimal, humans seemed to made fewer long saccades compared to the optimal models [1]. Humans also showed statistical dependencies between successive eye movement during visual search [8], but detailed comparison to the optimal models is still missing.

The Bayesian ideal searcher and the ELM model were optimal in the sense of fully using the visibility map [1,3], but they didn't consider other costs to perform the task. For humans, the requirement of unlimited memory capacity in these optimal models is unrealistic, and making eye movements also have costs. For example, longer saccades are less accurate and increase the chance to make a secondary saccade [9–13], take longer to finish [14–16], and disrupt vision during saccade more severely [17], so this might explain why humans made fewer long saccades than the optimal models [1]. With these constraints, it is unlikely that humans strictly follow the optimal search rule. We therefore reconsider the question of how optimal do humans search and ask if a visual search model with more biological

limitations can perform closer to humans.

Moreover, the temporal control of eye movements has received surprisingly little

attention in visual search models. For example, the Target Acquisition Model does not

explain fixation duration [18,19]; the Bayesian ideal searcher and ELM model assume each

fixation last for 250 ms [1,3]; and the Guided Search model assumes fixation duration is 200

– 250 ms [20]; whereas the fixation duration observed in experiment usually has a large

variation ranging from less than 100 ms to more than 700 ms [21]. We found only one

model of visual search that considered mean fixation duration, but it couldn't simulate the

large variation [22]. The lack of fixation durations in the above models may be caused by the

view that visual search is more about deciding fixation locations in the environment to find

the target than deciding how long each fixation should be. However, since interdependency

between fixation duration and spatial control of eye movements has been observed [8,23,24],

a complete model of visual search should explained control both in space and time instead of

focusing on a single aspect.

Eye movements are typically viewed as sequence of decisions, and fixation duration

can be viewed as reaction time of a saccade decision. Indeed, the distribution of fixation

duration showed similar right-skewed shape as the reaction time distribution of other

decision-making tasks [12,25,26]. Therefore, some models of reading and scene viewing

capture the fixation duration distribution by using the drift-diffusion model of decision

making [27–30], which is successful in explaining the reaction time distribution [31,32]. The

central idea is to accumulate information stochastically within a fixation and triggered a

saccade whenever the accumulation reaches a threshold, which has receive wide experiment

support [33–35]. Although this approach is successful, the accumulation process in these

models are usually simplified or artificial as they did not quantitatively measure the

dynamics of information accumulation within a fixation. Since previous researches have

shown that visual search task difficulty affects fixation duration [36,37], we believe that the

information accumulation process should be explicitly measured according to the visual

search stimulus used in the task, and the data can be incorporated to previous optimal models

[1,3] based on signal detection theory.

In this research, we experimentally measured the accumulation of visual information

by the brief stimulus exposure method. The data was then used to formulate a drift-diffusion

process that decides saccade timing. Combined with the ELM model, we proposed a

continuous-time eye movement model that determines both fixation location and fixation

duration. Though the search performance of human subjects was close to optimal, we found

that their eye movement statistics was inconsistent of the optimal search strategy. Instead,

adding constraints on saccade accuracy, saccade amplitude and memory capacity could

significantly improve the model's prediction on human eye movement statistics while only

slightly impair the search performance.

108   **Results**

Selecting Target Contrast

The stimulus image was a Gabor target (6 cycle/degree, 0.3 degrees in diameter)

embedded in a circular naturalistic background noise image (15 degrees in diameter, root-

mean-squared (RMS) contrast 0.2) (Fig 1A). Ten student subjects were recruited in this

study. To normalize visual search task difficulty across subjects, we first measured the

relationship between foveal target visibility (d' in signal detection theory) and target RMS

contrast. The subjects' correct response rate could be well fitted by a Weibull psychometric

function given the target RMS contrast (Fig 1B). Visibility was positively related to the

target RMS contrast and could be described by Equation (2) (Fig 1C). For each participant,

we selected the target RMS contrast that made visibility equals to 3.0 (Fig 1C). The selected

value ranged from 0.111 to 0.135, with a mean value of 0.125.

Temporal Course of Target Visibility and the Evidence Accumulation Model

We then measured how target visibility changed over time within one fixation across

the visual field by a brief stimulus presentation experiment. Four of the ten subjects finished

this experiment, and their data were pooled together. The target visibility first increased as a

function of time, and then reached stable peak values after stimulus onset (Fig 1DE). The

steady-state foveal visibility was approximately 3.14, which was close to the pre-defined

value of 3.0. The steady-state and rising speed of visibility was higher in central visual field

than in peripheral visual field (Fig 1E). There were some individual variability on the span

of visibility map (e.g. some participant could detect the target at larger eccentricity), but the

trend that central vision could detect the target faster than peripheral vision was basically

preserved across participants (Fig S1 to Fig S4).

We then formulated an evidence accumulation model to incorporate the temporal

course of visibility data into visual search models. We assumed that in each short time

interval, the visual system received a small normally distributed random sample of visual

information at each location. Similar to previous visual search models [1–3], the mean of the

random variable depends on target's presence at the location, but the variance is equal

(Equation (3)). We further assumed that these random independent samples were integrated

over time in a leaky manner (earlier samples were given lower weight, Equation (6)), because

perfect integration could produce arbitrary high visibility given enough samples (Equation

(4)). The integration of random samples produced a drift-diffusion process, and the

distribution at each time point could be analytically described (Equations (7)-(9)). According

to signal detection theory, visibility (d') is the separation between the noise and target+noise

distributions in units of their common standard deviation [38], therefore the temporal course

of visibility could be described as Equations (10), (12), (13), and fit well to visibility data

measured at each location (Fig 1DE).

Subjects' Eye Movement Statistics Were Predicted Better By A Suboptimal Visual

Search Strategy

Next, we performed a visual search experiment with the same stimulus images to

compare their eye movement data to visual search models. All ten subjects finished this task,

and they were split into training set (the four subjects that measured the temporal course of

visibility) and testing set (the rest six subjects).

We used the entropy-limit-minimization (ELM) model of visual search as the

baseline model and it served as a replication of previous study [1]. To model eye movements

control both in space and time, we combined the evidence accumulation model and the ELM

model into a continuous-time ELM (CTELM) model. Since several previous studies have

suggested that the control of fixation duration depends more on foveal than peripheral visual

analysis [39,40], the CTELM model terminates a fixation when the posterior probability of

target being at current fixation location drops below a collapsing threshold (Fig 2). The next

fixation location was chosen by the ELM rule (Equation (17)).

We also tested whether adding constraints to the CTELM model (called the CCTELM

model) could improve model's prediction on experiment data. Three constraints were

considered: preference for short saccades, inaccuracy of saccade landing position, and

memory limitation. We applied a penalty function (Equation (25)) when calculating the

expected information gain of the next fixation to suppress the probability of choosing a

distant saccade target. The relationship between variability of saccade landing position and

saccade target eccentricity was obtained from [12] (Fig S7), so that the model could fixate at

any location instead of the predefined 400 locations (Fig S6). We also considered a simple

form of memory so that the model could only integrate a fixed number of fixations when

calculating the posterior probability of target location (Equation (23)). Visual information

prior to what the memory could hold was discarded. We found that human eye movements

predicted that the memory capacity was about 8 fixations (including the current fixation). In

the next section we will show how we estimated the capacity.

There is only one free parameter in the ELM model that controls correct response rate,

and three additional free parameters in the CTELM model that controls the fixation duration.

The CCTELM model has five free parameters: one for correct response rate, three for

fixation duration, and one for the saccade amplitude penalty function (see methods and Table

S1). These parameters were fit to the training set and tested against the testing set.

We first examined how the three models predict subjects' spatial control of eye

movements. In previous studies of similar experiment, humans produced a doughnut-shaped

fixation location distribution peaked at about 5° from image center, and fixated more at

vertical part of the image than the horizontal part [1,2]. Our subjects in testing set, however,

fixated more uniformly across the image in both correct (Fig 3ACD) and error trials (Fig

S8ACD), though similar to previous results more fixations were located in the vertical part

(Fig 3B, Fig S8B). There was a fixation hotspot located slightly above the image center in

experiment data (Fig 3A), but it was caused by the first saccade from two subjects, so we

chose to focus more on global trends instead of this individual variability. All three models

could predict the preference to fixate at vertical part of the image (Fig 3B, Fig S8B); however,

the ELM and CTELM models produced a sharp doughnut-shaped distribution of fixation

locations, whereas the CCTELM model fixated more uniformly and was similar to subjects'

data (Fig 3ACD, Fig S8ACD). Importantly, ELM and CTELM models progressively fixated

at the outer part of the image as search continues, whereas the subjects' and CCTELM

model's fixation distance to image center was relatively stable (Fig 3E, Fig S8E). Therefore,

the agreement of ELM and CTELM model to experiment data decreased as the search

progressed, but the CCTELM model could achieve stable and better agreement (Fig 3F, Fig

S8F).

For the saccade amplitude, the two optimal models generated more long saccades

than the subjects did in both correct and error trials (Fig 4A), which was similar to results in

previous studies [1]. The difference was present since the first saccade (Fig S9, Fig S10),

and the disparity between the models' and humans' distributions increased as the search

progressed (Fig 4B). The CCTELM model prefer shorter saccades, and the prediction on

experiment data was better and more stable (Fig 4AB). Besides, in a sequence of eye

movements, the change of saccade direction after a saccade was usually larger for the ELM

and CTELM models than CCTELM model and subjects (Fig 4C). Both subjects and the

three models tended to make larger saccades after larger change in saccade direction, but the

slope of the relationship was larger for both the ELM and CTELM than subjects and

CCTELM model (Fig 4D). What's more, both the ELM and CTELM models tended to make

longer saccades after a long saccade, but the subjects and CCTELM model showed the

opposite behavior (Fig 4E). Therefore, the CCTELM model could better explain the subjects'

spatial control of eye movements.

We next examined how CTELM and CCTELM models predict subjects' temporal

control of fixations. Both models could predict the overall fixation duration distribution (Fig

5A), and the agreement was stable as search progressed in both correct and error trials (Fig

5B, Fig S11, Fig S12). However, as the spatial and temporal control of eye movements are

not independent, we then checked the relationship between fixation duration and other eye

movement metrics. Humans tended to fixate longer when the directions of previous and next

saccade were perpendicular to each other, forming an inverted-U shape relationship between

fixation duration and change in saccade direction (Fig 5C). The CCTELM model could

partially generate this relationship, but for the CTELM model, fixation tended to be longest

when the directions of previous and next saccade form a 135° angle (Fig 5C). The reason for

this behavior of the CCTELM model was because the previous saccade tended to be longer

when the next saccade changed direction closer to 90° (Fig S13A), so there was less preview

benefit of the fixation in between from previous fixation (Fig S13B) and the duration became

longer. However, the CCTELM model fixated longer than subjects when the next saccade

nearly reversed the direction (Fig 5C). This was because the previous saccade amplitude was

longer for the model under this situation (Fig S13A), and there was less preview benefit (Fig

S13B). What's more, humans and CCTELM model fixated shorter after short and long

saccades, but for the CTELM model longer fixations tended to follow large saccades (Fig

5D). Therefore, the CCTELM model explained the subjects' temporal control of eye

movements better.

The above detailed comparison of eye movement metrics showed that optimal visual

search models could only predict a few human eye movement metrics (Fig 3A, Fig 5A).

Many other details, especially the overall fixation density and saccade amplitude, the

distribution of eye movement statistics as a function of fixation/saccade order, and the

dependency between successive eye movements, showed remarkable difference between

human and optimal models, and could be well predicted by a model with constraints on

saccade accuracy, saccade amplitude and memory capacity. Therefore, the subjects were

clearly not using the optimal eye movement strategy in the sense of fully utilizing the

visibility map to search the target.

The Suboptimal Eye Movement Strategy Slightly Impaired Search Performance

Since subjects used a suboptimal search strategy, we next compared the search

performance of humans and the three models. With the appropriate choice of target detection

threshold θ_T (Table S1), the three models' correct response rate was similar to the correct

response rate of subjects in training set (about 88.0%, see Table 1). The subjects in the

testing set had lower correct response rate (84.7%), which may be caused by individual

variability and difference in prior training between the two groups of subjects (see

discussion).

In all correct trials, the ELM and CTELM model searched fastest in terms of median

fixation number (7 fixations), followed by the subjects in training set and CCTELM model (8

fixations), and subjects in testing set (10 fixations, see Table 1). The distribution of fixation

numbers of subjects and models had a similar peak, but the distribution was more heavy-

tailed for human subjects and CCTELM model (Fig 6**Error! Reference source not found.**A,

also see maximum fixation numbers in Table 1). With respect to fixation number as a

function of eccentricity, the CCTELM model only searched slower than both the ELM and

CTELM models when target was distant, and was closer to subjects' performance (Fig

6**Error! Reference source not found.**B). We also found that the current models could not

explain subjects' search performance in error trials (Table 1), but since most of the trials are

correct, so at least the model already agreed well with the majority of experiment data. To

summarize, though subjects used a suboptimal search strategy, the performance of this

strategy was close to the optimal performance.

With the three constraints, the CCTELM model approached the target slower than

both the ELM and CTELM models in the last few fixations in a trial, and was closer to

subjects' behavior (Fig 6C). Besides, the posterior probability at target location rose rapidly

within the last three fixations for the ELM and CTELM model (Fig 6D), which is similar to

the result in [3]. But for the CCTELM model, posterior probability at target location need

about five fixations to rise to the decision threshold (Fig 6D). This confirmed that subjects

and CCTELM model was less efficient (in the sense of fully utilizing the visibility map) than

the ELM and CTELM model though the difference wasn't large.

As in previous studies [1–3], we measured the visibility map with target location cue

in the detection task, one may question the validity of using it in the visual search task when

there is no target cue. We also measured the visibility map without a target location cue in

four subjects (see methods and S3 Text) and found that the optimal search performance was

much slower than the subjects' performance (Fig S16 in S3 Text). Therefore, in theory,

visibility map measured without a target location cue does not allow human-level search

performance.

We have shown that the CCTELM model agreed better with human visual search

behavior both in eye movement metrics and task performance. The remaining questions

were how we estimated the memory capacity, and why these constraints improved the

model's prediction. We have varied the CCTELM model's memory capacity and examined

how the eye movement metrics fit to the training set. Fig 7Error! Reference source not

found.A shows that the distributions of fixation distances to screen center and fixation

location were most sensitive to memory capacity, and the distributions of fixation duration

and saccade amplitude were less sensitive unless at extreme values. On average, the

matching to the experimental data peaked when the memory capacity was 8 fixations (Fig

7A). Fig 7**Error! Reference source not found.**B shows the mean number of fixations to

correctly find a distant target is affected much more by memory capacity than finding a near

target. Together, the results**Error! Reference source not found.** suggest that a model with

memory capacity of 8 fixations could significantly improve agreement to experiment data

while the search performance is only slightly affected, we therefore choose 8 fixations as the

memory of CCTELM model.

We further checked the scan path of humans and models to understand the effect of

saccade amplitude penalty function. Subjectively, the scan path looked similar when the

target was close and number of fixations was small; however, difference emerged when the

number of fixations was larger (Fig 8). The ELM and CTELM models chose the location

that maximize the expected information gain as the next fixation location. In general, one

can get most information by fixating at novel regions and avoid previously fixated regions.

Therefore, both the ELM and CTELM models tended to avoid image center (where the

search starts) and jumped between opposite sides of the search field (Fig 8), producing many

long saccades (Fig 4ADE) and larger change in saccade direction (Fig 4C). Adding

constraint on saccade amplitude prevent this behavior and forced the model to make series of

small saccades around the image to reach the other side of the image (Fig 8), so the change in

saccade direction decreased (Fig 4C). This was more similar to humans' behavior as some of

our subjects did report after the experiment that they fixated around the image to find the

target.

Discussion

Previous computational models predict that the human visual search behavior follows

the optimal Bayesian inference [1–3]. However, both our experiments and simulations

confirmed that the human visual search is indeed obeying the suboptimal strategy because of

the constraints from memory capacity and saccadic bias. This suboptimal strategy, however,

did not greatly affect the overall search performance. Including these constraints into the

previously proposed optimal model could significantly improve the model's prediction of the

human eye movement statistics.

Temporal Course of Visual Processing

An interesting result from the detection task is that central vision processed

information faster than peripheral vision. The result agrees with previous findings that scene

gist recognition depends more on central vision during the initial 100 ms of viewing [41]. At

the neuronal level, the initial central advantage is consistent with earlier finding that the

discriminability of neural activities for high contrast gratings peaked rapidly 100 ms after

stimulus onset [42], but what makes peripheral vision be slower in our task remains

ambiguous. A recent neurophysiological study showed that neurons in the anterior part of

inferior temporal cortex responded later to objects presented at peripheral than central visual

field [43], but the exact neural mechanisms leading to this phenomenon is still unknown.

One possible reason was that the discriminability of neural activities for suboptimal gratings

could peaked much slower [42], and that peripheral vision generally tunes for lower spatial

frequencies. From the perspective of our evidence accumulation model, it is possible that the

visual system shortens the integration time at central vision to achieve a faster response speed

but lengthens the integration time at the peripheral region to compensate for the low signal-

to-noise ratio.

The Control of Fixation Duration

The CCTELM model controlled fixation duration by a drift-diffusion process based

on experimentally measured temporal course of visibility and an artificial collapsing decision

threshold. Our approach shared some similarities to some previous eye movement models

which controlled fixation duration collectively by an autonomous timer and modulation by

processing demand from the current fixation [27,28,30]. From this viewpoint, the CCTELM

model implemented the autonomous timer as the collapsing threshold, and modulation from

the current fixation as the drift-diffusion process. Fixation will be prolonged if the model

cannot determine whether the current fixation location has a target because the probability

value at the fixation location will not decrease quickly. However, our approach differed from

previous models in that the diffusion process could be constructed from experiment data, thus

being more biologically realistic, and it is based on probability values so it can be

incorporated into the ideal searcher theory. The introduction of a collapsing threshold may

seem arbitrary, but its existence, though still controversial, has received certain experimental

support [44,45], and it allows human to trade off accuracy for speed if the current visual

information remains ambiguous about target location.

Recent models of eye movement are moving from separate control of fixation

location and fixation duration to a more integrated spatiotemporal control strategy [29].

Although the CCTELM model seemed to adopt a separate control mechanism (Fig 2), the

decision of fixation duration and fixation location were both based on posterior probability

map so they were not completely independent. The model fixated shorter after a smaller

saccade (Fig 5D) because part of the information at the new fixation location had already

been obtained from the previous fixation, so the probability value at the new fixation location

was closer to decision threshold. Besides, long saccades were not accurate, so the model was

likely to miss the saccade target and fixated on place with low probability value which made

the fixation shorter (Fig 5D). The preview benefit could also explain the relationship

between fixation duration and the change in saccade direction (Fig 5C). Though the model

fixated longer than subjects when the next saccade nearly reversed the direction, previous

study has reported relationship similar to our model's prediction in visual search task [8].

Memory Capacity of Visual Search

An interesting discovery from this study is that the subjects' eye movement statistics

predicts the memory capacity in visual search. Similar capacity value has also been used in

some models of scene viewing [46], but many models of visual search still ignore this

memory limitation. We found that the memory capacity had a considerable effect on

model's eye movement statistics and its agreement to experiment data, so it might be

worthwhile for future simulation studies to consider this factor.

One may wonder why the model needed a memory capacity of about 8 fixations when

correctly identifying the target needs only 5 fixations before the response (Fig 6D). Memory

helps not only in identifying the target, but also in rejecting regions without target so that the

model had a higher chance to meet the target in the future, which Fig 6D didn't show. The

simulation experiment with varies memory capacity showed that the model's prediction on

overall fixation location distribution decreased rapidly with less memory capacity (Fig 7A

purple dashed line). This was actually because with less memory the model would quickly

forget information near the image center (where the search started), and by the ELM rule the

model tended to place subsequent fixations near the image center to gain maximal

information (fixating near the image boundary causes part of the visibility map to be wasted).

Therefore, fixation locations were much more concentrated to the image center in low

capacity compared to high capacity model. In other words, larger memory promotes the

model to explore outer part of the image, and was therefore needed to efficiently find target

at distant locations (Fig 7B).

The type of short-term memory that we modeled is similar to the fragile visual short-

term memory (FVSTM). FVSTM is thought to be an intermediate stage between iconic

visual memory and visual working memory. It has a high capacity of approximately 5-15

items, lasts for at least 4 seconds [47] and has been shown to be tied to the location of the

original visual stimulus [48], making it particularly suitable for integrating information

across multiple fixations to generate a posterior probability map. However, the exact

memory capacity in visual search tasks remains controversial. There are reports indicating

that visual search has a memory of $3-4$ items [49], $7-9$ items [50,51], and more than 10

items [52]. The predicted memory capacity of 8 fixations of the CCTELM model lies within

the range of these reported results and thus may serve as additional evidence in this debate.

However, the exact memory capacity requires future investigations and may serve as a test of

our model.

Human Visual Search Strategy

The comparison of eye movement statistics between humans and both the ELM and

CTELM models showed significant difference on the distribution of fixation location,

fixation distance to image center, saccade amplitude, and the dependency between successive

eye movements. The CCTELM model further suggested that the discrepancy was mainly

due to constraints on saccade amplitude, saccade accuracy and memory capacity. The

humans' preference of short saccades compared to optimal model was also shown in

previous study [1]. Therefore, if we consider the degradation of visibility in peripheral vision

as the only limitation to visual search, the human eye movement statistics clearly deviated

from the optimal model. In this sense, the subjects employed a suboptimal eye movement

strategy to find the target.

However, this suboptimal strategy only increased the median fixation numbers by one

in the training set and three in the testing set. This relatively small impact, combined with

the physiological meanings of the constraints in CCTELM model, suggests that humans were

balancing task performance and costs when making eye movements to search for target. If

humans try to use the optimal eye movement strategy to fully use the visibility map, they will

need to make more long saccades, which means more time spent on saccades [14–16], more

subsequent corrective saccades because of decreased landing accuracy [9–13], and stronger

saccadic suppression during the saccade [17]; besides, they need to maintain a long history of

previous fixation in memory which will also increase the cognitive load. Choosing a

suboptimal eye movement strategy that reduces these costs while maintaining a close-to-

optimal search performance should therefore be a better solution.

Several previous studies have also shown that human eye movements are suboptimal

when optimally performing a task required effortful computation and careful planning [4–6],

so subjects may simply follow a good heuristics when searching in these noisy images. The

advantage of this strategy is that the computational cost of saccade target selection may be

further reduced to selecting a few random numbers, as even the relatively computationally

efficient ELM rule requires convolving two maps across the visual field in every fixation.

The heuristics may be good enough but not strictly optimal for this particular task. From this

perspective, the subjects may be close to optimal balance between search performance and

the cost to perform the task.

We found that the subjects' distribution of fixation location was more uniformly

distributed in the search field compared to previously published results on a similar

experiment [1,2]. The subjects in training and testing set also showed some difference on the

correct response rate and search performance. This could be caused by both individual

variability of visibility map and search behavior and difference of the amount of training

prior to the visual search experiment. Previous results in [2] came from two subjects who

had measured the target visibility with much more trials at more retinal locations, and had

performed more visual search trials with more target visibility levels, so it is possible that

previous results were the behavior of two over-trained subjects who performed closer to the

optimal model. In our study we had recruited more subjects, so because of time limitation

we could not obtain a very densely sampled visibility map and perform many visual search

trials, and we did not measure the full temporal course of visibility on some subjects in the

testing set before the visual search experiment. This may cause the performance difference

between different groups of subjects, but the current results may be more generalizable to a

larger pool of subjects.

Limitations of Current Model

Although the CCTELM model explained a range of behavioral data of visual search,

it is still a simple model and did not fully reflect the complexities of the visual system. First,

accurately measuring the target visibility is challenging, because the detection task may not

reproduce the actual attention deployment and pre-saccadic enhancement of visual

processing [53] happened in visual search, and introduced perceptual learning at measured

locations. Second, humans may plan multiple fixations ahead during a fixation [54–56],

whereas our model only plans one fixation ahead. Third, the implementation of memory is

still relatively simple. The model either kept information from a fixation or completely

forgot it, whereas human brain memory may gradually decay over time [57,58], and this was

considered in previous model of scene viewing [46]. In addition, multiple types of memory

may be involved in visual search [59,60], but this was not reflected in the current modeling

approach.

Subjects also had some eye movement features that the CCTELM model could not

reproduce. First, human saccade direction is biased toward horizontal and to a less extend

toward vertical directions [46,61]. The previous optimal models of visual search showed that

the horizontal bias could be explained by an horizontally elongated visibility map measured

in experiment [1,2]. However, our visibility map data is more radially symmetric (Fig 1E) so

we did not see the same modeling result as previous studies. There are probably other factors

(such as the distribution of features in natural scene) leading to this bias in humans [61], and

are not captured in the constraints of the CCTELM model. Second, the model did not spend

as many fixations as subjects did in error trials. One possible reason is that we used the

dynamic noise instead of the static noise which considers the variability of task difficulty due

to the noisy image background superimposed on the target. But since the target is well

visible under the chosen contrast ($d' = 3$), the model with dynamic noise already agreed with

correct trials, and previous study found only small effect of static noise on the optimal

model's behavior [2], we chose to use dynamic noise in this study for its computational

simplicity. We hope that this model could help developing more complete models of eye

movement in the future.

Materials and Methods

Human Subjects

466 Ten student volunteers (6 males and 4 females, age range 19-30 years) participated in

467 the experiment for monetary compensation. One subject was the author (Y.Z). All subjects

468 had normal or corrected-to-normal vision.

Ethics Statement

470 This study was approved and supervised by the Ethics Committee of the School of

471 Life Sciences at Fudan University (BE1942), and written informed consent was obtained

472 from all subjects.

Apparatus

Stimuli were presented on a 24.5-inch BenQ ZOWIE XL2540 LCD monitor at a

resolution of 1920×1080 and a refresh rate of 240 Hz. Subjects were seated 70 cm in front

of the display with their heads fixed by a forehead and chin rest. Stimuli were generated and

presented using MATLAB (MathWorks) and the Psychophysics Toolbox extensions [62–64]

running on a Windows 7 (Microsoft) machine. Eye movements of both eyes were recorded

at 2000 Hz with a TRACKPixx3 eye-tracker (Vpixx Technologies, Canada).

Experiment Design and Statistical Analysis

Target and background image. The target was a six cycle-per-degree Gabor with a

diameter of 0.3 degrees, oriented 45 degrees counterclockwise from the vertical, and

windowed by a symmetrical raised cosine (half-height width was one cycle of the Gabor).

The background image was a circular naturalistic noise image (whose statistics follow a $1/f$

power spectrum) placed at the center of the screen with a diameter of 15 degrees and root-

mean-squared (RMS) contrast of 0.2 (Fig 1A). The RMS contrast was defined as the

standard deviation of the pixel gray value divided by the mean gray value. The area outside

the background image was set to the mean gray value of the image (0.5). The background

images used in each trial of detection task and visual search task were randomly picked from

a database of 1000 independently generated images.

Eye-tracker calibration. During each laboratory visit, subjects first performed a 13-

point calibration routine. The outer edge of the 13 points formed a square that covered the

circular search area. We repeated the calibration until the average test-retest measurement

error of both eyes fell below 0.5°. Recalibration of the eye-tracker was performed whenever

the eye-tracking accuracy failed to meet the requirements of the experiment (described

below).

Selecting target RMS contrast. In this experiment we measured the relationship

between foveal target visibility and target RMS contrast and selected the target contrast level

that made the foveal visibility equal to 3.0. Each participant therefore had a unique target

contrast and was used for all subsequent experiments. The goal was to normalize the target

detection difficulty across subjects.

At the start of each trial, a black cross and stroked circle appeared at the center of the

screen, indicating the fixation location and target location. The remaining display area was

set to a 0.5 gray value. Subjects began a trial by fixating within 1° from the screen center and

pressing a button. The cross and circle then disappeared for 200−400 ms (chosen randomly),

followed by two 250 ms intervals of the stimulus image separated by a 500 ms gray interval.

The two stimulus intervals had the same noise background image; however, a randomly

chosen stimulus had a target at the screen center. The subjects then chose the interval that

contained the target with a keyboard. A trial was aborted if the participant fixated more than

1° away from the screen center at any time during the trial. This section contained 4−5

levels of target contrast (depending on the participant's pace), and each level included 200

trials. Trials with different target contrasts were randomly interleaved. We chose the

appropriate target contrast levels (ranging from 0.03 to 0.12) by a pilot experiment for each

participant to avoid floor or ceiling effects.

We first calculated the hit rate and correct rejection rate of each target contrast level

from behavior data. The hit (or correct rejection) rate was defined as the number of trials that

target appeared in the first (or second) interval, and the participant made a correct response,

divided by the total number of trials that target appeared in the first (or second) interval. The

relationships between the hit/correct rejection rate and target RMS contrast C were then

separately fit with a Weibull function:

$$f(C) = 0.5 + 0.5 \times \left\{ 1 - \exp\left[-\left(\frac{C}{C_T} \right)^s \right] \right\} \qquad (1)$$

522 The threshold parameter C_T and steepness parameter s were estimated by maximum-

523 likelihood methods implemented in the Palamedes Toolbox [65]. The relationship between

524 the foveal target visibility and target RMS contrast could then be estimated by signal

525 detection theory [66]:

$$d'(C) = \frac{z\left[f_H(C) \right] - z\left[1 - f_{CR}(C) \right]}{\sqrt{2}} \qquad (2)$$

Here, $z(x)$ is the inverse standard normal cumulative distribution function. $f_H(C)$ and $f_{CR}(C)$

are the estimated hit and correct rejection rates given by Equation (1). We could then obtain

the target contrast level that made $d'(C) = 3.0$.

The detection task. The goal of the detection task was to measure the change of

target visibility over time in the visual field. The experiment had three versions. Four

subjects participated in the first version, four participated in the second version (the author

Y.Z participated in both), and three participated in the third version.

In the first and second versions we measured the relationship between the stimulus

presentation time and target visibility along four cardinal directions in the search field. The

procedure was the same as the experiment to select target RMS contrast, except that we

varied both the stimulus duration and target location. In the first version of experiment,

subjects were required to fixate at the screen center and decide which of the two stimulus

intervals contained the target at the cued location. The experiment contained five blocks

(four cardinal directions plus the screen center). For each block, we chose 3−4 different

target locations (except when the target was at the screen center) and 4−5 levels of stimulus

presentation time. The target was located 0−6.75° (0−90% of the image radius) away from

the screen center. When the target appeared at the screen center, the stimulus duration was

chosen from 4 to 200 ms, and each level was tested for 100 trials. When the target appeared

at peripheral locations, the stimulus duration was chosen from 50 to 700 ms, and each

combination of stimulus length and target location was tested for 50 trials. In the second

version of experiment, the target location cue was not shown, and in each trial, the target

location and stimulus presentation time were randomly chosen from all possible

combinations in the first version of experiment. The results of the second version are shown

in Fig S15 in S3 Text, but it was not used in the results of the main text. The third version

was the same as the first version except that there is only one level of stimulus presentation

time (250 ms). It was used to measure the visibility map efficiently and get enough training

to prepare for the visual search experiment, so the data from this version was not used in this

manuscript.

The first and second version of the detection task contained about 5000 trials.

Subjects finished these trials by multiple laboratory visits within two months. Before the

start of the formal experiment, they practiced with 25-100 trials to stabilize the performance.

Subjects received feedback about their performance during practice trials but did not receive

feedback during the formal experiment.

The evidence accumulation model. Behavior data from different subjects in the

first and second version of the detection task was first separately pooled together. Target

visibility at each location for each level of stimulus duration was then calculated by Equation

(2). The data was used to formulate an evidence accumulation model that described the

change of target visibility over time, and this model was later used in the continuous-time eye

movement model. According to signal detection theory, visibility is essentially the distance

between noise and signal-plus-noise distributions. Therefore, we extended the template

response model to visual stimulus at each location in the visual field used in [1–3] to a drift-

diffusion process W_t.

Suppose the visual evidence ΔW generated at one location within a short time interval

Δt is independently drawn from a normal distribution. If the target appears at this location,

the distribution is $N(\Delta t, \sigma^2 \Delta t)$, otherwise $N(-\Delta t, \sigma^2 \Delta t)$. The value of standard deviation σ

controls target visibility at this location. If the evidence at each time step Δt is integrated

perfectly, then the total evidence at time $T = n \cdot \Delta t$ follows the distribution of the sum of n

normal random variables:

$$\begin{cases} N(T, \sigma^2 T), & \text{if target exists} \\ N(-T, \sigma^2 T), & \text{if no target exists} \end{cases} \tag{3}$$

576   According to signal detection theory [66], the evolution of target visibility d' over time is:

$$d'(T) = \frac{T - (-T)}{\sqrt{\sigma^2 T}} = \frac{2\sqrt{T}}{\sigma} \tag{4}$$

578   Equation (4) implies that target visibility will increase to infinity at any retina

579   location given unlimited amount of viewing time, which is impossible. This problem can be

580   resolved if we assume that the weight w of previous evidence decays exponentially by a

581   speed parameter k over time:

$$w(t) = \exp(-k \cdot t) \tag{5}$$

583   Suppose the total accumulated evidence at one location from 0 to the i^{th} time step is

584   W_i ($W_0 = 0$), then the by the $(i + 1)^{th}$ time step, the total accumulated evidence is:

$$W_{i+1} = \Delta W + W_i \cdot w(\Delta t) \tag{6}$$

586   Then the total acquired evidence W_n at time $T = n \cdot \Delta t$ follows the distributions:

$$\begin{cases} N\left(\Delta t \cdot \sum_{i=0}^{n-1} w(i\Delta t), \sigma^2 \Delta t \cdot \sum_{i=0}^{n-1} w(i\Delta t)^2 \right) & \text{if target exists} \\ N\left(-\Delta t \cdot \sum_{i=0}^{n-1} w(i\Delta t), \sigma^2 \Delta t \cdot \sum_{i=0}^{n-1} w(i\Delta t)^2 \right) & \text{if no target exists} \end{cases} \tag{7}$$

588   Note that:

$$\lim_{\Delta t \to 0} \left[\Delta t \cdot \sum_{i=0}^{n-1} w(i\Delta t) \right] = \int_0^T w(t) \, dt = \frac{1 - \exp(-kT)}{k} \tag{8}$$

$$\lim_{\Delta t \to 0} \left[\Delta t \cdot \sum_{i=0}^{n-1} w(i\Delta t)^2 \right] = \int_0^T w(t)^2 \, dt = \frac{1 - \exp(-2kT)}{2k} \tag{9}$$

591 Substituting Equations (8) and (9) into Equation (7), the evolution of target visibility over

592 time can be formulated as:

593
$$d'(T) = a\sqrt{\frac{1 - \exp(-kT)}{k[1 + \exp(-kT)]}}, \quad \text{where } a = \frac{4}{\sqrt{2}\sigma} \tag{10}$$

594 We first fit Equation (10) to the temporal course of target visibility at each measured

595 visual field location (Fig 1E) and got a series values of parameters a and k at different

596 locations (x, y) relative to the fixation location $(0, 0)$. We found that the values of these two

597 parameters decay exponentially from fixation location (Fig S5), so a simple function

598 describing parameter a (or k) is:

599
$$a(x, y) = p_1 \cdot \exp[-p_2 \cdot D(x, y)] \tag{11}$$

600 Here $D(x, y) = \sqrt{x^2 + y^2}$ is the distance between measured location to fixation location. To

601 capture potential asymmetry between horizontal and vertical visibility, Equation (11) is

602 further modified to be:

603
$$a(x, y) = p_1 \cdot \exp\left(-p_2 \cdot \sqrt{x^2 + p_5 \cdot y^2}\right) \tag{12}$$

604
$$k(x, y) = p_3 \cdot \exp\left(-p_4 \cdot \sqrt{x^2 + p_5 \cdot y^2}\right) \tag{13}$$

Equations (10), (12) and (13) together describe the change of visibility map over time.

The parameters p_1, p_2, p_3, p_4, p_5 in these equations were estimated by minimizing the MSE

between the calculated and measured visibility data using the GlobalSearch algorithm in the

Global Optimization Toolbox of MATLAB.

The visual search task. In this experiment, subjects were asked to search for the

target within the background noise image as fast as possible while trying to maximize the

response accuracy. The target locations were sampled uniformly inside the search area, and

subjects were informed about this feature. Subjects began each trial by fixating within 1°

away from a cross displayed at the screen center and pressing a button. Then, the cross

disappeared for a random interval (0.2-0.3 seconds), and the search image appeared and

waited for subjects' responses. There was no limit in waiting time. When the subjects found

the target, they fixated at the target and pressed a key on the keyboard. The final fixation

location and the target's true location were then shown on the screen. If the distance between

these two locations was less than 1°, we labeled the response as correct. Subjects were asked

to report if they had found the correct target location, but the response was judged as

incorrect. In this case we would recalibrate the eye tracker. Subjects performed 200−500

(mean = 315) visual search trials depending on their available time.

Eye-tracking data analysis. Eye-tracking data were analyzed by the EYE-EEG

extension [67] of the EEGLAB toolbox [68]. We used the algorithm described by Nyström

& Holmqvist (2010) to classify eye movements into saccades and fixations. Inaccurate eye

movement events from noisy period of one eye were replaced by events from the other eye.

Fixations separated by blinks were recognized as two fixations. Data from the four subjects

in first version of detection task were merged and served as training set to fit the parameters

in eye movement model (described below), and data from the rest six subjects were merged

and served as testing set. The training set contained 18941 fixations and 19603 saccades

from 1190 visual search trials, and the testing set contained 39985 fixations and 40010

saccades from 1958 visual search trials.

When summarizing fixation durations, we excluded the first (when subjects fixated at

screen center) and the last fixations (when a response was made) to avoid the effects of the

anticipation and motion preparation on the fixation duration. When summarizing fixation

locations, we excluded the first fixation at the screen center.

The Entropy Limit Minimization (ELM) Model

We used the ELM model [1] as our baseline model because it greatly reduced the

computational burden compared to the Bayesian ideal model while maintaining a similar

search performance [1,3] and has received electrophysiological support [70]. The model

could only fixate at 400 locations uniformly sampled inside the search field (Fig S6). We set

the fixation duration to 250 ms and evaluated the visibility map using Equation (10). The

visual information W_{i,L_F} obtained at location i ($i = 1 \cdots n$, $n = 400$) during the F^{th} fixation at

location L_F was sampled from normal distribution $N\left(0.5, 1/d'^2_{i,L_F}\right)$ if the target was at this

location, otherwise from normal distribution $N\left(-0.5, 1/d'^2_{i,L_F}\right)$. The ELM model did not

model the distribution of fixation duration, so the visual information at each location was

sampled once per fixation. The posterior probability map of target location was calculated

from information gathered in all previous fixations (indicating unlimited memory) according

to Bayesian theory [1]:

649
$$P_{i,F} = P\left(i \mid \mathbf{W}_{L_1}, \cdots, \mathbf{W}_{L_F}\right) = \frac{P\left(\mathbf{W}_{L_1}, \cdots, \mathbf{W}_{L_F} \mid i\right) p(i)}{\sum\limits_{j=1}^{n}\left[P\left(\mathbf{W}_{L_1}, \cdots, \mathbf{W}_{L_F} \mid j\right) p(j)\right]} \qquad (14)$$

650   Here $p(i) = 1/n$ is the prior probability of the target being at location i. The vector

651    $\mathbf{W}_{L_F} = \left(W_{1,L_F}, \cdots, W_{n,L_F}\right)$ is the visual evidence at all locations gathered during the F^{th} fixation

652   at location L_F. Assuming the noise was independent at each location and during each

653   fixation, we have:

654
$$P\left(\mathbf{W}_{L_1}, \cdots, \mathbf{W}_{L_F} \mid i\right) = \prod_{f=1}^{F} P\left(\mathbf{W}_{L_f} \mid i\right) = \prod_{f=1}^{F}\prod_{j=1}^{n} P\left(W_{j,L_f} \mid i\right) \qquad (15)$$

655   Since W_{j,L_f} conditioned on target location i follows normal distribution $N\left(\pm 0.5, 1/d_{j,L_F}^{'2}\right)$, by

656   substituting its probability density function into Equations (14) and (15) we could derive:

$$P_{i,F} = \frac{p(i)\cdot\exp\left(\sum_{f=1}^{F} d_{i,L_f}^{'2} W_{i,f}\right)}{\sum_{j=1}^{n}\left[p(j)\cdot\exp\left(\sum_{f=1}^{F} d_{j,L_f}^{'2} W_{j,f}\right)\right]} = \frac{P_{i,F-1}\cdot\exp\left(d_{i,L_F}^{'2} W_{i,F}\right)}{\sum_{j=1}^{n} P_{j,F-1}\cdot\exp\left(d_{j,L_F}^{'2} W_{j,F}\right)} \qquad (16)$$

658   After calculating the posterior probability map of target location, the ELM model

659   selected the next fixation location to maximize the expected information gain (which is the

660   expected reduction of entropy) of the next fixation. Najemnik & Geisler [1] showed that it

661   could be calculated in a very simple form:

$$L_{F+1} = \arg\max_{L_{F+1}}\left\{H_{L_F} - E\left[H_{L_{F+1}}\right]\right\} = \arg\max_{L_{F+1}}\left[\frac{1}{2}\sum_{i=1}^{n}\left(P_{i,T_F}\cdot d_{i,L_{F+1}}^{'2}\right)\right] \qquad (17)$$

where $H_{L_F} = \sum_{i=1}^{n}\left[P_{i,L_F}\cdot\ln\left(P_{i,L_F}\right)\right]$ is the entropy of posterior probability of target location.

The model terminated the search whenever the posterior probability of the target

being at the current fixation location exceeded a threshold θ_T, and the target location was set

as the final fixation location. The value of θ_T was chosen to make the model's correct

response rate comparable to the subjects' data (see Table S1).

The Continuous-time ELM (CTELM) Model

The CTELM model proposed here extends the ELM model to account for the

distribution of fixation durations. A schematic diagram of the CTELM model is shown in

Fig 2 and will be described in the following sections.

Temporal course of evidence accumulation. The accumulation of visual evidence

over time can be described by the evidence accumulation model discussed in previous

sections. In practice, for each fixation f, we first calculated the values of parameter a_{i,L_f} and

k_{i,L_f} at the 400 locations across the visual field according to Equations (12) and (13). These

values were calculated only once per fixation. Then for each time step Δt (1 ms), a random

evidence sample $\Delta W_{i,L_f}$ was generated at each location i from the normal distribution

$N\left(\pm\Delta t, 8\Delta t / a_{i,L_f}^2\right)$ (see the relationship between a and σ in Equation (10)) depending on

whether target was present at this location. The current total accumulated evidence W_{i,L_f,T_f} at

location i at time T_f since the start of the f^{th} fixation was calculated from $W_{i,L_f,T_f-\Delta t}$ in the

previous time step by:

682
$$W_{i,L_f,T_f} = \Delta W_{i,L_f} + W_{i,L_f,T_f-\Delta t} \cdot \exp\left(-k_{i,L_f}\Delta t\right) \tag{18}$$

683   **Calculating target's posterior probability map.** At each time step, the posterior

684   probability of target being at the i^{th} ($i = 1\cdots n$, $n = 400$) location could be calculated from the

685   accumulated evidence from the current and all previous fixations by Bayesian theory:

686
$$P_{i,T_F} = P\left(i \mid \mathbf{W}_{L_1,T_1}, \cdots, \mathbf{W}_{L_F,T_F}\right) = \frac{P\left(\mathbf{W}_{L_1,T_1}, \cdots, \mathbf{W}_{L_F,T_F} \mid i\right) p(i)}{\sum_{j=1}^{n}\left[P\left(\mathbf{W}_{L_1,T_1}, \cdots, \mathbf{W}_{L_F,T_F} \mid j\right) p(j)\right]} \tag{19}$$

687   The vector $\mathbf{W}_{L_F,T_F} = \left(W_{1,L_F,T_F}, \cdots, W_{n,L_F,T_F}\right)$ is the accumulated evidence by time T_F of the F^{th}

688   fixation at all locations. Like the ELM model, the CTELM model also had unlimited and

689   perfect memory across fixations.

690   Assuming that visual information was independently accumulated at each location

691   during each fixation, Equation (19) could be simplified to (see the S1 Text for details):

692
$$P_{i,T_F} = \frac{p(i) \cdot \exp\left[\sum_{f=1}^{F} \frac{a_{i,L_f}^2 \cdot W_{i,L_f,T_f}}{2 + 2\exp\left(-T_f \cdot k_{i,L_f}\right)}\right]}{\sum_{j=1}^{n}\left\{p(j) \cdot \exp\left[\sum_{f=1}^{F} \frac{a_{j,L_f}^2 \cdot W_{j,L_f,T_f}}{2 + 2\exp\left(-T_f \cdot k_{j,L_f}\right)}\right]\right\}}$$
(20)

By applying Equation (20) to all target locations at each time step, we could calculate

the change in the posterior probability map of the target location over time.

Decision on saccade timing. In the CTELM model, saccades were triggered

randomly in two different ways according to their relative frequency. The majority (97%) of

saccades (normal saccades) were triggered by a decision process concerning whether the

current attention location contained the target. The first saccade in a trial was always a

normal saccade. If the probability of the target being at the current attention location was

lower than a threshold, the model makes a saccade decision. We defined the current

attention location as the current fixation location when the next saccade decision had not

been made, and as the next fixation location when the next saccade decision had been made,

but the eyes had not moved because of the delay from the cortex to the eye movement

muscles (saccade lag). We implemented the saccade threshold $\theta_S(t)$ as a "collapsing bound",

similar to certain decision-making models [44,71–73]:

706
$$\log_{10}\left[\theta_S(t)\right] = q_1 \cdot \exp\left[-\left(\frac{t}{q_2}\right)^{q_3}\right]$$
(21)

Here, q_1, q_2, q_3 (q_1, $q_3 < 0$, $q_2 > 0$) are parameters whose values are estimated by fitting to

distributions of fixation durations from experimental data. After the saccade decision was

made, a new saccade decision process started immediately.

In addition to normal saccades, a small group of low-latency saccades can be

generated by other visual pathways [74,75]. In the model, we set the frequency of low-

latency saccades to 3% according to the frequency of express saccades in an overlap task

[76]. The latency (in seconds) is directly drawn from a gamma distribution with shape

parameter 10 and scale parameter 6.9×10^{-4}, plus a delay of 0.03 seconds. This latency

follows a distribution with mean = 99 ms, 5% percentile = 68 ms, and 95% percentile = 138

ms, which roughly falls in the 80-120 ms range of express saccade latency [77]. After the

saccade decision was made, a new saccade decision process started immediately before the

delay of 0.03 seconds.

In the model, the delay from the retina to the visual cortex (eye-brain lag) was set to

0.06 seconds [78], and the saccade lag was set to 0.03 seconds [79]. At the start of a new

fixation, the model continued to accumulate information from the previous fixation until the

arrival of new information after the eye-brain lag. We did not consider the duration of a

saccade itself (a saccade is finished instantly) because of saccadic masking [17].

Decision on saccade target. When making a saccade decision, the CTELM model

used the ELM rule (Equation (17)) to select the next fixation location. However, the

deviation of Equation (17) as shown by Najemnik and Geisler [1] requires the visibility $d'_{i,L_{f+1}}$

to be a fixed value within a fixation, but in the CTELM model, $d'_{i,L_{f+1}}$ changes with time. As

a simplification, we set the expected duration of the next fixation to be 0.25 seconds when

evaluating Equation (17). We ran Monte Carlo simulations and found that the expected

information gain calculated in this way had a high Pearson correlation (mean = 0.923) with

the actual information gain (Fig S14 in S2 Text).

Decision on target location. The search stopped whenever the posterior probability

at the current fixation location exceeded a target detection threshold θ_T, and the model set the

current fixation location as the target location. The value of θ_T was chosen to make the

model's correct response rate comparable to the subjects' data.

The Constrained-CTELM (CCTELM) model

The schematic diagram of the CCTELM model is the same as the CTELM model (Fig

2), but we limit the memory capacity, suppress the probability of making long saccades, and

add saccade landing position variability to the model.

Memory capacity. For simplicity, we set the memory of the model to be all-or-none.

The model either retained complete information from a fixation or completely forgot it. A

model with a memory capacity of M could only integrate information from the past $M-1$

fixations plus the current fixation, so at the F^{th} fixation, the earliest fixation that the model

could integrate was $f_s = \max(1, F-M+1)$. The posterior probability target being at location i

could be calculated as (see S1 Text for the derivation of this formula):

$$746 \quad P_{i,T_F} = P\left(i \mid \mathbf{W}_{L_{f_s},T_{f_s}}, \cdots, \mathbf{W}_{L_F,T_F}\right) = \frac{P\left(\mathbf{W}_{L_{f_s},T_{f_s}}, \cdots, \mathbf{W}_{L_F,T_F} \mid i\right) p(i)}{\sum_{j=1}^{n}\left[P\left(\mathbf{W}_{L_{f_s},T_{f_s}}, \cdots, \mathbf{W}_{L_F,T_F} \mid j\right) p(j)\right]} \quad (22)$$

747 In S1 Text we showed that the expression could be simplified to:

$$748 \quad P_{i,T_F} = \frac{p(i)\cdot\exp\left[\sum_{f=f_s}^{F}\frac{a_{i,L_f}^2 \cdot W_{i,L_f,T_f}}{2+2\exp\left(-T_f \cdot k_{i,L_f}\right)}\right]}{\sum_{j=1}^{n}\left\{p(j)\cdot\exp\left[\sum_{f=f_s}^{F}\frac{a_{j,L_f}^2 \cdot W_{j,L_f,T_f}}{2+2\exp\left(-T_f \cdot k_{j,L_f}\right)}\right]\right\}} \quad (23)$$

Decision on saccade timing. The CCTELM model used the same method to decide

saccade timing as the CTELM model. However, because of the saccadic inaccuracy, the

CCTELM model could fixate at every possible location in the search field (not just the

predefined 400 locations). The posterior probability of target being at current attention

location, therefore, was the sum of posterior probability at all the predefined 400 locations

within 0.5 degrees away from the actual attention location. Our Monte Carlo simulation

showed that in 44.46%, 47.13% and 8.41% cases, one, two, and three nearby locations were

counted, respectively.

Decision on saccade target. As we show in result section, the ELM and CTELM

model made too many long saccades compared to humans. The preference of small saccades

on humans has been observed in previous studies [23,61], and several possible reasons for

this preference have been proposed [61]: (1). short saccades decrease the time spent on

saccades [14–16]; (2). short saccades decrease the degree of saccadic suppression of motion

perception [17]; and (3). short saccades are more accurate and decrease the chance to make a

secondary saccade to the target [9–13]. We considered these factors as possible costs to

make a saccade, represented by a penalty function H(L_f, L_{f+1}) when selecting the next fixation

location:

766
$$L_{f+1} = \arg\max_{L_{f+1}} \left[H\left(L_f, L_{f+1}\right) \cdot \frac{1}{2} \sum_{i=1}^{n} \left(P_{i,T_f} \cdot d'^2_{i,L_{f+1}} \right) \right] \tag{24}$$

767
$$H\left(L_f, L_{f+1}\right) = \exp\left(-\frac{\max\left[D\left(L_f, L_{f+1}\right), 1 \right]}{c} \right) \tag{25}$$

where D(L_f, L_{f+1}) is the Euclidean distance between the current and next potential fixation

location in visual degree, and c is a free parameter. Thus, even though a distant location may

have high expected information gain according to the ELM rule, Equation (25) suppresses

the probability making one long saccade to that location and promotes making several short

amplitude saccades. We chose not to apply the penalty function within 1 degree away from

fixation location to prevent interfering with the inhibition of return phenomenon generated by

the model.

Variability of saccade landing position. The accuracy of saccades can be described

by the offset between mean saccade landing positions and the saccade target, and the

variability of saccade landing positions. Some studies found that the mean saccade landing

positions were quite accurate for the saccades typically made in our experiment [12,15,16],

but some others showed undershooting bias of long saccades ($> 7°$) [10], or both short and

long saccades [13]. However, many existing studies showed that the standard deviation (SD)

of saccade landing positions increased linearly with saccade amplitude to a similar scale

[10,12,13]. Therefore, for simplicity we only considered saccade landing position variability

in the model and assumed the mean landing positions were accurate. We further assumed the

actual saccade landing positions formed a 2-dimensional Gaussian distribution around the

mean [12], and ignored any difference in horizontal and vertical directions.

To accurately describe the relationship between SD of saccade landing positions and

saccade target eccentricity, we analyzed the raw data from experiment 2 of [12]. In brief,

this experiment required subjects to fixate at a target with eccentricity varying from 0.5 to

17.5 degrees left or right away from the initial fixation location, and identified the number of

small dots presented around the target location [12]. Only the first, non-anticipatory

saccades after presentation of the target were analyzed. Raw data was shown in Fig S7A.

Leftward and rightward trials with the same eccentricity were combined (leftward saccades

flipped to rightward). The SD of saccade landing positions σ_s was calculated as:

794
$$\sigma_s = \sqrt{\frac{\sum_{i=1}^{N}\left[\left(x_i - \bar{x}\right)^2 + \left(y_i - \bar{y}\right)^2\right]}{N}}$$
(26)

Here (x_i, y_i) is the saccade landing position of the i^{th} trial, $\left(\bar{x}, \bar{y}\right)$ is the mean saccade landing

position of all N trials with the same target eccentricity. The relationship between target

eccentricity and σ_s was fit by linear regression (Fig S7B). The values of slope (m) and

intercept (c) coefficients are shown in Table S1.

Decision on target location. The CCTELM model stopped searching whenever the

posterior probability at the current fixation location (sum of all 400 predefined locations

within 0.5 degrees from fixation location) exceeded a target detection threshold θ_T. The

model set the target location as the predefined location with highest posterior probability.

The value of θ_T was chosen to make the model's correct response rate comparable to the

subjects' data.

Fitting Model Parameters

Table S1 shows a summary of the parameters used in the ELM, CTELM, and

CCTLEM model. All the parameters were derived by fitting the models to the data of

training set (4 subjects, including both correct and error trials).

For the CTELM model, there are three free parameters in Equation (21) that control

the distribution of the fixation duration. The remaining parameters were estimated from

experimental data and fixed when fitting the free parameters. The values of the free

parameters were estimated by genetic algorithm [80] that minimized the sum of the

Bhattacharyya distance (DB) between the simulated and experimental histograms of the

fixation duration (T_{sim}, T_{exp}):

$$Loss = \mathrm{DB}\left(T_{sim}, T_{exp}\right) \tag{27}$$

816   where the $DB(H_1, H_2)$ of the two histograms H_1 and H_2 is defined as

$$\mathrm{DB}\left(H_1, H_2\right) = -\ln\left[\mathrm{BC}\left(H_1, H_2\right)\right] \tag{28}$$

$$\mathrm{BC}\left(H_1, H_2\right) = \sum_{i=1}^{N} \sqrt{H_1(i) \cdot H_2(i)} \tag{29}$$

Here, N represents the number of bins in the two histograms. The histogram should be

calculated as probability. The genetic algorithm was implemented in the Global

Optimization toolbox of MATLAB. We set the population size to 150 and max generations

to 25, leaving the other parameters unchanged. For each parameter sample in the population,

the model was run for 1000 times to obtain the histogram of fixation durations. We used the

Multicore package (https://www.mathworks.com/matlabcentral/fileexchange/13775-

multicore-parallel-processing-on-multiple-cores) to run the genetic algorithm on multiple

computers.

For the CCTELM model, we fit the four free parameters in Equations (21) and (25)

by genetic algorithm. The cost function is the sum of the Bhattacharyya distance (DB)

between the simulated and experimental histograms of the fixation duration (T_{sim}, T_{exp}) and

saccade amplitude (A_{sim}, A_{exp}):

831
$$Loss = \mathrm{DB}\left(T_{sim}, T_{exp}\right) + \mathrm{DB}\left(A_{sim}, A_{exp}\right) \tag{30}$$

We set the population size to 250 and max generations to 25, leaving the other

parameters unchanged. For each parameter sample in the population, the model was run

1000 times to obtain the histograms of the fixation durations and saccade amplitudes.

Recently there are proposals to find free parameters in eye movement models by

maximum likelihood estimation (MLE) [81]. Indeed, MLE has many merits over the genetic

algorithm that we used here, but it requires getting the likelihood function which is hard for

complex models like the CCTELM model. An alternative and popular likelihood-free

method, called the Approximate Bayesian Computation (ABC), works by evaluating the

model with different combinations of parameter values and minimizes the distance (by

calculating certain summary statistics) between simulated and experiment data [82].

However, with only a few parameters the speed of ABC gets very slow because of the large

parameter space to explore [83]. Therefore, we chose to use the genetic algorithm to

estimate free parameters which has been used in previous eye movement models [27,28,84].

Although it is not mathematically well-founded compared to MLE or ABC, in practice we

found that the method consistently produced good fitting to experiment data in reasonable

amount of time.

To find the memory capacity that best predicts the experiment data, we first assumed

unlimited memory capacity and fit the four free parameters to subjects' data. We then

evaluated the model with memory capacity of 2, 4, $\cdots$, 14 and infinite fixations for 50000

times each. The value of target detection threshold θ_T was set to 0.952 (Table S1). For the

simulation result belonging to each capacity, we calculated the histograms of fixation

duration, fixation distance and saccade amplitude of the initial 20 fixations and saccades, and

the overall distribution of fixation location. Both correct and error trials were used. Then for

fixation duration / distance and saccade amplitude, we calculated the Bhattacharyya

coefficient (BC) between histograms of simulation and experiment data corresponding to the

same fixation or saccade ordinal index. Thus, for each memory capacity value, we obtained

1 BC value for fixation location and 20 BC values for fixation duration, fixation distance,

and saccade amplitude. Finally, the 20 BC values were averaged to obtain a single BC value

per eye movement metric.

Simulating Visual Search

The three models were evaluated for 50000 trials to obtain eye movement statistics.

We randomly rotate the 400 potential target locations around the image center before each

trial to help obtain a smooth distribution of fixation locations. The target locations were

randomly selected with equal probability in each trial.

When we summarized the eye movement metrics, we excluded the first and the last

fixations for the fixation duration, and excluded the initial fixations for the fixation location.

We used BC to quantify the similarity between the histograms of the model's and humans'

eye movement metrics. When the histograms are calculated as probabilities and have the

same number of bins, BC has a maximum value of 1 if the two histograms are completely the

same and a minimum value of 0 if the two histograms have no overlap.

Data and Code Accessibility

The experiment and simulation results, the code for analyzing eye-tracking data and

visual search models are available on Open Science Framework at https://osf.io/ypcwx/.

Questions should be directed to the corresponding author.

877   **Acknowledgments**

878   We thank Professor Zhaoping Li for her advice on the manuscript.

880   **Supporting Information**

Fig S1. Temporal course of target visibility at four cardinal directions (shown in four

subplots) relative to fixation location of subject 1 in training set.

Fig S2. Temporal course of target visibility at four cardinal directions (shown in four

subplots) relative to fixation location of subject 2 in training set.

Fig S3. Temporal course of target visibility at four cardinal directions (shown in four

subplots) relative to fixation location of subject 3 in training set.

Fig S4. Temporal course of target visibility at four cardinal directions (shown in four

subplots) relative to fixation location of subject 4 in training set.

Fig S5. Relationship between the values of parameter a and k in Equation 10 in the main text

to target's distance from fixation location.

Fig S6. Locations of the 400 positions where the model can fixate.

Fig S7. Variability of saccadic landing position as a function of saccade target eccentricity.

Fig S8. Fixation location distribution of subjects and models in error trials.

Fig S9. Distribution of saccade amplitude as a function of ordinal position in a sequence of

saccades from all correct trials.

Fig S10. Distribution of saccade amplitude as a function of ordinal position in a sequence of

saccades from all error trials.

Fig S11. Distribution of fixation duration as a function of ordinal position in a sequence of

fixations from all correct trials.

Fig S12. Distribution of fixation duration as a function of ordinal position in a sequence of

fixations from all error trials.

Fig S13. Relationship between the change in saccade direction and the preview benefit of the

fixation in between.

S1 Text. Calculation of the Posterior Probability Map.

S2 Text. Validation of the ELM Rule.

S3 Text. Visibility Map without Target Location Cue.

S1 Table. Parameters used in the three visual search models.

Fig 1. Stimulus image and results of the detection task. **A.** The stimulus image was a 1/f

noise image (15° diameter, root-mean-squared (RMS) contrast 0.2) with an embedded

target. The target was a 6 cycle/degree Gabor grating with a diameter of 0.3 degrees, oriented

45° counterclockwise from the vertical and windowed by a symmetrical raised cosine (half-

height width of one cycle). The area outside the image was set to the mean gray value of the

image (0.5, not shown here). **B, C.** Detection rate (B) and foveal target visibility (C) as a

function of the target RMS contrast of the ten subjects. Dots are raw data (one color per

participant). In B, the curves are the Weibull function fit to the dots. In C, the curves are

calculated from Weibull functions fit to hit rates and the correct rejection rate of the raw data

(Equation (1)). The intersection between the dashed line ($d^{'} = 3.0$) and the curves is the target

RMS contrast chosen for each participant, which was used for all subsequent experiments. **D.**

Target visibility map after different stimulus exposure times in the detection task. The dots

are raw data merged from four subjects in first version of the detection task. The surface is

the visibility map function (Equations (10), (12), (13)) fit to the raw data. Not all locations

were tested in all exposure times so the number of black dots may differ in each subplot.

Hori/Vert: horizontal/vertical dimension of the search field. Fixation location was at the

center of search field. **E.** Temporal course of target visibility at four cardinal directions

(shown in four subplots) relative to the fixation location. The dots are raw data merged from

four subjects in first version of the detection task. Different markers represent raw data

measured at different relative eccentricities (shown in the legend). The eccentricity values

(0.0 - 0.9) are normalized with respect to the radius of the search field. The curves are

Equation (10) fitted to the raw data measured at each location. The data measured at the

fixation location (eccentricity = 0.0) are shown in every subplot. For clarity, not all measured

locations are shown here. See Fig S1-S4 for the complete data from each participant.

Fig 2. Schematic diagram of the continuous-time entropy limit minimization (CTELM) and

constrained-CTELM (CCTELM) models.

Fig 3. Fixation location distribution of subjects and models in correct trials (for error trials

see Fig S8). **A.** Distribution of fixations location in the search field (inside the white circle),

lighter means higher density. The densities were obtained by smoothing the scatterplot of the

fixation locations by a Gaussian window with a standard deviation of 0.35 degrees (15 pixels)

and then normalizing the maximum value in each subplot to one. **B.** Direction histograms of

fixation location relative to the image center. The histograms were obtained with a sliding

radial window with a width of 45° centered different radial positions (x-axis). Rightward

direction is 0° and upward direction is –90°. **C.** Horizontal cuts (through the center) through

the fixation densities in panel A. Rightward direction is positive in x-axis. **D.** Vertical cuts

(through the center) through fixation densities in panel A. Upward direction is negative in x-

axis. In panels BCD area under curve are normalized to one. **E.** Fixation distance

distribution to image center selected within the initial 11 fixations after the first saccade. **F.**

Bhattacharyya coefficient between models' and subjects' distributions of fixation distance to

image center of the initial 20 fixations after the first saccade. Dots represent raw data; curves

represent quadratic functions fitted to the dots. Legends from panel B to F are shown in

bottom-left of panel F.

Fig 4. Saccade amplitude distribution of the subjects and models. **A.** Saccade amplitude

histogram of all saccades in correct and error trials. **B.** Bhattacharyya coefficient (BC)

between the models' and subjects' saccade amplitude distribution of the initial 20 saccades in

correct and error trials. Dots represent raw data, curves represent quadratic functions fitted to

the dots. See Fig S9 and Fig S10 for the distribution of raw data at each ordinal position in

correct and error trials. **C.** Relationship between the first saccade's amplitude (SacAmp) in

two consecutive saccades and the change in saccade direction (SacDir) in all trials. **D.**

Relationship between the second saccade's amplitude in two consecutive saccades and the

change in saccade direction in all trials. **E.** Relationship between the second and the first

saccade's amplitude in two consecutive saccades in all trials. In panels CDE error bar

represents 95% confidence interval.

Fig 5. Fixation duration distribution of the subjects and models. **A:** Fixation duration

distribution of correct and error trials. The first fixation (when a trial started) and last

fixation (when making a response) are excluded. **B:** Bhattacharyya coefficient (BC) between

the models' and subjects' fixation duration distributions of the initial 20 fixations (first and

last fixation are excluded) in correct and error trials. Dots represent raw data; curves

represent quadratic functions fitted to the dots. See Fig S11 and Fig S12 for the distribution

of raw data at each ordinal position in correct and error trials. **C.** Relationship between

fixation duration between two consecutive saccades and the change in saccade direction in all

trials. **E.** Relationship between fixation duration previous saccade amplitude in all trials. In

C and D error bar represents 95% confidence interval.

Fig 6. Subjects and the three models' search performances. **A.** The distribution of the

number of fixations needed to find the target in all correct trials. **B.** Median number of

fixations to correctly find the target as a function of the median target eccentricity from the

image center. **C.** The distance between fixation location and the target location as a function

of the number of fixations before correctly finding the target. **D.** Posterior probability at the

target location as a function of the number of fixations before the model correctly finding the

target. In C and D error bar shows 95% confidence interval.

Fig 7. Effect of memory capacity on the CCTELM model's behavior. **A.** Effect of memory

capacity on the goodness of fit to training data. For fixation duration, fixation distance (to

screen center) and saccade amplitude, we first align sequences of eye movements at start of

the trial and calculated the initial 20 histograms of these metrics from all (both correct and

error) trials. Then we calculated the 20 Bhattacharyya coefficients (BC) at each ordinal

position and averaged them together to obtain a single value for each memory capacity per

metric. For fixation location we calculated the overall 2-dimensional histogram from all

trials, smoothed by a Gaussian window with a standard deviation of 0.35 degrees (15 pixels),

and calculated the BC value for each memory capacity. The thick black line is the average of

the four colored thin dashed lines. "Inf" represents the unlimited memory capacity. **B.**

Effect of memory capacity on the mean number of fixations to correctly find the target at

different eccentricities of the CCTELM model. The data in A and B came from the

CCTELM model whose parameters were fit assuming unlimited memory but evaluated under

different memory capacities.

1005

Fig 8. Example scan path of the subjects and models. Scan paths on each row have similar

fixation number shown at the left side. The search starts from image center. Black circle

represents the image boundary, cross represents a fixation, and the line between two crosses

represents a saccade. The final fixation to report the target location is labeled in red. The red

circle shows the true target location.

1013

	P(Correct)	Median Fixation Number		Maximum Fixation Number	
		Correct Trials	Error Trials	Correct Trials	Error Trials
Training Set	87.98%	8	38	176	158
Testing Set	84.73%	10	39	181	425
ELM	87.31%	7	6	42	40
CTELM	88.07%	7	7	38	36
CCTELM	88.14%	8	8	127	96

1014　　Table 1. Visual search performance of the two groups of subjects (training and testing set)

1015　　and three models. P(Correct) is the correct response rate.

1016

References

1. Najemnik J, Geisler WS. Simple summation rule for optimal fixation selection in

visual search. Vision Res. 2009;49(10):1286–94.

2. Najemnik J, Geisler WS. Eye movement statistics in humans are consistent with an

optimal search strategy. J Vis. 2008;8(3):4.

3. Najemnik J, Geisler WS. Optimal eye movement strategies in visual search. Nature.

2005;434(7031):387–91.

4. Araujo C, Kowler E, Pavel M. Eye movements during visual search: the costs of

choosing the optimal path. Vision Res. 2001;41(25–26):3613–25.

5. Nowakowska A, Clarke ADF, Hunt AR. Human visual search behaviour is far from

ideal. Proc R Soc B Biol Sci. 2017;284(1849):1–6.

6. Morvan C, Maloney LT. Human visual search does not maximize the post-saccadic

probability of identifying targets. PLoS Comput Biol. 2012;8(2):e1002342.

7. Steng E, Id RVDB. Imperfect Bayesian inference in visual perception. PLoS Comput

Biol. 2019;15(4):1–27.

8. Rothkegel LOM, Schütt HH, Trukenbrod HA, Wichmann FA, Engbert R. Searchers

adjust their eye-movement dynamics to target characteristics in natural scenes. Sci Rep.

2019;9(1635):1–12.

9. Lemij HG, Collewijn H. Differences in accuracy of human saccades between

stationary and jumping targets. Vision Res. 1989;29(12):1737–48.

10. Abrams RA, Meyer DE, Kornblum S. Speed and Accuracy of Saccadic Eye

Movements: Characteristics of Impulse Variability in the Oculomotor System. J Exp

Psychol Hum Percept Perform. 1989;15(3):529–43.

11.   Van Beers RJ. The sources of variability in saccadic eye movements. J Neurosci.

1041   2007;27(33):8757–70.

1042   12.   Nuthmann A, Vitu F, Engbert R, Kliegl R. No evidence for a saccadic range effect for

1043   visually guided and memory-guided Saccades in simple saccade-targeting tasks. PLoS

1044   One. 2016;11(9):e0162449.

1045   13.   Gillen C, Weiler J, Heath M. Stimulus-driven saccades are characterized by an

1046   invariant undershooting bias: No evidence for a range effect. Exp Brain Res.

1047   2013;230(2):165–74.

1048   14.   Baloh RW, Sills AW, Kumley WE, Honrubia V. Quantitative measurement of saccade

1049   amplitude, duration, and velocity. Neurology. 1975;25(11):1065–70.

1050   15.   Collewijn H, Erkelens CJ, Steinman RM. Binocular co□ordination of human

1051   horizontal saccadic eye movements. J Physiol. 1988;404(1):157–82.

1052   16.   Collewijn H, Erkelens CJ, Steinman RM. Binocular co□ordination of human vertical

1053   saccadic eye movements. J Physiol. 1988;404(1):183–97.

1054   17.   Bridgeman B, Hendry D, Stark L. Failure to detect displacement of the visual world

1055   during saccadic eye movements. Vision Res. 1975;15(6):719–22.

1056   18.   Zelinsky GJ. A Theory of Eye Movements During Target Acquisition. Psychol Rev.

1057   2008;115(4):787–835.

1058   19.   Zelinsky GJ. TAM: Explaining off-object fixations and central fixation tendencies as

1059   effects of population averaging during search. Vis cogn. 2012;20(4–5):515–45.

1060   20.   Wolfe JM, Gancarz G. Guided search 3.0: A model of visual search catches up with

1061   jay enoch 40 years later. In: Basic and Clinical Applications of Vision Science. 1997.

1062   p. 189–92.

21.   Henderson JM, Hollingworth A. Eye Movements During Scene Viewing: An

Overview. In: Underwood G, editor. Eye Guidancing in Reading and Scene Perception.

Elsevier Science Ltd; 1998. p. 269–93.

22.   Halverson T, Hornof AJ. A computational model of active vision for visual search in

human-computer interaction. Human-Computer Interact. 2011;26(4):285–314.

23.   Tatler BW, Vincent BT. Systematic tendencies in scene viewing. J Eye Mov Res.

2008;2(2):1–18.

24.   Wilming N, Harst S, Schmidt N, König P. Saccadic Momentum and Facilitation of

Return Saccades Contribute to an Optimal Foraging Strategy. PLoS Comput Biol.

2013;9(1).

25.   Ratcliff R, Murdock BB. Retrieval processes in recognition memory. Psychol Rev.

1976;83(3):190–214.

26.   Welford AT. Evidence of a Single-Channel Decision Mechanism Limiting

Performance in a Serial Reaction Task. Q J Exp Psychol. 1959;11(4):193–210.

27.   Nuthmann A, Smith TJ, Engbert R, Henderson JM. CRISP: A Computational Model

of Fixation Durations in Scene Viewing. Psychol Rev. 2010;117(2):382–405.

28.   Trukenbrod HA, Engbert R. ICAT: A computational model for the adaptive control of

fixation durations. Psychon Bull Rev. 2014;21(4):907–34.

29.   Tatler BW, Brockmole JR, Carpenter RHS. LATEST: A model of saccadic decisions

in space and time. Psychol Rev. 2017;124(3):267–300.

30.   Engbert R, Nuthmann A, Richter EM, Kliegl R. SWIFT: A dynamical model of

saccade generation during reading. Psychol Rev. 2005;112(4):777–813.

31.   Ratcliff R, Smith PL, Brown SD, McKoon G. Diffusion Decision Model: Current

1086   Issues and History. Trends Cogn Sci. 2016;20(4):260–81.

1087   32.   Ratcliff R. A Theory of Memory Retrieval. Psychol Rev. 1978;85(2):59–108.

1088   33.   Roitman JD, Shadlen MN. Response of neurons in the lateral intraparietal area during

1089   a combined visual discrimination reaction time task. J Neurosci. 2002;22(21):9475–89.

1090   34.   Shadlen MN, Newsome WT. Neural basis of a perceptual decision in the parietal

1091   cortex (area LIP) of the rhesus monkey. J Neurophysiol. 2001;86(4):1916–36.

1092   35.   Hanes DP, Schall JD. Neural control of voluntary movement initiation. Science (80-).

1093   1996;274(5286):427–30.

1094   36.   Hooge ITC, Vlaskamp BNS, Over EAB. Chapter 27 - Saccadic search: On the

1095   duration of a fixation. In: Gompel RPG Van, Fischer MH, Murray WS, Hill RL,

1096   editors. Eye Movements [Internet]. Oxford: Elsevier; 2007. p. 581–95. Available from:

1097   http://www.sciencedirect.com/science/article/pii/B978008044980750029X

1098   37.   Hooge ITC, Erkelens CJ. Control of fixation duration in a simple search task. Percept

1099   Psychophys. 1996;58(7):969–76.

1100   38.   Kingdom FAA, Prins N. Signal Detection Measures. In: Kingdom FAA, Prins N,

1101   editors. Psychophysics: A Practical Introduction. Second Edi. Elsevier Ltd; 2016. p.

1102   149–88.

1103   39.   Rayner K, Pollatsek A. Eye movement control during reading: Evidence for direct

1104   control. Q J Exp Psychol Sect A. 1981;33(4):351–73.

1105   40.   Hooge ITC, Erkelens CJ. Peripheral vision and oculomotor control during visual

1106   search. Vision Res. 1999;39(8):1567–75.

1107   41.   Larson AM, Freeman TE, Ringer R V., Loschky LC. The spatiotemporal dynamics of

1108   scene gist recognition. J Exp Psychol Hum Percept Perform. 2014;40(2):471–87.

42.   Müller JR, Metha AB, Krauskopf J, Lennie P. Information conveyed by onset

transients in responses of striate cortical neurons. J Neurosci. 2001;21(17):6978–90.

43.   Obara K, O'Hashi K, Tanifuji M. Mechanisms for shaping receptive field in monkey

area TE. J Neurophysiol. 2017;118(4):2448–57.

44.   Thura D, Beauregard-Racine J, Fradet C-W, Cisek P. Decision making by urgency

gating: theory and experimental support. J Neurophysiol. 2012;108(11):2912–30.

45.   Drugowitsch J, Moreno-Bote RN, Churchland AK, Shadlen MN, Pouget A. The cost

of accumulating evidence in perceptual decision making. J Neurosci.

2012;32(11):3612–28.

46.   Le Meur O, Liu Z. Saccadic model of eye movements for free-viewing condition.

Vision Res [Internet]. 2015;116:152–64. Available from:

http://dx.doi.org/10.1016/j.visres.2014.12.026

47.   Sligte IG, Scholte HS, Lamme VAF. Are there multiple visual short-term memory

stores? PLoS One. 2008;3(2):e1699.

48.   Report B. Fragile visual short-term memory is an object-based and location-specific

store. Psychon Bull Rev. 2013;20(4):732–9.

49.   McCarley JS, Wang RF, Kramer AF, Irwin DE, Peterson MS. How much memory

does oculomotor search have? Psychol Sci [Internet]. 2003;14(5):422–6. Available

from: http://www.ncbi.nlm.nih.gov/pubmed/12930471

50.   Kaunitz LN, Rowe EG, Tsuchiya N. Large Capacity of Conscious Access for

Incidental Memories in Natural Scenes. Psychol Sci. 2016;27(9):1266–77.

51.   Beck MR, Peterson MS, Vomela M. Memory for where, but not what, is used during

visual search. J Exp Psychol Hum Percept Perform. 2006;32(2):235–50.

52.   Dickinson CA, Zelinsky GJ. Memory for the search path: Evidence for a high-capacity

1133   representation of search history. Vision Res. 2007;47(13):1745–55.

1134   53.   Rolfs M, Carrasco M. Rapid Simultaneous Enhancement of Visual Sensitivity and

1135   Perceived Contrast during Saccade Preparation. J Neurosci. 2012;32(40):13744–52.

1136   54.   Hoppe D, Rothkopf CA. Multi-step planning of eye movements in visual search. Sci

1137   Rep [Internet]. 2019;9(1):1–12. Available from: http://dx.doi.org/10.1038/s41598-018-

1138   37536-0

1139   55.   De Vries JP, Hooge ITC, Verstraten FAJ. Saccades Toward the Target Are Planned as

1140   Sequences Rather Than as Single Steps. Psychol Sci. 2014;25(1):215–23.

1141   56.   Caspi A, Beutter BR, Eckstein MP. The time course of visual information accrual

1142   guiding eye movement decisions. Proc Natl Acad Sci. 2004;101(35):13086–90.

1143   57.   Hesse C, Franz VH. Grasping remembered objects: Exponential decay of the visual

1144   memory. Vision Res [Internet]. 2010;50(24):2642–50. Available from:

1145   http://dx.doi.org/10.1016/j.visres.2010.07.026

1146   58.   Ricker TJ, Vergauwe E, Cowan N. Decay theory of immediate memory: From Brown

1147   (1958) to today (2014). Q J Exp Psychol [Internet]. 2016;69(10):1969–95. Available

1148   from: http://dx.doi.org/10.1080/17470218.2014.914546

1149   59.   Van der Stigchel S, Hollingworth A. Visuospatial Working Memory as a Fundamental

1150   Component of the Eye Movement System. Curr Dir Psychol Sci. 2018;27(2):136–43.

1151   60.   Peterson MS, Beck MR, Vomela M. Visual search is guided by prospective and

1152   retrospective memory. Percept Psychophys. 2007;69(1):123–35.

1153   61.   Tatler BW, Vincent BT. The prominence of behavioural biases in eye guidance. Vis

1154   cogn. 2009;17(6–7):1029–54.

1155   62.   Brainard DH. The Psychophysics Toolbox. Spat Vis. 1997;10(4):433–6.

1156   63.   Pelli DG. The VideoToolbox software for visual psychophysics: Transforming

1157   numbers into movies. Spat Vis. 1997;10(4):437–42.

1158   64.   Kleiner M, Brainard D PD. "What's new in Psychtoolbox-3?" Perception 36 ECVP

1159   Abstract Supplement. Perception. 2007;36(14):1–16.

1160   65.   Prins N, Kingdom FAA. Applying the model-comparison approach to test specific

1161   research hypotheses in psychophysical research using the Palamedes toolbox. Front

1162   Psychol. 2018;9(JUL):1250.

1163   66.   Macmillan NA, Creelman CD. Comparison (Two-Distribution) Designs for

1164   Discrimination. In: Detection Theory: A User's Guide. 2005. p. 165–85.

1165   67.   Dimigen O, Sommer W, Hohlfeld A, Jacobs AM, Kliegl R. Coregistration of eye

1166   movements and EEG in natural reading: Analyses and review. J Exp Psychol Gen.

1167   2011;140(4):552–72.

1168   68.   Delorme A, Makeig S. EEGLAB: an open source toolbox for analysis of single-trial

1169   EEG dynamics including independent component analysis. J Neurosci Methods

1170   [Internet]. 2004;134(1):9–21. Available from:

1171   http://www.ncbi.nlm.nih.gov/pubmed/15102499

1172   69.   Nyström M, Holmqvist K. An adaptive algorithm for fixation, saccade, and glissade

1173   detection in eyetracking data. Behav Res Methods. 2010;42(1):188–204.

1174   70.   Horan M, Daddaoua N, Gottlieb JP. Parietal neurons encode instrumental sampling

1175   based on decision uncertainty. Nat Neurosci [Internet]. 2019;22(August):1327–35.

1176   Available from: http://dx.doi.org/10.1038/s41593-019-0440-1

1177   71.   Ratcliff R, Frank MJ. Reinforcement-based decision making in corticostriatal circuits:

1178  Mutual constraints by neurocomputational and diffusion models. Vol. 24, Neural

1179  Computation. 2012. p. 1186–229.

1180 72. Gluth S, Rieskamp J, Buchel C. Deciding When to Decide: Time-Variant Sequential

1181  Sampling Models Explain the Emergence of Value-Based Decisions in the Human

1182  Brain. J Neurosci. 2012;32(31):10686–98.

1183 73. Zhang S, Lee MD, Vandekerckhove J, Maris G, Wagenmakers EJ. Time-varying

1184  boundaries for diffusion models of decision making and response time. Front Psychol.

1185  2014;5(DEC):1364.

1186 74. Schiller PH, Sandell JH, Maunsell JH. The effect of frontal eye field and superior

1187  colliculus lesions on saccadic latencies in the rhesus monkey. J Neurophysiol

1188  [Internet]. 1987;57(4):1033–49. Available from:

1189  https://doi.org/10.1152/jn.1987.57.4.1033

1190 75. Zhaoping L. A new framework for understanding vision from the perspective of the

1191  primary visual cortex. Curr Opin Neurobiol [Internet]. 2019;58:1–10. Available from:

1192  https://doi.org/10.1016/j.conb.2019.06.001

1193 76. Munoz DP, Broughton JR, Goldring JE, Armstrong IT. Age-related performance of

1194  human subjects on saccadic eye movement tasks. Exp Brain Res. 1998;121(4):391–

1195  400.

1196 77. Fischer B, Ramsperger E. Human express saccades: effects of randomization and daily

1197  practice. Exp Brain Res. 1986;64(3):569–78.

1198 78. Nowak LG, Bullier J. The Timing of Information Transfer in the Visual System. In:

1199  Rockland KS, Kaas JH, Peters A, editors. Extrastriate Cortex in Primates [Internet].

1200  Boston, MA: Springer US; 1997. p. 205–41. Available from:

https://doi.org/10.1007/978-1-4757-9625-4_5

79.   Bruce CJ, Goldberg ME, Bushnell MC, Stanton GB. Primate frontal eye fields. II.

Physiological and anatomical correlates of electrically evoked eye movements. J

Neurophysiol [Internet]. 2017;54(3):714–34. Available from:

https://doi.org/10.1152/jn.1985.54.3.714

80.   Goldberg DE. Genetic algorithms in search, optimization, and machine learning. 1st

ed. Vol. 27, Choice Reviews Online. Boston, MA, USA: Addison-Wesley Longman

Publishing Co., Inc.; 2013. 27-0936-27–0936 p.

81.   Schütt HH, Rothkegel LOM, Trukenbrod HA, Reich S, Wichmann FA, Engbert R.

Likelihood-based parameter estimation and comparison of dynamical cognitive

models. Psychol Rev. 2017;124(4):505–24.

82.   Sunnåker M, Busetto AG, Numminen E, Corander J, Foll M, Dessimoz C.

Approximate Bayesian Computation. PLoS Comput Biol. 2013;9(1):1–10.

83.   Lintusaari J, Gutmann MU, Dutta R, Kaski S, Corander J. Fundamentals and recent

developments in approximate Bayesian computation. Syst Biol. 2017;66(1):e66–82.

84.   Engbert R, Trukenbrod HA, Wichmann FA. Spatial statistics and attentional dynamics

in scene viewing Simon Barthelm e. J Vis. 2015;15(1):1–17.

1218