Detection and characterization of copy number variants based on whole-genome sequencing by DNBSEQ platforms

Junhua Rao[1, *], Lihua Peng[2, *], Fang Chen[1], Hui Jiang[1], Chunyu Geng[1], Xia Zhao[1], Xin Liu[3], Xinming Liang[1, †], Feng Mu[1, 4, †]

[1] MGI, BGI-Shenzhen, Shenzhen 518083, China
[2] BGI-Shenzhen, Shenzhen 518083, China
[3] BGI-Qingdao, BGI-Shenzhen, Qingdao 266555 Shandong, China
[4] MGI-Wuhan , BGI-Shenzhen, Wuhan 430074, China

* These authors contributed equally to this work.
† Correspondence authors: liangxinming@genomics.cn (Xinming Liang) and mufeng@genomics.cn (Feng Mu)

Abstract

Background

Next-generation sequence (NGS) has rapidly developed in past years which makes whole-genome sequencing (WGS) becoming a more cost- and time-efficient choice in wide range of biological researches. We usually focus on some variant detection via WGS data, such as detection of single nucleotide polymorphism (SNP), insertion and deletion (Indel) and copy number variant (CNV), which playing an important role in many human diseases. However, the feasibility of CNV detection based on WGS by DNBSEQ[TM] platforms was unclear. We systematically analysed the genome-wide CNV detection power of DNBSEQ[TM] platforms and Illumina platforms on NA12878 with five commonly used tools, respectively.

Results

DNBSEQ[TM] platforms showed stable ability to detect slighter more CNVs on genome-wide (average 1.24-fold than Illumina platforms). Then, CNVs based on DNBSEQ[TM] platforms and Illumina platforms were evaluated with two public benchmarks of NA12878, respectively. DNBSEQ[TM] and Illumina platforms showed similar sensitivities and precisions on both two benchmarks. Further, the difference between tools for CNV detection was analyzed, and indicated the selection of tool for CNV detection could affected the CNV performance, such as count, distribution, sensitivity and precision.

Conclusion

The major contribution of this paper is providing a comprehensive guide for CNV detection based on WGS by DNBSEQ[TM] platforms for the first time.

Background

    Copy number variation (CNV) is becoming more and more important in genomic variation since first reported in 2004[1, 2]. Currently, the large structure variation, especially CNV, have been heavily studied to clearly demonstrated them playing an

[Insert Running title of <72 characters]

important role in human diseases, such as autism[3-6], schizophrenia[7],
Parkinson[8], Hirschsprung[9] and cancer[10]. In the same time, many sequencing
technologies and methods about CNV come into being. Fluorescence *in situ*
hybridization (FISH), array-based comparative genomic hybridization (array
CGH)[11, 12] and SNP array were used for CNV detection at the beginning. Later,
whole-exome sequencing (WES) and whole-genome sequencing (WGS), two
methods based on next-generation sequencing (NGS), were introduced for CNV
detection and were widely used in a large number of biological researches. Without
the limitations of specified target regions associated with hybridization or array, WES
and WGS become more advisable in CNV detection.
Illumina developed many sequencing platforms using reversible terminator
chemistry and Illumina`s sequencing by synthesis (SBS) technology, such as
HiSeq2500, HiSeq X Ten and NovaSeq6000[13]. WES and WGS sequenced on
Illumina platforms were widely used in biological research, including CNV detection.
Meanwhile, many tools were developed for CNV detection with WES[14] or
WGS[15, 16]. There are five main strategies used in tools for CNV detection: (1) read
pair (RP), (2) read depth (RD), (3) split read (SR), (4) de novo assembly (AS), and (5)
combination of approaches (CA). And each strategy has its own advantage and
limitation. RD-based tools can get accurate copy number but have no ability to detect
the breakpoints of CNV. SR-based tools can get breakpoints at base-pair resolution
but have low ability in low-complexity regions. AS-based tools could detect CNVs
without a known reference but have high-requirement of computational resources
[15]. Moreover, different tools were designed for different sample conditions. For
example, BreakDancer[17] was developed for RP strategy and was built for single
sample, HYDRA[18] based on CA strategy was suit for multiple samples and
CNVnorm[19] based on RD strategy was designed for case-control condition.
MGI Tech Co., Ltd. (MGI), a subsidiary of BGI Group and the parent company of
Complete Genomics^{TM}(CG), which is the instruments manufacturing business of BGI,
had launched several platforms using DNBSEQ^{TM} sequencing technology since 2016,
such as BGISEQ-500, DNBSEQ-G400 (MGISEQ-2000) and DNBSEQ-T7.
Compared to other existing sequencing platform, DNBSEQ^{TM} sequencing technology
combines the advantages of low amplification error rates from DNA nanoballs
(DNBs), high density patterned array and combinational probe anchor synthesis
(cPAS) sequencing technology. These advantages significantly improve sequencing
accuracy and have much lower duplication rates and reduced index hopping.
BGISEQ-500 platform showed high performance on detection of SNP and Indel on
WGS[20, 21] or WES[22]. Furthermore, DNBSEQ^{TM} platform is a good choice for
transcriptome analysis in plants[23].
Accompanied by the improvement of NGS, primarily for decrease of time and cost,
increase of data size per run and sequence quality, more CNV researches are carried
out based on WGS by NGS platforms. Many CNV detection analysis based on WGS
by Illumina platforms were evaluated, but there is no comprehensive guide for CNV
detection based on WGS by DNBSEQ^{TM} platform. Here, we presented a performance
analysis of CNV detection by analysing eight WGS demo data sequenced on two
DNBSEQ^{TM} platforms with five common tools based on four strategies. For
comparison, two Illumina platforms were used as control platforms and we indicated
that both the sensitivity and the precision of CNVs based on DNBSEQ^{TM} platforms
were consistent with those of CNVs based on Illumina platforms.

[Insert Running title of <72 characters]

Results

Selection of tools and benchmarks

We selected five tools for CNV detection from published CNV tools in three
factors: single sample pattern, widely used and keep date (Supplementary Table S1).
These five tools were designed for genome-wide CNV detection based on different
strategies: BreakDancer[17] was built on RP, CNVnator[24] was built on RD,
Pindel[25] was built on SR, DELLY[26] and LUMPY[27] were built on CA.

Moreover, two available CNV benchmarks of NA12878 were introduced for
further evaluation of CNV: 2,819 CNVs from Layer, et al. in 2014
(LUMPY_2014)[27] and 2,171 CNVs from the 1000 Genome Project WGS data in
2015 (1KG_2015)[28]. A CNV in benchmark would be considered as specific if the
proportion of its region size which overlapped with other CNVs in benchmark
reciprocally was less than a threshold. When the threshold was 90.00%, 56.05% of
CNVs in LUMPY_2014 and 32.43% of CNVs in 1KG_2015 were specific,
respectively (Supplementary Figure S1a). While the threshold was 50%, the ratio of
specific CNVs was 47.82% in LUMPY_2014 and 30.49% in 1KG_2015, respectively
(Supplementary Figure S1b). In a word, there were large proportion specific CNVs in
both LUMPY_2014 and 1KG_2015, so these two benchmarks both were used in this
study.

CNV detection and filtration

To detect CNV, we used ten WGS datasets of NA12878 sequenced on two
DNBSEQ^{TM} sequencing platforms (three datasets sequenced on BGISEQ-500, five
datasets sequenced on DNBSEQ-G400) and two Illumina sequencing platforms (one
dataset sequenced on HiSeq2500 and one dataset sequenced on NovaSeq6000),
(Supplementary Table S2, See Methods). Each dataset was down-sampled and
processed for BAM following our previous approach[20]. We got eight BAMs based
on DNBSEQ^{TM} platforms with average 31.43x and 99.02% whole genome coverage,
and two BAMs based on Illumina platforms with average 30.60x and 99.19% whole
genome coverage (Table 1). Then, these BAMs of ten datasets were used to detect
CNVs across genome by five tools: BreakDancer, CNVnator, Pindel, DELLY and
LUMPY, respectively. In total, we obtained 50 files of CNV results.

To reduce the false positives, firstly, low-quality CNVs were filtered out from raw
CNVs (See Materials and Methods). Still, high ratio ambiguous CNVs were remained
and these ambiguous CNVs might decreased the performance of CNV detection. Of
which, a CNV in each CNV result was defined as ambiguous if it had at least 1bp
overlap with other CNVs in the same CNV result, and the rest of CNVs were defined
as unambiguous CNVs. We found average 9.82% (rang from 3.75% to 20.36%)
CNVs detected by BreakDancer for ten datasets were ambiguous, while the ratio of
ambiguous CNVs was 39.43% (range from 30.97% to 49.96%) for Pindel, 19.87%
(range from 16.55% to 26.81%) for DELLY, 30.23% (range from 23.73% to 43.67%)
for LUMPY and 0% for CNVnator, respectively (Supplementary Figure S2a).
Further, we calculated the precision of ambiguous CNVs and unambiguous CNVs
with two benchmarks, respectively (See Materials and Methods). For LUMPY_2014
benchmark, the precision of unambiguous CNVs was significantly higher than that of
ambiguous CNVs (average 51.17% of unambiguous CNVs vs. average 12.83% of
ambiguous CNVs, p = 5.64e-13 with t-test, Supplementary Figure S2b). Similarly, for
1KG_2015 benchmark, we also found the precision of unambiguous CNVs was
significantly higher than ambiguous CNVs (average 39.23% vs. average 9.08%, p =
1.11e-16 with t-test, Supplementary Figure S2c). Those results indicated the negative

[Insert Running title of <72 characters]

effect of ambiguous CNVs and suggested the filtering of ambiguous CNVs to
improve performance of CNV detection.
In a word, after removing low-quality and ambiguous CNVs from raw CNVs, we
got final average 2,586 CNVs (range from 897 to 5,778) on genome-wide using five
tools for ten datasets (Figure 1). The data size, major alignment statistics and total
CNV calls using five tools were summarized in Table 1 (more statistics of CNVs were
list on Supplementary Table S3).
149
High quality CNVs produced from DNBSEQ^{TM} platforms
To evaluate the performance of CNVs based on DNBSEQ^{TM} platforms, two
Illumina platforms were used as control platforms. Firstly, we compared the number
of CNVs detected by each tool between DNBSEQ^{TM} and Illumina sequencing
datasets. We got average 1,827 (range from 1,519 to 2,329) CNVs using BreakDancer
for eight datasets from two DNBSEQ^{TM} platforms, while the CNV count was 3,523
(range from 2,209 to 5,778) using CNVnator, 4,506 (range from 4,172 to 4,924) using
Pindel, 1,838 (range from 1,624 to 2,209) using DELLY and 1,750 (range from 1,422
to 2,378) using LUMPY (Table 1). While in two datasets from two Illumina platforms,
we got 933 (897 and 968) CNVs using BreakDancer, 1,945 (1,229 and 2,660) using
CNVnator, 4,888 (4,045 and 5,730) using Pindel, 1,741 (1,709 and 1,773) using
DELLY and 1,365 (1,350 and 1,380) using LUMPY (Table 1). We found the average
CNVs from DNBSEQ^{TM} platforms was 1.96-fold of average CNVs from Illumina
platforms using BreakDancer, 1.81-fold using CNVnator, 0.92-fold using Pindel,
1.06-fold using DELLY and 1.28-fold using LUMPY (Table 1). Those results showed
that WGS data sequenced on DNBSEQ^{TM} platforms could produce more CNVs on
genome wide.
Secondly, we annotated CNVs by locating CNVs to seven genomic regions:
Upstream, Exonic, Intronic, Downstream, Intergenic, CpG island (CGI) and CGI-
shore. We found similar distribution of all 50 CNV result files (average 37.28%
CNVs based on DNBSEQ^{TM} platforms and 36.25% CNVs based on Illumina
platforms were in Intergenic, 28.32% and 31.47% in Exonic, 27.49% and 25.19% in
Intronic, 3.53% and 3.56% in Downstream, 3.38% and 3.53% in Upstream, 5.01%
and 4.53% in CGI-shore,2.85% and 2.05% in CGI, Supplementary Figure S6,
Supplementary Table S5), which suggested CNVs based on DNBSEQ^{TM} platforms
were highly consistent with Illumina platforms.
Further, we evaluated the sensitivity of CNVs based on DNBSEQ^{TM} platforms and
Illumina platforms. When compared with LUMPY_2014 benchmark, the average
sensitivity was 54.44% of CNVs based on DNBSEQ^{TM} platforms vs. 26.61% of
CNVs based on Illumina platforms using BreakDancer, while 13.36% vs. 12.73%
using CNVnator, 67.06% vs. 47.62% using Pindel, 38.64% vs. 30.08% using DELLY
and 43.52% vs. 29.57% using LUMPY when compared with LUMPY_2014 (Figure 2,
Supplementary Figure S5). And when the benchmark 1KG_2015 was used, the
average sensitivity was 51.57% vs. 30.26% using BreakDancer, 25.98% vs. 24.53%
using CNVnator, 70.47% vs. 52.85% using Pindel, 39.16% vs. 33.21% using DELLY
and 42.96% vs. 32.66% using LUMPY (Figure 2, Supplementary Figure S5). Those
results suggested that there were higher sensitivities of CNVs based on DNBSEQ^{TM}
platforms than CNVs based on Illumina platforms using different tool and different
benchmark.
Meanwhile, we evaluated the precision of CNVs between DNBSEQ^{TM} platforms
and Illumina platforms and found the average precision was 82.67% vs. 78.53% using
BreakDancer, 11.29% vs. 20.55% using CNVnator, 41.77% vs. 28.25% using Pindel,

[Insert Running title of <72 characters]

58.97% vs. 48.12% using DELLY and 69.27% vs. 60.58% using LUMPY when
compared with LUMPY_2014. While 58.26% vs. 64.22% using BreakDancer, 15.24%
vs. 26.90% using CNVnator, 33.23% vs. 23.75% using Pindel, 43.23% vs. 38.23%
using DELLY and 50.13% vs. 47.88% using LUMPY comparing with 1KG_2015.
Those results showed that with two benchmarks, there were higher precisions of
DNBSEQ[TM] platforms using Pindel, DELLY, LUMPY, but lower precisions of
DNBSEQ[TM] platforms using CNVnator.
199
Tool affects CNV detection
To investigate the characteristic of CNV detection by different tools, we firstly
compared the number or the length of CNVs detected by different tools from the same
datasets. We found that there were average 4,582 (range from 4,045 to 5,730) CNVs
from ten datasets using Pindel, which 87.01% (39,869 / 45,819) CNVs were smaller
than 1,000bp (Table 1, Supplementary Figure S3), verified that Pindel is an effective
tool for small CNVs[15]. Meanwhile, we got average 3,207 (range from 1,229
to5,778) CNVs using CNVnator, which 95.78% (30,717 / 32,072) were larger than
1,000bp (Table 1, Supplementary Figure S3), showed that CNVnator with RD-
strategy is more suitable to detect large CNVs. About BreakDancer, DELLY and
LUMPY, we got CNVs with similar average CNV count (average 1,648, 1,818 and
1,673 CNVs for BreakDancer, DELLY and LUMPY, respectively) and similar size
distributions which were major range from 100 to 5,000bp (Table 1, Supplementary
Figure S3).
Secondly, we compared the sensitivity and precision between different tools. As the
sensitivity and precision of CNVs detection described above, we found BreakDancer
showed the highest precision but unstable sensitivity, while CNVnator had both
lowest precision and sensitivity (Figure 2). Meanwhile, Pindel showed higher
sensitivity but lower precision, while DELLY and LUMPY had both balanced
sensitivity and precision (Figure 2).
Further, we studied the region distribution of CNVs across genomic from different
datasets by different tools. We found CNVnator could detected more CNVs in
Exonic, CpG Island (CGI) and CGI-shore than other tools (average 37.04% with
1,150 CNVs in Exonic, 5.43% with 198 in CGI and 8.84% with 291 in CGI-shore,
Supplementary Figure S6, Supplementary Table S5), while BreakDancer and Pindel
could detected more CNVs in Intronic and Intergenic (average 29.36% and 38.58% of
CNVs in Intronic and Intergenic using BreakDancer, 32.03% and 39.00% using
Pindel). No visible bias appeared in CNVs detected by DELLY or LUMPY.
In a word, we found similar results CNV count and length when analyzing different
datasets with the same tool but variety when analyzing the same dataset with different
tools. And distributions of length and genomics regions and performance would be
helpful for more critical selection of CNV detection tool.

Discussion

Detecting CNV using WGS sequenced on Illumina platforms were widely used and
many tools were designed based on those requirements, but the feasibility of CNV
detection on DNBSEQ[TM] platforms is unclear. This study represents a first systematic
investigation and characterization of CNV detection based on DNBSEQ[TM] platforms
and we found that both the sensitivity and the precision of CNVs based on
DNBSEQ[TM] platforms were consistent with those of CNVs based on Illumina
platforms, if not better. Furthermore, by comparing different CNV tools, we found
that there were different features of CNV detected by different tools, such as CNV

[Insert Running title of <72 characters]

count, the length region distribution across genome, CpG Island (CGI), CGI-shore,
sensitivity and precisionof CNVs, indicating that this study may help researchers to
choose tools according to different conditions.
There are some critical parameters affect the performance of CNV detection. First
parameter is the choice of CNV detection tools. Dozens of CNV detection tools were
available and designed for different sample conditions. We chose five common tools
for CNV detection on single WGS and still got obvious differences. BreakDancer
built on RP could only detect mediocre deletions influenced by the insert size of
library. CNVnator built on RD gets large CNVs with low sensitivity and precision.
Pindel build on SR would get high proportion overlapped CNVs with worse precision.
Those results indicated deficiency of current CNV detection tools and complicated
tool selection for CNV detection.
The second parameter is the lack of a high-quality benchmark. We used two public
benchmarks of NA12878 here. However, high proportion specific CNVs between
benchmarks and opposite comparisons with two benchmarks between sensitivity and
precision showed the influence of benchmark for CNV detection, and the necessity of
a high-quality benchmark.
Finally, the uncertain saturation is another parameter in evaluation performance of
CNV detection. A combination of current tools, benchmarks and data size could
confuse the saturation and performance of CNV detection.
In summary, the various performance of CNV detection on DNBSEQ^{TM} platforms
indicate the situation of CNV detection and the need for developing more efficient
and precise CNV detection and evaluation methods. CNV detection tools with high
performance and efficiency can enhance CNV researches using WGS sequenced on
NGS.

Conclusions

WGS sequenced on NGS is an efficient approach for genome researches. The
applies of WGS sequenced on Illumina platforms were widely-used for CNV
detection with numerous achievements. However, the feasibility of CNV detection on
DNBSEQ^{TM} platforms were not clear. Our results indicate CNV detection using WGS
sequenced on DNBSEQ^{TM} platforms is accurate and efficient. Our study provides a
comprehensive guide for CNV researchers using DNBSEQ^{TM} platforms with tool
selection, benchmark, performance.

Materials and Methods

Public data used.
All fastq data of NA12878 were downloaded from website: Gigadb, NCBI and
CNSA (Supplementary Table S2). All data were down-sampled for approximately
30x and processed following out previous WGS approach.
Two public benchmarks of CNVs of NA12878: 2,819 CNVs from Layer, et al. in
2014 (LUMPY_2014)[27] and 2,171 CNVs from the 1000 Genome Project WGS data
in 2015[28] were used. Both benchmarks were extracted from EXCEL and processed
with BEDtools (v2.16.2).
283
284 **CNV detection using BreakDancer**
285　　BreakDancer (ver.1.4.5) was used for CNV calling with default parameters with the
286 read-pair strategy. Raw CNVs from BreakDancer were filtered out according to: (1)

[Insert Running title of <72 characters]

287 SV type is not 'DEL', (2) confidence score < 90, (3) supporting read pairs < 3, (4) not
288 autosomal or chrX, (5) overlap a gap in the reference genome,
289
CNV detection using CNVnator
CNVnator (ver.0.3.3) was used for CNV detection using a read-depth strategy. The
optimal bin size for each data was chosen according to the authors` recommendations,
such that the ratio of the average read-depth signal to its standard deviation was
between 4 and 5 (Supplementary Table S4). Raw CNVs from CNVnator would be
filtered by those factors: (1) q0 ≥ 0.5 or q0 < 0, (2) e-val1 ≥ 0.05, (3) not autosomal or
chrX, (4) overlap a gap in the reference genome,
297
298 **CNV detection using Pindel**
299   Pindel (ver.0.2.5b9) was used with default parameters with the split read strategy.
300 Raw CNVs from Pindel were filtered with SVTYPE is not 'DEL' or
301 'DUP:TANDEM' and supporting read pairs < 3. Also, CNVs with: (1) not autosomal
302 or chrX, (2) overlap a gap in the reference genome were filtered out.
303
CNV detection using DELLY and LUMPY
Both DELLY (ver.0.7.8) and LUMPY (ver.0.2.13) were used to detect CNVs with
default parameters with a combination of approaches. CNVs from DELLY were
filtered out if: (1) SVTYPE is not 'DEL' or 'DUP', (2) FILTER is 'LowQual', (3)
supporting read pairs < 3. CNVs from LUMPY were filtered out if: (1) SVTYPE is
not 'DEL' or 'DUP', (2) PE < 3. Also, CNVs with: (1) not autosomal or chrX, (2)
overlap a gap in the reference genome were filtered out.
311
312 **Filtration of raw CNVs**
313   Firstly, a raw CNV detected by tool was filtered for removing low-quality CNV.
314 Then, a CNV was defined as ambiguous or unambiguous if it had at least 1bp overlap
315 with other CNVs in the same CNV result or not. All ambiguous CNVs were filtered
316 out for decreasing false positive.
317
Evaluation of CNVs
The evaluation of CNV compared with benchmark was processed by in-house
scripts. A CNV was considered valid if either it overlapped a single CNV in
benchmark by ≥ 50% reciprocally in size, or there existed a set of CNVs in
benchmark such that each CNV in benchmark had ≥ 50% size overlapped with the
CNV and ≥ 50% of the CNV overlapped with this set of CNVs in benchmark.
The sensitivity or precision were calculated using the following equations:
325                      $Precision = TP\_tool / SUM\_tool$
326                     $Sensitivity = TP\_benchmark / SUM\_benchmark$
327   where TP_ tool was the number of validated CNVs, SUM_tool was the total
328 number of CNVs, TP_ benchmark was the number of a set of CNVs in benchmark
329 that overlapped with validated CNVs, and SUM_ benchmark was the number of
330 CNVs in benchmark.
331
332 **Annotation of CNVs**
333   Genomic regions and CGI were downloaded from UCSC
334 (http://hgdownload.soe.ucsc.edu/goldenPath/hg19/database/). The region of 2,000bp

[Insert Running title of <72 characters]

335 frank of CGI in each direction were defined as CGI-shore. CNVs were located to any
336 of seven regions (Upstream, Exonic, Intronic, Intergenic, Downstream, CGI and CGI-
337 shore) if the midpoint of CNV region was in any regions.
338

Authors' contributions

340 J.R., L.P., X.L. and F.M. designed the project. J.R. and L.P. carried out the data
341 analysis and wrote the manuscript, with critical comments and suggestions from the
342 rest of the authors. All authors read and approved the final manuscript.

Acknowledgements

344 This research was supported by the National Key R&D Program of China
345 (2017YFC0906501), the Key R&D Program of Guangdong Province
346 (2019B020226001).
347

References

1.   Iafrate AJ, Feuk L, Rivera MN, Listewnik ML, Donahoe PK, Qi Y, Scherer
SW, Lee C: **Detection of large-scale variation in the human genome**. *Nat*
Genet 2004, **36**(9):949-951.
2.   Sebat J, Lakshmi B, Troge J, Alexander J, Young J, Lundin P, Maner S,
Massa H, Walker M, Chi M *et al*: **Large-scale copy number polymorphism**
in the human genome. *Science* 2004, **305**(5683):525-528.
3.   Levy D, Ronemus M, Yamrom B, Lee YH, Leotta A, Kendall J, Marks S,
Lakshmi B, Pai D, Ye K *et al*: **Rare de novo and transmitted copy-number**
variation in autistic spectrum disorders. *Neuron* 2011, **70**(5):886-897.
4.   Sebat J, Lakshmi B, Malhotra D, Troge J, Lese-Martin C, Walsh T, Yamrom
B, Yoon S, Krasnitz A, Kendall J *et al*: **Strong association of de novo copy**
number mutations with autism. *Science (New York, NY)* 2007,
316(5823):445-449.
5.   Pinto D, Pagnamenta AT, Klei L, Anney R, Merico D, Regan R, Conroy J,
Magalhaes TR, Correia C, Abrahams BS *et al*: **Functional impact of global**
rare copy number variation in autism spectrum disorders. *Nature* 2010,
466(7304):368-372.
6.   Chung BH, Tao VQ, Tso WW: **Copy number variation and autism: new**
insights and clinical implications. *J Formos Med Assoc* 2014, **113**(7):400-
408.
7.   Tam GW, Redon R, Carter NP, Grant SG: **The role of DNA copy number**
variation in schizophrenia. *Biol Psychiatry* 2009, **66**(11):1005-1012.
8.   Pankratz N, Dumitriu A, Hetrick KN, Sun M, Latourelle JC, Wilk JB, Halter
C, Doheny KF, Gusella JF, Nichols WC *et al*: **Copy number variation in**
familial Parkinson disease. *PLoS One* 2011, **6**(8):e20988.
9.   Jiang Q, Ho YY, Hao L, Nichols Berrios C, Chakravarti A: **Copy number**
variants in candidate genes are genetic modifiers of Hirschsprung disease.
PLoS One 2011, **6**(6):e21219.
10.   Shlien A, Malkin D: **Copy number variations and cancer**. *Genome Med*
2009, **1**(6):62.

[Insert Running title of <72 characters]

11. Pinkel D, Segraves R, Sudar D, Clark S, Poole I, Kowbel D, Collins C, Kuo
W-L, Chen C, Zhai Y *et al*: **High resolution analysis of DNA copy number**
variation using comparative genomic hybridization to microarrays.
Nature Genetics 1998, **20**:207.
12. Pinkel D, Albertson DG: **Array comparative genomic hybridization and its**
applications in cancer. *Nat Genet* 2005, **37 Suppl**:S11-17.
13. Bentley DR, Balasubramanian S, Swerdlow HP, Smith GP, Milton J, Brown
CG, Hall KP, Evers DJ, Barnes CL, Bignell HR *et al*: **Accurate whole human**
genome sequencing using reversible terminator chemistry. *Nature* 2008,
456(7218):53-59.
14. Zare F, Dow M, Monteleone N, Hosny A, Nabavi S: **An evaluation of copy**
number variation detection tools for cancer using whole exome
sequencing data. *BMC Bioinformatics* 2017, **18**(1):286.
15. Zhao M, Wang Q, Wang Q, Jia P, Zhao Z: **Computational tools for copy**
number variation (CNV) detection using next-generation sequencing
data: features and perspectives. *BMC bioinformatics* 2013, **14 Suppl**
11(Suppl 11):S1-S1.
16. Pirooznia M, Goes FS, Zandi PP: **Whole-genome CNV analysis: advances in**
computational approaches. *Front Genet* 2015, **6**:138.
17. Chen K, Wallis JW, McLellan MD, Larson DE, Kalicki JM, Pohl CS,
McGrath SD, Wendl MC, Zhang Q, Locke DP *et al*: **BreakDancer: an**
algorithm for high-resolution mapping of genomic structural variation.
Nat Methods 2009, **6**(9):677-681.
18. Quinlan AR, Clark RA, Sokolova S, Leibowitz ML, Zhang Y, Hurles ME,
Mell JC, Hall IM: **Genome-wide mapping and assembly of structural**
variant breakpoints in the mouse genome. *Genome Res* 2010, **20**(5):623-
635.
19. Gusnanto A, Wood HM, Pawitan Y, Rabbitts P, Berri S: **Correcting for**
cancer genome size and tumour cell content enables better estimation of
copy number alterations from next-generation sequence data.
Bioinformatics 2012, **28**(1):40-47.
20. Huang J, Liang X, Xuan Y, Geng C, Li Y, Lu H, Qu S, Mei X, Chen H, Yu T
et al: **A reference human genome dataset of the BGISEQ-500 sequencer**.
Gigascience 2017, **6**(5):1-9.
21. Galli A, Patch A-M, Nones K, Kazakoff SH, Newell F, Wood S, Leonard C,
Holmes O, Xu Q, Addala V *et al*: **Germline and somatic variant**
identification using BGISEQ-500 and HiSeq X Ten whole genome
sequencing. *Plos One* 2018, **13**(1).
22. Xu Y, Lin Z, Tang C, Tang Y, Cai Y, Zhong H, Wang X, Zhang W, Xu C,
Wang J *et al*: **A new massively parallel nanoball sequencing platform for**
whole exome research. *BMC Bioinformatics* 2019, **20**(1):153.
23. Zhu FY, Chen MX, Ye NH, Qiao WM, Gao B, Law WK, Tian Y, Zhang D,
Zhang D, Liu TY *et al*: **Comparative performance of the BGISEQ-500 and**
Illumina HiSeq4000 sequencing platforms for transcriptome analysis in
plants. *Plant Methods* 2018, **14**:69.
24. Abyzov A, Urban AE, Snyder M, Gerstein M: **CNVnator: an approach to**
discover, genotype, and characterize typical and atypical CNVs from
family and population genome sequencing. *Genome Res* 2011, **21**(6):974-
984.

[Insert Running title of <72 characters]

25.   Ye K, Schulz MH, Long Q, Apweiler R, Ning Z: **Pindel: a pattern growth**
approach to detect break points of large deletions and medium sized
insertions from paired-end short reads. *Bioinformatics* 2009, **25**(21):2865-
2871.
26.   Rausch T, Zichner T, Schlattl A, Stutz AM, Benes V, Korbel JO: **DELLY:**
structural variant discovery by integrated paired-end and split-read
analysis. *Bioinformatics* 2012, **28**(18):i333-i339.
27.   Layer RM, Chiang C, Quinlan AR, Hall IM: **LUMPY: a probabilistic**
framework for structural variant discovery. *Genome biology* 2014,
15(6):R84-R84.
28.   Sudmant PH, Rausch T, Gardner EJ, Handsaker RE, Abyzov A, Huddleston J,
Zhang Y, Ye K, Jun G, Fritz MH *et al*: **An integrated map of structural**
variation in 2,504 human genomes. *Nature* 2015, **526**(7571):75-81.
442

Figures

Figure 1. CIRCOS of CNVs. Circos plot depicting the landscape of CNVs on whole genome. The outermost circle shows the ideogram of chromosomes. The (i) circle displays the location of two benchmarks: LUMPY_2014 and 1KG_2015. The (ii), (iii), (iv), (v) and (vi) circle denote the distribution of CNV of ten datasets using BreakDancer, CNVnator, Pindel, DELLY and LUMPY, respectively.

Figure 2. Evaluation of CNVs. Dot plot shows the sensitivity and precision of ten datasets using five tools by compared with LUMPY_2014 (left) and 1KG_2015 (right). Ten datasets are marked with different colors, and five tools are marked with different point types.

Tables

Table 1. Statistics of data and CNVs.

Additional files

Supplementary Figure S1. Venn of benchmarks. Venn showing the number and ratio of specific CNVs in each benchmark with 90.00% threshold (a) or 50.00% threshold (b).

Supplementary Figure S2. Summary of the distribution and precision of ambiguous CNVs. (a) shows the proportion distribution of ambiguous in 50 CNV results of ten datasets using five tools after low-quality CNV filtration. The comparison of precision between ambiguous and unambiguous CNVs with LUMPY_2014 (b) and 1KG_2015 (c) is display bellow.

Supplementary Figure S3. Length distribution. The distribution of CNV length for ten datasets using five tools.

[Insert Running title of <72 characters]

475 Supplementary Figure S4. Evaluation between benchmarks. Comparison of sensitivity
476 (a) and precision (b) between two benchmarks.
477
478 Supplementary Figure S5. Evaluation between platforms. Comparison of sensitivity
479 and precision between Illumina platforms and DNBSEQ^{TM} platforms with two
480 benchmarks.
481
482 Supplementary Figure S6. Annotation of CNVs. Histogram shows the location of
483 CVNs in genomic regions, CGI and CGI-shore. CpG Island: CGI. CpG island-shore:
484 CGI-shore.
485
486 Supplementary Table S1. Tools for CNV detection.
487
488 Supplementary Table S2. Demo data.
489
490 Supplementary Table S3. Statistics of CNVs.
491
492 Supplementary Table S4. Bin size in CNVnator.
493
494 Supplementary Table S5. Annotation of CNVs.
495
496

[Insert Running title of <72 characters]

(i)   Benchmark
(ii)   BreakDancer
(iii)   CNVnator
(iv)   Pindel
(v)   DELLY
(vi)   LUMPY

a   LUMPY_2014
b   1KG_2015

I   BGISEQ-500_PE100
II   BGISEQ-500_PE150-1
III   BGISEQ-500_PE150-2
IV   DNBSEQ-G400_PE100
V   DNBSEQ-G400_PE150_PCR-1
VI   DNBSEQ-G400_PE150_PCR-2
VII   DNBSEQ-G400_PE150_PCRfree-1
VIII   DNBSEQ-G400_PE150_PCRfree-2
IX   HiSeq2500_PE150
X   NovaSeq6000_PE150

deletion
duplication

	Sequencing strategy	Clean bases (G)	Average sequencing	Mapping rate (%)	Duplicate rate (%)	Coverage (%)	BreakDancer	CNVnator	#CNV Pindel	DELLY	LUMPY
BGISEQ-500_PE100	PE100	113.6	37.44	99.22	2.45	99.12	2,329	5,778	4,924	1,904	2,378
BGISEQ-500_PE150-1	PE150	94.15	29.63	99.59	6.90	98.99	1,646	3,617	4,463	1,624	1,422
BGISEQ-500_PE150-2	PE150	94.20	29.51	99.57	7.49	98.97	2,265	4,241	4,310	2,209	2,202
DNBSEQ-G400_PE100	PE100	94.11	31.09	99.56	2.22	99.09	2,160	4,354	4,688	1,745	1,889
DNBSEQ-G400_PE150_PCR-1	PE150	94.11	30.83	99.54	2.19	98.99	1,576	2,234	4,577	1,902	1,609
DNBSEQ-G400_PE150_PCR-2	PE150	94.11	30.77	99.55	2.24	98.99	1,600	2,209	4,689	1,900	1,533
DNBSEQ-G400_PE150_PCRfree-1	PE150	94.11	31.13	99.60	1.24	98.98	1,519	2,890	4,221	1,705	1,463
DNBSEQ-G400_PE150_PCRfree-2	PE150	94.11	31.07	99.60	1.25	98.99	1,523	2,860	4,172	1,713	1,505
HiSeq2500_PE150	PE150	96.28	31.91	99.31	1.46	99.00	968	2,660	4,045	1,709	1,380
NovaSeq6000_PE150	PE150	93.69	29.30	99.06	5.91	99.06	897	1,229	5,730	1,773	1,350

Note: Pair-end (PE).