1   # Landmark-Based Navigation Instructions Improve
2   # Incidental Spatial Learning in Real-Life Environments
3

Anna Wunderlich[1] and Klaus Gramann[1,2,3]

Berlin Institute of Technology

Anna Wunderlich,[1] (0000-0003-2378-1164) and Klaus Gramann[1,2,3] (0000-0003-2673-1832)

[1] Technische Universität Berlin, FG Biopsychologie und Neuroergonomie, Berlin 10623,

Germany

[2] School of Computer Science, University of Technology Sydney, Sydney 2007, Australia

[3] Center for Advanced Neurological Engineering, University of California, San Diego 92093,

CA, USA

Running head: SPATIAL LEARNING WITH NAVIGATION ASSISTANCE

Manuscript type: Extended Multi-Phase Study

Word count: 7312

Acknowledgments: This research was supported by a stipend from the Stiftung der Deutschen

Wirtschaft to AW. We give thanks to André Brandewiede, Anja Marckwardt, as well as the

students in the neuroergonomics project course of the summer 2017 term for helping to

prepare and conduct the experiments.

The authors declare that there is no conflict of interest regarding the publication of this paper.

Correspondence should be addressed to Anna Wunderlich; anna.wunderlich@tu-berlin.de

Abstract

Background. The repeated use of navigation assistance systems leads to decreased

spatial orienting abilities. Previous studies demonstrated that augmentation of landmarks

using auditory navigation instructions can improve incidental spatial learning when driving a

single route through an unfamiliar environment.

Objective. Based on these results, two experiments were conducted to investigate the

generalizability of both the impairment of spatial knowledge acquisition by standard

navigation instructions and the positive impact on incidental spatial learning using landmark

augmentation in auditory navigation instructions.

Method. In a first experiment, spatial knowledge was tested after watching a video of

navigation of a real-world urban route. A second experiment investigated incidental spatial

knowledge acquisition when participants actively navigated through the same real-world,

urban environment.

Results. Both experiments demonstrated better cued-recall performance for

participants navigating with landmark-based auditory navigation instructions as compared to

standard instructions. Notably, standard instructions were associated with reduced learning of

landmarks at navigation relevant intersections while the acquired knowledge about landmarks

alongside straight segments as well as the recognition of novel landmarks was comparable

across navigation conditions.

Conclusion. The results replicated an improved spatial knowledge acquisition for

landmark-based navigation instructions emphasizing the positive impact of auditory

landmark augmentation on incidental spatial learning and its generalizability to real-life

settings.

Application. This research is paving the way for navigation assistants that, instead of

impairing orienting abilities, incidentally foster spatial learning during every-day navigation.

Keywords: automation, spatial knowledge acquisition, real-world, cued-recall

Précis: Two experiments replicated the suppression of incidental spatial learning by standard

navigation instructions as well as its improvement by landmark augmentation in auditory

navigation instructions. The experiments testing varying degrees of realism revealed that this

effect can be generalized and applied to real-life settings.

Introduction

Navigation aids have become common everyday tools (Axon, Speake, & Crawford,

2012; Kalin & Frith, 2016; Kitchin & Dodge, 2007). They provide visual as well as auditory

guidance as a support during wayfinding through known and unknown environments (Allen,

1999). With the use of navigation aids, wayfinding evolved from analog 2D map-based tasks

into digitally assisted instruction following tasks. Accordingly, a recent survey revealed a

stronger trend towards route-based wayfinding strategies as compared to twenty years ago,

along with an increasing inability to use wayfinding strategies among younger adults (Ulrich,

Grill, & Flanagin, 2019). This trend towards route-based wayfinding strategies is likely

fostered by the increased use of navigation assistance systems providing turn-by-turn

instructions and biasing a route perspective (Gardony, Brunyé, Mahoney, & Taylor, 2013).

Several studies investigated the user's interaction with navigation aids in order to

describe and understand the underlying cognitive processes. One finding was that the use of

automated assistance systems was associated with divided attention between the movement

related task and the assisted navigation (Fenech, Drews, & Bakdash, 2010; Gardony et al.,

2013; Gardony, Brunyé, & Taylor, 2015). This resource allocation conflict increases the

reliance on the navigation assistant in order to reduce attentional demands (Baus, Kray, &

Krüger, 2001; Klippel, Hirtl, & Davies, 2010; Parush, Ahuvia, & Erev, 2007) leading to an

automation bias (Lin, Kuehl, Schöning, & Hecht, 2017). The users tend to hand over the

decision-making to the automated system (Bakdash, Linkenauger, & Proffitt, 2008; Fenech et

al., 2010; Parush et al., 2007). They follow the system instructions without checking other

available information (Mosier, Skitka, Burdick, & Heers, 1996; Parasuraman, 2000) and this

overreliance leads to a decrease in processing the surrounding environment (Leshed, Velden,

Rieger, Kot, & Sengers, 2008; Hirtle & Raubal, 2013; Münzer, Zimmer, Schwalm, Baus &

Aslan, 2006). With repeated use of navigation assistance systems, the users' ability to

autonomously solve the navigation task decreases, revealing a deskilling of orienting abilities

(Bertel, Dressel, Kohlberg, & von Jan, 2017; Münzer, Zimmer, & Baus, 2012; Parush et al.,

2007).

As a consequence, people are more likely to get lost because of their inability to

orient using their own sense of direction when the navigation aid is no longer reliable (e.g.,

because of system errors or GPS signal loss). However, even when the system works

properly, the risk of getting lost remains by an inadequate application of or overreliance on

navigation assistance systems. Errors during navigation can have more or less severe

consequences ranging from time loss and stress to potential disaster when orientation fails in

extreme environments (Aporta et al., 2005). Lin and colleagues (2017) collected a corpus of

158 so called "Death by GPS" incidents published in the English news between 2010 and

2017. Only those reports were chosen that contained incidents caused by an improper use of

navigation assistance systems. They found an unusual high number of single-car crashes

(32%) and that most of the "Death by GPS" incidents happened in an unknown environment

(78%). These data point to a relative increase of rare accidents involving no other road users

demonstrating that the use of automated assistive technologies can negatively impact the

primary driving task.

To maintain spatial abilities while using navigation assistance systems, a variety of

methods can be used (Giannopoulos, Kiefer, & Raubal, 2015, Gramann, Hoepner, Karrer-

Gauss, 2017). One promising approach to support navigation without endangering the users'

safety is the inclusion of environmental information about salient objects, so called

landmarks (Evans, Smith, & Pezdek, 1982), in the navigation instructions (Li, Fuest, &

Schwering, 2014; May, Ross, Bayer & Burnett, 2001; Raubal & Winter, 2002). Studying

pedestrian navigation in the real world showed that visual augmentation of landmarks in the

navigated environment enhances spatial knowledge acquisition (Brügger, Richter, &

Fabrikant, 2019; Huang, Schmidt, & Gartner, 2012; Münzer et al. 2006). Furthermore, it was

shown that spatial knowledge can be incidentally acquired during navigation to a similar

level as intentional learning (van Asselen, Fritschy, & Postma, 2006). These previous studies

used visual tools only to improve spatial knowledge acquisition. Such tools require the same

visual resources for processing the navigation instructions that are also necessary for the

primary task. Compared to visual augmentation methods, acoustic navigation instructions

have the advantage to be safer as they do not interfere with visual attention needed to observe

the ongoing traffic (May & Ross, 2006). Ross, May, and Thompson (2004) investigated

landmark-based auditory navigation instructions regarding their usability for pedestrians. The

authors demonstrated the effectiveness of landmark-based auditory instructions leading to

less navigation errors and increased navigator's confidence during navigation, as compared to

a control group. While the study by Ross and colleagues demonstrated improved navigation

performance, the authors did not test for the impact of auditory landmark information on

spatial learning.

120   To test whether auditory landmark-based navigation instructions lead to spatial

knowledge acquisition while improving navigation, Gramann and colleagues (2017)

augmented landmarks at intersections in a virtual driving task. Landmark augmentation was

implemented by naming landmarks at navigation relevant intersections and providing

additional information about them. This resulted in incidentally learning of spatial

information of the environment (Gramann et al., 2017). Improved spatial knowledge

acquisition with landmark-based navigation instructions was observable even when tested

three weeks after a single exposure to an unfamiliar environment (Wunderlich & Gramann,

2018). It was further found to be associated with changes in brain activity likely reflecting

increased information recollection during cued-recall of landmark- and route-knowledge

about the navigated environment (Wunderlich & Gramann, 2018). Landmarks and routes are

the essential elements of spatial representations and necessary for conceiving spatial relations

(Siegel & White, 1975). Augmenting landmarks in auditory navigation instructions might

thus be a promising way to foster spatial knowledge acquisition during use of navigation

assistance systems. The results of both virtual driving studies showed a significantly

improved recognition performance for navigation relevant landmarks when navigators

received landmark-based instructions as compared to standard instructions known from

commercial navigation aids. Moreover, when using standard navigation instructions,

recognition of relevant landmarks was reduced compared to both navigation irrelevant

(salient objects in between navigation relevant intersections) and novel landmarks (landmarks

that were not part of the previously navigated route).

These results point to a possible suppression of spatial knowledge acquisition as

learning of the environment was reduced when standard navigation instructions were given

compared to segments without navigation instructions. It seemed like spatial learning was

suppressed by standard instructions that guided the users' attention to the intersection rather

than to the environment around the intersection. In comparison, landmark-based instructions

revealed better recognition performance for relevant landmarks with the other landmark

categories remaining at comparably high levels. These results support the assumption that the

inclusion of landmark information in navigation instructions was associated with directing

the users' attention towards environmental features leading to an incidental spatial learning of

these features. However, the cued-recall performance for relevant landmarks was not

improved beyond the performance for navigation irrelevant and novel landmarks indicating

that a learning suppression was overcome rather than that additional spatial learning took

place (Gramann et al., 2017). Importantly, overcoming the spatial learning suppression with

landmark-based instructions did not affect the subjective mental load or driving behavior

(Gramann et al., 2017; Wunderlich & Gramann, 2018).

In the previous studies using landmark-based navigation instructions, it was not tested

to what extent incidental spatial learning was fostered by the landmark reference itself or by

the additional information that was provided. The two versions of landmark-based navigation

instructions used in Gramann and colleagues (2017) and Wunderlich and Gramann (2018)

included both the name of a landmark at the intersection and additional information. In one

case this information was redundant, such as, "Turn right at the bookstore. There, you can

buy books." In the other case, it included a reference to one of the participant's personal

interests, like, "Turn right at the bookstore. There, you can buy books of J.R.R. Tolkien" in

case J.R.R. Tolkien was the favorite author of the tested participant. These personal-reference

instructions had been individualized for each participant. By using only these two conditions,

however, it was not possible to differentiate between the personal-reference or the additional

more detailed information in the instructions as the cause of the spatial knowledge acquisition

effect.

To answer this question, the studies reported in this paper introduced a *long*

instruction condition that augmented landmarks at navigation relevant intersections and

provided additional semantic information about the landmark. This instruction contained

more semantic information than the previously used redundant description of the landmark,

but had no relation to the personal interests of the participants ("Turn right at the bookstore.

There, public readings take place every week."). Because previous studies revealed improved

spatial learning for any landmark-based navigation instructions, we also introduced a *short*

instruction condition to test whether simply naming a landmark without additional

information might already foster spatial knowledge acquisition ("Turn right at the

bookstore."). This condition was similar to the landmark-based navigation instructions in the

usability study by Ross and colleagues (2004). In summary, the following experiments used

both short and long landmark-based navigation instructions in comparison to a control group.

The control group received standard auditory navigation instructions as known from

commercial navigation aids (e.g., "At the next intersection turn right."). None of the

conditions received visual guidance alongside the auditory instructions.

Besides investigating the amount of information in the landmark-based navigation

instructions, it remained an open question whether an improved incidental spatial learning in

virtual driving simulations can be generalized to more realistic environments. The previous

experiments took place in a highly controlled and restricted driving simulator setup

(Gramann et al., 2017; Wunderlich & Gramann, 2018). This artificial scenario lacked

naturalistic self-motion cues, other traffic participants, and natural visual information. Here,

we report two experiments that were conducted to investigate the potential impact of more

realistic navigation scenarios on spatial knowledge acquisition. In Experiment 1, the

navigation paradigm was transferred to a pedestrian context using real-world visuals. An

interactive movie was created showing a pedestrian's first-person perspective while

navigating through Berlin, Germany. The video was a realistic representation of city

navigation while allowing control of stimulus material for all participants. Experiment 2 then

investigated spatial knowledge acquisition during real-world assisted pedestrian navigation

through the city of Berlin.

We expected to observe the same impact of landmark-based navigation instructions

on incidental spatial knowledge acquisition in both the controlled video scenario as well as

the real-world setting. Following up on the previous findings, we analyzed incidental spatial

knowledge acquisition during assisted navigation with two main hypotheses. The *suppression*

hypothesis postulates that standard navigation instructions lead to a suppression of spatial

knowledge acquisition for landmarks at intersections (navigation relevant landmarks) as

reflected in reduced cued-recall performance compared to navigation irrelevant and novel

landmarks. The *learning hypothesis* posits that landmark-based navigation instructions

overcome this suppression effect and improve spatial knowledge acquisition at navigation

relevant intersections, with participants receiving long outperforming those receiving short

navigation instructions. To investigate the incidentally acquired spatial knowledge, the

performance in a cued recall task was analyzed using the percentage of correct responses

regarding each landmark type as dependent variable. This measure represents a combination

of landmark and route knowledge of the navigated environment, because correct responses

require associative memory of the street outline as well as the respective route direction. As

the cued-recall task was used in both experiments and had the same structure as the landmark

recognition task used in previous experiments, it was the only task allowing for a comparison

across experiments and testing the generalizability of the previous findings. To control for

individual differences in spatial abilities, the Santa Barbara Sense of Direction test (SBSOD,

Hegarty, Richardson, Montello, Lovelace & Subbiah, 2003) was applied in all experiments to

be used as covariate in case of significant correlation of the subjective sense of direction

measure with landmark recognition performance in the cued-recall test.

Experiment 1

222   The aim of Experiment 1 was to test landmark-based navigation instructions in a more

223 realistic environment providing real-world visuals. To this end, an interactive video was

224 created showing a pedestrian's first-person perspective during real-world navigation through

225 an urban environment.

Method

Participants. Forty-three participants assigned to three different navigation instruction

groups took part in this experiment. The recorded sample included 22 women and gender was

balanced across experimental conditions (14 participants in standard, 7 females; 14 in short, 7

females; and 15 in the long instruction condition, 8 females). The age ranged from 19 to 34

years (M = 26.2 years, SD = 2.75 years). Participants were recruited through an existing

database or personal contact and were reimbursed monetarily or received course credit. To

assure that participants were unfamiliar with the route, we used an online questionnaire prior

to the experiment. They were asked to rank up to five metro stations of Berlin according to

their frequency of personal use. If one of the stations was close to the route, the participant

was excluded from the experiment. All participants had normal or corrected to normal vision

and gave written informed consent prior to the study. The study was approved by the local

ethics committee.

Procedure. Following the previous approach (Gramann et al., 2017, Wunderlich &

Gramann, 2018), the experiments consisted of two parts. The first part was an assisted

navigation phase where participants followed auditory navigation instructions to navigate

along a predefined route. In the second part, participants had to solve different tasks testing

their spatial knowledge about the navigated environment. Participants were not informed

prior to the second part that they will be tested on the navigated environment allowing for

investigation of incidental spatial knowledge acquisition. Experiment 1 took place in a

controlled laboratory environment (Figure 1a) and lasted 2 hours and 40 minutes. Participants

were seated in front of a display and interacted with the video scenario by using the keypad in

front of them. Participants were equipped with electroencephalography (EEG; BrainAmps,

Brain Products, Gilching, Germany) and eye movements were recorded with a desktop-based

eye-tracker (SMI RED 5, SensoMotoric Instruments, Teltow, Germany).

Figure 1: a) Interactive video setup of Experiment 1. The screen in front of the participant

was displaying the video and was equipped with the eye-tracker, a second screen was for

EEG-data and the laptop for eye-tracking data collection. b) Video snapshot at a navigation

relevant landmark ("public restroom") as used in the cued-recall task (pictures were

presented in color).

Navigation phase. Participants watched a video showing real world recordings

complemented by auditory navigation instructions. The task was interactive as the video

stopped at intersections and participants had to respond according to the navigation

instructions. The video did not commence without a response. Some route characteristics

changed with the paradigm shift from simulated driving to walking through an urban

environment. Based on changes in locomotion speed, the definition of navigation relevant

landmarks was adapted. Hitherto, only landmarks at intersections with route direction

changes were defined as navigation relevant. In the pedestrian scenario, all landmarks at

intersections were defined as navigation relevant even in case no route direction change was

experienced. This was done because landmarks along the route can serve as confirmation and

improve user confidence in pedestrian navigation assistance (May Ross, Bayer, &

Tarkiainen, 2003; Rousell & Zipf, 2017). As a consequence, navigation instructions were

provided prior to all intersections. In the modified navigation instruction conditions, these

included information about the respective navigation relevant landmark.

The video content was recorded with a GoPro Hero 4 (GoPro. Inc., San Mateo, USA)

from a pedestrians' perspective (see Figure 1b). The cameraperson was continuously

recording while walking a predefined route. During the video, various other road users were

visible. Removing the real-world audio allowed for high realism of the visuals without

considering other auditory stimuli than the auditory navigation instructions. The video was

accelerated by 1.1 times the original speed to shorten the navigation task to approximately 35

minutes. The displayed route through Charlottenburg, Berlin in Germany, was 3.7 km long

and passed twenty intersections containing 14 direction changes. Auditory navigation

instructions were presented via loudspeakers prior to each intersection. When arriving at an

intersection, the movie stopped and a participants' response according to the instructed

direction was required. Participants indicated the navigation directions using the left (turn

left), up (go straight), or right (turn right) arrow key. This interaction was implemented to

ensure the participants' attention to the route. Irrespective of whether the response was

correct or not, pressing one of the response keys started the video again. The stimulus

material was identical for all participants and only the navigation instructions differed

between the groups. Besides the standard navigation instructions, the short and long

landmark-based navigation instructions were tested. After video navigation, the subjective

rating of navigation task-related load was measured using the NASA-RTLX (National

Aeronautics and Space Administration - raw task load index; Hart, 2006; Hart, & Staveland,

1988). In addition, participants answered questions about route familiarity and acceptance of

the modified navigation instructions.

Test phase. The test phase followed the navigation phase after a short break (as in

Gramann et al., 2017). This way, the EEG cap could remain on the participants' head and the

electrode positions were identical for both phases. The second part consisted of a sketch map

drawing, the cued-recall task, the Perspective Taking/Spatial Orientation Task (PTSOT;

Hegarty & Waller, 2004), and the circle task (triangular pointing task). Only the cued-recall

task was reported in detail here as it was the only task conducted in both current experiments

as well as in the previous studies. This way, its results allowed conclusions about the

generalizability of the impact of landmark-based navigation instructions for different

navigation contexts.

The cued-recall task combined a simple landmark recognition with a route direction

response comparable to Huang and colleagues (2012). The task of the participant was to

correctly recognize pictures taken from the navigated environment as being part of or not

being part of the previously navigated route. In case of recognizing a landmark, participants

responded according to the respective route direction at the landmark location. To capture the

overall acquired spatial knowledge, we used three landmark types which were categorized

according to their relevance for navigation: a) *navigation relevant landmarks* were located at

intersections and referenced in the modified navigation instructions while b) *navigation*

irrelevant landmarks were located at straight route segments. In addition, c) *novel landmarks*

were presented, which were from the same environment, but had not been encountered during

the navigation phase. Thus, relevant and irrelevant landmarks should be indicated as known

landmarks while novel landmarks should be identified as unknown.

Twenty pictures of each landmark type were randomized and presented one by one on

a desktop screen. Pictures of relevant and irrelevant landmarks were screenshot from the

navigation video. As novel landmarks served screenshots from additional video material

taken the same day as the navigation video. All landmarks were presented from the

pedestrians' point of view including their immediate surroundings (see Figure 1b). Each

landmark was displayed for 3 seconds and then replaced by a figure presenting four arrow

keys indicating the response options. Participants were instructed to press the right/left arrow

key, in case the route had turned right/left at the displayed landmark, respectively. In case the

route had proceeded straight ahead, the required response was to press the up-arrow key. In

case the landmark had not been encountered previously, participants were asked to press the

down-arrow key. The relative location of navigation relevant landmarks at intersections (left,

right, before or after the intersection) did not provide any indication for the respective turning

directions. Following each response, participants were asked how confident they were about

the given answer on a six-point scale ranging from '1 - very sure' to '6 - I did not know'. For

the analysis of event-related activity from the ongoing EEG, the set of landmarks was

randomized and presented five times to reach a sufficient number of epochs per landmark

type. For the present paper, only the responses to the first presentation of each landmark

picture are reported as these represent the unbiased responses of participants.

Questionnaire data about demographic characteristics, individual navigation and

learning habits, and spatial abilities were collected at the end of the experiment. For the

subjective individual orienting ability, the Santa Barbara Sense of Direction (SBSOD,

Hegarty et al., 2003) was used.

Statistical analysis. Statistical analysis was performed using the statistics software

SPSS (International Business Machines Corporation (IBM) Analytics, Armonk, USA). A

mixed measure analysis of variance (ANOVA) was computed with the between-subject

factor navigation instruction condition (standard, short, long) and the within-subject factor

landmark type (relevant, irrelevant, novel). In case of violation of the sphericity, the

Greenhouse-Geisser corrected p-values and degrees of freedom were reported (Rasch, Friese,

Hofmann & Naumann, 2010). As an indicator of effect size, partial eta squared was

calculated. To test the hypotheses of suppression and learning, post-hoc comparisons were

computed comparing all instruction conditions within each landmark type (nine comparisons)

as well as comparing all landmark types within each navigation instruction condition (nine

comparisons). The resulting p-values were Bonferroni corrected by dividing the p-value by

the total number of eighteen comparisons. Spearman correlation of the SBSOD score and the

percentage of correct responses to each landmark type was computed to control for a

potential covariance of subjective spatial abilities and performance.

Results

The Spearman correlation of the SBSOD score with the percentage of correct responses to

each landmark type was not significant ($\rho\text{'s} < .176$, $p\text{'s} > .262$). Thus, the SBSOD score was

not included as covariate in the ANOVA.

The group-boxplots and individual measures for the percentage of correct recognized

landmarks and associated directions in the cued-recall task can be seen in Figure 2. The

results of the ANOVA revealed a significant main effect of navigation instruction condition

($F_{(2,40)} = 4.33$, $p = .020$, $\eta_p^2 = .178$). Post-hoc comparisons revealed that the performance in

the long navigation instruction condition was better ($M = 71.2$, $SE = 2.28$) than in the short

instruction condition ($M = 62.3$, $SE = 2.36$, $p = .031$). The difference between long and

standard instructions ($M = 63.6$, $SE = 2.36$) showed a trend towards significance ($p = .074$).

The overall performance of standard and short instructions showed no difference ($p > .999$).

The a main effect of landmark type was also significant ($F_{(2,80)} = 18.1$, $p < .001$,

$\eta_p^2 = .312$). Post-hoc comparisons revealed that the cued-recall performance was lower for

navigation relevant ($M = 55.4$, $SE = 2.11$) compared to navigation irrelevant ($M = 73.2$,

$SE = 2.06$, $p < .001$) and novel landmarks ($M = 68.9$, $SE = 2.45$, $p = .001$). Novel and

irrelevant landmarks revealed comparable recognition performance ($p = .571$).

Finally, the interaction of both factors showed a trend towards significance

($F_{(4,80)} = 1.75$, $p = .148$, $\eta_p^2 = .080$).

To address the suppression hypothesis, landmark types were compared for each

navigation instruction condition. The results for the standard instructions revealed

significantly lower recognition performance for relevant ($M = 46.8$, $SE = 3.70$) as compared

to irrelevant ($M = 75.4$, $SE = 3.61$, $p < .001$) and novel landmarks ($M = 68.6$, $SE = 4.36$,

$p = .002$). In the short navigation instruction condition, recognition performance for relevant

landmarks ($M = 54.3$, $SE = 3.70$) was significantly lower than for irrelevant landmarks

($M = 68.6$, $SE = 3.61$, $p = .014$). When contrasting landmark types in the long navigation

instruction condition, the recognition performance for relevant ($M = 65.0$, $SE = 3.58$)

approached recognition levels of irrelevant landmarks ($M = 75.7$, $SE = 3.49$, $p = .096$).

Contrasting the performance differences regarding the learning hypothesis, the

percentage of correct responses for one landmark type was compared between navigation

instruction conditions. The recognition rates for navigation relevant landmarks revealed that

long instructions ($M = 65.0$, $SE = 3.58$) outperformed standard instructions ($M = 46.8$,

Figure 2: Boxplots and single subject performance scores in the first repetition of the cued-

recall task of Experiment 1 with twenty landmarks per landmark category (relevant,

irrelevant, novel). For mean correct responses, 100% equals the correct response to twenty

landmarks of the respective category. The performance measure could reach twenty different

values with a step-width of 5%. Whiskers display up to 1.5 standard deviations (SDs) from

the mean. Small dots represent individual values above the whiskers.

SE = 3.70, *p* = .006), but not short navigation instructions (*M* = 54.3, SE = 3.70, *p* = .262).

All other post-hoc contrasts were non-significant (all *p*-values > .498).

Discussion

In Experiment 1, a paradigm shift from simulated driving to video-based pedestrian

navigation was realized. This allowed us to test the incidental spatial learning effect of

landmark-based navigation instructions in a more realistic setting. Two different landmark-

based navigation instructions (short and long) were compared with a control group.

The performance data for all subgroups was in the same range as the performance

data of previous experiments (Gramann et al., 2017, Wunderlich & Gramann, 2018). And the

results revealed the positive impact of modified navigation instructions on spatial learning

during navigation. It can thus be concluded that the replication was successful even though

new modifications of landmark-based navigation instructions were introduced. In addition,

the navigation context changed from simulated driving to an interactive video of pedestrian

navigation that showed real-world visuals and included other traffic participants. This is

remarkable and demonstrates that landmark-based navigation instructions lead to incidental

spatial learning and that this impact is of a more general nature and context-independent. The

cued-recall performance supports the assumption that incidental spatial learning at navigation

relevant intersections was suppressed by standard navigation instructions and that this

suppression was alleviated by landmark-based navigation instructions. This strengthens the

reliability and generalizability of the effect as it was also observed in a more realistic

environment using a different locomotion mode.

In more detail, the post-hoc comparisons of the main effect navigation instruction

showed a better performance for the long as compared to the short navigation instructions

across all landmark types. But there was no difference between the short navigation

instruction and the standard instructions. This result was unexpected as we had assumed that

performance for short would be better than for standard instructions. These results point to a

difference in landmark learning based on the specifics of the landmark-based instructions. A

short reference to a landmark seems to be less effective with regards to incidental spatial

learning than an instruction providing additional landmark information. There was only a

strong trend (p = .07) for better recognition performance with long landmark-based

instructions compared to standard instructions. This can be explained by the very good

performance for navigation irrelevant and novel landmarks in the standard instruction

condition.

Regarding the factor landmark type, the least spatial knowledge was acquired for

landmarks at navigation relevant intersections. As the instructions were received during these

more difficult navigation phases, for example right before the turning manoeuver, less

attentional resources were available for processing the surroundings. Announcing the

intersection in the standard instructions seems to have shifted attention towards the

intersection instead of the surroundings. This result replicates previous findings and further

confirms the suppression hypothesis. Together with improved performance for landmark-

based instructions approaching the performance level of other landmark types, this lends

further support to the assumption that landmark-based instructions only overcome a

suppression of spatial knowledge acquisition instead of fostering additional spatial learning.

The post-hoc contrasts confirmed that long-modified navigation instructions were associated

with the best cued-recall performance followed by short and standard instructions. The

difference in performance for relevant as compared to irrelevant and novel landmarks

decreased accordingly, revealing an alleviation of the learning suppression by landmark-

based navigation instructions.

In summary in experiment 1, a video-based navigation paradigm replicated previous

results demonstrating improved spatial knowledge acquisition at navigation relevant

intersections when using navigation instructions with additional information about a

landmark. This first replication, however, still lacked natural movement, the accompanying

kinesthetic and proprioceptive information during real pedestrian navigation that might

further support learning of the spatial surroundings (Gramann, 2013). To allow for

multimodal information integration of all senses involved in natural navigation through the

real world, Experiment 2 implemented a real-world navigation task with pedestrians actively

navigating through Berlin.

446   **Experiment 2**

From the first to the second experiment, the experimental setting was changed from a

stationary laboratory setup to a real-world setting allowing free movement of navigators. The

second Experiment aimed at testing the full ecological validity of the previously

demonstrated incidental spatial learning effects during the use of modified navigation

instructions in an unrestricted, real-life setting.

Method

Participants. In this experiment, 41 participants were recorded during real-world

navigation. Due to technical issues, five of the participants had to be removed from the

database. The remaining 36 participants (21 females) were aged between 20 and 34 years

($M = 26.6$ years, $SD = 3.03$ years). Every experimental condition consisted of twelve

participants with gender being balanced across conditions (standard instructions: 8 female;

short instructions: 6 female; long instructions: 7 female participants). Participants were

recruited through an existing database or personal contact and were reimbursed monetarily or

received course credit. All had normal or corrected to normal vision and gave written

informed consent prior to the study. The study was approved by the local ethics committee.

462   *Procedure.* The experiment was scheduled in two sessions separated by a break of

463 two weeks. Both experimental sessions lasted in total about 3 hours and 30 minutes. In the

464 first part, participants navigated along a predefined route through an urban environment, the

465 district of Charlottenburg, Berlin in Germany. The route overlapped with the route segment

466 presented as video in Experiment 1. Each participant was guided by auditory navigation

467 instructions. There were three groups of participants including a control group receiving

468 standard navigation instructions. The landmark-based navigation instruction groups were

469 either receiving the short, or long landmark-based navigation instructions. After a break of

470 two-weeks (13 to 17 days, $M = 14.1$ days, $SD = 0.73$ days), the participants were invited to

471 return and to solve spatial tasks in a laboratory setting. Participants were informed about the

472 second session without providing information about its content. The relatively long break

473 between navigation and test phase enabled us to investigate the generalizability of the

474 previously reported long-term impact of landmark based navigation instructions on spatial

475 knowledge acquisition (Wunderlich & Gramann, 2018). Importantly, and in contrast to

476 Wunderlich and Gramann (2018), participants walked through a city environment during the

477 navigation phase and were also moving through the same city during the break. Thus, they

478 were experiencing a similar environment which could interfere with spatial knowledge about

479 the experimental route. This way, the experiment represents an ecologically valid case of

480 long-term spatial knowledge acquisition during assisted navigation.

481   *Navigation phase.* An experimenter met each participant at a train station close to the

482 starting point of the route. There, the participant was informed about the upcoming

483 navigation task. They were instructed to follow the auditory navigation instructions, to pay

484 attention to the traffic while crossing streets, and to stop in case they did not know which

485 direction to proceed. While navigating the route, an experimenter was walking in the vicinity

486 of the participant to intervene in case of hazards and ensure that the participant would follow

the correct route (see Figure 3a). The experimenter also manually triggered the auditory

navigation instructions at predefined trigger points alongside the route using a browser-based

application on a mobile phone. The auditory navigation instructions were provided to both,

the participant and the experimenter, via Bluetooth headphones (Cheetah Sport In-Ear,

Mpow, Hong Kong, China). The route consisted of 40 intersections including 22 direction

changes. Participants arrived at the end of the route after approximately 60 minutes.

Following the navigation phase, navigators provided their subjective rating of the

navigation task-related load as assessed using the NASA-RTLX (Hart, 2006; Hart, &

Staveland, 1988). In addition, participants answered questions about route familiarity and

acceptance of the modified navigation instructions.

Test phase. During the spatial test session in a controlled laboratory setting, the cued-

recall task and a video-turn task were recorded. During the two tasks, participants were

equipped with EEG (BrainAmps, Brain Products, Gilching, Germany) and seated at a table in

front of a computer screen and keyboard. Analogous to the cued-recall task of Experiment 1,

120 landmark pictures were presented including forty pictures of each landmark type.

Pictures of landmarks displayed their surroundings but in contrast to Experiment 1,

landmarks were presented in a front view that deviated from the first-person perspective

during walking (see Figure 3b compared to Figure 1b). Novel landmark pictures were

photographs taken in a similar way and similar weather conditions in a neighboring area.

Every landmark picture was shown until the participant responded by pressing one of the four

possible arrow keys. After each response, participants were asked to rate how confident they

had been about their answer on a six-point scale ranging from '1 - very sure' to '6 - I did not

know'.

Subsequent to the tasks, questionnaire data collected demographic characteristics, individual

navigation styles, and spatial abilities. To assess individual orienting ability the

Figure 3 a) Real-world setup of the navigation task in Experiment 2. The experimenter

followed the participant and initiated the auditory navigation instructions. b) Frontal view

picture of a navigation relevant landmark ("public restroom") as used in the cued-recall task

(pictures were presented in color).

SBSOD (Hegarty et al., 2003) was used.

Statistical analysis. As in Experiment 1, the design was a mixed measures ANOVA

with the between-subject factor navigation instruction condition (standard, short, long) and

the repeated measures factor landmark type (relevant, irrelevant, novel). For additional

information please see methods part of Experiment 1.

Results

The Spearman correlation of the SBSOD score and the percentage of correct

responses to each landmark type was not significant ($\rho's < .242$, $p's > .156$). Thus, the

SBSOD score was not included as covariate in the ANOVA.

The ANOVA for the percentage of correctly identified landmarks and associated

navigation decision revealed a significant main effect of navigation instruction condition

($F_{(1,33)} = 3.39$, $p = .036$, $\eta_p^2 = .183$). The post-hoc comparisons revealed trends towards

significance when comparing standard ($M = 40.2$, $SE = 2.75$) and short ($M = 49.0$, $SE = 2.75$,

$p = .090$) as well as standard and long navigation instructions ($M = 49.7$, $SE = 2.75$,

$p = .062$).

The main effect of landmark type also reached significance ($F_{(1.26, 41.7)} = 57.4$,

$p < .001$, $\eta_p^2 = .635$) with post-hoc comparisons showing that the performance for relevant

landmarks ($M = 40.6$, $SE = 1.99$) was significantly higher than for irrelevant landmarks

($M = 28.0$, $SE = 2.98$, $p < .001$) and significantly lower than the recognition performance for

novel landmarks ($M = 70.3$, $SE = 3.35$, $p < .001$). Additionally, novel landmarks were

significantly more often recognized than irrelevant landmarks ($p < .001$).

The interaction of instruction condition and landmark type did not reach significance

($F_{(2.53, 41.7)} = 1.72$, $p = .184$, $\eta_p^2 = .095$). The group-boxplots and individual measures can be

seen in Figure 4.

Figure 4: Boxplots and single subject performance scores of the cued-recall task of

Experiment 2 taking place in real-world using forty landmarks per landmark category.

Whiskers display up to 1.5 standard deviations (SDs) from mean and small dots represent

individual values above the whiskers.

546    According to the suppression hypothesis, the landmark types were compared within

547 each instruction condition. For the standard navigation instruction condition the post-hoc

548 comparisons revealed a significantly higher performance for novel *(M* = 60.8, *SE* = 5.81) as

549 compared to relevant (*M* = 30.4, *SE* = 3.44, *p* < .001) and irrelevant landmarks (*M* = 29.38,

550 *SE* = 5.16, *p* = .010). Relevant and irrelevant landmarks were statistically indifferent

551 (*p* > .999). In the short navigation instruction condition. The cued-recall performance for

552 relevant landmarks (*M* = 42.7, *SE* = 3.44) was significantly higher than for irrelevant

553 (*M* = 25.8, *SE* = 5.16, *p* = .006) and significantly lower than for novel landmarks (*M* = 78.5,

554 *SE* = 5.81, *p* < .001). The difference between irrelevant and novel landmarks was also

555 significant (*p* < .001). When contrasting the long navigation instruction condition, the

556 performance values for relevant landmarks (*M* = 48.5, *SE* = 3.44) were significantly higher

557 compared to irrelevant landmarks (*M* = 28.8, *SE* = 5.15, *p* = .002) and significantly lower

558 than for novel landmarks (*M* = 71.7, *SE* = 5.81, *p* = .006). Again, the difference between

559 irrelevant and novel landmarks was significant (*p* < .001).

560    Testing the landmark-based learning hypothesis by comparing the instruction

561 conditions within each landmark type revealed only significant post-hoc contrasts for relevant

562 landmarks. The cued-recall performance for relevant landmarks was marginally lower in the

563 standard navigation instruction condition (*M* = 30.4, *SE* = 3.44) compared to the short

564 (*M* = 42.7, *SE* = 3.44, *p* = .098) and significantly lower when compared to the long

565 instruction condition (*M* = 48.5, *SE* = 3.44, *p* = .004).

566 **Discussion**

567    Experiment 2 tested incidental spatial learning during assisted pedestrian navigation

568 in an uncontrolled, dynamically changing real-world setting including cars and other

569 pedestrians. Even after a break of two weeks, the results of the cued-recall task demonstrated

570 an improved performance when navigating with landmark-based navigation instructions, in

accordance with our learning hypothesis. The significant difference between short and long

navigation instructions as observed in Experiment 1, however, was not replicated. In

addition, the cued-recall results for irrelevant landmarks revealed a different pattern than all

previous experiments. For the first time, navigation irrelevant landmarks revealed

significantly lower recognition performance than navigation relevant landmarks irrespective

of the navigation instruction condition. The recognition performance for novel landmarks

was still relatively high, and comparable to the previous results (Experiment 1, Gramann et

al., 2017; Wunderlich & Gramann, 2018).

The surprisingly low recognition performance for navigation irrelevant landmarks

across all navigation instruction conditions was likely caused by the characteristics of the

specific experimental protocol. One explanation for this performance drop is the change in

perspective of the landmark pictures in the cued-recall task. In contrast to all previous

experiments, landmark pictures were presented from a frontal view instead of a navigators'

perspective. This might have been especially detrimental to the recognition of landmarks

positioned at straight segments without junctions as participants might not have turned their

heads to inspect all buildings and thus, irrelevant landmarks were less likely encountered

from this frontal perspective.

Regardless of this difference in recognition performance for irrelevant landmarks, we

again observed improved cued-recall performance for relevant landmarks when using

landmark-based as compared to standard navigation instructions. The learning suppression

was reflected in the performance differences for relevant landmarks compared to irrelevant

landmarks. Whereas the recognition performance for irrelevant landmarks remained low

across all navigation instruction conditions, the performance for relevant landmarks increased

significantly when using landmark-based instructions. This supports the suppression

hypothesis and that the alleviation of such a suppression effect is possible by including

landmark-based information in auditory navigation instructions.

General Discussion

The focus of the reported experiments was to investigate a potential spatial learning

suppression accompanying established navigation instructions as well as enhanced incidental

spatial knowledge acquisition when using new versions of landmark-based navigation

instructions. In addition, it was tested whether both effects can be generalized to ecologically

valid scenarios. To that end, two consecutive experiments were conducted investigating the

performance in a cued-recall task as an indicator for landmark- and route-level spatial

knowledge acquired during a single exposure to an unfamiliar environment. The navigation

contexts used were videos of (Experiment 1) as well as real-world pedestrian navigation

(Experiment 2) through an unknown city area.

608   The results of both experiments replicated the positive impact of landmark-based

navigation instructions on spatial knowledge acquisition which was shown for visual

landmark augmentation (Li, Fuest, & Schwering, 2014; Löwen, Krukar, Schwering, 2019;

Tom and Denis, 2003, 2004). Furthermore, they replicated the findings from Gramann and

colleagues (2017) and Wunderlich and Gramann (2018) demonstrating an increased cued-

recall performance especially regarding navigation relevant landmarks after navigating with

auditory, landmark-based navigation instructions. This underpins the robustness and the

ecological validity of the incidental spatial learning effect when using landmark information

in auditory navigation instructions.

617   The results provided further evidence that adding detailed information about a

landmark in addition to a landmark name is of advantage for incidental spatial knowledge

acquisition. In Experiment 1, the benefit of the additional semantic information improved

spatial learning compared to only naming the landmark in the instructions. It can be argued

that the detailed information about the landmarks in the long navigation instructions may

have helped to identify the landmark and this way eased the landmark recognition in the

cued-recall task. However, the additional semantic information was mostly related to the

function of the object and did not include characteristics that were visible (e.g., "Go straight

at the Malteser building. This aid organization counts one million members."). As such, the

identification of landmarks was similar in both landmark-based navigation instructions and a

confounding effect can be ruled out.

Following the argument that decreased spatial memory performance associated with

the use of navigation aids is likely caused by divided attention between the control of

movement and the navigation assistant (Gardony et al. 2013, 2015), spatial knowledge

acquisition was expected to be impaired irrespective of the landmark category. In the studies

of Gardony and colleagues only the retrieval of landmarks at decision points was

investigated. Here, comparing memory performance for different landmark types, we

demonstrated that spatial memory performance was decreased only for navigation relevant

landmarks when using standard navigation instructions. This was likely caused by

instructions biasing the attention towards the intersection while landmark-based navigation

instructions helped to process environmental features. The augmentation of landmarks, in

contrast, allowed to encode a specific landmark in association with a turning decision. The

combination of both speaks for a suppression of incidental spatial learning by standard

instructions that is abolished with an increasing amount of landmark-related information in

the auditory navigation instructions.

Landmark-based instructions might have led to a general increase in attention

towards the environment such that the instruction at relevant navigation points also impacted

how the surroundings were processed during navigation irrelevant segments. Comparable

recognition rates for navigation irrelevant and novel landmarks across navigation instruction

conditions, however, ruled out such a halo-effect of landmark augmentation. Furthermore, the

generally low recognition levels for irrelevant landmarks in Experiment 2 do not contradict

the suppression hypothesis as the performance for novel landmarks remained on a high level.

It rather raised the question whether the irrelevant landmarks were indeed recognized. The

perspective in the landmark pictures changed from a first-person perspective while walking

to a frontal perspective. This required a perspective-independent memory of a landmark and

not just the familiarity with the street scene. Thus, it is likely that the high recognition

performance for irrelevant landmarks in previous experiments was based on the street view

and other features of the environment surrounding a landmark instead of the specific

irrelevant landmark. This argument could be applied to navigation relevant landmarks as

well. However, the data of Experiment 2 showed no impact of the changed perspective on

these landmarks. The low performance for irrelevant landmarks in Experiment 2 encourages

us to further investigate the auditory augmentation of navigation irrelevant landmarks in the

future to better understand how this might affect incidental spatial learning during less

demanding navigation phases. To further understand what kind of spatial knowledge is

acquired during assisted navigation, future experiments will need to systematically

manipulate the picture perspective and/or content in the cued-recall task.

An interpretation of the reported results is still restricted to incidental spatial learning

after navigating one unknown route in an unfamiliar environment. A generalization to spatial

knowledge acquisition based on multiple uses of landmark-based navigation instructions for

the same route or different routes with overlap is not yet possible. However, the results let us

expect that spatial learning would be enhanced even more. Multiple use of navigation

assistance in the same area would also allow for assessing survey knowledge acquired from

landmark-based navigation instructions. Fostering the acquisition of survey knowledge would

be the ultimate goal of learning-oriented navigation assistance systems as this level of spatial

knowledge would allow more flexible use of the acquired spatial knowledge. For now, the

cued-recall performance allows for conclusions about the acquired landmark and route level

knowledge, but not survey knowledge. Yet, this series of experiments covers both the transfer

from low to high realism of the environment including visuals and other traffic participants as

well as the realism of the movement dimension and allowing interfering navigation

experiences. Despite the setup changes, the incidental spatial learning effects were replicated.

The results indicate that landmark-based navigation instructions using additional detailed

information about the landmark show improved spatial knowledge acquisition over standard

navigation instructions currently used as default in available navigation assistance systems.

681   **Conclusions**

682   The findings of the two experiments reported here replicated the previously described

incidental spatial learning associated with landmark-based navigation instructions. This effect

was shown to be generalizable across different navigation contexts and types of locomotion.

Thus, landmark-based navigation instructions are a promising tool to prevent deskilling of

spatial abilities that comes with the use of standard navigation assistance systems. Especially

the landmark reference combined with more detailed information prevailed amongst all tested

modifications of auditory navigation instructions, rendering this approach the most

promising. Future research should address the multiple use of landmark-based navigation

instructions and the accompanying spatial knowledge acquisition. This way, navigation

assistants may train the users' orientation abilities enabling them to autonomously navigate

the environment in the future.

Data Availability

Data were collected at TU Berlin. The data of single or both experiments are available on request from the corresponding author AW.

Key points

- Standard navigation instruction lead to a suppression of spatial knowledge acquisition at navigation relevant intersections
- Landmark-based navigation instructions are able to reverse this suppression effect
- This incidental spatial learning effect was tested in different experimental setups and was shown to be robust and ecological valid

References

Allen, G. L. (1999). Cognitive abilities in the service of wayfinding: A functional approach. The Professional Geographer, 51(4), 555-561., DOI:10.1111/0033-0124.00192

Aporta, C., Higgs, E., Hakken, D., Palmer, L., Palmer, M., Rundstrom, R., ... & Higgs, E. (2005). Satellite culture: global positioning systems, Inuit wayfinding, and the need for a new account of technology. Current Anthropology, 46(5), 729-753

van Asselen, M., Fritschy, E., & Postma, A. (2006). The influence of intentional and incidental learning on acquiring spatial knowledge during navigation. Psychological Research, 70(2), 151-156.

Axon, S., Speake, J., & Crawford, K. (2012). 'At the next junction, turn left': attitudes towards Sat Nav use. Area, 44(2), 170-177.

Bakdash, J. Z., Linkenauger, S. A., & Proffitt, D. (2008). Comparing decision-making and control for learning a virtual environment: Backseat drivers learn where they are going. In Proceedings of the human factors

and ergonomics society annual meeting (Vol. 52, No. 27, pp. 2117-2121). Sage CA: Los Angeles, CA:

SAGE Publications.

Baus, J., Kray, C., & Krüger, A. (2001). Visualization of route descriptions in a resource-adaptive navigation

aid. Cognitive Processing, 2(2-3), 323-345.

Bertel, S., Dressel, T., Kohlberg, T., & von Jan, V. (2017). Spatial knowledge acquired from pedestrian urban

navigation systems. In Proceedings of the 19th International Conference on Human-Computer

Interaction with Mobile Devices and Services (p. 32). ACM.

Brügger, A., Richter, K. F., & Fabrikant, S. I. (2019). How does navigation system behavior influence human

behavior?. Cognitive research: principles and implications, 4(1), 5.

Evans, G. W., Smith, C., & Pezdek, K. (1982). Cognitive maps and urban form. Journal of the American

Planning Association, 48(2), 232-244.

Fenech, E. P., Drews, F. A., & Bakdash, J. Z. (2010). The effects of acoustic turn-by-turn navigation on

wayfinding. In Proceedings of the human factors and ergonomics society annual meeting (Vol. 54, No.

23, pp. 1926-1930). Sage CA: Los Angeles, CA: SAGE Publications.

Gardony, A. L., Brunyé, T. T., Mahoney, C. R., & Taylor, H. A. (2013). How navigational aids impair spatial

memory: Evidence for divided attention. Spatial Cognition & Computation, 13(4), 319-350.

Gardony, A. L., Brunyé, T. T., & Taylor, H. A. (2015). Navigational aids and spatial memory impairment: The

role of divided attention. Spatial Cognition & Computation, 15(4), 246-284.

Giannopoulos, I., Kiefer, P., & Raubal, M. (2015). GazeNav: gaze-based pedestrian navigation. In Proceedings

of the 17th International Conference on Human-Computer Interaction with Mobile Devices and

Services (pp. 337-346). ACM.

Gramann, K. (2013). Embodiment of spatial reference frames and individual differences in reference frame

proclivity. *Spatial Cognition & Computation*, *13*(1), 1-25.

Gramann, K., Hoepner, P., & Karrer-Gauss, K. (2017). Modified navigation instructions for spatial navigation

assistance systems lead to incidental spatial learning. Frontiers in psychology, 8, 193.

Hart, S. G. (2006). NASA-task load index (NASA-TLX); 20 years later. In Proceedings of the human factors

and ergonomics society annual meeting (Vol. 50, No. 9, pp. 904-908). Sage CA: Los Angeles, CA:

Sage publications.

Hart, S. G. & Staveland, L. E. (1988) Development of NASA-TLX (Task Load Index): Results of empirical and

theoretical research. In P. A. Hancock and N. Meshkati (Eds.) Human Mental Workload. Amsterdam:

North Holland Press.

Hegarty, M., Richardson, A.E., Montello, D.R., Lovelace, K., Subbiah, I.(2003) Development of a self-report

measure of environmental spatial ability. Intelligence 30, 425–448. Santa Barbara sense of direction

scale questionnaire

Hegarty, M., & Waller, D. (2004) A dissociation between mental rotation and perspective-taking spatial

abilities. Intelligence, 32 175-191.

Hirtle, S. C., & Raubal, M. (2013). Many to many mobile maps. In Cognitive and linguistic aspects of

geographic space (pp. 141-157). Springer, Berlin, Heidelberg.

Huang, H., Schmidt, M., & Gartner, G. (2012). Spatial knowledge acquisition with mobile maps, augmented

reality and voice in the context of GPS-based pedestrian navigation: Results from a field test.

Cartography and Geographic Information Science, 39(2), 107-116.

Kalin, J., & Frith, J. (2016). Wearing the city: Memory p (a) laces, smartphones, and the rhetorical invention of

embodied space. Rhetoric Society Quarterly, 46(3), 222-235.

Kitchin, R., & Dodge, M. (2007). Rethinking maps. Progress in human geography, 31(3), 331-344.

Klippel, A., Hirtle, S., & Davies, C. (2010). You-are-here maps: Creating spatial awareness through map-like

representations. Spatial Cognition & Computation, 10(2-3), 83-93.

Leshed, G., Velden, T., Rieger, O., Kot, B., & Sengers, P. (2008). In-car gps navigation: engagement with and

disengagement from the environment. In Proceedings of the SIGCHI conference on human factors in

computing systems (pp. 1675-1684). ACM.

Li, R., Fuest, S., & Schwering, A. (2014). The effects of different verbal route instructions on spatial

orientation.

Lin, A. Y., Kuehl, K., Schöning, J., & Hecht, B. (2017). Understanding Death by GPS: A Systematic Study of
Catastrophic Incidents Associated with Personal Navigation Technologies. In Proceedings of the 2017
CHI Conference on Human Factors in Computing Systems (pp. 1154-1166). ACM.

Löwen, H., Krukar, J., & Schwering, A. (2019). Spatial Learning with Orientation Maps: The Influence of
Different Environmental Features on Spatial Knowledge Acquisition. ISPRS International Journal of
Geo-Information, 8(3), 149.

May, A. J., & Ross, T. (2006). Presence and quality of navigational landmarks: effect on driver performance and
implications for design. Human factors, 48(2), 346-361.

May, A., Ross, T., Bayer, S. H., & Burnett, G. E. (2001). Using landmarks to enhance navigation systems:
driver requirements and industrial constraints.

May, A. J., Ross, T., Bayer, S. H., & Tarkiainen, M. J. (2003). Pedestrian navigation aids: information
requirements and design implications. Personal and Ubiquitous Computing, 7(6), 331-338.

Mosier, K. L., Skitka, L. J., Burdick, M. D., & Heers, S. T. (1996). Automation bias, accountability, and
verification behaviors. In Proceedings of the Human Factors and Ergonomics Society Annual Meeting
(Vol. 40, No. 4, pp. 204-208). Sage CA: Los Angeles, CA: SAGE Publications.

Münzer, S., Zimmer, H. D., & Baus, J. (2012). Navigation assistance: A trade-off between wayfinding support
and configural learning support. Journal of experimental psychology: applied, 18(1), 18.

Münzer, S., Zimmer, H. D., Schwalm, M., Baus, J., & Aslan, I. (2006). Computer-assisted navigation and the
acquisition of route and survey knowledge. Journal of environmental psychology, 26(4), 300-308.

Parasuraman, R. (2000). Designing automation for human use: empirical studies and quantitative models.
Ergonomics, 43(7), 931-951.

Parush, A., Ahuvia, S., & Erev, I. (2007). Degradation in spatial knowledge acquisition when using automatic
navigation systems. In International Conference on Spatial Information Theory (pp. 238-254).
Springer, Berlin, Heidelberg.

Rasch, B., Friese, M., Hofmann, W. J., & Naumann, E. (Eds.) (2010). Quantitative Methoden. SPSS
Ergänzungen (3.th ed., Vol. 2). Heidelberg. Springer-Verlag.

Raubal, M., & Winter, S. (2002). Enriching wayfinding instructions with local landmarks. In International

conference on geographic information science (pp. 243-259). Springer, Berlin, Heidelberg.

Ross, T., May, A., & Thompson, S. (2004). The use of landmarks in pedestrian navigation instructions and the

effects of context. In International Conference on Mobile Human-Computer Interaction (pp. 300-304).

Springer, Berlin, Heidelberg.

Rousell, A., & Zipf, A. (2017). Towards a landmark-based pedestrian navigation service using OSM data.

ISPRS International Journal of Geo-Information, 6(3), 64.

Siegel, A. W., & White, S. H. (1975). The development of spatial representations of large-scale environments.

In Advances in child development and behavior (Vol. 10, pp. 9-55). JAI.

Tom, A., & Denis, M. (2003). Referring to landmark or street information in route directions: What difference

does it make?. In International Conference on Spatial Information Theory (pp. 362-374). Springer,

Berlin, Heidelberg.

Tom, A., & Denis, M. (2004). Language and spatial cognition: Comparing the roles of landmarks and street

names in route instructions. Applied Cognitive Psychology: The Official Journal of the Society for

Applied Research in Memory and Cognition, 18(9), 1213-1230.

Ulrich, S., Grill, E., & Flanagin, V. L. (2019). Who gets lost and why: A representative cross-sectional survey

on sociodemographic and vestibular determinants of wayfinding strategies. PloS one, 14(1), e0204781.

Wunderlich, A., & Gramann, K. (2018). Electrocortical Evidence for Long-Term Incidental Spatial Learning

Through Modified Navigation Instructions. In German Conference on Spatial Cognition (pp. 261-278).

Springer, Cham.

816   **Biographies**

Anna Wunderlich is a doctoral candidate and research assistant at Biological Psychology and

Neuroergonomics at the Berlin Institute for Technology since she had received her master's

degree in Human Factors at the same university in 2016.

Klaus Gramann is professor of Biological Psychology and Neuroergonomics at the Berlin

Institute for Technology. He is also a professor at the School of Computer Science of the

University of Technology Sydney and International Faculty at the University of California

San Diego. In 2002, he received his PhD in Psychology from the RWTH Aachen University

and habilitated 2007 at the LMU Munich in Biological and General Psychology.