Construction of habitat-specific training sets to achieve species-level assignment

in 16S rRNA gene datasets

Isabel F. Escapa[a,b,§] (ifescapa@forsyth.org), Yanmei Huang[a,b,§] (yhuang2@gmail.com),

Tsute Chen[a,b] (tchen@forsyth.org), Maoxuan Lin[a] (mlin8@uncc.edu), Alexis Kokaras[a]

(akorakas@forsyth.org), Floyd E. Dewhirst[a,b] (fdewhirst@forsyth.org), Katherine P.

Lemon[a,c,d,e,*] (katherine.lemon@bcm.edu)

[a]Forsyth Institute (Microbiology), Cambridge, Massachusetts, USA

[b]Department of Oral Medicine, Infection & Immunity, Harvard School of Dental Medicine,

Boston, Massachusetts, USA

[c]Department of Molecular Virology and Microbiology, Alkek Center for Metagenomics and

Microbiome Research, Baylor College of Medicine, Houston, Texas, USA

[d]Department of Pediatrics, Section of Infectious Diseases, Texas Children's Hospital,

Houston, Texas, USA

[e]Division of Infectious Diseases, Boston Children's Hospital, Harvard Medical School,

Boston, Massachusetts, USA

[§] These authors contributed equally to this work.

*Correspondence: katherine.lemon@bcm.edu

ABSTRACT

Background: The low cost of 16S rRNA gene sequencing facilitates population-scale molecular epidemiological studies. Existing computational algorithms can parse 16S rRNA gene sequences to high-resolution Amplicon Sequence Variants (ASVs), which represent ecologically coherent entities. Assigning species-level taxonomy to these ASVs is the critical remaining barrier to drawing ecologically/clinically relevant inferences from and comparing data across 16S rRNA gene-based microbiota studies.

Results: To overcome this barrier, we developed a broadly applicable method for constructing a phylogeny-based, high-resolution, habitat-specific training set. When used with the naïve Bayesian Ribosomal Database Project (RDP) Classifier, this training set achieved species/supraspecies-level taxonomic assignment to 16S rRNA gene-derived ASVs. The key steps for generating such a training set are 1) constructing an accurate and comprehensive phylogenetic-based, habitat-specific database; 2) compiling multiple 16S rRNA gene sequences to represent the natural sequence variability of each taxon in the database; 3) trimming the training set to match the sequenced regions if necessary; and 4) placing species sharing closely related sequences into a supraspecies taxonomic level to maintain subgenus resolution. As proof of principle, we developed a V1-V3 region training set for the bacterial microbiota of the human aerodigestive tract using our expanded Human Oral Microbiome Database (eHOMD). In addition, we overcame technical limitations to successfully use Illumina sequences for the 16S rRNA gene V1-V3 region, the most informative segment for classifying bacteria native to the human aerodigestive tract. We also generated a full-length eHOMD 16S rRNA gene training set,

which we used in conjunction with an independent PacBio Single Molecule, Real-Time

(SMRT)-sequenced sinonasal dataset to validate the representation of species in our

training set. The latter also established the effectiveness of a full-length training set for

assigning taxonomy of long-read 16S rRNA gene datasets.

Conclusion: Here, we present a systematic approach for constructing a phylogeny-

based, high-resolution, habitat-specific training set that permits species/supraspecies-

level taxonomic assignment to short- and long-read 16S rRNA gene-derived ASVs. This

advancement enhances the ecological and/or clinical relevance of 16S rRNA gene-based

microbiota studies.

Keywords: training set; naïve Bayesian RDP Classifier; species-level taxonomy; 16S

rRNA gene; habitat-specific database; microbiota; microbiome; eHOMD; nasal;

aerodigestive tract

BACKGROUND.

In microbiota studies of most ecosystems and/or habitats, achieving ecologically and/or

clinically relevant results requires species-level identification of constituents. For

example, species-level identification is often critically important for host-associated

microbial communities because these often include commensal and pathogenic species

of the same genus, e.g., [1, 2]. Also, some microbial genera include species that are site

specialists and inhabit distinct niches of a given environment [3]. Although high-

throughput close-to-full-length 16S rRNA gene sequencing (e.g., circular consensus

sequences from PacBio Single Molecule, Real-Time (SMRT) sequencing) and

metagenomic underlined{whole} underlined{genome} underlined{sequencing} (WGS) both hold promise for species-level

microbiota studies, the current cost per sample limits their utility for studies of more than

hundreds of samples. In contrast, the low cost of 16S rRNA gene short-read sequencing

makes population-scale (i.e., thousands of samples) molecular epidemiological studies

of bacterial microbiota of humans, other animals, plants and the environment broadly

feasible. The caveat being that the majority of published short-read 16S rRNA gene

sequencing studies use read clustering at a percent similarity that constrains resolution

to the genus level, i.e., 97% identity. Indeed, recent reviews on best practices and

benchmarking for 16S rRNA gene microbiota studies focus on genus-level operational

taxonomic unit (OTU) analysis, e.g., [4-6]. However, newer algorithms, many of which are

not based on similarity thresholds, allow single-nucleotide resolution and can parse 16S

rRNA gene short-read sequences to species- or strain-level resolution phylotypes, usually

called underlined{amplicon} underlined{sequence} underlined{variants} (ASVs) (e.g., MED (Minimal Entropy Decomposition)

[7, 8], DADA2 (Divisive Amplicon Denoising Algorithm) [9, 10] and UNOISE [11, 12],

among others [13, 14]). Thus, it is vital to develop methods that achieve accurate

taxonomic assignment while preserving the sub-genus level resolution of ASVs and

permit consistent cross-study comparison.

Microbial databases encompassing broad phylogenetic diversity, such as SILVA [15, 16],

RDP [17] and Greengenes [18], serve the key role of being applicable to myriad different

habitats but this valuable breadth comes with the trade-off of inclusion of taxonomically

misannotated 16S rRNA gene sequences. For example, Edgar estimated annotation error

rates as high as ~10-17% in these comprehensive databases [19]. (Of note, SILVA and

RDP continue to undergo regular updates and contain a broadly expansive and

comprehensive record of 16S rRNA gene sequences from all explored habitats, whereas,

Greengenes was last updated in 2013.) For habitats that have yet to be deeply

interrogated, the access to this breadth outweighs the risk of misclassification due to

annotation error. However, once a habitat is sufficiently explored, a habitat-specific

database enables accurate fine-level phylogenetic resolution for taxonomic assignment

to ASVs [20-30]. Existing habitat-specific databases are constructed with different

methods and can be used to assign taxonomy via different approaches. Examples of this

include the following: 1) stand-alone habitat-specific databases consisting of curated

collections of close-to-full-length 16S rRNA gene sequences compiled both from other

repositories and by generating new sequences from the habitat of interest, e.g., eHOMD

for the human aerodigestive tract [20, 29], HITdb for the human gut [23] and RIM-DP for

rumen [22]; 2) custom addition of compiled sequences from a specific habitat of interest

to augment a broad general database, e.g., HBDB for honey bee [21], DictDB for termite

and cockroach gut [27], SILVA19Rum for rumen [30] and MiDAS for activated sludge [24,

26]; 3) both a general and a habitat-specific database combined in the same pipeline,

e.g., a general database followed by a most common ancestors approach with a custom

species-level phylogeny of selected human-associated genera with pathogenic members

[31] and FreshTrain with the TaxAss workflow for freshwater [28]. Many of these

databases are used to train classifiers for taxonomy assignment.

The naïve Bayesian RDP Classifier [32] is one of several effective algorithms for

assigning taxonomy, all of which require a training set. (For benchmarking and

comparison with other methods, see [33-35].) Properly formatted versions of the broad

16S rRNA gene databases SILVA, RDP and Greengenes are available to train the most

popular implementations of the naïve Bayesian RDP Classifier. The quality of the training

set strongly influences taxonomic assignment and habitat-specific training sets have been

developed to increase accuracy of taxonomic assignments [21, 27, 33-36]. However, the

resolution of available training sets is mostly limited to the genus level. An exception is

the manually curated subset of the Greengenes database corresponding to 89 clinically

relevant bacterial genera that was used to assign species-level taxonomy of full-length

16S rRNA gene sequences of clinical isolates [37]. Notwithstanding, species-level

taxonomy assignment of short-read 16S rRNA gene datasets remains a challenge.

We hypothesized that starting from a habitat-specific, locally comprehensive, phylogeny-

based, high-resolution (separated at ≥ 98.5% identity) set of curated reference sequences

with distinct taxonomic names, we could develop a method to rapidly generate a training

set to leverage the strength of the naïve Bayesian RDP Classifier to consistently achieve

species- or supraspecies (i.e., subgenus)-level taxonomic assignment of ASVs. Here, we

describe this method along with improvements to Illumina sequencing strategies to

maximize information content of 16S rRNA gene V1-V3 sequencing reads. We show that

use of the naïve Bayesian RDP Classifier with a training set in which each taxon is

represented by a collection of highly similar sequences that captures the natural variability

of each species resulted in accurate species-level taxonomic assignment of short-reads

from the V1-V3 region of the 16S rRNA gene. This represents a methodological

advancement. Based on our own research interests and availability of the requisite

habitat-specific database of reference sequences, we developed and validated short- and

long-read training sets for the microbiota of the human aerodigestive tract using our

expanded Human Oral Microbiome Database (eHOMD). The eHOMD is a locally

comprehensive, high-resolution, phylogeny-based database for the microbiomes of sites

within the human aerodigestive tract (mouth, nasal passages, sinuses, throat,

esophagus) that also has good coverage of the lower respiratory tract [29]. The eHOMD

provisional naming scheme permits cross-study comparison of 16S rRNA gene

sequences from both formally named species and as-yet-unnamed or uncultivated

species. Using this, we describe a systematic approach for generating training sets that

is applicable to any ecosystem/habitat of interest.

RESULTS.

Identify the 16S rRNA gene regions to optimize species-level identification for taxa

in the habitat of interest. The choice of the 16S rRNA gene region(s) for short-read

sequencing places an upper bound on the amount of species-level resolution that is

achievable within a dataset [38-41]. Therefore, it is key to determine which regions

provide the most information for distinguishing bacterial species that are common to that

specific ecosystem. For the habitats within the human aerodigestive tract, i.e., the nasal

passages, sinuses, throat, mouth, esophagus, as well as the lower respiratory tract, we

previously showed that many more taxa are distinguishable at the species level with the

V1-V3 region than with the commonly used V3-V4 region of the 16S rRNA gene [29].

A method for achieving highly informative 16S rRNA gene V1-V3 region sequencing

data using Illumina MiSeq. The length of the V1-V3 16S rRNA gene region, which

corresponds to *E. coli* positions 28 to 517, is highly variable in bacteria. The eHOMD

includes 770-plus species level taxa and the eHOMD phylogeny is available at

http://www.homd.org/ftp/HOMD_phylogeny/current/. For all but three taxa the V1-V3

region size ranged from 431 to 523 base pairs (bp). Three Campylobacter species, with

intervening sequences in the V2 region, were up to 653 base pairs in length (**Figure 1A**).

This size variability makes it extraordinarily difficult to capture full-length V1-V3

sequences for all bacterial taxa using Illumina technology. Even using the 500 or 600

cycle MiSeq kits, this is impeded by the decline in sequence quality as the run progresses

(**Additional file 1A**). Many analysis pipelines reject read pairs that do not overlap.

Excluding taxa with longer V1-V3 regions biases results and generates a false

understanding of these microbial communities. To solve these problems, we

hypothesized that there are specific subregions within V1-V3 that are most informative

such that complete sequencing across the V1-V3 region via overlapping paired reads is

unnecessary. To identify the more informative V1-V3 subregions, we evaluated Shannon

entropy for each position across all of taxa represented by eHOMD reference sequences

(eHOMDrefs) (**Figure 1B**). Based on examination of the entropy values across the V1-

V3 region, we postulated that sequencing 300 bp from the V1 primer and 150 bp from the

V3 primer would capture the majority of the sequencing diversity needed to maximize

species-level taxonomic assignment to the V1-V3 region for species included in eHOMD.

Moreover, one advantage of the naïve Bayesian RDP Classifier, which is a k-mer-based

Bayesian approach, is that it can provide a single taxonomic assignment when analyzing

Illumina pair-end data without requiring overlap of the forward and reverse reads.

Therefore, from each primer, V1 and V3, we separately visualized at what read length

there was no longer a gain in the percentage of classified sequences using a simulated

eHOMD-derived dataset. To accomplish this for primer V3, we fixed the read length from

primer V1 at 350 bp (**Figure 1C**) based on the indication in Figure 1B that the first 300 bp

captures the majority of sequence variability with the extra 50 bp allowing for variability in

region length. Similarly, for primer V1, we fixed the read length from primer V3 at 200 bp

(**Figure 1D**). We then determined the percentage of sequences classified at species level

at increasing read lengths from the complementary primer using the 998 eHOMDrefs as

a training set (*FL_eHOMDrefs_TS*). Based on these assays, species-level assignment

plateaued across all bootstrap values at 70 bp from primer V3 (**Figure 1C**). Moreover,

species-level assignment started to plateau across all bootstrap values around 210 bp

from primer V1 (**Figure 1D**). These results indicated that species-level identification can

be achieved with nonoverlapping reads for the 16S rRNA gene V1-V3 region using the

naïve Bayesian RDP Classifier, at least for the taxa in eHOMD.

Furthermore, these results establish guidance for actual read lengths needed for Illumina

sequencing of the V1-V3 16S rRNA gene region. Knowing this, we next determined

experimentally what length of high-quality sequences are obtainable using primers V1

and V3 with 500 cycles on the Illumina MiSeq. Amplicon-based libraries can be

challenging to sequence using Illumina's 2-channel sequencing chemistry since their low

diversity hinders correct identification of DNA clusters and accurate base calling [42]. To

mitigate this, we changed Read 1 (R1) to start from the V3 primer instead of V1, since

clusters are defined very early in an Illumina run (first 4 cycles) [43] and sequences are

mostly identical in the first positions immediately 3' of the V1 primer. We also increased

the proportion of PhiX from a range of 10-25% up to a range of 30-50%, as recommended

in [43]. Together, these steps accomplished a significant improvement in sequence

quality (**Additional file 1A-B**).

During our experiments, we also observed that variability in library quality, e.g., from low

biomass habitats such as the human nostrils, can negatively impact the accuracy of

library quantification leading to an inadvertently low percentage of PhiX. Because the

informative region from V1 (R2) includes the first 250 bp from the primer (**Figure 1D**), we

routinely perform asymmetrical sequencing of R1 and R2 with R1 = 100 bp and R2 = 400

bp (e.g., **Additional file 1C**) to avoid having the decrease in sequence quality that is

sometimes observed at the end of an Illumina MiSeq run falling within the informative

region from the V1 primer (R2) (**Figure 1B**). After trimming poor quality regions from each

experimentally-derived read, this generally results in high-quality sequences of 200 to 250

bp from primer V1 and 100 bp from primer V3. Thus, for the simulated eHOMD-derived

dataset (**V1V3_eHOMDSim_250N100**) created to test each step in the development of

the eHOMD training set, we mimicked these Illumina-generated nonoverlapping reads by

designing artificial reads consisting in 250 bp from primer V1 and 100 bp from primer V3

(**Additional file 2**). (To enhance clarity, the names of datasets appear in **bold** whereas

the names of training sets appear in ***bold italics***.)

Compilations of closely-related sequences for each taxon in a training set improve

the accuracy of species-level taxonomic classification. Genus-level taxonomic

assignment is not an inherent limitation of the naïve Bayesian RDP Classifier. Rather,

taxonomic assignment to 16S rRNA gene short reads is limited by both the resolution to

which sequences in datasets are parsed and by the nature of the training set used. The

former is overcome by using approaches such as oligotyping/MED [7, 8], DADA2 [9, 10]

or zero-radius OTU [11, 19] to parse sequence variants at high resolution. We

hypothesized that the limitations inherent in training sets could also be overcome.

The naïve Bayesian RDP Classifier algorithm indicates that a training set with a larger

number of sequences representing each taxon will result in more confident taxonomic

assignment [32]. Based on the conditional probability for a member of a taxon (T), the

higher the number of possible times a given "k-mer" (word or w_i) exists in the training set,

the greater the confidence with which assignment of that taxon is made. Thus, as the

number of sequences (M) in the training set increases (**Figure 2A vs. 2B**), the number of

accurate assignments should increase. In support of this, Werner and colleagues found

more sequence counts result in more assignments [36]. Therefore, to systematically

increase M, we used each of the reference sequences in eHOMD, i.e., the eHOMDrefs,

as bait to capture closely matching, publicly available sequences and combined the

resulting compilation of sequences for each taxon into a close-to-full-length compilation

training set (***FL_Compilation_TS***) that reflects the 16S rRNA gene sequence variability

for each taxon (**Additional file 3**). We then assessed the percentage of reads in the

simulated dataset **V1V3_eHOMDSim_250N100** that classified at the species-level at

incremental bootstrap values from 50 to 100 using the training set ***FL_Compilation_TS***

(**Figure 3A,** orange bars) compared with the training set ***FL_eHOMDrefs_TS*** (**Figure 3A,**

purple bars) and observed an increase with the compilation except at a bootstrap value

of 100. We postulate that the additional sequences classified with the

FL_eHOMDrefs_TS TS at a bootstrap of 100 are misclassified sequences. A higher rate

of misclassification is expected with the training set ***FL_eHOMDrefs_TS***, since it includes

only a few representative sequences for each taxon. Therefore, we next assayed for any

misclassifications. At each bootstrap threshold, the percentage of reads that were

misclassified (i.e., reads for which the assigned taxonomic identity was different than the

known identity of the original sequence from which the simulated read was derived) was

at least 50% lower using the training set *FL_Compilation_TS* (**Figure 3B**, orange line)

than with the training set *FL_eHOMDrefs_TS* (**Figure 3B**, purple line). Thus,

classification of the dataset **V1V3_eHOMDSim_250N100** showed a reduced error rate

and increased confidence level when using a training set consisting of a compilation of

closely related sequences rather than one or a few reference sequences for each taxon.

Moving towards an appropriate short-read fragment training set. The training set

FL_Compilation_TS consisted of close to full-length 16S rRNA gene sequences. We

hypothesized that the presence in the training set of k-mers outside the V1-V3 region

might lead to misclassifications when using it with a V1-V3 region dataset. Supporting

this, when using a training set based on a large general database, trimming reference

sequences to match the sequenced region increases the number of sequences that are

assigned taxonomy [36]. Therefore, we trimmed the sequences in the training set

FL_Compilation_TS to cover only the V1-V3 region generating training set

V1V3_Raw_TS (**Figure 2C**). Using this there was no gain in the percentage of reads in

the simulated dataset **V1V3_eHOMDSim_250N100** classified to the species-level

(**Figure 4A**, green bar). Moreover, we observed an increase in the percentage of

misclassified reads (**Figure 4B**, green line). Therefore, we next determined why the use

of appropriate short-read fragments in this training set paradoxically decreased

confidence and accuracy of species-level assignment and resolved the issue.

Combining closely related, indistinguishable taxa into supraspecies decreases the

error rate for a short-read training set. Considering the possible explanations for this,

we realized that taxa with distinct full-length 16S rRNA gene sequences can have

identical V1-V3 sequences. In silico, using only V1-V3, 37 of the ~770 species-level taxa

in eHOMD are no longer distinguishable from at least one other species at 100% identity

[29]. Therefore, we hypothesized that the observed loss in accuracy using training set

V1V3 _Raw_TS was due to identical sequences with more than one species name, e.g.,

Veillonella parvula and *Veillonella dispar* [29]. To avoid this problem, we removed

duplicate sequences and assigned a combined name, i.e., a supraspecies name, e.g.,

Veillonella parvula_dispar to the remaining unique sequence (**Figure 2D**). This generated

the training set ***V1V3_Curated_TS***, which showed improved accuracy compared to both

the ***FL_Compilation_TS*** and ***V1V3_Raw_TS*** (**Figure 4B**, red line). However, this

improvement came at a cost of an 0.7 to 4.4 % decrease in the reads assigned

supraspecies- or species-level taxonomy at each bootstrap threshold (**Figure 4A**, red

bar). This trade-off can be illustrated by graphing at each bootstrap threshold the

percentage of reads from the simulated **V1V3_eHOMDSim_250N100** dataset that were

misclassified   versus   confidently   assigned   species-level   taxonomy   using   the

V1V3_Curated_TS with the naïve Bayesian RDP Classifier (**Figure 4C**).

Maximizing performance of the naïve Bayesian RDP Classifier for subgenus-level

taxonomic assignment of short-read sequences requires both insertion of

supraspecies as a taxonomic level and setting a threshold bootstrap. Two steps

were required to reap the benefits of using the supraspecies definition. First, formally

inserting supraspecies as a taxonomic level between genus and species in the name

header for each sequence in the training set, which yielded the training set

V1V3_Supraspecies_TS (**Figure 2E; Additional File 4**). Second, establishing the

bootstrap cut-off at which a sequence is not assigned at the species level so that naïve

Bayesian RDP Classifier will then default to supraspecies, rather than defaulting to genus,

allowing for a higher percentage of reads to be assigned (**Figure 5A**, blue bar). This latter

step preserves subgenus level information encoded in the ASVs. This choice inevitably

involves a trade-off between accuracy and percentage of reads classified below genus

level, e.g., see **Figure 4C**. For our purposes, we chose a conservative bootstrap value of

70 (**Figure 5B,** blue line). With the simulated data, for which the truth is known, this gave

an error rate of around 0.05%. Of note, the default bootstrap setting for the naïve

Bayesian RDP Classifier is 50 and we would encourage use of a more conservative value

for species-level taxonomic assignment.

Using an independent sinonasal dataset validated the performance of the eHOMD

training set. We next validated the performance of the eHOMD training set against a

dataset of close-to-full-length 16S rRNA gene sequences from sinonasal samples. Very

importantly, these sequences are independent of the sequences recruited to build the

training set. Earl and colleagues performed PacBio SMRT sequencing of close-to-full-

length 16S rRNA genes from multiple sinonasal samples from each of 12 adults without

sinus inflammation who were undergoing removal of a pituitary adenoma [44]. Because

this dataset was deposited in the SRA, these sequences were not present in the NCBI

nr/nt sequence repository (from which sequences were recruited for the eHOMD training

set) and therefore not used in the generation of the eHOMD training set. We used DADA2

to denoise these sequences and identify the relative abundance of each ASV in this

dataset (**FL_sinonasal_SMRT_ASV; Additional File 5**). After which, we followed a

three-pronged approach assess the validity of the eHOMD training set for use with this

fully independent sinonasal dataset.

First, we compared the blastn-generated taxonomic assignment for these ASVs using

eHOMD compared to using NCBI 16S Microbial to identify any taxa in the dataset that

might be missing in eHOMD, and thus the training set (**Table 1; Additional File 6A**). A

detailed comparison (**Additional File 6B**), showed that 50 ASVs, corresponding to 11.1%

of the total reads, were differentially assigned by blastn (98.5% identity cutoff) against

eHOMDv15.1 versus against NCBI 16S Microbial. Of these 50 ASVs, 33 were assigned

to taxa with an HMT (Human Microbial Taxon) # as a provisional species designation.

The majority (17/33) were assigned to *Peptoniphilus* sp. HMT-187, which corresponded

in the NCBI 16S Microbial blastn output to *Peptoniphilus lacydonensis* and accounted for

7.6 % of the total reads. Similarly, *Peptoniphilus* sp. HMT-187 was 11th in total reads

across the nostril samples of 210 HMP participants [29]. The new species name

Peptoniphilus lacydonensis was published in 2018 and is formally recognized [45];

therefore, it is now linked to HMT-187 in eHOMD. Of the remaining 17 ASVs, 8 were

mismatches between closely related *Streptococcus* species. Only 6 ASVs were

nonassigned (NA) using eHOMD, thus, eHOMD included the vast majority (99.7%) of

taxa present in the Earl-Mell sinonasal dataset. We note that based on recent additions

both eHOMD and NCBI 16S Microbial allowed correct assignment of ASVs to *Lawsonella*

clevelandensis, which previously might be misclassified by best blastn hit as a Dietzia

species, and to *Neisseriaceae* G-1 bacterium HMT-327, which before receiving a stable

taxonomic designation in eHOMD might be misclassified by best blastn hit as a

Snodgrassella species [29].

Second, we compared species-level assignment of the dataset

FL_sinonasal_SMRT_ASV using blastn against eHOMD versus the naïve Bayesian

RDP Classifier with the full-length eHOMD training set **FL_Compilation_TS**. Less than

2% (1.91%) of the total reads in the dataset **FL_sinonasal_SMRT_ASV**, which are

represented by 25 ASVs, were differentially assigned species-level taxonomy by these

approaches (**Table 1; Additional File 6A**). There was no clear pattern to this differential

assignment (**Additional File 6C**). This served to validate the use of the full-length

eHOMD training set **FL_Compilation_TS** and demonstrated that our approach is an

effective method for assigning species-level taxonomy to close-to-full-length 16S rRNA

gene sequences such as those derived from PacBio SMRT sequencing.

Third, having established that our approach is comparable to blastn for species-level

assignment to full-length sequences, we used naïve Bayesian RDP Classifier derived

assignments with the training set **FL_Compilation_TS** as a proxy for the true species

representation in the dataset **FL_sinonasal_SMRT_ASV**. We then used these to assess

the performance of the training set **V1V3_Supraspecies_TS** for assigning species-level

taxonomy to the V1-V3 region sequences of the dataset **FL_sinonasal_SMRT_ASV**

(**V1V3_sinonasal_SMRT_ASV; Additional File 7**). There were seventeen V1-V3 ASVs

that were differentially assigned, corresponding to 1.64% of the reads (**Table 1;**

Additional File 6D). Of these 17 differentially-assigned ASVs, 5 belonged to a

supraspecies, a level not represented in the full-length training set **FL_Compilation_TS**.

Another 4 ASVs, all of which were present at very low relative abundance, had full-length

ASVs assigned to *Anaerococcus tetradius*, whereas the V1-V3 region was assigned to

Anaerococcus octavius, all with bootstrap values ≤ 92 (**Additional File 6A**). In contrast,

when 16S rRNA gene sequences were parsed into ASVs based on their full-length, then

cut to V1-V3 there was little to no species-level ambiguity (**Additional File 6D**). Thus, the

ambiguity observed with V1-V3 16S rRNA short reads most likely occurs at the level of

parsing into ASVs, due to fewer informative sequences, rather than at the assignment

step with the naïve Bayesian RDP Classifier and eHOMD training set.

Table 1. The eHOMD workflow performed well for species/supraspecies taxonomy

assignment of an independent long-read 16S rRNA gene sinonasal dataset.

	# ASVs	# Reads	% ASVs	% Reads
NCBI 16S Microbial blastn	178	140,455	87.3	97.3
eHOMD blastn	188	143,274	92.2	99.3
eHOMD FL_Compilation_TS	194	142,843	95.1	99.0
eHOMD V1V3_Supraspecies_TS	201	144,279	98.5	99.9

Table 1 Legend. Columns three and four indicate the % of ASVs and reads, respectively,

assigned subgenus-level taxonomy using each of the four approaches tested.

The eHOMD training set outperforms both the SILVA and RDP training sets. Having

validated the use of the eHOMD training set with an independent 16S rRNA gene

sinonasal dataset (**Table 1**), we next compared the use of our taxonomic assignment

workflow with other currently available pipelines that are coupled with the RDP or SILVA

databases. We used three different datasets for this: 1) we generated a V1-V3 dataset

derived from a collection of human aerodigestive tract 16S rRNA gene clone libraries

(**V1V3_hADT_CL; Additional File 8**); 2) the HMP 16S rRNA gene V1-V3 454-sequenced

nostril dataset that we previously analyzed [29]; and 3) the close-to-full-length ASVs of

the **FL_sinonasal_SMRT_ASV** dataset. We then assigned genus-level taxonomy to all

of these using the naïve Bayesian RDP Classifier with a bootstrap threshold of 70 coupled

with three different training sets: an eHOMD training set (V1-V3 or FL), RDP16 or

SILVA132. The eHOMD training set resulted in a larger percentage of reads assigned to

a specific genus for each dataset; however, all three training sets resulted in genus-level

assignment of > 90% of the sequences (**Table 2**). In contrast, a striking difference

emerged between the different workflows when assigning taxonomy to species level. Our

method of coupling the naïve Bayesian RDP Classifier with an eHOMD training set

showed superior performance in terms of the percentage of reads classified compared to

the exact string match method that is currently implemented in DADA2 in conjunction with

SILVA132 or RDP16 (**Table 2**). As would be expected, the exact match algorithm

performed much better for close-to-full-length ASVs than for V1-V3 region ASVs. For the

V1-V3 region ASVs, it also performed much better with the V1-V3 sequences in the V1-

V3 human aerodigestive tract clone library dataset than with the HMP V1-V3 dataset. We

speculate this occurred because the close-to-full-length sequences from the human

aerodigestive tract clone library (**V1V3_hADT_CL**) dataset are part of both the RDP and

SILVA databases, whereas the HMP V1-V3 454 sequences are not.

Table 2. The eHOMD training set is superior for assigning species/supraspecies-

level taxonomy to short- and long-read human aerodigestive tract datasets.

		V1V3_hADT_CL	V1V3_HMPnares_ ASV[#]		FL_sinonasal_SMRT_ASV	
		(% reads)	(% ASVs)	(% reads)	(% ASVs)	(% reads)
eHOMD	Genus	100.0	95.5	98.9	99.5	100.0
	Species	100.0	93.9	98.5	95.1	99.0
SILVA	Genus	96.1	94.7	97.6	96.6	98.9
	Species	44.7*	4.1*	29.9*	18.6*	71.9*
RDP	Genus	93.2	90.2	92.2	94.1	98.5
	Species	38.5*	3.1*	27.5*	13.2*	60.6*

Table 2 Legend. *Exact match algorithm; # ASVs derived from the HMP nares V1-V3

dataset, as described in [29], constitute the **V1V3_HMPnares_ASV** dataset (**Additional**

File 9).

A key implication of these data is that our overall method yields comparable species-level

results for 16S rRNA gene sequencing of the human aerodigestive tract using V1-V3

short-read sequences, which is very cost effective, compared to using close-to-full-length

PacBio SMRT sequences. For example, it readily distinguished sequences of

Staphylococcus aureus and *Staphylococcus epidermidis.* Another implication is that for

species-level analysis of the microbiota of habitats lacking a high-resolution, accurate

16S rRNA gene database, PacBio SMRT sequencing coupled with the newly available

DADA2 PacBio pipeline [46] to generate ASVs followed by blastn against NCBI 16S

Microbial can provide effective species-level taxonomic assignment (**Table 1**).

CONCLUSIONS.

Here, we present a systematic approach for generating and validating habitat-specific

16S rRNA gene training sets to achieve species/supraspecies-level taxonomic

assignment for short- or long-read 16S rRNA gene sequences. We used the naïve

Bayesian RDP classifier with our training set; however, such a training set can be used

with other taxonomic classifiers [34, 35, 47-54]. Our training set-construction approach

includes several methodological advancements. First, we generated clusters of existing

close-to-full length 16S rRNA gene sequences at the 99% level (with ≥ 98% coverage)

around highly curated reference sequences. This collection of sequences for each taxon

represented the currently known sequence variability for each taxon and increased the

accuracy of taxonomic assignment using the naïve Bayesian RDP Classifier (**Figure 3**).

Second, we added an intermediate taxonomic level between genus and species, which

we dubbed supraspecies, to which we assigned taxa in which sequences overlapped

between two or more taxonomic clusters. This increased the percentage of sequences

assigned subgenus-level taxonomy by preventing the default of consigning difficult-to-

assign sequences to the genus level (**Figure 5**). The process of constructing a short-read

training set started with the generation of an effective close-to-full-length training set,

which could then be used for taxonomic assignment of long-read 16S rRNA gene

sequences such as those from clone libraries and from high-throughput long-read

sequencing. As a final critical step, we validated the composition of the eHOMD training

set using a PacBio SMRT-sequenced sinonasal dataset consisting of sequences

independent of those used to build the training set (**Table 1**). Facilitating

species/supraspecies-level analysis of 16S rRNA gene sequence datasets paves the way

for cost-effective, population-scale molecular epidemiological microbiota studies that can

achieve greater ecological/clinical relevance by reaching species level.

The successful implementation of a training set for species/supraspecies-level

assignment of 16S rRNA gene short-read (e.g., V1-V3) datasets involved a collaborative

give-and-take to iteratively optimize the sequencing protocol and the analysis workflow in

conjunction with each other. As a result, here, we also provided three specific protocol

recommendations for sequencing of the 16S rRNA gene V1-V3 region with the Illumina

MiSeq. First, we show that excellent taxonomic assignment can be achieved with

nonoverlapping Illumina reads from V1 and V3 using our recommended sequencing

protocol and taxonomic assignment workflow. This counters a common misperception

that overlapping Illumina reads are required [5, 55]. The naïve Bayesian RDP Classifier

tolerates nonoverlapping V1-V3 sequences; however, some other classifiers might not.

Second, we demonstrated the value of initiating Read 1 from the V3 reverse primer since

R1 usually consists of a longer stretch of high-quality sequence. Third, we provide

evidence for a role for increased amounts of PhiX when sequencing from the V1 primer,

due to the high-degree of sequence conservation 3' to this primer. This is analogous to

the respective recommendations by Illumina and Mitra and colleagues to add PhiX to

reach up to or, sometimes, greater than 50% of the total DNA for low diversity samples

[43].

We note these three limitations to the presented method for constructing a habitat-specific

training set. First, capturing the natural sequence variation for the 16S rRNA gene(s) for

each taxon is limited by the number of such sequences currently available in public

repositories. For example, 140 of the ~770 taxa in eHOMD are represented by four or

fewer distinct close-to-full-length sequences in the training set *FL_Compilation_TS*,

whereas, ~630 taxa are represented by five or greater. Second, the comprehensiveness

of a training set depends on the comprehensiveness of the phylogeny-based, habitat-

specific database from which it is constructed. Therefore, if an ASV is from a species that

is absent from the database, then misclassification of that ASV to the mostly closely

related species present in the database is possible. This is a known limitation of closed

reference-based taxonomic assignment. As such, the known limitations of eHOMD are

also limitations of any eHOMD training set [20, 29]. Third, as with databases, training sets

also require regular updating over time.

Within these limitations, we note several advantages. First, when coupled with a training

set built with our method, the k-mer-based naïve Bayesian approach accommodates the

natural variability of 16S rRNA gene sequences that exists within many bacterial species

enabling high rates of accurate taxonomic assignment. In contrast, this natural variability

limits the utility of any exact match algorithm to assigning species-level taxonomy for only

those sequences already existing in a training set (**Table 2**). Second, despite all of the

known limitations of a single-gene taxonomic indicator, the huge number of 16S rRNA

gene sequences from diverse ecosystems available in public repositories supports the

utility of the 16S rRNA gene for taxonomic assignment. In contrast, the utility of WGS

metagenomic sequencing, which holds the promise of strain-level taxonomic assignment,

will remain limited by the number of reads that cannot be mapped until multiple strains

genomes are sequenced for each taxon residing in the ecosystem/habitat of interest.

Finally, there are several additional recommendations to improve taxonomic assignment

achieved with this method. First, we recommend incorporating a stable provisional

naming scheme into any habitat-specific database, e.g., the HMTs in eHOMD [20, 29].

Second, we recommend validating any training set generated with this method using a

habitat-appropriate dataset that is fully independent of the sequences used to construct

the training set, as we did with the sinonasal PacBio SMRT-generated dataset. Third, for

ASVs that remain unassigned at finer taxonomic levels and are of interest based on their

relative abundance and/or prevalence in the population, we recommend two steps. First,

query these unassigned ASVs against a broad database such as SILVA, RDP and/or

NCBI 16S Microbial via blastn (≥98.5% identity over ≥98% coverage) to ascertain if these

belong to a named species. Second, if no such named species match exists, then create

a new provisional taxon in your database [20, 29]. This approach will identify candidate

new taxa, both named and unnamed, for addition to a habitat-specific database and

training set.

METHODS.

Determination of the 16S rRNA gene V1-V3 sequence length for each taxon in

eHOMD. To construct Figure 1A, the 998 eHOMDv15.1 aligned 16S reference sequences

(eHOMDrefs) were downloaded in fasta format from eHOMD

(http://www.homd.org/?name=seqDownload&type=R) [29]. One eHOMDref was selected

for each of the 770 HMTs in eHOMD as a representative of the given HMT. The resulting

alignment was trimmed from *E. coli* position 28 to 517 (V1-V3 region) and further trimmed

to positions 28-220 (V1-V2 region) and 436-517 (V3 region).

Entropy calculation for the 16S rRNA gene V1-V3 region for each taxon in eHOMD.

To construct Figure 1B, sequences in the eHOMDv15.1 alignment were trimmed from

aligned positions 40 to 880. The resulting sequences with alignment gaps are much

longer than actual V1-V3 sequences. Shannon entropy for each position in the aligned

sequences was estimated with a maximum likelihood method using the "entropy" R

package [56]. Because the distribution of ungapped V1-V3 lengths centered around 489

bases, a V1-V3 fragment with an ungapped length of 489 (eHOMDref 762_5043) was

randomly chosen from the V1-V3 sequence collection as a representative onto which the

entropy results were plotted.

Nonoverlapping V1-V3 16S rRNA gene sequencing. Supragingival pooled plaque

samples were deposited into collection tubes containing 150 µL TE buffer. Samples were

incubated at 37°C for 3 hrs with 1 µL of Lucigen's Ready-Lyse Lysozyme, and then

subsequently processed using Lucigen's MasterPure Complete protocol beginning at

step C-Lysis of Fluid or Tissue Samples. The method deviated from the protocol at step

4 where the incubation time was increased to 30 mins and steps 5 and 6 were omitted.

Samples were precipitated using step F-Precipitation of Total Nucleic Acids and were

resuspended in 25 µl of TE buffer instead of the suggested 30 µl. 16S rRNA gene libraries

were prepared by targeted amplicon sequencing performed using a custom dual-index

protocol [55]. The 16S rRNA gene primers described by Allen and colleagues (**Additional**

File 10) were used to amplify the V1-V3 region of the 16S rRNA gene [57]. These primers

provide broad coverage of 16S rRNA genes while maintaining high sensitivity. The

sample libraries were prepared using a 22-cycle PCR reaction to reduce the chimera

formation that is common when using a high cycle number. The final PCR products were

purified using Ampure XP beads, pooled in equal amounts, and gel purified using the

QIAGEN MinElute Gel Extraction Kit. Purified, pooled libraries were quantified using the

NEBNext Library Quant Kit for Illumina. Final libraries were sequenced on Illumina®

MiSeq™ with a v2 reagent kit (500 cycles) using a 250x250 or 100x400 configuration.

The sequencing was performed at a 10 pM loading concentration with the indicated

percentage of PhiX added. Quality Phred Score of the reads was assessed using FastQC

[58].

Construction of eHOMD-based training datasets for the naïve Bayesian RDP

Classifier. Training datasets were constructed in FASTA format as described on the

DADA2 official website (https://benjjneb.github.io/dada2/index.html) [9], with taxonomy in

the FASTA header line for each individual sequence. Training sets used in this study are

described below.

FL_eHOMDrefs_TS. All of the full-length 16S eHOMDrefs, together with their respective

taxonomic assignment, were formatted as a training set for the naïve Bayesian RDP

Classifier, as above.

FL_Compilation_TS. This is the final version of the full-length 16S rRNA gene eHOMD

training set, available as **Additional File 3** and for download from eHOMD.org as

eHOMDv15.1_FL_Compilation_TS.fa.gz. First, to more precisely calculate the percent

identity for recruiting sequences for the training set, we trimmed each of the eHOMDrefs

to nucleotides 28 and 1373. This was necessary for two reason: 1) several eHOMDrefs

have hanging 5' or 3' ends that, if left in place, would affect the calculation of percent

identity and 2) this trimming permitted capture of sequences from the extensive datasets

that use the reverse primer at ~1390. Second, each of the 998 trimmed eHOMDrefs was

queried against the NCBI nonredundant nucleotide (nr/nt) database using blastn (NCBI

BLAST 2.6.0+ package) (https://www.ncbi.nlm.nih.gov/books/NBK279690/) with the

parameters -db nr -remote -perc_identity 97. Nucleotide sequences of GenBank IDs with

≥ 97% sequence identity to any of the eHOMDrefs were downloaded in FASTA format

using the efetch.fcgi command of NCBI's Entrez Programming Utilities (E-utilities;

https://www.ncbi.nlm.nih.gov/books/NBK25501/). The blastn hits were downloaded in the

same orientation as the eHOMDrefs in two batches. 1) For subject sequence length

between 1000 and 2000 nt, the entire subject sequence was downloaded. 2) For subject

sequence length > 2000 bp (e.g., a complete genomic sequence), only the aligned portion

of the sequence was downloaded. Sequences < 1000 bp were not downloaded. Third,

the 301,794 downloaded sequences, which matched to HMTs at ≥ 97%, were parsed

based on their highest sequence percent identity (≥ 99%) and alignment coverage (≥ 98%

calculated based on the length of the reference) to any of the eHOMDrefs in a given HMT.

The choice of ≥ 99% identity was designed to obtain the centrally conserved set of

sequences for each eHOMDref. The choice of ≥ 98% coverage was to ensure that the

majority of the close-to-full-length sequence was present. Sequences that matched to

multiple HMTs at equal percent identity and coverage were randomly assigned to only

one HMT. The **FL_Compilation_TS** training set is comprised of a total of 223,144

sequences parsed to their corresponding HMT, with a range of 1 to 4004 sequences per

HMT.

V1V3_Raw_TS. We generated this training set version in two steps. First, each

eHOMDref was individually aligned with the compilation of downloaded sequences that

were matched to it at ≥ 99% identity and ≥ 98% coverage (see immediately above).

Second, the sequences in the V1-V3 region, defined as positions 40-880 in the gapped

eHOMDrefs alignment, were captured and then the alignment gaps removed. These steps

were performed using a custom script (**Additional File 11**).

V1V3_Curated_TS. Sequences that were identical across V1-V3 in **V1V3_Raw_TS** were

collapsed into a single sequence with the names of all taxa involved concatenated with a

":" separator. The majority of such concatenations occurred among either the same

species, resulting in no name change, or different species of the same genus, resulting

in assignment of a concatenated species name. However, there were a number of cases

where species from two different genera were involved. These intergenus concatenations

were carefully examined case by case. In all but one case, the concatenation was only

supported by two to three sequences and, therefore, was deemed unreliable and rejected.

After manual examination, only one intergenus concatenation remained. This was

between HMT-559 (*Afipia broomeae*) and HMT-597 (*Bradyrhizobium elkanii*) and was

supported by 29 sequences. The genus of the concatenated taxa was assigned as

Afipia:Bradyrhizobium and species as *broomeae:elkanii*.

V1V3_Supraspecies_TS. This is the final version of the V1-V3 16S rRNA gene eHOMD

training set, available as **Additional File 4** and for download from eHOMD.org as

eHOMDv15.1_V1V3_Supraspecies_TS.fa.gz

(http://www.homd.org/ftp/publication_data/20190709/). The sequences in this training set

are the same as those included in the *V1V3_Curated_TS* version; only the header

information was edited to include the supraspecies notation as a taxonomical level

between genus and species. Therefore, instead of the header with seven-levels included

in previous versions of the eHOMD training set (i.e.,

>Kingdom;Phylum;Class;Order;Family;Genus;Species), the *V1V3_Supraspecies_TS*

training set includes a header with eight levels (i.e.,

>Kingdom;Phylum;Class;Order;Family;Genus;Supraspecies;Species). A supraspecies

was defined between two or more HMTs when there was a phylogenetic distance less

than 0.005 between at least one pair of sequences of the corresponding HMTs. To

calculate the distances, V1V3 sequences were aligned with MAFTT v6.935b [59] and

treed with FastTree version 2.1.9 [60] with default parameters. Pairwise distances

between sequences were calculated as the sum of horizontal branch length between two

sequence nodes based on FastTree's default "Jukes-Cantor + CAT" DNA evolution model

[60]. The name of the resultant supraspecies is a concatenation of the species names of

all HMTs involved, separated by ":" and is assigned at the supraspecies level (seventh

level) for all the sequences of the involved HMTs. Sequences that were identical across

the V1-V3 region between more than one taxon were assigned the concatenated name

both at the supraspecies and species levels (e.g.,

>Bacteria;Actinobacteria;Actinobacteria;Corynebacteriales;Corynebacteriaceae;Coryne-

bacterium;accolens:macginleyi:tuberculostearicum;accolens:macginleyi:tuberculostearic

um). Whereas, the rest of the reads for those taxa were named at the supraspecies level

as the concatenated name and maintained their unique identifier at the species level (e.g.,

>Bacteria;Actinobacteria;Actinobacteria;Corynebacteriales;Corynebacteriaceae;Coryne-

bacterium;accolens:macginleyi:tuberculostearicum;accolens). For taxa not requiring

concatenations (see the *V1V3_Curated_TS* description), the species designation is

repeated at the supraspecies level such that the seventh- and eighth-level designations

are identical (e.g., >Bacteria;Firmicutes;Bacilli;Lactobacillales;Carnobacteriaceae;Dolo-

sigranulum;pigrum;pigrum).

Generation of a V1-V3 16S rRNA gene simulated dataset derived from eHOMD.

Simulated reads were generated from each unique sequence in the *V1V3_Curated_TS*

training set. During read generation, one percent of the bases in each unique initial

sequence were randomly selected and changed into a different base to simulate a 1%

error rate. The resulting dataset contains 19,480 simulated sequences, each of them

labelled with the ID of the parent eHOMDref sequence from which they were derived.

Then, each error-simulated read was trimmed into two fragments to simulate Illumina pair-

end reads (R1 starting from the V3 primer and R2 starting from the V1 primer). We

generated multiple length configurations of both the R1 and R2 fragments. First, fixing R2

at 350 bp, we generated R1 fragments from the V3 primer ranging from 20 to 200 bp

(Simulated_R2_350_R1_20-200, **Additional File 12**). Second, fixing R1 at 200 bp, we

generated R2 fragments from the V1 primer ranging from 140 to 350 bp

(Simulated_R2_140-350_R1_200, **Additional File 13**). Prior to analysis with the naïve

Bayesian RDP Classifier, paired reads were connected with a "10N" linker to form one

fragment ordered R2-10N-R1 (**Figure 1C** and **1D**). Subsequent evaluation of the steps

for generating the eHOMD training sets in Figures 3 to 5 was done using the configuration

R2(250 bp)-10N-R1(100 bp) **(V1V3_eHOMDSim_250N100; Additional File 2)**.

Reanalysis of a sinonasal PacBio-SMRT-sequenced full-length 16S rRNA gene

dataset. Earl and colleagues kindly provided the circular consensus sequences (CCS)

already demultiplexed, labeled by sample, pooled together and, then, filtered based on

length distribution, terminal matches to the primer sequences, not aligning to a provided

host or background genome sequence and with a cumulative expected error (EE < 1)

[44]. We then used the DADA2 PacBio pipeline to denoise these CCS and identify the

relative abundance of each ASV in the dataset; i.e., we used the learnErrors() function

with errorEstimationFunction=PacBioErrfun and BAND_SIZE=32 [9, 46]. The sequences

of the resulting 204 ASVs are in the **FL_sinonasal_SMRT_ASV** dataset (**Additional File**

5). The V1-V3 region was trimmed using bedtools getfasta with default parameters

(bedtools version 2.26.0, https://bedtools.readthedocs.io/en/latest/) and reads were

further trimmed into two fragments to simulate Illumina pair-end reads using the

configuration   R2(250   bp)-10N-R1(100   bp),   as   described   above

(**V1V3_sinonasal_SMRT_ASV**; **Additional File 7**).

Generating a test V1-V3 human aerodigestive tract (hADT) microbiota dataset from

full-length 16S rRNA gene clone libraries (CL). We previously used the close-to-full-

length 16S rRNA gene sequences from clone library-based microbiota studies of the

human aerodigestive tract, as described in Supplemental Text S1 of [29]: Segre-Kong

nostril (SKn) [61-66], Pei-Blaser [67, 68], Harris-Pace [69], van der Gast-Bruce [70],

Flanagan-Bristow [71] and Perkins-Angenent [72]. Here, we compiled these into one

dataset along with clones from NCBI PopSet UIDs 399192397, 399202217, 399199823,

399197584, 399194446, 399189902, 399186216, 399183739, 399182414, 399179617,

399175646 and 399173254 [73]. Aligned eHOMDrefs (eHOMDv15.1) sequences were

trimmed from *E. coli.* position 28-1373 and used to query this compiled dataset via blastn.

We retained 27,816 sequences that hit with 100% coverage and ≥ 99.5% identity to 401

HMTs as the full-length <u>h</u>uman <u>a</u>ero<u>d</u>igestive <u>t</u>ract clone library dataset (**FL_hADT_CL;**

Additional File 14). Of these, 5254 (18.9%) matched to more than one HMT, whereas

22,562 (81.1%) unambiguously matched to single HMTs. Sequences in this full-length CL

dataset were then aligned using MAFTT v6.935b with default parameters [59]. Segments

corresponding to the V1-V3 region were extracted based on positions of V1-V3 in the

alignment (V1V3_hADT_CL, **Additional File 8**) using bedtools getfasta with default

parameters (bedtools version 2.26.0, https://bedtools.readthedocs.io/en/latest/).

Taxonomic assignment with the naïve Bayesian RDP Classifier. ASVs and CL

sequences were assigned taxonomy using the naïve Bayesian RDP Classifier via the

dada2::assignTaxonomy() function in R (an implementation of the algorithm with a kmer

size of 8 and 100 bootstrap iterations) with the specified training set and with

outputBootstraps=TRUE and the indicated minBoot value [9, 32]. In addition to our

eHOMD training sets, we used the RDP16 (*rdp_train_set_16.fa.gz*) and SILVA132

(*silva_nr_v132_train_set.fa.gz*) genus-level training sets

(https://benjjneb.github.io/dada2/training.html). Since the eHOMD training set

V1V3_Supraspecies_TS generates an output with eight taxonomic levels that might not

be compatible with common downstream applications that accept only seven levels, we

provide a custom-written R function (**Additional File 15**) that converts the output from

eight to seven levels as follows. First, if a sequence is not assigned at species level (i.e.,

the eighth level) at a given threshold (output as "NA") then the eighth level is replaced

with the classification result and bootstrap value from the corresponding seventh level.

Next, the seventh level is deleted and only the resultant merged eighth level that can

contain either species or supraspecies information is reported. Please note that this

merged last supraspecies-or-species level is labeled simply as species.

Taxonomic assignment with the DADA2 exact match. ASVs and CL sequences were

assigned species-level taxonomy with the RDP16 (*rdp_species_assignment_16.fa.gz*)

and SILVA132 (*silva_species_assignment_v132.fa.gz*) training set files downloaded

from https://benjjneb.github.io/dada2/training.html using the dada2::assignSpecies()

function in R with allowMultiple=TRUE [9].

Taxonomic assignment with blastn. The NCBI BLAST 2.6.0+ package

(https://www.ncbi.nlm.nih.gov/books/NBK279690/) was installed and the "blastn"

command used with max_target_seqs 1, hits with < 98.5% identity were considered

nonassigned. ASVs (**FL_sinonasal_SMRT_ASV**) derived from the sinonasal PacBio

SMRT-sequenced dataset were also assigned taxonomy using blastn against two

databases: the NCBI 16S Microbial database was downloaded from

ftp://ftp.ncbi.nlm.nih.gov/blast/db/ on January 2019 [74] and eHOMDv15.1 was converted

to a BLAST database using "makeblastdb" from the NCBI BLAST 2.6.0+ package.

DECLARATIONS.

Ethics approval and consent to participate. All participants provided informed consent

and samples used to generate the V1-V3 region 16S rRNA dataset in Additional File 1

were collected under a protocol (#13-14 to FED) approved by the Forsyth Institutional

Review Board**.**

Consent for publication. Not applicable.

Availability of data and material. All data are included as additional files. The following

are also available for download at eHOMD.org

(http://www.homd.org/ftp/publication_data/20190709/): 1) the simulated eHOMD derived

dataset (**Additional File 2** as V1V3_eHOMDSim_250N100.fa), 2) both eHOMD training

set files (**Additional File 3** as eHOMDv15.1_FL_Compilation_TS.fa.gz; and **Additional**

File 4 as eHOMTv15.1_V1V3_Supraspecies_TS.fa.gz) and 3) both custom scripts

(**Additional File 11** as retrieveSegment.py and **Additional File 15** as eight2seven.R).

Competing interests. The authors declare that they have no competing interests.

Funding. This work was funded in part by a pilot grant (IFE, KPL) from the Harvard Catalyst | The Harvard Clinical and Translational Science Center (National Center for Research Resources and the National Center for Advancing Translational Sciences, National Institutes of Health Award UL1 TR001102 and financial contributions from Harvard University and its affiliated academic health care centers); by the National Institute of General Medical Sciences under award number R01GM117174 (KPL); by the National Institute of Allergy and Infectious Diseases under award number R01AI101018 (KPL); and by the National Institute of Dental and Craniofacial Research under award numbers R37DE016937 and R01DE024468 (FED). The content is solely the responsibility of the authors and does not reflect the official views of the National Institutes of Health or other funding source.

Authors' contributions. Conceived Project: YH, IFE, FED, KPL. Designed Project: YH, IFE, FED, KPL. Generated and Analyzed data: YH, IFE, TC, ML, AK. Interpreted results: YH, IFE, TC, ML, AK, FED, KPL. Generated figures and tables: IFE, YH. Wrote manuscript: KPL, IFE. All authors reviewed and edited the manuscript and approved the final version.

Acknowledgements. We are grateful to Joshua Earl, Joshua Chang Mell and colleagues for providing the intermediate data table that facilitated analysis with a newly available algorithm and to members of the Lemon Lab and the Starr-Dewhirst-Johnston-Lemon Joint Group Meeting for helpful questions and suggestions throughout the project.

REFERENCES

1.	Egerton S, Culloty S, Whooley J, Stanton C, Ross RP: **The Gut Microbiota of Marine Fish.** *Front Microbiol* 2018, **9:**873.

2.	Berendsen RL, van Verk MC, Stringlis IA, Zamioudis C, Tommassen J, Pieterse CM, Bakker PA: **Unearthing the genomes of plant-beneficial Pseudomonas model strains WCS358, WCS374 and WCS417.** *BMC Genomics* 2015, **16:**539.

3.	Welch JLM, Dewhirst FE, Borisy GG: **Biogeography of the Oral Microbiome: The Site-Specialist Hypothesis.** *Annu Rev Microbiol* 2019.

4.	D'Amore R, Ijaz UZ, Schirmer M, Kenny JG, Gregory R, Darby AC, Shakya M, Podar M, Quince C, Hall N: **A comprehensive benchmarking study of protocols and sequencing platforms for 16S rRNA community profiling.** *BMC Genomics* 2016, **17:**55.

5.	Pollock J, Glendinning L, Wisedchanwet T, Watson M: **The Madness of Microbiome: Attempting To Find Consensus "Best Practice" for 16S Microbiome Studies.** *Appl Environ Microbiol* 2018, **84**.

6.	Almeida A, Mitchell AL, Tarkowska A, Finn RD: **Benchmarking taxonomic assignments based on 16S rRNA gene profiling of the microbiota from commonly sampled environments.** *Gigascience* 2018, **7**.

7.	Eren AM, Maignien L, Sul WJ, Murphy LG, Grim SL, Morrison HG, Sogin ML: **Oligotyping: Differentiating between closely related microbial taxa using 16S rRNA gene data.** *Methods in ecology and evolution / British Ecological Society* 2013, **4**.

8.   Eren AM, Morrison HG, Lescault PJ, Reveillaud J, Vineis JH, Sogin ML: **Minimum**

entropy decomposition: unsupervised oligotyping for sensitive partitioning

of high-throughput marker gene sequences. *The ISME journal* 2015, **9:**968-

979.

9.   Callahan BJ, McMurdie PJ, Rosen MJ, Han AW, Johnson AJ, Holmes SP: **DADA2:**

High-resolution sample inference from Illumina amplicon data. *Nat Methods*

2016, **13:**581-583.

10.   Callahan BJ, McMurdie PJ, Holmes SP: **Exact sequence variants should**

replace operational taxonomic units in marker-gene data analysis. *ISME J*

2017, **11:**2639-2643.

11.   Edgar RC: **UNOISE2: improved error-correction for Illumina 16S and ITS**

amplicon sequencing. *bioRxiv* 2016**:**081257.

12.   Edgar RC: **Updating the 97% identity threshold for 16S ribosomal RNA OTUs.**

Bioinformatics 2018, **34:**2371-2375.

13.   Tikhonov M, Leach RW, Wingreen NS: **Interpreting 16S metagenomic data**

without clustering to achieve sub-OTU resolution. *ISME J* 2015, **9:**68-80.

14.   Amir A, McDonald D, Navas-Molina JA, Kopylova E, Morton JT, Zech Xu Z,

Kightley EP, Thompson LR, Hyde ER, Gonzalez A, Knight R: **Deblur Rapidly**

Resolves Single-Nucleotide Community Sequence Patterns. *mSystems* 2017,

2.

15.   Quast C, Pruesse E, Yilmaz P, Gerken J, Schweer T, Yarza P, Peplies J, Glockner

FO: **The SILVA ribosomal RNA gene database project: improved data**

processing and web-based tools. *Nucleic Acids Res* 2013*,* **41:**D590-596.

16. Yilmaz P, Parfrey LW, Yarza P, Gerken J, Pruesse E, Quast C, Schweer T, Peplies

J, Ludwig W, Glockner FO: **The SILVA and "All-species Living Tree Project**

(LTP)" taxonomic frameworks. *Nucleic Acids Res* 2014, **42:**D643-648.

17. Cole JR, Wang Q, Fish JA, Chai B, McGarrell DM, Sun Y, Brown CT, Porras-Alfaro

A, Kuske CR, Tiedje JM: **Ribosomal Database Project: data and tools for high**

throughput rRNA analysis. *Nucleic Acids Res* 2014, **42:**D633-642.

18. McDonald D, Price MN, Goodrich J, Nawrocki EP, DeSantis TZ, Probst A,

Andersen GL, Knight R, Hugenholtz P: **An improved Greengenes taxonomy**

with explicit ranks for ecological and evolutionary analyses of bacteria and

archaea. *ISME J* 2012, **6:**610-618.

19. Edgar R: **Taxonomy annotation and guide tree errors in 16S rRNA databases.**

PeerJ 2018, **6:**e5030.

20. Dewhirst FE, Chen T, Izard J, Paster BJ, Tanner AC, Yu WH, Lakshmanan A,

Wade WG: **The human oral microbiome.** *J Bacteriol* 2010, **192:**5002-5017.

21. Newton IL, Roeselers G: **The effect of training set on the classification of**

honey bee gut microbiota using the Naive Bayesian Classifier. *BMC Microbiol*

2012, **12:**221.

22. Seedorf H, Kittelmann S, Henderson G, Janssen PH: **RIM-DB: a taxonomic**

framework for community structure analysis of methanogenic archaea from

the rumen and other intestinal environments. *PeerJ* 2014, **2:**e494.

23. Ritari J, Salojarvi J, Lahti L, de Vos WM: **Improved taxonomic assignment of**

human intestinal 16S rRNA sequences by a dedicated reference database.

BMC Genomics 2015, **16:**1056.

24. McIlroy SJ, Saunders AM, Albertsen M, Nierychlo M, McIlroy B, Hansen AA, Karst

SM, Nielsen JL, Nielsen PH: **MiDAS: the field guide to the microbes of**

activated sludge. *Database (Oxford)* 2015, **2015:**bav062.

25. Deshpande V, Wang Q, Greenfield P, Charleston M, Porras-Alfaro A, Kuske CR,

Cole JR, Midgley DJ, Tran-Dinh N: **Fungal identification using a Bayesian**

classifier and the Warcup training set of internal transcribed spacer

sequences. *Mycologia* 2016, **108:**1-5.

26. McIlroy SJ, Kirkegaard RH, McIlroy B, Nierychlo M, Kristensen JM, Karst SM,

Albertsen M, Nielsen PH: **MiDAS 2.0: an ecosystem-specific taxonomy and**

online database for the organisms of wastewater treatment systems

expanded for anaerobic digester groups. *Database (Oxford)* 2017, **2017**.

27. Mikaelyan A, Kohler T, Lampert N, Rohland J, Boga H, Meuser K, Brune A:

Classifying the bacterial gut microbiota of termites and cockroaches: A

curated phylogenetic reference database (DictDb). *Syst Appl Microbiol* 2015,

38:472-482.

28. Rohwer RR, Hamilton JJ, Newton RJ, McMahon KD: **TaxAss: Leveraging a**

Custom Freshwater Database Achieves Fine-Scale Taxonomic Resolution.

mSphere 2018, **3**.

29. Escapa IF, Chen T, Huang Y, Gajare P, Dewhirst FE, Lemon KP: **New Insights**

into Human Nostril Microbiome from the Expanded Human Oral Microbiome

Database (eHOMD): a Resource for the Microbiome of the Human

Aerodigestive Tract. *mSystems* 2018, **3**.

30.   Henderson G, Yilmaz P, Kumar S, Forster RJ, Kelly WJ, Leahy SC, Guan LL,

814   Janssen PH: **Improved taxonomic assignment of rumen bacterial 16S rRNA**

815   **sequences using a revised SILVA taxonomic framework.** *PeerJ* 2019,

816   **7:**e6496.

817   31.   Conlan S, Kong HH, Segre JA: **Species-level analysis of DNA sequence data**

818   **from the NIH Human Microbiome Project.** *PLoS One* 2012, **7:**e47075.

819   32.   Wang Q, Garrity GM, Tiedje JM, Cole JR: **Naive Bayesian classifier for rapid**

820   **assignment of rRNA sequences into the new bacterial taxonomy.** *Appl*

821   *Environ Microbiol* 2007, **73:**5261-5267.

822   33.   Lan Y, Wang Q, Cole JR, Rosen GL: **Using the RDP classifier to predict**

823   **taxonomic novelty and reduce the search space for finding novel organisms.**

824   *PLoS One* 2012, **7:**e32491.

825   34.   Vinje H, Liland KH, Almoy T, Snipen L: **Comparing K-mer based methods for**

826   **improved classification of 16S sequences.** *BMC Bioinformatics* 2015, **16:**205.

827   35.   Murali A, Bhargava A, Wright ES: **IDTAXA: a novel approach for accurate**

828   **taxonomic classification of microbiome sequences.** *Microbiome* 2018, **6:**140.

829   36.   Werner JJ, Koren O, Hugenholtz P, DeSantis TZ, Walters WA, Caporaso JG,

830   Angenent LT, Knight R, Ley RE: **Impact of training sets on classification of**

831   **high-throughput bacterial 16s rRNA gene surveys.** *ISME J* 2012, **6:**94-103.

832   37.   Srinivasan R, Karaoz U, Volegova M, MacKichan J, Kato-Maeda M, Miller S,

833   Nadarajan R, Brodie EL, Lynch SV: **Use of 16S rRNA gene for identification of**

834   **a broad range of clinically relevant bacterial pathogens.** *PLoS One* 2015,

835   **10:**e0117617.

836   38.   Kumar PS, Brooker MR, Dowd SE, Camerlengo T: **Target region selection is a**
837   **critical determinant of community fingerprints generated by 16S**
838   **pyrosequencing.** *PLoS One* 2011, **6:**e20956.

839   39.   Yang B, Wang Y, Qian P-Y: **Sensitivity and correlation of hypervariable**
840   **regions in 16S rRNA genes in phylogenetic analysis.** *BMC bioinformatics* 2016,
841   **17:**135-135.

842   40.   Zhang J, Ding X, Guan R, Zhu C, Xu C, Zhu B, Zhang H, Xiong Z, Xue Y, Tu J, Lu
843   Z: **Evaluation of different 16S rRNA gene V regions for exploring bacterial**
844   **diversity in a eutrophic freshwater lake.** *Sci Total Environ* 2018, **618:**1254-
845   1267.

846   41.   Bukin YS, Galachyants YP, Morozov IV, Bukin SV, Zakharenko AS, Zemskaya TI:
847   **The effect of 16S rRNA region choice on bacterial community metabarcoding**
848   **results.** *Scientific Data* 2019, **6:**190007.

849   42.   **Best practices for low diversity sequencing on the NextSeq and MiniSeq**
850   **systems**   [https://support.illumina.com/bulletins/2016/03/best-practices-for-
851   lowdiversity-sequencing-on-the-nextseq-and-miniseq-systems.html]

852   43.   Mitra A, Skrzypczak M, Ginalski K, Rowicka M: **Strategies for achieving high**
853   **sequencing accuracy for low diversity samples and avoiding sample**
854   **bleeding using illumina platform.** *PLoS One* 2015, **10:**e0120520.

855   44.   Earl JP, Adappa ND, Krol J, Bhat AS, Balashov S, Ehrlich RL, Palmer JN,
856   Workman AD, Blasetti M, Sen B, et al: **Species-level bacterial community**
857   **profiling of the healthy sinonasal microbiome using Pacific Biosciences**
858   **sequencing of full-length 16S rRNA genes.** *Microbiome* 2018, **6:**190.

859   45.   Beye M, Bakour S, Le Dault E, Rathored J, Michelle C, Cadoret F, Raoult D,

860   Fournier PE: **Peptoniphilus lacydonensis sp. nov., a new human-associated**

861   **species isolated from a patient with chronic refractory sinusitis.** *New*

862   *Microbes New Infect* 2018, **23:**61-69.

863   46.   Callahan BJ, Wong J, Heiner C, Oh S, Theriot CM, Gulati AS, McGill SK,

864   Dougherty MK: **High-throughput amplicon sequencing of the full-length 16S**

865   **rRNA gene with single-nucleotide resolution.** *Nucleic Acids Res* 2019.

866   47.   Nguyen NP, Mirarab S, Liu B, Pop M, Warnow T: **TIPP: taxonomic identification**

867   **and phylogenetic profiling.** *Bioinformatics* 2014, **30:**3548-3555.

868   48.   Allard G, Ryan FJ, Jeffery IB, Claesson MJ: **SPINGO: a rapid species-classifier**

869   **for microbial amplicon sequences.** *BMC Bioinformatics* 2015, **16:**324.

870   49.   Edgar RC: **SINTAX: a simple non-Bayesian taxonomy classifier for 16S and**

871   **ITS sequences.** *bioRxiv* 2016**:**074161.

872   50.   Gao X, Lin H, Revanna K, Dong Q: **A Bayesian taxonomic classification**

873   **method for 16S rRNA gene sequences with improved species-level accuracy.**

874   *BMC Bioinformatics* 2017, **18:**247.

875   51.   Liland KH, Vinje H, Snipen L: **microclass: an R-package for 16S taxonomy**

876   **classification.** *BMC Bioinformatics* 2017, **18:**172.

877   52.   Matias Rodrigues JF, Schmidt TSB, Tackmann J, von Mering C: **MAPseq: highly**

878   **efficient k-mer search with confidence estimates, for rRNA sequence**

879   **analysis.** *Bioinformatics* 2017, **33:**3808-3810.

880   53.   Bokulich NA, Kaehler BD, Rideout JR, Dillon M, Bolyen E, Knight R, Huttley GA,

881   Gregory Caporaso J: **Optimizing taxonomic classification of marker-gene**

amplicon sequences with QIIME 2's q2-feature-classifier plugin. *Microbiome*

2018, **6:**90.

54.   Zheng Q, Bartow-McKenney C, Meisel JS, Grice EA: **HmmUFOtu: An HMM and**

phylogenetic placement based ultra-fast taxonomic assignment and OTU

picking tool for microbiome amplicon sequencing studies. *Genome Biol* 2018,

19:82.

55.   Kozich JJ, Westcott SL, Baxter NT, Highlander SK, Schloss PD: **Development of**

a dual-index sequencing strategy and curation pipeline for analyzing

amplicon sequence data on the MiSeq Illumina sequencing platform. *Appl*

Environ Microbiol 2013, **79:**5112-5120.

56.   Hausser J, Strimmer K: **Entropy inference and the James-Stein estimator, with**

application to nonlinear gene association networks. *J Mach Learn Res*

2009**:**1469-1484.

57.   Allen HK, Bayles DO, Looft T, Trachsel J, Bass BE, Alt DP, Bearson SM, Nicholson

T, Casey TA: **Pipeline for amplifying and analyzing amplicons of the V1-V3**

region of the 16S rRNA gene. *BMC Res Notes* 2016, **9:**380.

58.   Wingett SW, Andrews S: **FastQ Screen: A tool for multi-genome mapping and**

quality control. *F1000Res* 2018, **7:**1338.

59.   Katoh K, Misawa K, Kuma K, Miyata T: **MAFFT: a novel method for rapid**

multiple sequence alignment based on fast Fourier transform. *Nucleic Acids*

Res 2002, **30:**3059-3066.

60.   Price MN, Dehal PS, Arkin AP: **FastTree: computing large minimum evolution**
trees with profiles instead of a distance matrix. *Mol Biol Evol* 2009, **26:**1641-
1650.

61.   Grice EA, Kong HH, Conlan S, Deming CB, Davis J, Young AC, Bouffard GG,
Blakesley RW, Murray PR, Green ED, et al: **Topographical and temporal**
diversity of the human skin microbiome. *Science* 2009, **324:**1190-1192.

62.   Kong HH, Oh J, Deming C, Conlan S, Grice EA, Beatson MA, Nomicos E, Polley
EC, Komarow HD, Murray PR, et al: **Temporal shifts in the skin microbiome**
associated with disease flares and treatment in children with atopic
dermatitis. *Genome research* 2012, **22:**850-859.

63.   Oh J, Conlan S, Polley EC, Segre JA, Kong HH: **Shifts in human skin and nares**
microbiota of healthy children and adults. *Genome medicine* 2012, **4:**77.

64.   Findley K, Oh J, Yang J, Conlan S, Deming C, Meyer JA, Schoenfeld D, Nomicos
E, Park M, Kong HH, Segre JA: **Topographic diversity of fungal and bacterial**
communities in human skin. *Nature* 2013, **498:**367-370.

65.   Oh J, Freeman AF, Park M, Sokolic R, Candotti F, Holland SM, Segre JA, Kong
HH: **The altered landscape of the human skin microbiome in patients with**
primary immunodeficiencies. *Genome research* 2013, **23:**2103-2114.

66.   Oh J, Byrd AL, Deming C, Conlan S, Kong HH, Segre JA: **Biogeography and**
individuality shape function in the human skin metagenome. *Nature* 2014,
514:59-64.

67.   Pei Z, Bini EJ, Yang L, Zhou M, Francois F, Blaser MJ: **Bacterial biota in the**
human distal esophagus. *Proc Natl Acad Sci U S A* 2004, **101:**4250-4255.

68. Pei Z, Yang L, Peek RM, Jr Levine SM, Pride DT, Blaser MJ: **Bacterial biota in**

reflux esophagitis and Barrett's esophagus. *World J Gastroenterol* 2005,

11:7277-7283.

69. Harris JK, De Groote MA, Sagel SD, Zemanick ET, Kapsner R, Penvari C, Kaess

H, Deterding RR, Accurso FJ, Pace NR: **Molecular identification of bacteria in**

bronchoalveolar lavage fluid from children with cystic fibrosis. *Proc Natl*

Acad Sci U S A 2007, **104:**20529-20533.

70. van der Gast CJ, Walker AW, Stressmann FA, Rogers GB, Scott P, Daniels TW,

Carroll MP, Parkhill J, Bruce KD: **Partitioning core and satellite taxa from within**

cystic fibrosis lung bacterial communities. *ISME J* 2011, **5:**780-791.

71. Flanagan JL, Brodie EL, Weng L, Lynch SV, Garcia O, Brown R, Hugenholtz P,

DeSantis TZ, Andersen GL, Wiener-Kronish JP, Bristow J: **Loss of bacterial**

diversity during antibiotic treatment of intubated patients colonized with

Pseudomonas aeruginosa. *J Clin Microbiol* 2007, **45:**1954-1962.

72. Perkins SD, Woeltje KF, Angenent LT: **Endotracheal tube biofilm inoculation of**

oral flora and subsequent colonization of opportunistic pathogens. *Int J Med*

Microbiol 2010, **300:**503-511.

73. Shelef KM: **Ecology in the dentist's chair: patterns of biogeography and**

stability in human subgingival microbial communities. Stanford University,

Department of Biology; 2013.

74. O'Leary NA, Wright MW, Brister JR, Ciufo S, Haddad D, McVeigh R, Rajput B,

Robbertse B, Smith-White B, Ako-Adjei D, et al: **Reference sequence (RefSeq)**

database at NCBI: current status, taxonomic expansion, and functional

annotation. *Nucleic Acids Res* 2016, **44:**D733-745.

 FIGURE LEGENDS.

Figure 1. 16S rRNA gene V1-V3 region sequences do not require overlap to provide

maximal information for human aerodigestive tract-associated bacteria. (**a**) Rank

order of eHOMD taxa based on the nucleotide length of regions V1-V3 (purple), V1-V2

(orange) and V3 of the 16S rRNA gene. (**b**) Shannon Entropy (H) across the 16S rRNA

gene V1-V3 region for all taxa in eHOMD. For easier visualization, bars are color-coded

in gray scale based on their entropy values, i.e., the taller a bar is the darker it is. The

percentage of eHOMD-derived simulated reads that can be classified with the

FL_eHOMDrefs training set at bootstrap values from 70 to 100 (see key) using (**c**) a fixed

read length of 350 bp from primer V1 and variable read lengths from primer V3 or (**d**) a

fixed read length of 200 bp from primer V3 and variable read lengths from primer V1.

Figure 2. Schematic representation of the steps to generate sequential habitat-

specific training sets. (**a**) The *FL_eHOMDrefs_TS* training set contains all full-length

eHOMDrefs (thick lines) from eHOMDv15.1 together with their respective taxonomic

assignment. When only one read represents each taxon (M=1) a given k-mer (green

fragment) can only be either present (1) or absent (0). (**b**) A higher number of sequences

per taxon (M) allows for better resolution on the assignment, with the presence of a given

k-mer (green fragment) across each cluster of reads (w_i) being represented as a

proportion out of the total number of reads in that taxon (M). Therefore, to better represent

the known sequence diversity of the 16S rRNA gene(s) for each taxon, the training set

FL_Compilation_TS includes clusters of sequences (thin lines) recovered from the NCBI

nonredundant nucleotide (nr/nt) database that matched with 99% identity and ≥ 98%

coverage (see methods) to each eHOMDref (thick line). (**c**) The training set

V1V3_Raw_TS is a V1-V3 trimmed version of the **FL_Compilation_TS** training set. The

schematic illustrates how trimming to this region leads to identical reads (purple lines)

having two different taxonomic designations. Here, G is genus and species are labeled

as A or B. (**d**) To construct the **V1V3_Curated_TS** training set, identical V1-V3 sequences

in the **V1V3_Raw_TS** training set were collapsed into one. If identical sequences came

from more than one taxon (purple), species-level names of all taxa involved were

concatenated (AB). (**e**) The **V1V3_Supraspecies_TS** training set includes the same

sequences that the **V1V3_Raw_TS** training set; however, the headers in the fasta file

include the supraspecies taxon (AB) as an extra level between the genus (G) and species

taxonomic levels (A, B or AB), as illustrated here.

Figure 3. The *FL_Compilation_TS* training set provides higher classification

percentages with a lower error rate. The naïve Bayesian RDP Classifier was used with

bootstrap values ranging from 50 to 100. (**a**) The percentage of eHOMD-derived

simulated reads classified using the **FL_eHOMDrefs_TS** training set (purple) versus the

FL_Compilation_TS training set (orange). (**b**) The percentage of classified reads that

were misclassified (i.e., reads for which the assigned taxonomic identity was different

than the known identity of the original sequence from which the simulated read was

derived).

Figure 4. Trimming the training set to the specific sequenced region further

reduces the error rate. (**a**) The percentage of eHOMD-derived simulated reads classified

at species level using the **FL_Compilation_TS** (orange) training set compared to

subsequent trimmed versions ***V1V3_Raw_TS*** (green) and ***V1V3_Curated_TS*** (red). (**b**)

The percentage of classified reads that were misclassified with each of these three

training sets. The naïve Bayesian RDP Classifier was used with bootstrap values ranging

from 50 to 100. (**c**) This graph, which is specific to the eHOMD training set construction

(**V1V3_eHOMDSim_250N100** dataset), indicates how researchers can determine the

bootstrap value to use with the naïve Bayesian RDP Classifier by deciding an acceptable

level of the % of reads misclassified (blue line; e.g., 0.5%) and/or of the % of reads that

are not classified (red line).

Figure 5. Addition of a supraspecies level to the training set increases the

percentage of classified reads. (**a**) The percentage of eHOMD-derived simulated reads

classified at species/supraspecies level using the ***V1V3_Curated_TS*** training set (red)

versus the ***FL_Supraspecies_TS*** training set (blue). (**b**) Percentage of classified reads

that were misclassified with each of these TS. The naïve Bayesian RDP Classifier was

used with bootstrap values ranging from 50 to 100.

1011

ADDITIONAL FILES.

Additional File 1: IlluminaQC.pdf. Quality Phred score plots of representative 16S rRNA gene V1-V3 region Illumina runs.

Additional file 2: V1V3_eHOMDSim_250N100.fa. The simulated eHOMD-derived **V1V3_eHOMDSim_250N100** dataset.

Additional file 3: eHOMDv15.1_FL_Compilation_TS.fa. The 16S rRNA gene full-length eHOMD training set (***FL_Compilation_TS***).

Additional file 4: eHOMDv15.1_V1V3_Supraspecies_TS.fa. The 16S rRNA gene V1-V3 eHOMD training set (***V1V3_Supraspecies_TS***).

Additional file 5: FL_sinonasal_SMRT_ASV.fa. Sequences of the resulting 204 ASVs in the Earl-Mell sinonasal 16S rRNA gene dataset (**FL_sinonasal_SMRT_ASV** dataset).

Additional file 6: Earl-Mell_sinonasal_analysis.xlsx with legend and tabs A-D. Species-level taxonomic assignment of the Earl-Mell sinonasal 16S rRNA gene dataset.

Additional file 7: V1V3_sinonasal_SMRT_ASV.fa. Sequences of the resulting 204 ASVs in the **FL_sinonasal_SMRT_ASV** dataset trimmed to the V1-V3 region (**V1V3_sinonasal_SMRT_ASV** dataset).

Additional file 8: V1V3_hADT_CL.fa. V1-V3 trimmed 16S rRNA gene human

aerodigestive tract clone library dataset (**V1V3_hADT_CL** dataset).

Additional file 9: V1V3_HMPnares_ASV.fa. ASVs derived from the HMP nares 16S

rRNA gene V1-V3 dataset (**V1V3_HMPnares_ASV** dataset).

Additional file 10: V1V3_Primers.xlsx. Sequencing primers used to amplify the V1-V3

region of the 16S rRNA gene.

Additional file 11: retrieveSegment.py. Custom script developed to generate a trimmed

version of a training set (in our example to positions 40-880 in the gapped eHOMDrefs

alignment) from a compilation of 16S rRNA gene full-length sequences.

Additional file 12: Simulated_R2_350_R1_20-200.7z. Simulated eHOMD-derived

dataset versions with R2 fixed at 350 bp and R1 fragments from the V3 primer ranging

from 20 to 200 bp.

Additional file 13: Simulated_R2_140-350_R1_200.7z. Simulated eHOMD-derived

dataset versions with R1 fixed at 200 bp and R2 fragments from the V1 primer ranging

from 140 to 350 bp.

Additional file 14: FL_hADT_CL.fa. Full-length 16S rRNA gene human aerodigestive

tract clone library dataset (**FL_hADT_CL** dataset).

Additional file 15: eight2seven.R. Custom-written R function that converts the

dada2::assignTaxonomy() output from eight to seven taxonomic levels for compatibility

with downstream applications.

A

$$P(w_i|T_A) = \frac{1 + P_i}{M + 1}$$

$$P(w_i|T_B) = \frac{0 + P_i}{M + 1}$$

k-mer (w_i)

TAXON A

TAXON B

FL_eHOMDrefs_TS

B

$$P(w_i|T_A) = \frac{m(w_i + P_i)}{M + 1}$$

$$P(w_i|T_B) = \frac{m(w_i + P_i)}{M + 1}$$

TAXON A

TAXON B

FL_Compilation_TS

C

G:A

TAXON A

G:A
G:B

TAXON B

G:B

V1V3_Raw_TS

D

G:A

TAXON A

G:AB

TAXON B

G:B

V1V3_Curated_TS

E

G:AB:A

TAXON A

G:AB:AB

TAXON B

G:AB:B

V1V3_Supraspecies_TS