Construction of habitat-specific training sets to achieve species-level assignment

in 16S rRNA gene datasets

Isabel F. Escapa[a,b,c,§] (Isabel.FernandezEscapa@bcm.edu), Yanmei Huang[a,b,§]

(yhuang2@gmail.com), Tsute Chen[a,b] (tchen@forsyth.org), Maoxuan Lin[a]

(mlin8@uncc.edu), Alexis Kokaras[a] (akorakas@forsyth.org), Floyd E. Dewhirst[a,b]

(fdewhirst@forsyth.org), Katherine P. Lemon[a,c,d,e*] (Katherine.lemon@bcm.edu)

[a]Forsyth Institute (Microbiology), Cambridge, Massachusetts, USA

[b]Department of Oral Medicine, Infection & Immunity, Harvard School of Dental Medicine,

Boston, Massachusetts, USA

[c]Alkek Center for Metagenomics & Microbiome Research, Department of Molecular

Virology & Microbiology, Baylor College of Medicine, Houston, Texas, USA

[d]Division of Infectious Diseases, Boston Children's Hospital, Harvard Medical School,

Boston, Massachusetts, USA

[e]Section of Infectious Diseases, Department of Pediatrics, Texas Children's Hospital and

Baylor College of Medicine, Houston, Texas, USA

[§] These authors contributed equally to this work.

*Correspondence: Katherine.lemon@bcm.edu

ABSTRACT

Background: The low cost of 16S rRNA gene sequencing facilitates population-scale

molecular epidemiological studies. Existing computational algorithms can parse 16S

rRNA gene sequences to high-resolution Amplicon Sequence Variants (ASVs), which

represent consistent labels comparable across studies. Assigning these ASVs to species-

level taxonomy strengthens the ecological and/or clinical relevance of 16S rRNA gene-

based microbiota studies and further facilitates data comparison across studies.

Results: To achieve this, we developed a broadly applicable method for constructing

high-resolution training sets based on the phylogenic relationships among microbes found

in a habitat of interested. When used with the naïve Bayesian Ribosomal Database

Project (RDP) Classifier, this training set achieved species/supraspecies-level taxonomic

assignment of 16S rRNA gene-derived ASVs. The key steps for generating such a

training set are: 1) constructing an accurate and comprehensive phylogenetic-based,

habitat-specific database; 2) compiling multiple 16S rRNA gene sequences to represent

the natural sequence variability of each taxon in the database; 3) trimming the training

set to match the sequenced regions, if necessary; and 4) placing species sharing closely

related sequences into a supraspecies taxonomic level to preserve subgenus-level

resolution. As proof of principle, we developed a V1-V3 region training set for the bacterial

microbiota of the human aerodigestive tract using the full-length 16S rRNA gene

reference sequences compiled in our expanded Human Oral Microbiome Database

(eHOMD). We also overcame technical limitations to successfully use Illumina sequences

for the 16S rRNA gene V1-V3 region, the most informative segment for classifying

bacteria native to the human aerodigestive tract. Finally, we generated a full-length

eHOMD 16S rRNA gene training set, which we used in conjunction with an independent

PacBio Single Molecule, Real-Time (SMRT)-sequenced sinonasal dataset to validate the

representation of species in our training set. This also established the effectiveness of a

full-length training set for assigning taxonomy of long-read 16S rRNA gene datasets.

Conclusion: Here, we present a systematic approach for constructing a phylogeny-

based, high-resolution, habitat-specific training set that permits species/supraspecies-

level taxonomic assignment to short- and long-read 16S rRNA gene-derived ASVs. This

advancement enhances the ecological and/or clinical relevance of 16S rRNA gene-based

microbiota studies.

Keywords: training set; naïve Bayesian RDP Classifier; species-level taxonomy; 16S

rRNA gene; V1-V3; habitat-specific database; microbiome; eHOMD; nasal; aerodigestive

tract

BACKGROUND.

In microbiota studies of most ecosystems and/or habitats, achieving species- or strain-

level identification of constituents improves the ecological and/or clinical relevance of the

results compared with genus-level identification. For example, species-level identification

is often critically important for host-associated microbial communities because these

communities frequently include commensal and pathogenic species of the same genus,

e.g., [1, 2], with the caveat that strain-level variation in pathogenicity also exists, e.g., [3].

Additionally, some microbial genera include species that are site specialists and inhabit

distinct niches of a given environment [4]. High-throughput close-to-full-length 16S rRNA

gene sequencing (e.g., circular consensus sequences from PacBio Single Molecule,

Real-Time (SMRT) sequencing) and metagenomic whole genome sequencing (WGS)

hold promise for species- and strain-level microbiota studies. However, the easier

accessibility, and lower cost, of 16S rRNA gene short-read sequencing makes population-

scale (i.e., thousands of samples) molecular epidemiological studies of bacterial

microbiota of humans, other animals, plants, and the environment broadly feasible now.

A caveat to this is that the majority of published short-read 16S rRNA gene sequencing

studies use read clustering at a percent similarity that constrains resolution to the genus

level, i.e., 97% identity. Indeed, recent reviews on best practices and benchmarking for

16S rRNA gene microbiota studies focus on genus-level operational taxonomic unit

(OTU) analysis, e.g., [5-7]. However, newer algorithms, many of which are not based on

similarity thresholds, allow single-nucleotide resolution and can parse 16S rRNA gene

short-read sequences into species- or strain-level resolution phylotypes, usually called

amplicon sequence variants (ASVs) (e.g., MED (Minimal Entropy Decomposition) [8, 9],

DADA2 (Divisive Amplicon Denoising Algorithm) [10, 11] and UNOISE [12, 13], among

others [14, 15]). Another limitation of short-read 16S rRNA microbiome studies is that the

choice of the 16S rRNA gene region(s) sequenced places an upper bound on the degree

of species-level resolution that is achievable within a dataset [16-19]. Therefore, it is

critical to determine which regions provide the most information for distinguishing

bacterial species that are common to that specific ecosystem. For the habitats within the

human aerodigestive tract, i.e., the nasal passages, sinuses, throat, mouth, esophagus,

as well as the lower respiratory tract, we previously showed that many more taxa are

distinguishable at the species level with the V1-V3 region than with the commonly used

V3-V4 region of the 16S rRNA gene [20]. Therefore, we have developed a method that,

by combining the "reusability, reproducibility and comprehensiveness" of ASVs [11, 13]

and the selection of highly informative regions of the 16S rRNA gene, maximizes 16S

rRNA gene short-read sequencing potential to achieve sub-genus level resolution

taxonomic assignment.

Microbial databases encompassing broad phylogenetic diversity, such as SILVA [21, 22],

RDP [23] and Greengenes [24], serve the key role of being applicable to myriad different

habitats. However, this valuable breadth comes with the trade-off of inclusion of

taxonomically misannotated 16S rRNA gene sequences. For example, Edgar estimated

annotation error rates as high as ~10-17% in these comprehensive databases [25]. SILVA

and RDP continue to undergo regular updates and contain a broadly expansive and

comprehensive record of 16S rRNA gene sequences from all explored habitats, whereas

Greengenes was last updated in 2013. For habitats that have yet to be deeply

interrogated, the access to this breadth outweighs the risk of misclassification due to

annotation error. However, once a habitat is sufficiently explored through sequencing,

creation of a habitat-specific database enables accurate fine-level phylogenetic resolution

for taxonomic assignment to ASVs [20, 26-35]. Existing habitat-specific databases are

constructed with different methods and can be used to assign taxonomy via different

approaches, as in the following three examples. First, there are stand-alone habitat-

specific databases consisting of curated collections of close-to-full-length 16S rRNA gene

sequences compiled both from other repositories and by generating new sequences from

the habitat of interest, e.g., eHOMD for the human aerodigestive tract [20, 26, 36], HITdb

for the human gut [29] and RIM-DP for rumen [28]. Second, custom addition of compiled

sequences from a specific habitat of interest can be used to augment a broad general

database, e.g., HBDB for honey bee [27], DictDB for termite and cockroach gut [33],

SILVA19Rum for rumen [35] and MiDAS for activated sludge [30, 32]. Third, both a

general and a habitat-specific database can be combined in the same pipeline, e.g., for

human-associated genera with pathogenic members [37], for freshwater (FreshTrain with

the TaxAss workflow [34]) and the multistage blastn workflow with eHOMD [38]. Many of

these databases are formatted for use as training sets to train classifier algorithms for

taxonomy assignment.

The naïve Bayesian RDP Classifier [39] is one of several effective algorithms for

assigning taxonomy. (For benchmarking and comparison with other methods, see [40-

43]). This type of supervised learning algorithm requires a training set, which is a set of

input-output examples to learn a function that can be used to make predictions [44]. In

this case, sequences are input and taxonomic assignments are output. Properly formatted

versions of the broad 16S rRNA gene databases SILVA, RDP and Greengenes are

available to train the most popular implementations of the naïve Bayesian RDP Classifier.

The quality of the training set strongly influences taxonomic assignment and habitat-

specific training sets have been developed to increase accuracy of taxonomic

assignments [27, 33, 40-42, 45]. However, the resolution of available training sets is

mostly limited to the genus level. An exception is the manually curated subset of the

Greengenes database corresponding to 89 clinically relevant bacterial genera that was

used to assign species-level taxonomy of full-length 16S rRNA gene sequences of clinical

isolates [46]. Notwithstanding, species-level taxonomy assignment of short-read 16S

rRNA gene datasets remains a challenge.

We hypothesized that we could develop a method to rapidly generate a habitat-specific

training set to leverage the strength of the naïve Bayesian RDP Classifier to consistently

achieve species- or supraspecies (i.e., subgenus)-level taxonomic assignment of ASVs

starting from a locally comprehensive, phylogeny-based, high-resolution (i.e., separated

at ≥ 98.5% identity) set of curated reference sequences with distinct taxonomic names.

Here, we show that the use of the naïve Bayesian RDP Classifier with a training set in

which each taxon is represented by a collection of highly similar sequences that captures

the natural variability of each species resulted in accurate species-level taxonomic

assignment of short-read and long-read sequences of the 16S rRNA gene. This

represents a methodological advancement. Our systematic approach for generating

training sets is applicable to any ecosystem/habitat of interest and is summarized in

Figure 1. This approach requires compiling high-quality close-to-full-length 16S rRNA

gene datasets from a habitat (**Figure 1A**). These compiled datasets are then used to

identify curated reference sequences to build a 16S rRNA gene database (**Figure 1B**)

from which training sets for that habitat are derived (**Figure 1C**).

To test our hypothesis, we developed and validated short- and long-read training sets for

the microbiota of the human aerodigestive tract (mouth, nasal passages, sinuses, throat,

and esophagus) using our expanded Human Oral Microbiome Database (eHOMD). This

database was originally created and later expanded to serve as a resource for the

community of investigators generating datasets to study habitats within the human

aerodigestive tract [20, 26, 36]. In addition to 16S rRNA gene reference sequences

(eHOMDrefs), it also includes genomic and proteomic data. (It also works well for the

lower respiratory tract [20].) The lack of proper taxonomical representation in traditional

databases is a challenge in predicting taxonomic assignments [43]. A strength of the

eHOMD is that, by placing 16S rRNA gene reference sequences for each Human

Microbial Taxon (HMT) on a phylogenetic tree

(http://ehomd.org/index.php?name=HOMD&show_tree=_), as-yet unnamed or

uncultivated species are defined based on sequence identity and added to the phylogeny

using a provisional naming scheme that permits taxonomic assignment for cross-study

comparison [26]. Also, sequences that are misnamed in other databases are easily

identified and given a correct designation in eHOMD. Another key strength of eHOMD is

that it is locally comprehensive often allowing approximately 95% of sequences from V1-

V3 aerodigestive tract datasets to be assigned to the taxonomy [20].

RESULTS.

Compiling closely-related sequences for each taxon in a training set improves the

accuracy of species-level taxonomic classification. Genus-level taxonomic

assignment is not an inherent limitation of the naïve Bayesian RDP Classifier. Rather,

taxonomic assignment to 16S rRNA gene short reads is limited by both the resolution to

which sequences in datasets are parsed and by the nature of the training set used. The

former is overcome by using approaches such as oligotyping/MED [8, 9], DADA2 [10, 11]

or unoise2 [12, 25] to parse sequence variants at high resolution. We hypothesized that

the limitations inherent in training sets could also be overcome.

The naïve Bayesian RDP Classifier algorithm indicates that a training set with a larger

number of sequences representing each taxon will result in more confident taxonomic

assignment [39]. Based on the conditional probability for a member of a taxon (T), the

higher the occurrence of a given distinguishing "k-mer" (word or w_i) in the training set, the

greater the confidence with which assignment of that taxon is made, i.e., more sequences

can be classified unambiguously. Thus, as the number of sequences (M) for each taxon

in the training set increases (**Figure 2A vs. 2B**), the number of accurate assignments

should increase. (See **Additional File 1** for a more detailed explanation.) In support of

this, Werner and colleagues found more sequence counts result in more assignments

[45]. Therefore, to systematically increase M, we used each of the reference sequences

in eHOMD, i.e., the eHOMDrefs, as bait to capture closely matching, publicly available

sequences and combined the resulting compilation of sequences for each taxon into a

close-to-full-length compilation training set (***FL_Compilation_TS***) that reflects the

currently known 16S rRNA gene sequence variability for each taxon, both natural and

sequencing-error derived (**Additional File 2**).

To evaluate the performance of the ***FL_Compilation_TS*** and for further method

optimization, we created the simulated dataset **V1V3_eHOMDSim_250N100** by

introducing a 1% error rate in a V1-V3 trimmed version of our training set sequences.

(See Methods for details and **Additional File 3** for the dataset itself.) This simulated

dataset aims to mimic real sequencing short-reads similar to the ones that can be

obtained with our method for achieving highly informative 16S rRNA gene V1-V3 region

sequencing data using Illumina MiSeq, which is detailed in **Additional File 4**. We then

assessed the percentage of reads in the simulated dataset **V1V3_eHOMDSim_250N100**

that classified at the species-level at incremental bootstrap values from 50 to 100 using

the training set *FL_Compilation_TS* (**Figure 3A,** orange bars) compared with the training

set *FL_eHOMDrefs_TS* (**Figure 3A,** purple bars), which consists of only the eHOMDrefs.

Doing this, we observed an increase in the percentage of reads that classified at species-

level with the compilation TS except at a bootstrap value of 100. We postulate that the

additional sequences classified with the *FL_eHOMDrefs_TS* TS at a bootstrap of 100 are

misclassified sequences. A higher rate of misclassification is expected with the training

set *FL_eHOMDrefs_TS*, since it includes only a few representative sequences for each

taxon. Therefore, we next assayed for any misclassifications. At each bootstrap threshold,

the percentage of reads that were misclassified (i.e., reads for which the assigned

taxonomic identity was different than the known identity of the original sequence from

which the simulated read was derived) was at least 50% lower using the training set

FL_Compilation_TS (**Figure 3B**, orange line) than with the training set

FL_eHOMDrefs_TS (**Figure 3B**, purple line). Thus, classification of the dataset

V1V3_eHOMDSim_250N100 showed a reduced error rate and increased confidence

level when using a training set consisting of a compilation of closely related sequences

rather than one consisting of only one or a few reference sequences for each taxon.

Moving towards an appropriate short-read fragment training set. The training set

FL_Compilation_TS consisted of close-to-full-length 16S rRNA gene sequences. We

hypothesized that the presence of k-mers outside the V1-V3 region in the training set

might lead to misclassifications when using it with a V1-V3 region dataset. Supporting

this, when using a training set based on a large general database, trimming reference

sequences to match the sequenced region increases the number of sequences that are

assigned taxonomy [45]. Therefore, we trimmed the sequences in the training set

FL_Compilation_TS to cover only the V1-V3 region generating training set

V1V3_Raw_TS (**Figure 2C**). Using this there was no gain in the percentage of reads in

the simulated dataset **V1V3_eHOMDSim_250N100** classified to the species-level

(**Figure 4A**, green bar). Moreover, we observed an increase in the percentage of

misclassified reads (**Figure 4B**, green line), i.e. the assignment accuracy decreased.

Therefore, we next determined why the use of appropriate short-read fragments in this

training set paradoxically decreased confidence and accuracy of species-level

assignment and resolved the issue.

Combining closely related, indistinguishable taxa into supraspecies decreases the

error rate for a short-read training set. Considering the possible explanations for the

above paradox, we realized that taxa with distinct full-length 16S rRNA gene sequences

can have identical V1-V3 sequences. In silico, using only V1-V3, 37 of the ~770 species-

level taxa in eHOMD are no longer distinguishable from at least one other species at

100% identity [20]. Therefore, we hypothesized that the observed loss in accuracy using

training set *V1V3 _Raw_TS* was due to identical sequences with more than one species

name, e.g., *Veillonella parvula* and *Veillonella dispar* [20]. To solve this problem, we

removed duplicate sequences and assigned a combined name, i.e., a supraspecies name

such as *Veillonella* parvula_dispar, to the remaining unique sequence (**Figure 2D**). This

resulted in the training set *V1V3_Curated_TS*, which showed improved accuracy

compared with both the *FL_Compilation_TS* and the *V1V3_Raw_TS* (**Figure 4B**, red

line). However, this improvement came at a cost of a 0.7 to 4.4 % decrease in the reads

assigned supraspecies- or species-level taxonomy at each bootstrap threshold (**Figure**

4A, red bar). This trade-off can be illustrated by graphing at each bootstrap threshold the

percentage of reads from the simulated **V1V3_eHOMDSim_250N100** dataset that were

misclassified versus confidently assigned species-level taxonomy using the

V1V3_Curated_TS with the naïve Bayesian RDP Classifier (**Figure 4C**).

Maximizing performance of the naïve Bayesian RDP Classifier for subgenus-level

taxonomic assignment of short-read sequences requires both insertion of

supraspecies as a taxonomic level and setting a threshold bootstrap. Two steps

were required to reap the benefits of using the supraspecies definition. First, formally

inserting supraspecies as a taxonomic level between genus and species in the name

header for each sequence in the training set, which yielded the training set

V1V3_Supraspecies_TS (**Figure 2E; Additional File 5**). Second, establishing the

bootstrap cut-off at which a sequence is not assigned at the species level so that the

naïve Bayesian RDP Classifier will then default to the supraspecies level, rather than

defaulting to genus, allowing for a higher percentage of reads to be assigned (**Figure 5A**,

blue bar). This latter step preserves subgenus level information encoded in the ASVs.

This choice inevitably involves a trade-off between accuracy and percentage of reads

classified below genus level, e.g., see **Figure 4C**. For our purposes, we chose a

conservative bootstrap value of 70 (**Figure 5B,** blue line). With the simulated data, for

which the truth is known, this gave an error rate of around 0.05%. Of note, although one

common bootstrap setting for the naïve Bayesian RDP Classifier is 50, we use of a more

conservative value for species-level taxonomic assignment with the

V1V3_Supraspecies_TS.

Using an independent sinonasal dataset validated the performance of the eHOMD

training set. We next validated the performance of the eHOMD training set against a

dataset of close-to-full-length 16S rRNA gene sequences from sinonasal samples. Very

importantly, these sequences are independent of the sequences recruited to build the

training set. Earl and colleagues performed PacBio SMRT sequencing of close-to-full-

length 16S rRNA genes from multiple sinonasal samples from each of 12 adults without

sinus inflammation who were undergoing removal of a pituitary adenoma [47]. Because

this dataset was deposited in the SRA, these sequences were not present in the NCBI

nr/nt sequence repository (from which sequences were recruited for the eHOMD training

set) and therefore not used in the generation of the eHOMD training set. We used the

DADA2 pipeline for PacBio SMRT reads [48] to denoise these sequences and identify the

relative abundance of each ASV in this dataset (**FL_sinonasal_SMRT_ASV; Additional**

File 6). Next, we followed a three-pronged approach to assess the validity of the eHOMD

training set for use with this fully independent sinonasal dataset.

First, we compared the best match by blastn, as a proxy for taxonomic assignment for

these ASVs, using eHOMD compared to using NCBI 16S Microbial to identify any taxa in

the dataset that might be missing in eHOMD, and thus the training set (**Table 1;**

Additional File 7A). A detailed comparison (**Additional File 7B**), showed that 50 ASVs,

corresponding to 11.1% of the total reads, were differentially assigned by blastn (98.5%

identity cutoff) against eHOMDv15.1 versus against NCBI 16S Microbial. Of these 50

ASVs, 33 were assigned to taxa with an HMT (Human Microbial Taxon) # as a provisional

species designation. The majority (17/33) were assigned to *Peptoniphilus* sp. HMT-187,

which corresponded in the NCBI 16S Microbial blastn output to *Peptoniphilus*

lacydonensis and accounted for 7.6 % of the total reads. Similarly, *Peptoniphilus* sp.

HMT-187 was 11th in total reads across the nostril samples of 210 HMP (Human

Microbiome Project) participants [20]. The new species name *Peptoniphilus lacydonensis*

was published in 2018 and is formally recognized [49]; therefore, it is now linked to HMT-

187 in eHOMD. Of the remaining 17 ASVs, 8 were mismatches between closely related

Streptococcus species. Only 6 ASVs were nonassigned (NA) using eHOMD, thus,

eHOMD included the vast majority (99.7%) of taxa present in the Earl-Mell sinonasal

dataset. We note that based on recent additions both eHOMD and NCBI 16S Microbial

allowed correct assignment of ASVs to *Lawsonella clevelandensis*, which previously

might be misidentified by blastn best match as a Dietzia species, and to *Neisseriaceae*

G-1 bacterium HMT-327, which before receiving a stable taxonomic designation in

eHOMD might be misidentified by blastn best match as a *Snodgrassella* species [20].

Second, we compared species-level assignment of the dataset

FL_sinonasal_SMRT_ASV using blastn against eHOMD versus the naïve Bayesian

RDP Classifier with the full-length eHOMD training set *FL_Compilation_TS*. Less than

2% (1.91%) of the total reads in the dataset **FL_sinonasal_SMRT_ASV**, which are

represented by 25 ASVs, were differentially assigned species-level taxonomy by these

approaches (**Table 1; Additional File 7A**). There was no clear pattern to this differential

assignment (**Additional File 7C**). This served to validate the use of the full-length

eHOMD training set *FL_Compilation_TS* and demonstrated that our approach is an

effective method for assigning species-level taxonomy to close-to-full-length 16S rRNA

gene sequences such as those derived from PacBio SMRT sequencing.

Third, based on the above, we used naïve Bayesian RDP Classifier-derived assignments

with the training set *FL_Compilation_TS* as a proxy for the true species representation

in the dataset **FL_sinonasal_SMRT_ASV**. We then used these to assess the

performance of the training set *V1V3_Supraspecies_TS* for assigning species-level

taxonomy to the V1-V3 region sequences of the dataset **FL_sinonasal_SMRT_ASV**

(**V1V3_sinonasal_SMRT_ASV; Additional File 8**). There were seventeen V1-V3 ASVs

that were differentially assigned, corresponding to 1.64% of the reads (**Table 1;**

Additional File 7D). Of these 17 differentially-assigned ASVs, 5 belonged to a

supraspecies, a level not represented in the full-length training set *FL_Compilation_TS*.

Another 4 ASVs, all of which were present at very low relative abundance, had full-length

ASVs assigned to *Anaerococcus tetradius*, whereas the V1-V3 region was assigned to

Anaerococcus octavius, all with bootstrap values ≤ 92 (**Additional File 7A**). In contrast,

when 16S rRNA gene sequences were parsed into ASVs based on their full-length and

then cut to V1-V3, there was little to no species-level ambiguity (**Additional File 7D**).

Thus, the ambiguity observed with V1-V3 16S rRNA short reads most likely occurs at the

level of parsing into ASVs, due to fewer informative sequences, rather than at the

assignment step with the naïve Bayesian RDP Classifier and the eHOMD training set.

Table 1. The eHOMD training sets performed well for species/supraspecies

taxonomy assignment of an independent long-read 16S rRNA gene sinonasal

dataset.

	# ASVs	# Reads	% ASVs	% Reads
NCBI 16S Microbial blastn	178	140,455	87.3	97.3
eHOMD blastn	188	143,274	92.2	99.3
eHOMD FL_Compilation_TS	194	142,843	95.1	99.0

| eHOMD V1V3_Supraspecies_TS | 201 | 144,279 | 98.5 | 99.9 |

Table 1 Legend. Columns three and four indicate the % of ASVs and reads, respectively, assigned subgenus-level taxonomy using each of the four approaches tested.

The eHOMD training set outperforms both the SILVA and RDP training sets. Having validated the use of the eHOMD training set with an independent 16S rRNA gene sinonasal dataset (**Table 1**), we next compared the use of our taxonomic assignment approach with other currently available pipelines that are coupled with the RDP or SILVA databases. We used three different datasets for this: 1) we generated a V1-V3 dataset derived from a collection of human aerodigestive tract 16S rRNA gene clone libraries (**V1V3_hADT_CL; Additional File 9**); 2) the HMP 16S rRNA gene V1-V3 454-sequenced nostril dataset that we previously analyzed [20]; and 3) the close-to-full-length ASVs of the **FL_sinonasal_SMRT_ASV** dataset. We then assigned genus-level taxonomy to all of these using the naïve Bayesian RDP Classifier with a bootstrap threshold of 70 coupled with three different training sets: an eHOMD training set (V1-V3 or FL), RDP16 or SILVA132 (the latter two from https://benjjneb.github.io/dada2/training.html). The eHOMD training set resulted in a larger percentage of reads assigned to a specific genus for each dataset; however, all three training sets resulted in genus-level assignment of >90% of the sequences (**Table 2**). In contrast, a striking difference emerged between the different workflows when assigning taxonomy to species level. Our method of coupling the naïve Bayesian RDP Classifier with an eHOMD training set showed superior performance in terms of the percentage of reads classified compared to the exact string match method that is currently implemented in the DADA2 R Package in conjunction with SILVA132 or RDP16 (**Table 2**). As would be expected, the exact match algorithm

assigned a higher percentage of close-to-full-length ASVs than V1-V3 region ASVs to

taxonomy. The caveat being that these comprehensive databases have an estimated

annotation error rates as high as ~10-17% [25]. For the V1-V3 region ASVs, it also

performed much better with the V1-V3 sequences in the V1-V3 human aerodigestive tract

clone library dataset than with the HMP V1-V3 dataset. We speculate this occurred

because the close-to-full-length sequences from the human aerodigestive tract clone

library (**V1V3_hADT_CL**) dataset are part of both the RDP and SILVA databases,

whereas the HMP V1-V3 454 sequences are not.

Table 2. The eHOMD training set is superior for assigning species/supraspecies-

level taxonomy to short- and long-read human aerodigestive tract datasets.

		V1V3_hADT_CL	V1V3_HMPnares_ ASV[#]		FL_sinonasal_SMRT_ASV	
		(% reads)	(% ASVs)	(% reads)	(% ASVs)	(% reads)
eHOMD	Genus	100.0	95.5	98.9	99.5	100.0
	Species	100.0	93.9	98.5	95.1	99.0
SILVA	Genus	96.1	94.7	97.6	96.6	98.9
	Species	44.7*	4.1*	29.9*	18.6*	71.9*
RDP	Genus	93.2	90.2	92.2	94.1	98.5
	Species	38.5*	3.1*	27.5*	13.2*	60.6*

Table 2 Legend. *Exact match algorithm; [#] ASVs derived from the HMP nares V1-V3

dataset, as described in [20], constitute the **V1V3_HMPnares_ASV** dataset (**Additional**

File 10).

A key implication of these data is that our overall method yields comparable species-level

results for 16S rRNA gene sequencing of the human aerodigestive tract using V1-V3

short-read sequences, which is very cost effective, compared to using close-to-full-length

PacBio SMRT sequences. For example, it readily distinguished sequences of

Staphylococcus aureus and *Staphylococcus epidermidis*. Another implication is that for

species-level analysis of the microbiota of habitats lacking a high-resolution, accurate

16S rRNA gene database, PacBio SMRT sequencing coupled with the newly available

DADA2 PacBio pipeline [48] to generate ASVs followed by blastn against NCBI 16S

Microbial can provide effective species-level taxonomic assignment (**Table 1**). Of note,

the definition of supraspecies is dependent on the database and can vary for different

short-read 16S rRNA gene regions. As such, a separate training set needs to be

generated for each short-read region of interest. In addition, training sets need regular

maintenance in conjunction with the database and need to be regenerated with each

major revision of their associated database. In theory, other closed-reference methods

for assigning taxonomy could benefit from the addition of an intermediate taxonomic level

to preserve the highest level of resolution possible for that method, e.g., suprastrain

between species and strain for metagenomics if there are strains that are too closely

related to clearly distinguish.

CONCLUSIONS.

Here, we present a systematic approach for generating and validating habitat-specific

16S rRNA gene training sets to achieve species/supraspecies-level taxonomic

assignment for short- or long-read 16S rRNA gene sequences. We used the naïve

Bayesian RDP classifier with our training set; however, such a training set can be used

with other taxonomic classifiers [41, 42, 50-57]. Our training set-construction approach

includes several methodological advancements. First, we generated clusters of existing

close-to-full length 16S rRNA gene sequences at the 99% level (with ≥ 98% coverage)

around highly curated reference sequences. This collection of sequences for each taxon

represented the currently known sequence variability for each taxon and increased the

accuracy of taxonomic assignment using the naïve Bayesian RDP Classifier (**Figure 3**).

Second, we added an intermediate taxonomic level between genus and species, which

we dubbed supraspecies, to which we assigned taxa in which sequences overlapped

between two or more taxonomic clusters. This increased the percentage of sequences

assigned subgenus-level taxonomy by preventing the default of consigning difficult-to-

assign sequences to the genus level (**Figure 5**). The process of constructing a short-read

training set started with the generation of an effective close-to-full-length training set,

which could then be used for taxonomic assignment of long-read 16S rRNA gene

sequences such as those from clone libraries and from high-throughput long-read

sequencing. As a final critical step, we validated the composition of the eHOMD training

set using a PacBio SMRT-sequenced sinonasal dataset consisting of sequences

independent of those used to build the training set (**Table 1**). Facilitating

species/supraspecies-level analysis of 16S rRNA gene sequence datasets paves the way

for cost-effective, population-scale molecular epidemiological microbiota studies that can

achieve greater ecological/clinical relevance by reaching species level.

The successful implementation of a training set for species/supraspecies-level

assignment of 16S rRNA gene short-read (e.g., V1-V3) datasets involved a collaborative

give-and-take to iteratively optimize the sequencing protocol and the analysis workflow in

conjunction with each other. As a result, here, we also provided three specific protocol

recommendations for sequencing of the 16S rRNA gene V1-V3 region with the Illumina

MiSeq. As detailed in **Additional File 4**, first, we show that excellent taxonomic

assignment can be achieved with nonoverlapping Illumina reads from V1 and V3 using

our recommended sequencing protocol and taxonomic assignment workflow. This

counters a common misperception that overlapping Illumina reads are required [6, 58].

The naïve Bayesian RDP Classifier tolerates nonoverlapping V1-V3 sequences;

however, some other classifiers might not. Second, we demonstrated the value of

initiating Read 1 (R1) from the V3 reverse primer since R1 usually consists of a longer

stretch of high-quality sequence. Third, we provide evidence for a role for increased

amounts of PhiX when sequencing from the V1 primer, due to the high-degree of

sequence conservation 3' to this primer. This is analogous to the respective

recommendations by Illumina and Mitra and colleagues to add PhiX to reach up to or,

sometimes, greater than 50% of the total DNA for low diversity samples [59].

We note four limitations to the presented method for constructing a habitat-specific

training set. First, capturing the natural sequence variation for the 16S rRNA gene(s) for

each taxon is limited by the number of such sequences currently available in public

repositories. For example, 140 of the ~770 taxa in eHOMD are represented by four or

fewer distinct close-to-full-length sequences in the training set **FL_Compilation_TS**,

whereas ~630 taxa are represented by five or greater. Second, the comprehensiveness

of a training set depends on the comprehensiveness of the phylogeny-based, habitat-

specific database from which it is constructed. Therefore, if an ASV is from a species that

is absent from the database, then misclassification of that ASV to the mostly closely

related species present in the database is possible. This can also occur during validation

and benchmarking if using a simulated dataset with the same origin as the training set

[43], e.g., our **V1V3_eHOMDSim_250N100** dataset. This is a known limitation of closed

reference-based taxonomic assignment. As such, the known limitations of eHOMD are

also limitations of any eHOMD training set [20, 26]. Third, as with databases, training sets

also require regular updating over time.

Within these limitations, we note several advantages. First, when coupled with a training

set built with our method, the k-mer-based naïve Bayesian approach accommodates the

natural variability of 16S rRNA gene sequences that exists within many bacterial species

enabling high rates of accurate taxonomic assignment. In contrast, this natural variability

limits the utility of any exact match algorithm to assigning species-level taxonomy for only

those sequences already existing in a training set (**Table 2**). Second, despite all of the

known limitations of a single-gene taxonomic indicator, the huge number of 16S rRNA

gene sequences from diverse ecosystems available in public repositories supports the

utility of the 16S rRNA gene for taxonomic assignment. In contrast, the utility of WGS

metagenomic sequencing, which holds the promise of strain-level taxonomic assignment,

remains limited by the quality and comprehensiveness of the genomic database used for

closed-reference assignment. For example, at least one single-amplified genome (SAG)

of each species is needed for more accurate species-level assignment. This remains

problematic for habitats with many as-yet uncultivated species. Also, accurate strain-level

assignment is dependent on the presence of SAGs of multiple strains of each species in

the reference database. Further, a reference database should be free of chimeric

metagenome-assembled genomes (MAGs) that combine genomic sequences that are

unique to different strains of a species into one genome.

Finally, there are several additional recommendations to improve taxonomic assignment

achieved with our method. First, it is critical to incorporate a stable provisional naming

scheme into any habitat-specific database, e.g., the HMT numbers in eHOMD [20, 26].

Second, we recommend validating any training set generated with this method using a

habitat-appropriate dataset that is fully independent of the sequences used to construct

the training set, as we did with the sinonasal PacBio SMRT-generated dataset. Third, for

ASVs that remain unassigned at finer taxonomic levels and are of interest based on their

relative abundance and/or prevalence in the population, we recommend two additional

steps: first, query these unassigned ASVs against a broad database such as SILVA, RDP

and/or NCBI 16S Microbial via blastn (≥98.5% identity over ≥98% coverage) to ascertain

if these belong to a named species; and second, if no such named species match exists,

then create a new provisional taxon in your database [20, 26]. This approach will identify

candidate new taxa, both named and as-yet unnamed, for addition to a habitat-specific

database and its associated training set.

METHODS.

Construction of eHOMD-based training datasets for the naïve Bayesian RDP

Classifier. Training datasets were constructed in FASTA format as described on the

DADA2 official website (https://benjjneb.github.io/dada2/index.html) [10], with taxonomy

in the FASTA header line for each individual sequence. Training sets used in this study

are described below.

FL_eHOMDrefs_TS. All of the full-length 16S eHOMDrefs, together with their respective

taxonomic assignment, were formatted as a training set for the naïve Bayesian RDP

Classifier, as above.

FL_Compilation_TS. This is the final version of the full-length 16S rRNA gene eHOMD

training set, available as **Additional File 2** and for download from eHOMD.org as

eHOMDv15.1_FL_Compilation_TS.fa.gz. First, to more precisely calculate the percent

identity for recruiting sequences for the training set, we trimmed each of the eHOMDrefs

to nucleotides 28 and 1373. This is necessary for two reason: 1) several eHOMDrefs have

hanging 5' or 3' ends that, if left in place, would affect the calculation of percent identity,

and 2) this trimming permitted capture of sequences from the extensive datasets that use

the reverse primer at ~1390. Second, each of the 998 trimmed eHOMDrefs was queried

against the NCBI nonredundant nucleotide (nr/nt) database using blastn (NCBI BLAST

2.6.0+ package) (https://www.ncbi.nlm.nih.gov/books/NBK279690/) with the parameters

-db nr -remote -perc_identity 97. Nucleotide sequences of GenBank IDs with ≥ 97%

sequence identity to any of the eHOMDrefs were downloaded in FASTA format using the

efetch.fcgi command of NCBI's Entrez Programming Utilities (E-utilities;

https://www.ncbi.nlm.nih.gov/books/NBK25501/). The blastn hits were downloaded in the

same orientation as the eHOMDrefs in two batches: 1) for subject sequence length

between 1000 and 2000 nt, the entire subject sequence was downloaded; and 2) for

subject sequence length > 2000 bp (e.g., a complete genomic sequence), only the aligned

portion of the sequence was downloaded. Sequences < 1000 bp were not downloaded.

Third, the 301,794 downloaded sequences, which matched to Human Microbial Taxa

(HMTs) at ≥ 97%, were parsed based on their highest sequence percent identity (≥ 99%)

and alignment coverage (≥ 98% calculated based on the length of the reference) to any

of the eHOMDrefs in a given HMT. The choice of ≥ 99% identity was designed to obtain

the centrally conserved set of sequences for each eHOMDref. The choice of ≥ 98%

coverage was to ensure that the majority of the close-to-full-length sequence was present.

Sequences that matched to multiple HMTs at equal percent identity and coverage were

randomly assigned to only one HMT. (The use of supraspecies, see below, mitigates

bioinformatic variability introduced at this step.) The **_FL_Compilation_TS_** training set is

comprised of a total of 223,144 sequences parsed to their corresponding HMT, with a

range of 1 to 4004 sequences per HMT.

_V1V3_Raw_TS_. We generated this training set version in two steps. First, each

eHOMDref was individually aligned with the compilation of downloaded sequences that

were matched to it at ≥ 99% identity and ≥ 98% coverage (see immediately above).

Second, the sequences in the V1-V3 region, defined as positions 40-880 in the gapped

eHOMDrefs alignment, were captured and then the alignment gaps removed. These steps

were performed using a custom script (**Additional File 11**).

_V1V3_Curated_TS_. Sequences that were identical across V1-V3 in **_V1V3_Raw_TS_** were

collapsed into a single sequence with the names of all taxa involved concatenated with a

“:” separator. The majority of such concatenations occurred among either the same

species, resulting in no name change, or different species of the same genus, resulting

in assignment of a concatenated species name. However, there were a number of cases

where species from two different genera were involved. These intergenus concatenations

were carefully examined case by case. In all but one case, the concatenation was only

supported by two to three sequences and, therefore, was deemed unreliable and rejected.

After manual examination, only one intergenus concatenation remained. This was

between HMT-559 (*Afipia broomeae*) and HMT-597 (*Bradyrhizobium elkanii*) and was

supported by 29 sequences. The genus of the concatenated taxa was assigned as

Afipia:Bradyrhizobium and species as *broomeae:elkanii*. Of note, although these two

genera are almost identical on the V1-V3 region, they are 97% identical across the full

length of the 16S rRNA gene.

V1V3_Supraspecies_TS. This is the final version of the V1-V3 16S rRNA gene eHOMD

training set, available as **Additional File 5** and for download from eHOMD.org as

eHOMDv15.1_V1V3_Supraspecies_TS.fa.gz

(http://www.homd.org/ftp/publication_data/20190709/). The sequences in this training set

are the same as those included in the ***V1V3_Curated_TS*** version; only the header

information was edited to include the supraspecies notation as a taxonomical level

between genus and species. Therefore, instead of the header with seven-levels included

in   previous   versions   of   the   eHOMD   training   set   (i.e.,

>Kingdom;Phylum;Class;Order;Family;Genus;Species),   the   ***V1V3_Supraspecies_TS***

training   set   includes   a   header   with   eight   levels   (i.e.,

>Kingdom;Phylum;Class;Order;Family;Genus;Supraspecies;Species).   A   supraspecies

was defined between two or more HMTs when there was a phylogenetic distance less

than 0.005 between at least one pair of sequences of the corresponding HMTs. To

calculate the distances, V1V3 sequences were aligned with MAFTT v6.935b [60] and

treed with FastTree version 2.1.9 [61] with default parameters. Pairwise distances

between sequences were calculated as the sum of horizontal branch length between two

sequence nodes based on FastTree's default "Jukes-Cantor + CAT" DNA evolution model

[61]. The name of the resultant supraspecies is a concatenation of the species names of

all HMTs involved, separated by ":" and is assigned at the supraspecies level (seventh

level) for all the sequences of the involved HMTs. Sequences that were identical across

the V1-V3 region between more than one taxon were assigned the concatenated name

both   at   the   supraspecies   and   species   levels   (e.g.,

>Bacteria;Actinobacteria;Actinobacteria;Corynebacteriales;Corynebacteriaceae;Coryne-

bacterium;accolens:macginleyi:tuberculostearicum;accolens:macginleyi:tuberculostearic

um). Whereas, the rest of the reads for those taxa were named at the supraspecies level

as the concatenated name and maintained their unique identifier at the species level (e.g.,

>Bacteria;Actinobacteria;Actinobacteria;Corynebacteriales;Corynebacteriaceae;Coryne-

bacterium;accolens:macginleyi:tuberculostearicum;accolens). For taxa not requiring

concatenations (see the *V1V3_Curated_TS* description), the species designation is

repeated at the supraspecies level such that the seventh- and eighth-level designations

are identical (e.g., >Bacteria;Firmicutes;Bacilli;Lactobacillales;Carnobacteriaceae;Dolo-

sigranulum;pigrum;pigrum).

Generation of a V1-V3 16S rRNA gene simulated dataset derived from eHOMD.

Simulated reads were generated from each unique sequence in the *V1V3_Curated_TS*

training set. During read generation, one percent of the bases in each unique initial

sequence were randomly selected and changed into a different base to simulate a 1%

error rate. The resulting dataset contains 19,480 simulated sequences, each of them

labelled with the ID of the parent eHOMDref sequence from which they were derived.

Then, each error-simulated read was trimmed into two fragments to simulate Illumina pair-

end reads (R1 starting from the V3 primer and R2 starting from the V1 primer). We

generated multiple length configurations of both the R1 and R2 fragments. First, fixing R2

at 350 bp, we generated R1 fragments from the V3 primer ranging from 20 to 200 bp

(Simulated_R2_350_R1_20-200, **Additional File 12**). Second, fixing R1 at 200 bp, we

generated R2 fragments from the V1 primer ranging from 140 to 350 bp

(Simulated_R2_140-350_R1_200, **Additional File 13**). Prior to analysis with the naïve

Bayesian RDP Classifier, paired reads were connected with a "10N" linker to form one

fragment ordered R2-10N-R1 (For further explanation see **Additional File 4**).

Subsequent evaluation of the steps for generating the eHOMD training sets in Figures 3

to 5 was done using the configuration R2(250 bp)-10N-R1(100 bp)

(V1V3_eHOMDSim_250N100; Additional File 3).

Reanalysis of a sinonasal PacBio-SMRT-sequenced full-length 16S rRNA gene

dataset. Earl and colleagues kindly provided the circular consensus sequences (CCS)

already demultiplexed, labeled by sample, pooled together and, then, filtered based on

length distribution, terminal matches to the primer sequences, not aligning to a provided

host or background genome sequence and with a cumulative expected error (EE < 1)

[47]. We then used the DADA2 PacBio pipeline to denoise these CCS and identify the

relative abundance of each ASV in the dataset; i.e., we used the learnErrors() function

with errorEstimationFunction=PacBioErrfun and BAND_SIZE=32 [10, 48]. The

sequences of the resulting 204 ASVs are in the **FL_sinonasal_SMRT_ASV** dataset

(**Additional File 6**). The V1-V3 region was trimmed using bedtools getfasta with default

parameters (bedtools version 2.26.0, https://bedtools.readthedocs.io/en/latest/) and

reads were further trimmed into two fragments to simulate Illumina pair-end reads using

the configuration R2(250 bp)-10N-R1(100 bp), as described above

(**V1V3_sinonasal_SMRT_ASV**; **Additional File 8**).

Generating a test V1-V3 human aerodigestive tract (hADT) microbiota dataset from

full-length 16S rRNA gene clone libraries (CL). We previously used the close-to-full-

length 16S rRNA gene sequences from clone library-based microbiota studies of the

human aerodigestive tract, as described in Supplemental Text S1 of [20]: Segre-Kong

nostril (SKn) [62-67], Pei-Blaser [68, 69], Harris-Pace [70], van der Gast-Bruce [71],

Flanagan-Bristow [72] and Perkins-Angenent [73]. Here, we compiled these into one

dataset along with clones from NCBI PopSet UIDs 399192397, 399202217, 399199823,

399197584, 399194446, 399189902, 399186216, 399183739, 399182414, 399179617,

399175646 and 399173254 [74]. Aligned eHOMDrefs (eHOMDv15.1) sequences were

trimmed from *E. coli.* position 28-1373 and used to query this compiled dataset via blastn.

We retained 27,816 sequences that hit with 100% coverage and ≥ 99.5% identity to 401

HMTs as the full-length human aerodigestive tract clone library dataset (**FL_hADT_CL;**

Additional File 14). Of these, 5254 (18.9%) matched to more than one HMT, whereas

22,562 (81.1%) unambiguously matched to single HMTs. Sequences in this full-length CL

dataset were then aligned using MAFTT v6.935b with default parameters [60]. Segments

corresponding to the V1-V3 region were extracted based on positions of V1-V3 in the

alignment (**V1V3_hADT_CL**, **Additional File 9**) using bedtools getfasta with default

parameters (bedtools version 2.26.0, https://bedtools.readthedocs.io/en/latest/).

Taxonomic assignment with the naïve Bayesian RDP Classifier. ASVs and CL

sequences were assigned taxonomy using the naïve Bayesian RDP Classifier via the

dada2::assignTaxonomy() function in R (an implementation of the algorithm with a k-mer

size of 8 and 100 bootstrap iterations) with the specified training set and with

outputBootstraps=TRUE and the indicated minBoot value [10, 39]. In addition to our

eHOMD training sets, we used the RDP16 (*rdp_train_set_16.fa.gz*) and SILVA132

(*silva_nr_v132_train_set.fa.gz*)   genus-level   training   sets   available   at

https://benjjneb.github.io/dada2/training.html.   Since   the   eHOMD   training   set

V1V3_Supraspecies_TS generates an output with eight taxonomic levels that might not

be compatible with common downstream applications that accept only seven levels, we

provide a custom-written R function (**Additional File 15**) that converts the output from

eight to seven levels as follows. First, if a sequence is not assigned at species level (i.e.,

the eighth level) at a given threshold (output as "NA") then the eighth level is replaced

with the classification result and bootstrap value from the corresponding seventh level.

Next, the seventh level is deleted and only the resultant merged eighth level that can

contain either species or supraspecies information is reported. Please note that this

merged last supraspecies-or-species level is labeled simply as species.

Taxonomic assignment with the DADA2 exact match. ASVs and CL sequences were

assigned species-level taxonomy with the RDP16 (*rdp_species_assignment_16.fa.gz*)

and SILVA132 (*silva_species_assignment_v132.fa.gz*) training set files downloaded

from   https://benjjneb.github.io/dada2/training.html   using   the   dada2::assignSpecies()

function in R with allowMultiple=TRUE [10].

Taxonomic   assignment   with   blastn.   The   NCBI   BLAST   2.6.0+   package

(https://www.ncbi.nlm.nih.gov/books/NBK279690/)   was   installed   and   the   "blastn"

command used with max_target_seqs 1, hits with < 98.5% identity were considered

nonassigned. ASVs (**FL_sinonasal_SMRT_ASV**) derived from the sinonasal PacBio

SMRT-sequenced dataset were also assigned taxonomy using blastn against two

databases: the NCBI 16S Microbial database was downloaded from

ftp://ftp.ncbi.nlm.nih.gov/blast/db/ on January 2019 [75] and eHOMDv15.1 was converted

to a BLAST database using "makeblastdb" from the NCBI BLAST 2.6.0+ package.

DECLARATIONS.

Ethics approval and consent to participate. All participants provided informed consent

and samples used to generate the V1-V3 region 16S rRNA dataset in **Additional File 4**

Figure B were collected under a protocol (#13-14 to FED) approved by the Forsyth

Institutional Review Board**.**

Consent for publication. Not applicable.

Availability of data and material. All data are included as additional files. The following

are also available for download at eHOMD.org

(http://www.homd.org/ftp/publication_data/20190709/): 1) the simulated eHOMD derived

dataset (**Additional File 3** as V1V3_eHOMDSim_250N100.fa), 2) both eHOMD training

set files (**Additional File 2** as eHOMDv15.1_FL_Compilation_TS.fa.gz; and **Additional**

File 5 as eHOMTv15.1_V1V3_Supraspecies_TS.fa.gz) and 3) both custom scripts

(**Additional File 11** as retrieveSegment.py and **Additional File 15** as eight2seven.R).

Competing interests. The authors declare that they have no competing interests.

Funding. This work was funded in part by a pilot grant (IFE, KPL) from the Harvard Catalyst | The Harvard Clinical and Translational Science Center (National Center for Research Resources and the National Center for Advancing Translational Sciences, National Institutes of Health Award UL1 TR001102 and financial contributions from Harvard University and its affiliated academic health care centers); by the National Institute of General Medical Sciences under award number R01GM117174 (KPL); by the National Institute of Allergy and Infectious Diseases under award number R01AI101018 (KPL); and by the National Institute of Dental and Craniofacial Research under award numbers R37DE016937 and R01DE024468 (FED). The content is solely the responsibility of the authors and does not reflect the official views of the National Institutes of Health or other funding source.

Authors' contributions. Conceived Project: YH, IFE, FED, KPL. Designed Project: YH, IFE, FED, KPL. Generated and Analyzed data: YH, IFE, TC, ML, AK. Interpreted results: YH, IFE, TC, ML, AK, FED, KPL. Generated figures and tables: IFE, YH. Wrote manuscript: KPL, IFE. All authors reviewed and edited the manuscript and approved the final version.

Acknowledgements. We are grateful to Joshua Earl, Joshua Chang Mell and colleagues for providing the intermediate data table that facilitated analysis with a newly available algorithm and to members of the Lemon Lab and the Starr-Dewhirst-Johnston-Lemon Joint Group Meeting for helpful questions and suggestions throughout the project.

REFERENCES

1. Egerton S, Culloty S, Whooley J, Stanton C, Ross RP: **The Gut Microbiota of Marine Fish.** *Front Microbiol* 2018, **9:**873.

2. Berendsen RL, van Verk MC, Stringlis IA, Zamioudis C, Tommassen J, Pieterse CM, Bakker PA: **Unearthing the genomes of plant-beneficial Pseudomonas model strains WCS358, WCS374 and WCS417.** *BMC Genomics* 2015, **16:**539.

3. Brito IL, Alm EJ: **Tracking Strains in the Microbiome: Insights from Metagenomics and Models.** *Front Microbiol* 2016, **7:**712.

4. Welch JLM, Dewhirst FE, Borisy GG: **Biogeography of the Oral Microbiome: The Site-Specialist Hypothesis.** *Annu Rev Microbiol* 2019.

5. D'Amore R, Ijaz UZ, Schirmer M, Kenny JG, Gregory R, Darby AC, Shakya M, Podar M, Quince C, Hall N: **A comprehensive benchmarking study of protocols and sequencing platforms for 16S rRNA community profiling.** *BMC Genomics* 2016, **17:**55.

6. Pollock J, Glendinning L, Wisedchanwet T, Watson M: **The Madness of Microbiome: Attempting To Find Consensus "Best Practice" for 16S Microbiome Studies.** *Appl Environ Microbiol* 2018, **84**.

7. Almeida A, Mitchell AL, Tarkowska A, Finn RD: **Benchmarking taxonomic assignments based on 16S rRNA gene profiling of the microbiota from commonly sampled environments.** *Gigascience* 2018, **7**.

8. Eren AM, Maignien L, Sul WJ, Murphy LG, Grim SL, Morrison HG, Sogin ML: **Oligotyping: Differentiating between closely related microbial taxa using 16S**

rRNA gene data. *Methods in ecology and evolution / British Ecological Society*

2013, **4**.

9.   Eren AM, Morrison HG, Lescault PJ, Reveillaud J, Vineis JH, Sogin ML: **Minimum**

entropy decomposition: unsupervised oligotyping for sensitive partitioning

of high-throughput marker gene sequences. *The ISME journal* 2015, **9:**968-

979.

10.   Callahan BJ, McMurdie PJ, Rosen MJ, Han AW, Johnson AJ, Holmes SP: **DADA2:**

High-resolution sample inference from Illumina amplicon data. *Nat Methods*

2016, **13:**581-583.

11.   Callahan BJ, McMurdie PJ, Holmes SP: **Exact sequence variants should**

replace operational taxonomic units in marker-gene data analysis. *ISME J*

2017, **11:**2639-2643.

12.   Edgar RC: **UNOISE2: improved error-correction for Illumina 16S and ITS**

amplicon sequencing. *bioRxiv* 2016**:**081257.

13.   Edgar RC: **Updating the 97% identity threshold for 16S ribosomal RNA OTUs.**

Bioinformatics 2018, **34:**2371-2375.

14.   Tikhonov M, Leach RW, Wingreen NS: **Interpreting 16S metagenomic data**

without clustering to achieve sub-OTU resolution. *ISME J* 2015, **9:**68-80.

15.   Amir A, McDonald D, Navas-Molina JA, Kopylova E, Morton JT, Zech Xu Z,

Kightley EP, Thompson LR, Hyde ER, Gonzalez A, Knight R: **Deblur Rapidly**

Resolves Single-Nucleotide Community Sequence Patterns. *mSystems* 2017,

2.

16. Kumar PS, Brooker MR, Dowd SE, Camerlengo T: **Target region selection is a critical determinant of community fingerprints generated by 16S pyrosequencing.** *PLoS One* 2011, **6:**e20956.

17. Yang B, Wang Y, Qian P-Y: **Sensitivity and correlation of hypervariable regions in 16S rRNA genes in phylogenetic analysis.** *BMC bioinformatics* 2016, **17:**135-135.

18. Zhang J, Ding X, Guan R, Zhu C, Xu C, Zhu B, Zhang H, Xiong Z, Xue Y, Tu J, Lu Z: **Evaluation of different 16S rRNA gene V regions for exploring bacterial diversity in a eutrophic freshwater lake.** *Sci Total Environ* 2018, **618:**1254-1267.

19. Bukin YS, Galachyants YP, Morozov IV, Bukin SV, Zakharenko AS, Zemskaya TI: **The effect of 16S rRNA region choice on bacterial community metabarcoding results.** *Scientific Data* 2019, **6:**190007.

20. Escapa IF, Chen T, Huang Y, Gajare P, Dewhirst FE, Lemon KP: **New Insights into Human Nostril Microbiome from the Expanded Human Oral Microbiome Database (eHOMD): a Resource for the Microbiome of the Human Aerodigestive Tract.** *mSystems* 2018, **3**.

21. Quast C, Pruesse E, Yilmaz P, Gerken J, Schweer T, Yarza P, Peplies J, Glockner FO: **The SILVA ribosomal RNA gene database project: improved data processing and web-based tools.** *Nucleic Acids Res* 2013, **41:**D590-596.

22. Yilmaz P, Parfrey LW, Yarza P, Gerken J, Pruesse E, Quast C, Schweer T, Peplies J, Ludwig W, Glockner FO: **The SILVA and "All-species Living Tree Project (LTP)" taxonomic frameworks.** *Nucleic Acids Res* 2014, **42:**D643-648.

23.   Cole JR, Wang Q, Fish JA, Chai B, McGarrell DM, Sun Y, Brown CT, Porras-Alfaro

744   A, Kuske CR, Tiedje JM: **Ribosomal Database Project: data and tools for high**

745   **throughput rRNA analysis.** *Nucleic Acids Res* 2014, **42:**D633-642.

746   24.   McDonald D, Price MN, Goodrich J, Nawrocki EP, DeSantis TZ, Probst A,

747   Andersen GL, Knight R, Hugenholtz P: **An improved Greengenes taxonomy**

748   **with explicit ranks for ecological and evolutionary analyses of bacteria and**

749   **archaea.** *ISME J* 2012, **6:**610-618.

750   25.   Edgar R: **Taxonomy annotation and guide tree errors in 16S rRNA databases.**

751   *PeerJ* 2018, **6:**e5030.

752   26.   Dewhirst FE, Chen T, Izard J, Paster BJ, Tanner AC, Yu WH, Lakshmanan A,

753   Wade WG: **The human oral microbiome.** *J Bacteriol* 2010, **192:**5002-5017.

754   27.   Newton IL, Roeselers G: **The effect of training set on the classification of**

755   **honey bee gut microbiota using the Naive Bayesian Classifier.** *BMC Microbiol*

756   2012, **12:**221.

757   28.   Seedorf H, Kittelmann S, Henderson G, Janssen PH: **RIM-DB: a taxonomic**

758   **framework for community structure analysis of methanogenic archaea from**

759   **the rumen and other intestinal environments.** *PeerJ* 2014, **2:**e494.

760   29.   Ritari J, Salojarvi J, Lahti L, de Vos WM: **Improved taxonomic assignment of**

761   **human intestinal 16S rRNA sequences by a dedicated reference database.**

762   *BMC Genomics* 2015, **16:**1056.

763   30.   McIlroy SJ, Saunders AM, Albertsen M, Nierychlo M, McIlroy B, Hansen AA, Karst

764   SM, Nielsen JL, Nielsen PH: **MiDAS: the field guide to the microbes of**

765   **activated sludge.** *Database (Oxford)* 2015, **2015:**bav062.

31.   Deshpande V, Wang Q, Greenfield P, Charleston M, Porras-Alfaro A, Kuske CR,

Cole JR, Midgley DJ, Tran-Dinh N: **Fungal identification using a Bayesian**

classifier and the Warcup training set of internal transcribed spacer

sequences. *Mycologia* 2016, **108:**1-5.

32.   McIlroy SJ, Kirkegaard RH, McIlroy B, Nierychlo M, Kristensen JM, Karst SM,

Albertsen M, Nielsen PH: **MiDAS 2.0: an ecosystem-specific taxonomy and**

online database for the organisms of wastewater treatment systems

expanded for anaerobic digester groups. *Database (Oxford)* 2017, **2017**.

33.   Mikaelyan A, Kohler T, Lampert N, Rohland J, Boga H, Meuser K, Brune A:

Classifying the bacterial gut microbiota of termites and cockroaches: A

curated phylogenetic reference database (DictDb). *Syst Appl Microbiol* 2015,

38:472-482.

34.   Rohwer RR, Hamilton JJ, Newton RJ, McMahon KD: **TaxAss: Leveraging a**

Custom Freshwater Database Achieves Fine-Scale Taxonomic Resolution.

mSphere 2018, **3**.

35.   Henderson G, Yilmaz P, Kumar S, Forster RJ, Kelly WJ, Leahy SC, Guan LL,

Janssen PH: **Improved taxonomic assignment of rumen bacterial 16S rRNA**

sequences using a revised SILVA taxonomic framework. *PeerJ* 2019,

7:e6496.

36.   Chen T, Yu WH, Izard J, Baranova OV, Lakshmanan A, Dewhirst FE: **The Human**

Oral Microbiome Database: a web accessible resource for investigating oral

microbe taxonomic and genomic information. *Database (Oxford)* 2010,

2010:baq013.

37.   Conlan S, Kong HH, Segre JA: **Species-level analysis of DNA sequence data**

790   **from the NIH Human Microbiome Project.** *PLoS One* 2012, **7:**e47075.

791   38.   Al-Hebshi NN, Nasher AT, Idris AM, Chen T: **Robust species taxonomy**

792   **assignment algorithm for 16S rRNA NGS reads: application to oral**

793   **carcinoma samples.** *J Oral Microbiol* 2015, **7:**28934.

794   39.   Wang Q, Garrity GM, Tiedje JM, Cole JR: **Naive Bayesian classifier for rapid**

795   **assignment of rRNA sequences into the new bacterial taxonomy.** *Appl*

796   *Environ Microbiol* 2007, **73:**5261-5267.

797   40.   Lan Y, Wang Q, Cole JR, Rosen GL: **Using the RDP classifier to predict**

798   **taxonomic novelty and reduce the search space for finding novel organisms.**

799   *PLoS One* 2012, **7:**e32491.

800   41.   Vinje H, Liland KH, Almoy T, Snipen L: **Comparing K-mer based methods for**

801   **improved classification of 16S sequences.** *BMC Bioinformatics* 2015, **16:**205.

802   42.   Murali A, Bhargava A, Wright ES: **IDTAXA: a novel approach for accurate**

803   **taxonomic classification of microbiome sequences.** *Microbiome* 2018, **6:**140.

804   43.   Edgar RC: **Accuracy of taxonomy prediction for 16S rRNA and fungal ITS**

805   **sequences.** *PeerJ* 2018, **6:**e4652.

806   44.   Russell S, Norvig P: *Artificial Intelligence: A Modern Approach.* Prentice Hall

807   Press; 2009.

808   45.   Werner JJ, Koren O, Hugenholtz P, DeSantis TZ, Walters WA, Caporaso JG,

809   Angenent LT, Knight R, Ley RE: **Impact of training sets on classification of**

810   **high-throughput bacterial 16s rRNA gene surveys.** *ISME J* 2012, **6:**94-103.

46.   Srinivasan R, Karaoz U, Volegova M, MacKichan J, Kato-Maeda M, Miller S,

Nadarajan R, Brodie EL, Lynch SV: **Use of 16S rRNA gene for identification of**

a broad range of clinically relevant bacterial pathogens. *PLoS One* 2015,

10:e0117617.

47.   Earl JP, Adappa ND, Krol J, Bhat AS, Balashov S, Ehrlich RL, Palmer JN,

Workman AD, Blasetti M, Sen B, et al: **Species-level bacterial community**

profiling of the healthy sinonasal microbiome using Pacific Biosciences

sequencing of full-length 16S rRNA genes. *Microbiome* 2018, **6:**190.

48.   Callahan BJ, Wong J, Heiner C, Oh S, Theriot CM, Gulati AS, McGill SK,

Dougherty MK: **High-throughput amplicon sequencing of the full-length 16S**

rRNA gene with single-nucleotide resolution. *Nucleic Acids Res* 2019.

49.   Beye M, Bakour S, Le Dault E, Rathored J, Michelle C, Cadoret F, Raoult D,

Fournier PE: **Peptoniphilus lacydonensis sp. nov., a new human-associated**

species isolated from a patient with chronic refractory sinusitis. *New*

Microbes New Infect 2018, **23:**61-69.

50.   Nguyen NP, Mirarab S, Liu B, Pop M, Warnow T: **TIPP: taxonomic identification**

and phylogenetic profiling. *Bioinformatics* 2014, **30:**3548-3555.

51.   Allard G, Ryan FJ, Jeffery IB, Claesson MJ: **SPINGO: a rapid species-classifier**

for microbial amplicon sequences. *BMC Bioinformatics* 2015, **16:**324.

52.   Edgar RC: **SINTAX: a simple non-Bayesian taxonomy classifier for 16S and**

ITS sequences. *bioRxiv* 2016**:**074161.

53. Gao X, Lin H, Revanna K, Dong Q: **A Bayesian taxonomic classification**

method for 16S rRNA gene sequences with improved species-level accuracy.

BMC Bioinformatics 2017, **18:**247.

54. Liland KH, Vinje H, Snipen L: **microclass: an R-package for 16S taxonomy**

classification. *BMC Bioinformatics* 2017, **18:**172.

55. Matias Rodrigues JF, Schmidt TSB, Tackmann J, von Mering C: **MAPseq: highly**

efficient k-mer search with confidence estimates, for rRNA sequence

analysis. *Bioinformatics* 2017, **33:**3808-3810.

56. Bokulich NA, Kaehler BD, Rideout JR, Dillon M, Bolyen E, Knight R, Huttley GA,

Gregory Caporaso J: **Optimizing taxonomic classification of marker-gene**

amplicon sequences with QIIME 2's q2-feature-classifier plugin. *Microbiome*

2018, **6:**90.

57. Zheng Q, Bartow-McKenney C, Meisel JS, Grice EA: **HmmUFOtu: An HMM and**

phylogenetic placement based ultra-fast taxonomic assignment and OTU

picking tool for microbiome amplicon sequencing studies. *Genome Biol* 2018,

19:82.

58. Kozich JJ, Westcott SL, Baxter NT, Highlander SK, Schloss PD: **Development of**

a dual-index sequencing strategy and curation pipeline for analyzing

amplicon sequence data on the MiSeq Illumina sequencing platform. *Appl*

Environ Microbiol 2013, **79:**5112-5120.

59. Mitra A, Skrzypczak M, Ginalski K, Rowicka M: **Strategies for achieving high**

sequencing accuracy for low diversity samples and avoiding sample

bleeding using illumina platform. *PLoS One* 2015, **10:**e0120520.

60. Katoh K, Misawa K, Kuma K, Miyata T: **MAFFT: a novel method for rapid**

multiple sequence alignment based on fast Fourier transform. *Nucleic Acids*

Res 2002, **30:**3059-3066.

61. Price MN, Dehal PS, Arkin AP: **FastTree: computing large minimum evolution**

trees with profiles instead of a distance matrix. *Mol Biol Evol* 2009, **26:**1641-

1650.

62. Grice EA, Kong HH, Conlan S, Deming CB, Davis J, Young AC, Bouffard GG,

Blakesley RW, Murray PR, Green ED, et al: **Topographical and temporal**

diversity of the human skin microbiome. *Science* 2009, **324:**1190-1192.

63. Kong HH, Oh J, Deming C, Conlan S, Grice EA, Beatson MA, Nomicos E, Polley

EC, Komarow HD, Murray PR, et al: **Temporal shifts in the skin microbiome**

associated with disease flares and treatment in children with atopic

dermatitis. *Genome research* 2012, **22:**850-859.

64. Oh J, Conlan S, Polley EC, Segre JA, Kong HH: **Shifts in human skin and nares**

microbiota of healthy children and adults. *Genome medicine* 2012, **4:**77.

65. Findley K, Oh J, Yang J, Conlan S, Deming C, Meyer JA, Schoenfeld D, Nomicos

E, Park M, Kong HH, Segre JA: **Topographic diversity of fungal and bacterial**

communities in human skin. *Nature* 2013, **498:**367-370.

66. Oh J, Freeman AF, Park M, Sokolic R, Candotti F, Holland SM, Segre JA, Kong

HH: **The altered landscape of the human skin microbiome in patients with**

primary immunodeficiencies. *Genome research* 2013, **23:**2103-2114.

67.   Oh J, Byrd AL, Deming C, Conlan S, Kong HH, Segre JA: **Biogeography and**

individuality shape function in the human skin metagenome. *Nature* 2014,

514:59-64.

68.   Pei Z, Bini EJ, Yang L, Zhou M, Francois F, Blaser MJ: **Bacterial biota in the**

human distal esophagus. *Proc Natl Acad Sci U S A* 2004, **101:**4250-4255.

69.   Pei Z, Yang L, Peek RM, Jr Levine SM, Pride DT, Blaser MJ: **Bacterial biota in**

reflux esophagitis and Barrett's esophagus. *World J Gastroenterol* 2005,

11:7277-7283.

70.   Harris JK, De Groote MA, Sagel SD, Zemanick ET, Kapsner R, Penvari C, Kaess

H, Deterding RR, Accurso FJ, Pace NR: **Molecular identification of bacteria in**

bronchoalveolar lavage fluid from children with cystic fibrosis. *Proc Natl*

Acad Sci U S A 2007, **104:**20529-20533.

71.   van der Gast CJ, Walker AW, Stressmann FA, Rogers GB, Scott P, Daniels TW,

Carroll MP, Parkhill J, Bruce KD: **Partitioning core and satellite taxa from within**

cystic fibrosis lung bacterial communities. *ISME J* 2011, **5:**780-791.

72.   Flanagan JL, Brodie EL, Weng L, Lynch SV, Garcia O, Brown R, Hugenholtz P,

DeSantis TZ, Andersen GL, Wiener-Kronish JP, Bristow J: **Loss of bacterial**

diversity during antibiotic treatment of intubated patients colonized with

Pseudomonas aeruginosa. *J Clin Microbiol* 2007, **45:**1954-1962.

73.   Perkins SD, Woeltje KF, Angenent LT: **Endotracheal tube biofilm inoculation of**

oral flora and subsequent colonization of opportunistic pathogens. *Int J Med*

Microbiol 2010, **300:**503-511.

74.   Shelef KM: **Ecology in the dentist's chair: patterns of biogeography and**
stability in human subgingival microbial communities. Stanford University,
Department of Biology; 2013.
75.   O'Leary NA, Wright MW, Brister JR, Ciufo S, Haddad D, McVeigh R, Rajput B,
Robbertse B, Smith-White B, Ako-Adjei D, et al: **Reference sequence (RefSeq)**
database at NCBI: current status, taxonomic expansion, and functional
annotation. *Nucleic Acids Res* 2016, **44:**D733-745.

FIGURE LEGENDS.

Figure 1. Relationships between the datasets, databases and training sets in constructing training sets for a specific habitat: the human aerodigestive tract. A) Datasets gathered from public repositories or obtained by sequencing of new samples are used to explore the 16S rRNA gene diversity of the habitat of interest. These include both 16S rRNA full-length sequences and region-specific short-read sequences used for method validation or benchmarking. **B)** A curated habitat-specific full-length 16S rRNA gene reference database is assembled and expanded in an iterative way by selecting from those datasets in A representative sequences for both named and as-yet unnamed or uncultivated species (i.e., HMTs in eHOMD), and placing them in a phylogenetic tree (See Figure 1 in [20]). **C)** Training sets are derived from the taxonomical hierarchy of the habitat-specific database and enhanced by the following steps: compiling multiple 16S rRNA gene sequences to represent the natural sequence variability of each taxon, trimming the training set to match the sequenced region/s, and placing species sharing closely related sequences into a supraspecies taxonomic level. To enhance clarity, the *names of training sets* appear in bold italics whereas the **names of datasets** appear in bold throughout this paper. Datasets in grey are the specific examples used for the construction of the eHOMD derived training sets described here. Solid arrows indicate where the sequences described come from and dotted arrows indicate when datasets were used for validation or benchmarking.

Figure 2. Schematic representation of the steps to generate sequential habitat-specific training sets. (a) The *FL_eHOMDrefs_TS* training set contains all full-length

eHOMDrefs (thick lines) from eHOMDv15.1 together with their respective taxonomic

assignment. When only one read represents each taxon (M=1) a given distinguishing k-

mer (green fragment) can only be either present (1) or absent (0). (**b**) A higher number of

sequences per taxon (M) allows for better resolution on the assignment, with the presence

of a given distinguishing k-mer (green fragment) across each cluster of reads (w_i) being

represented as a proportion out of the total number of reads in that taxon (M). Therefore,

to better represent the known sequence diversity of the 16S rRNA gene(s) for each taxon,

the training set ***FL_Compilation_TS*** includes clusters of sequences (thin lines)

recovered from the NCBI nonredundant nucleotide (nr/nt) database that matched with

99% identity and ≥ 98% coverage (see methods) to each eHOMDref (thick line). (**c**) The

training set ***V1V3_Raw_TS*** is a V1-V3 trimmed version of the ***FL_Compilation_TS***

training set. The schematic illustrates how trimming to this region leads to identical reads

(purple lines) having two different taxonomic designations. Here, G is genus and species

are labeled as A or B. (**d**) To construct the ***V1V3_Curated_TS*** training set, identical V1-

V3 sequences in the ***V1V3_Raw_TS*** training set were collapsed into one. If identical

sequences came from more than one taxon (purple), species-level names of all taxa

involved were concatenated (AB). (**e**) The ***V1V3_Supraspecies_TS*** training set includes

the same sequences that the ***V1V3_Raw_TS*** training set; however, the headers in the

fasta file include the supraspecies taxon (AB) as an extra level between the genus (G)

and species taxonomic levels (A, B or AB), as illustrated here.

Figure 3. The *FL_Compilation_TS* training set provides higher classification

percentages with a lower error rate. The naïve Bayesian RDP Classifier was used with

bootstrap values ranging from 50 to 100. (**a**) The percentage of eHOMD-derived

simulated reads classified using the **FL_eHOMDrefs_TS** training set (purple) versus the

FL_Compilation_TS training set (orange). (**b**) The percentage of classified reads that

were misclassified (i.e., reads for which the assigned taxonomic identity was different

than the known identity of the original sequence from which the simulated read was

derived).

Figure 4. Trimming the training set to the specific sequenced region further

reduces the error rate. (**a**) The percentage of eHOMD-derived simulated reads classified

at species level using the **FL_Compilation_TS** (orange) training set compared to

subsequent trimmed versions **V1V3_Raw_TS** (green) and **V1V3_Curated_TS** (red). (**b**)

The percentage of classified reads that were misclassified with each of these three

training sets. The naïve Bayesian RDP Classifier was used with bootstrap values ranging

from 50 to 100. (**c**) This graph, which is specific to the eHOMD training set construction

(**V1V3_eHOMDSim_250N100** dataset), indicates how researchers can determine the

bootstrap value to use with the naïve Bayesian RDP Classifier by deciding an acceptable

level of the % of reads misclassified (blue line; e.g., 0.5%) and/or of the % of reads that

are not classified (red line).

Figure 5. Addition of a supraspecies level to the training set increases the

percentage of classified reads. (**a**) The percentage of eHOMD-derived simulated reads

classified at species/supraspecies level using the **V1V3_Curated_TS** training set (red)

versus the **FL_Supraspecies_TS** training set (blue). (**b**) Percentage of classified reads

that were misclassified with each of these TS. The naïve Bayesian RDP Classifier was

used with bootstrap values ranging from 50 to 100.

ADDITIONAL FILES.

Additional File 1: The expected effect of an uneven distribution of sequences among taxa in a training set for the Naïve Bayesian RDP Classifier.

Additional File 2: eHOMDv15.1_FL_Compilation_TS.fa. The 16S rRNA gene full-length eHOMD training set (***FL_Compilation_TS***).

Additional File 3: V1V3_eHOMDSim_250N100.fa. The simulated eHOMD-derived **V1V3_eHOMDSim_250N100** dataset.

Additional File 4: A method for achieving highly informative 16S rRNA gene V1-V3 region sequencing data using Illumina MiSeq.

Additional File 5: eHOMDv15.1_V1V3_Supraspecies_TS.fa. The 16S rRNA gene V1-V3 eHOMD training set (***V1V3_Supraspecies_TS***).

Additional File 6: FL_sinonasal_SMRT_ASV.fa. Sequences of the resulting 204 ASVs in the Earl-Mell sinonasal 16S rRNA gene dataset (**FL_sinonasal_SMRT_ASV** dataset).

Additional File 7: Earl-Mell_sinonasal_analysis.xlsx with legend and tabs A-D. Species-level taxonomic assignment of the Earl-Mell sinonasal 16S rRNA gene dataset.

Additional File 8: V1V3_sinonasal_SMRT_ASV.fa. Sequences of the resulting 204 ASVs in the **FL_sinonasal_SMRT_ASV** dataset trimmed to the V1-V3 region (**V1V3_sinonasal_SMRT_ASV** dataset).

Additional File 9: V1V3_hADT_CL.fa. V1-V3 trimmed 16S rRNA gene human

aerodigestive tract clone library dataset (**V1V3_hADT_CL** dataset).

Additional File 10: V1V3_HMPnares_ASV.fa. ASVs derived from the HMP nares 16S

rRNA gene V1-V3 dataset (**V1V3_HMPnares_ASV** dataset).

Additional File 11: retrieveSegment.py. Custom script developed to generate a trimmed

version of a training set (in our example to positions 40-880 in the gapped eHOMDrefs

alignment) from a compilation of 16S rRNA gene full-length sequences.

Additional File 12: Simulated_R2_350_R1_20-200.7z. Simulated eHOMD-derived

dataset versions with R2 fixed at 350 bp and R1 fragments from the V3 primer ranging

from 20 to 200 bp.

Additional File 13: Simulated_R2_140-350_R1_200.7z. Simulated eHOMD-derived

dataset versions with R1 fixed at 200 bp and R2 fragments from the V1 primer ranging

from 140 to 350 bp.

Additional File 14: FL_hADT_CL.fa. Full-length 16S rRNA gene human aerodigestive

tract clone library dataset (**FL_hADT_CL** dataset).

Additional File 15: eight2seven.R. Custom-written R function that converts the

dada2::assignTaxonomy() output from eight to seven taxonomic levels for compatibility

with downstream applications.

A

$$P(w_i|T_A) = \frac{1 + P_i}{M + 1}$$

$$P(w_i|T_B) = \frac{0 + P_i}{M + 1}$$

TAXON A

k-mer (w_i)

TAXON B

FL_eHOMDrefs_TS

B

$$P(w_i|T_A) = \frac{m(w_i) + P_i}{M + 1}$$

$$P(w_i|T_B) = \frac{m(w_i) + P_i}{M + 1}$$

TAXON A

TAXON B

FL_Compilation_TS

C

G:A
TAXON A
G:A
G:B
TAXON B
G:B

V1V3_Raw_TS

D

G:A
TAXON A
G:AB
TAXON B
G:B

V1V3_Curated_TS

E

G:AB:A
TAXON A
G:AB:AB
TAXON B
G:AB:B

V1V3_Supraspecies_TS