Title: Context-invariant neural dynamics underlying the encoding of Bayesian uncertainty,

but not confidence

Abbreviated Title: Network dynamics of uncertainty and confidence

Vincenzo G. Fiore[1*], Xiaosi Gu[1,2,3*]

[1] Department of Psychiatry, Icahn School of Medicine at Mount Sinai, New York, NY

10029-5674, USA

[2] Nash Family Department of Neuroscience, Icahn School of Medicine at Mount Sinai, New

York, NY 10029-5674, USA

[3] The Mental Illness Research, Education, and Clinical Center (MIRECC VISN 2) at the

James J. Peter Veterans Affairs Medical Center, Bronx, NY

[*] Correspondence should be addressed to: Vincenzo G. Fiore, vincenzo.fiore@mssm.edu,

Xiaosi Gu, xiaosi.gu@mssm.edu

Number of Pages: 22

Number of figures: 4

Number of words: 238 (abstract), 597 (introduction), 864 (discussion)

Conflict of Interest. The authors declare no financial and non-financial competing interest.

Acknowledgments. We thank Prof. Karl Friston for his comments and kind suggestions in

shaping this manuscript. We thank Jennifer Jung for her help in setting up the code for both

tasks (Psychtoolbox library in Matlab), Ann-Cathrin V. Guertler, Chandana C. Tatineni, and

Ju-Chi Yu, for their help in collecting the data. XG is supported by NIDA R01DA043695 and

the Mental Illness Research, Education, and Clinical Center (MIRECC VISN 2) at the James

J. Peter Veterans Affairs Medical Center, Bronx, NY.

Abstract

Beliefs about action-outcomes contingencies are often updated in opaque environments where feedbacks might be inaccessible and agents might need to rely on other information for evidence accumulation. It remains unclear, however, whether and how the neural dynamics subserving confidence and uncertainty during belief updating might be context-dependent. Here, we applied a Bayesian model to estimate uncertainty and confidence in healthy humans (n=28) using two multi-option fMRI tasks, one with and one without feedbacks. We found that across both tasks, uncertainty was computed in the anterior insular, anterior cingulate, and dorsolateral prefrontal cortices, whereas confidence was encoded in anterior hippocampus, amygdala and medial prefrontal cortex. However, dynamic causal modelling (DCM) revealed a critical divergence between how effective connectivity in these networks was modulated by the available information. Specifically, there was directional influence from the anterior insula to other regions during uncertainty encoding, independent of outcome availability. Conversely, the network computing confidence was driven either by the anterior hippocampus when outcomes were not available, or by the medial prefrontal cortex and amygdala when feedbacks were immediately accessible. These findings indicate that confidence encoding might largely rely on evidence accumulation and therefore dynamically changes as a function of the available sensory information (i.e. symbolic sequences monitored by the hippocampus, and monetary feedbacks computed by amygdala and medial prefrontal cortex). In contrast, uncertainty could be triggered by any information that disputes existing beliefs (i.e. processed in the insula), independent of its content.

Significance Statement

Our choices are guided by our beliefs about action-outcome contingencies. In environments

where only one action leads to a desired outcome, high estimated action-outcome

probabilities result in confidence, whereas low probabilities distributed across multiple

choices result in uncertainty. These estimations are continuously updated, sometimes based

on feedbacks provided by the environment, but sometimes this update takes place in opaque

environments where feedbacks are not readily available. Here, we show that uncertainty

computations are driven by the anterior insula, independent of feedback availability.

Conversely, confidence encoding dynamically adapts to the information available, as we

found it was driven either by the anterior hippocampus, when feedback was absent, or by the

medial prefrontal cortex and amygdala, otherwise.

Introduction

In classic decision-making theories, the presence of explicit outcomes or feedback after choice selections is considered a crucial source of information for behavioral adaptability and belief updating, e.g. by triggering prediction error signals (Rangel et al., 2008; Glimcher, 2011). However, real-life decision-making often occurs in opaque environments where outcomes can be sporadic or temporarily inaccessible, so that confidence or uncertainty in estimated action-outcome contingencies must rely on other sources of information (Pouget et al., 2013; Ma and Jazayeri, 2014; Meyniel et al., 2015a). Previous studies on value-based decision-making with explicit outcomes (Platt and Huettel, 2008; Tajima et al., 2016) have revealed multiple neural regions involved in encoding uncertainty or confidence in action-outcome estimations (White et al., 2014; Morriss et al., 2018). However, it is yet to be determined whether the neural dynamics underlying one's uncertainty or confidence are affected by the sources of available information.

We developed two multi-option decision-making tasks to allow non-binary decision-making (Churchland et al., 2008; Churchland and Ditterich, 2012) in the presence or absence of explicit stochastic outcomes in humans (**Fig. 1**). Both tasks were designed to allow a quantifiable manipulation of uncertainty and confidence on a trial-by-trial basis. The environments granted only one optimal choice per trial, and participants could estimate action-outcome contingencies on the basis of the evidence made available. Thus, given n available choices, decision-making resulted in nuanced transitions between trials characterized by high uncertainty (i.e. $\frac{1}{n}$ probability to produce the desired outcome, for all available choices) and those characterized by high confidence (i.e. one choice selection associated with the desired outcome with high probability). At the same time, we aimed at reducing second-order uncertainty (Allen et al., 2016; Spence et al., 2016), by relying on the

simplicity of task structures, with unambiguous stimuli used as evidence, and a low level of

stochasticity, where outcomes were available. These features of the tasks were exploited in a

Bayesian model, used to quantify uncertainty and confidence in both tasks.

In Bayesian terms, beliefs represent – as probability distributions – the estimated likelihood

any action will produce a desired outcome (Kording and Wolpert, 2006; Payzan-LeNestour

and Bossaerts, 2011; Fleming and Daw, 2017). As uncertainty normally increases in presence

of conflicting information and confidence increases in the face of accumulating confirming

evidence, it has been proposed that one derives from the inverse of the other (Ma and

Jazayeri, 2014; Meyniel et al., 2015b; Meyniel et al., 2015a; Adler and Ma, 2018). The theory

of Bayesian inference has found empirical support in studies demonstrating that probabilistic

distributions are taken into account in choice selections (Orban and Wolpert, 2011; Sanders et

al., 2016) and they are represented by the activity of neural populations (Ma et al., 2006;

Pouget et al., 2013; Rich et al., 2015). Investigations into the neural computations of

uncertainty and confidence have revealed a rich network of regions involved (Pouget et al.,

2016; Meyniel and Dehaene, 2017; Morriss et al., 2018). In particular, neural regions

monitoring conflict and errors, with a prominent role for insular (Seymour et al., 2004;

Palminteri et al., 2012; Gu et al., 2015), and dorsal anterior cingulate (ACC) cortices

(Behrens et al., 2007; Botvinick, 2007; Rushworth and Behrens, 2008), and areas such as the

medial prefrontal cortex (mPFC) or the amygdala, implicated in the processing of value

estimates, in presence of risk (Koechlin and Hyafil, 2007; Sarinopoulos et al., 2010; Peters et

al., 2017). Based on this literature, and considering that our model-defined uncertainty was

formalized as the inverse of our model-defined confidence for both task environments, we

hypothesized that both uncertainty- and confidence-encoding networks would be found to

change, depending on the context.

Materials and Methods

Experimental design and statistical analyses I: 3-options continuous choice tasks. In a

first task, termed *bead task* (**Fig. 1A**) (modified from: Huq et al., 1988), a new visual

stimulus (a red, blue or green *bead*) was presented at each trial, adding a congruent (e.g. a red

bead after another red one) or incongruent (e.g. a blue bead following a green one) color

stimulus in a sequence of beads. Participants had 2 seconds to decide from which of three jars

displayed on the monitor the bead had been extracted. The jars were illustrated on screen as

containing beads of three colors in a ratio of 80%-10%-10%. After each button press, the

selected jar would be highlighted with a black rectangle, for the remaining time on the clock

allowed for the choice selection, plus 0.5 seconds. The last five extracted beads were always

present on screen (**Fig. 1A**), and the participants were allowed to make the first choice

selection starting from the 5th bead extraction. Between trials, a grey square would appear to

conceal the new extracted bead for a variable time of 2 to 3.5 seconds. Participants had access

to immediate feedbacks during a training session, which would show that each correct guess

would result in accumulating 100 points. However, no feedback was provided during the

MRI task and the participants were made aware that the accumulated points would be

disclosed only at the end of the task.

In the second task, termed *card task* (**Fig. 1B**) (modified from: O'Doherty et al., 2001), the

participants had 2 seconds to select among three cards presented on the screen and

characterized by three geometric figures (randomly selected among triangle, square, circle,

star and diamond). Each card was assigned a different predominant value among the three

possible outcomes of 100, 10 and 0 and after selecting a card, the screen would display a

stochastic outcome, highlighted in green (variable duration: 1-2.5 seconds), with assigned

probability of 80%, for the predominant value, and 10% for each of the remaining outcomes.

A second message on screen also signaled the amount won on white screen (fixed interval:

0.5 seconds), followed by a fixation cross (variable interval: 1-2.5 seconds), which would

precede a new trial. The total amount of points accumulated, per block, was always displayed

in the lower part of the screen.

Finally, the participants were instructed that the computer would randomly change the jar

from which it extracted beads, or the card-value associations. The pace of these pseudo-

random changes was determined in an interval of 5 to 7 trials for both tasks and it was

independent of the performance of the participants. For both tasks, participants were

compensated with $1 for every 500 points, selecting the points accumulated during one

random block per task. Both tasks consisted in 3 blocks of 71 trials each, so the participants

were told that the maximum amount of bonus they could gain consisted in about $15 dollars

from each task. Three identical sequences -one per block- were used for all subjects, for both

the bead colors and the card-value associations. Task order and block order were

counterbalanced across subjects.

Experimental design and statistical analyses II: model and parametric modulators. We

used two similar Bayesian models to estimate: 1) in the bead task, the probability that the

latest color bead had been extracted from the selected jar; 2) in the card task, the probability

that the selected card was associated with the 100 value, given the outcomes received from

the previous choices. In both cases, we used a standard Bayes theorem in the context of

Bayes updating:

$$P(A|B) = \frac{P(B|A)P(A)}{P(B)}$$

155   Where *P(A/B)*, indicates the conditional probability of the event A to occur, given the

156   evidence B. *P(A)* indicates the distribution of probabilities before new evidence is provided

157   (carried from a previous trial), and *P(B)* is derived from the subject-specific assumptions

158   about the distribution of events in the task environment. We assumed these were normally

159   distributed:

$$f(B|\sigma) = \frac{1}{\sigma\sqrt{2\pi}} e^{\frac{-(B)^2}{2\sigma^2}}$$

where the mean of the normal distribution is assumed to be zero ($\mu = 0$), the variable σ

(standard deviation of the normal distribution) was fixed per each subject, to compute *P(B)*,

using the law of total probability. Under these conditions, higher values of σ resulted in

simulated behaviors characterized by slower updates. For the Bead task, a new colored bead

evidence would update the probability distribution associated with the three jars, increasing

the probability associated with the matched colored jar and equally decreasing the probability

associated with the remaining ones. Similarly, for the card task, an outcome equivalent to 100

would be used as positive evidence to increase the probability to find the same outcome again

by selecting the same card. Outcomes of 10 or 0 were used to decrease the probability to find

the maximum reward by repeating the same choice, therefore equally increasing the

probability associated with both non-selected cards.

We used a Monte Carlo method to estimate the value of the parameter σ, per each task, that

would better match real choice selections expressed by the 28 participants. We then coupled

the trial-by-trial distribution of probabilities resulting from these model-based estimations

with the actual choice selection of each participant, having in turn the estimated probability *p*

associated with each choice. This resulted in the trial-by-trial estimated choice-dependent

probability to reach the desired outcome (i.e. the estimated probability to guess the correct

extraction jar or the card associated with 100 points) and therefore was used as a parametric

modulator for the analysis of confidence. The inverse *1-p*, indicating the estimated

probability to receive any outcome but the desired one, given the chosen action, was used as

parametric modulator of uncertainty.

Participants. We recruited 28 healthy volunteers (16 females), age 24.8 ± 7.0. Participants

taking any medication, or with a history of mental disorder or drug abuse were excluded from

the study. One subject was excluded from all fMRI analysis involving the card task, due to

excessive movement. The study was approved by the Institutional Review Board at the

University of Texas, Dallas and University of Texas Southwestern Medical Center. Informed

consent was obtained from all subjects and all participants were informed that they could

withdraw from the study at any point.

fMRI data acquisition and preprocessing. Functional MRI data were acquired using a

Philips 3-Tesla MR scanner at the Advanced Imaging Research Center at University of Texas

Southwestern Medical Center. The anatomical scan sequence (multi-echo MPRAGE) was

carried out with a resolution of 1 mm, Multi Parametric Maps. Functional images (EPI) were

acquired with a resolution of 3.4 x 3.4 x 4mm, repetition time of 2000 milliseconds, echo

time of 25 milliseconds, 38 axial slices, flip angle=90°, and a field of view of 240 mm. We

used Statistical Parametric Mapping (SPM12, Wellcome Department of Imaging

Neuroscience) for data preprocessing. The functional images were motion realigned to the

first volume, coregistered to the participant's anatomical scan, MNI normalized, and spatially

smoothed using an isotropic 8-mm full-width at half-maximum (FWHM) Gaussian kernel.

Model-based fMRI. For the GLM analysis, we used default SPM12 functions to observe

BOLD signals associated with the onsets of choice selections (i.e. button presses). This is

consistent with our computational definition of confidence and uncertainty, as well as with existing literature (De Martino et al., 2013; Ma and Jazayeri, 2014; Meyniel et al., 2015a), as where these phenomena in association with a choice, i.e. confidence or uncertainty that the selected action with deliver the desired result. RTs were used as trial-by-trial covariates in both tasks, and parametric modulators (*p* for confidence and *1-p* for uncertainty) were used to identify the relationship between the -parametrically modulated- task events and the hemodynamic response. We concatenated the three blocks for each task. Whole brain activations were determined using a threshold of *P*<.05 corrected for familywise errors (P_{FWE}<.05; **Fig. 2A,B**).

Dynamic causal modelling (DCM). For the DCM estimation, we relied on SPM12 default functions. Our model-based GLM revealed two distinct networks subserving uncertainty (insula, ACC, dlPFC; **Fig. 2A,C,E**) and confidence (hippocampus, amygdala, mPFC; **Fig. 2B,D,F**). We extracted fMRI time series from individual ROIs, using their principal eigenvariates: we relied on anatomical maps manually generated for the amygdala and the anterior hippocampus, and we used spherical ROIs (8mm radius) for all cortical regions. These were centered on task-specific, group-averaged, peaks activity, at the following coordinates: anterior insula (bead: [-27, 23, -1] and [33, 23, 2]; card:[-30, 20, -7] and [30, 23, -4]), ACC (bead: [-6, 29, 41] and [6, 29, 41]; card:[-9, 29, 23] and [9, 29, 26]), dlPFC (bead: [-42, 23, 26] and [42, 29, 29]; card:[-36, 26, 32] and [36, 26, 29]), mPFC (bead: [-9, 56, -1] and [9, 56, -1]; card: [-9, 56, -4]). We also included the visual cortex as a network input region, with ROIs centred on the following coordinates: bead: [12 -88 32] and [-12 -94 -7]; card: [21 -91 11] and [-21 -91 11]. With the exception of the response to the signal of confidence recorded during the card task, which was limited to the ROIs in the left hemisphere, we found significant increase in BOLD response bilaterally, for all ROIs. Thus,

we used independent DCM analysis for both hemispheres for a cross validation of the results

within tasks.

For the network architectures (the *A matrix*), we assumed reciprocal (extrinsic) connections

among all four regions (the signal-dependent ROIs triplets and the input ROI of the visual

cortex), as well as recurrent (self) connections. Then we established the targets of the

modulatory inputs (the *B matrix*), represented by the signal of estimated confidence (*p*) or

uncertainty (*1-p*). We assumed that these modulatory inputs would affect the connectivity

between visual cortex and the main three active ROIs, bilaterally, for all models, but they

would target the connectivity between the three main ROIs in one direction only. Finally, we

assumed the sensory input would only directly drive the activity of the visual cortex (*C*

matrix). These assumptions resulted in eight models, which were characterized by identical

architecture and targets of sensory input, but differed for their *B matrix* or targets of

modulatory inputs (combination of 2 possible directions between 3 pairs of nodes, **Fig. 3A-**

B).

We used a Bayesian family-wise random effect approach to estimate the directed connectivity

between each pair of nodes within the two network triplets, grouping the eight models each

time into two families of four models, each family characterized by one common modulated

directed connectivity. This method allowed comparing, for instance, the four models with an

insula-to-ACC modulated connectivity (with varying connectivity between insula and dlPFC

and between ACC and dlPFC, **Fig. 3A**) vs the four models characterized by an ACC-to-insula

modulated connectivity (and varying connectivity for the remaining couples of nodes). The

method allowed to assess the likelihood a modulator signal would affect the information flow

in a specific direction, within a single pair of nodes, independent of the presence of a single

winning model that would have emerged in a single model comparison. Finally, we tested our

results independently across hemispheres. The estimated exceedance probability was deemed

inconclusive for the ACC-dlPFC connectivity, in both tasks, and for the connectivity between

Amg and mPFC, limited to the bead task, due to lack of convergence across hemispheres and

insufficient difference between the compared families.

Results

Parameter regression with Monte Carlo resulted in subject-specific values determining each

participant's own pace of belief update (σ=.497±.095, σ=.321±.156, respectively for the bead

and card task, **Fig. 1C**). These values resulted in optimized Bayesian models that provided a

mean behavioral prediction accuracy of 85.75%±4.73% for the bead task and 75.93%±6.44%

for the card task.

In the context of our study, we defined confidence as the estimated probability to succeed in

securing the desired outcome (*p*), and uncertainty as the inverse probability (*1-p*), given a

selected action (De Martino et al., 2013; Meyniel et al., 2015a; Pouget et al., 2016).

Specifically, the model was used to estimate, on a trial-by-trial basis, each participant's

confidence (*p*) that their selected jar was the extraction jar (bead task) or their selected card

was associated with the maximum reward (card task). A subject by subject correlation

analysis revealed this estimated confidence (*p*) was negatively correlated with the reaction

times (RTs) in the bead task (r= -.43 ± .16; *P*=.01 ± .05), but not in the card task (r= -.01 ±

.11; *P*=.33 ± .31; cf. **Fig. 1D** and **E**). Next, we included RTs values as covariates and we

examined the neural activations associated with the estimated uncertainty (1-*p*) or confidence

(*p*) (**Fig. 1D,E**). Consistent with previous literature (Payzan-LeNestour et al., 2013; Meyniel

and Dehaene, 2017), we found that uncertainty was encoded in bilateral anterior insula,

bilateral ACC, and right dorsolateral prefrontal cortex (dlPFC), across tasks [**Fig. 2A;** *P*<.05,

family-wise error (FWE) corrected]. Conversely, confidence was encoded in the mPFC, left

anterior hippocampus (aHip) and left amygdala (Amg), across both tasks (**Fig. 2B**,

P_{FWE}<.05). A contrast between the two tasks did not reveal any difference, after FWE

correction. A less stringent threshold (*P*<.005, uncorrected) revealed increased activity in the

right lateral frontopolar cortex, in association with uncertainty processing, when comparing

Card vs Bead task BOLD activity, but this result would not survive FWE correction.

Next, we used DCM (Friston et al., 2003) to investigate the causal dependencies among

uncertainty- and confidence-encoding regions. Family-wise model comparison estimated

independently on both hemispheres revealed that, for both tasks, *uncertainty* modulated

insula-to-ACC [exceedance probability for bead task: 94% (left hemisphere), 67% (right

hemisphere), **Fig. 4A;** card task: 65% (left),75% (right), **Fig. 4C**] and insula-to-dlPFC

connectivity [exceedance probability for bead task 75% (left),78% (right), **Fig. 4A**; card task:

69% (left),72% (right), **Fig. 4C**]. However, the directed influences associated with

confidence-encoding depended on feedback availability. Confidence primarily modulated the

connections from the anterior hippocampus to other regions in the bead task (aHip-to-mPFC:

94% (left),83% (right) and aHip-to-Amg: 97% (left),61% (right), **Fig. 4B**), when immediate

outcome was absent. In contrast, when feedback was available, confidence primarily

modulated mPFC-to-aHip, mPFC-to-Amg, and Amg-to-aHip connectivity (exceedance

probability, left hemisphere: 95% and 81%, and 82%, **Fig. 4D**).

Discussion

Uncertainty and confidence are typically considered two sides of the same coin, where one

increases as the other decreases. Our findings reveal a more complex and nuanced picture,

demonstrating that the relationship between uncertainty and confidence is not the same across

all Marrian levels of analysis (Marr and Poggio, 1976). Specifically, despite the fact we

defined uncertainty and confidence as computationally symmetric processes (i.e. model-

estimated *p* and *1-p*), we found asymmetry and divergence in the implementation of these

estimations in terms of neural network dynamics. In our tasks, both confidence- and

uncertainty-encoding neural regions remain unchanged, i.e. they are independent from the

task frame. Both tasks presented similar action-outcome volatility, implying that different

sources of information (colored beads vs. card/money) were used by the same neural areas

(hippocampus-mPFC-amygdala and insula-ACC-dlPFC) to estimate changes in probability

distributions of expected outcomes, independent of feedback availability. Furthermore, the

use of dynamic causal modelling revealed that uncertainty-related neural network dynamics

were also not affected by the source of information available. Specifically, we found that the

anterior insula drove the uncertainty-encoding network and exerted its directed influence over

ACC and dlPFC, regardless of the presence of immediate monetary feedback. The insula-

ACC-dlPFC circuit has been consistently implicated in various cognitive tasks (e.g. attention,

response selection, cognitive control), leading to the hypothesis that they are part of a

ubiquitous salience network (Seeley et al., 2007). This network also responds to any threat to

homeostasis, as, for instance, in the case of information conflicting with established beliefs,

which seems to be independent of the nature of such information (Gu and FitzGerald, 2014).

In this sense, our finding of the insula driving uncertainty computations across tasks is

consistent with its role in salience processing and belief updating (Gu and FitzGerald, 2014;

Uddin, 2015), demonstrating that the brain monitors conflicting information in action-

outcome contingencies, even in the absence of immediate outcomes.

In sharp contrast, we found that the directional influence among brain regions encoding

confidence in action-outcome contingencies changed depending on the availability of explicit

outcomes and the source of available information. As confidence encoding in the bead task

relies on the sequence of colored beads as evidence, we speculate that this process engages

first the hippocampus to track and accumulate this information (Strange et al., 2005; Zeidman

and Maguire, 2016), and then mPFC and amygdala for the value estimations on the basis of

this information (Gluth et al., 2015). Differently, in the card task, evidence accumulation is

based on expected values estimated from the stochastic outcomes; thus, in this case, the

mPFC and amygdala are the first to be engaged to monitor changes in action-outcome

contingencies (Koechlin and Hyafil, 2007; De Martino et al., 2013).

This is an intriguing decoupling of the network implementation for confidence and

uncertainty, despite the fact that the computational definitions of the two estimations are

perfectly anticorrelated in both tasks. Importantly, these results were achieved relying on

multi-alternative decision-making processes, which present several advantages. First, they

avoid a critical downside of binary decision tasks, which are biased by a

confirmation/exclusion criterion, as the exclusion of one option inherently implies the only

alternative available is the correct choice to make. Second, despite the significant increase in

computational demands associated with 3-options tasks (Churchland et al., 2008; Churchland

and Ditterich, 2012; Itthipuripat et al., 2018; Tajima et al., 2019), the tasks used for this study

rely on a simple set of rules, easy-to-compute stochastic associations (80% for the most

prevalent bead in a jar and for the most likely outcome value associated to a card) and only

three types of discrete evidence (i.e. the three feedback values or the three bead colors),

reducing the effect of second-order uncertainty (Fleming and Dolan, 2012; Fleming and Daw,

2017). By avoiding these issues, our tasks allow a more precise manipulation of first-order

uncertainty and confidence, as the maximum uncertainty (determined by an even distribution

of probabilities among all available options) increases with the number of possible choices

$(1 - \frac{1}{n})$. This feature eventually results in a large number of trials available for the

investigation of uncertainty in particular, strengthening the fMRI BOLD responses as well as

the DCM analysis. On this matter, the key findings supporting our interpretation are

consistent across hemispheres and tasks, after running four independent sets of DCM

analyses (in the case of the uncertainty network) or three independent sets of DCM analyses

(for the confidence network). Thus, even in those cases reporting lower values for the

exceedance probabilities, the cross validations increased the robustness of the overall result in

terms of estimated effective connectivity.

Finally, it can be argued that, in terms of active inference, this dissociation we found between

Bayesian *uncertainty* and *confidence* in belief updating (Friston et al., 2017) can be

accounted considering the former corresponds to *uncertainty about hidden states* of the world

(that does not depend upon reward), while the latter corresponds to *uncertainty about policies*

being pursued (that depends upon prior preferences). This dissociation also fits comfortably

with the functional anatomy described above. Taken together, our findings reveal both the

distinct neurocomputational mechanisms underlying uncertainty and confidence encoding,

and the importance of outcomes in directing information flow between the neural regions

computing confidence, but not uncertainty.

Limitations: simplicity of the model does not account for volatility e.g. compare with (Adams

et al., 2016) for a model of Beads task

References:

References:

Adams RA, Huys QJ, Roiser JP (2016) Computational Psychiatry: towards a mathematically informed
understanding of mental illness. J Neurol Neurosurg Psychiatry 87:53-63.
Adler WT, Ma WJ (2018) Comparing Bayesian and non-Bayesian accounts of human confidence
reports. PLoS Comput Biol 14:e1006572.
Allen M, Frank D, Schwarzkopf DS, Fardo F, Winston JS, Hauser TU, Rees G (2016) Unexpected
arousal modulates the influence of sensory noise on confidence. Elife 5.
Behrens TE, Woolrich MW, Walton ME, Rushworth MF (2007) Learning the value of information in
an uncertain world. Nat Neurosci 10:1214-1221.
Botvinick MM (2007) Conflict monitoring and decision making: reconciling two perspectives on
anterior cingulate function. Cognitive, affective & behavioral neuroscience 7:356-366.
Churchland AK, Ditterich J (2012) New advances in understanding decisions among multiple
alternatives. Curr Opin Neurobiol 22:920-926.
Churchland AK, Kiani R, Shadlen MN (2008) Decision-making with multiple alternatives. Nat Neurosci
11:693-702.
De Martino B, Fleming SM, Garrett N, Dolan RJ (2013) Confidence in value-based choice. Nat
Neurosci 16:105-110.
Fleming SM, Dolan RJ (2012) The neural basis of metacognitive ability. Philos Trans R Soc Lond B Biol
Sci 367:1338-1349.
Fleming SM, Daw ND (2017) Self-evaluation of decision-making: A general Bayesian framework for
metacognitive computation. Psychol Rev 124:91-114.
Friston K, FitzGerald T, Rigoli F, Schwartenbeck P, Pezzulo G (2017) Active Inference: A Process
Theory. Neural Comput 29:1-49.
Friston KJ, Harrison L, Penny W (2003) Dynamic causal modelling. Neuroimage 19:1273-1302.
Glimcher PW (2011) Understanding dopamine and reinforcement learning: the dopamine reward
prediction error hypothesis. Proc Natl Acad Sci U S A 108 Suppl 3:15647-15654.
Gluth S, Sommer T, Rieskamp J, Buchel C (2015) Effective Connectivity between Hippocampus and
Ventromedial Prefrontal Cortex Controls Preferential Choices from Memory. Neuron
86:1078-1090.
Gu X, FitzGerald TH (2014) Interoceptive inference: homeostasis and decision-making. Trends Cogn
Sci 18:269-270.
Gu X, Wang X, Hula A, Wang S, Xu S, Lohrenz TM, Knight RT, Gao Z, Dayan P, Montague PR (2015)
Necessary, yet dissociable contributions of the insular and ventromedial prefrontal cortices
to norm adaptation: computational and lesion evidence in humans. J Neurosci 35:467-473.
Huq SF, Garety PA, Hemsley DR (1988) Probabilistic judgements in deluded and non-deluded
subjects. Q J Exp Psychol A 40:801-812.
Itthipuripat S, Cha K, Deering S, Salazar AM, Serences JT (2018) Having More Choices Changes How
Human Observers Weight Stable Sensory Evidence. J Neurosci 38:8635-8649.
Koechlin E, Hyafil A (2007) Anterior prefrontal function and the limits of human decision-making.
Science 318:594-598.
Kording KP, Wolpert DM (2006) Bayesian decision theory in sensorimotor control. Trends Cogn Sci
10:319-326.
Ma WJ, Jazayeri M (2014) Neural coding of uncertainty and probability. Annu Rev Neurosci 37:205-
220.
Ma WJ, Beck JM, Latham PE, Pouget A (2006) Bayesian inference with probabilistic population codes.
Nat Neurosci 9:1432-1438.
Marr D, Poggio T (1976) From understanding computation to understanding neural circuitry.
Cambridge: Massachusetts Institute of Technology, Artificial Intelligence Laboratory.
Meyniel F, Dehaene S (2017) Brain networks for confidence weighting and hierarchical inference
during probabilistic learning. Proc Natl Acad Sci U S A 114:E3859-E3868.

Meyniel F, Sigman M, Mainen ZF (2015a) Confidence as Bayesian Probability: From Neural Origins to
Behavior. Neuron 88:78-92.
Meyniel F, Schlunegger D, Dehaene S (2015b) The Sense of Confidence during Probabilistic Learning:
A Normative Account. PLoS Comput Biol 11:e1004305.
Morriss J, Gell M, van Reekum CM (2018) The uncertain brain: A co-ordinate based meta-analysis of
the neural signatures supporting uncertainty during different contexts. Neurosci Biobehav
Rev.
O'Doherty J, Kringelbach ML, Rolls ET, Hornak J, Andrews C (2001) Abstract reward and punishment
representations in the human orbitofrontal cortex. Nat Neurosci 4:95-102.
Orban G, Wolpert DM (2011) Representations of uncertainty in sensorimotor control. Curr Opin
Neurobiol 21:629-635.
Palminteri S, Justo D, Jauffret C, Pavlicek B, Dauta A, Delmaire C, Czernecki V, Karachi C, Capelle L,
Durr A, Pessiglione M (2012) Critical roles for anterior insula and dorsal striatum in
punishment-based avoidance learning. Neuron 76:998-1009.
Payzan-LeNestour E, Bossaerts P (2011) Risk, unexpected uncertainty, and estimation uncertainty:
Bayesian learning in unstable settings. PLoS Comput Biol 7:e1001048.
Payzan-LeNestour E, Dunne S, Bossaerts P, O'Doherty JP (2013) The neural representation of
unexpected uncertainty during value-based decision making. Neuron 79:191-201.
Peters MAK, Thesen T, Ko YD, Maniscalco B, Carlson C, Davidson M, Doyle W, Kuzniecky R, Devinsky
O, Halgren E, Lau H (2017) Perceptual confidence neglects decision-incongruent evidence in
the brain. Nature human behaviour 1.
Platt ML, Huettel SA (2008) Risky business: the neuroeconomics of decision making under
uncertainty. Nat Neurosci 11:398-403.
Pouget A, Drugowitsch J, Kepecs A (2016) Confidence and certainty: distinct probabilistic quantities
for different goals. Nat Neurosci 19:366-374.
Pouget A, Beck JM, Ma WJ, Latham PE (2013) Probabilistic brains: knowns and unknowns. Nat
Neurosci 16:1170-1178.
Rangel A, Camerer C, Montague PR (2008) A framework for studying the neurobiology of value-
based decision making. Nat Rev Neurosci 9:545-556.
Rich D, Cazettes F, Wang Y, Pena JL, Fischer BJ (2015) Neural representation of probabilities for
Bayesian inference. Journal of computational neuroscience 38:315-323.
Rushworth MF, Behrens TE (2008) Choice, uncertainty and value in prefrontal and cingulate cortex.
Nat Neurosci 11:389-397.
Sanders JI, Hangya B, Kepecs A (2016) Signatures of a Statistical Computation in the Human Sense of
Confidence. Neuron 90:499-506.
Sarinopoulos I, Grupe DW, Mackiewicz KL, Herrington JD, Lor M, Steege EE, Nitschke JB (2010)
Uncertainty during anticipation modulates neural responses to aversion in human insula and
amygdala. Cereb Cortex 20:929-940.
Seeley WW, Menon V, Schatzberg AF, Keller J, Glover GH, Kenna H, Reiss AL, Greicius MD (2007)
Dissociable intrinsic connectivity networks for salience processing and executive control. J
Neurosci 27:2349-2356.
Seymour B, O'Doherty JP, Dayan P, Koltzenburg M, Jones AK, Dolan RJ, Friston KJ, Frackowiak RS
(2004) Temporal difference models describe higher-order learning in humans. Nature
429:664-667.
Spence ML, Dux PE, Arnold DH (2016) Computations underlying confidence in visual perception. J
Exp Psychol Hum Percept Perform 42:671-682.
Strange BA, Duggins A, Penny W, Dolan RJ, Friston KJ (2005) Information theory, novelty and
hippocampal responses: unpredicted or unpredictable? Neural Netw 18:225-230.
Tajima S, Drugowitsch J, Pouget A (2016) Optimal policy for value-based decision-making. Nat
Commun 7:12400.

Tajima S, Drugowitsch J, Patel N, Pouget A (2019) Optimal policy for multi-alternative decisions. Nat
Neurosci.
Uddin LQ (2015) Salience processing and insular cortical function and dysfunction. Nat Rev Neurosci
16:55-61.
White TP, Engen NH, Sorensen S, Overgaard M, Shergill SS (2014) Uncertainty and confidence from
the triple-network perspective: voxel-based meta-analyses. Brain and cognition 85:191-200.
Zeidman P, Maguire EA (2016) Anterior hippocampus: the anatomy of perception, imagination and
episodic memory. Nat Rev Neurosci 17:173-182.

Figure 1. Experimental paradigm, choice behavior, and model estimations for trial-by-trial confidence and uncertainty. (**A**) Bead task. Participants chose from which of three jars, containing predominantly red, blue or green beads (80%-10%-10% ratio), the latest bead was extracted from. The latest five beads extracted were always displayed on screen, and no feedback was provided after each choice selection. (**B**) Card task. Participants chose one card among three cards characterized by different geometric figures. Each card yielded 100, 10 or 0 points (immediate feedback) with a probability distribution of 80%-10%-10%. The extraction jar and the card-value associations were changed every 5 to 7 trials, in three pre-established pseudo-random sequences that were used for all participants, in a counterbalanced order. (**C**) Subject-specific values of the coefficient σ, used in the Bayesian models to estimate confidence and uncertainty in each participant on a trial-by-trial basis. Different σ values determine different rates of belief update: for instance, the higher the value, the more confirming evidence is required to increase confidence and decrease uncertainty. The color of each extracted new bead or the feedback provided after each card selection were used as discrete new evidence to update the estimated probability distribution or priors of each participant. (**D-E**) The actual choices of all the participants (upper row, expressed in percentages) match the model-estimated probabilities (p) assigned to each available option (lower row, expressed as mean and standard deviation). In grey, superimposed on the participant choice selection percentages, mean and standard deviation of the reaction times, per task.

Figure 2. Model-based BOLD responses encoding Bayesian confidence and uncertainty. (A-B) Model-based fMRI response recorded across tasks in association with the model-estimated signal of uncertainty (left column) or confidence (right column), used as parametric modulator and using reaction times as covariates ($P_{FWE}<0.05$). (C-F) Task-specific, model-

based, fMRI responses in association with the model-estimated signals of uncertainty and confidence ($P_{uncorrected}$<0.005, k=50).

Figure 3. Neural network architectures tested in the family-wise DCM. These neural architectures illustrate the eight models used to test the effective connectivity associated with the signal of uncertainty (A) or confidence (B). The same models have been tested in both tasks for a comparison of the results. The general architecture (*A matrix*) remains unchanged, whereas the targets of the modulatory inputs (*B matrix*) are different in each model. This differentiation results in the generation of the 8 models, then divided into two families of 4, to allow family-wise comparisons for each pair of nodes in a triplet (Ins-ACC-dlPFC or aHip-Amg-mPFC).

Figure 4. DCM results using family-wise comparison. Histograms report the family Exceedance probability for each tested pair-wise connection in the confidence- and uncertainty-encoding networks. The network diagrams illustrate a summary of all pair-wise analysis, with thick red arrow used to highlight the direction of causal effects and thin red lines used for those connections for which DCM analysis did not provide a conclusive result. In the bead task, the insula drives the uncertainty-encoding network (**A**) and the anterior Hippocampus drives the confidence-encoding network (**B**). In the card task, the network estimating uncertainty remains unchanged in comparison with the bead task, despite the presence of the immediate feedback (**C**). Conversely, the estimation of confidence is driven in this task by the medial prefrontal cortex and amygdala (**D**).

A

B

Total

100 □

Total points: 320

C

Estimated Sigmas

Bead   Card

D

Button Presses and RTs (sequence 1)

Bayes-estimated Uncertainty-Confidence (sequence 1)

E

Button Presses and RTs (sequence 1)

Bayes-estimated Uncertainty-Confidence (sequence 1)

Bayes Estimated Uncertainty
x=9, y=23

Bayes Estimated Confidence
x=-6, z=-19

Both tasks
p<.05 (FWE), k=0

Bead task
p<.005 (unc.), k=50

Card task
p<.005 (unc.), k=50

A B C D E F

DCM for Bayes Estimated Uncertainty

DCM for Bayes Estimated Confidence

Bead task

A

B

Card task

C

D

Left hemisphere   Right hemisphere