Title Page

Title

Sub-optimality of the early visual system explained through biologically plausible plasticity

Authors

Tushar Chauhan*[1,2], Timothée Masquelier[1,2], Benoit R. Cottereau[1,2]

Corresponding author: Tushar.Chauhan@cnrs.fr

Affiliations

1. Centre de Recherche Cerveau et Cognition, Université de Toulouse, 31052 Toulouse,
France
2. Centre National de la Recherche Scientifique, 31055 Toulouse, France

Acknowledgements

We are grateful to Dr. Dario Ringach for generously sharing single-cell data, and to Dr. Bruno
Olshausen for sharing the original/initial versions of his sparse-coding routines. We would also
like to thank Dr. Yves Trotter and Dr. Lionel Nowak for their critical feedback.

Funding

1. Fondation pour la Recherche Médicale (FRM: SPF20170938752) awarded to T.C.
2. Agence Nationale de la Recherche (ANR-16-CE37-002-01, 3D3M) awarded to B.R.C.

Abstract

The early visual cortex is the site of crucial pre-processing for more complex, biologically

relevant computations that drive perception and, ultimately, behaviour. This pre-processing is

often viewed as an optimisation which enables the most efficient representation of visual input.

However, measurements in monkey and cat suggest that receptive fields in the primary visual

cortex are often noisy, blobby, and symmetrical, making them sub-optimal for operations such

as edge-detection. We propose that this suboptimality occurs because the receptive fields do

not emerge through a global minimisation of the generative error, but through locally operating

biological mechanisms such as spike-timing dependent plasticity. Using an orientation

discrimination paradigm, we show that while sub-optimal, such models offer a much better

description of biology at multiple levels: single-cell, population coding, and perception. Taken

together, our results underline the need to carefully consider the distinction between

information-theoretic and biological notions of optimality in early sensorial populations.

Introduction

The human visual system processes an enormous throughput of sensory data in successive operations to generate percepts and behaviours necessary for biological functioning (Anderson et al., 2005; Raichle, 2010). Computations in the early visual cortex are often explained through unsupervised normative models which, given an input dataset with statistics similar to our surroundings, carry out an optimisation of criteria such as energy consumption and information-theoretic efficiency (Bell & Sejnowski, 1997; Bruce et al., 2016; Hoyer & Hyvärinen, 2000; Olshausen & Field, 1996; van Hateren & van der Schaaf, 1998; Zhaoping, 2006). While such arguments do explain why many properties of the early visual system are closely related to characteristics of natural scenes (Bell & Sejnowski, 1997; Beyeler et al., 2019; Geisler, 2008; Hunter & Hibbard, 2015; Lee & Seung, 1999; Olshausen & Field, 1996), they are not equipped to answer questions such as how cortical structures which support complex computational operations implied by such optimisation may emerge, how these structures adapt, even in adulthood (Hübener & Bonhoeffer, 2014; Wandell & Smirnakis, 2010), and why some neurones possess receptive fields which are sub-optimal in terms of information processing (Jones & Palmer, 1987; Ringach, 2002).

It is now well established that locally-driven synaptic mechanisms such as spike-timing dependent plasticity (STDP) are natural processes which play a pivotal role in shaping the computational architecture of the brain (Brito & Gerstner, 2016; Caporale & Dan, 2008; Delorme et al., 2001; Larsen et al., 2010; Markram et al., 1997; Masquelier, 2012). Therefore, it is only natural to hypothesise that locally operating, biologically plausible models of plasticity must offer a better description of receptive fields in early visual cortex. However, such line of reasoning leads to the obvious question: what exactly constitutes a 'better description' of a biological system, and more specifically, the early visual cortex. Here, we use a series of criteria

spanning across electrophysiology, information theory, and machine learning, to investigate

how descriptions of early visual RFs provided by a local, abstract STDP model differ from two

influential and widely employed normative schemes – Independent component analysis (ICA),

and Sparse coding (SC). Our results demonstrate that a local process-based model of

experience-driven plasticity is better suited to capturing the receptive fields (RFs) of simple-

cells, thus suggesting that biological preference does not always concur with forms of global,

information-theoretic optimality.

More specifically, we show that STDP units are able to better capture the characteristic sub-

optimality in RF shape reported in literature (Jones & Palmer, 1987; Ringach, 2002), and their

orientation tuning closely matches measurements in the macaque primary visual cortex (V1)

(Ringach et al., 2002). To investigate the possible effects of this sub-optimality on downstream

processing we estimated the performance of an ideal observer and a linear decoder on an

orientation discrimination task. We find that decoding from the STDP population shows a bias

for cardinal orientations (horizontal and vertical gratings) – something that is not observed for

ICA and SC. This increase in discriminability for cardinal orientations has been reported in

numerous behavioural studies (Heeley & Timney, 1988; Orban et al., 1984), and there is

converging evidence which places its locus in the early visual cortex (Furmanski & Engel,

2000; Maffei & Campbell, 1970; Mansfield, 1974) – a claim that is amply supported by our

results.

Taken together, our findings suggest that while the information carrying capacity of an STDP

ensemble is not optimal when compared to generative schemes, it is precisely this sub-

optimality which may make process-based, local models more suited for describing the initial

stages of sensory processing.

Results

We used an abstract model of the early visual system with three representative stages: retinal

input, lateral geniculate nucleus (LGN) processing, and V1 activity (Figure 1B). To simulate

retinal activity corresponding to natural inputs, patches of size $3° \times 3°$ (visual angles) were

sampled randomly from the Hunter-Hibbard database (Hunter & Hibbard, 2015) of natural

scenes (Figure 1A). 10^5 patches were used to train models corresponding to three encoding

schemes: ICA, SC and STDP. Each model used a specific procedure for implementing the LGN

processing and learning the synaptic weights between the LGN and V1 (see Figure 1B and

Methods).

A

B

Figure 1: Dataset and the computational pipeline. **A.** Training data. The Hunter-Hibbard dataset of natural images
was used. The images in the database have a 20° × 20° field of view. Patches of size 3° × 3° were sampled from
random locations in the images (overlap allowed). The same set of 100,000 randomly sampled patches was used
to train three models: Spike-timing dependent plasticity (STDP), Independent component analysis (ICA) and

Sparse coding (SC). **B.** Modelling the early visual pathway. Three representative stages of early visual computation were captured by the models: retinal input, processing in the lateral geniculate nucleus (LGN), and the activity of early cortical populations in the primary visual cortex (V1). Each input patch represented a retinal input. This was followed by filtering operations generally associated with the LGN, such as decorrelation and whitening. Finally, the output from the LGN units/filters was connected to the V1 population through all-to-all (dense) plastic synapses which changed their weights during learning. Each model had a specific optimisation strategy for learning: the STDP model relied on a local rank-based Hebbian rule, ICA minimised mutual information (approximated by the negentropy), and SC enforced sparsity constraints on V1 activity. Abbreviations: DoG: Difference of Gaussian, PCA: Principal component analysis.

As expected, units in all models converged to oriented, edge-detector like RFs. While the RFs from ICA (Figure 2B) and SC (Figure 2C) were elongated and highly directional, STDP (Figure 2A) RFs were more compact and less sharply tuned. This is in agreement with simple-cell recordings in the macaque and cat, where studies have reported that not all RFs are optimally tuned for edge-detection (Jones & Palmer, 1987; Ringach, 2002). A quantitative measure of this phenomenon was obtained by fitting Gabor functions to the RFs and considering the frequency-normalised spread vectors or FSVs (Ringach, 2002) of the fit. The first component (n_x) of the FSV characterises the number of lobes in the RF, and the second component (n_y) is a measure of the elongation of the RF (perpendicular to carrier propagation). A considerable number of simple-cell RFs measured in macaque and cat tend to fall within the square bounded by $n_x = 0.5$ and $n_y = 0.5$. The FSVs of a sample of neurones ($N = 93$) measured in the macaque V1 (Ringach, 2002) indicate that 59.1% of the neurones lay within this region (Figure 2D). Since they are not elongated, and contain few lobes (typically 2-3 on/off regions), they tend to be compact – making them less effective as edge-detectors compared to more crisply tuned, elongated RFs. While a considerable number of STDP units (82.2%) tend to fall in this realistic regime, ICA (10.7%) and SC (4.0%) show a distinctive shift upwards and to the right.

Figure 2: Receptive field (RF) shape. **A, B, C.** RFs of neurones randomly chosen from the three converged populations. The STDP population is shown in **A**, ICA in **B**, and SC in **C**. **D.** Frequency-scaled spread vectors (FSVs). FSV is a compact metric for quantifying RF shape. n_x is proportional to the number of lobes in the RF, n_y is a measure of the elongation of the RF, and values near zero characterise symmetric, often blobby RFs. The FSVs for STDP (pink), ICA (green) and SC (blue), are shown with data from macaque V1 (black) (Ringach, 2002). Measurements in macaque and cat simple-cells tend to fall within the square bound by 0.5 along both axes (shaded in grey, with a dotted outline). Three representative neurones are indicated by colour-coded arrows: one for each

algorithm. The corresponding RFs are outlined in **A**, **B** and **C** using the corresponding colour. The STDP neurone

has been chosen to illustrate a blobby RF, the ICA neurone shows a multi-lobed RF, and the SC neurone illustrates

an elongated RF. Insets above and below the scatter plot show estimations of the probability density function for

n_x and n_y. Both axes have been cut-off at 1.5 to make comparison with biological data easier (complete

distributions are shown in Supplementary Figure S 1).

The inlays in Figure 2D provide estimations of the probability densities of two FSV parameters

for the macaque data and the three models. An interesting insight into these distributions is

given by the Kullback-Leibler (KL) divergence from the model distributions to the distribution

of the macaque data. KL divergence is a directed measure which can intuitively be interpreted

as the additional number of bits required if one of the three models were used to encode data

sampled from the macaque distribution. The KL divergence for the STDP model was found to

be 3.0 bits indicating that, on average, it would require three extra bits to encode data sampled

from the macaque distribution. In comparison, SC and ICA were found to require 8.4 and 14.6

additional bits respectively. An examination of the KL divergence of marginal distributions of

the FSV parameters (Supplementary Table S 1) suggests that STDP offers a better encoding of

both the n_x (number of lobes) and the n_y (compactness) parameters.

Given this sub-optimal, compact nature of STDP RF shapes, we next investigated how this

affected the responses of these neurones to sharp edges. In particular, we were interested in how

the orientation tuning curves of the units from the three models would compare to biological

data. We simulated a typical electrophysiological experiment to probe orientation tuning

(Figure 3A). To each unit, we presented noisy sine-wave gratings (SWGs) at its preferred

frequency and recorded its activity as a function of the stimulus orientation. This allowed us to

plot its orientation tuning curve (OTCs) (Figure 3B) and estimate the peak and tuning

bandwidth. While the peak indicates the preferred orientation of the unit, the bandwidth is a

measure of the local selectivity of the unit around its peak – low values corresponding to sharply

tuned neurones and higher values corresponding to broadly tuned, less selective neurones. For

all three models, we estimated the probability density functions of the OTC bandwidth, and

compared it to the distribution estimated over a large set of data ($N = 308$) measured in

macaque V1 (Ringach et al., 2002) (Figure 3C). The ICA and SC distributions peak at about

10-degrees (ICA: 9.1deg, SC: 8.5deg) while the STDP and macaque data have much broader

tunings (STDP: 15.1deg, Macaque data: 19.1deg). This is also reflected in the KL divergence

measured from the three model distributions to the macaque distribution (ICA: 2.4 bits, SC: 3.5

bits, STDP: 0.29 bits).

Figure 3: Orientation encoding. **A.** Orientation tuning. Sine-wave gratings with additive Gaussian noise (0dB SNR) were presented to the three models to obtain single-unit orientation tuning curves (OTCs). OTC peak identifies the preferred orientation of the unit, and OTC bandwidth (half width at $1/\sqrt{2}$ peak response) is a measure of its selectivity around the peak. Low bandwidth values are indicative of sharply tuned units while high values signal broader, less specific tuning. **B.** Single-unit tuning curves. RF (left) and the corresponding OTC (right) for representative units from ICA (top row, green), SC (second row, blue) and STDP (bottom row, pink). The bandwidth is shown above the OTC. **C.** Population tuning. Estimated probability density of the OTC bandwidth for the three models (same colour code as panel **B**), and data measured in macaque V1 (black) (Ringach et al., 2002). The inlay shows estimated probability density of the preferred orientation for the three models.

After characterising the encoding capacity of the models, we next probed the possible

downstream implications of such codes. The biological goal of most neural code, in the end, is

the generation of behaviour that maximises evolutionary fitness. However, due to the

complicated neural apparatus that separates behaviour from early sensory processing, it is not

straightforward (or at times, even possible) to analyse the interaction between the two. Here,

we make use of two separate metrics to investigate this relationship. In both cases, the models

were presented with oriented SWGs, followed by an analysis of the resulting population activity

(Figure 4A).

In the first analysis, we estimated the Fisher information (FI) contained in the generated

responses. Orientation discrimination tasks are particularly suited to such an analysis (i.e., the

study of a behavioural measure using early sensory activity) as V1 activity has been shown to

correlate with orientation discrimination thresholds (Vogels & Orban, 1990), something that

has not been observed for other visual properties such as binocular disparity (Nienborg &

Cumming, 2006) or motion (Grunewald et al., 2002). Given the responses of an encoding

model, the Crámer-Rao bound permits us to use the FI to draw inferences about the optimal

discrimination performance – leading to the simulation of what could be called a locally-

optimal ideal observer (Wei & Stocker, 2017). We find that ICA and SC ideal observers have

lower thresholds (i.e., a better orientation discrimination performance) compared to STDP

(Figure 4B). Considering the sharper population tuning of the ICA and SC models, this is not

surprising. Interestingly, the STDP ideal observer shows a bias for cardinal orientations

(horizontal and vertical gratings), while ICA and SC ideal observers show uniform performance

across all stimulus orientations.

Figure 4: Orientation decoding. **A.** Retrieving encoded information. Sine-wave gratings (SWGs) with additive
Gaussian noise at 0dB were presented to the three models. The following question was then posed: how much
information about the stimulus (in this case, the orientation) can be decoded from the population responses? The
theoretical limit of the accuracy of such a decoder can be approximated by estimating the Fisher information (FI)
in the responses. This can be interpreted as the response of an ideal observer capable of extracting all the
information contained in the population responses. In addition, a linear decoder was also used to directly decode
the population responses. This could be a downstream process which is linearly driven by the population activity,
or a less-than-optimal 'linear observer'. **B.** Ideal observer (Fisher information). The abscissa shows the stimulus
orientation, and the ordinate shows the inverse square-root of the estimated FI. Due to the Cramér-Rao bound, low
values on the ordinate denote more precise encoding of the orientation, while higher values denote lower precision.
Results for ICA are shown in green, SC in blue, and STDP in pink. **C.** Linear decoding. The stimuli and responses
from **B** were used to train a linear-discriminant classifier. The ordinate shows the accuracy (probability of correct
classification) for each ground-truth value of the stimulus orientation (abscissa). The same symbols as **B** are used,
and envelopes around the solid lines show 95% confidence intervals. **D.** Post-training threshold variation in STDP.
The SWG stimuli used in **C** were used to test STDP models with different values of the threshold parameter, which
represents the threshold potential of the neurones in the model. The threshold was either increased (by 25%, 50%
or 75%) or decreased (by 25%, 50% or 75%) with respect to the training threshold (denoted by Θ_0). The abscissa
and ordinate denote the same quantities as **B**, and each line shows the ideal observer response from one of the

models. The magnitude of change in the threshold is denoted by a corresponding change in colour from pink (Θ_0)

to orange (increase) or blue (decrease).

Although the FI ideal observer represents the optimal decoding of a given encoding scheme, it

does not automatically follow that all the encoded information is available for downstream

processing (Quiroga & Panzeri, 2009). This is especially true in the presence of significant

higher-order correlations (Shamir & Sompolinsky, 2004). To investigate more realistic

orientation decoding in the three models, we implemented a second analysis where we reduced

the complexity of the decoding and examined the performance of a decoder built on linear

discriminant classifiers (these classifiers assume fixed first-order correlations in the input).

Such decoders could be interpreted as linearly-driven feedforward populations downstream

from the thalamo-recipient layer (the 'V1' populations in the three models), or a simplified,

'linear' observer. In general, we found the decoding performance (Figure 4C) to be consistent

with ideal observer predictions (Figure 4B), indicating that linear correlations represent a

sizeable amount of correlations in all three encoding schemes. Both ICA and SC showed

uniform decoding scores across the orientations, with SC being the most accurate of the three

models. Once again, STDP showed a modulation at the cardinal orientations, with the scores

being almost three times higher at the peaks (horizontal and vertical gratings) than the troughs.

Since the STDP model is linear up to a thresholding operation, we hypothesised that the

modulation in decoding (Figure 4A and B) must result from the intervening thresholding

nonlinearity. To test this hypothesis, we ran simulations where the threshold parameter

(analogue of the threshold potential in the STDP model) was either increased or decreased.

Note that in all simulations the model was first trained (i.e., synaptic learning using natural

stimuli, see Figure 1) using the same 'training' threshold, and the increase/decrease of the

threshold parameter was imposed post-convergence. Our results (Figure 4D) showed that the

modulation of the classification performance for horizontal and vertical gratings became more

pronounced as the threshold was increased, and flattened as the threshold was decreased.

However, this increase in the cardinal orientation bias came at the cost of an overall decrease

in precision.

Discussion

Traditionally, process-based descriptions (often studied through mean-field statistics under

large N limits) have been used to model fine-grained neuronal dynamics (Harnack et al., 2015;

Kang & Sompolinsky, 2001; Moreno-Bote et al., 2014), while more global, normative schemes

are employed to predict population-level characteristics (Hoyer & Hyvärinen, 2000; Lee &

Seung, 1999; Olshausen & Field, 1997; van Hateren & van der Schaaf, 1998). Detailed process-

based models suffer from constraints imposed by computational complexity, prohibitively long

execution times (which do not scale well for large networks), and hardware that is geared

towards synchronous processing. On the other hand, most one-shot models can leverage faster

computational libraries and architectures developed over decades, thereby leading to more

efficient and scalable computation. Through this work, we argue that more abstract forms of

process-based models, when used to answer specific questions, can still give a closer

approximation of biological processes than normative schemes. Our model, despite important

limitations such as the use of at most one spike per neuron, lack of cortico-cortical connections,

and feedback from higher visual areas, is still able to describe a number of phenomena which

are not predicted by normative schemes.

The converged RFs of the STDP model are closer to those reported in electrophysiological

measurements in the macaque. A number of them display a characteristic departure from the

optimal, sharply tuned edge-detectors predicted by ICA and SC (Figure 2). This suboptimal

shape also results in suboptimal orientation encoding, which, once again, was found to be closer

to data measured in the macaque V1 (Figure 3). Furthermore, decoding from this population

shows a distinct bias for horizontal and vertical stimuli, with the performance for the cardinal

orientations being roughly two times better than other orientations (Figure 4). Interestingly, this

bias for cardinal directions has also been observed in human participants (Orban et al., 1984),

who also show an almost two-fold reduction in just-noticeable-differences for horizontal and

vertical stimuli (Heeley & Timney, 1988). Our results suggest that such behavioural biases for

cardinal directions (the so-called oblique effect) are supported by the cortical architecture as

early as the early thalamocortical interface – a claim that is further reinforced by

electrophysiology (Dragoi et al., 2001; Li et al., 2003) and imaging experiments (Furmanski &

Engel, 2000) which suggest that neural activity in the primary visual cortex may be directly

correlated with the perceptual oblique effect.

Moreover, our simulations also demonstrated that the magnitude of the cardinal orientation bias

in the STDP model can be changed by manipulating the spiking threshold (Figure 4D). Thus,

even after the initial learning phase has ended, the network is still theoretically capable of

shrinking or expanding its encoded dictionary without modifying its synaptic connectivity –

simply by modulating its threshold. In the cortex, such changes are likely to be mediated by

homeostatic processes (Harnack et al., 2015; Perrinet, 2019) and metaplastic regulation

(Abraham, 2008; Cooke & Bear, 2010). This supports the idea that purely bottom-up changes

are indeed capable of driving perceptually relevant cortical changes in adults who are beyond

the critical window of plasticity – an observation of particularly relevance for reports claiming

that low-level changes in the early visual cortex may accompany perceptual learning (Bao et

al., 2010; Furmanski et al., 2004). In the context of the current model, this is only possible if

the information content in the non-spiking activity is larger than the spiking activity (Figure S

5), and suggests that the model may employ some form of variable-length encoding. This

becomes especially pertinent for realistic natural inputs which are more complicated and varied

than SWGs. When we characterised the sparsity of non-spiking activity for each of the three

models using naturalistic stimuli (Figure 5A), our results (Figure 5B) confirmed that the STDP

responses do indeed show a higher variability in sparsity when measured across both the

encoding ensemble ('spatial sparsity'), and the input sequence ('temporal sparsity'). Thus, the

sparsity of the STDP neurones is stimulus-dependent, and likely driven by the relative

probability of occurrence of specific features in the dataset.

Figure 5: Sparsity of responses to natural stimuli. **A.** Sparsity indices. To estimate the sparsity of the non-spiking
responses to natural stimuli, 10^4 patches ($3° \times 3°$ visual angle) randomly sampled from natural scenes were
presented to the three models. Two measures of sparsity were defined: Spatial sparsity Index (Λ_S) was defined as
the average sparsity of the activity of the entire neuronal ensemble, while Temporal sparsity Index (Λ_T) was
defined as the average sparsity of the activity of single neurones to the entire input sequence. **B.** Spatial and
temporal sparsity. The top panel shows the estimated probability density of Λ_S for ICA (green), Sparse coding
(blue) and STDP (red). Λ_S varied between 0 (all units activate with equal intensity) and 1 (only one unit activates)

by definition. The bottom panel shows the estimated probability density of Λ_T in a manner analogous to Λ_S. Λ_T

also varied between 0 (homogeneous activity for the entire input sequence) and 1 (activity only for few inputs in

the sequence).

The encoding that emerges from localised learning, as we have shown, can confer biological

advantages while being sub-optimal in a global information-theoretic framework. This

dichotomy has indeed been characterised at various stages of the early visual system (Chelaru

& Dragoi, 2008; Field & Chichilnisky, 2007; Liu et al., 2009; Ringach, 2002; Ringach et al.,

2002), and offers an interesting glimpse into the notion of 'optimality' in biological systems. In

such systems input information is not the only criterion of fitness, and the landscape is

modulated by factors such as the topological and dynamical constraints of the learning

mechanisms, decoding capabilities of the downstream apparatus, and relevance of the resulting

behaviour(s) to the functioning and survival of the organism. Given these realistic and

complicated constraints, it is obvious that a clear global optimisation function which describes

the responses of real neural populations is very difficult, if not impossible, to formulate. This

makes an ideal case for the use of process-based, local descriptions which, by definition, offer

a much deeper insight into the organisation and functioning of biological systems. Such models

offer the flexibility to not only describe normative hypotheses about stimulus encoding, but to

also predict how meaningful internal parameters and interactions in the model impact the

behaviour of the system. With increasingly common availability of faster and more adaptable

computing solutions, we hope process-based modelling will be adopted more widely by

cognitive and computational neuroscientists.

Finally, it must be noted that in this study we have used classical forms of the ICA and SC

algorithms. More generally, these models are part of a class of data-adaptive encoding schemes

which also comprises other algorithms such as principal-component analysis (PCA) and

nonnegative matrix factorisation (NMF). These algorithms rely on the optimality of the

encoding manifold at representing the training data, and their use in neuroscience is motivated

by the proven energetic and information-theoretic efficiency of neural processes at representing

natural statistics. We would like to draw attention to a growing number of insightful studies

based on hybrid encoding schemes which address multiple optimisation criteria (Beyeler et al.,

2019; Martinez-Garcia et al., 2017; Perrinet & Bednar, 2015), often through local process-based

computation (Isomura & Toyoizumi, 2018; Savin et al., 2010; Zylberberg et al., 2011).

Methods

Dataset

The Hunter-Hibbard dataset of natural images was used (Hunter & Hibbard, 2015). It is

available under the MIT license at https://github.com/DavidWilliamHunter/Bivis, and consists

of 139 stereoscopic images of natural scenes captured using a realistic acquisition geometry

and a 20 degree field of view. Only images from the left channel were used, and each image

was resized to a resolution of 5 pixels/degree along both horizontal and vertical directions.

Inputs to all encoding schemes were 3×3 degree patches (i.e. 15×15 pixels) sampled

randomly from the dataset (Figure 1A).

Encoding models

Samples from the dataset were used to train and test three models corresponding to ICA, SC

and STDP encoding schemes. Each model consisted of three successive stages (Figure 1B). The

first stage represented retinal activations. This was followed by a pre-processing stage

implementing operations which are typically associated with processing in the LGN, such as

whitening and decorrelation. In the third stage, LGN output was used to drive a representative

V1 layer.

During learning, 10^5 patches (3×3 degree) were randomly sampled from the dataset to

simulate input from naturalistic scenes. In this phase, the connections between the LGN and V1

layers were plastic, and modified in accordance with one of the three encoding schemes. Care

was taken to ensure that the sequence of inputs during learning was the same for all three

models. After training, the weights between the LGN and V1 layers were no longer allowed to

change. The implementation details of the three models are described below.

Sparse Coding

SC algorithms are based on energy-minimisation, which is typically achieved by a

'sparsification' of activity in the encoding population. We used a now-classical SC scheme

proposed by (Olshausen & Field, 1996, 1997). The pre-processing in this algorithm consists of

an initial whitening of the input using low pass filtering, followed by a trimming of higher

frequencies. The latter was employed to counter artefacts introduced by high frequency noise,

and the effects of sampling across a uniform square grid. In the frequency domain the pre-

processing filter was given by a zero-phase kernel:

383
$$H(f) = f \cdot e^{-\left(\frac{f}{f_0}\right)^4}$$

Here, $f_0 = 10$ cycles/degree is the cut-off frequency. The outputs of these LGN filters were

then used as inputs to the V1 layer composed of 225 units ($3° \times 3°$ RF at 5 pixels/degree).

Retinal projections of the converged RFs (Figure 2C) were recovered by an approximate

reverse-correlation algorithm (Ringach, 2002; Ringach & Shapley, 2004) derived from a linear-

stability analysis of the SC objective function about its operating point. The RFs (denoted as

columns of a matrix, say $\boldsymbol{\xi}$) were given by:

390
$$\boldsymbol{\xi} = \boldsymbol{A}[\boldsymbol{A}^T\boldsymbol{A} + \lambda S''(0)\boldsymbol{I}]^{-1}$$

Here, $\boldsymbol{A}$ is the matrix containing converged sparse components as column vectors, λ is the

regularisation parameter (for the reconstruction, it is set to 0.14σ, where σ^2 is the variance in

the input dataset), and $S(x)$ is the shape-function for the prior distribution of the sparse

coefficients (this implementation uses $log\,(1 + x^2)$).

Independent Component Analysis (ICA)

ICA algorithms are based on the idea that the activity of an encoding ensemble must be as

information-rich as possible. This typically involves a maximisation of mutual information

between the retinal input and the activity of the encoding ensemble. We used a classical ICA

algorithm called *fastICA* (Hyvärinen & Oja, 2000) which achieves this through an iterative

estimation of input negentropy. The pre-processing in this implementation was performed using

a truncated Principal Component Analysis (PCA) transform ($\tilde{d} = 150$ components were used),

leading to low-pass filtering and local decorrelation akin to centre-surround processing reported

in the LGN. If the input patches are denoted by the columns of a matrix (say $\boldsymbol{X}$), the LGN

activity $\boldsymbol{L}$ can be written as:

406
$$\boldsymbol{L} = \widetilde{\boldsymbol{U}}^T \boldsymbol{X}_C$$

407   Here, $\boldsymbol{X}_C = \boldsymbol{X} - \langle \boldsymbol{X} \rangle$ and $\widetilde{\boldsymbol{U}}$ is a matrix composed of the first $\tilde{d}$ ($= 150$) principal components

408   of $\boldsymbol{X}_C$. The activity of these LGN filters was then used to drive the ICA V1 layer consisting of

409   150 units, with its activity $\boldsymbol{\Sigma}$ being given by:

410
$$\boldsymbol{\Sigma} = \boldsymbol{W}\boldsymbol{L}$$

411   Here, $\boldsymbol{W}$ is the un-mixing matrix which is optimised during learning. The recovery of the RFs

412   for ICA was relatively straight forward, as, in our implementation, they were assumed to be

413   equivalent to the filters which must be applied to a given input to generate the corresponding

414   V1 activity. The RFs (denoted as columns of a matrix, say $\boldsymbol{\xi}$) were given by:

415
$$\boldsymbol{\xi} = \widetilde{\boldsymbol{U}}\boldsymbol{W}^T + \langle \boldsymbol{X} \rangle$$

Spike timing dependent plasticity (STDP)

STDP is a biologically observed, Hebbian-like learning rule which relies on local

spatiotemporal patterns in the input. We used a feedforward model based on an abstract rank-

based STDP rule (Chauhan et al., 2018). The pre-processing in the model consisted of ON/OFF

filtering using difference-of-Gaussian filters based on the properties of magno-cellular LGN

cells. The outputs of these filters were converted to relative first-spike latencies using a

monotonically decreasing function ($1/x$ was used), and only the earliest 10% spikes were

allowed to propagate to V1 (Delorme et al., 2001; Masquelier & Thorpe, 2007). These spikes

were used to drive an unsupervised network of 225 (non-leaky) integrate-and-fire neurones.

During learning, changes in the synaptic weights between LGN and V1 were governed by a

simplified version of the STDP rule proposed by (Gütig et al., 2003). After each iteration, the

change (Δw) in the weight (w) of a given synapse was given by:

429
$$\Delta w = \begin{cases} -\alpha^- \cdot w^{\mu^-}, & \Delta t \leq 0 \\ \alpha^+ \cdot (1-w)^{\mu^+}, & \Delta t > 0 \end{cases}$$

Here, Δt is the difference between the post- and pre-synaptic spike times, and the constants $\alpha^\pm$

and $\mu^\pm$ describe the learning-rate and non-linearity of the process respectively. Thus, the weight

was increased if a presynaptic spike occurred before the postsynaptic spike (causal firing), and

decreased if it occurred after the post-synaptic spike (acausal firing). During each iteration of

learning, the population followed a winner-take-all inhibition rule wherein the firing of one

neurone reset the membrane potentials of all other neurones. After learning, this inhibition was

no longer active and multiple units were allowed to fire for each input. The RFs of the

converged neurones were recovered using a linear approximation. If w_i denotes the weight of

the synapse connecting a given neurone to the ith LGN filter, the RF $\boldsymbol{\xi}$ of the neurone was given

by:

440
$$\xi = \sum_{i \in LGN} w_i \psi_i$$

Here, ψ_i is the RF of the ith LGN neurone.

Evaluation metrics

Gabor fitting

Linear approximations of RFs (Figure 2, panels A, B and C) obtained by each encoding strategy

were fitted using 2-D Gabor functions. This is motivated by the fact that all the encoding

schemes considered here lead to linear, simple-cell-like RFs. In this case, the goodness-of-fit

parameter (R^2) provides an intuitive measure of how Gabor-like a given RF is. The fitting was

carried out using an adapted version of the code available here, generously shared under an

open-source license by Gerrit Ecke (University of Tübingen).

Frequency-normalised spread vector

The shape of the RFs approximated by each encoding strategy was characterised using

frequency-normalised spread vectors (FSVs) (Chauhan et al., 2018; Ringach, 2002). For a RF

fitted by a Gabor-function with sinusoid carrier frequency f and envelope size $\sigma = \begin{bmatrix} \sigma_x & \sigma_y \end{bmatrix}^T$,

the FSV is given by:

457
$$\begin{bmatrix} n_x & n_y \end{bmatrix}^T = \begin{bmatrix} \sigma_x & \sigma_y \end{bmatrix}^T f$$

While n_x provides an intuition of the number of cycles in the RF, n_y is a cycle-adjusted measure

of the elongation of the RF perpendicular to the direction of sinusoid propagation. The FSV

serves as a compact, intuitive descriptor of the RF shape-invariance to affine operations such

as translation, rotation and isotropic scaling.

Fisher Information

The information content in the activity of the converged units was quantified by using

approximations of the Fisher information (FI, denoted here by the symbol Φ). If $x =$

$\{x_1, x_2, x_3, \dots, x_N\}$ is a random variable describing the activity of an ensemble of N independent

units, the FI of the population with respect to a parameter θ is given by:

468
$$\Phi(\theta) = \sum_{i=1}^{N} E\left[\left\{\frac{\partial \, ln \, ln \, P(x_i|\theta)}{\partial \theta}\right\}^2\right]_{P(x_i|\theta)}$$

Here, $E[.]_{P(x_i|\theta)}$ denotes expectation value with respect to the firing-state probabilities of the

i^{th} neurone in response to the stimuli corresponding to parameter value θ. In our simulations,

θ was the orientation (defined as the direction of travel) of a set of sine-wave gratings (SWGs)

with additive Gaussian noise. The SWGs were presented at frequency of 1.25cycles/visual

degree, and the responses were calculated by averaging over 8 evenly spaced phase values in

$[0°, 360°)$. This effectively simulated a drifting grating design within the constraints of the

computational models. In Figure 4 (panels B and D) we report values for an SNR of 0dB (i.e.,

the signal and noise had equal variance – a fairly noisy condition), but the behaviour of the

system was found to be similar for SNR values of -3dB and 3dB (Supplementary Figure S 2).

The ground-truth values of θ were sampled at intervals of 4° in the range $[0°, 180°)$, and each

simulation was repeated 100 times.

Decoding using a linear classifier

In addition to FI approximations, we also used a linear decoder on the population responses

obtained in the FI analysis. The decoder was an error-correcting output codes model composed

of binary linear-discriminant classifiers configured in a one-vs.-all scheme. Similar to the FI

experiment, ground-truth values of the orientation at intervals of $4°$ in the range $[0°, 180°)$ were

used as the class labels, and the activity generated by the corresponding SWG stimuli with

added Gaussian noise was used as the training/testing data. The SWGs were presented at

frequency of 1.25cycles/visual degree, and the responses were calculated by averaging over 8

evenly spaced phase values in $[0°, 360°)$. Each simulation was repeated 100 times, each time

with 5-fold validation. Figure 4C shows the results for a 0dB SNR, but the overall trends

remained unchanged for -3dB and 3dB SNR levels (Supplementary Figure S 3).

Post-convergence threshold variation in STDP

To test how post-learning changes in the threshold affect the specificity of a converged network,

we tested an STDP network trained using a threshold $\Theta_{training}$ by increasing or decreasing its

threshold (to say, $\Theta_{testing}$) and presenting it with SWGs (same stimuli as the ones used to

calculate the FI). We report the results of seven simulations where the relative change in

threshold was given by 25% increments/decrements, i.e.:

$$\frac{\Theta_{testing} - \Theta_{training}}{\Theta_{training}} = \{0, \pm 0.25, \pm 0.50, \pm 0.75\}$$

The results reported in Figure 4D were calculated for an input SNR of 0dB, but similar results

were obtained for -3 and 3dB SNR as well (Supplementary Figure S 4).

Kullback-Leibler divergence

For each model, we estimated probability density functions (pdfs) over parameters such as the

FSVs and the population bandwidth. To quantify how close the model pdfs were to those

estimated from the macaque data, we employed the Kullback-Leibler (KL) divergence. KL

divergence is a directional measure of distance between two probability distributions. Given

two distributions P and Q with corresponding probability densities p and q, the KL divergence

(denoted D_{KL}) from a Q to P is given by:

510
$$D_{KL}(P||Q) = \int_{\Omega} p(\boldsymbol{x}) \log_2 \left(\frac{p(\boldsymbol{x})}{q(\boldsymbol{x})} \right) d\boldsymbol{x}$$

Here, $\boldsymbol{\Omega}$ is the support of the distribution Q. In our analysis, we considered p as a pdf estimated

from the macaque data, and q as the pdf (of the same variable) estimated using ICA, SC or

STDP. In this case, KL divergence lends itself to a very intuitive interpretation: it can be

considered as the additional bandwidth (in bits) which would be required if the biological

variable were to be encoded using one of the three computational models. Note that P and Q

may be multivariate distributions.

Sparsity: Gini index

The sparseness of the encoding was evaluated using the Gini index (GI). GI is a measure which

characterises the deviation of the population-response from a uniform distribution of activity

across the samples. It is 0 if all units have the same response and tends to 1 as the responses

become sparser (being equal to 1 if only one unit responds, while others are silent). It is invariant

to the range of the responses within a given sample, and robust to variations in sample-size

(Hurley & Rickard, 2009). Formally, the GI (denoted here as Λ) is given by:

$$\Lambda(\boldsymbol{x}) = 1 - 2\int_0^1 L(F)\, dF$$

Here, L is the Lorenz function defined on the cumulative probability distribution F of the neural activity (say, $\boldsymbol{x}$). We defined two variants of the GI which measure the spatial (Λ_s) and temporal sparsity (Λ_t) of an ensemble of encoders (Figure 5A). Given a sequence of M inputs to an ensemble of N neurones, the spatial sparsity of the ensemble response to the mth stimulus is given by:

$$\Lambda_S(m) = \Lambda(\{x_m^1, x_m^2, \dots, x_m^N\})$$

Here, x_m^n denotes the activity of the nth neurone in response to the mth input. Similarly, the temporal sparsity of the nth neurone over the entire sequence of inputs is given by:

$$\Lambda_T(n) = \Lambda(\{x_1^n, x_2^n, \dots, x_M^n\})$$

Code

The code for ICA was written in python using the sklearn library which implements the classical *fastICA* algorithm. The code for SC was based on the C++ and Matlab code shared by Prof. Bruno Olshaussen. The STDP code was based on a previously published binocular-STDP algorithm available here.

Bibliography

Abraham, W. C. (2008). Metaplasticity: Tuning synapses and networks for plasticity. *Nature*

Reviews Neuroscience, *9*(5), 387. https://doi.org/10.1038/nrn2356

Anderson, C., Van Essen, D., & Olshausen, B. (2005). CHAPTER 3—Directed Visual

Attention and the Dynamic Control of Information Flow. In L. Itti, G. Rees, & J. K.

Tsotsos (Eds.), *Neurobiology of Attention* (pp. 11–17). Academic Press.

https://doi.org/10.1016/B978-012375731-9/50007-0

Bao, M., Yang, L., Rios, C., He, B., & Engel, S. (2010). Perceptual learning increases the

strength of the earliest signals in visual cortex. *The Journal of Neuroscience : The*

Official Journal of the Society for Neuroscience, *30*(45), 15080–15084.

https://doi.org/10.1523/JNEUROSCI.5703-09.2010

Bell, A., & Sejnowski, T. (1997). The "independent components" of natural scenes are edge

filters. *Vision Research*, *37*(23), 3327–3338. https://doi.org/10.1016/S0042-

6989(97)00121-1

Beyeler, M., Rounds, E., Carlson, K., Dutt, N., & Krichmar, J. (2019). Neural correlates of

sparse coding and dimensionality reduction. *PLOS Computational Biology*, *15*(6),

e1006908. https://doi.org/10.1371/journal.pcbi.1006908

Brito, C. S. N., & Gerstner, W. (2016). Nonlinear Hebbian Learning as a Unifying Principle in

Receptive Field Formation. *PLOS Computational Biology*, *12*(9), e1005070.

https://doi.org/10.1371/journal.pcbi.1005070

Bruce, N., Rahman, S., & Carrier, D. (2016). Sparse coding in early visual representation: From

specific properties to general principles. *Neurocomputing*, *171*, 1085–1098.

https://doi.org/10.1016/j.neucom.2015.07.070

Caporale, N., & Dan, Y. (2008). Spike Timing–Dependent Plasticity: A Hebbian Learning

Rule.   *Annual   Review   of   Neuroscience*,   *31*(1),   25–46.

https://doi.org/10.1146/annurev.neuro.31.060407.125639

Chauhan, T., Masquelier, T., Montlibert, A., & Cottereau, B. (2018). Emergence of binocular

disparity selectivity through Hebbian learning. *The Journal of Neuroscience*, *38*(44),

9563–9578. https://doi.org/10.1523/JNEUROSCI.1259-18.2018

Chelaru, M. I., & Dragoi, V. (2008). Efficient coding in heterogeneous neuronal populations.

Proceedings   of   the   National   Academy   of   Sciences,   *105*(42),   16344–16349.

https://doi.org/10.1073/pnas.0807744105

Cooke, S., & Bear, M. (2010). Visual Experience Induces Long-Term Potentiation in the

Primary   Visual   Cortex.   *Journal   of   Neuroscience*,   *30*(48),   16304–16313.

https://doi.org/10.1523/JNEUROSCI.4333-10.2010

Delorme, A., Perrinet, L., & Thorpe, S. J. (2001). Networks of integrate-and-fire neurons using

Rank Order Coding B: Spike timing dependent plasticity and emergence of orientation

selectivity.   *Neurocomputing*,   *38–40*,   539–545.   https://doi.org/10.1016/S0925-

2312(01)00403-9

Dragoi, V., Turcu, C. M., & Sur, M. (2001). Stability of Cortical Responses and the Statistics

of   Natural   Scenes.   *Neuron*,   *32*(6),   1181–1192.   https://doi.org/10.1016/S0896-

6273(01)00540-2

Field, G. D., & Chichilnisky, E. J. (2007). Information Processing in the Primate Retina:

Circuitry   and   Coding.   *Annual   Review   of   Neuroscience*,   *30*(1),   1–30.

https://doi.org/10.1146/annurev.neuro.30.051606.094252

Furmanski, C., & Engel, S. (2000). An oblique effect in human primary visual cortex. *Nature

Neuroscience*, *3*(6), 535–536. https://doi.org/10.1038/75702

Furmanski, C., Schluppeck, D., & Engel, S. (2004). Learning Strengthens the Response of

Primary Visual Cortex to Simple Patterns. *Current Biology*, *14*(7), 573–578.

https://doi.org/10.1016/j.cub.2004.03.032

Geisler, W. (2008). Visual perception and the statistical properties of natural scenes. *Annual*

Review   of   Psychology,   *59*,   167–192.

https://doi.org/10.1146/annurev.psych.58.110405.085632

Grunewald, A., Bradley, D., & Andersen, R. (2002). Neural Correlates of Structure-from-

Motion Perception in Macaque V1 and MT. *Journal of Neuroscience*, *22*(14), 6195–

6207. https://doi.org/10.1523/JNEUROSCI.22-14-06195.2002

Gütig, R., Aharonov, R., Rotter, S., & Sompolinsky, H. (2003). Learning Input Correlations

through Nonlinear Temporally Asymmetric Hebbian Plasticity. *Journal of*

Neuroscience, *23*(9), 3697–3714.

Harnack, D., Pelko, M., Chaillet, A., Chitour, Y., & Rossum, M. C. W. van. (2015). Stability

of Neuronal Networks with Homeostatic Regulation. *PLOS Computational Biology*,

11(7), e1004357. https://doi.org/10.1371/journal.pcbi.1004357

Heeley, D., & Timney, B. (1988). Meridional anisotropies of orientation discrimination for sine

wave gratings. *Vision Research*, *28*(2), 337–344. https://doi.org/10.1016/0042-

6989(88)90162-9

Hoyer, P., & Hyvärinen, A. (2000). Independent component analysis applied to feature

extraction from colour and stereo images. *Network: Computation in Neural Systems*,

11(3), 191–210. https://doi.org/10.1088/0954-898X_11_3_302

Hübener, M., & Bonhoeffer, T. (2014). Neuronal Plasticity: Beyond the Critical Period. *Cell*,

159(4), 727–737. https://doi.org/10.1016/j.cell.2014.10.035

Hunter, D., & Hibbard, P. (2015). Distribution of independent components of binocular natural

images. *Journal of Vision*, *15*(13), 6. https://doi.org/10.1167/15.13.6

Hurley, N., & Rickard, S. (2009). Comparing Measures of Sparsity. *IEEE Transactions on*

Information Theory, *55*(10), 4723–4741. https://doi.org/10.1109/TIT.2009.2027527

Hyvärinen, A., & Oja, E. (2000). Independent component analysis: Algorithms and

applications. *Neural Networks*, *13*(4–5), 411–430. https://doi.org/10.1016/S0893-

6080(00)00026-5

Isomura, T., & Toyoizumi, T. (2018). Error-Gated Hebbian Rule: A Local Learning Rule for

Principal and Independent Component Analysis. *Scientific Reports*, *8*(1), 1835.

https://doi.org/10.1038/s41598-018-20082-0

Jones, J., & Palmer, L. (1987). An evaluation of the two-dimensional Gabor filter model of

simple receptive fields in cat striate cortex. *Journal of Neurophysiology*, *58*(6), 1233–

1258.

Larsen, R. S., Rao, D., Manis, P. B., & Philpot, B. D. (2010). STDP in the Developing Sensory

Neocortex. *Frontiers in Synaptic Neuroscience*, *2*, 9.

https://doi.org/10.3389/fnsyn.2010.00009

Lee, D., & Seung, H. (1999). Learning the parts of objects by non-negative matrix factorization.

Nature, *401*(6755), 788–791. https://doi.org/10.1038/44565

Li, B., Peterson, M., & Freeman, R. (2003). Oblique Effect: A Neural Basis in the Visual

Cortex. *Journal of Neurophysiology*, *90*(1), 204–217.

https://doi.org/10.1152/jn.00954.2002

Liu, Y. S., Stevens, C. F., & Sharpee, T. O. (2009). Predictable irregularities in retinal receptive

fields. *Proceedings of the National Academy of Sciences*, *106*(38), 16499–16504.

https://doi.org/10.1073/pnas.0908926106

Maffei, L., & Campbell, F. (1970). Neurophysiological Localization of the Vertical and

Horizontal Visual Coordinates in Man. *Science*, *167*(3917), 386–387.

https://doi.org/10.1126/science.167.3917.386

Mansfield, R. (1974). Neural Basis of Orientation Perception in Primate Vision. *Science*, *186*(4169), 1133–1135. https://doi.org/10.1126/science.186.4169.1133

Markram, H., Lübke, J., Frotscher, M., Sakmann, B., Hebb, D. O., Bliss, T. V. P., Collingridge, G. L., Friedlander, M. J., Sayer, R. J., Redman, S. J., Stuart, G., Sakmann, B., Regehr, W. G., Connor, J. A., Tank, D. W., Markram, H., Lübke, J., Frotscher, M., Roth, A., … Singer, W. (1997). Regulation of synaptic efficacy by coincidence of postsynaptic APs and EPSPs. *Science*, *275*(5297), 213–215. https://doi.org/10.1126/science.275.5297.213

Martinez-Garcia, M., Martinez, L. M., & Malo, J. (2017). Topographic Independent Component Analysis reveals random scrambling of orientation in visual space. *PLOS ONE*, *12*(6), e0178345. https://doi.org/10.1371/journal.pone.0178345

Masquelier, T. (2012). Relative spike time coding and STDP-based orientation selectivity in the early visual system in natural continuous and saccadic vision: A computational model. *Journal of Computational Neuroscience*, *32*(3), 425–441. https://doi.org/10.1007/s10827-011-0361-9

Masquelier, T., & Thorpe, S. J. (2007). Unsupervised learning of visual features through spike timing dependent plasticity. *PLoS Computational Biology*, *3*(2), e31. https://doi.org/10.1371/journal.pcbi.0030031

Nienborg, H., & Cumming, B. (2006). Macaque V2 Neurons, But Not V1 Neurons, Show Choice-Related Activity. *Journal of Neuroscience*, *26*(37), 9567–9578. https://doi.org/10.1523/JNEUROSCI.2256-06.2006

Olshausen, B., & Field, D. (1996). Emergence of simple-cell receptive field properties by learning a sparse code for natural images. *Nature*, *381*(6583), 607–609. https://doi.org/10.1038/381607a0

Olshausen, B., & Field, D. (1997). Sparse coding with an overcomplete basis set: A strategy employed by V1? *Vision Research*, *37*(23), 3311–3325. https://doi.org/10.1016/S0042-6989(97)00169-7

Orban, G., Vandenbussche, E., & Vogels, R. (1984). Human orientation discrimination tested with long stimuli. *Vision Research*, *24*(2), 121–128. https://doi.org/10.1016/0042-6989(84)90097-X

Perrinet, L. U. (2019). An Adaptive Homeostatic Algorithm for the Unsupervised Learning of Visual Features. *Vision*, *3*(3), 47. https://doi.org/10.3390/vision3030047

Perrinet, L. U., & Bednar, J. A. (2015). Edge co-occurrences can account for rapid categorization of natural versus animal images. *Scientific Reports*, *5*, 11400. https://doi.org/10.1038/srep11400

Quiroga, R., & Panzeri, S. (2009). Extracting information from neuronal populations: Information theory and decoding approaches. *Nature Reviews Neuroscience*, *10*(3), 173–185. https://doi.org/10.1038/nrn2578

Raichle, M. (2010). Two views of brain function. *Trends in Cognitive Sciences*, *14*(4), 180–190. https://doi.org/10.1016/j.tics.2010.01.008

Ringach, D. (2002). Spatial Structure and Symmetry of Simple-Cell Receptive Fields in Macaque Primary Visual Cortex. *Journal of Neurophysiology*, *88*(1). http://jn.physiology.org/content/88/1/455.short

Ringach, D., & Shapley, R. (2004). Reverse correlation in neurophysiology. *Cognitive Science*, *28*(2), 147–166. https://doi.org/10.1207/s15516709cog2802_2

Ringach, D., Shapley, R., & Hawken, M. (2002). Orientation Selectivity in Macaque V1: Diversity and Laminar Dependence. *Journal of Neuroscience*, *22*(13), 5639–5651. https://doi.org/10.1523/JNEUROSCI.22-13-05639.2002

Savin, C., Joshi, P., & Triesch, J. (2010). Independent Component Analysis in Spiking Neurons.

PLoS Computational Biology, *6*(4), e1000757.

https://doi.org/10.1371/journal.pcbi.1000757

Shamir, M., & Sompolinsky, H. (2004). Nonlinear Population Codes. *Neural Computation*,

16(6), 1105–1136. https://doi.org/10.1162/089976604773717559

van Hateren, J., & van der Schaaf, A. (1998). Independent component filters of natural images

compared with simple cells in primary visual cortex. *Proceedings. Biological Sciences*

/ The Royal Society, *265*(1394), 359–366. https://doi.org/10.1098/rspb.1998.0303

Vogels, R., & Orban, G. (1990). How well do response changes of striate neurons signal

differences in orientation: A study in the discriminating monkey. *Journal of*

Neuroscience, *10*(11), 3543–3558. https://doi.org/10.1523/JNEUROSCI.10-11-

03543.1990

Wandell, B., & Smirnakis, S. (2010). Plasticity and stability of visual field maps in adult

primary visual cortex. *Nature Reviews Neuroscience*, *10*(12), 873.

https://doi.org/10.1038/nrn2741

Wei, X. X., & Stocker, A. (2017). Lawful relation between perceptual bias and discriminability.

Proceedings of the National Academy of Sciences, *114*(38), 10244–10249.

https://doi.org/10.1073/pnas.1619153114

Zhaoping, L. (2006). Theoretical understanding of the early visual processes by data

compression and data selection. *Network: Computation in Neural Systems*, *17*(4), 301–

334. https://doi.org/10.1080/09548980600931995

Zylberberg, J., Murphy, J. T., & DeWeese, M. R. (2011). A Sparse Coding Model with

Synaptically Local Plasticity and Spiking Neurons Can Account for the Diverse Shapes

of V1 Simple Cell Receptive Fields. *PLoS Computational Biology*, *7*(10), e1002250.

https://doi.org/10.1371/journal.pcbi.1002250

Supplementary Material

Kullback-Leibler divergence of receptive-field shape distributions

	ICA	SC	STDP
Joint distribution			
$[n_x \; n_y]^T$	14.6	8.4	3.0
Marginal distributions			
n_x	7.6	1.4	1.3
n_y	14.0	3.8	0.4

Table S 1: Kullback-Leibler (KL) divergence of frequency-normalised spread vectors (FSVs) from the models to
the macaque distribution. The receptive-field (RF) shape of the neurones from the models and measurements in
macaque V1 (Ringach, 2002) was parametrised by estimating the frequency-normalised spread vectors (FSVs).
FSVs are characterised by two parameters n_x and n_y: n_x is proportional to the number of lobes in the receptive
field, and n_y is modulated by its elongation. The KL divergence reflects the number of additional bits required to
encode the parameter(s) of interest from the macaque data using the distributions from one of the three models
(ICA, SC or STDP). The KL divergence for the FSV reported in the Results section was based on an estimation
of the joint distribution of the two FSV parameters. Here, we also report the KL divergence for the marginal
distribution of each FSV parameter separately. All values are in bits.

   Frequency-normalised spread vector distributions

Figure S 1: Frequency-normalised spread vector (FSV) distributions. FSVs are a compact metric for quantifying
RF shape. To facilitate comparison with macaque data in Figure 2D, the two axes were cut off at 1.5 (marked with
red, dashed lines). Here, we show the data without any cut-offs. The macaque data (black) and STDP (pink) are
limited to a small region near the origin, while ICA (green) and SC (blue) show a much higher range of values.

Effect of noise on ideal observer responses

Figure S 2: Ideal observer response across noise levels. Approximations of Fisher information were used to
estimate ideal observer responses to sine-wave gratings with additive Gaussian noise (Figure 4B). The
approximations were made at three noise levels: -3dB, 0dB and 3dB, corresponding to the variance of the noise
being double, equal to or half the signal variance.

Effect of noise on linear decoding

Figure S 3: Classification accuracy across noise levels. Decoding scores of a linear classification model were
calculated by using stimulus orientation as the class labels and population responses to the stimuli as the
training/testing data (Figure 4C). The stimuli used were sine-wave gratings with three levels of additive Gaussian
noise: -3dB, 0dB and 3dB, corresponding to the variance of the noise being double, equal to or half the signal
variance.

Effect of noise on the cardinal orientation bias

Figure S 4: Cardinal orientation bias across noise levels. The threshold of the STDP model was increased/decreased post-convergence to investigate its effect on the modulation of the ideal observer response at horizontal and vertical (cardinal) orientations (Figure 4D). Oriented sine-wave gratings with additive Gaussian noise were used for these simulations. The simulations were run at three noise levels: -3dB, 0dB and 3dB, corresponding to the variance of the noise being double, equal to or half the signal variance.

Fisher information from spiking and non-spiking responses

Figure S 5: Spiking and non-spiking activity. The STDP model was presented with oriented sine-wave grating stimuli (see Methods and Figure 4A) and the resulting activity was used to estimate the Fisher information using spiking and non-spiking responses of the network. This was used to compute ideal-observer performance as a function of the stimulus orientation.