10   Functional brain network reconfiguration during learning in a dynamic environment

11   Chang-Hao Kao[1], Ankit N. Khambhati[2], Danielle S. Bassett[3,4,5,6,7,8], Matthew R. Nassar[9,10],
12   Joseph T. McGuire[11], Joshua I. Gold[12], Joseph W. Kable[1,*]

[1]Department of Psychology, University of Pennsylvania, Philadelphia, PA 19104, USA

[2]Department of Neurological Surgery, University of California, San Francisco, CA 94122, USA

[3]Department of Bioengineering, University of Pennsylvania, Philadelphia, PA 19104, USA

[4]Department of Neurology, University of Pennsylvania, Philadelphia, PA 19104, USA

[5]Department of Electrical & Systems Engineering, University of Pennsylvania, Philadelphia, PA
19104 USA

[6]Department of Physics & Astronomy, University of Pennsylvania, Philadelphia, PA 19104,
USA

[7]Department of Psychiatry, University of Pennsylvania, Philadelphia, PA 19104, USA

[8]Santa Fe Institute, Santa Fe, NM 87501, USA

[9]Department of Neuroscience, Brown University, Providence, RI 02912, USA

[10]Robert J. and Nancy D. Carney Institute for Brain Science, Brown University, Providence, RI
02912, USA

[11]Department of Psychological and Brain Sciences, Boston University, Boston, MA 02215, USA

[12]Department of Neuroscience, University of Pennsylvania, Philadelphia, PA 19104, USA

[*] Correspondence: kable@psych.upenn.edu

Abstract

When learning about dynamic and uncertain environments, people should update their beliefs
most strongly when new evidence is most informative, such as when the environment undergoes
a surprising change or existing beliefs are highly uncertain. Here we show that modulations of
surprise and uncertainty are encoded in a particular, temporally dynamic pattern of whole-brain
functional connectivity, and this encoding is enhanced in individuals that adapt their learning
dynamics more appropriately in response to these factors. The key feature of this whole-brain
pattern of functional connectivity is stronger connectivity, or functional integration, between the
fronto-parietal and other functional systems. Our results provide new insights regarding the
association between dynamic adjustments in learning and dynamic, large-scale changes in
functional connectivity across the brain.

Introduction

Human decisions are guided by beliefs about current features of the environment. These beliefs often must be inferred from indirect and uncertain evidence. For example, deciding to go to a restaurant typically relies on a belief about its current quality, which can be inferred from past experiences at that restaurant. This inference process is particularly challenging in dynamic environments whose features can change unexpectedly. For example, the current quality of the restaurant might not reflect its past quality if a new chef was just hired. In these environments, people tend to follow normative principles and update their beliefs dynamically and adaptively, such that new evidence is used to update existing beliefs more strongly in some conditions (e.g., when existing beliefs are weak or irrelevant, and/or the new evidence is strong or surprising) than others (e.g., when existing beliefs are strong and relevant, and/or the new evidence is weak or expected)[1, 2, 3]. A number of studies have begun to identify potential neural substrates of this adaptive belief-updating process, including univariate and multivariate activity patterns that encode key variables like uncertainty and surprise in a number of brain regions including parts of the dorsomedial frontal cortex, anterior insula, lateral prefrontal cortex, and lateral parietal cortex[2, 4, 5, 6, 7]. The goal of the present study was to gain deeper insights into how these representations might interact dynamically and adaptively to support dynamic and adaptive belief updating.

Here we focused on how changes in belief updating relate to changes in functional connectivity between brain regions with task-relevant activity modulations. Functional connectivity reflects statistical dependencies between regional activity time series[8] and can be used to build functional-connectivity networks that can provide new perspectives on brain function[9, 10, 11]. Many recent studies of learning have focused on brain network reconfigurations that occur between naïve and well-learned phases in various domains such as motor, perceptual, category, spatial, or value learning[12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22]. In these cases, functional connectivity associated with the fronto-parietal system decreased gradually as learning progressed and this change in connectivity was associated with individual learning or performance[13, 19, 22]. In dynamic environments, however, people progressively learn the current state and then re-initialize learning once the state changes. Thus, we expected frequent reconfigurations in functional connectivity, as learning shifts between slower and faster updating in response to changes in uncertainty and surprise. Additionally, although brain regions that encode uncertainty and surprise participate in multiple networks, including the fronto-parietal task control system, the dorsal attention system, the salience system, and the memory system[2, 4, 5, 6, 7], based on previous network analyses of learning in stable environments we hypothesized that the fronto-parietal system would serve a particularly important role in network reconfiguration during learning in dynamic environments.

In the current study, we aimed to identify such frequent reconfigurations in functional connectivity during adaptive belief updating. A key to our approach was the use of an unsupervised machine-learning technique known as non-negative matrix factorization (NMF)[23]. NMF decomposes the whole-brain network into subgraphs, which describe patterns of functional connectivity across the entire brain, and the time-dependent magnitude with which these subgraphs are expressed. Briefly, a subgraph is a weighted pattern of functional interactions that that statistically recurs as the brain network evolves over time. We chose NMF because it provides two key advantages over other approaches to matrix factorization, such as principal components analysis (PCA) or independent components analysis (ICA)[24, 25]. First, NMF yields a

parts-based representation of the network, in which the individual components are strictly
additive – a constraint that is not present in PCA and ICA. This important feature enables
interpretation of the resulting subgraph and time-dependent expression coefficients on the basis
of their positive distance from zero. Second, NMF does not enforce an orthogonality or
independence constraint and, therefore, allows subgraphs to overlap in their structure. This
property may more effectively model distinct subgraphs that may be jointly related via weak
connections and better account for the flexibility of neural systems, such that one connection
between regions can be involved in multiple systems or cognitive functions. Recently, NMF has
been used to identify network dynamics during rest and task states[25, 26] and to determine how
these dynamics vary across development[24]. Here we extend the use of this technique to examine
changes in network dynamics linked to task variables and individual differences.

Our primary hypothesis was that uncertainty and surprise, task variables that drive the
adjustment of learning, are related to the temporal expression of specific patterns of functional
connectivity (i.e., specific subgraphs). Given previous univariate and multivariate results on
learning in dynamic environments, and previous network results on learning in stable
environments, we expected these patterns of functional connectivity to prominently involve the
fronto-parietal network. We also expected that the dynamic modulation of these patterns of
functional connectivity (i.e., subgraph expression) are associated with individual differences in
learning.

Results

Belief updating is influenced by normative factors related to uncertainty and surprise

Participants performed a predictive-inference task during fMRI (Fig. 1a). For this task,
participants positioned a bucket to catch a bag that dropped from an occluded helicopter. The
location of the bag was sampled from a Gaussian distribution with a mean value that
corresponded to the location of the helicopter and a standard deviation (noise level) that was set
to either high or low in each 120-trial run. The location of the helicopter usually remained stable
but occasionally changed suddenly and unpredictably (with an average probability of change of
0.1 across trials); the new location was sampled from a uniform distribution. Additionally,
whether the bag (if caught) was rewarded or neutral was assigned randomly on each trial and
indicated by color. This task challenged participants to form and update a belief about a latent
variable (the location of the helicopter) based on noisy evidence (the location of dropped bags).

In our previous reports[2, 7], we described a theoretical model approximating the normative
solution for this task. This theoretical model takes the form of a delta-rule and approximates the
Bayesian ideal observer. Beliefs (B_{t+1}) are updated based on past beliefs (B_t) and prediction
errors ($X_t - B_t$; the difference between the current outcome location and the predicted location),
with the extent of updating controlled by a learning rate (α_t; Fig. 1b). Learning rates vary from
trial to trial and are determined by two factors: (i) change-point probability (CPP), which is the
probability that a change-point has happened and represents a form of belief surprise; and (ii)
relative uncertainty (RU), which is the reducible uncertainty regarding the current state relative
to the irreducible uncertainty that results from environmental noise and represents a form of
belief uncertainty (Fig. 1c). Learning rates are higher when either CPP or RU is higher: $\alpha_t = $
$CPP + RU(1 - CPP)$.

We previously reported how participants' predictions were influenced by both normative
and non-normative factors and how these factors that influence learning are encoded in
univariate and multivariate activity[2, 7]. Participants updated their beliefs more when the value of
CPP or RU was higher, consistent with the normative model. Participants also updated their
beliefs more when the outcome was rewarded, however, which is not a feature of the normative
model. CPP, RU and reward, as well as residual updating (belief updating not captured by CPP,
RU or reward), were all encoded in univariate and multivariate brain activity in distinct regions[2,
7]. In the current study, we built on these previous findings and investigated how these factors, as
well as individual differences in how these factors influence belief updating, are related to the
dynamics of whole-brain functional connectivity.

NMF identified ten subgraphs, or patterns of whole-brain functional connectivity, that varied
over time

We used NMF to decompose whole-brain functional connectivity over time into specific
patterns of functional connectivity, called subgraphs, and quantified the expression of these
patterns over time. To perform NMF, we first defined regions of interest (ROIs) based on a
previously defined parcellation[27] (Fig. 2a) and extracted blood-oxygenation-level-dependent
(BOLD) time series for each ROI (Fig. 2b). For every pair of ROIs, we calculated the Pearson
correlation coefficient between the BOLD time series in 10-TR (25 s) time windows, offset by 2
TRs for each time step (and thus 80% overlap between consecutive time windows). This
procedure thus yielded a matrix whose entries represented time-dependent changes in the
strengths of these pairwise correlations in the brain during the task. We unfolded each time
window from this correlation matrix (Fig. 2c) into a one-column vector, and then concatenated
these vectors from all time windows and all participants (Fig. 2d). As required for NMF, we
transformed the resulting matrix to have strictly non-negative values: we duplicated the full
matrix, set all negative values to zero in the first copy, and set all positive values to zero in the
second copy before multiplying all remaining values by negative one. Thus, we divided the final
full data matrix into two halves, with one half containing the positive correlation coefficients
(zero if the coefficient was negative) and one half containing the absolute values of the negative
correlation coefficients (zero if the coefficient was positive)[26]. This procedure ensured that our
approach did not give undue preference to either positive or negative functional connectivity, and
that subgraphs were identified based on both positive and negative functional connectivity.

We applied NMF to this matrix (A) to identify functional subgraphs and their expression
over time. Specifically, we decomposed the full data matrix into a subgraph matrix W and an
expression matrix H (Fig. 2d). The columns of W represent different subgraphs and the rows
represent different edges (i.e., pairs of regions), with the value in each cell representing the
strength of that edge (i.e., the functional connectivity strength for that pair of regions) for that
subgraph. The rows of H represent different subgraphs, and the columns represent time
windows, with the value in each cell representing the degree of expression of that subgraph in
that time window. We implemented NMF by minimizing the residual error ($\|A - WH\|_F^2$) via
three parameters: (i) the number of subgraphs (k), (ii) the subgraph regularization (α), and (iii)
the expression sparsity (β) (Supplementary Fig. 1). The final result of NMF is a set of subgraphs
(the number of which was determined by the parameter k), which reflected patterns of functional
connectivity strengths across every pair of regions in the brain, as well as the expression of these
subgraphs over time.

Using NMF, we identified ten subgraphs in our data. The full description of each
subgraph specifies the edge strength between every pair of ROIs, corresponding to a 247x247
matrix. We calculated a simpler summary description that specifies the edge strength between
every pair of functional systems in the previously defined parcellation, corresponding to a 13x13
matrix[27]. Edges between ROIs were categorized according to the functional system of each ROI.
To estimate the diagonal entries in the system-by-system matrix, we averaged the weights of all
edges connecting two ROIs within a given system (Fig. 3a). To estimate the off-diagonal entries
of the system-by-system matrix, we averaged the weights of all edges linking an ROI in one
system with an ROI in another system. In line with common parlance, we refer to the edges
within the same system as within-system edges, whereas we refer to the edges between two
different systems as between-system edges. For presentation, we ordered and numbered the ten
subgraphs according to the strength of within-system edges relative to that of between-system
edges (Fig. 3b, Supplementary Fig. 2a-c). Finally, we thresholded the system-by-system matrix
to show only edges that passed a permutation test ($p<0.05$ after the Bonferroni correction for
multiple comparisons; see Methods).

Figure 3b shows the ten subgraphs identified in our data. Two examples have relatively
straightforward interpretations. Subgraph 1 has high edge strengths along the diagonal. Thus, this
subgraph describes functional connectivity that lies predominantly within functional systems. In
contrast, subgraph 5 has high edge strengths along a single row and column, corresponding to the
visual system. Thus, this subgraph describes functional connectivity that predominantly links the
visual system with all other systems. Many of the other subgraphs have more complex patterns
than these two examples.

The full data matrix on which we performed NMF was divided into two halves, with the
first half corresponding to positive functional connectivity and the second half corresponding to
negative functional connectivity. The expression matrix H was therefore also divided into two
halves, with the first half corresponding to positive expression over time and the second half
corresponding to negative expression over time. Positive and negative expression coefficients
were highly negatively correlated with each other across time for all the subgraphs (all $r<-0.61$,
all $p<0.001$). Given this result, for the analyses of subgraph expression below, we constructed a
measure of relative subgraph expression by subtracting the negative expression from the positive
expression at each time point[26]. Across subgraphs, the average relative expression across time
was strongly correlated with the relative strength of within- versus between-system edges
(Supplementary Fig. 2d-f). That is, higher within-system strength was associated with greater
relative expression of the subgraph. This result implies that the subgraphs are also numbered
roughly in order of their average relative expression.

Normative factors that drive belief updating modulated the temporal expression of a learning-
related subgraph

We next investigated how CPP, RU, reward, and residual updating influenced the
temporal expression of each subgraph. We identified a particularly strong relationship between
the normative factors (CPP, RU and the residuals that reflected the participants' subjective
estimates of those variables) and subgraph 4, whose strongest edges were in the fronto-parietal
task-control system, followed by the memory retrieval, salience and dorsal-attention systems
(Fig. 4d). Specifically, we used multiple regression to estimate the trial-by-trial relationship

between these four factors and the relative expression strength of each subgraph. Regression coefficients were fitted separately for each participant and each subgraph. Then, the significance of these coefficients was tested at the group level for each subgraph (Supplementary Fig. 3). Among the ten subgraphs, these four factors explained the most variance in the time-dependent relative expression of subgraph 4 (Supplementary Fig. 2g), in each case showing positive modulations (CPP: mean±SEM=0.202±0.053, t_{31}=3.78, $p<0.001$; RU: 0.392±0.077, t_{31}=5.11, $p<0.001$; residual updating: 0.177±0.079, t_{31}=2.23, $p=0.033$; Fig 4a). We also evaluated the influence of head motion by including motion, as indexed as the relative root-mean-square of the six motion parameters, in the regression model. Motion was not significant ($p=0.29$) and the effects of CPP, RU and residual updating remained significant and of similar effect size.

Although CPP or RU also modulated the relative expression of some other subgraphs (e.g., subgraph 1, 3 and 7; Supplementary Fig. 3), below we focus on subgraph 4 for several reasons. First, as stated above, the four factors we investigated (CPP, RU, reward and residual updating) explained more variance in the time-dependent relative expression of subgraph 4 than that of any other subgraph. Second, the effects of CPP and RU on subgraph 4 were strong enough to survive correction for multiple comparisons across ten subgraphs, whereas the effects of CPP and RU on other subgraphs were not. Third, as discussed below (see the section of "Results are robust to the time window used to identify functional connectivity"), the effects of CPP and RU on subgraph 4 were also robust across analyses that used differently sized time windows, whereas the effects of CPP and RU on other subgraphs were not.

Expression of the learning-related subgraph varied across subjects with individual differences in normative belief updating

The expression of subgraph 4 was not only modulated by task factors that drive normative learning, but also varied across subjects in a manner that reflected individual differences in normative learning. As an index of normative learning, we estimated the influence of CPP and RU on trial-by-trial belief updates using multiple regression and took the sum of the regression coefficients of CPP (β_2 in Equation 6) and RU (β_3 in Equation 6) for each participant[2]. This sum reflected how much each individual updated their beliefs in response to normative factors. We examined the relationship between individual differences in this normative belief-updating metric and two aspects of subgraph expression.

First, we examined the relationship between normative belief updating and the dynamic modulation of subgraph expression by normative factors (Supplementary Fig. 4). As an index of the dynamic modulation of subgraph expression by normative factors, we used the sum of the regression coefficients of CPP and RU on relative subgraph expression from the analyses above (Supplementary Fig. 3). We found a positive correlation between the dynamic modulation of subgraph 4 expression by normative factors and normative belief updating across participants ($r=0.448$, $p=0.004$; Fig. 4b). Second, we examined the relationship between normative belief updating and the average relative subgraph expression (Supplementary Fig. 5). We also found a positive correlation between the average relative expression of subgraph 4 and normative belief updating across participants ($r=0.332$, $p=0.029$; Fig. 4c). These effects were still significant when we controlled for the influence of motion on dynamic modulation or average relative expression, whereas the effects of motion itself were not significant (all $p>0.31$).

These two results show that participants with the highest average relative expression of
subgraph 4, and for whom the normative factors account for the most variance in the relative
expression of subgraph 4 across time, tended to update their beliefs in a manner more consistent
with the normative model than the other subjects.

Contribution of specific edges within the learning-related subgraph to its relationship with task
factors and individual differences

Subgraph 4 describes both within- and between-system functional connectivity for
multiple different functional systems (Figs. 3b and 4d-e, Supplementary Fig. 2a-c). We next
examined the contribution of specific edges (i.e., functional connectivity between specific pairs
of brain regions) within subgraph 4 to the task and individual difference effects we observed for
that subgraph.

The task-related modulations of subgraph 4 involved primarily between-system, not
within-system, functional connectivity. Specifically, we re-estimated the effects of CPP, RU,
reward, and residual updating on the relative expression of subgraph 4 using only within-system
edges (i.e., only the diagonal cells of the system-by-system matrix in Fig. 3b; "Within") or only
between-system edges (i.e., only the off-diagonal cells of the system-by-system matrix in Fig.
3b; "Between"). We compared these effects to our previous estimates using all edges (Fig. 5a;
"All"). Removing the between-system edges (Within versus All) reduced the size of the
estimated effects of CPP (mean±SEM=-0.155±0.042, t_{31}=-3.73, p<0.001), RU (-0.300±0.062,
t_{31}=-4.82, p<0.001), and residual updating (-0.140±0.053, t_{31}=-2.63, p=0.013). In contrast,
removing the within-system edges (Between versus All) led to no reliable changes in these
effects (all p>0.21). Further, in a direct comparison of the reduced subgraphs with only within-
or between-system edges, the effects estimated with between-system edges only were stronger
for CPP (0.151±0.042, t_{31}=3.63, p<0.001), RU (0.290±0.063, t_{31}=4.63, p<0.001), and residual
updating (0.139±0.048, t_{31}=2.91, p=0.007).

The contributions of within- and between-system functional connectivity to the individual
difference effects of subgraph 4 were less clear. For the relationship between individual
differences in normative learning and average relative expression, the pattern across comparisons
was similar to that observed for task effects (Fig. 5b), which would indicate a greater
contribution of between-system edges, but none of the comparisons were statistically significant.
In contrast, for the relationship between individual differences in normative learning and the
dynamic modulation of subgraph 4, within-system edges appeared to be more important, as
removing the within-system edges (Between versus All) reduced this correlation (difference =
0.048, p=0.006; Fig. 5b).

We also identified contributions of specific functional systems and of specific system-by-
system edges to the task and individual difference effects on subgraph 4. Specifically, we
conducted similar analyses to the ones described above after removing all edges of one
functional system (i.e., one row/column from the system-by-system matrix in Figure 3b;
Supplementary Fig. 6) or removing one system-by-system edge (i.e., one cell from the system-
by-system matrix in Figure 3b; Supplementary Fig. 7). Detailed results from these analyses are
provided in the supplementary materials, but generally the strongest functional systems or
individual edges in subgraph 4 (Fig. 4d) contributed the most to the task and individual
difference effects described above.

Results are robust to the time window used to identify functional connectivity

For the analyses above, we calculated functional connectivity within time windows of 25
seconds (10 TRs), with an overlap between adjacent windows of 20 seconds (8 TRs). To
determine the sensitivity of our results to the size of this time window, we repeated the entire
procedure using shorter (8-TR/20 s window with 6-TR/15 s overlap; Supplementary Fig. 8-11) or
longer (12-TR/30 s window with 10-TR/25 s overlap; Supplementary Fig. 12-15) time windows.
That is, we shorten or lengthen the time window by the interval of one trial (~5 s). With both
shorter and longer time windows, we identified ten subgraphs. As a measure of the similarity
between these subgraphs and the subgraphs identified in the main analysis, we calculated the
Pearson correlation coefficient between the edge strengths of the subgraphs, for both edges
between ROIs and edges between systems. There was a high degree of similarity between the ten
subgraphs identified in the main analysis and those identified using either shorter (edges between
nodes: all $r>0.81$; edges between systems: all $r>0.80$) or longer (edges between nodes: all
$r>0.98$; edges between systems: all $r>0.98$) time windows. With longer time windows, the
relative expression of subgraph 4 still showed the same relationship to task factors (CPP and RU)
and to individual differences in normative learning; with shorter time windows, these effects
were also present but weaker.

Relationship between the learning-related subgraph and univariate activity

In our previous report, we described how CPP, RU, reward, and residual updating
influenced univariate brain activity. In a final set of analyses, we examined the relationship
between these previously reported univariate effects and the changes in dynamic functional
connectivity we identified above.

The brain regions that were most strongly represented in subgraph 4 overlapped spatially
with the brain regions whose activity was modulated reliably by CPP and RU in our previous
report. As a measure of a region's involvement in subgraph 4, for each ROI, we calculated the
mean strength of every edge between that ROI and all other ROIs in subgraph 4, and normalized
these mean values between 0 and 1. We then related this metric to activation from our previous
study[2], as measured by the *z*-statistic of the modulation effect of CPP or RU. This *z*-statistic
indicated the effect size of change of univariate activity in response to CPP or RU across
participants. Across all ROIs, there was a positive correlation between edge strength in subgraph
4 and activation for CPP ($r=0.403$, $p<0.0001$; Fig. 6a) and activation for RU ($r=0.704$, $p<0.0001$;
Fig. 6b). Figure 6c shows the map of normalized mean edge strengths for subgraph 4 alongside
the thresholded activation maps for CPP and RU. Regions with stronger edge strength in
subgraph 4, such as the insula, dorsomedial frontal cortex, dorsolateral prefrontal cortex,
posterior parietal cortex, and occipital cortex, also tended to show stronger increases in
activation with increases in CPP and RU.

In addition to these strong associations between univariate brain activation and edge
strength, effects beyond those captured by univariate task activity also contributed to our
dynamic functional connectivity results. To demonstrate this, we first fit a general linear model
to quantify effects of CPP, RU, reward, and residual updating on univariate brain activity. For
each ROI, we then constructed a time series of predicted BOLD activity from this GLM. This

predicted BOLD time series captured all fluctuations in activity in that ROI that could be
accounted for by the linear effects of CPP, RU, reward, and residual updating. Next, we
estimated the matrix of functional connectivity from this predicted task-modulated BOLD time
series. This matrix captures only the aspects of functional connectivity that can be fully
explained by task-modulated co-activation across brain regions. We then performed NMF on this
matrix and repeated all of our main analyses, including task effects and individual difference
effects (Supplementary Fig. 16-19). This analysis again identified a subgraph 4 whose strongest
edges were in the fronto-parietal system, but it did not recapitulate all of the relationships
between subgraph 4 expression and task factors and individual differences seen in our main
analyses. Namely, with regard to task effects, only RU significantly modulated the temporal
expression of the subgraph, and with regard to individual-difference effects, only the relationship
between individual differences in normative learning and average relative expression was
significant. These results implied that the dynamic functional connectivity patterns identified in
our main analyses reflect a mixture of coordinated activity across regions (which can be captured
by univariate analyses) and other statistical dependencies across regions that require network-
based analyses.

Discussion

We identified a pattern of dynamic functional brain connectivity in human subjects
performing a predictive-inference task. This pattern was expressed most strongly during times
that demanded faster belief updating and was enhanced in individuals who most effectively used
adaptive belief updating to perform the task. To identify this pattern, we used NMF, an
unsupervised machine-learning technique that decomposes the full matrix of time-dependent
functional connectivity into subgraphs (patterns of functional connectivity), and the time-
dependent magnitude of these subgraphs. Among the subgraphs we identified in our data, the
expression of one subgraph in particular was modulated reliably by three trial-by-trial factors
that influenced the degree of behavioral belief updating: CPP (surprise), RU (uncertainty), and
residual updating (updating unaccounted for by surprise or uncertainty). Notably, CPP and RU
are factors that normatively promote greater belief updating, scaling the degree to which past
observations are discounted relative to the most recent evidence. Residual updating likely
captures, at least in part, deviations between the objective values of CPP and RU in the
normative model and the individual's subjective estimates of those factors. Thus, the expression
of this subgraph reflects not only normative factors that should influence belief updating but also
likely fluctuations in subjective estimates of those factors. In addition to being modulated by
these trial-by-trial task factors, expression of this subgraph also varied across individuals in a
manner associated with individual differences in belief updating. Participants who tended to
update their beliefs in a more normative manner – that is, with a stronger influence of surprise
(CPP) and uncertainty (RU) – showed stronger dynamic modulation of the expression of this
subgraph by normative factors and showed stronger average expression of this subgraph.

Relationship to previous results: neural activation during learning in dynamic environments

The brain-wide pattern of functional connectivity that we identified as connected to belief
updating included interactions between multiple functional systems, most prominently the
fronto-parietal task control, memory-retrieval, salience, and dorsal-attention systems (Fig. 3b &

Fig. 4d). These systems include multiple regions in the anterior insula, dorsolateral and
dorsomedial frontal cortex, and lateral and medial parietal cortex (Fig. 4e & Fig. 6c). These
regions showed a large degree of overlap with areas that we have previously shown to have
increased univariate activation in response to both surprise and uncertainty (in this same dataset;
Figure 6)[2]. The current results show that the same regions also exhibit increased functional
connectivity in response to surprise and uncertainty. Our previous report also identified a subset
of these regions, including parts of the dorsomedial frontal cortex, anterior insula, inferior frontal
cortex, posterior cingulate cortex, and posterior parietal cortex, where activity was modulated by
both normative (surprise and uncertainty) and non-normative (reward) factors. This smaller
subset includes regions that participate in the fronto-parietal task-control, memory-retrieval,
salience, and dorsal-attention systems, which is where we identified learning-related increases in
functional connectivity in the current study.

Previously, we also reported regions whose univariate activity was modulated by either
surprise or uncertainty alone. Surprise was associated selectively with activation in occipital
cortex, and uncertainty was associated selectively with activation in anterior prefrontal and
parietal cortex[2]. We similarly have reported multivariate activation patterns that were associated
selectively with either surprise or uncertainty alone[7]. In the current study, we identified a key
pattern of functional connectivity that was modulated by both surprise and uncertainty, but we
did not identify any other pattern that was modulated reliably by either surprise or uncertainty
alone. One possible explanation for this lack of a positive result was our need to use relatively
long time windows (25 s, corresponding to 4-6 trials) in order to obtain reliable estimates of
functional connectivity. These time windows likely included both the surprise elicited by
change-points and the uncertainty that follows. Thus, functional connectivity related to surprise
and uncertainty may have been difficult to dissociate temporally in our task and analysis design.
Using a task that can temporally separate the tracking of surprise and uncertainty[28] might enable
the identification of distinct patterns of functional connectivity for each factor.

The pattern of whole-brain functional connectivity we identified here was also expressed
across individuals in a manner that varied with the degree to which they updated their beliefs
more in line with the normative model. Thus, individual differences in learning were also
reflected in features of individual functional connectomes. In our previous study, we noted a
relationship between individual differences in normative learning and the degree to which
activity in dorsomedial frontal cortex and anterior insula was modulated by normative factors
(surprise and uncertainty)[2]. Here we showed that normative learning was also associated with
how functional connectivity was modulated dynamically by the same normative factors. These
new findings add to previous work showing that brain network dynamics can reflect individual
differences in learning in various domains[12, 13, 15, 19, 22]. Potentially, these differences in individual
functional connectomes during learning could reflect individual differences in resting-state (task-
independent) functional connectivity [29], which merits further study.

Functional connectivity captures many different kinds of statistical dependencies between
brain regions, including those that result from task-driven co-activation. The strong association
between neural activation and functional connectivity during periods of surprise and uncertainty
in our results (Fig. 6), as well as previous studies in other domains[13, 15, 17, 19, 21, 22], raises the
possibility that the increases in functional connectivity between brain regions might have arisen
because these regions became more tightly synchronized to external task events, without
necessarily any increase in communication between them. To refute this possibility, we repeated

our analyses on the predicted BOLD time series from univariate GLMs. These predicted time
series, which contain only task-driven statistical dependencies between brain regions, could not
recapitulate all of the effects that we observed in our actual BOLD time series. Specifically, we
found modulations by task (e.g., the modulation of subgraph expression by surprise and residual
updating) and individual differences (e.g., the relationship between individual differences in
normative learning and the dynamic modulation of subgraph expression by normative factors)
that were apparent only in the full, original functional connectivity matrices. Thus, these effects
appear to include neural communications that do not simply reflect task-driven co-activation.
Even though the changes in functional connectivity that we describe may reflect a mixture of
task-driven and endogenous dynamics, the network analysis provides an important higher-level,
reduced-dimensionality description of these changes.

Relationship to previous results: fronto-parietal integration

A key feature of the brain-wide pattern of functional connectivity that we identified was
connectivity involving the fronto-parietal task-control system. We characterized the complex
pattern of functional connectivity in the learning-related subgraph by summarizing the
connectivity according the putative functional system of each region[27]. Among all the functional
systems, the largest proportion of connectivity in the learning-related subgraph involved the
fronto-parietal system. Connectivity associated with the fronto-parietal system has been shown to
increase at the beginning of learning and decrease toward the later phases of learning[13, 19, 22]. Our
result extends this finding by showing that fronto-parietal functional connectivity is modulated
dynamically in a trial-by-trial manner according to the need for new learning. That is, the pattern
of functional connectivity captured by the learning-related subgraph increased after surprising
task changes and then decreased gradually as more information was gained about the current
state. The fronto-parietal system is thought of as a control system that is involved in flexible
adjustments of behavior[30, 31]. In particular, connectivity between the fronto-parietal network and
other systems has been shown to change in response to different task requirements[32]. This type of
flexible control is critical for learning in a dynamic environment, a context in which people
should adjust their degree of belief updating in a context-dependent manner[1, 4].

Although the learning-related subgraph was also characterized by a balanced strength of
within-system connectivity and between-system connectivity, the critical features that changed in
response to task dynamics involved primarily between-system connectivity. This result implies
that faster learning was associated with a greater degree of integration between different
functional systems. Several previous studies have shown that complex cognitive tasks are
associated with more integration between systems[33, 34, 35, 36]. For example, brain networks tend to
be more segregated during sensory processing, and more integrated during complex cognitive
tasks such as the n-back or gambling. Other work has shown that as a task becomes more
practiced over time, the interaction between systems decreased while the connections within
systems remained strong[13]. Here we demonstrated changes in integration on a fast time scale, as
task demands varied from trial to trial. Integration between systems was greater during periods of
the task when surprise or uncertainty was high, and therefore there was a need to update one's
beliefs and base them more on the current evidence than on expectations developed from past
experience.

Relationship to previous results: arousal and network dynamics

The dynamics of functional connectivity that we identified may be linked to arousal. We
and others have shown previously that surprise and uncertainty induce changes in arousal, as
indexed by pupil responses[3, 6, 37]. The increases in integration between the fronto-parietal and
other systems that we observed in this study in response to surprise and uncertainty are
consistent with previous studies of the relationship between arousal, measured in terms of
wake/sleep, heart rate, and pupil-size metrics, and the dynamics of functional connectivity in
large-scale brain networks[36, 38, 39, 40, 41, 42]. Specifically, high arousal states are associated with
changes in connectivity in regions in the fronto-parietal, dorsal attention, ventral attention,
salience, and default mode systems[38, 41], and particularly to increases in integration in the fronto-
parietal and default-mode systems[36].

Potential links between arousal and dynamic functional connectivity are particularly
interesting in light of theories about the functional role of arousal in changing neural gain, or the
sensitivity of neural communication[43]. Arousal is associated with changes in the activity of
noradrenergic neurons in the locus coeruleus[44, 45, 46], which is hypothesized to modulate neural
gain in their cortical projection targets. As neural gain increases, neurons receiving excitatory
input become more active while neurons receiving inhibitory input become less active. These
kinds of effects are thought to underlie certain changes in network topology[47]. One previous
study used a simulated brain functional network to show that increased neural gain can lead to
stronger network integration, particularly in the fronto-parietal system[48]. Further support for
these ideas comes from studies using atomoxetine, a noradrenergic reuptake inhibitor, which
when given systemically can increase network integration during performance of certain tasks[49]
and modulate learning in dynamic environments[50]. Future studies could incorporate direct
measures of arousal to test these proposed relationships between arousal, network
reconfiguration, and belief updating more directly.

Conclusion

In this study, we provided a network-based perspective on the neural substrates of
learning in dynamic and uncertain environments. In such environments, people should flexibly
adjust between slow and fast learning: beliefs should be updated more strongly when new
evidence is most informative, such as when the environment undergoes a surprising change or
beliefs are highly uncertain. Here we identified a specific brain-wide pattern of functional
connectivity (subgraph) that fluctuated dynamically with changes in surprise and uncertainty.
The dynamics and expression of this pattern of functional connectivity also varied across
individuals in a manner that reflected differences in learning. This pattern was expressed more
strongly and was more strongly modulated by surprise and uncertainty in people who updated
their beliefs in a more normative manner, with a stronger influence of surprise and uncertainty.
The most important aspect of this learning-related pattern of functional connectivity is functional
integration between the fronto-parietal and other functional systems. These results establish a
novel link between dynamics adjustments in learning and dynamic, whole-brain changes in
functional connectivity.

Methods

Participants

The dataset has been described in our previous reports[2]. Thirty-two individuals participated in the fMRI experiment: 17 females, mean age = 22.4 years (SD = 3.0; range 18-30). Human subject protocols were approved by the Internal Review Board in University of Pennsylvania. All participants provided informed consent before the experiment.

Task

Each participant completed four 120-trial runs during functional magnetic resonance imaging. In each run, participants performed a predictive-inference task (Fig. 1a). On each trial, participants made a prediction about where the next bag would be dropped from an occluded helicopter by positioning a bucket along the horizontal axis (0-300) of the screen. The location of the bag was sampled from a Gaussian distribution with a mean (the location of the helicopter) and a standard deviation (noise). The standard deviation was high (SD = 25) or low (SD = 10) in different runs. The location of the helicopter usually remained stable but it changed occasionally. The probability of change was zero for the first three trials after a change and 0.125 for the following trials. When the location changed, the new location was sampled from a uniform distribution. Correctly predicting the location of the bag resulted in coins landing in the bucket. These coins either had positive or neutral value depending on their color, which was randomly assigned for each trial.

Behavior model

We applied the same normative model described in our previous study[2]. An approximation to the ideal observer solution to this task updates beliefs according to a delta learning rule (Fig. 1b):

$$\delta_t = X_t - B_t \tag{1}$$
$$B_{t+1} = B_t + \alpha_t \times \delta_t \tag{2}$$

where δ_t is the prediction error, which is the difference between the observed outcome (bag drop location, X_t) and the prediction (bucket location, B_t). Beliefs are updated in proportion to the prediction error, and this proportion is determined by α_t, the learning rate. The learning rate is adjusted adaptively on each trial according to two normative factors (Fig. 1c):

$$\alpha_t = \Omega_t + (1 - \Omega_t) \times \tau_t \tag{3}$$

where Ω_t is the change-point probability (CPP) and τ_t is the relative uncertainty (RU). CPP reflects the likelihood that a change-point has happened:

$$\Omega_t = \frac{U(X_t|0,300)H}{U(X_t|0,300)H + N(X_t|B_t, \sigma_t^2)(1-H)}$$ (4)

where $U(X_t|0,300)$ indicates the probability of X_t from a uniform distribution between 0 and
300, $N(X_t|B_t, \sigma_t^2)$ indicates the probability of X_t from a Gaussian distribution with mean of B_t
and variance of σ_t^2, σ_t^2 is the variance of predictive distribution of the bag location, and H is the
average probability of change (0.1) across trials.

RU reflects the uncertainty about the current location of the helicopter relative to the
amount of noise in the environment:

$$\tau_{t+1} = \frac{\Omega_t \sigma_N^2 + (1-\Omega_t)\tau_t \sigma_N^2 + \Omega_t(1-\Omega_t)(\delta_t(1-\tau_t))^2}{\Omega_t \sigma_N^2 + (1-\Omega_t)\tau_t \sigma_N^2 + \Omega_t(1-\Omega_t)(\delta_t(1-\tau_t))^2 + \sigma_N^2}$$ (5)

where σ_N^2 is the variance of outcome distribution used to generate the location of bag. There are
three terms present in both the numerator and denominator. The first term is the variance of the
helicopter distribution conditional on a change-point while the second term is the variance of the
helicopter distribution conditional on no change-point. The third term reflects the variance due to
the difference in mean between the two conditional distributions. The three terms together
capture the uncertainty about the location of the helicopter.

Figure 1c shows an example of the dynamics of CPP and RU. CPP increases when there
is an unexpectedly large prediction error. RU increases after CPP increases and decays slowly as
more precise estimates of the helicopter location are possible.

As in our previous study, a regression model was applied to investigate how the factors in
this normative model, as well as other aspects of the task, influenced participants' belief updates.
We regressed trial-by-trial updates $(B_{t+1} - B_t)$ against the prediction error (δ_t), the interaction
between prediction error and the two factors from the normative model, CPP (Ω_t) and RU (τ_t),
as well as the interaction between prediction error and whether the outcome was rewarded or
not[2]. Note that these interaction terms test whether learning rates vary as a function of CPP, RU
or reward; if these coefficients are zero, updates would be a constant fraction of prediction errors
(given by the β_1 term). The form of the regression model can be written as

$Update_t = \beta_0 + \beta_1\delta_t + \beta_2\delta_t\Omega_t + \beta_3\delta_t\tau_t(1-\Omega_t) + \beta_4\delta_t Reward_t + \beta_5 Edge_t + \varepsilon$ (6)

where *Edge* is regressor of no interest that captures the tendency to avoid updating toward the
edges of the screen $((150 - B_{t+1})|150 - B_{t+1}|)$. This regression model was fitted separately to
each participant's data to estimate the influence of each factor on each participant's behavior.
We used the residuals of this regression to examine the relationship between subgraph
expression and residual updating. To examine the relationship between individual differences in

normative learning and functional network dynamics, we used the sum of the regression
coefficients on the CPP term (β_2) and the RU term (β_3) as an index of normative learning.

MRI data acquisition and preprocessing

MRI data were collected on a 3T Siemens Trio with a 32-channel head coil. Functional
data were acquired using gradient-echo echoplanar imaging (EPI) (3 mm isotropic voxels, 64 x
64 matrix, 42 axial slices tilted 30° from the AC-PC plane, TE = 25 ms, flip angle = 75°, TR =
2500 ms). There were four runs with 226 images per run. T1-weighted MPRAGE structural
images (0.9375 X 0.9375 X 1 mm voxels, 192 X 256 matrix, 160 axial slices, TI = 1100 ms, TE
= 3.11 ms, flip angle = 15°, TR = 1630 ms) and matched fieldmap images (TE = 2.69 and 5.27
ms, flip angle = 60°, TR = 1000 ms) were also collected. Data were preprocessed with FSL[51, 52]
and AFNI[53, 54]. Functional data were corrected for slice timing (AFNI's 3dTshift) and head
motion (FSL's MCFLIRT), attenuated for outliers (AFNI's 3dDespike), undistorted and warped
to MNI space (FSL's FLIRT and FNIRT), smoothed with 6 mm FWHM Gaussian kernel (FSL's
fslmaths) and intensity-scaled by the grand-mean value per run. Details of these preprocessing
steps were described in our previous study[2]. Structural images were segmented into gray matter,
white matter (WM) and cerebrospinal fluid (CSF) (FSL's FAST)[55].

Constructing time-varying functional networks

For each run and each participant, blood-oxygenation-level-dependent (BOLD) time
series were obtained from each of 264 regions of interest (ROIs; diameter = 9mm) based on the
previously defined parcellation[27]. ROIs that did not have valid BOLD time series for all runs and
all participants were removed, resulting in $N = 247$ ROIs. For each BOLD time series, a band-
pass filter was applied with a cutoff of 0.01-0.08 Hz. This low-frequency band has been shown
to reflect neuronal activation and neural synchronization[56, 57, 58]. To remove the influence of head
motion, a confound regression was implemented to regress out nuisance factors from each
BOLD time series. This confound regression included 24 motion parameters (three translation
and three rotation motion parameters and their expansion ($[R_t R_t^2 R_{t-1} R_{t-1}^2]$))[59], as well as
average signals from WM and CSF[60].

In order to construct dynamic functional networks, we defined sliding time windows and
calculated Pearson correlation coefficients between ROI time series in each sliding time window.
We assigned these coefficients to the first TR in the time windows. To ensure magnetization
equilibrium, the first 6 volumes of each run were removed from the analysis. For the rest of the
volumes in each run, a sliding window was defined with a 10-TR (25 seconds) length and 80%
overlap across windows. Each run had 106 sliding time windows, leading to $T = 424$ sliding time
windows for each participant. Each participant's data thus formed a matrix of dynamic functional
networks with dimensions $N \times N \times T$. Then, we took each participant's $N \times N$ matrix and unfurled
the upper triangle into an $\frac{N(N-1)}{2}$ vector. By concatenating vectors across all time windows (T),
we obtained an $\frac{N(N-1)}{2} \times T$ matrix. Furthermore, we concatenated matrices from $S = 32$
participants to form a $\frac{N(N-1)}{2} \times (T \times S)$ matrix. To ensure that our approach did not give undue
preference to either positively or negatively weighted functional edges, we separated this matrix
into two thresholded matrices: one composed of positively weighted edges, and one composed of

negatively weighted edges. That is, in the matrix of positive functional correlations between ROI
time series, the original negative correlations between ROI time series were set to 0; in the
matrix of negative functional correlations between ROI time series, all values were multiplied by
-1, and the original positive functional correlations between ROI time series were set to 0. After
concatenating the matrix composed of positively weighted edges and the matrix of negatively
weighted edges, we had a final $\frac{N(N-1)}{2} \times (T \times S \times 2)$ matrix $\mathbf{A}$.

Clustering functional networks into subgraphs

650 We applied an unsupervised machine learning algorithm called non-negative matrix
651 factorization (NMF)[23] on A to identify subgraphs W and the time-dependent expressions of
652 subgraphs H. The matrix factorization problem $A \approx WH \ s.t. W \geq 0, H \geq 0$ was solved by
653 optimization of the cost function:

655
$$min_{W,H} \ \frac{1}{2} \|A - WH\|_F^2 + \alpha \|W\|_F^2 + \beta \sum_{t=1}^{TS} \|H(:,t)\|_1^2 \tag{7}$$

where A is the functional connectivity matrix, W is a matrix of subgraph connectivity with size
$\frac{N(N-1)}{2} \times k$, and H is a matrix of time-dependent expression coefficients for subgraphs with size
$k \times (T \times S \times 2)$. The parameter k is the number of subgraphs, α is a regularization of the
connectivity for subgraphs, and β is a penalty that imposes sparsity on the temporal expression
coefficients[61]. For fast and efficient factorization to solve this equation, we used an alternative
non-negative least square with block-pivoting method with 100 iterations[62]. The matrices W and
H were initialized with randomized values from a uniform distribution between 0 and 1.

A random sampling procedure was used to find the optimal parameters k, α, and β[63]. In
this procedure, the NMF algorithm was re-run 1,000 times with parameter k drawn from $U(2,15)$,
parameter α drawn from $U(0.01, 1)$, and parameter β drawn from $U(0.01, 1)$. The subgraph
learning performance was evaluated through 4-fold cross-validation. In each fold, twenty-four
participants were used for training; Eight participants were used for testing and calculating cross-
validation error ($\|A - WH\|_F^2$). An optimal parameter set should minimize the cross-validation
error. We chose an optimal parameter set ($k = 10, \alpha = 0.535, \beta = 0.230$) that ensured the
cross-validation error in the bottom 25% of the distribution of cross-validation error from our
random sampling scheme[25].

Since the result of NMF is non-deterministic, we implemented consensus clustering to
obtain reliable subgraphs[64]. In this procedure, we (i) used the optimal parameters and ran the
NMF 100 times on A, (ii) concatenated subgraph matrix W across 100 runs into an aggregate
matrix with dimensions $\frac{N(N-1)}{2} \times (k \times 100)$, (iii) applied NMF to this aggregate matrix to obtain a
final set of subgraphs $W_{consensus}$ and expression coefficients $H_{consensus}$.

Properties of subgraphs

Applying NMF yielded a set of subgraphs, or patterns of functional connectivity (**W**), and
the expression of these subgraphs over time (**H**). To understand the subgraphs, we first
rearranged **W** into k different $N \times N$ subgraphs. To understand the roles of cognitive systems in
each subgraph, we mapped each ROI to 13 putative cognitive systems from the previously
defined parcellation: uncertain, sensory, cingulo-opercular task control, auditory, default mode,
memory retrieval, visual, fronto-parietal task control, salience, subcortical, dorsal attention,
ventral attention, and cerebellar[24, 27]. This yielded a 13 x 13 representation of each subgraph. To
show which within-system and between-system edges in this representation were strongest, we
applied a permutation test. We permuted the system label for ROIs and formed a matrix with
system-by-system edges. This process was repeated 10,000 times to determine which strength of
system-by-system edges was above the 95% confidence interval threshold after correction for
multiple comparisons.

To characterize the connectivity pattern of each subgraph, we ordered them according to
the relative strength of within-system edges versus between-system edges. For each subgraph,
we calculated the average strength of within-system edges (edges that link two ROIs that both
belong to the same system), and the average strength of between-system edges (edges that link
an ROI in one system to an ROI in another system). Then, we subtracted the average strength of
between-system edges (E_B) from the average strength of within-system edges (E_W) and divided
this difference by the sum of them ($\frac{E_W - E_B}{E_W + E_B}$). We estimated the 95% confidence interval of these
measures (average relative strength, average within-system strength or average between-system
strength) by implementing bootstrapping 10,000 times.

Next, we investigated the relationship between these connectivity patterns and the
temporal expression of each subgraph. As the matrix of functional connectivity was divided in
two, with the first half reflecting positive connectivity and the second half reflecting negative
connectivity, the temporal expression matrix also had two halves, with the first reflecting
positive expression over time and the second reflecting negative expression over time. As there
was a strong negative correlation between positive and negative expression, we did all of our
analyses on the relative expression (positive expression minus negative expression) of each
subgraph[26]. Across subgraphs, we calculated Pearson correlation coefficients between the
average relative expression and the average within-system strength, average between-system
strength, and average relative strength of each subgraph. To determine the significance of the
correlation coefficients, we implemented 10,000 permutations of the subgraph labels to form the
null distribution of correlation coefficients.

Modulation of subgraph expression by task factors

We investigated how fluctuations in the trial-by-trial relative expression of each subgraph
were related to four trial-by-trial task factors: CPP, RU, reward, and residual updating. CPP and
RU were estimated based on the normative learning model[1, 2, 3]. Residual updating was derived
as the residual of the behavioral regression model described above. We examined the effect of
these four trial-by-trial task factors together, including all four in a regression model predicting
trial-by-trial relative expression. Since NMF yielded values of temporal expression every 2 TRs
(5 seconds), we applied a linear interpolation on the temporal expression values to obtain an
expression value aligned with outcome onset on each trial. Regression models were implemented

for each participant separately. Regression coefficients were then tested at the group level using
two-tailed *t*-tests.

The relationship between subgraph expression and individual differences in normative
learning

Next, we examined the relationship between subgraph expression and individual
differences in the extent to which belief updating followed normative principles. As an index of
normative learning for each individual, we used the sum of the regression coefficients on the
CPP term (β_2) and the RU term (β_3) in the behavior model[2]. This normative learning index
reflected the extent to which a participant's trial-by-trial updates were influenced by the two
normative factors CPP and RU. We examined the relationship between this index and two
aspects of subgraph expression. First, across subjects, we calculated the Pearson correlation
coefficient between normative learning and the dynamic modulation of relative expression by
normative factors for each subgraph. This dynamic modulation was indexed as the sum of the
regression coefficients for CPP and RU from the regression model predicting trial-by-trial
relative expression. That is, dynamic modulation reflected how normative factors were
associated with the change in relative expression of the subgraph. Second, across subjects, we
calculated the Pearson correlation coefficient between normative learning and the average
relative expression of each subgraph. To determine the significance of these correlation
coefficients, we permuted the participant labels 10,000 times to form the null distribution.

The relationship between task and individual difference effects across subgraphs

To show the relative importance of each subgraph, we examined the variance explained
for task effects and individual differences effects for each subgraph. The variance explained for
task effects was the R^2 of the regression model that investigated the relationship between the four
task factors (CPP, RU, reward and residual updating) and trial-by-trial subgraph relative
expression. The variance explained for individual differences effects was the R^2 of a regression
model that investigated the relationship between individual differences in normative learning and
two individual-level measures of subgraph relative expression (dynamic modulation by
normative learning factors and average relative expression). We investigated the relationship
between variance explained for task and individual differences effects using Pearson correlation.
To determine the significance of this correlation coefficient, we permuted the subgraph labels
10,000 times to form the null distribution of correlation coefficients.

Contributions of different types of edges to task and individual differences effects

We evaluated the contributions of different types of edges to the task effects (influence of
CPP, RU, reward and residual updating on subgraph expression across time) and individual
differences effects (relationship between normative learning and subgraph expression across
subjects). We mainly focused on the contribution of within-system edges and between-system
edges. For this analysis, we implemented three types of comparison: Within versus All, Between
versus All, and Between versus Within. For Within versus All, we kept within-system edges only
and re-estimated task and individual differences effects; then, we compared these effects with the
effects estimated using all edges. This comparison showed the change of effects after between-

system edges were removed, and thus, this comparison revealed the contribution of between-
system edges. For Between versus All, we kept between-system edges only and re-estimated task
and individual differences effects. We then compared these effects with the effects estimated
using all edges. In this comparison, within-system edges were removed and thus, we examined
the contribution of within-system edges. Last, the comparison of Between versus Within is a
direct comparison between effects estimated with between-system edges only and effects
estimated with within-system edges only. Thus, this comparison examined the different
contributions of between-system and within-system edges.

Specifically, for task effects, we examined the change of coefficients in the regression
model that investigated the influence of four task factors—CPP, RU, reward and residual
updating—on subgraph relative expression. The change was calculated for each participant
separately, and the significance of change was then tested at the group level using two-tailed t-
tests. For individual differences effects, we examined the change of correlation coefficients for
two types of relationship: the relationship between individual normative learning and dynamic
modulation of subgraph relative expression and the relationship between individual normative
learning and average subgraph relative expression. To determine the significance of the change
of correlation coefficients, we permuted the labels of participants for individual normative
learning 10,000 times to form the null distribution of the change of correlation coefficients.

We also investigated the contribution of different functional systems and the contribution
of different system-by-system edges. For the contribution of different functional systems, we
compared the effects after removing edges of one functional system with the effects estimated
with all edges. For the contribution of different system-by-system edges, we compared the
effects after removing one system-by-system edge with the effects estimated with all edges.
Statistical testing was conducted with the same procedures described in the previous paragraph.

Relationship between univariate activation and functional connectivity

To investigate the relationship between dynamic functional connectivity and univariate
activation, we fit a mass univariate GLM. In this GLM, the regressors were the outcome onset
and four modulators of outcome onset: CPP, RU, reward and residual updating. These regressors
were convolved with a gamma hemodynamic response function (HRF) as well as the temporal
derivative of this function. Six motion parameters were also included as regressors.

To examine what aspects of our functional connectivity results could be accounted for by
functional coactivation, we used the regression coefficients from the GLM above (including both
the main HRF and its temporal derivative for each regressor) to create a predicted BOLD time
series. We then repeated the same sequence of analyses described above on this predicted BOLD
time series. This predicted BOLD time series reflected the modulation of univariate activation by
CPP, RU, reward and residual updating. However, this predicted BOLD time series lacked any
statistical dependencies between regions that were present in the actual BOLD time series that
could not be explained by task-driven changes in univariate activation. Thus, any functional
connectivity results we observed with this predicted BOLD time series could be fully accounted
for by task-driven changes in univariate activation.

Data availability

The data for the current study are available from the corresponding author upon request.
810

811 **Code availability**
812 Code is available at https://github.com/changhaokao/nmf_network_learning.
813

References

1.   Nassar MR, Wilson RC, Heasly B, Gold JI. An approximately Bayesian delta-rule model explains the dynamics of belief updating in a changing environment. *The Journal of Neuroscience* **30**, 12366-12378 (2010).

2.   McGuire JT, Nassar MR, Gold JI, Kable JW. Functionally Dissociable Influences on Learning Rate in a Dynamic Environment. *Neuron* **84**, 870-881 (2014).

3.   Nassar MR, Rumsey KM, Wilson RC, Parikh K, Heasly B, Gold JI. Rational regulation of learning dynamics by pupil-linked arousal systems. *Nature Neuroscience* **15**, 1040-1046 (2012).

4.   Behrens TEJ, Woolrich MW, Walton ME, Rushworth MFS. Learning the value of information in an uncertain world. *Nature Neuroscience* **10**, 1214-1221 (2007).

5.   Meder D, *et al.* Simultaneous representation of a spectrum of dynamically changing value estimates during decision making. *Nature Communications* **8**, 1942 (2017).

6.   O'Reilly JX, Schüffelgen U, Cuell SF, Behrens TEJ, Mars RB, Rushworth MFS. Dissociable effects of surprise and model update in parietal and anterior cingulate cortex. *Proceedings of the National Academy of Sciences* **110**, E3660-E3669 (2013).

7.   Nassar MR, McGuire JT, Ritz H, Kable JW. Dissociable Forms of Uncertainty-Driven Representational Change Across the Human Brain. *The Journal of Neuroscience* **39**, 1688-1698 (2019).

8.   Friston KJ. Functional and Effective Connectivity: A Review. *Brain Connectivity* **1**, 13-36 (2011).

9.   Bassett DS, Sporns O. Network neuroscience. *Nature Neuroscience* **20**, 353-364 (2017).

10.   Bullmore E, Sporns O. Complex brain networks: graph theoretical analysis of structural and functional systems. *Nature Reviews Neuroscience* **10**, 186 (2009).

11.   Medaglia JD, Lynall M-E, Bassett DS. Cognitive network neuroscience. *Journal of cognitive neuroscience* **27**, 1471-1491 (2015).

12.   Bassett DS, Wymbs NF, Porter MA, Mucha PJ, Carlson JM, Grafton ST. Dynamic reconfiguration of human brain networks during learning. *Proceedings of the National Academy of Sciences* **108**, 7641-7646 (2011).

13.   Bassett DS, Yang M, Wymbs NF, Grafton ST. Learning-induced autonomy of sensorimotor systems. *Nature Neuroscience* **18**, 744-751 (2015).

14.   Mattar MG, Wymbs NF, Bock AS, Aguirre GK, Grafton ST, Bassett DS. Predicting future learning from baseline network architecture. *NeuroImage* **172**, 107-117 (2018).

15. Gerraty RT, Davidow JY, Foerde K, Galvan A, Bassett DS, Shohamy D. Dynamic
     Flexibility in Striatal-Cortical Circuits Supports Reinforcement Learning. *The Journal of
     Neuroscience* **38**, 2442-2453 (2018).

16. Mattar MG, Thompson-Schill SL, Bassett DS. The network architecture of value
     learning. *Network Neuroscience* **2**, 128-149 (2018).

17. Antzoulatos Evan G, Miller Earl K. Increases in Functional Connectivity between
     Prefrontal Cortex and Striatum during Category Learning. *Neuron* **83**, 216-225 (2014).

18. Baeg EH, Kim YB, Kim J, Ghim J-W, Kim JJ, Jung MW. Learning-Induced Enduring
     Changes in Functional Connectivity among Prefrontal Cortical Neurons. *The Journal of
     Neuroscience* **27**, 909-918 (2007).

19. Büchel C, Coull JT, Friston KJ. The predictive value of changes in effective connectivity
     for human learning. *Science* **283**, 1538-1541 (1999).

20. Fatima Z, Kovacevic N, Misic B, McIntosh AR. Dynamic functional connectivity shapes
     individual differences in associative learning. *Human Brain Mapping* **37**, 3911-3928
     (2016).

21. Lewis CM, Baldassarre A, Committeri G, Romani GL, Corbetta M. Learning sculpts the
     spontaneous activity of the resting human brain. *Proceedings of the National Academy of
     Sciences* **106**, 17558-17563 (2009).

22. Sun FT, Miller LM, Rao AA, D'esposito M. Functional connectivity of cortical networks
     involved in bimanual motor sequence learning. *Cerebral cortex* **17**, 1227-1234 (2006).

23. Lee DD, Seung HS. Learning the parts of objects by non-negative matrix factorization.
     Nature **401**, 788-791 (1999).

24. Chai LR*, et al.* Evolution of brain network dynamics in neurodevelopment. *Network
     Neuroscience* **1**, 14-30 (2017).

25. Khambhati AN, Mattar MG, Wymbs NF, Grafton ST, Bassett DS. Beyond modularity:
     Fine-scale mechanisms and rules for brain network reconfiguration. *NeuroImage* **166**,
     385-399 (2018).

26. Khambhati AN, Medaglia JD, Karuza EA, Thompson-Schill SL, Bassett DS. Subgraphs
     of functional brain networks identify dynamical constraints of cognitive control. *PLOS
     Computational Biology* **14**, e1006234 (2018).

27. Power JD*, et al.* Functional Network Organization of the Human Brain. *Neuron* **72**, 665-
     678 (2011).

907 28. Nassar MR, Bruckner R, Gold JI, Li S-C, Heekeren HR, Eppinger B. Age differences in
908   learning emerge from an insufficient representation of uncertainty in older adults. *Nature*
909   *communications* **7**, 11609 (2016).
910

911 29. Tompson S, Falk EB, Vettel JM, Bassett DS. Network Approaches to Understand
912   Individual Differences in Brain Connectivity: Opportunities for Personality
913   Neuroscience. *Personality Neuroscience* **1**, e5 (2018).
914

915 30. Cole MW, Repovš G, Anticevic A. The Frontoparietal Control System:A Central Role in
916   Mental Health. *The Neuroscientist* **20**, 652-664 (2014).
917

918 31. Power JD, Petersen SE. Control-related systems in the human brain. *Current Opinion in*
919   *Neurobiology* **23**, 223-228 (2013).
920

921 32. Cole MW, Reynolds JR, Power JD, Repovs G, Anticevic A, Braver TS. Multi-task
922   connectivity reveals flexible hubs for adaptive task control. *Nature Neuroscience* **16**,
923   1348-1355 (2013).
924

925 33. Bertolero MA, Yeo BTT, D'Esposito M. The modular and integrative functional
926   architecture of the human brain. *Proceedings of the National Academy of Sciences* **112**,
927   E6798-E6807 (2015).
928

929 34. Shine JM, Poldrack RA. Principles of dynamic network reconfiguration across diverse
930   brain states. *NeuroImage* **180**, 396-405 (2017).
931

932 35. Cohen JR, D'Esposito M. The Segregation and Integration of Distinct Brain Networks
933   and Their Relationship to Cognition. *The Journal of Neuroscience* **36**, 12083-12094
934   (2016).
935

936 36. Shine JM*, et al.* The Dynamics of Functional Brain Networks: Integrated Network States
937   during Cognitive Task Performance. *Neuron* **92**, 544-554 (2016).
938

939 37. Krishnamurthy K, Nassar MR, Sarode S, Gold JI. Arousal-related adjustments of
940   perceptual biases optimize perception in dynamic environments. *Nature Human*
941   *Behaviour* **1**, 0107 (2017).
942

943 38. Wang C, Ong JL, Patanaik A, Zhou J, Chee MWL. Spontaneous eyelid closures link
944   vigilance fluctuation with fMRI dynamic connectivity states. *Proceedings of the National*
945   *Academy of Sciences* **113**, 9653-9658 (2016).
946

947 39. Chang C*, et al.* Tracking brain arousal fluctuations with fMRI. *Proceedings of the*
948   *National Academy of Sciences* **113**, 4518-4523 (2016).
949

950 40. Haimovici A, Tagliazucchi E, Balenzuela P, Laufs H. On wakefulness fluctuations as a
951   source of BOLD functional connectivity dynamics. *Scientific Reports* **7**, 5908 (2017).
952

953   41.   Patanaik A, Tandi J, Ong JL, Wang C, Zhou J, Chee MWL. Dynamic functional
954   connectivity and its behavioral correlates beyond vigilance. *NeuroImage* **177**, 1-10
955   (2018).
956
957   42.   Young CB*, et al.* Dynamic Shifts in Large-Scale Brain Network Balance As a Function
958   of Arousal. *The Journal of Neuroscience* **37**, 281-290 (2017).
959
960   43.   Servan-Schreiber D, Printz H, Cohen JD. A network model of catecholamine effects:
961   gain, signal-to-noise ratio, and behavior. *Science* **249**, 892-895 (1990).
962
963   44.   Aston-Jones G, Cohen JD. An integrative theory of locus coeruleus-norepinephrine
964   function: adaptive gain and optimal performance. *Annual Review of Neuroscience* **28**,
965   403-450 (2005).
966
967   45.   Sara Susan J. The locus coeruleus and noradrenergic modulation of cognition. *Nature
968   Reviews Neuroscience* **10**, 211-223 (2009).
969
970   46.   Sara Susan J, Bouret S. Orienting and Reorienting: The Locus Coeruleus Mediates
971   Cognition through Arousal. *Neuron* **76**, 130-141 (2012).
972
973   47.   Eldar E, Cohen JD, Niv Y. The effects of neural gain on attention and learning. *Nature
974   Neuroscience* **16**, 1146-1153 (2013).
975
976   48.   Shine JM, Aburn MJ, Breakspear M, Poldrack RA. The modulation of neural gain
977   facilitates a transition between functional segregation and integration in the brain. *Elife* **7**,
978   e31130 (2018).
979
980   49.   Shine JM, van den Brink RL, Hernaus D, Nieuwenhuis S, Poldrack RA.
981   Catecholaminergic manipulation alters dynamic network topology across cognitive states.
982   *Network Neuroscience* **2**, 381-396 (2018).
983
984   50.   Jepma M, Murphy PR, Nassar MR, Rangel-Gomez M, Meeter M, Nieuwenhuis S.
985   Catecholaminergic Regulation of Learning Rate in a Dynamic Environment. *PLOS
986   Computational Biology* **12**, e1005171 (2016).
987
988   51.   Jenkinson M, Beckmann CF, Behrens TEJ, Woolrich MW, Smith SM. FSL. *NeuroImage*
989   **62**, 782-790 (2012).
990
991   52.   Smith SM*, et al.* Advances in functional and structural MR image analysis and
992   implementation as FSL. *NeuroImage* **23**, S208-S219 (2004).
993
994   53.   Cox RW. AFNI: Software for Analysis and Visualization of Functional Magnetic
995   Resonance Neuroimages. *Computers and Biomedical Research* **29**, 162-173 (1996).
996
997   54.   Cox RW. AFNI: What a long strange trip it's been. *NeuroImage* **62**, 743-747 (2012).
998

55. Zhang Y, Brady M, Smith S. Segmentation of brain MR images through a hidden
Markov random field model and the expectation-maximization algorithm. *IEEE*
Transactions on Medical Imaging **20**, 45-57 (2001).

56. Biswal B, Zerrin Yetkin F, Haughton VM, Hyde JS. Functional connectivity in the motor
cortex of resting human brain using echo-planar mri. *Magnetic Resonance in Medicine*
34, 537-541 (1995).

57. Lu H*, et al.* Synchronized delta oscillations correlate with the resting-state functional
MRI signal. *Proceedings of the National Academy of Sciences* **104**, 18265-18269 (2007).

58. Zuo X-N*, et al.* The oscillating brain: Complex and reliable. *NeuroImage* **49**, 1432-1445
(2010).

59. Friston KJ, Williams S, Howard R, Frackowiak RSJ, Turner R. Movement-Related
effects in fMRI time-series. *Magnetic Resonance in Medicine* **35**, 346-355 (1996).

60. Fox MD, Snyder AZ, Vincent JL, Corbetta M, Van Essen DC, Raichle ME. The human
brain is intrinsically organized into dynamic, anticorrelated functional networks.
Proceedings of the National Academy of Sciences **102**, 9673-9678 (2005).

61. Kim J, Park H. Fast Nonnegative Matrix Factorization: An Active-Set-Like Method and
Comparisons. *SIAM Journal on Scientific Computing* **33**, 3261-3281 (2011).

62. Kim J, He Y, Park H. Algorithms for nonnegative matrix and tensor factorizations: a
unified view based on block coordinate descent framework. *Journal of Global*
Optimization **58**, 285-319 (2014).

63. Bergstra J, Bengio Y. Random search for hyper-parameter optimization. *Journal of*
Machine Learning Research **13**, 281-305 (2012).

64. Monti S, Tamayo P, Mesirov J, Golub T. Consensus Clustering: A Resampling-Based
Method for Class Discovery and Visualization of Gene Expression Microarray Data.
Machine Learning **52**, 91-118 (2003).

1033
1034

1035

Acknowledgements

This work was supported by grants from National Institute of Mental Health (R01-MH098899 to J.I.G. and J.W.K.) and National Science Foundation (1533623 to J.I.G. and J.W.K.). The funders had no role in study design, data collection and analysis, decision to publish or preparation of the manuscript.

Author contributions

C.-H.K. and J.W.K. designed the study. A.N.K. established the software for NMF. A.N.K. and D.S.B. provided suggestions in network analyses. C.-H.K. implemented all the analyses and visualization and drafted the manuscript. All authors interpreted the results and revised the manuscript.

Competing interests

The authors declare no competing interests.

1051

Fig. 1 Overview of the task and theoretical model of belief updating (McGuire et al., 2014).
a Sequence of the task. At the start of each trial, participants predict where a bag will drop from
an occluded helicopter by positioning a bucket on the screen. After participants submit their
prediction, the bag drops and any rewarded coins that fall in the bucket are added to the
participant's score. The location of the last prediction and the last bag drop are noted on the next
trial. **b** An example sequence of trials. Each data point represents the location of a bag on each
trial (yellow for rewarded coins, gray for neutral coins). The dashed line represents the true
generative mean. The mean changes occasionally. The cyan line represents the prediction from a
normative model of belief updating. The inset equation shows how the model updates beliefs (B_t
= belief, X_t = observed outcome, α_t = learning rate on trial t). The vertical dashed line represents
the boundary of the noise conditions: high-noise (left) and low-noise condition (right). Noise
refers to the variance of the generative distribution. **c** Two learning components from the
normative model. Change-point probability (CPP) reflects the likelihood that a change-point
happens, which is increased when there is an unexpectedly large prediction error. Relative
uncertainty (RU) reflects the uncertainty about the generative mean relative to the environmental
noise, which is increased after high CPP trials and decays slowly as more precise estimates of the
generative mean are possible. The inset formula shows how CPP and RU contribute to single
trial estimates of learning rates.

1070

1071

Fig. 2 Schematic overview of the method. a Regions of interest (ROIs). Functional MRI BOLD
signals were extracted from spherical ROIs based on the coordinate system of Power et al.
(2011). There were 264 ROIs in this coordinate system. We only kept ROIs that had usable data
from all subjects. Thus, we used 247 ROIs for the following analyses. Each ROI can be assigned
to one of 13 putative functional systems. **b** An example of Pearson correlation coefficients
calculated between regional BOLD time series over the course of the experiment. Each BOLD
time series was divided into 10-TR (25 seconds) time windows, and consecutive time windows
were placed every 2 TRs leading to 80% overlap between consecutive time windows. Pairwise
Pearson correlation coefficients were calculated between ROI time series in each time window. **c**
An example of edge strength over time. In each time window, there were 247*(247-1)/2 edges. **d**
Nonnegative matrix factorization (NMF). In each time window, the matrix of edge strengths was
unfolded into one column. Then, edges from all time windows in all participants were
concatenated into a single matrix. Each row in the full data matrix contained an edge (pairwise
correlation coefficients between BOLD time series from two ROIs) and each column contained a
time window (across all scans and participants). Correlation values in this matrix were strictly
non-negative; the full data matrix was divided into two halves, with one half containing the
positive pairwise correlation coefficients (zero if the correlation coefficient was negative) and
one half containing the absolute values of negative pairwise correlation coefficients (zero if the
correlation coefficient was positive). Thus, subgraphs were identified based on both the
similarity of positive functional connectivity and the similarity of negative functional
connectivity together. Then, NMF was applied to decompose the concatenated matrix into a

1093   matrix W, which encoded the strengths of edges for each subgraph, and a matrix H, which
1094   encoded the time-dependent expression of each subgraph. For example, the strength of edges of
1095   the fourth subgraph (the fourth column in the matrix W) can be folded into a squared matrix,
1096   reflecting the edge strength between every pair of ROIs.

1097

Fig. 3 Patterns of connectivity in subgraphs. a Converting edges between nodes into edges
between systems. First, the edges of each subgraph can be folded into a square matrix,
representing the edges between every pair of nodes (ROIs). Then, based on the 13 putative
functional systems reported by Power et al. (2011), we categorized each edge according to the
system(s) to which the two nodes (ROIs) belonged. We calculated the mean strength of edges
linking a node in one system to a node in another system, and refer to that value as the between-
system edge. Similarly, we calculated the mean strength of edges linking two nodes that both
belong to the same system and refer to that value as the within-system edge. Edges between
nodes and edges between systems were normalized into the scale between 0 and 1. **b** Edges
between systems in the ten subgraphs identified by NMF. For each subgraph, the top matrix
shows the significant edges in that subgraph within or between systems. We show only
significant edges ($p<0.05$ after the Bonferroni correction for multiple comparisons). All nodes

1111   from systems involved in significant edges are shown on the brain below. Subgraphs varied in

1112   the degree to which they represent interactions within the same system (e.g., subgraph 1) versus

1113   interactions between different systems (e.g., subgraph 10).

1114

1115

Fig. 4 Temporal expression of subgraph 4 was related to task factors and individual differences. a Modulation of temporal expression of subgraph 4 by task factors. A regression model that included CPP, RU, reward and residual updating as predictors of temporal relative expression (calculated by subtracting negative expression from positive expression) of subgraph 4 was fitted for each participant, and coefficients were tested on the group level. The results showed positive effects of CPP, RU and residual updating. Error bars represent one SEM. (*$p<0.05$, ***$p<0.001$) **b** The relationship between individual normative learning and the dynamic modulation of subgraph 4 expression by normative factors. This dynamic modulation was indexed as the sum of the coefficients of CPP and RU in **a**, and represents the extent to which trial-by-trial expression was influenced by the two normative learning factors. There was a significant positive correlation across participants. Each point represents one participant. The red line represents the regression line and the shaded area represents the 95% confidence interval. **c** The relationship between individual normative learning and average relative expression of subgraph 4. There was a significant positive correlation across participants. Each point represents one participant. The red line represents the regression line and the shaded area represents the 95% confidence interval. Source data of **a-c** are provided as a Source Data file. **d** Summary of the pattern of connectivity in subgraph 4. We summarized the pattern of connectivity as within-system strength (which is the value in the diagonal) and between-system strength (which is the average of values in the off-diagonal) for each system. The fronto-parietal system as well as three other systems (memory retrieval, salience and dorsal attention) showed the strongest contributions to this subgraph in terms of both within-system and between-system strength. The 95% confidence interval of each system was estimated by boostrapping 10,000 times on the edges of that system. **e** Nodes for the top four systems with strong within-system and between-system strength. We showed the nodes of fronto-parietal system, memory retrieval system, salience system and dorsal attention system on the brain.

1141

Fig. 5 The contribution of between-system and within-system edges to effects of task factors and individual differences on subgraph 4 expression. a The contribution of between-system and within-system edges to the effect of task factors on temporal relative expression of subgraph 4. To determine the relative contribution of between- and within-system edges on time-dependent subgraph 4 expression, we performed three comparisons on the effects estimated by different types of edges: within-system edges only (Within), between-system edges only (Between) and all edges (All). First, removing between-system edges (Within versus All) decreased the effect of CPP, RU and residual updating. Second, in contrast, after removing within-system edges (Between vs All), there was no significant change in these coefficients. Third, we directly compared the effects contributed from between-system edges only and from within-system edges only (Between versus Within). For between-system edges, there were stronger positive effects for CPP, RU and residual updating. Error bars represent one SEM. (*$p<0.05$, **$p<0.01$, ***$p<0.001$) **b** The contribution of between-system and within-system edges to the relationship between normative learning and dynamic modulation and average expression of subgraph 4. We performed the same three comparisons to determine the relative contribution of between- and within-system edges for each relationship with individual differences. For the effect of dynamic modulation, removing within-system edges (Between versus All) decreased the correlation coefficient. This correlation coefficient was also larger for within-system edges only than between-system edges only, but this effect was not statistically significant. For the effect of average expression, removing between-system edges (Within versus All) decreased the correlation coefficient, and the correlation coefficient was larger for between-system edges only than within-system edges only, though neither of these effects were statistically significant. Source data are provided as a Source Data file. Error bars represent one SEM. (**$p<0.01$)

1166

1167
Fig. 6 Relationship between edge strength of subgraph 4 and univariate task activations. a
Relationship between the activation for CPP and the edge strength of subgraph 4. We calculated
the Pearson correlation coefficient between the *z*-statistic for CPP from McGuire et al. (2014)
and the edge strength across nodes in subgraph 4. Each data point represents an ROI. The edge
strength for each ROI was calculated as the column sum of that ROI's edges to other ROIs,
reflecting the summed interactions between that ROI and all others. The edges were normalized
into the scale between 0 and 1. A significantly positive correlation was observed. The red line
represents the regression line and the shaded area represents the 95% confidence interval. **b**
Relationship between the activation for RU and the edge strength of subgraph 4. We observed a
significant positive correlation between the *z*-statistic for RU from McGuire et al. (2014) and the
edge strength across nodes in subgraph 4. The red line represents the regression line and the
shaded area represents the 95% confidence interval. Source data of **a-b** are provided as a Source

1180   Data file. **c** Whole-brain thresholded activation maps for CPP and RU from McGuire et. al
1181   (2014) and whole-brain maps for edge strength of subgraph 4 in the current study.