Title

Visual discrimination of optical material properties: a large-scale study

Authors

Masataka Sawayama[1], Yoshinori Dobashi[2,3], Makoto Okabe[4], Kenchi Hosokawa[1,5], Takuya Koumura[1], Toni Saarela[6], Maria Olkkonen[7], & Shin'ya Nishida[1, 8]

Affiliations

1. NTT Communication Science Laboratories, Nippon Telegraph and Telephone Corporation

2. Hokkaido University

3. Prometech CG Research

4. Shizuoka University

5. Ritsumeikan University

6. University of Helsinki

7. Durham University

8. Kyoto University

corresponding author: Masataka Sawayama (masa.sawayama@gmail.com)

Abstract

Complex visual processing involved in perceiving the object materials can be better elucidated by taking a variety of research approaches. Sharing stimulus and response data is an effective strategy to make the results of different studies directly comparable and can assist researchers with different backgrounds to jump into the field. Here, we constructed a database containing a variety of material images annotated with visual discrimination performance. We created various material images by using physically-based computer graphics techniques and conducted psychophysical experiments using them in both laboratory and crowdsourcing settings. The observer's task was to discriminate materials on six dimensions (gloss contrast, gloss sharpness, translucent vs. opaque, metal vs. plastic, metal vs. glass, and glossy vs. painted) with several task difficulties. The illumination consistency and object geometry were also varied. We used a non-verbal procedure (an oddity task) so that our database could be used in diverse cross-cultural, cross-species, clinical, and developmental studies. The results showed that discrimination performance was affected by the illumination condition and object geometry, in agreement with previous studies on gloss perception, although the pattern of effects was slightly different for some material dimensions. We also found that the ability to discriminate the spatial consistency of specular highlights in glossiness perception showed larger individual differences than in other tasks. The results obtained through crowdsourcing were strongly correlated with those obtained in the laboratory, which suggests that our database can be used even when the experimental conditions are not strictly controlled. Several projects using our dataset are underway.

Introduction

Humans can visually recognize a variety of material properties of the objects they daily encounter. Although material properties, such as glossiness and wetness, substantially contribute to recognition, the contributions of value-based decision making, motor control, and computational and neural mechanisms underlying material perception had been overlooked until relatively recently—for a long time vision science mainly used simple artificial stimuli to elucidate the underlying brain mechanisms. In the last two decades, however, along with the advancement in computer graphics and machine vision, material perception becomes one of major topics in vision science (Adelson, 2001; Fleming, 2017; Nishida, 2019).

Visual material perception can be considered to be an estimation of material-related properties from an object image. For example, gloss/matte perception entails a visual computation of the diffuse and specular reflections of the surface. However, psychophysical studies have shown that human gloss perception does not have robust constancy against changes in surface geometry and illumination (e.g., Nishida & Shinya, 1998; Fleming et al. 2003), the other two main factors of image formation. Such estimation errors have provided useful information as to what kind of image cues humans use to estimate gloss. In addition to gloss, a significant number of psychophysical studies have concentrated on perception of other optical material properties (e.g., transparency, transparency and wetness) (Fleming et al., 2005; Motoyoshi, 2010; Xiao et al., 2014; Sawayama, Adelson, & Nishida, 2017) and mechanical properties (e.g., viscosity, elasticity) (Kawabe et al., 2015; Paulun et al., 2017; van Assen, Barla & Fleming, 2018). Neurophysiological and neuroimaging studies have revealed various neural mechanisms underlying material perception (Kentridge et al., 2012; Nishio et al., 2012, 2014; Miyakawa et al., 2017). Some recent studies have also focused on developmental, environmental, and clinical factors of material processing (Yang et al., 2015; Goda et al., 2016; Ohishi et al. 2018). For instance, Goda et al. (2016) showed in their monkey fMRI study that the visuo-haptic experience of material objects alters the visual cortical representation. In addition, large individual differences in the perception of colors and materials depicted in one photo (#TheDress) has attracted a broad range of interest and has provoked intensive discussions (Brainard & Hurlbert, 2015; Gegenfurtner et al., 2015).

For a more global understanding of material perception, we need to promote multidisciplinary studies that compare behavioral/physiological responses of humans and animals obtained under a variety of developmental, environmental, cultural, and clinical conditions. There are two problems however. One lies in the high degree of freedom in selecting experimental stimulus parameters and task procedures. Since the appearance of a material depends not only on high-dimensional reflectance parameters, but also on geometry and illumination, both of which are also high dimensional, use of different stimuli (and different tasks) in different studies could impose serious limitations on direct comparisons of their data. The other problem is the technical expertise necessary for rendering realistic images, which could be an obstacle for researchers unfamiliar with graphics to start a new material perception study. Aiming at removing these obstacles, the present study is an attempt to build a standard image set for material recognition and collect the

behavioural responses of a large number of "standard" observers participating in general-purpose
discrimination tasks.

To make our database as useful as possible, we examined a diversity of material attributes. In
particular, we controlled them on six different dimensions by using computer graphics techniques
(Fig. 1). Three of these dimensions are related to gloss (Fig. 1, Task 1: GC, Task 2: GD, and Task
6: GP), the most widely investigated material attribute (Pellacini et al., 2000; Fleming et al., 2003;
Motoyoshi et al., 2007; Olkkonen & Brainard, 2010; Doerschner et al., 2011; Kim et al., 2011;
Marlow et al., 2011; 2012; Kentridge et al., 2012; Sun et al., 2015; Nishio et al., 2014; Adams et
al., 2016; Miyakawa et al., 2017). We controlled the contrast gloss and distinctness-of-image
(DOI) gloss (gloss sharpness) as in previous studies (Pellacini et al., 2000; Fleming et al., 2003;
Nishio et al., 2014). For instance, Nishio et al. (2014) found neurons in the inferior temporal cortex
(ITC) of monkeys that selectively and parametrically respond to gloss changes in these two
dimensions. We also controlled the spatial consistency of specular highlights, which is another
stimulus manipulation of gloss perception (Fig. 1, Task 6: GP). That is, by breaking consistency,
some highlights look like albedo changes by white paint (Beck & Prazdny, 1981; Kim et al., 2011;
Marlow et al., 2011; Sawayama & Nishida, 2018). Moreover, besides gloss perception,
translucency perception has also been widely investigated (Fleming & Bülthoff, 2005; Motoyoshi,
2010; Nagai et al., 2013; Gkioulekas et al., 2013; Xiao et al., 2014; Chadwick et al., 2018). We
adopted the task of discriminating opaque from translucent objects by controlling the thickness of
the translucent media (Fig. 1, Task 3: OT). Furthermore, we adopted the task of plastic-
yellow/gold discrimination (Okazawa et al., 2011, Task 4: MP) and glass/silver discrimination
(Kim & Marlow, 2016; Tamura et al., 2019, Task 5: MG).

We used an oddity task (Fig. 3) to evaluate the capability of discriminating each material
dimension. We chose this task because it requires neither complex verbal instruction, nor verbal
responses by the observer. Therefore, it can be applied to a wide variety of observers including
infants, animals, and machine vision algorithms, and their task performances can be directly
compared. Indeed, several research projects using our dataset are underway (see the Discussion
section).

To control the task difficulty, we varied the value of the parameter of each material dimension.
In addition, we manipulated the stimulus in two ways that affected the task difficulty. First, we set
three illumination conditions: one set of stimuli included images of different poses taken in
identical illumination environments (Fig. 2a, Illumination condition 1); the second set contained
stimuli of identical poses taken in slightly different illumination environments (Fig. 2a,
Illumination condition 2); the third set contained identical poses taken in largely different
illumination environments (Fig. 2a, Illumination condition 3). Second, we used the five different
object geometries for each task (Fig. 2b).

We wish to collect data from a large number of observers. A laboratory experiment affords
control over the stimulus presentation environment, but is unsuited to collecting a large amount of
data from numerous participants. In contrast, one can collect a lot of data through crowdsourcing,

at the expense of a reliable stimulus control. To overcome this trade-off, we conducted identical
psychophysical experiments both in the laboratory and through crowdsourcing. This enabled us to
evaluate individual difference distributions along with the effects of environmental factors on the
task performance.

In sum, we made a large set of image stimuli for evaluations of visual discrimination
performance on six material dimensions (gloss contrast, gloss sharpness, translucency-opaque,
plastic-gold, glass-silver and glossy-painted) and measured a large number of adult human
observers performing oddity tasks in the laboratory and through crowdsourcing. The tasks had
three illumination conditions and five object geometries. Although the original motivation of this
project was to make a standard stimulus-response dataset of material recognition for promotion of
multidisciplinary studies, it also has its own scientific value as it is the first systematic comparison
of the effects of illumination condition and object geometry, as well as of individual variations
across a variety of material dimensions. Our data include several novel findings, as shown below.

Figure 1. Schematic overview of six tasks recorded in the database.

Figure 2. (a) Illumination conditions. Object images were rendered with six global
illumination environments and were presented to observers under three illumination
conditions. Under illumination condition 1, a stimulus display consisted of four objects
rendered with the same illumination environment. Under illumination condition 2, a
stimulus display consisted of three objects rendered with slightly different (in terms of
their pixel histograms) light probes. Under illumination condition 3, a stimulus display
consisted of three objects rendered with largely different illumination environments. (b)
Geometrical conditions. We used five different object shapes for each material task under
each illumination condition.

Figure 3. Example of a four-object oddity task (illumination condition 1) used for collecting

standard observer data. The observers were asked to select which image was the odd

one out in the four images. We did not tell the observer that the experiment was on

material recognition. We conducted experiments both in the laboratory and through

crowdsourcing.

Methods

We evaluated the observers' performance of six material recognition tasks. We selected tasks that had been used in previous material studies: 1) Contrast gloss discrimination (GC); 2) DOI gloss (gloss sharpness) discrimination (GD); 3) Opaque vs. translucent (OT); 4) Metallic gold vs. plastic yellow (MP); 5) Metallic silver vs. glass (MG); 6) Glossy vs. painted (GP). For each task, we used five geometry models and six global illuminations. We conducted behavioral experiments with an oddball procedure, which can be used even with human babies, animals, and brain-injured participants, because it does not entail complex verbal instructions. In the experiment, the observers were asked to select the stimulus that represented an oddity among three or four object stimuli. They were not given any feedback about whether their responses were correct or not. We controlled the task difficulty by changing the illumination and material parameters. To test the generality of the resultant database, we conducted identical experiments in the laboratory and through crowdsourcing.

Image generation for making standard image database

We utilized the physically-based rendering software called *Mitsuba* (Jakob 2010) to make images of objects consisting of different materials, and we controlled six different material dimensions.

Material for tasks 1) Gloss discrimination (contrast dimension) (Task 1: GC) and 2) Gloss discrimination (sharpness dimension) (Task 2: GD)

To control the material property of the gloss discrimination tasks, we used the perceptual light reflection model proposed by Pellacini et al. (2000). They constructed a model based on the results of psychophysical experiments using stimuli rendered by the Ward reflection model (Ward, 1992) and rewrote the Ward model parameters in perceptual terms. The model of Pellacini et al. has two parameters, named *d* and *c*, and they roughly correspond to the DOI gloss and the contrast gloss of Hunter (1987). The difficulty of our two gloss discrimination tasks was controlled by separately modulating these two parameters.

The parameter space of the Ward reflection model can be described as follows.

$$\rho(\theta_i, \phi_i, \theta_o, \phi_o) = \frac{\rho_d}{\pi} + \rho_s \frac{\exp\left[-\tan^2\delta / \alpha^2\right]}{4\pi\alpha^2\sqrt{\cos\theta_i \cos\theta_o}},$$

where $\rho(\theta_i, \phi_i, \theta_o, \phi_o)$ is the surface reflection model, and θ_i, ϕ_i, and θ_o, ϕ_o are the incoming and outgoing directions, respectively. The model has three parameters; ρ_d is the diffuse reflectance of a surface, ρ_s is the energy of its specular component, and α is the spread of the specular lobe. Pellacini et al. (2000) defined *c* and *d* on the basis of the Ward model's three parameters as follows.

$$d = 1 - \alpha$$

$$c = \sqrt[3]{\rho_s + \frac{\rho_d}{2}} - \sqrt[3]{\frac{\rho_d}{2}}$$

Although more physically feasible BRDF models than the Ward model have been proposed for gloss simulation (Ashikmin et al., 2000; Walter et al., 2007), we based ours on the Ward model because it has been used in many previous psychophysics and neuroscience studies (Nishio et al., 2014).

For the task of gloss discrimination in the contrast dimension, the contrast parameter c was varied in a range from 0.00 to 0.12 in 0.02 steps while keeping d constant (d=0.94) (Fig. 4, *Task 1: GC*). As c gets closer to 0, the object appears to have a matte surface. The contrast c of the non-target stimulus in the task was 0.06.

For the experiment of gloss discrimination in the sharpness dimension, the sharpness parameter d was varied from 0.88 to 1.00 in 0.02 steps while keeping c constant (c=0.06) (Fig. 4, *Task 2: GD*). As d gets closer to 1.00, the highlights of the object appear sharper. The sharpness d of the non-target stimulus on the task was 0.94.

Task 1: GC

Task 2: GD

Figure 4. Material examples of tasks 1 (GC) and 2 (GD). For task 1 (GC), the contrast of the specular reflection of the odd target stimulus was varied from 0.00 to 0.12. The non-target stimuli that were presented as the context objects in each task had contrasts of

0.06. For task 2 (GD), the sharpness of the target specular reflection was varied from
1.00 to 0.88. The non-target stimuli had a sharpness of 0.94.

Material for task 3) Opaque vs. Translucent (Task 3: OT)
To make translucent materials, we used the function of homogeneous participating medium
implemented in the Mitsuba renderer. In this function, a flexible homogeneous participating
medium is embedded in each object model. The intensity of the light that travels in the medium is
decreased by scattering and absorption and is increased by nearby scattering. The parameters of
the absorption and scattering coefficients of the medium describe how the light is decreased. We
used the parameters of the "Whole milk" measured by Jensen et al. (2001). The parameter of the
phase function describes the directional scattering properties of the medium. We used an isotropic
phase function. To control the task difficulty, we modulated the scale parameter of the scattering
and absorption coefficients. The parameter describes the density of the medium. The smaller the
scale parameter is, the more translucent the medium becomes. The scale parameter was varied as
follows: 0.0039, 0.0156, 0.0625, 0.25, and 1.00 (Fig. 5, Task 3: OT). The scale parameter of the
non-target stimulus in the task was 1.00. In addition, the surface of the object was modeled as a
smooth dielectric material to produce strong specular highlights, as in previous studies
(Gkioulekas, I. et al, 2013; Xiao et al., 2014).

Task 3: OT

Scale 1.0   Scale 0.25   Scale 0.0625   Scale 0.0156   Scale 0.0039

Non-target stimulus →

Task 4: MP

Ratio 0.0 (gold)   Ratio 0.2   Ratio 0.4   Ratio 0.6   Ratio 0.8

Non-taget stimulus →

Task 5: MG

Ratio 0.0 (silver)   Ratio 0.2   Ratio 0.4   Ratio 0.6   Ratio 0.8

Non-target stimulus →

Figure 5. Material examples of tasks 3 (OT), 4 (MP), and 5 (MG). For task 3 (OT), the scale of the volume media that consisted of milk was varied from 1.0 to 0.0039. For task 4 (MP) and 5 (MG), the blending ratio of the two materials was varied from 0.0 to 0.8. The non-target stimuli in the tasks were shown as in the legend.

Material for task 4) Metallic gold vs. Plastic yellow (Task 4: MP)

To morph the material between gold and plastic yellow, we utilized a linear combination of gold and plastic BRDFs, which is implemented in the Mitsuba renderer. By changing the weight of the combination, the appearance of a material (e.g., gold) can be modulated toward that of the other material (e.g., plastic yellow). In this task, the weight was varied in a range from 0.00 to 0.80 in 0.20 steps (Fig. 5, Task 4: MP). The parameter of the non-target stimulus was 0, at which the material appeared to be pure gold.

Material for task 5) Metallic silver vs. Glass (Task 5: MG)

Similar to task 4), we utilized a linear combination of dielectric glass and silver materials, which is also implemented in the Mitsuba renderer. The weight of the combination was varied from 0.00 to 0.80. The parameter of the non-target stimulus was 0, at which the material appeared to be pure silver (Fig. 5, Task 5: MG).

Material for task 6) Glossy vs. Painted (Task 6: GP)

The skewed intensity distribution due to specular highlights of an object image can be a diagnostic cue for gloss perception (Motoyoshi et al., 2007). However, when the specular highlights are inconsistent in terms of their position and/or orientation with respect to the diffuse shading component, they look more like white blobs produced by surface reflectance changes even if the intensity distribution is kept constant (Beck & Prazdny; 1981; Anderson & Kim, 2009; Kim et al., 2011; Marlow et al., 2011; Sawayama & Nishida, 2018). For our last task of glossy objects vs. matte objects with white paint, we rendered the glossy objects on the basis of Pellacini et al. (2000)'s model. The parameter c was set to 0.08, and the parameter d ranged from 0.88 to 1.00 in 0.04 steps (Fig. 6, lower).

To make object images with inconsistent highlights (white paints), we rendered each scene twice with different object materials. First, we rendered a glossy object image by setting the diffuse reflectance to 0; i.e., we made an image that includes only specular highlights. The rendered image of specular highlights was a texture for the second rendering. We eliminated the brown table when rendering the first scene. Next, we rendered a diffuse object image, i.e., one without specular reflection, with the texture of specular highlights. Since we added the texture to an arbitrary position of the object by using a spherical mapping, the highlight positions were inconsistent with the diffuse shadings. We varied the parameter d of the first rendering from 1.00 to 0.88 (Fig. 6, lower). After we rendered the inconsistent-highlights image, the color histogram of the image was set to that of a consistent glossy object image by using a standard histogram matching method (Sawayama & Nishida, 2018).

Figure 6. Material examples of task 6. The sharpness of the specular reflection was varied from 1.00 to 0.88. This parameter was the same for the non-target painted objects and the target glossy object in each stimulus display.

Geometry

For each material, we rendered the object images by using five different abstract geometries (Fig. 2b). These geometries were made from a sphere by modulating each surface normal direction with different kinds of noise (see also ShapeToolbox: https://github.com/saarela/ShapeToolbox) (Saarela & Olkkonen, 2016, Saarela, 2018). Specifically, Object_1 was made from modulations of low-spatial-frequency noise and crater-like patterns. The source code of this geometry is available on the web (http://saarela.github.io/ShapeToolbox/gallery-moon.html). Object_2 was a bumpy sphere modulated by low-pass band-pass noise. Object_3 was a bumpy sphere modulated by sine-wave noise. Object_4 and Object_5 were bumpy spheres modulated by Perlin noise with different parameters.

Illumination and pose

We used six high-dynamic-range (HDR) light-probe images as illuminations for rendering.
These images were obtained from Bernhard Vogl's light probe database
(http://dativ.at/lightprobes/). To vary the task difficulty, we used three illumination conditions
(illumination conditions 1, 2, and 3, Fig. 2a). Under illumination condition 1, the observers
selected one oddity from four images in a task. We rendered the images by using an identical light
probe (i.e., 'Overcast Day/Building Site (Metro Vienna)'). We prepared five poses for each task of
illumination condition 1 by rotating each object in 36-degree steps; four of them were randomly
selected in each task.

Under illumination condition 2, the observers selected one oddity from three images in a task.
We created the images by using slightly different (in terms of their pixel histograms) light probes
(i.e., 'Overcast Day/Building Site (Metro Vienna)', 'Overcast day at Techgate Donaucity', and
'Metro Station (Vienna Metro)'). The task procedure of illumination condition 3 was the same as
that of illumination condition 2. For illumination condition 3, we created the three images by using
light probes that were rather different from each other ('Inside Tunnel Machine', 'Tungsten Light
in the Evening (Metro Building Site Vienna)', and 'Building Site Interior (Metro Vienna)'). We
computed the pixel histogram similarity for each illumination pair and used it as the distance for
the multidimensional scaling analysis (MDS). We extracted three largely different light probes in
the MDS space and used them for illumination condition 3. We also selected three similar light
probes in the space and used them for illumination condition 2.

Rendering

To render the images, we used the integrator of the photon mapping method for tasks 1, 2, 4, 5,
and 6 and used the integrator of the simple volumetric path tracer implemented in the Mitsuba
renderer for task 3 (OT). The calculation was conducted using single-float precision. Each
rendered image was converted into sRGB format with a gamma of 2.2 and saved as an 8-bit .png
image.

Behavioral experiments

Laboratory experiment

Twenty paid volunteers participated in the laboratory experiment. Before starting the
experiment, we confirmed that all had normal color vision by having them take the Famsworth–
Munsell 100 Hue Test and that all had normal or corrected-to-normal vision by having them take a
simple visual acuity test. The participants were naïve to the purpose and methods of the

experiment. The experiment was approved by the Ethical Committees at NTT Communication Science Laboratories.

The generated stimuli were presented on a calibrated 30-inch EIZO color monitor (ColorEdge CG303W) controlled with an NVIDIA video card (Quadro 600). Each participant viewed the stimuli in a dark room at a viewing distance of 86 cm, where a single pixel subtended 1 arcmin. Each object image of 512 x 512 pix was presented at a size of 8.5 x 8.5 degrees.

In each trial, four (Illumination 1) or three (Illumination 2 & 3) object images chosen for each task were presented on the monitor (Fig. 3). Measurements of different illumination conditions were conducted in different blocks. Under illumination condition 1, four different object images in different orientations were presented. Under illumination conditions 2 and 3, the three different object images had different illuminations. The order of illumination conditions 1, 2, and 3 was counterbalanced across observers. The observers were asked to report which of the object images looked odd by pushing one of the keys. The stimuli were presented until the observer made a response. The task instructions were simply to find the odd one with no further explanation about how it was different from the rest. The observers were not given any feedback about whether their response was correct or not. All made ten judgments for each task of illumination condition 1. Seventeen observers made ten judgments for each task of illumination condition 2, while three made only seven judgments due to the experiment's time limitation. Seventeen observers made ten judgments for each task of illumination condition 3, while three made seven judgments due to the experiment's time limitation.

Crowdsourcing experiment

In the web experiment, 416, 411, and 405 paid volunteers participated in the tasks of illumination conditions 1, 2, and 3, respectively. We recruited these observers through a Japanese commercial crowdsourcing service. All who participated under illumination condition 3 also participated under illumination conditions 1 and 2. Moreover, all who participated in illumination condition 2 had also participated under illumination condition 1. The experiment was approved by the Ethical Committees at NTT Communication Science Laboratories.

Each observer used his/her own PC's or tablet's web browser to participate in the experiment. We asked them to watch the screen from a distance of about 60 cm. Each object image was shown on the screen at a size of 512 x 512 pix.

The procedure was similar to that of the laboratory experiment. In each trial, four or three object images that had been chosen depending on the task were presented on the screen, as in Fig. 3. The measurement was conducted under illumination condition 1 first, followed by one under illumination condition 2 and one under illumination condition 3. The observers were asked to

363 report which of the object images looked odd by clicking one of the images. Each participant made
364 one judgment for each condition. The other steps of the procedure were the same as those in the
365 laboratory experiment.
366

Data analysis

For each oddity task, we computed the proportion that each participant got correct. The chance
level of the correct proportion was 0.25 for illumination condition 1 and 0.33 for illumination
conditions 2 and 3. We computed the sensitivity d' from each correct proportion by using a
numerical simulation to estimate the sensitivity of the oddity task (Craven, 1992). We used the
"Palamedes" data analysis library for the simulation (Kindom & Prins, 2010; 2016; Prins &
Kingdom, 2018). To avoid values of infinity, a correct proportion of 1 was replaced with 0.999 in
the simulation. For the laboratory experiment, we computed the sensitivity d' of each observer and
averaged it across observers. For the crowdsourcing experiment, since each observer engaged in
each task one time, we computed the proportion correct for each task from all observers' responses
and used it to compute d'.
378

Results

Environment dependence

For cross-cultural, cross-species, brain-dysfunction, and developmental studies, stimulus
presentation on a monitor cannot always be strictly controlled because of apparatus or ethical
limitations. Therefore, a performance validation of each task across different apparatuses is critical
to decide which tasks the users of our database should select in their experimental environment.
Figure 7a shows the results of the correlation analysis between the laboratory and crowdsourcing
experiments. The coefficient of determination (R^2) of the linear regression between the sensitivity
d' in the laboratory experiment and that of the crowdsourcing experiment is 0.83, indicating a high
linear correlation. However, the slope of the regression is less than 1. This shows that the
sensitivity of the crowdsourcing experiment was worse than that of the laboratory experiment,
with many repetitions in general. These findings suggest that the present tasks maintain relative
performance across different experimental environments.
Figure 7b shows the results for each task of the laboratory and crowdsourcing experiments in
more detail. The coefficients of determination (R^2) in tasks 1 to 6 are 0.66, 0.38, 0.81, 0.67, 0.67,
and 0.33, respectively. The coefficient of task 6 (GP) was the worst, followed by task 2 (GD). As
in the latter section, task 6 (GP) also showed large individual differences, and thus, the correlation

between the laboratory and crowdsourcing experiments was decreased. The slope of the linear regression on task 2 (GD) was 0.34, and the proportion correct in the crowdsourcing experiment for tasks 2 were generally lower than those in the laboratory for tasks 2. In the laboratory experiment, we used a 30-inch LCD monitor, and the stimulus size of each image was presented at a size of 8.5 x 8.5 degrees, which we expected to be larger than when participants on the web observed the image on a tablet or PC. Task 2 (GD) is related to the sharpness of the specular reflection, and thus, the spatial resolution might have affected the accuracy of the observers' responses, although the relative difficulty for task 2 (GD) even in the crowdsourcing experiment was similar to that in the laboratory experiment. These findings suggest that the absolute accuracy of task 2 (GD) depends largely upon the experimental environment.

(a) All tasks

(b) Individual tasks

Figure 7. Results of laboratory and crowdsourcing experiments. The sensitivity d' in each task in the crowdsourcing experiment is plotted as a function of that in the laboratory experiment. (a) Results of all tasks. Each plot indicates a task with an object, an illumination, and a difficulty. The red line indicates the linear regression between the crowdsourcing and laboratory results. The coefficient of determination (R^2) of the regression and the equation are shown in the legend. The results show that the present tasks are generally robust across experimental environments. (b) Results of individual tasks. Different panels indicate tasks involving different materials. Each plot in a panel indicates a task with an object, illumination, and difficulty. The red line indicates the linear regression between the laboratory and crowdsourcing results. The coefficient of

determination (R^2) of the regression and the equation are shown in the legend. The
accuracy of task 2 (GD) in the crowdsourcing experiment was generally lower than that in
the laboratory experiment. The correlation of task 6 (GP) between the laboratory and
crowdsourcing experiments was the worst.

Illumination and geometry

Figures 8 to 13 show the performance of each task in the laboratory experiment. Different
panels depict results obtained for different objects. Different symbols in each panel depict different
illumination conditions. The results of the crowdsourcing experiment are shown in Appendix A.
For each task conducted under identical illumination and object conditions, i.e., for the identical
symbols of each panel in Fig. 8 to 13, discrimination accuracy monotonically improved as the
material parameter of the target stimulus deviated from that of the non-target stimulus. This
finding suggests that our material manipulation appropriately controlled the task difficulty.

By comprehensively assessing material recognition performance across different stimulus
conditions, we found novel properties that have been overlooked in the previous literature. One
regards the geometrical dependence of material recognition. When object images changed in the
glossiness-sharpness dimension (task 2: GD, Fig. 9), the observers could detect the material
difference better for smooth objects (Object 2 & 3) than for rugged objects (Object 4 & 5). In
contrast, when the object images changed in the glossiness-contrast dimension (task 1: GC, Fig. 8),
little geometrical dependence was found. While geometrical dependences of glossiness perception
have been reported before (Nishida & Shinya, 1998; Vangorp, Laurijssen, & Dutré, 2007), they
were mainly about the effects of shape on apparent gloss characteristics, not on gloss
discrimination. Furthermore, our results also show a geometrical dependence of translucency
perception (task 3: OT, Fig. 10). Similar to the dependence on the glossiness-sharpness dimension,
the sensitivity changed between the smooth objects (Object 2 & 3) and rugged objects (Object 4 &
5), but in the opposite way. Specifically, the translucent difference was more easily detected for
the rugged objects than for the smooth objects (Fig. 10).

Figure 8. Results of task 1 (GC) in the laboratory experiment. Different panels show different objects. Different symbols in each panel depict different illumination conditions. The vertical red line in each panel indicates the parameter of the non-target stimulus. Error bars indicate ± 1 SEM across observers.

457   Figure 9. Results of task 2 (GD) in the laboratory experiment.

461 Figure 10. Results of task 3 (OT) in the laboratory experiment.

Figure 11. Results of task 4 (MP) in the laboratory experiment. One of the observer data on Object 1 and Illumination 2 is missing due to a mistake in the stimulus presentation.

470 Figure 12. Results of task 5 (MG) in the laboratory experiment.

Figure 13. Results of task 6 (GP) in the laboratory experiment.

We also found an illumination dependence in material recognition. We used three illumination conditions, wherein the illumination environments used in a task were identical (Illumination 1), similar to each other (Illumination 2), or largely different from each other (Illumination 3). The results showed that task accuracy decreased as the difference in light probes across the images increased from Illumination 1 to 2 and 3 (Figs. 8-13). This finding not only confirms the large

effect of illumination on gloss perception reported before (Fleming et al., 2003; Motoyoshi &
Matoba 2012; Zhang et al., 2019), but also demonstrates similarly strong effects of illumination on
other material discrimination tasks (OT, MP and MG).

Not mean color judgments

One may raise a concern that our observers might have made oddity judgments based on
differences in low-level image properties such as mean color of the object, because our procedure
did not explicitly ask them to select one object image on the basis of the appearance of the
material. To examine the possible contribution of mean color information to the oddity task,
Figure 14 shows a scatter plot of the sensitivity d' as a function of the mean color difference of
each comparison task. The color difference ΔE*ab was defined in the L*a*b* space as follows.

$$\Delta E_{ab}^* = \left[\left(L_2^* - L_1^* \right)^2 + \left(a_2^* - a_1^* \right)^2 + \left(b_2^* - b_1^* \right)^2 \right]^{1/2}$$

493   ,

where L_1^*, a_1^*, and b_1^* are the spatial mean CIE $L^*a^*b^*$ values averaged over all possible non-
target stimuli, while L_2^*, a_2^*, and b_2^* are those averaged over all possible target stimuli. When the
color difference was large, d' was generally high, but even when the color difference was small, d'
was relatively high for some tasks. The color difference explains only 32% of the variance of
sensitivity in the lab experiment. These results suggest that the observers did not simply rely on
the mean color differences to perform the oddity tasks; they also relied on the material differences.

Figure 14. Comparison between the mean color difference of each task and the
observers' sensitivity. The mean difference of the target and non-target stimuli was
calculated in the L*a*b* color space.

Individual differences

Next, we evaluated the individual differences of each task in the Japanese adult population. Figure 15 shows the histogram of the response accuracy for each observer in the crowdsourcing experiment. The number of observers of illumination conditions 1, 2, and 3 was 416, 411, and 405, respectively. For each condition, the probability of a correct response was calculated by averaging the responses of each observer across objects and task difficulties. The standard deviations of tasks 1 to 6 under illumination condition 1 are .14, .11, .12, .12, .12, and .23, indicating a particularly large individual difference for task 6 (GP). The standard deviation under illumination conditions 2 and 3 ranged from .09 to .18. It should be also noted that most of the conditions show unimodal distributions, while task 6 (GP) shows a nearly uniform distribution. This finding suggests that individual differences in discrimination ability of the spatial consistency of specular highlights are larger than those for other material properties, including glossiness contrast and sharpness (GC, and GD).

Figure 15. Histogram of response accuracy for each observer in the crowdsourcing experiment. Different panels indicate different material tasks and illumination conditions. For each condition, the probability of a correct response was calculated by averaging the responses of each observer across objects and task difficulties. The mean and standard deviation of each distribution are shown in each panel.

Discussion

The present study aimed to construct a database of material images annotated with the results
of human discrimination tasks. We created material images that varied in six different material
dimensions on the basis of the previous material-recognition studies. Our database includes
various objects and illuminations so that users can comprehensively investigate the effects of these
physical causes on material recognition. The results of psychophysical experiments showed that
the task difficulty could be appropriately controlled by manipulating the material parameters.
Furthermore, they showed that the observers' performance of the tasks cannot be explained by
their exploiting simple color differences. One crucial point of our database is that we used a non-
verbal procedure to collect the observers' data and evaluated the dependence of the experimental
conditions such as laboratory versus crowdsourcing. A number of recent studies have focused on
the effect of developmental and environmental factors on material recognition. Our database is not
only for research on healthy adult humans but also for research on babies, brain-injured
participants, and animals. The present results showed that the performance of the tasks in the
crowdsourcing experiment was strongly correlated with that in the laboratory experiment. This
suggests that the database has enough tolerance to conduct new experiments involving a variety of
observers and experimental conditions. We also evaluated the possible effects of different
experimental conditions on material recognition.

Since we comprehensively investigated the material recognition using a structured dataset, our
database itself revealed novel findings about material recognition. One is the geometrical
dependence of translucency perception (Fig. 10). Specifically, the translucency discrimination
sensitivity was high when the object had rugged surfaces (e.g., Object 1, 4, & 5). Some studies
have shown that physically prominent features of translucent objects appear around sharp corners
on the surface (Fleming et al., 2005; Gkioulekas et al., 2013). One possibility is that the diagnostic
features for translucent perception lie in the edge/corner of a translucent object and our rugged
objects included much information to judge translucency. More recently, Xiao et al. (2019)
investigated the effect of geometry on translucency perception. In their experiments, they changed
the smoothness of the object edges. In agreement with our findings, the edge modulation was
critical to the translucency perception. Specifically, the object with the smooth edge was perceived
as more translucent than the sharp one.

Another finding is that the ability to discriminate the spatial consistency of specular highlights
in glossiness perception has large individual differences, although other glossiness discrimination
tasks do not show such large differences. Some studies suggest that image statistics are diagnostic
for glossiness perception (Adelson, 2001; Motoyoshi et al., 2008). However, when specular
highlights of an object image are inconsistent in terms of their position and/or orientation with
respect to the diffuse shading component, they look more like white blobs produced by surface
reflectance changes (Beck & Prazdny, 1981; Kim et al., 2011; Marlow et al., 2011). This is why
the highlight-inconsistency effect is considered to be a counterexample to the image statistics
explanation. The large individual differences suggest that the discrimination of the spatial
consistency of specular highlights may be mediated by a different, and possibly more complicated,

mechanism than that responsible the glossiness contrast/sharpness discrimination. In agreement
with this notion, Sawayama and Nishida (2018) showed that highlight inconsistency is
discriminated by different image gradient features from those used in the human material
computation. This suggests that the glossiness computation is mediated by multiple stages, i.e.,
one is to discriminate different materials on a surface for extracting a region-of-interest (ROI), and
another is to compute the degree of glossiness in the ROI as shown in Motoyoshi et al. (2007).

Although our database includes diverse material dimensions, they are still not enough to cover
the full range of natural materials. One example is cloth (Xiao et a., 2016; Bi & Xiao, 2016; Bi et
al., 2018; 2019). Cloth material is ubiquitous in everyday environments. A reason we did not
include this class of materials is that it has been shown that the cloth perception strongly relies on
dynamic information (Bi et al., 2018; 2019). Because of the limited experimental time, our
database currently focuses on static images. This is why other materials related to dynamic
information (reviewed by Nishida et al., 2018) related to the perception of liquidness (Kawabe et
al., 2015), viscosity (Kawabe et al., 2015, van Assen & Fleming, 2018), stiffness (Paulun et al.,
2017), etc., were not used in the current investigation. In addition, the perception of wetness
(Sawayama, Adelson, & Nishida, 2017) and the fineness of surface microstructures (Sawayama,
Nishida, & Shinya, 2017) were not investigated because of the difficulty of continuously
controlling physical material parameters by using identical geometries of other tasks. Since we
only used five geometries, material perceptions derived from object mechanical properties were
not investigated either (Schmidt et al., 2017). A crucial point is that our database is open-source,
because we want to remove obstacles to constructing a new database and contribute to future work
on material recognition.

Currently, several research groups including ones in behavioral science, computer science, and
neuroscience have on-going projects utilizing our database, and some findings have already been
reported at conferences. For instance, Kawasaki et al. (2019) used our database to explore the role
of the monkey ITC on material perception by using the electrocorticography (ECoG) recordings.
Koumura et al. (2018) investigated how mid-level features in deep convolutional neural networks
can explain human behavioral data. Imura et al. (2017) compared the discrimination performance
of children and adults. Takakura et al., (2017) investigated the role of attention in material
recognition.

Conclusion

We constructed image and observer database for material recognition experiments. We collected observation data about material discrimination in tasks that had a non-verbal procedure for six material dimensions and several task difficulties. The results of psychophysical experiments in laboratory and crowdsourcing environments showed that the performance of the tasks in the crowdsourcing experiment was strongly correlated with the performance of the tasks in the laboratory experiment. In addition, by using the above comprehensive data, we showed novel findings on the perception of translucence and glossiness. Not only can the database be used as benchmark data for neuroscience and psychophysics studies on the material recognition capability of healthy adult humans; it can also be used in cross-cultural, cross-species, brain-dysfunction, and developmental studies of humans and animals.

Acknowledgements

This work was supported by a Grant-in-Aid for Scientific Research on Innovative Areas from the Japan Society of Promotion of Science to SN and YD (JSPS KAKENHI Grant Numbers JP15H05915 and JP15H05924, respectively).

Commercial relationships: none.

Competing interests

The authors declare no competing financial interests.

References

Adelson, E. H. in *Photonics West 2001-Electronic Imaging.* 1-12 (International Society for Optics and Photonics).

Adams, W. J., Kerrigan, I. S. & Graf, E. W. (2016) Touch influences perceived gloss. *Scientific reports* **6**, 21866.

Ashikmin, M., Premože, S. & Shirley, P. in *Proceedings of the 27th annual conference on Computer graphics and interactive techniques.* 65-74 (ACM Press/Addison-Wesley Publishing Co.).

Beck J., & Prazdny S. (1981). Highlights and the perception of glossiness. *Perception, & Psychophysics*, 30(4), 407–410.

Bi, W, and Xiao, B. (2016). Perceptual constancy of mechanical properties of fabrics under variation of external force. *Proceedings of the ACM Symposium on Applied Perception* (pp. 19–23). New York, NY: ACM.

Bi, W., Jin, P., Nienborg, H., & Xiao, B. (2018). Estimating mechanical properties of cloth from videos using dense motion trajectories: Human psychophysics and machine learning. *Journal of Vision*, 18(5):12, 1–20,

Bi, W., Jin, P., Nienborg, H., & Xiao, B. (2019). Manipulating patterns of dynamic deformation elicits the impression of cloth with varying stiffness. *Journal of Vision*, 19(5):18, 1–18

Brainard, D. H. & Hurlbert, A. C. Colour vision: understanding #thedress. *Current Biology* **25**, R551-R554 (2015).

Chadwick, A.C., Cox, G., Smithson, H.E., Kentridge, R.W. Beyond scattering and absorption: perceptual unmixing of translucent liquids. *Journal of Vision.* 18(11):18, 1–15 (2018)

Craven, B. J. (1992). A table of d′ for M-alternative odd-man-out forced-choice procedures. *Perception & Psychophysics*, *51*(4), 379-385.

Doerschner, K. *et al.* Visual motion and the perception of surface material. *Current Biology* **21**, 2010-2016, doi:10.1016/j.cub.2011.10.036 (2011).

Fleming, R. W. (2017). Material perception. *Annual review of vision science*, 3, 365-388.

Fleming, R. W. & Bülthoff, H. H. Low-level image cues in the perception of translucent materials. *ACM Transactions on Applied Perception (TAP)* **2**, 346-382 (2005).

Fleming, R. W., Dror, R. O. & Adelson, E. H. Real-world illumination and the perception of surface reflectance properties. *Journal of vision* **3**, 3-3 (2003).

Gegenfurtner, K. R., Bloj, M., & Toscani, M. (2015). The many colours of 'the dress'. *Current Biology*, 25(13), R543-R544.

Gkioulekas, I., Xiao, B., Zhao, S., Adelson, E.H., Zickler, T., Bala, K. (2013) Understanding the role of phase function in translucent appearance. *ACM Transactions on Graphics* **32**, 1-19, doi:10.1145/2516971.2516972.

Gkioulekas, I., Walter, B., Adelson, E.H., Bala, K., Zickler, T. (2015) On the appearance of translucent edges, *In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)* 2015, pp. 5528–5536.

Goda, N., Yokoi, I., Tachibana, A., Minamimoto, T. & Komatsu, H. (2016) Crossmodal association of visual and haptic material properties of objects in the monkey ventral visual cortex. *Current Biology* **26**, 928-934.

Imura, T., Sawayama, M., Shirai, T., Tomonaga, M., & Nishida, S. (2017)ヒト児童における光沢質感の知覚．日本基礎心理学会第 36 回大会，大阪，日本

Jakob, W. Mitsuba physically based renderer. mitsuba-renderer. Org. (2010).

Jensen, H. W., Marschner, S. R., Levoy, M. & Hanrahan, P. (2001) A practical model for subsurface light transport. *In Proceedings of the 28th annual conference on Computer graphics and interactive techniques,* 511-518.

Kawabe, T., Maruya, K. & Nishida, S. (2015) Perceptual transparency from image deformation. *Proceedings of the National Academy of Sciences* **112**, E4620-E4627

Kawabe, T., Maruya, K., Fleming, R. W. & Nishida, S. (2015) Seeing liquids from visual motion. *Vision Research* **109**, 125-138, doi:10.1016/j.visres.2014.07.003.

Kawasaki, K., Miki, H., Anzai, K., Sawayama, M., Matsuo, T., Suzuki, T., Hasegawa, T., & Okatani, T. (2019) Spatial and time-frequency representations of glossy material properties in the monkey inferior temporal cortex. Society for Neuroscience 2019, Chicago, IL

Kentridge, R. W., Thomson, R. & Heywood, C. A. (2012) Glossiness perception can be mediated independently of cortical processing of colour or texture. *Cortex* **48**, 1244-1246, doi:10.1016/j.cortex.2012.01.011.

Kim, J., & Marlow, P. J. (2016). Turning the world upside down to understand perceived transparency. *i-Perception*, 7(5), 2041669516671566.

Kim, J., Marlow, P. & Anderson, B. L. (2011) The perception of gloss depends on highlight congruence with surface shading. *Journal of Vision* **11**, doi:10.1167/11.9.4.

Kingdom, F. A .A. & Prins, N. (2010) Psychophysics: A Practical Introduction. Academic Press: an imprint of Elsevier, London.

Kingdom, F. A .A. & Prins, N. (2016) Psychophysics: A Practical Introduction, Second Edition. Academic Press: an imprint of Elsevier, London.

Koumura, T., Sawayama, M., & Nishida, S., (2018), "Explaining behavioral data of visual material discrimination with a neural network for natural image recognition", 28th Annual Conference of Japanese Neural Network Society, Okinawa, Japan

Marlow, P., Kim, J. & Anderson, B. L. (2011) The role of brightness and orientation congruence in the perception of surface gloss. *Journal of Vision* **11**, doi:10.1167/11.9.16.

Marlow, P. J., Kim, J. & Anderson, B. L. (2012) The perception and misperception of specular surface reflectance. *Current Biology* **22**, 1909-1913, doi:10.1016/j.cub.2012.08.009.

Miyakawa N., Banno T., Abe H., Tani T., Suzuki W., & Ichinohe N. (2017). Representation of glossy material surface in ventral superior temporal sulcal area of common marmosets. *Frontiers in Neural Circuits*, 11, 17, 1–15.

Motoyoshi, I. (2010) Highlight-shading relationship as a cue for the perception of translucent and transparent materials. *Journal of Vision* **10**, 6, doi:10.1167/10.9.6.

Motoyoshi, I., & Matoba, H. (2012). Variability in constancy of the perceived surface reflectance across different illumination statistics. *Vision Research*, *53*(1), 30-39.

Motoyoshi I., Nishida S., Sharan L., & Adelson E. H. (2007). Image statistics and the perception of surface qualities. *Nature*, 447(7141), 206–209. pmid:17443193

Nagai, T. *et al.* Image regions contributing to perceptual translucency: A psychophysical reverse-correlation study. *i-Perception* **4**, 407-428 (2013).

Nishida, S. Y. (2019). Image statistics for material perception. *Current Opinion in Behavioral Sciences*, 30, 94-99.

Nishida, S. Y., Kawabe, T., Sawayama, M., & Fukiage, T. (2018). Motion perception: From detection to interpretation. Annual review of vision science, 4, 501-523.

Nishida, S. & Shinya, M. Use of image-based information in judgments of surface-reflectance properties. *Journal of the Optical Society of America A* **15**, 2951-2965 (1998).

Nishio, A., Goda, N., & Komatsu, H. (2012). Neural selectivity and representation of gloss in the monkey inferior temporal cortex. *Journal of Neuroscience*, *32*(31), 10780-10793.

Nishio, A., Shimokawa, T., Goda, N. & Komatsu, H. Perceptual gloss parameters are encoded by population responses in the monkey inferior temporal cortex. *Journal of Neuroscience* **34**, 11143-11151, doi:10.1523/JNEUROSCI.1451-14.2014 (2014).

Okazawa, G., Koida, K. & Komatsu, H. Categorical properties of the color term "GOLD". *Journal of Vision* **11**, 4-4, doi:10.1167/11.8.4 (2011).

Olkkonen, M. & Brainard, D. H. Perceived glossiness and lightness under real-world illumination. *Journal of Vision* **10**, 5-5, doi:10.1167/10.9.5 (2010).

Pellacini, F., Ferwerda, J. A., & Greenberg, D. P. (2000, July). Toward a psychophysically-based light reflection model for image synthesis. In *Proceedings of the 27th annual conference on Computer graphics and interactive techniques* (pp. 55-64). ACM Press/Addison-Wesley Publishing Co.

Prins, N & Kingdom, F. A. A. (2018) Applying the model-comparison approach to test specific research hypotheses in psychophysical research using the Palamedes Toolbox. Frontiers in Psychology, 9:1250. doi: 10.3389/fpsyg.2018.01250

Saarela, T., & Olkkonen, M. (2016) ShapeToolbox, https://github.com/saarela/ShapeToolbox

Saarela, T. (2018) ShapeToolbox: Creating 3D models for vision research. *Journal of Vision* 18(10):229. doi: 10.1167/18.10.229.

Sawayama, M., Adelson, E. H., & Nishida, S. (2017). Visual wetness perception based on image color statistics. *Journal of Vision*, 17(5):7, 1–24, doi:10.1167/17.5.7.

Sawayama, M., & Nishida, S. Y. (2018). Material and shape perception based on two types of intensity gradient information. *PLoS computational biology*, 14(4), e1006061.

Sawayama, M., Nishida, S., & Shinya, M. (2017). Human perception of subresolution fineness of dense textures based on image intensity statistics. *Journal of Vision*, 17(4):8, 1–18, doi:10.1167/17.4.8.

Schmidt, F., Paulun, V. C., van Assen, J. J. R., & Fleming, R. W. (2017). Inferring the stiffness of unfamiliar objects from optical, shape, and motion cues. *Journal of Vision*, 17(3):18, 1–17, doi:10.1167/17.3.18.

Sun, H.-C., Ban, H., Di Luca, M. & Welchman, A. E. fMRI evidence for areas that process surface gloss in the human visual cortex. *Vision research* **109**, 149-157 (2015).

Takakura, K., Tseng, C., Matsumiya, K., Kuriki, I., & Shioiri, S. (2018) 質感と初期視覚特徴の間の時間周波数特性の違いに関する検討. 日本視覚学会 2018 年夏季大会. 茨城, 日本

Tamura, H., Prokott, K. E., & Fleming, R. W. (2019). Distinguishing mirror from glass: A 'big
data' approach to material perception. arXiv preprint arXiv:1903.01671.

van Assen, J. J. R., Barla, P., & Fleming, R. W. (2018). Visual features in the perception of
liquids. *Current biology*, 28(3), 452-458.

Vangorp, P., Laurijssen, J., & Dutré, P. (2007, August). The influence of shape on the perception
of material reflectance. *ACM Transactions on graphics (TOG)*, 26(3), 267-276.

Walter, B., Marschner, S. R., Li, H. & Torrance, K. E. (2007) Microfacet models for refraction
through rough surfaces. *In Proceedings of the 18th Eurographics conference on*
Rendering Techniques, 195-206.

Ward, G. J. Measuring and modeling anisotropic reflection. *ACM SIGGRAPH Computer Graphics*
26, 265-272 (1992).

Xiao, B., Walter, B., Gkioulekas, I., Zickler, T., Adelson, E., & Bala, K. (2014). Looking against
the light: how perception of translucency depends on lighting direction. *Journal of Vision*,
14(3):17, 1–22, doi:10.1167/14.3.17.

Xiao, B., Bi, W., Jia, X., Wei, H., & Adelson, E. H. (2016). Can you see what you feel? Color and
folding properties affect visual–tactile material discrimination of fabrics. *Journal of*
Vision, 16(3):34, 1–15, doi:10.1167/16.3.34.

Xiao, B., Zhao, S., Gkioulekas, I., Bi, W., & Bala, K., Effect of geometric sharpness on
translucent material perception. bioRxiv, doi: https://doi.org/10.1101/795294

Yang, J., Kanazawa, S., Yamaguchi, M. K. & Motoyoshi, I. Pre-constancy vision in infants.
Current Biology **25**, 3209-3212 (2015).

Zhang, F., de Ridder, H., Barla, P., & Pont, S. (2019). A systematic approach to testing and
predicting light-material interactions. Journal of Vision, 19(4):11, 1–22,
https://doi.org/10.1167/19.4.11.

775
776
777

Appendix

Data records

The database is available at https://www.dropbox.com/s/6bh1ncm8mv3i7dx/material_swym.zip?dl=0 [Currently, the database is in a Dropbox folder, but we will put it on our project page later]. Figure A1 shows the data structure. The standard data are divided into three folders according to the illumination conditions. Each illumination condition folder contains folders of the material tasks (Task 1 to 6). Each material task folder includes experimental task folders. Each experimental task folder corresponds to one task in the behavioural experiments. The name of each folder indicates the illumination

condition, object, material task, and task level. For instance, the name "Il1_obj1_Task1_06_12"

indicates illumination condition 1 (i.e., Il1), object 1 (i.e., obj1), task 1 (Task1), contrast of 0.06

for the non-target stimulus, and contrast of 0.12 for the comparison stimulus.

Each task folder contains the two folders named "1" and "0". The images in the folder "0"

indicate the non-target stimuli, while the images in the folder "1" are the target stimuli. Under

illumination condition 1, three images are randomly selected from folder "0", and one correct

image is selected from folder "1". Five images with different poses are stored in each "1" or "0"

folder for illumination condition 1, while three images with different illuminations are stored for

illumination conditions 2 and 3. The images in the database are in .png format and have a size of

512 x 512 px. In addition, standard observer data are placed on the top layer in the database in

a .csv file. The file includes observer data including the probability of the correct response and the

sensitivity d' for each task in the crowdsourcing and laboratory experiments.

Figure A1. Data structure in the database. Solid rectangles indicate a folder, while the

dashed ones indicate a file.