Shared neural representations of cognitive conflict and negative affect in the medial frontal

cortex

Luc Vermeylen[1*], David Wisniewski[1], Carlos González-García[1], Vincent Hoofs[1], Wim

Notebaert[1], Senne Braem[1,2]

[1]Department of Experimental Psychology, Ghent University, Belgium

[2]Department of Experimental and Applied Psychology, Vrije Universiteit Brussel, Belgium

*Correspondence

Luc Vermeylen

Department of Experimental Psychology

Henri Dunantlaan 2

B – 9000 Ghent

BELGIUM

Email: Luc.Vermeylen@ugent.be

Abstract

Influential theories of medial frontal cortex (MFC) function suggest that the MFC registers

cognitive conflict as an aversive signal, but no study directly tested this idea. Instead, recent

studies suggested that non-overlapping regions in the MFC process conflict and affect. In this

pre-registered human fMRI study, we used multivariate pattern analyses to identify which

regions respond similarly to conflict and aversive signals. The results reveal that, of all conflict-

and value-related regions, the ventral pre-supplementary motor area (or dorsal anterior cingulate

cortex) showed a shared neural pattern response to different conflict and affect tasks. These

findings challenge recent conclusions that conflict and affect are processed independently, and

provide support for integrative views of MFC function.

Introduction

The medial frontal cortex (MFC), and dorsal anterior cingulate cortex (dACC) in particular, have

been implicated in various psychological processes such as cognitive control, somatic pain,

emotion regulation, reward learning and decision making (Ebitz & Hayden, 2016; Heilbronner &

Hayden, 2016; Shackman et al., 2011). In the domain of cognitive control, the dACC is

consistently activated by cognitive conflict, that is, the simultaneous activation of mutually

incompatible stimulus, task, or response representations (Botvinick et al., 2001). However, other

studies also showed dACC's involvement during the evaluation of negative outcomes, such as

reductions in reward (Gehring & Willoughby, 2002), negative feedback (Nieuwenhuis et al.,

2004) and pain (Rainville, 2002). Therefore, more integrative accounts of the dACC started to

redescribe its role in conflict monitoring as detecting a domain-general aversive learning signal

that can bias behavior away from the source of conflict (Botvinick, 2007; Shackman et al., 2011;

Shenhav et al., 2013, 2016). In other words, the dACC is thought to register "cognitive" conflict

as an aversive event. In accordance with this idea, recent studies have supported the presence of

a behavioral bias to avoid conflict, and have also shown that humans automatically evaluate

conflict as negative (Dignath et al., 2020; Dreisbach & Fischer, 2015; Inzlicht et al., 2015).

If conflict is registered as an aversive event in the dACC, one intriguing possibility is that

conflict and negative affect are encoded similarly in dACC ("shared or overlapping

representations", Kragel et al., 2018). This conjecture also relates to a broader debate on the

functional organization of the MFC in regard to the psychological domains of cognitive control,

negative affect and pain (Inzlicht et al., 2015; Lieberman & Eisenberger, 2015; Shackman et al.,

2011). Towards the end of the last century, cognitive neuroscientists argued for the functional

segregation of affect (ventral part of the ACC) and cognitive control (dorsal part of the ACC) in

the MFC (Bush et al., 2000; Devinsky et al., 1995). In contrast, an influential meta-analysis by

Shackman and colleagues (2011) seemed to contradict this idea by showing substantial overlap

in the dorsal part of the ACC for the three-way conjunction of negative affect, conflict and pain

(Shackman et al., 2011). Similarly, one previous study tried to investigate the overlap in

activation between cognitive conflict and negative affect by using a repetition suppression

procedure, and found that dACC showed an attenuated response to negative affect following

cognitive conflict (Braem et al., 2017).

In more recent years, however, other studies failed to provide evidence for such functional

integration. For example, a number of recent studies and meta-analyses demonstrated that

distinct rather than overlapping parts of the MFC are associated with cognitive conflict and pain

processing (De La Vega et al., 2016; Jahn et al., 2016; Lieberman et al., 2016). Similarly, one

recent mega-analysis study reported a multivariate pattern analysis (MVPA) on full activation

maps from 18 studies to assess the similarity of patterns evoked by different domains. This study

also did not observe overlap between the activation patterns evoked by cognitive control, pain,

and negative emotion in the MFC (Kragel et al., 2018). Taken together, current studies seem to

be at odds with integrative views of MFC (Botvinick, 2007; Brown & Alexander, 2017; Calhoun

& Hayden, 2015; Heilbronner & Hayden, 2016; Shackman et al., 2011; Shenhav et al., 2013,

2016), which aim to explain the various responses of dACC by one underlying process (e.g.,

avoidance learning, value estimation, surprise processing). However, these studies relied on

group-averaged (often univariate) activation differences originating from distinct paradigms. For

example, the mega-analysis by Kragel and colleagues (2018) used a context-insensitive

"cognitive control" signal (i.e., across working memory, response inhibition, and conflict

processing tasks) considering paradigms from multiple studies that differ in experimental

control. Moreover, many of these previous studies made use of intense pain responses that could

mask similarities with the arguably subtler affective evaluation of cognitive conflict.

Here, we took a different approach and developed a more targeted and well-controlled within-

subjects test of shared neural representations of conflict and negative affect. Namely, by using

multivariate cross-classification analyses, we assessed whether and where a classifier algorithm

trained to discern conflict (incongruent vs congruent events) can successfully predict affect

(negative vs positive events), and vice versa. Successful classification (i.e., classification above

chance) would be indicative of a similarity between the neural pattern response, and thus a

shared representational code between these two domains (Kaplan et al., 2015; Wisniewski,

2018). To test our predictions, 38 human subjects performed a color Stroop (Stroop, 1935) and

flanker task (Eriksen & Eriksen, 1974) in the conflict domain, and two closely matched tasks in

the affective domain (Fig. 1A). Importantly, we used two tasks in each domain in order to first

demonstrate an abstract or generalizable representation of conflict (and affect), that is

independent of conflict type (and affect source) (Jiang & Egner, 2014). Conflict and affect-

related brain signals were modeled using run-wise beta images retrieved from single subject

(first-level) analysis and were then used to perform a five-fold leave-one-run-out cross-

classification analysis using a linear Support Vector Machine (see Methods).

Next, we performed preregistered Region of Interest (ROI, Fig. 2D) and whole brain searchlight

analyses (Supplementary Table 1), and report accuracy-minus-chance values (chance level: 50

%) for each searchlight sphere or ROI (Amygdala, Anterior Cingulate Cortex [ACC], dACC/pre-

SMA, Anterior Insula [AI], Posterior Cingulate Cortex [PCC], Ventral Striatum [VS], and the

ventromedial Prefrontal Cortex [vmPFC]). To construct the ROIs, we entered the name of the

anatomical area as a search term in Neurosynth (Yarkoni et al., 2011) and constructed 10mm

109 spheres around the peak z-value of the corresponding meta-analytical activation map (see

110 Methods and [1]). For our main set of ROI analyses (i.e. successful cross-domain cross-task

111 classification), we report the uncorrected p-values and Bayes Factors (always one-tailed; is

112 accuracy-minus-chance larger than 0?), as well as the Bonferroni-corrected p-values that control

113 for the fact that we analyzed seven ROIs (i.e., multiplying the uncorrected p-value by 7). Please

114 note that although our literature study above focuses on the MFC, we wanted to ensure in our

115 preregistration that other regions could be evaluated as well. For the other (secondary) set of ROI

116 analyses, we present uncorrected p-values, but these results can be more strictly evaluated in

117 light of the adjusted Bonferroni alpha level for seven tests ($\alpha = .00714$).

---

[1] We actually pre-registered that the ROIs would come from the Harvard-Oxford cortical and subcortical atlases, thresholded at 25%. However, at the time of pre-registration we did not realize that the dACC ROI has no clear analogue in the Harvard-Oxford or most other atlases. We reasoned that the most neutral way to deviate from the pre-registration was to construct spheres from peak-values of the Neurosynth maps for each respective ROI.

Figure 1. Task Design and Behavioral Data. **(A)** Task design. Subjects either judged the color of

words or the color of circles. In the conflict domain, the color either matched or mismatched with

word meaning or background color creating congruent or incongruent conditions, respectively.

In the affective domain, positive or negative words and pictures were used to create the

respective conditions. Note that regardless of the domain, subjects always had to judge the color

of the word or the circle. These four task contexts were presented block-wise (with order

counterbalanced) in each run. **(B)** Reaction time and accuracy for the corresponding four task

contexts. Error bars denote the 95% CI.

Results

We first analyzed the behavioral data to check whether the conflict task showed the typical

congruency effects, and subjects processed the affective stimuli in the affective task. The

behavioral data from the conflict tasks (Fig. 1B, left panels and Supplementary Table 3) showed

typical congruency effects in reaction time (RT, $F_{(1,37)}$=149.81, $P<.001$, $BF10>100$) and

accuracy ($F_{(1,37)}$=11.72, $P=.002$, $BF=52$), which were larger in the color-word task ($M=109$ ms,

$T_{(68)}$=13.39, $P<.001$) relative to the color-circle task ($M=51$ ms, $T_{(68)}$=6.31, $P<.001$) for the RT

measure (interaction between task and congruency effect: $F_{(1,37)}$=35.55, $P<.001$, $BF>100$). In the

affective tasks, we found slower RTs with negative relative to positive background stimuli

($F_{(1,37)}$=5.74, $P=.025$, $BF=0.38$), but this was only the case for the color-circle task ($M=12$ ms,

$T_{(73)}$=3.12, $P=.003$) and not the color-word task ($M=1$ ms, $T_{(73)}$=0.37, $P=.710$) (interaction

between task and valence effect: $F_{(1,37)}$=4.27, $P=.046$, $BF=0.37$) (Fig. 1B, right panels and

Supplementary Table 4). No effects on accuracy were found in the affective tasks (Fs<3.12,

Ps>.085). In the conflict tasks, catch trials were used to draw attention to the conflicting nature

of the stimuli. Here, subjects had to judge the irrelevant rather than the relevant dimension (see

Method). We observed above-chance catch trial performance (chance level = 25 %), which did

not differ between the two conflict tasks, ($\chi^2_{(1)}$=0.10, P=.755, BF=0.12; color-circle task: 90.7 %;

color-word task 89.9 %). In the affective tasks, catch trials (where subjects had to make a

valence judgement instead of a color judgement) and a post-experiment incidental memory test

were used to inform processing of the (task-irrelevant) affective stimuli. We observed above-

chance catch trial performance (chance level = 50%), which did not differ between the two affect

tasks, ($\chi^2_{(1)}$=0.19, P=.664, BF=0.12; color-circle task: 86.4 %; color-word task 87.8 %), and

successful post-experiment recognition of the affective stimuli (Supplementary Figure 5),

ensuring that subjects processed the affective pictures.

In a first set of multivariate pattern analyses, we trained and tested a classifier within-task (within

the Stroop or flanker task; Fig. 2A, left panels; which regions respond to conflict within tasks?),

in each of our preregistered ROIs (for analysis details, see Method). Within-task ROI analyses in

the conflict domain (congruent vs. incongruent) revealed evidence for above chance-level

decoding in the ACC (*Wilcoxon V*=388, *uncorrected P*=.003, BF=15.61, Bonferroni-adjusted α

= .00714), dACC/pre-SMA (*V*=327, *P*=.009, BF=8.48) and PCC (*V*=346, *P*=.009, BF=4.57) but

not in in any of the other regions (all *P*>.145, BF<0.61) (Fig. 2A, right panel). The decoding

accuracies did not differ by task (ACC: $F_{(1,37)}$=0.01, P=.915, BF=0.18, dACC/preSMA:

$F_{(1,37)}$=0.72, P=.400, BF=0.24, PCC: $F_{(1,37)}$=0.51, P=.476, BF=0.22).

A second set of multivariate pattern analyses evaluated whether we could also cross-classify

conflict signals cross-task (train and test on different tasks; which regions respond similarly to

conflict independent of specific task features? Fig. 2B, left panels). To our knowledge, no study

has shown a voxel pattern response to conflict that is independent of conflict task in the ACC or

pre-SMA (e.g., Jiang & Egner, 2014). Here, our within-conflict cross-task ROI analyses revealed

above chance level conflict decoding across tasks in the dACC/pre-SMA (V=283, P=.012,

BF=5.57) and PCC (V=328, P=.023, BF=3.67) (Fig. 2B, right panel). Decoding accuracy did not

differ between cross-task combination for the dACC/pre-SMA ($F_{(1,37)}$=0.89, P=.352, BF=0.26),

but was larger in the Stroop to flanker decoding relative to the flanker to Stroop decoding for the

PCC ($F_{(1,37)}$=4.35, P=.043, BF=1.21). These results were also replicated in an overall decoding

approach where the classifier was trained and tested in the whole domain regardless of task

(resulting in more samples to train the classifier; Supplementary Fig. 1A). Within the affective

domain (positive vs. negative), we also performed similar within- and cross-task decoding

analyses. However, while these analyses showed evidence for affect information in the AI and

vmPFC, they did not show evidence for decoding in the ACC, dACC/pre-SMA or PCC

(Supplementary Fig. 2; but see follow-up analyses below).

Finally, we investigated our main hypothesis by training a classifier on discerning conflict

(incongruent vs congruent) and testing its performance on discerning affect (negative vs

positive), and vice versa. For this main set of analyses, we report the uncorrected and

Bonferonni-corrected p-values, and focused on the cross-domain cross-task decoding (train and

test in different domains on different tasks) as this analysis controls for low-level features shared

between the two tasks (Fig. 2C, left panel). The cross-domain cross-task ROI decoding revealed

evidence for cross-classification in the dACC/pre-SMA (V=330, P=.007, BF=8.43; Fig. 2C, right

panel) and vmPFC (V=277, P=.045, BF=1.56), which did not differ by cross-task combination

(dACC/pre-SMA: $F_{(1,37)}$=0.36, P=.551, BF=0.20, vmPFC: $F_{(1,37)}$=0.02, P=.880, BF=0.18).

Bonferroni corrected p-values controlling for the use of seven ROIs showed this result was still

significant for the dACC/pre-SMA (P_{corr}=.049), but not for the vmPFC (P_{corr}=.316). None of the

other ROIs reached significance (all Ps>.444, BFs <0.24). Using the overall decoding approach

(training on both tasks in one domain and testing on both tasks in the other domain), we were

only able to replicate successful cross-domain decoding in dACC/pre-SMA (V=449, P=.021,

BF=4.65; Supplementary Fig. 1C).

Figure 2. Main Results. **(A)** Training and testing the classifier within the conflict domain, within

the same task. **(B)** Training the classifier on one conflict task and testing its performance on

another conflict task. **(C)** Training the classifier to discern conflict and testing its performance on

classifying affect in another task (and vice versa). **(D)** ROIs: Anterior Cingulate Cortex (ACC),

Anterior Insula (AI), Amygdala (Amyg), dorsal Anterior Cingulate Cortex/pre-Supplementary

Motor Area (dACC/pre-SMA or dACC/pSMA), Posterior Cingulate Cortex (PCC), ventromedial

Prefrontal Cortex (vmPFC), Ventrial Striatum (VS). Black dots and error bars represent mean

and ± 95 CI respectively; transparent dots represent individual data points; the shape of the violin

shows the distribution of the data.

In what follows, we report three additional sets of control analyses. A first set was designed to

evaluate the extent to which our analysis choices influenced our findings (Botvinik-Nezer et al.,

2020). A second set was geared towards ruling out alternative hypotheses. Finally, a third set

further zoomed in on the above observation that we could not decode affect within- or across-

tasks in the dACC/pre-SMA, but did observe cross-domain decoding.

First, a number of control analyses using different analysis choices further confirmed our main

finding. We replicated our results using permutation testing (see Methods), as classification rates

might not match theoretical chance levels (Jamalabadi et al., 2016). This approach revealed

similar results (dACC/pre-SMA: P=.006, P_{corr}=.041, vmPFC: P=.034, P_{corr}=.238) and further

demonstrated that chance level was not inflated as the mean of the group null distribution of the

accuracy minus chance measure did not differ from zero for each of the two ROIs (dACC/pre-

SMA: P=.753; vmPFC: P=.267). We also replicated our main finding using different smoothing

parameters (Supplementary Fig. 3), or when using Harvard-Oxford atlas ROIs (Supplementary

Fig. 4) instead of ROIs retrieved from NeuroSynth. Moreover, when using a set of functionally

(rather than anatomically) defined conflict-sensitive ROIs based on a recent meta-analysis (from

Chen et al., 2018, see their Table 2 for MNI coordinates), we again observed evidence for cross-

domain cross-task classification in the dACC/pre-SMA (V=450, P=.013, BF=3.75) but not for

other conflict-sensitive ROIs (left MOG, right AI, left AI, left IFG, left IPL, right IPL, left

MFG), except for the left AI (V=425, P=.005, BF=8.61). The result again replicated when using

the overall decoding approach in the dACC/pre-SMA (V=449, p=.001, BF=41.06), but not in the

left AI (V=335, P=.260, BF=0.34) (Supplementary Fig. 1, panel D).

Second, to further study whether the main effect was specific to the congruency identity and

valence of our experimental conditions, we also tested whether task difficulty differences or

differences in arousal could not explain our results. Notably, there was a small performance

difference in task performance on negative versus positive affect trials. Therefore, it is possible

that our cross-decoding result reflects the decoding of reaction time, rather than a shared conflict

and affect signal. However, the RT effects for the affective domain were rather small (BF<1) and

only present for one of the two affective tasks (also, note that there were no effects on accuracy).

Importantly, as reported above, the cross-domain decoding accuracy did not depend on which

task was used for testing. Moreover, cross-domain decoding accuracy was not higher when

splitting the sample for the subsample that did show the RT effect (RT effect>0, N=28, M=1.96,

P=.050, BF=1.66) relative to a subsample that did not show the RT effect (RT effect<0, N=10, M

=3.50, P=.017, BF=4.58) ($F_{(1,36)}$=0.59, P=.444), nor did the RT effect correlate with cross-

domain decoding accuracy (R=-0.23, P=.162). Nevertheless, in order to control for any potential

confounding effects of RT, we also ran another control analysis regressing out RT-related effects

from the neural data (via parametric modulation). This analysis led to the same conclusions as

above (cross-domain cross-task dACC/pre-SMA: $V=380$, $p=.036$, $BF=1.91$, overall cross-domain

dACC/pre-SMA: $V=348$, $p=.025$, $BF=2.61$). Note that this does make the effect slightly smaller,

which should not be surprising as this procedure also removes variance of interest (as the

effectiveness of the congruency manipulation is often defined by RT differences).

Next, we also found that the cross-domain decoding was unlikely to be due to arousal. First, we

were only able to decode arousal (high vs. low arousal; based on a median-split of arousal

ratings, orthogonal to valence) within-tasks in the ACC ($V=260$, $P=.039$, $BF=1.43$) and vmPFC

($V=240$, $P=.048$, $BF=1.38$), but not in the dACC/pre-SMA ($V=230$, $P=.082$, $BF=0.83$) or other

ROIs ($P>.217$, $BF<0.39$). Second, training a classifier on conflict and testing on arousal (and

vice versa) did not show any evidence for cross-decoding in the dACC/pre-SMA ($V=294$,

$P=.404$, $BF=0.26$), nor any of the other ROIs ($Ps>.139$, $BF<0.51$), except for the vmPFC

($V=401$, $P=.015$, $BF=3.25$).

Third, and finally, we wanted to follow up on the unexpected result that we did not observe

within and cross-task decoding of affect in the dACC/pre-SMA. One potential explanation is that

the SNR was lower for our affect differences than the congruency differences. In line with this,

while the univariate affect contrast (negative > positive) showed no cluster-corrected activation

in the MFC (Supplementary Table 2), a large cluster of dmPFC activity does become visible,

when we lower the threshold ($p < .005$, uncorrected). Similarly, when restricting the whole-brain

decoding analysis to the MFC using the same mask as Kragel and colleagues (2018), within-

affect decoding did reveal a large cluster in the MFC, overlapping with our main dACC/pre-

SMA ROI, as well as the within-conflict decoding and cross-domain decoding results (see

Supplementary Fig. 6). A second reason for observing weaker affect decoding signals, could be

because the affect signals weakened or habituated throughout the experiment, as the same

affective words and pictures were repeated in each run. Therefore, we also investigated whether

affect might have been easier to decode in the beginning of the experiment, by studying cross-

task affect for the first half (run 1 and 2) and second half (run 4 and 5), separately. Indeed, there

was significant cross-task affect decoding in main dACC/pre-SMA ROI in the first half of the

experiment (run 1 and 2, $V=237$, $P=.019$, $BF=2.38$), but not in the second half of the experiment

(run 4 and 5, $V=138$, $P=.646$, $BF=0.10$). Finally, it is worth noting that our ROIs were primarily

selected to detect conflict-based differences (see also our literature-based ROIs on conflict

decoding, Supplementary Fig. 1, panel D), which again potentially lowered our chances to

observe affect decoding. When using ROIs based on an affect processing meta-analysis (from

Lindquist et al., 2016, their Table 2, cf. our conflict-sensitive ROIs), a pre-SMA ROI close to our

original dACC/pre-SMA ROI (but a bit more dorsal) did show significant affect ($V=314$, $P=.001$,

$BF=39.70$), conflict ($V=308$, $P=.002$, $BF=27.19$) and cross-domain decoding ($V=375$, $P=.042$,

$BF=1.52$). Together, these results do suggest that there was affect decoding in, or at least around

our main dACC/pre-SMA ROI.

Discussion

Together, our results reveal that the dACC/pre-SMA shows a similar voxel pattern response to

conflict and negative affect. Moreover, to the best of our knowledge, our study is also the first to

show decoding of conflict across conflict tasks in the dACC/pre-SMA, suggesting a shared

component in the detection of conflict across the Stroop and flanker task (Jiang & Egner, 2014).

These findings fit with integrative accounts of MFC function which propose that multiple

domains (e.g., cognitive conflict, negative emotion and pain) activate a single underlying process

in the MFC (e.g., adaptive control, avoidance learning, cost-benefit value estimation), and thus

predict similar activation patterns across domains (Botvinick, 2007; Brown & Alexander, 2017;

Calhoun & Hayden, 2015; Heilbronner & Hayden, 2016; Shackman et al., 2011; Shenhav et al.,

2013, 2016). Since our study focused on the domains of cognitive conflict and negative affect,

our finding is especially relevant for theories that have tried to explain dACC's sensitivity to

conflict and negative outcomes by a single unifying process (Botvinick, 2007; Shenhav 2013,

2016). These theories have proposed the idea that conflict is in itself an aversive outcome

(Botvinick, 2007; Shackman et al., 2011; Shenhav et al., 2013), and the main mechanism of the

dACC is to bias behavior away from any costly, demanding or suboptimal outcome ("domain-

general avoidance learning", Botvinick, 2007) or to allocate control based on the expected

benefits discounted by the expected costs of controlling behavior ("cost-benefit value

estimation" Shenhav et al., 2013).

Importantly, our study was not set up to disentangle the multiple candidate processes as to why

conflict and negative affect would elicit a shared neural pattern response in the MFC, so while

our main finding (i.e., similar voxel pattern response to conflict and negative affect) follows

naturally from above-mentioned models that predict similar patterns of brain activity for

different domains, it does not favor a specific mechanism (e.g. domain-general avoidance

learning). Still, our finding does lend credence to the idea that that cognitive control can be

understood as an emotional process (Inzlicht et al., 2015), and that conflict can be registered as

an aversive event (i.e., Botvinick, 2007; Dignath et al., 2020; Dreisbach & Fischer, 2015), at

least in the dACC/pre-SMA. Similarly, additional analyses further show that our effect is

unlikely to be driven by general differences in reaction time or task difficulty, or differences in

arousal.

Other recent studies failed to find similarities, and suggest that theories of MFC function should

not look for a unitary neural implementation, but rather focus on a unified computational

mechanism (Kragel et al., 2018). Our study does not argue against this idea, as shared neural

"representations" in fMRI could still be driven by different local neighboring neural populations.

However, we believe our findings do license consideration of a unitary neural implementation,

and offer support for the idea of a unified computational mechanism. Still, one might wonder

why we did, and others did not, find shared neural representations of conflict and affect. First, we

employed a multivariate approach rather than a univariate approach which is more sensitive and

more informative to assess similarity in brain activation (without necessarily being orthogonal to

a univariate approach; Davis et al., 2014). Second, our design was specifically set up to evaluate

similarity between two specific domains (conflict and negative affect) rather than very general

domains (cognitive control, negative emotion, pain). Third, related to this, we used a within-

subjects design (rather than the between-subject nature of meta- or mega-analyses), which

allowed for more sensitive analyses and to make the different task contexts as similar as possible

(high level of experimental control).

One unexpected finding relates to the fact that we did not observe a similar (significant) above-

chance decoding of affect in the dACC/pre-SMA, but did observe cross-domain decoding.

Although this finding was surprising to us at first, it most likely suggests differences in signal to

noise ratio (SNR) between the two domains and does not invalidate the cross-domain decoding

result (for a review and discussion of similar findings, see van den Hurk & de Beeck, 2019). This

idea was also further corroborated by follow-up analyses which showed affect decoding in the

dACC/pre-SMA when using other analysis techniques, or focusing on the first half of the

experiment only. Moreover, a lower SNR in the affect domain can also be explained by the fact

that affect was not relevant for the main task (which allowed us to keep the affective tasks as

similar as possible to the conflict tasks).

Finally, while our analyses were based on theories and a NeuroSynth ROI of the dACC,

investigating the (uncorrected) whole-brain searchlight decoding maps did reveal that the

conflict, affect and cross-domain decoding all trigger a dorsomedial frontal area, that might be

more accurately referred to as pre-SMA rather than dACC. This area roughly corresponds to our

main dACC/pre-SMA ROI which was retrieved by searching "dACC" in NeuroSynth (Yarkoni

et al., 2011), and therefore, we decided to refer to this ROI as dACC/pre-SMA. Nevertheless,

this illustrates the consequent mislabeling of the dACC in the literature and we are not the first to

report pre-SMA activation for domains such as cognitive control, pain and negative emotion

(Brown & Alexander, 2017; De La Vega et al., 2016; Jahn et al., 2016; Kolling et al., 2016;

Kragel et al., 2018; Lieberman & Eisenberger, 2015; Lindquist et al., 2016).

In sum, by using a well-controlled within-subject design and multivariate analysis techniques, we

show that conflict and negative affect evoke a similar voxel pattern response in the MFC. Our

finding brings important nuance to other recent studies suggesting different neural activations or

representations, and helps to further constrain theories of integrative MFC function.

Materials and Methods

Participants

The study was pre-registered with the pre-registration template from AsPredicted.org on the

Open Science Framework (https://osf.io/p5frq/). As pre-registered, 40 participants participated in

our study. Two participants were excluded (one due to excessive head motion [>2.5mm

translation] and one aborted the scanning session). The average age of the remaining 38

participants (13 male) was 23.71 years (*SD*=3.53, min=18, max=33). Thirty-six participants

were right-handed, one was left-handed and one was ambidextrous (as assessed by the Edinburgh

Handedness Inventory (Oldfield, 1971)). Every participant had normal or corrected to normal

vision and reported no current or history of neurological, psychiatric or major medical disorder.

Every participant gave their informed written consent before the experiment, and was paid 35

euros for participating afterwards. The study was approved by the local ethics committee

(University Hospital Ghent University, Belgium).

Experimental Paradigm

The experiment was implemented using Psychopy 2 version 1.85.2 (Peirce, 2007). On each trial,

participants had to judge the color of a target stimulus in the center of the screen, using two MR-

compatible response boxes (each box had two buttons) to indicate one out of four possible

response options (red, blue, green and yellow). The key-to-color mapping was counterbalanced

between participants. The exact features of the target stimulus varied block-wise, depending on

one of four different task-contexts. Specifically, participants either had to respond to the color of

words ("color-word naming task") or respond to the color of circles ("color-circle naming task"),

which both had a conflict and affective version.

The conflict-version of the color-word naming task was a Stroop task (Stroop, 1935), where the

meaning of the words could either be congruent or incongruent with the actual color of the word.

For example, participants could see the words "BLUE", "RED", "GREEN" or "YELLOW"

(Dutch: "ROOD", "BLAUW", "GROEN" or "GEEL") presented in a blue, red, green or yellow

font. The conflict version of the color-circle naming task was essentially a color-based variant on

the Eriksen flanker task (Eriksen & Eriksen, 1974), where the irrelevant feature consisted of a

colored background square which could either be congruent or incongruent with the color of the

circle. Here, participants could see blue, red, green or yellow circles presented on a blue, red,

green or yellow background square. In both tasks, half of the trials were congruent (e.g., "RED"

in a red font; a red circle presented on a red square background) while the other half of the trials

were incongruent (e.g., "RED" in a blue font; a red circle on a blue square background).

The affect-versions of the color-word naming and color-circle naming tasks made use of

irrelevant affective words or pictures, respectively. In the color-word naming task, 16 positive

and 16 negative words were presented (Moors et al., 2013) that were matched on arousal, power,

age of acquisition, Dutch word frequency (Keuleers et al., 2010), word length and grammatical

category (Noun, Adjective and Verbs). The affective picture distractors in the background of the

color-circle naming task were retrieved from the OASIS database (Kurdi et al., 2017). Sixteen

positive and 16 negative pictures were presented that were matched on semantic category

(Animals, Objects, People, Scenery) and arousal. This resulted in a total of eight conditions:

congruent, incongruent, positive or negative trials, that either involved words or pictures/colored

backgrounds.

Each trial started with a fixation sign ("+") that was presented for 3 to 6.5 seconds (in steps of

0.5 s; M=3.5 s; drawn from an exponential distribution). Next, the target stimulus was presented

for 1.5 seconds (fixed presentation time regardless of RT). In order to increase the saliency of the

irrelevant dimension (conflict and affect), the onset of the affective word or picture preceded the

presentation of the target feature by 200 ms during which the color of the target feature (word or

circle) was white.

Participants performed five scanning runs and during each run the subjects performed each of the

four task contexts in separate blocks. The order of the four blocked task contexts was fixed

within participant but counterbalanced between participants. Each block hosted 32 trials (16

congruent/positive and 16 incongruent/negative) which were presented in a pseudo-random

fashion with the following restriction: neither relevant nor irrelevant features of the target

stimulus could be repeated. This restriction was used to investigate confound-free congruency

sequence effects (see Braem et al., 2019; Schmidt, 2019; but this was not the aim of the current

study and will not be discussed further). In total, each participant made 640 trials (i.e., five runs

of four blocks of 32 trials).

In each task context (block), we also included one catch trial (at random, but not in the first two

or last two trials of each block). In these catch trials, the presentation of the task-irrelevant word,

picture, or colored square would not be followed by the presentation of the target color, and

remain on screen for three seconds. Participants were instructed that during these catch trials,

when no color information was present in the relevant dimension, their goal was to judge the

irrelevant dimension depending on the cognitive domain. In the conflict domain, participants had

to respond to the meaning of the word ("RED", "BLUE", "GREEN" or "YELLOW") or to the

color of the background square (red, blue, green or yellow) by using the respective key that

would be used to judge the relevant dimension. In the affective domain, participants had to judge

the affective word or background picture as either positive or negative by pressing all keys once

or twice (response mapping for positive and negative stimuli counterbalanced between

participants). The purpose of these catch trials was to increase the saliency of the irrelevant

dimension.

Before the scanning session, participants were welcomed and instructed to read the informed

consent after which they started practicing the experimental paradigm. After the scanning

sessions, participants performed an unannounced recognition memory test on old and new

affective words and pictures. Here, participants had to indicate whether they had previously seen

the word or picture in the experiment (old/new judgement). The new words were matched with

the old words in terms of valence, arousal, power, age of acquisition, word length, frequency,

grammatical category. The new pictures were matched on valence, arousal and semantic

category. In both a behavioral (n = 20) and fMRI pilot (n = 20), we already established that

participants showed adequate performance on both the main task and the recognition memory

task. Finally, participants completed four questionnaires (Need for Cognition, Behavioral

Inhibition/Activation Scale, Positive and Negative Affect Schedule, Barret Impulsivity Scale)

and were thanked for their participation. No significant correlations between these questionnaire

scales and cross-classification accuracies were found (see Supplementary Table 5 and 6).

Behavioral Data Analysis

Behavioral analyses were performed in R (RStudio version 1.1.463, www.rstudio.com). For the

reaction time (RT) analyses, we removed incorrect, premature (< 150 ms), and extreme

responses (RTs outside 3 SD from each condition mean for each participant). This resulted in an

average of 94.42 % of the trials left for the RT analyses (*SD*=3.18, min=84.22, max=98.28). We

conducted a repeated measures ANOVA on the reaction time and accuracy measure with the

within-subject factors Condition (conflict domain: congruent vs. incongruent, affective domain:

positive vs. negative) and Task (color-word naming vs. color-circle naming). We also assessed

post-scanning recognition memory of affective stimuli with a probit generalized linear mixed

effects model on the probability to say that the stimulus was 'old' with fixed effects for

Experience (old vs. new), Valence (positive vs. negative) and Task Type (word vs. picture) and

crossed random effects for Participant and Item. We also pre-registered some exclusion criteria

based on behavioral performance. Participants with a mean RT outside 3 SD from the sample

mean or a hit rate below 3 SD or 60 % (chance level=25 %) from the sample mean were

excluded. Participants that performed poorly on the post-scanning recognition memory test, i.e.,

hit rate or false alarm rate outside 3 SD of the sample mean were also excluded. In the end, no

exclusions based on task performance had to be made. While performance on catch trials was not

a pre-registered exclusion criterion, we found that two participants responded on chance level in

the catch trials of the affective domain (chance level=50 %, positive vs. negative judgement).

Excluding these participants did not change our conclusions.

fMRI data acquisition

fMRI data was collected using a 3T Magnetom Prisma MRI scanner system (Siemens Medical

Systems, Erlangen, Germany), with a sixty-four-channel radio-frequency head coil. A 3D high-

resolution anatomical image of the whole brain was acquired for co-registration and

normalization of the functional images, using a T1-weighted MPRAGE sequence (TR=2250 ms,

TE=4.18 ms, TI=900 ms, acquisition matrix=256 × 256, FOV=256 mm, flip angle=9°, voxel

size=1 × 1 × 1 mm). Furthermore, a field map was acquired for each participant, in order to

correct for magnetic field inhomogeneities (TR=520 ms, TE1=4.92 ms, TE2=7.38 ms, image

matrix=70 x 70, FOV=210 mm, flip angle=60°, slice thickness=3 mm, voxel size=3 x 3 x 2.5

mm, distance factor=0%, 50 slices). Whole brain functional images were collected using a T2*-

weighted EPI sequence (TR=1730 ms, TE=30 ms, image matrix=84 × 84, FOV=210 mm, flip

angle=66°, slice thickness=2.5 mm, voxel size=2.5 x 2.5 x 2.5 mm, distance factor=0%, 50

slices) with slice acceleration factor 2 (Simultaneous Multi-Slice acquisition). Slices were

oriented along the AC-PC line for each subject.

fMRI data analysis

fMRI data analysis was performed using Matlab (version R2016b 9.1.0, MathWorks) and

SPM12 (www.fil.ion.ucl.ac.uk/spm/software/spm12/). Raw data was imported according to

BIDS standards (http://bids.neuroimaging.io/) and functional data was subsequently realigned,

slice-time corrected, normalized (resampled voxel size 2 mm^3) and smoothed (full-width at half

maximum of 8 mm). The preprocessed data was then entered into a first-level general linear

model analysis (GLM), and subsequently into a multivariate pattern analysis (MVPA(Cox &

Savoy, 2003; Haxby, 2012; Haynes, 2015; Kriegeskorte et al., 2006). Results were analyzed

using a mass-univariate approach. Although we pre-registered that we would not normalize and

smooth the data for our classification analyses, we found that Signal-to-Noise Ratio (SNR) was

significantly improved with these additional preprocessing steps (Supplementary Fig. 3A). In

addition, an independent classification analysis (classifying left vs. right responses in primary

motor cortex) showed that decoding accuracies were significantly higher with these additional

preprocessing steps (Supplementary Fig. 3B). Knowing that decoding information in the PFC is

notoriously difficult as decoding accuracies are close to chance (relative to decoding in

occipitotemporal cortex (Bhandari et al., 2018), and the finding that smoothing can and does

often improve SNR and decoding performance (Hendriks et al., 2017; Kamitani & Sawahata,

2010; Op de Beeck, 2010), we decided to optimize our MVPA analyses by decoding on

normalized and smoothed data. For completeness, however, we also depict the results from our

main cross-classification analysis for different levels of smoothing (FWHM 0, 4 and 8 mm; see

Supplementary Fig. 3C).

First-level GLM analyses consisted of 5 identically modeled sessions (i.e., the five runs). Each

session consists of eight regressors of interest (for the eight conditions, see above), four block

regressors (to account for the blocked presentation of each combination of word versus picture

versions of the conflict versus affect tasks), two nuisance regressors (that model performance

errors and catch trials) and six movement regressors. The regressors were convolved with the

canonical HRF. The modeled duration of the regressors of interest (the eight conditions) and

nuisiance regressors (errors, catch trials) was zero, while the modeled duration of the block

regressors was equal to the length of the blocks.

Next, the beta images from the first-level GLM were submitted to leave-one-run-out decoding

scheme with 'The Decoding Toolbox' (Hebart et al., 2015) using a linear support-vector

classification algorithm (C=1). We performed whole-brain searchlight decoding (sphere radius: 3

voxels; Supplementary Table 1) as well as ROI decoding (see below for ROI methods). Cross-

validation decoding was conducted within the affective (positive vs. negative) and conflict

(congruent vs. incongruent) domain for each task separately ("within-domain within-task

classification"). To assess the generalizability of the classifier within the domain, we also

conducted cross-classification analyses where we trained the classifier on one task and tested its

performance on the other task for each task type combination (from color-circle naming to color-

word naming and vice versa) separately ("within-domain cross-task classification"). To

investigate the generalizability of these classifiers across the domain (our main hypothesis), we

trained the classifier in the conflict domain and tested its performance in the affective domain,

and vice versa. We conducted these analyses cross task type combinations (i.e., from color-circle

naming to color-word naming, or from color-word naming to color-circle naming) to further

control for low-level task features, following the same reasoning as the within-domain cross-task

classification analyses ("cross-domain cross-task classification"). For each of these three

decoding analyses, we also ran ANOVAs to evaluate whether the result differed depending on

the task (e.g., color-circle naming versus color-word naming) or task-to-task direction (i.e., from

color-circle naming to color-word naming, or from color-word naming to color-circle naming).

Finally, we also report an "overall decoding" analysis, where the classifier was trained across the

two task types at once, thereby ignoring whether the event featured words or pictures/colored

backgrounds.

Each classification analysis resulted in 'accuracy-minus-chance' decoding maps for each subject.

These maps were then entered into a group second-level GLM analysis in SPM12. Here, a one-

sample t-test determined which voxels show significant accuracy above chance level.

Importantly, counterbalancing schemes that are not problematic for traditional analyses can

introduce problems for the assessment of chance performance in MVPA (Gorgen et al., 2018).

This can be the case when the counterbalancing is "broken" by splitting the runs in training and

test sets given that the counterbalancing and cross-validation are situated on the same level (e.g.

the within-subject level of the runs, Gorgen et al., Neuroimage 2018). However, in our study, the

order of the four tasks within a scanning run was counterbalanced between participants but fixed

within participant (which is where the leave one run out cross-validation occurs). Therefore,

counterbalancing conditions were always matched between training and testing runs. In addition,

we modeled the blocked structure of the scanning runs by adding block regressors in the first

level GLM's (before entering the beta images to the classification analyses). Therefore, it is

unlikely that our counterbalancing could have introduced problems for the assessment of chance

level. Nonetheless, for our main findings, this was verified by inspecting the null distributions

obtained via permutation testing. Further, we did not remove univariate difference (more

specifically, response differences of the same sign), as is sometimes done. Univariate differences

are often a useful source of information and should not necessarily be viewed as irrelevant for

multivariate analyses (Hebart & Baker, 2018). Further, we do not intend to make a special claim

about fine grained subtle patterns that go beyond univariate response differences.

536 Next to MVPA, we also conducted classic univariate analyses. Here, we constructed a set of

537 contrasts subtracting (A) positive from negative conditions and (B) congruent from incongruent

538 conditions for (1) each task separately as well as across both tasks. These contrast images were

539 then entered into a second-level analysis in which a one-sample t-test determined which voxels

540 show significant activation for each contrast. We applied a statistical threshold of $p < 0.001$

541 (uncorrected) at the voxel level, and $p < 0.05$ (family-wise error corrected) at the cluster level on

542 all analyses (Supplementary Table 2).

ROI analyses

544 As part of our pre-registered main analysis plan, we conducted ROI decoding analyses. We set

545 out to study the Amygdala, Anterior Cingulate Cortex (ACC), dorsal Anterior Cingulate

546 Cortex/pre-SMA (dACC/pre-SMA), Anterior Insula (AI), Parietal Cingulate Cortex (PCC),

547 Ventral Striatum (VS), and the ventromedial PFC (vmPFC). Our preregistration noted that all

548 ROIs would be obtained from the Harvard-Oxford cortical and subcortical structural atlases,

549 thresholded at 25%. However, as the dACC ROI was not defined in the Harvard-Oxford atlas,

550 we decided to retrieve this ROI from Neurosynth (Yarkoni et al., 2011) by entering "dacc" as

551 search term (returning 162 studies reporting 4547 activations). Although this ROI was based on

552 the "dacc" search term, the peak effect of studies reporting dACC activity actually lies more

553 dorsally than the cingulate gyrus, overlapping with the pre-SMA (Lieberman & Eisenberger,

554 2015). Therefore, we refer to this ROI as the dACC/pre-SMA. Next, we built a 10 mm sphere

555 around the peak activation point in this activation map (association map). Because the dACC

556 ROI was spherical (in contrast to the other six atlas ROIs), we decided to retrieve all ROIs from

557 NeuroSynth for comparability. However, because our preregistration mentioned that the ROIs

558 would be obtained from the Harvard-Oxford cortical and subcortical structural atlases, we also

report the analyses where all non-dACC regions were evaluated using these ROIs, which

returned similar results and did not change our main conclusions (see Supplementary Figure 4).

In addition to the pre-registered ROI analyses which were based on anatomically determined

ROIs, we also ran another set of ROI analyses with functionally informed ROIs. Namely, we

created 10 mm sphere ROIs for all conflict-sensitive regions based on the most recent and

inclusive meta-analysis we could find on cognitive conflict (Chen et al., 2018, Table 2).

Each ROI decoding analysis returned one accuracy-minus-chance value per ROI and participant.

We tested whether these values were significantly higher than zero (one-tailed) with the non-

parametric Wilcoxon signed-rank test and a Bayesian t-test (using the default priors from the

BayesFactor package in R; Cauchy prior width: $r=.707$). We report the Bayes Factor (BF) that

quantifies the evidence for the alternative hypothesis (i.e., decoding accuracy is higher than

zero). For our main hypothesis (cross-domain cross-task classification) we also report

permutation tests. Here, the labels of the classification categories were shuffled (within-run only)

and classification was performed for all possible permutations leading to first-level null

distributions (i.e., for each subject) of accuracy-minus-chance values. A second-level null

distribution was retrieved by calculating 10000 group averages (where the value for each subject

is a random draw from its respective null distribution). We retrieved a p-value by dividing the

number of samples above the empirical accuracy-minus-chance level by the total number of

samples in the null distribution. The procedure of obtaining the second-level null distribution and

p-value was repeated 1000 times after which we averaged the resulting p-values. This lead to

stable p-values that are not influenced by stochasticity in the procedure. We report uncorrected

as well as Bonferroni-corrected p-values for our main test. The secondary tests are not corrected

as they are not the main aim of the study (but can be more strictly evaluated by handling the

Bonferonni-corrected alpha: $p<.00714$). Finally, we investigated whether the significant cross-

task cross-domain classification accuracy correlated with the following behavioral indices: post-

scanning affective recognition memory (d-prime), congruency sequence effects in reaction time

and error rate and congruency sequence effects in reaction time and error rates (p-values of

reported correlations are Holm-corrected for five tests) (see Supplementary Figure 5).

Acknowledgements

We would like to thank Tobias Egner for valuable comments on a previous draft of the

manuscript. W.N., S.B. (G.0660.17N) and L.V. (11H5619N) were supported by the FWO –

Research Foundation Flanders. C.G.G. was supported by the Special Research Fund of Ghent

University (BOF.GOA.2017.0002.03). D.W. was supported by the FWO

(FWO.KAN.2019.0023.01), and the European Union's Horizon 2020 research and innovation

program under the Marie Skłodowska-Curie grant agreement No 665501. All procedures applied

in the present experiment were carried out with adequate understanding and written consent of

the subjects and are in accordance with the Declaration of Helsinki.

Author Contributions

597   S.B. and W.N. developed the study concept. S.B., W.N. and L.V. contributed to the study design.

598   Data collection was performed by L.V. and V.H.. Data analysis was performed by L.V. under the

599   supervision of S.B., D.W. and C.G.C.. The manuscript was drafted by L.V. in cooperation with

600   S.B., W.N., D.W. and C.G.C.. All authors approved the final version of the manuscript for

601   submission.

Declaration of Interests

603   The authors have no competing interests to declare.

References

Bhandari, A., Gagne, C., & Badre, D. (2018). Just above Chance: Is It Harder to Decode Information from Prefrontal Cortex Hemodynamic Activity Patterns? *Journal of Cognitive Neuroscience*, *30*(10), 1473–1498. https://doi.org/10.1162/jocn_a_01291

Botvinick, M. M. (2007). Conflict monitoring and decision making: Reconciling two perspectives on anterior cingulate function. *Cognitive, Affective, & Behavioral Neuroscience*, *7*(4), 356–366. https://doi.org/10.3758/CABN.7.4.356

Botvinick, M. M., Braver, T. S., Link to external site, this link will open in a new window, Barch, D. M., Carter, C. S., & Cohen, J. D. (2001). Conflict monitoring and cognitive control. *Psychological Review*, *108*(3), 624–652. http://dx.doi.org/10.1037/0033-295X.108.3.624

Botvinik-Nezer, R., Holzmeister, F., Camerer, C. F., Dreber, A., Huber, J., Johannesson, M., Kirchler, M., Iwanir, R., Mumford, J. A., Adcock, R. A., Avesani, P., Baczkowski, B. M., Bajracharya, A., Bakst, L., Ball, S., Barilari, M., Bault, N., Beaton, D., Beitner, J., … Schonberg, T. (2020). Variability in the analysis of a single neuroimaging dataset by many teams. *Nature*, *582*(7810), 84–88. https://doi.org/10.1038/s41586-020-2314-9

Braem, S., Bugg, J. M., Schmidt, J. R., Crump, M. J. C., Weissman, D. H., Notebaert, W., & Egner, T. (2019). Measuring Adaptive Control in Conflict Tasks. *Trends in Cognitive Sciences*, *23*(9), 769–783. https://doi.org/10.1016/j.tics.2019.07.002

Braem, S., King, J. A., Korb, F. M., Krebs, R. M., Notebaert, W., & Egner, T. (2017). The role of anterior cingulate cortex in the affective evaluation of conflict. *Journal of Cognitive Neuroscience*, *29*(1), 137–149.

Brown, J. W., & Alexander, W. H. (2017). Foraging value, risk avoidance, and multiple control signals: How the anterior cingulate cortex controls value-based decision-making. *Journal of Cognitive Neuroscience*, *29*(10), 1656–1673.

Bush, G., Luu, P., & Posner, M. I. (2000). Cognitive and emotional influences in anterior cingulate cortex. *Trends in Cognitive Sciences*, *4*(6), 215–222.

Calhoun, A. J., & Hayden, B. Y. (2015). The foraging brain. *Current Opinion in Behavioral Sciences*, *5*, 24–31.

Chen, T., Becker, B., Camilleri, J., Wang, L., Yu, S., Eickhoff, S. B., & Feng, C. (2018). A domain-general brain network underlying emotional and cognitive interference processing: Evidence from coordinate-based and functional connectivity meta-analyses. *Brain Structure and Function*, *223*(8), 3813–3840.

Cox, D. D., & Savoy, R. L. (2003). Functional magnetic resonance imaging (fMRI) "brain reading": Detecting and classifying distributed patterns of fMRI activity in human visual cortex. *NeuroImage*, *19*(2), 261–270. https://doi.org/10.1016/S1053-8119(03)00049-1

Davis, T., LaRocque, K. F., Mumford, J. A., Norman, K. A., Wagner, A. D., & Poldrack, R. A. (2014). What do differences between multi-voxel and univariate analysis mean? How subject-, voxel-, and trial-level variance impact fMRI analysis. *NeuroImage*, *97*, 271–283. https://doi.org/10.1016/j.neuroimage.2014.04.037

De La Vega, A., Chang, L. J., Banich, M. T., Wager, T. D., & Yarkoni, T. (2016). Large-scale meta-analysis of human medial frontal cortex reveals tripartite functional organization. *Journal of Neuroscience*, *36*(24), 6553–6562.

Devinsky, O., Morrell, M. J., & Vogt, B. A. (1995). Contributions of anterior cingulate cortex to behaviour. *Brain*, *118*(1), 279–306.

Dignath, D., Eder, A. B., Steinhauser, M., & Kiesel, A. (2020). Conflict monitoring and the

affective-signaling hypothesis—An integrative review. *Psychonomic Bulletin & Review*,

1–24.

Dreisbach, G., & Fischer, R. (2015). Conflicts as aversive signals for control adaptation. *Current*

Directions in Psychological Science, *24*(4), 255–260.

Ebitz, R. B., & Hayden, B. Y. (2016). Dorsal anterior cingulate: A Rorschach test for cognitive

neuroscience. *Nature Neuroscience*, *19*(10), 1278.

Eriksen, B. A., & Eriksen, C. W. (1974). Effects of noise letters upon the identification of a

target letter in a nonsearch task. *Perception & Psychophysics*, *16*(1), 143–149.

Gehring, W. J., & Willoughby, A. R. (2002). The medial frontal cortex and the rapid processing

of monetary gains and losses. *Science*, *295*(5563), 2279–2282.

Haxby, J. V. (2012). Multivariate pattern analysis of fMRI: The early beginnings. *NeuroImage*,

62(2), 852–855. https://doi.org/10.1016/j.neuroimage.2012.03.016

Haynes, J.-D. (2015). A Primer on Pattern-Based Approaches to fMRI: Principles, Pitfalls, and

Perspectives. *Neuron*, *87*(2), 257–270. https://doi.org/10.1016/j.neuron.2015.05.025

Hebart, M. N., & Baker, C. I. (2018). Deconstructing multivariate decoding for the study of brain

function. *NeuroImage*, *180*, 4–18. https://doi.org/10.1016/j.neuroimage.2017.08.005

Hebart, M. N., Görgen, K., & Haynes, J.-D. (2015). The Decoding Toolbox (TDT): A versatile

software package for multivariate analyses of functional imaging data. *Frontiers in*

Neuroinformatics, *8*. https://doi.org/10.3389/fninf.2014.00088

Heilbronner, S. R., & Hayden, B. Y. (2016). Dorsal anterior cingulate cortex: A bottom-up view.

Annual Review of Neuroscience, *39*, 149–170.

Hendriks, M. H. A., Daniels, N., Pegado, F., & Op de Beeck, H. P. (2017). The Effect of Spatial Smoothing on Representational Similarity in a Simple Motor Paradigm. *Frontiers in Neurology*, *8*. https://doi.org/10.3389/fneur.2017.00222

Inzlicht, M., Bartholow, B. D., & Hirsh, J. B. (2015). Emotional foundations of cognitive control. *Trends in Cognitive Sciences*, *19*(3), 126–132. https://doi.org/10.1016/j.tics.2015.01.004

Jahn, A., Nee, D. E., Alexander, W. H., & Brown, J. W. (2016). Distinct regions within medial prefrontal cortex process pain and cognition. *Journal of Neuroscience*, *36*(49), 12385–12392.

Jamalabadi, H., Alizadeh, S., Schönauer, M., Leibold, C., & Gais, S. (2016). Classification based hypothesis testing in neuroscience: Below-chance level classification rates and overlooked statistical properties of linear parametric classifiers. *Human Brain Mapping*, *37*(5), 1842–1855. https://doi.org/10.1002/hbm.23140

Jiang, J., & Egner, T. (2014). Using neural pattern classifiers to quantify the modularity of conflict–control mechanisms in the human brain. *Cerebral Cortex*, *24*(7), 1793–1805.

Kamitani, Y., & Sawahata, Y. (2010). Spatial smoothing hurts localization but not information: Pitfalls for brain mappers. *NeuroImage*, *49*(3), 1949–1952. https://doi.org/10.1016/j.neuroimage.2009.06.040

Kaplan, J. T., Man, K., & Greening, S. G. (2015). Multivariate cross-classification: Applying machine learning techniques to characterize abstraction in neural representations. *Frontiers in Human Neuroscience*, *9*, 151.

Keuleers, E., Brysbaert, M., & New, B. (2010). SUBTLEX-NL: A new measure for Dutch word

frequency based on film subtitles. *Behavior Research Methods*, *42*(3), 643–650.

https://doi.org/10.3758/BRM.42.3.643

Kolling, N., Wittmann, M. K., Behrens, T. E., Boorman, E. D., Mars, R. B., & Rushworth, M. F.

(2016). Value, search, persistence and model updating in anterior cingulate cortex.

Nature Neuroscience, *19*(10), 1280.

Kragel, P. A., Kano, M., Van Oudenhove, L., Ly, H. G., Dupont, P., Rubio, A., Delon-Martin,

C., Bonaz, B. L., Manuck, S. B., & Gianaros, P. J. (2018). Generalizable representations

of pain, cognitive control, and negative emotion in medial frontal cortex. *Nature*

Neuroscience, *21*(2), 283.

Kriegeskorte, N., Goebel, R., & Bandettini, P. (2006). Information-based functional brain

mapping. *Proceedings of the National Academy of Sciences*, *103*(10), 3863–3868.

https://doi.org/10.1073/pnas.0600244103

Kurdi, B., Lozano, S., & Banaji, M. R. (2017). Introducing the Open Affective Standardized

Image Set (OASIS). *Behavior Research Methods*, *49*(2), 457–470.

https://doi.org/10.3758/s13428-016-0715-3

Lieberman, M. D., Burns, S. M., Torre, J. B., & Eisenberger, N. I. (2016). Reply to Wager et al.:

Pain and the dACC: The importance of hit rate-adjusted effects and posterior

probabilities with fair priors. *Proceedings of the National Academy of Sciences*, *113*(18),

E2476–E2479.

Lieberman, M. D., & Eisenberger, N. I. (2015). The dorsal anterior cingulate cortex is selective

for pain: Results from large-scale reverse inference. *Proceedings of the National*

Academy of Sciences, *112*(49), 15250–15255.

Lindquist, K. A., Satpute, A. B., Wager, T. D., Weber, J., & Barrett, L. F. (2016). The brain basis

of positive and negative affect: Evidence from a meta-analysis of the human

neuroimaging literature. *Cerebral Cortex*, *26*(5), 1910–1922.

Moors, A., De Houwer, J., Hermans, D., Wanmaker, S., van Schie, K., Van Harmelen, A.-L., De

Schryver, M., De Winne, J., & Brysbaert, M. (2013). Norms of valence, arousal,

dominance, and age of acquisition for 4,300 Dutch words. *Behavior Research Methods*,

45(1), 169–177. https://doi.org/10.3758/s13428-012-0243-8

Nieuwenhuis, S., Holroyd, C. B., Mol, N., & Coles, M. G. (2004). Reinforcement-related brain

potentials from medial frontal cortex: Origins and functional significance. *Neuroscience*

& Biobehavioral Reviews, *28*(4), 441–448.

Oldfield, R. C. (1971). The assessment and analysis of handedness: The Edinburgh inventory.

Neuropsychologia, *9*(1), 97–113. https://doi.org/10.1016/0028-3932(71)90067-4

Op de Beeck, H. P. (2010). Against hyperacuity in brain reading: Spatial smoothing does not

hurt multivariate fMRI analyses? *NeuroImage*, *49*(3), 1943–1948.

https://doi.org/10.1016/j.neuroimage.2009.02.047

Peirce, J. W. (2007). PsychoPy—Psychophysics software in Python. *Journal of Neuroscience*

Methods, *162*(1), 8–13. https://doi.org/10.1016/j.jneumeth.2006.11.017

Rainville, P. (2002). Brain mechanisms of pain affect and pain modulation. *Current Opinion in*

Neurobiology, *12*(2), 195–204.

Schmidt, J. R. (2019). Evidence against conflict monitoring and adaptation: An updated review.

Psychonomic Bulletin & Review, *26*(3), 753–771.

Shackman, A. J., Salomons, T. V., Slagter, H. A., Fox, A. S., Winter, J. J., & Davidson, R. J.

(2011). The Integration of Negative Affect, Pain and Cognitive Control in the Cingulate

Cortex. *Nature Reviews Neuroscience*, *12*(3), 154–167. https://doi.org/10.1038/nrn2994

Shenhav, A., Botvinick, M. M., & Cohen, J. D. (2013). The expected value of control: An

integrative theory of anterior cingulate cortex function. *Neuron*, *79*(2), 217–240.

Shenhav, A., Cohen, J. D., & Botvinick, M. M. (2016). Dorsal anterior cingulate cortex and the

value of control. *Nature Neuroscience*, *19*(10), 1286.

Stroop, J. R. (1935). Studies of interference in serial verbal reactions. *Journal of Experimental*

Psychology, *18*(6), 643.

van den Hurk, J., & de Beeck, H. P. O. (2019). Generalization asymmetry in multivariate cross-

classification: When representation A generalizes better to representation B than B to A.

BioRxiv, 592410.

Wisniewski, D. (2018). Context-dependence and context-invariance in the neural coding of

intentional action. *Frontiers in Psychology*, *9*.

Yarkoni, T., Poldrack, R. A., Nichols, T. E., Essen, D. C. V., & Wager, T. D. (2011). Large-scale

automated synthesis of human functional neuroimaging data. *Nature Methods*, *8*(8), 665–

670. https://doi.org/10.1038/nmeth.1635