Entorhinal and ventromedial prefrontal cortices abstract and generalise the structure of reinforcement learning problems

Alon B Baram (alon.baram@merton.ox.ac.uk)[1]
Timothy H Muller (timothymuller127@gmail.com) [3]
Hamid Nili (nili.hamed@gmail.com) [1]
Mona Garvert (garvert@cbs.mpg.de) [2]
Timothy E J Behrens (behrens@fmrib.ox.ac.uk) [1,3]

[1] Wellcome Centre for Integrative Neuroimaging, University of Oxford,
John Radcliffe Hospital, Oxford OX3 9DU, UK
[2] Max-Planck-Institute for Human Cognitive and Brain Sciences, Stephanstraße 1a, 04103, Leipzig,
Germany
[3] Wellcome Trust Centre for Neuroimaging, University College London, London WC1N 3AR, UK

Abstract

Knowledge of the structure of a problem, such as relationships between stimuli, enables rapid learning and flexible inference. Humans and other animals can abstract this structural knowledge and generalise it to solve new problems. For example, in spatial reasoning, shortest-path inferences are immediate in new environments. Spatial structural transfer is mediated by grid cells in entorhinal and (in humans) medial prefrontal cortices, which maintain their structure across different environments. Here, using fMRI, we show that entorhinal and mPFC representations perform a much broader role in generalising the structure of problems. We introduce a task-remapping paradigm, where subjects solve multiple reinforcement learning (RL) problems differing in structural or sensory properties. We show that, as with space, entorhinal representations are preserved across different RL problems only if task structure is preserved. In ventromedial PFC, representations of standard RL signals such as prediction error also vary as a function of task structure.

Introduction

Reinforcement learning (RL) theory [1] has given deep insights into the brain's algorithms for learning, but has remained relatively mute about the representations that are the foundation for this learning. For example, how might a task, or an element of a task, be represented in the brain? Some recent progress has been made through comparison with spatial navigation, where representations are better understood. It has been suggested that the same representations that map Euclidean space (such as hippocampal place cells and entorhinal grid cells) may be extended to a broad range of non-spatial problems. In these cases, instead of representing physical location, they may represent location in an abstract space that captures the regularities of the task at hand [2–9].

One attractive corollary of these ideas is that non-spatial tasks might benefit from the profound representational efficiencies that are known in space. In space, entorhinal cortex (EC) grid cells encode unique locations in the most efficient manner possible, given the correlation structure of observations on a 2D Euclidean plane [5,10–12]. Furthermore, in remapping experiments, this representational structure is transferred across environments [13–15]. Hence, in new spatial environments, it is not necessary to re-learn the associations implied by 2D space. Instead it is sufficient to learn what sensory observation is where in the map [8] and inferences (such as shortest paths [16,17]) can be made immediately. The ability to transfer structural knowledge in non-spatial tasks would, similarly, bestow efficiencies. The structure of a problem, learnt in one situation, could be mapped onto a new situation with different sensory observations, and solutions could immediately be inferred. Behaviourally, it is clear that both humans and animals profit from such efficiencies. In psychology, this phenomenon is known as "learning-set" [18] - subjects with prior exposure to the structure of a problem are routinely better at solving new examples.

Might similar mechanisms support both spatial and non-spatial generalisation? One prerequisite is that brain regions that contain grid representations in Euclidian spatial tasks should also represent the structure of a reinforcement learning task. A second is that these representations should (a) generalise across different sensory exemplars of the same structural problem and (b) differ between two problems of different structure.

In humans, grid-like coding has not only been recorded in EC, as in rodents, but also in a network of brain regions in association cortex [19–22] including ventromedial prefrontal cortex (vmPFC). Notably, these brain regions are often also implicated in RL tasks [23], where signals commonly reflect algorithmic variables such as value [24,25] and prediction error [24,26,27]. If these variables have different consequences in different task structures, they may also conform to the representational predictions above [6]. Instead of a unitary representation of prediction error, these regions might generalise prediction error representations across different problems with the same task structure, but have different representations across problems with different structures.

To answer these questions, we designed an RL task where we manipulated either the problem structure (by changing the correlation structure of serial bandits) or the sensory stimuli in a 2X2 factorial design. This design mirrors a spatial remapping experiment with two important differences: (1) It is non-spatial task elements that are being remapped, as opposed to locations in 2D space. (2) We include 2 separate structures as well as 2 separate environments (sensory stimuli) in each structure. This design therefore enabled us to test for

representations of the task structure, factorised from the representations of the stimuli they were tied to.

Using fMRI in humans, we found that the EC contained a representation that differed between different task structures, but generalised over different sensory examples of the same structure. Similarly learning signals in regions including vmPFC and ventral striatum maintained different voxelwise patterns for different task structures, again generalising over different environments with the same structure.

Results

Task

Subjects performed a task where three 1-armed bandits were interleaved pseudo-randomly. Two of the bandits (bandits A & B) had correlated outcome probabilities, while the third (C) was independent. Crucially, we manipulated two features of the task across the different blocks: 1) the sign of the correlation between the A & B bandit probabilities. We refer to this correlation as the relational structure of the stimuli. 2) The stimuli set, with two possible triplets of images. Thus, there were 4 block types, each with a specific combination of a relational structure and a stimuli set, arranged in a 2x2 factorial design (Fig. 1c). The fMRI experiment comprised of 8 blocks, divided into two independent runs of each of the four block-types, with a pseudo-random block order counterbalanced across subjects. Hence, in total subjects completed 8 blocks.

In each trial, subjects viewed one of the three stimuli and had to indicate their prediction for its associated binary outcome (a "good" or a "bad" outcome, demarked by a King of Hearts or Two of Spades card, respectively) by either accepting or rejecting the stimulus (Fig. 1a and S1a). Thus, there was always one correct answer in each trial: subjects should accept a stimulus if they predict the outcome to be the "good" outcome, and should reject if they predict the outcome to be the "bad" outcome (Fig. 1a). Only in accepted trials, the subject would either win or lose a point, depending on the outcome. Outcome identity was revealed in all trials, including rejection trails, even though the subject's score did not change in these trials (Fig. 1a). Predictions of the outcomes could be formed based on the recent history of outcomes. The outcome probabilities switched pseudo-randomly between 0.9 and 0.1 with an average switch probability of 0.15. As the two correlated bandits switched together (Fig. 1b), subjects could use their knowledge of the correlation structure to learn from the outcome on one related stimulus about the other.

The outcome probabilities associated with the related stimuli were positively correlated (+Corr pairs) in half of the blocks (Fig. 2b, top two panels), and negatively correlated (-Corr pairs) in the other half (Fig. 2b, bottom two panels). In all blocks the third stimulus had an outcome probability which was uncorrelated with the other two stimuli (0Corr pairs). The current block-type was signalled by the background colour of all stimuli in the block. Subjects learned the mapping between background colour and correlation structure prior to scanning. Consequently, the only learning performed during scanning was of outcome probabilities, not of the relational structure - knowledge of which was available from the first scanning trial.

Subject behaviour

We modelled the subjects' behaviour using an adapted delta-rule, with a crucial addition of "cross-terms" that enable learning from one stimulus to another. The model separately tracks the probabilities of a "good" outcome associated with the three stimuli, all of which are updated every trial. Following an outcome at trial t where stimulus X was presented, the estimate of the outcome probability associated with X is updated according to the classic delta-rule:

$$\hat{g}^X_{t+1} = (1 - \alpha)\hat{g}^X_t + \alpha y_t \qquad \text{(equation 1)}$$

Where $\hat{g}^X_t$ is the outcome probability estimation for stimulus X before trial t, α is the learning rate, and $y_t \in \{-1,1\}$ is the binary outcome at trial t.

Crucially, the estimates of the probabilities associated with the two other stimuli are also updated:

$$\hat{g}^Y_{t+1} = (1 - \alpha|H_{XY}|)\hat{g}^Y_t + \alpha H_{XY} y_t \qquad \text{(Equation 2)}$$

Where H_{XY} is the cross-term between stimuli X and Y, fitted to the subject's behaviour in each block. $H_{XY} = 1$ indicates subjects treated X and Y as the same stimulus for learning purposes – for +Corr stimuli pairs this is the correct correlation structure. Similarly, $H_{XY} = -1$ and $H_{XY} = 0$ indicates correct correlation knowledge for -Corr and 0Corr pairs, respectively. y_t is still the outcome in trial t (a trial where stimulus X was presented).

The fitted cross-terms indicate that subjects indeed used the correlation structure correctly (Fig. 1d; Corr vs 0Corr (mean across all blocks of $|H_{AB}^{-,+}|$ vs $(|H_{AC}| + |H_{BC}|)/2$) paired $t(27) = 13.06$, $P<10^{-12}$). Subjects benefited from the extra information afforded by the correlation structure, and performed better in trials of one of the two related stimuli than in the control stimulus trials (-Corr vs 0Corr paired $t(27)=6.2$ $P<10^{-6}$; +Corr vs 0Corr paired $t(27)=4.06$ $P<10^{-3}$, Fig. S1b).

Figure 1. Task, behaviour and univariate RL neural signals. **a.** Possible progressions of a single trial. **b.** Example of the reward schedule for one subject. Solid grey lines and dashed black line are the probabilities of a good outcome for the related stimuli and the control stimulus, respectively. Xs mark the stimulus (colour) and actual binary outcome (y-axis: 0.1 and 0.9 are bad and good outcomes, respectively) in each trial. For visualisation purposes, the two 30 trials long blocks of each of the four conditions were concatenated. While related stimuli in +corr blocks are associated with exactly the same probability, their corresponding light and dark grey lines are slightly offset for visualisation purposes. **c.** Experimental design and neural predictions: 2x2 factorial design of stimuli set x relational structure. **d.** Subjects use the correlation structure correctly to guide their behaviour. Fitted cross-terms for pairs of stimuli, separated to +corr and -corr blocks. Error bars are standard errors across subjects. **e.** Effect of the chosen action value estimates from STRUCT model, in a GLM where it competes with estimates from NAÏVE model.

The reward network and the hippocampus use the relational structure to encode the value of the chosen action

We first aimed to test whether known neural signals of RL showed evidence of knowledge about the relational structure of the task. We tested this by comparing how well a model that uses relational structure explained neural signals relative to one that does not use structure. In both models, we calculated the value of the chosen action (accept/reject) on each trial of the two related stimuli (A and B). Note that the chosen action value has the same magnitude as the stimulus value tracked by the models but has an opposite sign on rejected trials. The first model was a naïve Rescorla-Wagner model (NAÏVE, cross-terms in equation 2 set to zero), and the second model utilised the relational structure (STRUCT, cross-terms in equation 2 fit to behaviour). The chosen action value estimates were used to construct one regressor per model at the time of stimulus presentation (GLM1). Estimates from both models were pitted

against each other in the same GLM, meaning any variance explained by a particular regressor was unique to that regressor, allowing us to compare the neural signals uniquely explained by each model. The contrasts in this section only included the two related stimuli in each block, as the differences between the models for the control stimulus were negligible.

A network of regions including the medial prefrontal cortex (mPFC), the amygdala (AMG), the anterior hippocampus (HPC) and the EC coded positively for the chosen action value from the STRUCT model, while a network including the anterior cingulate cortex (ACC), insula, angular gyrus and most of the orbitofrontal cortex (OFC) showed negative coding (Fig. 1e & Table S1; Similar results were obtained for the STRUCT > NAÏVE contrast, Fig. S1c). These results largely form a replication of the work in [24]. This indicates the reward network and HPC use the relational structure to calculate the value of chosen actions.

Entorhinal representations generalise across tasks with the same structure but not those with different structures.

A representation of the relational structure of the task should be similar (generalise) for stimuli which are part of the same relational structure, but dissimilar for stimuli under a different relational structure. We asked whether any region on the cortical surface displayed these properties at the times of stimulus presentation, using Representational Similarity Analysis (RSA, [28]) with a searchlight approach.

A searchlight centred on a cortical voxel consisted of the 100 surrounding voxels with the smallest surface-wise geodesic distance from the central voxel. For each searchlight, we obtained 16 patterns of (whitened within-searchlight) regression coefficients of the responses to presentations of each of the two related stimuli (A and B) in each of the 8 blocks (GLM2). In other words, we obtained two patterns, one from each of the repeated runs, for each of our 8 experimental conditions (a particular stimulus under a particular correlation structure). To control for effects of time, we used a "cross-run correlation distance" where only patterns from different runs (i.e. more than 30 minutes apart) were correlated with each other. That is, to define the distance $d_{i,j}$ between conditions i and j we first calculated the correlation distance $(1 - r)$ between the condition i pattern from run 1 and condition j pattern from run 2, and then calculated the correlation distance between the condition j pattern from run 1 and condition i pattern from run 2. $d_{i,j}$ was defined as the mean of these two distances. Notably, this means that the diagonal in the symmetric Representational Dissimilarity Matrix (RDM) is meaningful, and shows the consistency between the two runs of the same condition.

This resulted in an 8 conditions by 8 conditions symmetric RDM, summarising the representational geometry in the searchlight (e.g. Fig. 2b). The ideal structural representation can be formalised as an 8x8 model RDM, where the distances between conditions are determined by relational structure (Fig. 2a). To test whether the data RDM of a given searchlight was consistent with the model RDM, we calculated the contrast between the means of the data RDM's hypothesised "dissimilar" and "similar" elements (white and black elements in Fig. 2a, respectively). We then used permutation tests to ask whether this contrast was significantly positive across subjects (see Methods). We repeated this procedure for each searchlight centre on the cortical surface, resulting in a cortical map of p-values.

The only cluster to survive multiple comparisons correction across a cortical hemisphere was located focally in the right entorhinal cortex (Fig. 2b, 2c and 2d, P<0.05 FWE corrected for cluster mass, cluster-forming threshold P<0.001, peak MNI coordinates: [25,-5,-28]). This

effect did not change when we repeated the analysis using model RDMs where same-stimuli or same stimuli set elements were ignored (Fig. S2a and S2b). The effect was therefore not driven by background colour or low-level plasticity between stimuli that appear in the same block, but rather by a representation of the relational structure between the stimuli in the task. We note that a cluster in the right temporal-parietal junction (TPJ), where evidence of grid-like coding has been reported [19,20], was the strongest and largest amongst the few other clusters surviving the cluster-forming threshold of P<0.001 (but did not survive FWE-correction). To verify that our analysis approach was indeed valid, we tested for stimulus visual identity coding using a similar procedure with an appropriate model RDM (Fig. 2a, bottom). As expected, we observed bilateral effects in visual areas, peaking in the lateral occipital cortex (Fig 2b, 2c and 2d, bottom, P<0.05 FWE corrected on cluster level, cluster-forming threshold P<0.001, peak MNI coordinates: [44,-74,-4]). Therefore, the relational structure of our task is represented and generalised in EC.

Figure 2. The relational structure of the task is represented in the entorhinal cortex.
Top: Structure effect, peaking in EC. Bottom: stimulus effect, peaking in LOC. **a.** model RDM. Black elements should be similar, white elements should be dissimilar. Pairs of stimuli with orange and purple rectangles around them are +Corr and -Corr, respectively. **b.** Visualisation of the data RDM from peak vertex of the effect, marked with an arrow in **d**. **c.** Visualisation of the paired mean difference effects between *same* (black RDM elements in **a.**) and *different* (white elements in **a.**) pairs of conditions, from the peak vertex of the effects. Both groups are plotted on the left axes as a slope-graph: each paired set of observations for one subject is connected by a line. The paired mean difference is plotted on a floating axis on the right, aligned to the mean of the *same* group. The mean difference is depicted by a dashed line (consequently aligned to the mean of the *diff* group). Error bars indicate the 95% confidence interval obtained by a bootstrap procedure. **d.** Whole surface results, right hemisphere. Clusters surviving FWE correction at a cluster forming threshold of P<0.001 are indicated in green.

vmPFC and ventral striatum represent the relational structure in learning signals

The vmPFC is central to reward-guided learning [23]. Intriguingly, previous studies suggest grid-like coding can also be found in mPFC [19–22]. We hypothesised that vmPFC learning signals of the type typically observed in RL tasks [24,26,27] may be sensitive to the relational structure. That is, because prediction errors have different implications for learning under the

two different relational structures, we hypothesized that vmPFC would not simply encode a signal that monotonically increases with prediction error as previously reported. Instead, we hypothesized that the representation of prediction errors across voxels would differ depending on the relational structure.

We first found a strong univariate prediction error signal in a network of regions including vmPFC (Fig. 3b, inset) and the ventral striatum (vStr, Fig. 3c, inset), in line with previous findings [24,26,27]. Note that the prediction error used here is the "correctness" prediction error, defined as the magnitude of the prediction error from the STRUCT model, and a sign that depends on the congruence between the subject's choice and the outcome: positive when the outcome matches the subject's choice (accept-"good" outcome; reject-"bad" outcome), and negative when choice and outcome are incongruent (accept-"bad" outcome; reject-"good" outcome).

We next asked whether the multivariate pattern of this prediction error signal depends on the relational structure on a fine-grained scale, in a multivariate analysis. We conducted a searchlight RSA analysis similar to the one from the previous section, with two notable differences: A) the patterns used as inputs to the RSA were not the average responses to the stimuli, but instead the regression coefficients of the prediction errors on the two related stimuli (A and B) in each block. This means the patterns entering this analysis are the local spatial variations in the representation of prediction errors. B) These analyses only have a single measure per block (prediction error coefficients) as opposed to two (separate stimuli) in the previous section (GLM3). The resulting RDMs are therefore 4x4, not 8x8.

Because we are testing the multivariate differences on the (orthogonal) univariate prediction error effect, we could use the peaks of the univariate effect to constrain our regions of interest. The top two univariate peaks were in vmPFC (peak MNI [-4,44,20]) and ventral striatum (vStr, peak MNI [-10,8,-12]. In searchlights centred on both these peaks, the multivariate prediction error X structure interaction effect was significant (vmPFC P=0.014, Fig. 3a and 3b; vStr P=0.034, Fig. 3c). We also note that other regions where grid-like coding was previously observed, such as the posterior cingulate cortex (PCC) [19,20] showed this interaction effect, as well as other reward-related regions like the ventrolateral PFC [23]. See Fig. S3 for a description of these exploratory results.

These results indicate that prediction error signals in vmPFC and vStr (and perhaps vlPFC and PCC) depend on the current relational structure of the task. The critical difference between the two relational structures in our experiment is not how the prediction error should be computed, but rather how it should be used to inform future behaviour – how should 'credit' for the error be assigned [2,4,29–32] One intriguing possibility is therefore that different representations of prediction errors allow different credit assignment for the same prediction errors in the two relational structures. Factorising these computations from the sensory particularities of the task allows them to be rapidly 'remapped' to new stimuli for rapid learning.

Figure 3. Prediction error signals in vmPFC and ventral striatum depend on the current relational structure of the task. a. Visualisation of whole-surface results of the multivariate prediction error X structure interaction effect, medial left hemisphere. b. Interaction effect at the vmPFC peak univariate prediction error effect (MNI: [-4,42,-20]). c. Interaction effect at the ventral striatum peak univariate prediction error effect (MNI: [-10,8,-12]). Insets in b. and c. show the univariate prediction error effect. Legend for panels b. and c. is the same as in Figure 2c.

OFC representation of task space respects relational structure.

The precise computations that mediate model-contingent credit assignment depend on the brain's internal representation of the task state-space [2–4,32,33]. In many laboratory tasks, including ours, more than one task representation is possible [2,33]. However, to benefit from the relational knowledge, any such representation must differentiate the related stimuli (A,B) from the control stimulus (C) so that AB outcomes can cause learning on both A and B but not C. For example, one possible representation is to maintain a single variable encoding the state of the AB pair [2] and a second variable encoding the state of C.

We therefore tested for regions where the representation of AB trials were more similar than AC or BC, again by constructing RDMs. To increase statistical power, we consider representational similarity at stimulus time (S-S), at outcome time (O-O) and between stimulus and outcome (S-O). It is particularly interesting for credit assignment if representations generalise from outcome time to the time when the stimulus was presented. Note that unlike previous analyses, these RDMs are defined within blocks, not between blocks, made possible as ABC trials are presented in pseudo-random order. Hence, within each block, we used correlation distances to calculate three 3x3 data RDMs (S-S, O-O, S-O), where the three conditions in each RDM correspond to the three stimuli. We then averaged the RDMs across all 8 blocks, and defined contrasts between unrelated (AC, BC) and related (AB) pairs of stimuli. Finally, we averaged the three contrasts to obtain a single measure of the latent AB variable representation, and submitted it to permutation tests as described above.

The strongest effects in cortex (Fig. 4a) were observed in the medial OFC (Brodmann areas (BA) 11,13,14 P=< 0.0002 uncorrected, P = 0.039 FWE cluster-corrected in frontal-temporal mask) and the right posterior parahippocampal (pPHC) gyrus (P=0.0005 uncorrected, P=0.0445 FWE cluster corrected for whole surface). All three experimental periods RDMs

(S-S, O-O, S-O) contributed to the effect (Fig. 4b). See methods for description and discussion of statistical correction.

Intriguingly, the periods-averaged latent variable effect at its spatial peak (mOFC) correlated on a subject-by-subject level with the vmPFC prediction error X structure interaction effect at its peak (Fig. S4, r=0.5, P=0.01, mOFC MNI [-6,30,-26]), vmPFC MNI [-8,46,-16]). Though causal directionality cannot be inferred from this correlation, it is possible that subjects with a vmPFC representation that structurally differentiates credit assignment for errors can utilise it to create a stronger latent variable representation in mOFC.

Figure 4. OFC represents a latent variable, respecting the task structure. a. Right: Whole-surface results (top/bottom: orbital/medial views) for the [unrelated stimuli – related stimuli] contrast, averaged over all experimental periods (S-S, O-O, S–O). The semi-transparent uncorrected p-value map is overlaid over the two clusters that survived FWE correction, shown in green. Left: Visualisation of the effect from the peak of the OFC cluster, located in the left medial OFC (BA14). **b.** Same as **a. (left),** separated to the different experimental periods (S–S, O-O, S-O). Legends are the same as in **Figure 2c**.

Discussion

Understanding how the brain represents abstract task state-spaces remains a major challenge. Our data joins growing evidence suggesting state-space representations rely on the hippocampal formation [5,9,34–36] and interconnected regions in the ventral PFC [2,3,36,37]. This is particularly interesting in light of the historical role of these regions in generalisation and relational reasoning [38–42], which are essential for efficient task representations. Here, we show that these regions, and in particular the same areas where evidence of grid cells was found, generalise the relational structure of a non-spatial RL task. EC representations of stimuli generalised over tasks with the same structure, but not over tasks with a different structure.

The same was true for vmPFC (and vStr) representations of prediction error. These results suggest a common framework for the representation and generalisation of task structures in a wide variety of domains. In addition, we found that OFC and posterior PHC gyrus representations were consistent with the coding of a behaviourally-relevant latent variable, respecting the task structure [2,3].

Our experiment can be viewed as a set of non-spatial "remapping" experiments. The horizontal arms in Fig. 1c (same task structure, different stimuli) are analogous to the classic spatial sensory remapping experiments in rodents [13,15], where an animal is moved between different sensory examples of the same task structure (namely free foraging in a Euclidian 2D space). In these experiments, entorhinal grid cells maintain (generalise) their covariance structure across environments (i.e. they do not remap, in contrast to hippocampal place cells [43]). Such generalisation was also observed in Macaque OFC neurons, across different sensory examples of an economic decision-making task [44]. The vertical arms in Fig. 1c (same stimuli, different task structure) can be viewed as "task remapping" experiments. In the spatial case of such experiments, where animals are required to perform different tasks in the same sensory environment, recent evidence suggests the grid code changes (remaps) across tasks [45,46]. Our EC effect (Fig. 2) mirrors these results in a non-spatial RL task in humans. Future work might address whether the exact same neuronal population underlies generalisation in both spatial and non-spatial tasks.

A unified framework for the representation of task structure might also afford a new way to interpret standard RL neural signals like prediction error. Our vmPFC prediction error X structure interaction effect (Fig. 3) brings together observations about vmPFC function from several seemingly disparate fields, including RL [23]. In the memory literature, vmPFC has been strongly implicated in the representation of schemas – abstract structures of previous knowledge, which bear many parallels to the relational structures discussed here [47,48]. vmPFC is particularly important when new information is assimilated into an existing schema [49,50], analogous to a prediction error update of the internal model of the task within the current structure. Finally, some of the strongest effects of spatial and nonspatial grid-like coding in fMRI were recorded in the medial PFC [19–21]. Notably PCC, where we found the strongest prediction error X structure interaction effect in our exploratory analysis, also exhibits grid-like coding [19,20] and has also been strongly implicated in the representations of schemas [48,49]. Finally, we show a relationship between the vmPFC structural learning signal and the representation of a behaviourally relevant latent variable in OFC [2–4,32]. Both of these representations are useful for facilitating appropriate model-contingent credit assignment [29–31].

Learning can be dramatically improved by a useful representation of the world you are learning about. Here, we show that the brain can "recycle" (generalise) these representations, enabling fast and flexible inferences. We believe the comparison of generalisable representations in our abstract RL task to their parallels in spatial cognition is a useful one, and can suggest a path for a more precise understanding of the nature of these representations.

References

1. Sutton, R. S. & Barto, A. G. *REINFORCEMENT LEARNING : an introduction.* (MIT Press, 1998).
2. Wilson, R. C., Takahashi, Y. K., Schoenbaum, G. & Niv, Y. Orbitofrontal cortex as a cognitive map of task space. *Neuron* **81**, 267–278 (2014).
3. Schuck, N. W., Cai, M. B., Wilson, R. C. & Niv, Y. Human Orbitofrontal Cortex Represents a Cognitive Map of State Space. *Neuron* **91**, 1402–1412 (2016).
4. Gershman, S. J. & Niv, Y. Learning latent structure: Carving nature at its joints. *Current Opinion in Neurobiology* **20**, 251–256 (2010).
5. Stachenfeld, K. L., Botvinick, M. M. & Gershman, S. J. The hippocampus as a predictive map. *Nat. Neurosci.* **20**, 1643–1653 (2017).
6. Wang, J. X. *et al.* Prefrontal cortex as a meta-reinforcement learning system. *Nat. Neurosci.* **21**, 860–868 (2018).
7. Behrens, T. E. J. *et al.* What Is a Cognitive Map? Organizing Knowledge for Flexible Behavior. *Neuron* **100**, 490–509 (2018).
8. Whittington, J. C. R. *et al.* The Tolman-Eichenbaum Machine: Unifying space and relational memory through generalisation in the hippocampal formation. *bioRxiv* 770495 (2019). doi:10.1101/770495
9. Garvert, M. M., Dolan, R. J. & Behrens, T. E. J. A map of abstract relational knowledge in the human hippocampal–entorhinal cortex. *Elife* **6**, 1–20 (2017).
10. Dordek, Y., Soudry, D., Meir, R. & Derdikman, D. Extracting grid cell characteristics from place cell inputs using non-negative principal component analysis. *Elife* **5**, 1–36 (2016).
11. Mathis, A., Stemmler, M. B. & Herz, A. V. M. Probable nature of higher-dimensional symmetries underlying mammalian grid-cell activity patterns. *Elife* **2015**, 1–29 (2015).
12. Banino, A. *et al.* Vector-based navigation using grid-like representations in artificial agents. *Nature* **557**, 429–433 (2018).
13. Fyhn, M., Hafting, T., Treves, A., Moser, M.-B. & Moser, E. I. Hippocampal remapping and grid realignment in entorhinal cortex. *Nature* **446**, 190–194 (2007).
14. Yoon, K. *et al.* Specific evidence of low-dimensional continuous attractor dynamics in grid cells. *Nat. Neurosci.* **16**, 1077–1084 (2013).
15. Barry, C., Ginzberg, L. L., O'Keefe, J. & Burgess, N. Grid cell firing patterns signal environmental novelty by expansion. *Proc. Natl. Acad. Sci.* **109**, 17687–17692 (2012).
16. Bush, D., Barry, C., Manson, D. & Burgess, N. Using Grid Cells for Navigation. *Neuron* **87**, 507–520 (2015).
17. Tolman, E. C. Cognitive maps in rats and men. *Psychol. Rev.* **55**, 189–208 (1948).
18. Harlow, H. F. The formation of learning sets. *Psychol. Rev.* (1949). doi:10.1037/h0062474
19. Doeller, C. F., Barry, C. & Burgess, N. Evidence for grid cells in a human memory network. *Nature* **463**, 657–661 (2010).
20. Constantinescu, A. O., OReilly, J. X. & Behrens, T. E. J. Organizing conceptual knowledge in humans with a gridlike code. *Science (80-.).* **352**, 1464–1468 (2016).
21. Jacobs, J. *et al.* Direct recordings of grid-like neuronal activity in human spatial navigation. *Nat. Neurosci.* **16**, 1188–1190 (2013).
22. Bao, X. *et al.* Grid-like Neural Representations Support Olfactory Navigation of a Two-Dimensional Odor Space. *Neuron* **102**, 1066-1075.e5 (2019).
23. Rushworth, M. F. S., Noonan, M. P., Boorman, E. D., Walton, M. E. & Behrens, T. E. Frontal Cortex and Reward-Guided Learning and Decision-Making. *Neuron* **70**, 1054–

1069 (2011).

24. Hampton, A. N., Bossaerts, P. & O'Doherty, J. P. The Role of the Ventromedial Prefrontal Cortex in Abstract State-Based Inference during Decision Making in Humans. *J. Neurosci.* **26**, 8360–8367 (2006).

25. Knutson, B., Taylor, J., Kaufman, M., Peterson, R. & Glover, G. Distributed neural representation of expected value. *J. Neurosci.* **25**, 4806–4812 (2005).

26. Ramnani, N., Elliott, R., Athwal, B. S. & Passingham, R. E. Prediction error for free monetary reward in the human prefrontal cortex. *Neuroimage* **23**, 777–786 (2004).

27. Wimmer, G. E., Daw, N. D. & Shohamy, D. Generalization of value in reinforcement learning by humans. *Eur. J. Neurosci.* **35**, 1092–1104 (2012).

28. Kriegeskorte, N., Mur, M. & Bandettini, P. A. Representational similarity analysis - connecting the branches of systems neuroscience. *Front. Syst. Neurosci.* **2**, 4 (2008).

29. Walton, M. E., Behrens, T. E. J., Buckley, M. J., Rudebeck, P. H. & Rushworth, M. F. S. Separable Learning Systems in the Macaque Brain and the Role of Orbitofrontal Cortex in Contingent Learning. *Neuron* **65**, 927–939 (2010).

30. Rudebeck, P. H., Saunders, R. C., Lundgren, D. A. & Murray, E. A. Specialized Representations of Value in the Orbital and Ventrolateral Prefrontal Cortex: Desirability versus Availability of Outcomes. *Neuron* **95**, 1208-1220.e5 (2017).

31. Jocham, G. *et al.* Reward-Guided Learning with and without Causal Attribution. *Neuron* **90**, 177–190 (2016).

32. Gershman, S. J., Norman, K. A. & Niv, Y. Discovering latent causes in reinforcement learning. *Curr. Opin. Behav. Sci.* **5**, 43–50 (2015).

33. Niv, Y. Learning task-state representations. *Nat. Neurosci.* **22**, 1544–1553 (2019).

34. Miller, K. J., Botvinick, M. M. & Brody, C. D. Dorsal hippocampus contributes to model-based planning. *Nat. Neurosci.* **20**, (2017).

35. Vikbladh, O. M. *et al.* Hippocampal Contributions to Model-Based Planning and Spatial Memory. *Neuron* **102**, 683-693.e4 (2019).

36. Zhou, J. *et al.* Complementary Task Structure Representations in Hippocampus and Orbitofrontal Cortex during an Odor Sequence Task. *Curr. Biol.* (2019). doi:10.1016/J.CUB.2019.08.040

37. Zhou, J. *et al.* Rat orbitofrontal ensemble activity contains a multiplexed but value-invariant representation of task structure in an odor sequence task (supplemental information). *Curr. Biol.* 507376 (2019). doi:10.1101/507376

38. Cohen, N. J. & Eichenbaum, H. *Memory, Amnesia, and the Hippocampal System.* (Cambridge: MIT Press, 1993).

39. Morrissey, M. D., Insel, N. & Takehara-nishiuchi, K. Generalizable knowledge outweighs incidental details in prefrontal ensemble code over time. *Elife* **6**, 1–20 (2017).

40. Preston, A. R. & Eichenbaum, H. Interplay of Hippocampus and Prefrontal Cortex in Memory. *Curr. Biol.* **23**, R764–R773 (2013).

41. Zeithamova, D. & Preston, A. R. Flexible Memories: Differential Roles for Medial Temporal Lobe and Prefrontal Cortex in Cross-Episode Binding. *J. Neurosci.* **30**, 14676–14684 (2010).

42. Bowman, C. R. & Zeithamova, D. Abstract memory representations in the ventromedial prefrontal cortex and hippocampus support concept generalization. *J. Neurosci.* **38**, 2811–17 (2018).

43. Bostock, E., Muller, R. U. & Kubie, J. L. Experience-dependent modifications of hippocampal place cell firing. *Hippocampus* **1**, 193–205 (1991).

44. Xie, J. & Padoa-Schioppa, C. Neuronal remapping and circuit persistence in economic decisions. *Nat. Neurosci.* **19**, 855–861 (2016).

45.   Boccara, C. N. *et al.* The entorhinal cognitive map is attracted to goals. *Science (80-.).* **363**, 1443–1447 (2019).

46.   Butler, W. N., Hardcastle, K. & Giocomo, L. M. Remembered reward locations restructure entorhinal spatial maps. *Science (80-.).* **363**, 1447–1452 (2019).

47.   Gilboa, A. & Marlatte, H. Neurobiology of Schemas and Schema-Mediated Memory. *Trends Cogn. Sci.* **21**, 618–631 (2017).

48.   Baldassano, C., Hasson, U. & Norman, K. A. Representation of Real-World Event Schemas during Narrative Perception. *J. Neurosci.* **38**, 9689–9699 (2018).

49.   Sommer, T. The Emergence of Knowledge and How it Supports the Memory for Novel Related Information. *Cereb. cortex* **27**, 1906–1921 (2017).

50.   Tse, D. *et al.* Schema-Dependent Gene Activation and Memory Encoding in Neocortex. *Science (80-.).* **333**, 891–895 (2011).

Methods

subjects

We trained 49 volunteers over 4 days on an online version of the task. 17 Subjects did not proceed to be scanned as they either did not comply with task demands (e.g. failed to complete training on time) or did not reach a behavioural criteria for knowledge of the outcome probabilities correlation structure (a difference of more than 0.3 between the fitted cross-term of the related stimuli and the mean of the fitted cross-terms of the unrelated stimuli, see below). 32 volunteers (aged 21-32 years, mean age 23.4, 18 females) with normal or corrected-to-normal vision and no history of neurological or psychiatric disorders participated in the fMRI experiment. 4 subjects were excluded from the analyses: 3 due to technical difficulties during the scanning, and one due to excessive motion. Hence, all analyses presented are based on data from 28 subjects. All subjects gave written informed consent and the study was approved by the University of Oxford ethics committee (reference: R51215/RE001).

Training and task

Subjects trained online for 4 days prior to the scan day, and were scanned on day 5. In each training session, subjects performed a task where three 1-armed bandits were interleaved pseudo-randomly. The bandits were cued by three different visual stimuli, randomly sampled without replacement for each session from a bank of 35 images. Two of the bandits (bandits A & B) had correlated outcome probabilities, while the third (C) was independent. There were two possible correlation structures for the outcome probabilities of bandits A & B: positive correlation (+Corr blocks) or negative correlation (-Corr blocks). Each training session comprised of 8 blocks with 60 trials each (3 stimuli X 20 trials per stimulus).

In each trial, subjects viewed one of the three stimuli and had to indicate their prediction for its associated binary outcome (a "good" or a "bad" outcome, demarked by a King of Hearts or Two of Spades card, respectively) by either accepting or rejecting the stimulus. Thus, there was always one correct answer in each trial: subjects should accept a stimulus if they predict the outcome to be the "good" outcome, and should reject if they predict the outcome to be the "bad" outcome (Fig 1a). Only in accepted trials, the subject would either win or lose a point, depending on the outcome (i.e. accepting incorrectly resulted in a loss of a point). Outcome identity was revealed in all trials, including rejection trails (except on training days 3 and 4, see below), even though the subject's score did not change in these trials (Fig 1a). Predictions of the outcomes could be formed based on the recent history of outcomes. The outcome probabilities switched pseudo-randomly between 0.9 and 0.1 with an average switch probability of 0.05 in each trial of the training sessions. As the two correlated bandits switched together, subjects could use their knowledge of the correlation structure to learn from the outcome on stimulus A about stimulus B and vice versa (Fig 1b). Subjects were informed and reminded at the beginning of each training block that two of the bandits had correlated outcome probabilities, and that this correlation might be positive or negative. However, subjects had to infer which two bandits were correlated and what was the sign of the correlation.

On day 1 subjects completed two sessions with a different triplet of stimuli used as the ABC cues in each session. In both sessions, two of the stimuli had a particular correlation structure, counterbalanced across subjects. That is, half of the subjects performed two sessions of 8 -Corr blocks each, while the other half performed two sessions of 8 +Corr blocks. Day 2 was identical to day 1, except that the two stimuli sets used were novel and the correlation

structure was the one that the subject did not experienced on day 1. On day 3 subjects again completed 2 sessions with a novel stimuli set per session, where the correlation structure between two of the stimuli alternated between blocks. The correlation structure was indexed by the background colour of stimuli (e.g. Fig 1b and 1c), and subjects were informed that the combination of stimuli set, background colour and correlation structure in day 3 will be the same in days 4 and 5, including in the scanning task. Thus, subjects could already learn the background colour-correlation structure mapping prior to entering the scanner. On day 4 subjects completed one session with all the 4 possible block types (2 stimuli sets x 2 correlation structures, e.g. Fig 1b and 1c). To reduce available information and facilitate subjects' need to use the extra information afforded by the correlation structure, no counterfactual feedback was given on rejection trials in any of the last 15 trials of a block in training days 3 and 4.

Prior to scanning on day 5, subjects completed a pre-scanning reminder session with all 4 block types, again with the same stimuli set - background colour - correlation structure combinations as in days 3 and 4. In both the pre-scanning session and during scanning, full outcome feedback was given, including in all rejection trials. During scanning, subjects completed 8 blocks of 30 trials each (10 trials per stimulus), with a break after 4 blocks for structural and field-maps scans. The two groups of 4 blocks (before and after the structural scan) included one of each of the 4 experimental block types in a pseudo-random order, counterbalanced across subjects. Outcome probabilities switched faster in the scanner than during training due to the shorter blocks, with a switch probability of 0.15.

Before the first trial of each block, all three stimuli and the background colour of that block were presented. A trial was on average 11.5 seconds long, progressing in the following order (Fig S1a): 1) A stimulus would appear in the middle of the screen, together with the available choices: left for accept (corresponding to an index finger button press) and right to reject (middle finger button press). 2) After 1.5 seconds, the frame of the stimulus and the accept/reject text turned white, indicating that choice can now be made. Subjects who indicated their choice prior to the appearance of the white frame lost half a point. 3) Subjects indicated their choice by pressing either the index or middle finger buttons. Next, a red rectangle appeared around the chosen option for 0.5 seconds. 4) A white fixation cross appeared for a variable period, drawn from an exponential distribution with a mean of 4.5 seconds and truncated between 3.5-5.5 seconds. The purpose of this long delay between choice and outcome was to enable the independent analysis of both periods, due to the sluggish nature of the hemodynamic response function. 5) The outcome of the trial appeared for 1 second in the middle of the screen - either the "good" outcome (King of Hearts card) or the "bad" outcome (Two of Spades card). If the subject has accepted the trial earlier, they will either win or lose a point: if they accepted correctly (outcome was "good"), a "sack of gold" image would appear in the left side of the screen to indicate that a point was gained; if they accepted incorrectly (outcome was "bad"), a "no sack of gold" image would appear to indicate that a point was lost. If the subject rejected the trial, no points would be won or lost (and hence no "sack of gold" or "no sack of gold" image would appear), but the outcome card image would still appear (Fig 1a). Hence subjects received full counterfactual feedback. Note that subjects should reject trials if they predict the outcome to be the "bad" outcome, as they will lose a point for incorrectly accepting a trial. 6) A white fixation cross appeared for a variable inter trial interval, drawn from an exponential distribution with a mean of 3 seconds and truncated between 2.5-4 seconds.

Behaviour modelling

We modelled the behaviour of the subjects using an adapted delta-rule model [1]. The original delta-rule model estimates the outcome probabilities for a given stimulus using the following equation:

$\hat{g}^S{}_{t+1} = \hat{g}^S{}_t + \alpha \epsilon^S{}_t$; $\epsilon^S{}_t = y_t - \hat{g}^S{}_t$, where $S \in \{A, B, C\}$; $\{A, B, C\}$ are the three stimuli presented in a block, $\hat{g}^S{}_t$ is the "good" outcome probability estimation for stimulus S before trial t, α is the learning rate, ϵ is the outcome prediction error, and y_t is the outcome at trial t: $y_t = 1$ for the "good" outcome and $y_t = -1$ for the "bad" outcome. Note that the model is estimating the stimulus value, based on the outcome identity (not the reward actually obtained by the subject), and is agnostic to the choice the subject made. The stimulus value should be distinguished from the "chosen action value" used in GLM1 (see below), which has the same magnitude as the stimulus value, but has an opposite sign on rejection trials: in a trial where the subject's hypothetical estimate of the stimulus value is very low (close to -1), they will be confident in rejecting the trial, making the value of the chosen "reject" action high (close to $+1$). Similarly, ϵ should not to be confused with the "correctness" prediction error used in GLM3 and Fig 3, which has the same magnitude as ϵ but with a sign determined by the congruence between the subject's choice and the outcome. The stimulus value estimation can then be used by a "selector model" to make a choice in the next trial, by using a simple sigmoidal function: $P(choice\ on\ stimulus\ S\ on\ trial\ t + 1 = accept) = (1 + e^{-\beta(\hat{g}^S{}_t)})^{-1}$, where β is the inverse temperature, controlling the randomness of the choice. In this model, α and β are free parameters fit to subjects' behaviour.

However, this model does not use any knowledge about the correlations between the outcome probabilities of different stimuli. To allow for this, we added three free parameters to the model, which we refer to as cross-terms. These parameters determine how information on one stimulus affects the outcome estimate on another stimulus.
Following an outcome on stimulus A, we update the outcome estimates of all three stimuli:

$$\hat{g}^A{}_{t+1} = (1 - \alpha)\hat{g}^A{}_t + \alpha y_t$$
$$\hat{g}^B{}_{t+1} = (1 - \alpha|H_{AB}|)\hat{g}^B{}_t + \alpha H_{AB} y_t$$
$$\hat{g}^C{}_{t+1} = (1 - \alpha|H_{AC}|)\hat{g}^C{}_t + \alpha H_{AC} y_t$$

Where $-1 \leq H_{XY} \leq 1$ is the cross-term for stimuli X and Y. Note that the first equation (update of the estimate for stimulus A following an outcome on stimulus A) is identical to the update in the original delta-rule model. $H_{XY} = 1$ means stimuli X and Y are treated as the same: the outcome estimates for both stimuli will be updated in exactly the same way following feedback on one of them. $H_{XY} = -1$ means stimuli X and Y are treated as having opposite (anti-correlated) outcome probabilities. $H_{XY} = 0$ means the two outcome probabilities are treated as uncorrelated: the outcome estimates for stimulus X will not change following feedback on stimulus Y, and vice versa. Analogous updates occur when feedback is given on stimuli B or C.

The 5 free parameters of the model were fit to the behaviour of each subject, separately for each of the 4 block types. Due to the small number of trials of a particular stimulus in a particular block type, we pooled each subject's data from the scanning session, the pre-scanning session and the last online session (training day 4, after subjects have already learned the mapping between stimuli set, background colour and correlation structure), and fit the parameters separately for +Corr and -Corr blocks. This resulted in a total of 150 trials for each of the 4 block types. The outcome estimates for all stimuli was reset to 0 at the beginning of each block. We fit the parameters by maximising the negative log likelihood of

the data with respect to the parameters using the Matlab function *fmincon()*. The learning rate was constrained to be between 0 and 1, the cross-terms between -1 and 1, and the inverse temperature between 0 and 8. Finally, we tested whether subjects indeed used the relational structure correctly by averaging the cross-terms from the same relational structure within-subject (+Corr or -Corr, Fig 1e) and performing a paired t-test between the AB cross-term and the mean of AC and BC cross-terms.

fMRI data acquisition and preprocessing
Data were acquired on a 3T Siemens Prisma scanner, using a 32-channel head coil. Functional scans were collected using a T2*-weighted echo-planar imaging (EPI) sequence with a multi-band acceleration factor of 3, within-plane acceleration factor (iPAT) of 2, TR = 1.235 s, TE = 20 ms, flip angle = 65 degrees, voxel resolution of 2x2x2 mm and a tilt of 30 degrees relative to axial axis. A field map with dual echo-time images (TE1 = 4.92ms, TE2 = 7.38ms, whole-brain coverage, voxel size 3x3x3 mm) was acquired to correct for geometric distortions. Structural scans were acquired using a T1-weighted MP-RAGE sequence with 1x1x1 mm voxels. Preprocessing was performed using tools from the fMRI Expert Analysis Tool (FEAT), part of FMRIB's Software Library (FSL [2]). Data for each of the 8 blocks were preprocessed separately. Each block was aligned to the first, presaturated image using the motion-correction tool MCFLIRT [3]. Brain extraction was preformed using automated brain extraction tool BET [4]. All data were high-pass temporally filtered with a cutt-off of 100 seconds. Registration of EPI images to high-resolution structural images and to standard (MNI) space was performed using FMRIB's Linear and Non-Linear Registration Tool (FLIRT and FNIRT [3,5]), respectively. The registration transformations were then used to move each blocks' EPI data to the native structural space, downsampled to 2x2x2 resolution. No spatial smoothing was performed during preprocessing (see below for different smoothing protocols for univariate and multivariate analyses).

Univariate analyses
Due to incompatibility of FSL with the MATLAB RSA toolbox [6] used in subsequent analyses, we estimated all first-level GLMs and univariate group-level analyses using SPM12 (Wellcome Trust Centre for Neuroimaging, http://www.fil.ion.ucl.ac.uk/spm).
For univariate analyses, contrasts of parameter estimates were first smoothed with a kernel of 5mm FWHM.

In the following descriptions, [A, B, C] refer to the three stimuli presented in a particular block, where the outcome probabilities associated with A & B was correlated (either positively or negatively, depending on the block).

To test whether known RL signals in the reward network were consistent with a model that used the relational structure, we constructed a GLM where chosen action value estimates from both STRUCT and NAÏVE models were pitted against each other (Fig 1e and S1c). GLM1 included the following regressors per each block: two main effect regressors of all related stimuli trials ([AB]): one modelling the times of stimulus presentation and modelling outcome times. Two parametric regressors were locked to stimulus presentation times of [AB]: the value of the chosen option from the STRUCT and the NAÏVE models. In addition, the GLM included several other regressors: C trials at stimulus presentation; C trials at outcome; 2 regressors modelling button presses across all stimuli: one modelling all "accept" trials and one modelling all "reject" trials; 6 motion parameters as nuisance regressors; bias term modelling the mean activity in each block. Fig 1e shows the results of the contrast

[STRUCT chosen option value] > [baseline]. Fig S1c shows the results of the contrast [STRUCT chosen option value] > [NAIVE chosen option value]

See below for a description of the univariate STRUCT model prediction error analysis, the results of which are shown in the insets of Fig 3b and 3c.

RSA analyses
In this section, we will first outline the steps common to all RSA [7] analyses, and then describe details which were specific to each analysis. All RSA analyses were conducted as follows: 1) A searchlight [8] was constructed around each cortical voxel, including the 100 cortical voxels with the smallest surface-wise geodesic distance from the central voxel. This was performed using adapted scripts from the RSA toolbox (Nili et al., 2014 original surface-based searchlight scripts written by Joern Diedrichsen & Naveed Ejaz, code available at https://github.com/rsagroup/rsatoolbox) . The searchlight definition depends on cortical reconstruction and alignment performed via Freesurfer's *recon-all* command [9–15]. 2) For each searchlight, first-level univariate GLMs on unsmoothed data were conducted using the RSA toolbox, based on SPM12. Regression coefficients were then spatially pre-whitened within the searchlight using the RSA toolbox. 3) A distance metric was defined to summarise the representational geometry between conditions. The metrics used were either the cross-run correlation distance or a within-block correlation distance (See below). This resulted in data RDMs of size [number of conditions] x [number of conditions]. 4) A hypothesis about the representational geometry was formalised as a contrast between the mean of RDM elements that should "dissimilar" to each other and the mean of RDM elements that should be "similar" to each other. This contrast was calculated in each searchlight, resulting in a single contrast map per subject. 5) The contrast maps of the different subjects were aligned on the common cortical surface using Freesurfer-based scripts adapted from the RSA toolbox. 6) Group-level statistical significance of the contrast (equivalent to a one-sided t-test) and family-wise error (FWE) correction were performed using permutation tests [16] using PALM [17]. In this procedure, the contrast values from each subject were randomly multiplied by either 1 or -1, following the null hypothesis that the contrasts are symmetric around 0. The test's statistic was then defined as the cross-subject average of contrast values. This was repeated 10000 times, creating a null distribution of the means. The true value of this mean was then compared to this null distribution. The resulting (uncorrected) p-value map is displayed in figures 2d, 3a and 4a as a heat map, at a threshold of $P<0.01$. See below for a separate section discussing FWE correction. The paired mean difference across subjects between the two groups of RDM elements at particular vertices of interest is visualised in the Gardner-Altman estimation plots in figures 2c, 3b, 3c, 4a and 4b. The figures were generated using an adaptation of the openly available Matlab package DABEST [18]. We make an important distinction between estimation plots containing data from peaks of FWE-surviving clusters, which are subject to selection bias (and are shown for visualisation purposes only; figures 2c, 4a and 4b), and estimation plots with data from unbiased ROIs, which are not subject to selection bias (figures 3b and 3c. In these ROIs an uncorrected statistical test can be performed.

To search for a representation of the relational structure between stimuli in the task (Figs 2 & S2), we conducted a GLM (GLM2) which included the following regressors per each block: 3 main effect regressors ([A],[B],[C]) modelling the times of stimulus presentation; 3 main effect regressors ([A], [B], [C]) modelling the times of outcome presentation; 2 regressors modelling button presses across all stimuli: one modelling all "accept" trials and one modelling all "reject" trials; 6 motion parameters as nuisance regressors; bias term modelling

the mean activity in each block. Only the 2 regressors modelling the presentation of the two related stimuli (A&B) in each block were used in the "relational structure representation" analysis (as stimulus C was not part of a relational structure, Fig 2 top and Fig S2), while all stimulus presentation regressors (A, B & C) were used in the "visual stimulus identity representation" analysis (Fig 2, bottom). Each condition (a particular stimulus under a particular structure) had two patterns (100-long vectors of spatially pre-whitened regression coefficients) – one from each independent run. We defined the cross-run correlation distance between each pair of conditions by averaging the following quantities: [correlation distance between condition i pattern from run 1 and condition j pattern from run 2] and [correlation distance between condition i pattern from run 2 and condition j pattern from run 1]. This resulted in [number of conditions] x [number of conditions] data RDM for each searchlight (8x8 for the "relational structure representation" analysis; 12x12 for the "visual stimulus identity representation" analysis). We then defined a hypothesis-driven contrast between RDM elements: In the main "relational structure representation" analysis, "different structure" elements should be more dissimilar to each than "same structure" elements. For the control analyses in Fig S2, we ignored elements of the same visual stimulus (Fig S2a) or the same stimuli set (Fig S2b). In the "visual stimulus identity representation" analysis, "different visual stimulus" elements should be more dissimilar than "same visual stimulus" elements. Using the maximum cluster mass statistic [16] for multiple comparisons correction, we report clusters that survived FWE correction at a cluster-forming threshold of P<0.001 within a cortical hemisphere (green clusters in figures 2 and S2).

To test whether standard prediction error signals depended on the relational structure (prediction error X structure interaction analysis, Figs 3 and S3), we first wanted to replicate the previously described ventral striatum (vStr) and vmPFC univariate prediction error signals [19–22]. We conducted a GLM (GLM3) which included the following regressors per each block: 2 main effect regressors ([AB],[C]) modelling outcome times; one parametric regressor of the "correctness" prediction error from the STRUCT model, locked to the time of [AB] outcome presentation; 2 main effect regressors ([AB],[C]) modelling stimulus presentation times; 2 regressors modelling button presses across all stimuli: one modelling all "accept" trials and one modelling all "reject" trials; 6 motion parameters as nuisance regressors; bias term modelling the mean activity in each block. For each subject, we calculated the contrast [STRUCT AB "correctness" prediction error] > [baseline], smoothed the contrast image using a 5mm FWHM kernel, and obtained group-level results using SPM Fig 3b and 3c, insets). As expected, the two strongest peaks were in vStr and vmPFC. We then used these peaks as (unbiased) ROIs for the multivariate prediction error X structure interaction analysis. To this end, in addition to the surface-based cortical searchlight procedure described above, we also defined 100 voxels long volumetric searchlights within an anatomical mask of the vStr (Harvard-Oxford Subcortical Structure Atlas). Unlike the surface-based searchlight, the analyses for the volumetric searchlight were all performed in MNI152 space. Only the regressor modelling the [AB] "correctness" prediction error in each block was used in the RSA analyses for Figs 3 & S3, resulting in 8 patterns – one pattern per block. We again used the cross-run correlation distance to collapse patterns of the same conditions (a particular stimuli set under a particular structure) across runs, this time to construct 4x4 data RDMs – one condition per block type. Again, we defined a hypothesis-driven contrast between RDM elements, where "different structure" elements should be more dissimilar to each than "same structure" elements. We report the (uncorrected) p-values obtained by permutation tests in the searchlights centred on the vStr and vmPFC peaks of the univariate prediction error effect (Fig 3). We also present the exploratory, uncorrected results

across cortex of this effect (Fig S3).

To test for a representation of the latent AB variable (Fig 4), we once again used the regression coefficients from GLM2. This time, however, we used the regression coefficients from all three stimuli in each block at both stimulus presentation (S) and outcome presentation (O) times. This was enabled by the long (mean ~4.5 seconds, jittered) S-O delay period. As we were testing for a within-block effect, here we used a different distance metric: a simple correlation distance, calculated within each block. Thus, we obtained three 3x3 data RDMs per block, one for each pair of experimental periods (S-S, O-O, S-O), where the 3 conditions in each RDM correspond to the 3 stimuli presented in the block. Note that each element in the S-O RDM is an average of two correlations, e.g. $d_{A,B} = 1 - mean(corr(A_O, B_S), corr(A_S, B_O))$. We then averaged the RDMs across all blocks (collapsing over blocks of different relational structures). To obtain a single measure of the latent variable representation and to increase statistical power, we averaged the S-S, O-O and S-O RDMs. Next, we defined a hypothesis-driven contrast between RDM elements: unrelated (AC, BC) elements should be more dissimilar to each other than related (AB) elements. We once again used permutation tests for statistical testing and FWE correction (see below for more details).

Lastly, we tested whether the vmPFC prediction error X structure interaction effect correlated on a subject-by-subject level with the mOFC latent variable representation effect, by extracting the contrasts of different subjects at the peaks of both effects and correlating across subjects.

Multiple comparisons correction
Multiple comparisons correction was performed using the permutation tests machinery (Nichols & Holmes 2002) in PALM [17]: we first thresholded the (uncorrected) P-map at either P<0.001 (fig 2) or P<0.01 (fig 4), and measured the mass of all surviving clusters. We then repeated this procedure for each of the 10000 random sign-flip iterations described above, and created a null distribution of cluster masses by saving only the mass of the largest cluster in each iteration. Comparing the true cluster masses to the resulting null distributions results in a FWE-corrected P-values.

Whilst the effects in the latent variable representation analysis (fig 4) do not survive multiple comparisons correction with the same parameters as the entorhinal effect in fig 2, they do survive with a lower cluster forming threshold of P<0.01 (pPHC gyrus: P=0.0445 whole-surface corrected; mOFC: P = 0.046 small volume corrected in an anatomical mask of the frontal and temporal lobes based on the MNI Structural Atlas in FSL), indicating that the effects are weaker but larger than the EC effect in fig 2. This is perhaps not surprising as the OFC and pPHC are larger than EC and therefore can support larger more diffuse clusters. However, in the absence of pre-registration, we note that the FWE results of fig 4, whilst strong, involved minor parameter search and therefore may not control precisely for family-wise errors.

Methods References

1. Rescorla, R. A. & Wagner, A. R. A theory of Pavlovian conditioning: Variations in the effectiveness of reinforcement and nonreinforcement. *Class. Cond. II Curr. Res. Theory* **21**, 64–99 (1972).
2. Jenkinson, M., Beckmann, C. F., Behrens, T. E. J., Woolrich, M. W. & Smith, S. M. FSL. *Neuroimage* **62**, 782–790 (2012).
3. Jenkinson, M., Bannister, P., Brady, M. & Smith, S. Improved Optimization for the Robust and Accurate Linear Registration and Motion Correction of Brain Images. *Neuroimage* **17**, 825–841 (2002).
4. Smith, S. M. Fast robust automated brain extraction. *Hum. Brain Mapp.* **17**, 143–155 (2002).
5. Jenkinson, M. & Smith, S. A global optimisation method for robust affine registration of brain images. *Med. Image Anal.* **5**, 143–156 (2001).
6. Nili, H. *et al.* A Toolbox for Representational Similarity Analysis. *PLoS Comput. Biol.* **10**, e1003553 (2014).
7. Kriegeskorte, N., Mur, M. & Bandettini, P. A. Representational similarity analysis - connecting the branches of systems neuroscience. *Front. Syst. Neurosci.* **2**, 4 (2008).
8. Kriegeskorte, N., Goebel, R. & Bandettini, P. A. Information-based functional brain mapping. *Proc. Natl. Acad. Sci.* **103**, 3863–3868 (2006).
9. Ségonne, F. *et al.* A hybrid approach to the skull stripping problem in MRI. *Neuroimage* **22**, 1060–1075 (2004).
10. Desikan, R. S. *et al.* An automated labeling system for subdividing the human cerebral cortex on MRI scans into gyral based regions of interest. *Neuroimage* **31**, 968–80 (2006).
11. Reuter, M., Rosas, H. D. & Fischl, B. Highly accurate inverse consistent registration: A robust approach. *Neuroimage* **53**, 1181–1196 (2010).
12. Fischl, B., Sereno, M. I. & Dale, A. M. Cortical Surface-Based Analysis: II: Inflation, Flattening, and a Surface-Based Coordinate System. *Neuroimage* **9**, 195–207 (1999).
13. Fischl, B. *et al.* Whole Brain Segmentation: Automated Labeling of Neuroanatomical Structures in the Human Brain. *Neuron* **33**, 341–355 (2002).
14. Fischl, B., Liu, A. & Dale, A. M. Automated manifold surgery: constructing geometrically accurate and topologically correct models of the human cerebral cortex. *IEEE Trans. Med. Imaging* **20**, 70–80 (2001).
15. Dale, A. M., Fischl, B. & Sereno, M. I. Cortical Surface-Based Analysis: I. Segmentation and Surface Reconstruction. *Neuroimage* **9**, 179–194 (1999).
16. Nichols, T. E. & Holmes, A. P. Nonparametric permutation tests for functional neuroimaging: A primer with examples. *Hum. Brain Mapp.* **15**, 1–25 (2002).
17. Winkler, A. M., Ridgway, G. R., Webster, M. A., Smith, S. M. & Nichols, T. E. Permutation inference for the general linear model. *Neuroimage* **92**, 381–397 (2014).
18. Ho, J., Tumkaya, T., Aryal, S., Choi, H. & Claridge-Chang, A. Moving beyond P values: data analysis with estimation graphics. *Nat. Methods* **16**, 565–566 (2019).
19. Hampton, A. N., Bossaerts, P. & O'Doherty, J. P. The Role of the Ventromedial Prefrontal Cortex in Abstract State-Based Inference during Decision Making in Humans. *J. Neurosci.* **26**, 8360–8367 (2006).
20. Ramnani, N., Elliott, R., Athwal, B. S. & Passingham, R. E. Prediction error for free monetary reward in the human prefrontal cortex. *Neuroimage* **23**, 777–786 (2004).
21. O'Doherty, J. P., Dayan, P., Friston, K., Critchley, H. & Dolan, R. J. Temporal difference models and reward-related learning in the human brain. *Neuron* **38**, 329–337 (2003).

22. Delgado, M. R., Nystrom, L. E., Fissell, C., Noll, D. C. & Fiez, J. A. Tracking the Hemodynamic Responses to Reward and Punishment in the Striatum. *J. Neurophysiol.* **84**, 3072–3077 (2000).

Supplementary materials

Table S1. Effect of chosen action value of STRUCT model, when competing with NAÏVE model in the same GLM (GLM1, Fig. 1e). The contrast is [STRUCT chosen action value] > Baseline. All clusters with a FEW-corrected P-value < 0.05 are reported. Note that negative effects (with a negative t-score) are also reported,

Peak MNI cords	Brain region(s) of cluster	Peak t-score (df=27)	p-value (FWE-corrected on cluster level)
-32,-16,-20	L anterior hippocampus + amygdala + entorhinal cortex	6.71	P<0.001
-4,10,-12	Posterior mPFC (subcallosal cortex)	6.45	P=0.001
-6,58,36	Dorsal mPFC	4.56	P<0.001
28,-44,64	L Somatosensory cortex	5.56	P=0.006
0,34,-8	vmPFC	5.53	P<0.001
-32,-20,2	Insula/parietal operculum/white matter	5.07	P<0.001
26,4,-22	R hippocampus + amygdala + entorhinal cortex	5	P=0.003
52,-32,20	R parietal operculum	4.88	P<0.001
8,34,42	ACC	6.92	P<0.001
-42,16,6	L Insula	6.68	P<0.001
46,-52,34	R Angular gyrus	6.03	P<0.001
40,44,-2	OFC	5.69	P=0.002

Supplementary figures

Figure S1. a. Timeline of an example trial. **b.** Subjects benefited from the relational structure, and performed better on trials where a related stimulus was presented than trials where the control stimulus was presented (-Corr vs 0Corr paired t(27)=6.2 P<10^-6; +Corr vs 0Corr paired t(27)=4.06 P<10^-3). **c.** Univariate chosen value effect for the contrast STRUCT > NAÏVE.

Figure S2. Control contrasts for the EC relational structure effect (Figure 2, top). Left: model RDMs. Black elements should be similar, white elements should be dissimilar, blue elements are ignored. Right: whole-surface results (right hemisphere). color map is the same as in **Figure 2**. **a.** Structure effect, ignoring all elements of pairs of same-stimulus conditions. **b.** Structure effect, ignoring all elements of pairs of same stimuli set conditions.

Figure S3. Exploratory results of the prediction error X structure interaction effect.
Visualisation of whole-surface results of the multivariate prediction error X structure interaction effect (top/bottom: orbital/medial views, effects do not survive FWE-correction across a cortical hemisphere). The strongest effects in cortex where observed in PCC RH (right hemisphere): P<0.001 uncorrected), vlPFC (LH: P < 0.001 uncorrected, P=0.002 at the peak of the univariate prediction error vlPFC effect) and vmPFC (LH: P=0.002 uncorrected, Fig.3a). In all of these regions, the effects were also observed bilaterally, albeit weaker (PCC LH: P = 0.005 uncorrected; VLPFC RH: P=0.005 uncorrected); vmPFC RH: P=0.01 uncorrected). This network of regions is of particular interest for this effect, as it brings together several seemingly disparate literatures. The vmPFC and vlPFC are central to reward-guided learning [23]. The vmPFC [47,49,50], and PCC [49] have been strongly implicated in the representation of knowledge schemas. In addition, grid-like coding was reported in both vmPFC and PCC [19,20].

Figure S4. Subject-wise correlation between the prediction error X structure interaction effect size at the vmPFC peak of the that effect (**Figure 3a**) and the within-block, latent variable effect size at the mOFC (BA14) peak of the effect (**Figure 4a**).