Frontoparietal action-oriented codes support novel instruction implementation

Carlos González-García, Silvia Formica, David Wisniewski, and Marcel Brass

Department of Experimental Psychology, Ghent University, Belgium

Corresponding author: Carlos González-García

(carlos.gonzalezgarcia@ugent.be)

Abstract

A key aspect of human cognitive flexibility concerns the ability to convert complex

symbolic instructions into novel behaviors. Previous research proposes that this

transformation is supported by two neurocognitive states: an initial declarative

maintenance of task knowledge, and an implementation state necessary for

optimal task execution. Furthermore, current models predict a crucial role of frontal

and parietal brain regions in this process. However, whether declarative and

procedural signals independently contribute to implementation remains unknown.

We report the results of an fMRI experiment in which participants executed novel

instructed stimulus-response associations. We then used a pattern-tracking

procedure to quantify the contribution of format-unique signals during instruction

implementation. This revealed independent procedural and declarative

representations of novel S-Rs in frontoparietal areas, prior to execution. Critically,

the degree of procedural activation predicted subsequent behavioral performance.

Altogether, our results suggest an important contribution of frontoparietal regions to

the neural architecture that regulates cognitive flexibility.

Keywords: "Cognitive Control", "Instructions", "fMRI", "multivariate analysis",

"frontoparietal network", "retro-cues"

INTRODUCTION

Instruction following constitutes a powerful instance of human cognitive flexibility. The greater specificity and efficiency in the transmission of task procedures compared to trial-and-error or reinforcement learning make it a distinctive skill that separates humans from other species (Cole et al., 2013). While recent years have witnessed substantial progress in our understanding of instruction following, the precise neural coding schemes that organize brain activity during the rapid transformation of abstract instructed content into effective behavior are still poorly understood.

Previous behavioral studies have reported an intriguing signature of instruction processing, namely, a rapid configuration of instructed content predominantly towards action (González-García et al., 2020; Liefooghe et al., 2012, 2013; Liefooghe and De Houwer, 2018; Meiran et al., 2012, 2015a). This signature separates instruction implementation from related work in task switching and working memory: although preparation for action is not unique to novel instructions, in other contexts repetitive task execution makes it possible to retrieve specific long-term memory traces that allows for successful execution (Qiao et al., 2017; Zhang et al., 2013). In instruction implementation, however, long-term memory traces are reasonably ruled out (Liefooghe et al., 2012; Meiran et al., 2015a; Muhle-Karbe et al., 2016), and rather, an efficient proactive configuration can be achieved without prior practice. This configuration has a profound impact on brain activity. The intention to execute an instruction induces automatic motor activation (Everaert et al., 2014; Meiran et al., 2015b) and specific oscillatory

features (Formica et al., 2020b), engages different brain regions to coordinate

novel stimuli and responses (Demanet et al., 2016; González-García et al., 2017a;

Hartstra et al., 2011; Palenciano et al., 2019b, 2019a), and alters the neural

representation of instructed content in control brain regions, primarily, the

frontoparietal network (FPN) (Bourguignon et al., 2018; Muhle-Karbe et al., 2017).

These and other findings propose a crucial role of the FPN in the rapid access to

and configuration of an implementation stage, a highly efficient task readiness

state that support successful execution (Bourguignon et al., 2018; González-

García et al., 2017b; Hartstra et al., 2011; Muhle-Karbe et al., 2017; Palenciano et

al., 2019b, 2019a; Woolgar et al., 2015).

To account for these findings, prominent theoretical models (Brass et al., 2017) put

forward a *serial-coding hypothesis* of frontoparietal function, a multi-step process in

which the FPN first encodes instructed information into a *declarative* code, that is,

a persistent representation of the memoranda conveyed by the instruction. When

this information becomes behaviorally relevant, FPN declarative representations

are transformed into an implementation state that is optimized for specific task

demands (Brass et al., 2017). Current models propose that such implementation

state consists primarily of *procedural* codes, a proactive binding of relevant

perceptual and motor information into a compound representation that leads to the

boost of relevant action codes related to behavioral routines (Muhle-Karbe et al.,

2017).

However, the characterization of neural coding during implementation remains

unclear, primarily due to the fact that previous analytical approaches were unable

to track representational formats of specific nature. Previous work thus identified

some properties of the FPN during the implementation of novel instructions, such

as enhanced decoding of stimulus (González-García et al., 2017a; Muhle-Karbe et

al., 2017) and rule identity (Ruge et al., 2019), or altered similarity within to-be-

implemented S-R associations (Bourguignon et al., 2018; Palenciano et al.,

2019b). Although these results reveal unique signatures of instruction

implementation, they are agnostic regarding the functional representational state

underlying such effects, that is, the extent to which they capture a contribution of

procedural and declarative signals. Furthermore, previous approaches were not

able to eliminate the contribution of domain-general processes, such as arousal or

attention, which could potentially drive some of the differences between

implementation and other experimental conditions. Therefore, currently, it cannot

be discerned whether such implementation state is uniquely supported through the

proposed procedural codes, or whether it additionally preserves task content in an

independent, declarative format. Furthermore, the specific contribution of these two

representational formats to successful behavior remains unknown.

Here, we used a canonical template tracking procedure to capture whether

different signals governed FPN activity during the prioritization of novel instructions

(Brass et al., 2017). Using data from two independent localizers that encouraged

either a declarative or action-oriented maintenance of novel instructions, we

derived instruction-specific multivariate patterns of activity in declarative and

procedural formats, respectively. We then assessed the contribution of these

canonical declarative and procedural templates prior to task execution. Importantly,

this partialling logic allowed to determine the format-specific contribution of

procedural and declarative representational formats and to partial out the

contribution of domain-general processes.

MATERIALS AND METHODS

Methods are reported, when applicable, in accordance with the Committee on Best

Practices in Data Analysis and Sharing (COBIDAS) report (Nichols et al., 2017).

Participants

Thirty-two participants (mean age = 23.16, range = 19-33; 20 females, 12 males)

recruited from the participants' pool from Ghent University participated in exchange

of 40 euros. They were all right-handed (confirmed by the Edinburgh handedness

inventory), clinically healthy and MRI-safe. The study was approved by the UZ

Ghent Ethics Committee and all participants provided informed consent before

starting the experiment. Of the initial 32 participants, 3 were excluded after

acquisition (1 participant performed at chance during the task; 1 participant had an

error rate of 1 in catch trials (see below); 1 participant's within-run head movement

exceeded voxel size), resulting in a final sample of 29 participants. Due to an

incomplete orthogonalization of the cued and uncued S-R pairings, the first three

participants were excluded from multivariate analyses (n = 26).

Apparatus, stimuli, and procedure

S-R associations were created by combining images with words that indicated the

response finger. Each S-R association was presented just once during the entire

experiment to prevent the formation of long-term memory traces (Meiran et al.,

2015a). Given this prerequisite, images of animate (non-human animals) and

inanimate (vehicles and instruments) items were compiled from different available

databases (Brady et al., 2013, 2008; Brodeur et al., 2014; Griffin et al., 2006;

Konkle et al., 2010), creating a pool of 1550 unique pictures (770 animate items,

780 inanimate). To increase perceptual similarity and facilitate recognition, the

background was removed from all images, items were centered in the canvas, and

images were converted to black and white.

The response dimension was defined by the combination of a word ("index" or

"middle") and the position of the mapping in the encoding screen. For instance, if

an S-R pair containing the word "index" was displayed on the left-hand side of the

screen, this informed participants that the correct response associated with that

particular stimulus would be "*left* index". This allowed us to have 2 mappings on

screen that involved the same (stimulus and) *response category* (e.g. index finger)

but different effectors (e.g. *left* index finger vs *right* index finger).

Importantly, even though specific S-R associations were presented only once

throughout the experiment, they could be grouped depending on the specific

combination of stimulus and response dimensions. Specifically, the combination of

the 2 stimulus dimensions (animate/inanimate items) and the 2 response

dimensions (index/middle finger) lead to 4 finger-animacy pairings: S-R 1

(animate-index), S-R 2 (inanimate-index), S-R 3 (animate-middle), and S-R 4

(inanimate-middle).

In the main task, each trial started with an encoding screen (5000 ms) that

displayed 4 S-R associations. The two mappings on the upper half of the encoding

screen belonged to one S-R pairing, and the other two belonged to another S-R

pairing. Immediately after the encoding screen, a retro-cue appeared. Informative

retro-cues (75% of trials) consisted of an arrow centered in the middle of the

screen pointing either upwards or downwards. Therefore, informative retro-cues

did not select a specific S-R mapping but rather two mappings belonging to the

same S-R pairing (e.g. "animate - index finger"). Such grouping was crucial for

analysis purposes since it allowed us to identify the *selected* S-R pairing, as well

as the *unselected* category that was initially encoded but could be dropped from

working memory after the retro-cue. Additionally, for each trial, we identified the *not*

presented S-R pairings, which would serve as empirical baseline for our template

tracking analysis (see below). In contrast, neutral retro-cues did not select any

mapping. The retro-cue was displayed for 1000 ms and was followed by a fixation

point (cue-target interval; CTI), which duration was jittered following a pseudo-

logarithmic distribution (mean duration = 2266 ms, SD = 1276 ms, range = [600-

5000]). Directly after the CTI, a target was on screen for 1500 ms. Target screens

displayed the image belonging to one of the selected mappings, prompting

participants to execute the associated response by pressing the corresponding

button in an MRI-compatible button box. In neutral trials, the target could be the

stimulus of any of the 4 S-R encoded mappings. Additionally, in ~6% of trials, a

catch target appeared. This consisted of a new image, different from any of the

encoded stimuli, to which participants had to answer by pressing the 4 available

buttons in the response box. Catch trials were included to ensure that participant

encoded all four S-R associations and were equally likely after an informative and

a neutral retro-cue. Last, after the target screen, a fixation point was shown

between trials (inter-trial interval, ITI) for a jittered duration (following the same

parameters as the CTI jitter). Each trial lasted on average 12 seconds. The

sequence of trial events is depicted in Figure 1.

Figure 1. Behavioral paradigm. On each trial, participants first encoded four novel

S-R mappings consisting in the association between an (animate or inanimate)

item and a response (index or middle fingers; response hand defined by the

position of the mapping on the screen; e.g. "helicopter-index" on the left-hand side

of the screen requested participants to press the *left* index if the target screen

displayed a helicopter). After the encoding screen, an informative retro-cue (75%

of the trials) signaled the relevance of two of the mappings. In the remaining 25%

of trials, a neutral retro-cue appeared, and none of the mappings were cued. Last,

a target stimulus prompted participants to provide the associated response (in this

example, "right index" finger press).

The main task was divided into 4 runs. Each run contained 51 trials (48 regular and

3 catch trials). Of the 48 regular trials, 75% contained an informative retro-cue, and

the remaining trials displayed neutral retro-cues. The S-R pairings selected and

unselected by the retro-cue were fully counterbalanced, resulting in 36 trials per

pairing across the entire experiment. For instance, there were 36 trials in which

Pairing 1 mappings were selected by the retro-cue. Of these 36 trials, in one third,

the unselected mappings (that is, mappings shown in the encoding screen but not

selected by the retro-cue) belonged to Pairing 2, another third to Pairing 3, and the

last third to Pairing 4. Each run lasted around 10 minutes, and the main task,

containing 204 trials, lasted around 40 minutes in total. Prior to the main task,

outside of the scanner, participants performed a practice session with trials

following the same structure described above with the exception that feedback was

included to help familiarization. The practice session was structured in blocks of 11

trials. Participants performed these blocks until they achieved at least 9 correct

responses. S-R mappings used during the practice were never used again.

After the main task, participants performed two localizers to obtain an independent

canonical representation of each S-R pairing in the two formats of interest. The two

localizers were aimed at encouraging either a primarily procedural or a primarily

declarative coding of new S-Rs. Although a localizer eliciting uniquely one of these

two types of coding is hard to conceive (for instance, one could claim a declarative

representation of the elements of a task is required before any procedural

representation can emerge (Formica et al., 2020a)), our pattern analysis (see

below) capitalized on the specific engagement of procedural and declarative

strategies encouraged by each of these localizers.

The structure of the task was almost identical in the two localizers. In both

localizers, trials started with an encoding screen (2000 ms) that contained two

mappings of the same S-R pairing, followed by an inter-stimulus interval of jittered

duration (same parameters as the jitters in the main task). Importantly, in both

localizers, even though the two encoded mappings belonged to the same S-R

pairing, they specified different effectors (for instance: "if you see an elephant,

press left index finger; if you see a tiger, press right index finger), and therefore

participants needed to maintain both mappings rather using other strategies, such

as remembering 2 images and one response.

Last, a target screen appeared (1500 ms) followed by a jittered ITI. The target

screen differed in the two localizers and was inspired by previous studies

investigating the dissociation of implementing vs. memorizing new instructions

(Liefooghe et al., 2012; Liefooghe and De Houwer, 2018; Muhle-Karbe et al.,

2017). In the procedural localizer, the target consisted of a single image that

prompted participants to execute the associated response. Although this

configuration renders the procedural localizer similar to the main task, it remained

different in a crucial aspect. Whereas in the procedural localizer participants could

prepare for executing one of the 2 mappings directly in the encoding screen, in the

main task this highly action-oriented coding format was strategically optimal only

after the selection process elicited by the retro-cue. Since our analyses focused on

this moment of the main task, the localizer thus provided a means to test whether

the selection of a novel S-R from working memory engaged similar procedural

signals.

The declarative localizer, in contrast to the procedural one, displayed a memory

target consisting of one image and one response finger (e.g. left index).

Participants were trained to answer whether the displayed mapping was correct

(same association as the encoded one) or incorrect (different association) by

pressing both left-hand buttons (when "correct") or both right-hand buttons (when

"incorrect"). Therefore, in the memorization localizer, participants never had to

prepare to execute the encoded mapping but rather just maintain its information.

As in the main task, catch trials consisted of new images, to which participants had

to respond by pressing all 4 available buttons. Each trial lasted around 8 s on

average, and each localizer contained 66 trials (15 per S-R pairing + 6 catch trials),

resulting in a total of 9 minutes per localizer. Given that the task demands for the

procedural localizer were more similar to the main task, this localizer was

performed always before the declarative localizer, which required more detailed

explanation to participants. Importantly, the nature of our template tracking

approach (see below) accounted for any potential order confound in such analysis,

since template activation is measured against an empirical within-localizer

baseline, and not directly compared between localizers.

All tasks were presented in PsychoPy 2 (Peirce, 2007) running on a Windows PC

and back-projected onto a screen located behind the scanner. Participants

responded using an MRI-compatible button box on each hand (each button box

contained two buttons, on which participants placed their index and middle

fingers).

Data acquisition and preprocessing

Imaging was performed on a 3T Magnetom Trio MRI scanner (Siemens Medical

Systems, Erlangen, Germany), equipped with a 64-channel head coil. T1 weighted

anatomical images were obtained using a magnetization-prepared rapid acquisition

gradient echo (MP-RAGE) sequence (TR=2250 ms, TE=4.18 ms, TI=900 ms,

acquisition matrix=256 × 256, FOV=256 mm, flip angle=9°, voxel size=1 × 1 × 1

mm). Moreover, 2 field map images (phase and magnitude) were acquired to

correct for magnetic field inhomogeneities (TR=520 ms, TE1=4.92 ms, TE2=7.38

ms, image matrix=70 x 70, FOV=210 mm, flip angle=60°, slice thickness=3 mm,

voxel size=3 x 3 x 2.5 mm, distance factor=0%, 50 slices). Whole-brain functional

images were obtained using an echo planar imaging (EPI) sequence (TR=1730

ms, TE=30 ms, image matrix=84 × 84, FOV=210 mm, flip angle=66°, slice

thickness=2.5 mm, voxel size=2.5 x 2.5 x 2.5 mm, distance factor=0%, 50 slices

with slice acceleration factor 2 (Simultaneous Multi-Slice acquisition)). Slices were

orientated along the AC-PC line for each subject.

For each run of the main task, 373 volumes were acquired, whereas 330 volumes

were acquired during each localizer. In all cases, the first 8 volumes were

discarded to allow for (1) signal stabilization, and (2) sufficient learning time for a

noise cancellation algorithm (OptoACTIVE, Optoacoustics Ltd, Moshav Mazor,

Israel). Before data preprocessing, DICOM images obtained from the scanner

were converted into NIfTI files using HeuDiConv

(https://github.com/nipy/heudiconv), in order to organize the dataset in accordance

with the BIDS format (Gorgolewski et al., 2017). Further data preprocessing was

performed in SPM12 (v7487) running on MATLAB R2016b. First, anatomical

images were defaced to ensure anonymization. They were later segmented into

gray matter, white matter and cerebro-spinal fluid components using SPM default

parameters. In this step, we obtained inverse and forward deformation fields to

later (1) normalize functional images to the atlas space (forward transformation)

and (2) transform ROIs from the atlas on to the individual, native space of each

participant (inverse transformation). Regarding functional images, preprocessing

included the following steps in the following order: (1) Images were realigned and

unwarped to correct for movement artifacts (using the first scan as reference slice)

and magnetic field inhomogeneities (using fieldmaps); (2) slice timing correction;

(3) coregistration with T1 (intra-subject registration): rigid-body transformation,

normalized mutual information cost function; 4^{th} degree B-spline interpolation; (4)

registration to MNI space using forward deformation fields from segmentation: MNI

2mm template space, 4^{th} degree B-spline interpolation; and (5) smoothing (8-mm

FWHM kernel). Multivariate analyses were conducted on the unsmoothed,

individual subject's functional data space and results were later pooled across

participants for region-of-interest analyses.

Experimental design and statistical analysis

Our main task design consisted of two within-subject factors orthogonally

manipulated: retro-cue status (informative vs. neutral) and selected S-R pairing.

Regarding behavioral data analyses, we used JASP (JASP Team, 2018) to

perform two-tail paired t-tests comparing reaction times and error rates for trials

with informative vs. neutral trials (collapsing across selected S-R pairing).

General Linear Model (GLM) estimations and mass-univariate analyses.

Four GLMs were estimated for each participant in SPM. First, a GLM was used to

assess changes in activation magnitude between informative and neutral retro-

cues during the main task. A model was constructed including, for each run,

regressors for the encoding screen (zero duration), informative/neutral retro-cues

(with duration), informative/neutral CTI (with duration), target (zero duration) and

ITI interval (with duration). Trials with errors were included as a different regressor

that encompassed the total duration of the trial. All regressors were convolved with

a hemodynamic response function (HRF). At the population level, parameter

estimates of each regressor were entered into a mixed-effects analysis. To correct

for multiple comparisons, first we identified individual voxels that passed a 'height'

threshold of $p < 0.001$, and then the minimum cluster size was set to the number of

voxels corresponding to $p < 0.05$, FWE-corrected. This combination of thresholds

has been shown to control appropriately for false-positives (Eklund et al., 2016). A

second GLM was estimated on the non-normalized and unsmoothed main task

data for all multivariate analyses. This GLM contained beta estimates that specified

the cued/uncued S-R pairings during informative retro-cues. For each participant

and run, a model was built including the following regressors: encoding (zero

duration), neutral retro-cues (with duration), targets (zero duration), CTI and ITI

(with duration). For informative retro-cues, a regressor that encompassed the total

duration of the retro-cue was created for each S-R pairing combination (e.g.

CuedPairing1_UncuedPairing2), resulting in a total of 12 regressors (3 per finger-

animacy pairing). Errors were included as a different regressor encompassing the

full duration of the trial. Last, a third and fourth GLMs were performed on the non-

normalized and unsmoothed data from the two localizers. For each localizer, we

built a model that contained regressors for the encoding screen (zero duration),

encoding-target interval (ISI, with duration) for each S-R pairing (total of 4

regressors), target (zero duration), ITI (with duration), and errors (full trial). As in

the previous GLM, these models were not used in a population-level GLM and

were estimated for later use in the canonical template tracking procedure.

Multivariate pattern analysis (MVPA). MVPA was performed on the beta

images of the second GLM using The Decoding Toolbox (Hebart et al., 2015)

(v3.99). To assess the representation of cued S-R pairings during implementation,

we carried out ROI-based one-vs-one multiclass decoding of S-R pairings. In each

fold of the leave-one-run-out procedure, we trained a classifier (linear support

vector machine (SVM); regularization parameter = 1) on the identity of the *cued* S-

R pairing using all informative retro-cue betas but four (one from each class). The

classifier was then tested on the remaining samples. Thus, the held-out data in

each cross-validation fold was from different experimental runs to the training data.

The accuracy was averaged across folds. Only one decoding was performed per

ROI, using all voxels. To remove any potential magnitude difference between

classes, we z-scored the values of each condition across voxels before the

analysis (therefore, each condition that entered the analysis had a mean activation

of 0 and an s.d. of 1). We then repeated the same procedure but now training and

testing the classifier on the identity of the *uncued* S-R pairing.

Statistics of decoding analyses followed a permutation approach

(Combrisson and Jerbi, 2015). For each ROI, we computed a null distribution by

repeating the decoding protocol 1000 times swapping the labels of the true

classes. We then established the chance level for a given participant as the mean

value of this null distribution. To assess significance at the population level, we first

compared accuracy minus chance scores of all participants against 0, using a one-

sample t-test. Then, we computed the empirical null distribution of t-values by, on

each of 1000 permutations, randomly flipping the sign of each individual score and

performing a new t-test. Finally, an effect was considered significant if the

observed t-value was larger than 95% of the t-values in the null distribution (thus,

significance level = $p < 0.05$).

Canonical template tracking procedure. The main goal of the current study

was to assess the contribution of procedural and declarative signals during

instruction implementation. To do so, we followed a canonical template tracking

procedure (Wimber et al., 2015) (see Figure 4 for a visual representation of the

analysis). The main rationale of this analysis was (1) to obtain canonical

representations of the different S-R pairings under the two different formats of

interest (procedural and declarative) from the ISI of the localizers, and later (2)

estimate the extent of variance during implementation in the main task uniquely

explained by each of these representations. Importantly, this analysis was aimed at

obtaining evidence for the presence (or lack thereof) of procedural and/or

declarative signals and not to compare their strengths.

The functional localizers performed after the main task allowed us to obtain a

participant-specific canonical pattern of activation for each S-R pairing in

declarative and procedural formats. All patterns were derived from beta weights of

the GLMs described in the section General Linear Model estimations. Prior to

analysis, betas were converted into t-maps and, given the impact of noise on

correlation estimates, we performed multivariate noise normalization on each

individual run of the main task and template separately (Walther et al., 2016). To

do so, we used the residuals of each participant's GLMs to estimate the noise

covariance between voxels. These estimates, regularized by the optimal shrinkage

factor (Ledoit and Wolf, 2004), were used to spatially pre-whiten the t-maps.

To measure the contribution of the canonical patterns during the main task, for

each region, we computed the semi-partial correlation between the pattern of

activity during the retro-cue in the main task and the canonical template of each S-

R pairing in the two formats. Semi-partial correlations make it possible to estimate

how much *unique* variance the independent variable (e.g. the residuals of

regressing the procedural template of one S-R pairing on the declarative template

of the same pairing) explains in relation to the total variance in the dependent

variable (e.g. activity during the main task), and are thus more practically relevant

than partial correlations because they are scaled to the total variability in the

dependent variable, rather than to the variance unaccounted for by the rest of

variables.

An important feature of the described template tracking approach is that it was

optimized to detect whether the two signals of interest were independently

accounting for unique variance during implementation, and not to compare the

strength of these two signals. Therefore, the raw semi-partial correlation magnitude

of each template with the task was of no interest. Only the relative difference

between correlation of cued, uncued S-Rs, and the empirical baseline provided by

the not-presented S-R was informative for our hypotheses. Since our GLM

included different retro-cue regressors depending on the selected S-R pairing, we

could obtain a specific activation value for cued, uncued and not-presented

pairings. Importantly, semi-partial correlations were used to obtain the amount of

variance shared between the main task and a template of an S-R pairing (e.g. in

procedural state) that is not explained by the template of that same pairing in the

opposite state (e.g. declarative). As such, this approach is sensitive to content-

specific signals and rules out the relative contribution of domain general processes

that are shared between the two localizers, ensuring that any significant result

would only capture the activation of S-R information in a specific format. To

statistically test the boost of cued information, we first normalized the semi-partial

correlation scores by using Fisher's z transformation and then performed paired t-

tests between the cued, uncued and not-presented S-R pairings activation (FDR-

corrected for multiple comparisons).

Region-of-interest (ROI) definition

Frontoparietal ROIs were obtained from a parcellated map of the multiple-demand

network (Fedorenko et al., 2013). Specifically, frontal ROIs comprised the inferior

and middle frontal gyrus regions of the map, and parietal ROIs comprised the

inferior and superior parietal cortex regions. All ROIs were registered back to the

native space of each subject using the inverse deformation fields obtained during

segmentation.

We obtained a ventral visual cortex ROI by extracting the following regions in the

WFU pickatlas software (http://fmri.wfubmc.edu/software/PickAtlas): bilateral

inferior occipital lobe, parahippocampal gyrus, fusiform gyrus, and lingual gyrus (all

bilateral and based on AAL definitions). The primary motor cortex ROI was also

obtained using WFU pickatlas by extracting the bilateral M1 region.

RESULTS

S-R prioritization enhances instruction execution

Analysis of participants' behavioral performance revealed that retro-cues helped

participants in prioritizing novel S-Rs. Specifically, participants were faster ($t_{28,1} =$

13.51, $p < 0.001$, Cohen's $d = 2.51$; Fig. 2a) and made less errors ($t_{28,1} = 7.96$, $p <$

0.001, Cohen's $d = 1.47$; Fig. 2b, left panel) in trials with informative retro-cues,

compared to neutral. Participants were slower in catch trials compared to

informative ($t_{28,1} = 11.68$, $p < 0.001$, Cohen's $d = 2.17$) and neutral trials ($t_{28,1} =$

3.36, $p = 0.002$, Cohen's $d = 0.63$). This longer RT probably reflected the

requirement to disengage from the encoded S-Rs and respond correctly to the

new, non-encoded image. In line with this interpretation, responses to catch

images after a neutral retro-cue (M = 981 ms, SD = 122) were slower than after an

informative retro-cue (M = 909 ms, SD = 95; $t_{27,1}$ = 3.81, p < 0.001, Cohen's d =

0.72). This cost of WM load only modulated RTs: error rates for catch trials were

lower than in neutral trials ($t_{28,1}$ = 4.83, p < 0.001, Cohen's d = 0.90), and not

significantly different from informative trials (t < 1), suggesting that participants

were able to detect new images and, therefore, that they successfully encoded all

mappings of the encoding screen.

Regarding performance during the two localizers, we expected more successful

behavior during the procedural localizer task, given the simpler nature of the task.

Accordingly, participants responded faster ($t_{28,1}$ = 25.75, p < 0.001, Cohen's d =

4.78) and made less errors ($t_{28,1}$ = 3.99, p < 0.001, Cohen's d = 0.74) during the

procedural localizer (RT M = 652 ms, SD = 84; ER M = 0.15, SD = 0.1), compared

to declarative one (RT M = 1042, SD = 75; ER M = 0.25, SD = 0.08).

Figure 2. Behavioral results. (**a**) Reaction times in neutral, informative, and catch

trials. (**b**) Error rates in neutral, informative, and catch trials. The thick line inside

box plots depicts the second quartile (median) of the distribution (n = 29). The

bounds of the boxes depict the first and third quartiles of the distribution. Whiskers

denote the 1.5 interquartile range of the lower and upper quartile. Dots represent

individual subjects' scores. Grey lines connect dots corresponding to the same

participant in two different experimental conditions.

Identifying novel S-R selection activity

As a first step, we investigated which brain regions were predominantly involved in

the selection of instructions from working memory (WM). Based on recent

experimental results (González-García et al., 2020; Myers et al., 2018; Yu and

Postle, 2018) and theoretical models of WM (Myers et al., 2017), we assumed that

selection would prioritize relevant S-R associations into a behavior-optimized state,

akin to implementation. As such, retro-cues served as a tool to locate in time the

moment after initial encoding in which implementation-specific signals should be

magnified in detriment of encoded but uncued S-Rs, which could be potentially

dropped from WM. Specifically, we predicted that if such prioritization of S-Rs is

indeed similar to instruction implementation, then the FPN should be particularly

engaged in trials with informative retro-cues (Bourguignon et al., 2018; González-

García et al., 2017a; Jackson and Woolgar, 2018; Muhle-Karbe et al., 2017;

Palenciano et al., 2019a; Woolgar et al., 2015). We thus established a set of a

priori candidate regions that encompassed frontal (inferior and middle frontal gyri)

and (inferior and superior) parietal cortices (see Fig. 3b, and the Region-of-interest

definition section in the Methods). We then performed a whole-brain analysis to

find regions sensitive to S-R selection (defined as informative vs. neutral retro-

cues) in their overall activation magnitude using a general linear model (GLM). We

found that informative retro-cues elicited significantly higher activity in regions of

the FPN, including the inferior and middle frontal gyri, inferior and superior parietal

cortices, as well as regions outside the FPN, such as the lateral occipital cortex

(Fig. 3a, primary voxel threshold [$p < 0.001$ uncorrected] and cluster-defining

threshold [FWE $p < .05$]). Overall, the resulting statistical map roughly overlap with

the set of a priori defined regions of interest (ROIs; Fig. 3b), confirming the

involvement of the FPN in S-R selection and, more broadly, providing initial

evidence that such prioritization could engage similar mechanisms as instruction

implementation.

Next, we predicted that the prioritization state would modulate the representation of

S-R pairings. To test this hypothesis, we performed two similar multivariate

decoding analyses in the 4 FPN ROIs. First, we tested if at the moment of the

retro-cue the patterns of activity in these four regions carried information about the

specific finger-animacy pairing of the cued S-R. We found significant decoding in

the right PFC and bilateral parietal ROIs (permutation-based one-sample t-tests, all

ps < 0.02), and not significant decoding in the left PFC ($t_{25,1} = 1.69$, $p = 0.1$),

although a Bayesian t-test suggested no conclusive evidence for neither the

alternative nor the null hypothesis in this ROI ($BF_{10} = 0.45$). Next, we tested the

extent to which the FPN also carried information about the encoded, but not cued

pairing. In contrast to the previous results, we expected these pairings not to be

decodable, given that uncued mappings could be dropped from memory. In line

with our prediction, decoding did not reach significance in any of the ROIs (all *p*s >

0.06), and a Bayesian counterpart of the analysis provided support for the null

hypothesis (in left DLPFC and bilateral parietal ROIs, all BFs < 0.3) and

inconclusive evidence in the right DLPFC (BF_{10} = 0.58). Finally, we directly

compared the decoding accuracies for the cued and uncued pairings. This analysis

revealed significantly stronger decoding of the cued pairing compared to the

uncued one in right PFC and bilateral parietal cortices (permutation-based paired t-

tests, all *p*s < 0.02, Fig. 3c; see Table 1 for individual statistics, p-values and BF_{10}

estimates).

Figure 3. S-R selection induced changes in frontoparietal neural activity. (**a**) GLM

contrast of informative > neutral retro-cue trials. Warm colors show regions with

significantly higher activity magnitude during informative compared to neutral retro-

cues (primary voxel threshold [*p* < 0.001 uncorrected] and cluster-defining

threshold [FWE *p* < .05]). (**b**) Set of regions-of-interest defined prior to analyses,

encompassing frontal (inferior and middle frontal gyri) and (inferior and superior)

parietal cortices. (**c**) Mean S-R pairing decoding (minus empirical chance level)

within each region of interest. Error bars denote between-participants s.e.m. Grey

asterisks denote accuracies significantly above chance level (permutation-based

one-sample t-test, 1k permutations). Black asterisks denote significantly higher

accuracies for cued compared to uncued S-R pairings (permutation-based paired t-

test, 1k permutations).

	ROI	t	p	BF_{10}
cued	ldlpfc	1.3088	0.108	0.445
	rdlpfc	2.1274	0.02	1.412
	lpar	3.5149	< 0.001	21.601
	rpar	3.4638	< 0.001	19.32
uncued	ldlpfc	-0.2089	0.406	0.211
	rdlpfc	-1.5223	0.068	0.575
	lpar	-0.0739	0.454	0.208
	rpar	-0.336	0.384	0.218
comparison	ldlpfc	1.1338	0.142	0.632
	rdlpfc	2.4384	0.01	4.794
	lpar	2.5978	0.01	6.475
	rpar	2.2243	0.018	3.255

Table 1. Statistics, p-values and BF_{10} estimates for ROI-based decoding results.

BF10 > 3 suggests support for the alternative hypothesis, whereas BF10 < 0.3

indicates support for the null hypothesis.

Tracking format-unique S-R patterns

Altogether, these results show that instruction prioritization has a profound impact

on FPN activity, impacting the representation of selected and irrelevant S-Rs.

However, similarly to previous studies, they are agnostic regarding the nature of

the signals underlying such effect. The main goal of our study was to test whether

both declarative and procedural signals contributed to the representational

organization of FPN activity during instruction implementation. To do so, we

implemented a canonical template tracking procedure that allowed us to estimate

neural activations of specific S-R pairings under the two functional formats of

interest (see Figure 4, for a visual representation of the procedure, and Methods,

for a detailed description of the analysis). Importantly, this approach revealed the

amount of shared variance between task data and a given template (e.g. S-R

pairing 1 in procedural state) that is not explained by the same template in the

alternative state (e.g. S-R pairing 1 in declarative state). Therefore, processes

common to both localizers (e.g. arousal, domain-general attention and/or task

preparation) cannot inflate correlations, and any significant enhancement from

baseline rather reflects the activation of S-R-specific information in a specific

format during the main task.

Figure 4. Schematic of the canonical template tracking procedure. For each region

of interest, we extracted the pattern of activity of specific S-R pairings during

informative retro-cues (upper panel, in yellow) and computed similarity with

canonical templates of such pairings in declarative (bottom left, in blue) and

procedural (bottom right, in green) formats, obtained in two separate localizers.

Importantly, similarity was assessed via semi-partial correlations, obtaining the

proportion of uniquely shared variance between task and template data (middle,

Venn diagram) of the cued, uncued and not-presented S-R pairings, which provide

an empirical baseline. Graphs represent a hypothetical set of results, in which

implementation recruits non-overlapping procedural and declarative

representations of cued S-R pairing. This informational boost, relative to baseline

(not-presented S-R pairings), is superior to that of the uncued pairing.

To validate this procedure outside the FPN, we created an ROI comprising the

primary motor cortex, where implementation should be dominated by action-

oriented signals and no declarative information about S-R pairings is expected.

The results obtained (Fig. 5) matched the predictions, revealing a specific

enhancement of procedural information of the cued pairing compared to the

uncued ($t_{25,1}$ = 4.08, p < 0.001, Cohen's d = 0.80), and critically, to the empirical

baseline defined by the not-presented pairings ($t_{25,1}$ = 5.45, p < 0.001, Cohen's d =

1.07). No activation of the uncued S-R pairing was found ($t_{25,1}$ = 1.32, p = 0.2,

Cohen's d = 0.26). As predicted, no differences between cued, uncued and

baseline pairings were found in declarative signals (all *t*s < 1.53, all *p*s > 0.14).

Figure 5. Template tracking procedure results in the primary motor cortex. Bars

represent the normalized semi-partial correlation between task data and the

procedural and declarative templates of cued, uncued and not presented S-R

pairings. Error bars denote within-participants s.e.m (Morey, 2008). Asterisks

denote significant differences ($p < 0.05$, paired t-test).

To further assess the sensitivity of our tracking approach, we repeated the analysis

on the beta estimates obtained during the encoding screen of the trial, where no

differences should be found between cued and uncued mappings. Given the

results during the retro-cue period, here we focused on procedural activation

scores. We then entered the template activation scores of the encoding and retro-

cue events in a repeated-measures ANOVA with the factors S-R type (cued vs.

uncued) and Event (Encoding vs. Retro-cue). Importantly, the activation scores

entered were the scores for cued and uncued relative to not-presented mappings,

therefore not-presented mappings were not included as a separate level in the S-R

type factor of the ANOVA. This analysis yielded a significant S-R type * Event

interaction ($F_{25,1} = 10.61$, $p = 0.003$, $\eta^2_p = 0.3$). The interaction effect revealed a

difference in activation of cued and uncued S-Rs only during the retro-cue screen

($F = 16.68$, $p < 0.001$), whereas no significant differences were found during the

encoding screen ($F < 1$, $p = 0.67$). Furthermore, it revealed a boost in the

activation of cued mappings during the retro-cue, compared to the encoding

screen ($F = 4.9$, $p = 0.036$). No difference was found for the uncued S-Rs ($F = 2.5$,

$p = 0.125$), although activation was numerically weaker during the retro-cue ($M =$

0.001, $SD = 0.004$) than during the encoding screen ($M = 0.003$, $SD = 0.006$). To

directly test whether activation for cued and uncued during the retrocue was

greater that during the encoding screen, we performed a new ANOVA in which we

introduced direct scores (not relative to baseline), therefore including not-

presented S-R as another level of the S-R type factor. This ANOVA confirmed the

Event * S-R type interaction (F = 6.71, p = 0.003). Moreover, post-hoc tests

(Bonferroni-corrected) revealed, first, that during the retrocue screen cued S-Rs

had higher activation than uncued (t = 4.66, p < 0.001) and not-presented S-Rs (t =

5.58, p < 0.001), whereas uncued and not-presented S-Rs did not differ (t < 1). In

contrast, no differences were found between cued, uncued and not-presented S-

Rs during the encoding epoch (all ps > 0.11).

Declarative and procedural contributions to instruction implementation in

frontoparietal regions (and beyond)

To elucidate which signals govern implementation in control-related regions, we

carried out the template tracking procedure on each FPN region separately.

Furthermore, we decided to include the ventral visual cortex (VVC) in this analysis

to explore the effect of implementation in higher-order visual regions, since these

have been consistently shown to be involved in instruction processing (González-

García et al., 2017a; Muhle-Karbe et al., 2017; Palenciano et al., 2019b, 2019a)

and our univariate results also revealed their engagement in the current task.

Importantly, our main goal was to assess whether FPN contained procedural

and/or declarative signals during implementation and not to compare the strength

of these to each other. Therefore, the raw semi-partial correlation of cued pairings

in procedural and declarative formats, which could be biased by for instance higher

resemblance between the procedural localizer and the main task, was not

informative for our purpose (and did not differ between procedural [M = 0.03, SD =

0.014] and declarative signals [M = 0.03, SD = 0.015], t < 1, p = 0.34). Instead, we

focused on the comparison of these activations to the within-localizer empirical

baselines provided by the irrelevant mappings on each format. Supporting previous

results and theoretical models (Brass et al., 2017; Muhle-Karbe et al., 2017), this

analysis (Fig. 6a) revealed prioritization involves the representation of relevant

information in an action-oriented format in the FPN (two-tail paired t-test against

empirical baseline [not-presented pairings], all ts > 2.16, all ps < 0.04, all Cohen's

d > 0.42). Critically, procedural information of cued pairings was significantly more

activated than uncued pairings (all ts > 2.26, all ps < 0.04, all Cohen's d > 0.44).

Regarding declarative information (Fig. 6b), parietal nodes of the FPN showed a

specific enhancement of declarative information of the cued S-R pairing, compared

to the irrelevant (ts > 3, all ps < 0.005, all Cohen's d > 0.6) and uncued ones (ts >

2.16, all ps < 0.02, all Cohen's d > 0.49). In contrast, no significant differences

were found in frontal nodes between cued and uncued S-Rs, and cued and

irrelevant S-Rs (ts < 2.06, all ps < 0.05, all Cohen's d < 0.4). To further assess this

difference between frontal and parietal nodes we performed an ANOVA on the

activation scores with the factors ROI (left frontal, right frontal, left parietal, right

parietal) and S-R (cued, irrelevant). This yielded a significant ROI*S-R interaction

($F_{75,3}$ = 4.33, p = 0.007, η^2_p = 0.15), revealing that the declarative activation of

cued S-Rs was significantly above baseline in parietal (Fs > 9.5, ps < 0.005) but

not frontal nodes (Fs < 0.6, ps > 0.28) of the FPN. Another ANOVA but with cued

and uncued as levels of the S-R factor revealed a similar profile difference,

although the interaction in this case was not significant (F = 2, p = 0.13). Last, an

ANOVA with uncued and irrelevant as S-R levels revealed no significant

differences in activation between these two levels (F = 1.22, p = 0.28), and this

was not modulated by the ROI (F < 1, p = 0.78), suggesting that declarative

information of uncued S-Rs was not activated above baseline in any of the FPN

nodes.

Importantly, the lack of declarative activation of cued S-Rs on frontal nodes, and

overall the lower enhancement from baseline compared to procedural information

(as can be seen comparing Figure 6a and 6b) cannot be due to a lower correlation

magnitude of declarative signals with the main task (no significant differences with

the correlation magnitude of procedural signals, t < 1, p = 0.45). Still, given the

overall low signal-to-noise ratio and pattern reliability in prefrontal cortices

(Bhandari et al., 2018), slight differences inherent in the templates could affect the

activation measures. For instance, it could be argued that the amount of signal in

declarative templates is intrinsically lower than that of procedural templates, which

in turn might induce a lack of power to detect the activation of declarative

templates in the same regions during the task. To rule out these concerns, for each

template and region of the FPN, we compared the signal-to-noise ratio (computed

as mean t-value across voxels of the ROI divided by the standard deviation),

informational content (computed as Shannon entropy) and correlationability of the

templates (i.e. the degree to which individual templates correlated with other

templates from the same localizer). This analysis revealed that procedural and

declarative FPN templates did not differ in any of these measures (all $BF_{10} < 0.5$).

Moreover, we tested pattern reliability on each localizer separately by assessing

the stability of patterns of the same S-R pairing in odd and even trials. To do so,

we computed a new GLM with two regressors per S-R pairing, one for odd and

another for even trials. We then estimated the correlation (Spearman's rho)

between each regressor. Finally, we compared the similarity of each specific S-R

pairing (e.g. in odd trials) with its counterpart (in even trials) to the similarity of the

same S-R pairing and the rest of pairings (in even trials). A higher within-pairing

compared to between-pairing correlations would suggest reliability of the patterns

of activity obtained during the localizers. This analysis revealed statistically reliable

patterns in all ROIs and in both localizers (all t > 2.6, all p < 0.05, FDR-corrected

for multiple comparisons), supporting the idea that templates contained S-R

specific information.

Last, higher-order visual regions showed a similar pattern to parietal nodes of the

FPN. As before, the raw semi-partial correlation magnitude of cued pairings with

the main task was of no interest and did not differ (t < 1, p = 0.63) between

declarative (M = 0.018, SD = 0.024) and procedural signals (M = 0.022, SD =

0.023). Compared to the empirical baseline, we found a significant enhancement of

both procedural ($t = 8.80$, $p < 0.001$, Cohen's $d = 1.73$) and declarative ($t = 6.76$, p

< 0.001, Cohen's $d = 1.33$) information of the cued S-R pairing. Crucially, these

signals were significantly stronger than the ones of uncued mappings (procedural:

[$t = 6.19$, $p < 0.001$, Cohen's $d = 1.21$]; declarative: [$t = 5.84$, $p < 0.001$, Cohen's d

$= 1.15$]).

Figure 6. Canonical template tracking procedure results in frontoparietal cortices

and ventral visual cortex. Bars represent the normalized semi-partial correlation

between task data and (**a**) the procedural and (**b**) declarative templates of cued

and uncued S-R pairings. Importantly, raw semi-partial correlation magnitudes of

cued pairings are not informative (and did not differ between procedural and

declarative signals, all *t*s < 1), and therefore results are plotted relative to the

empirical baseline (not-presented S-Rs). Thus, the heights of the bars in panels **a**

and **b** simply reflect the difference from baseline and not necessarily different raw

semi-partial correlations. Error bars denote within-participants s.e.m. Gray

asterisks denote a significant increase from baseline ($p < 0.05$, paired t-test, FDR-

corrected). Black asterisks denote significant differences between cued and

uncued pairings (p < 0.05, paired t-test, FDR-corrected). (**c**) Across-participant

correlation of Inverse Efficiency Scores and procedural activation index in

frontoparietal cortices. (**d**) Correlation of Inverse Efficiency Scores with declarative

activation index in frontoparietal cortices. In **c** and **d**, dots represent individual

participants, thick lines depict the linear regression fit, and asterisks denote

significant Pearson's correlation (p < 0.05). Activation indices are obtained by

subtracting the activation of uncued S-Rs to the activation of cued S-Rs (this can

lead to negative values, as can be seen in the **c** and **d**).

Action-oriented codes support novel instruction implementation

To assess the behavioral relevance of declarative and procedural signals, we

reasoned that if action-oriented representations are crucial during implementation

in control-related regions, and implementation can be conceived as a behavior-

optimized state, then the degree of action-oriented activation should predict the

efficiency of instruction execution. To test this hypothesis, we first converted RTs

and error rates of informative retro-cue trials into a single compound measure

(Inverse Efficiency Scores; IES. IES were obtained by dividing each participant's

mean RT by the percentage of accurate responses (Townsend and Ashby, 1983)).

Then, we derived a template activation index by subtracting the degree of

activation of cued pairings to that of uncued pairings for each region and format

(procedural and declarative). Note that this can lead to a negative activation index

(if activation for uncued pairings is stronger than for cued ones). Finally, we

correlated individual IES with the activation indices on each region of the FPN.

This analysis revealed significant negative correlations in all FPN regions between

IES and procedural activation (all Pearson's rs > -0.475, all ps < 0.02; See Table 2

for individual ROI Pearson's rs, p-value and BF_{10} estimates).

Regarding declarative codes, we considered three hypotheses. First, if procedural

representations are highly dependent on the quality of declarative representations

so that participants with high procedural activation also have high declarative

activation, one could expect that declarative signals of relevant S-Rs should in

principle aid performance as well. Second, declarative activations could be driven

primarily by participants with lower procedural activation. In that case, we should

find the opposite correlation with behavior (higher declarative activation would

predict worse performance). Last, if declarative correlations reflect a residual

activation of this coding format that might support the emergence of procedural

codes but it is not itself related to behavior, we should expect no correlation. This

analysis revealed that IES did not correlate with declarative activation in any region

(all rs < -0.34, all ps > 0.09), although conclusive evidence for the null hypothesis

was only found for the left DLPFC and right parietal ROIs (BF10s < 0.3; for the

remaining ROIs, evidence was inconclusive; see Table 2).

	ROI	r	p	BF_{10}
procedural	ldlpfc	-0.475	0.014	4.203
	rdlpfc	-0.583	0.002	24.887
	lpar	-0.641	< 0.001	88.146
	rpar	-0.605	0.001	39.057
declarative	ldlpfc	0.096	0.639	0.27
	rdlpfc	-0.339	0.09	0.955
	lpar	0.213	0.297	0.408
	rpar	0.113	0.582	0.281

Table 2. Individual ROI Pearson's rs, p-values, and BF_{10} estimates. BF

interpretation is identical to Table 1.

When averaging activation indices across FPN regions, an identical pattern was

found, namely, a significant correlation of IES with procedural ($r = -0.679$, p <

0.001) but not declarative ($r = 0.06$, $p = 0.77$) activation (Fig. 6c-d). Moreover,

these two correlations were significantly different ($z = -3.13$, p = 0.0018). Similar

results were obtained when using RTs (procedural: r = -0.67, p < 0.001;

declarative: r = 0.076, p = .71) and error rates (procedural: r = -0.54, p = 0.004;

declarative: r = -0.019, p = 0.93) as behavioral measures. Also, when removing

participants with negative procedural activation scores (which could reflect the use

of suboptimal strategies to solve the task, or noise in the estimation of the neural

measures) from the analysis, the correlation with IES remained significant (r = -

0.54, p = 0.009), whereas the correlation of declarative activation and IES was not

significant (r = -0.17, p = 0.43). Finally, we tested if the degree of procedural

activation predicted the degree of declarative activation. This correlation was also

not significant (r = -0.17, p = 0.40), and if anything pointed in the direction that

participants with higher procedural activation were the ones with weakest

declarative signals, and vice versa.

Altogether, these results show that the more implementation was governed by

relevant procedural codes in the FPN, the faster and more accurately participants

executed the instruction. In contrast, the strength of declarative signals of the same

S-R association did not predict behavioral performance.

DISCUSSION

In the current study, we report a pervasive effect of novel instruction

implementation across behavioral and neural data. A canonical template tracking

procedure revealed that unique declarative and procedural representations govern

FPN activity during implementation, prior to execution. These representations were

specific to prioritized S-Rs and did not take place for irrelevant mappings. Critically,

our results show that procedural (but not declarative) activation in the FPN

predicted efficient execution of novel instructions.

Frontoparietal flexible coding of novel S-Rs

Previous research has highlighted the important role of the FPN in the

implementation of novel instructions (Bourguignon et al., 2018; Demanet et al.,

2016; González-García et al., 2017a; Hartstra et al., 2011; Muhle-Karbe et al.,

2017; Palenciano et al., 2019a, 2019b; Ruge and Wolfensteller, 2010).

Accordingly, our results show that the FPN represents relevant S-R pairings during

implementation. However, these results remain agnostic regarding the functional

nature of the neural codes underlying this effect. Here, we leveraged a canonical

template tracking approach to approximate to process-pure measures of

procedural and declarative coding formats. This allowed us to later investigate the

unique contribution of each format to instruction implementation.

 In accordance with the serial-coding hypothesis, we observed that implementation

engaged the activation of procedural representations (Brass et al., 2017; Muhle-

Karbe et al., 2017). Interestingly, our results show that, in addition to procedural

codes, some nodes of the FPN preserve relevant declarative information about the

upcoming task.

A first consideration concerns the exact nature of the reactivated signals. In the

declarative localizer, participants had to remember specific S-R associations and

match them to another S-R probe. In contrast, in the procedural localizer,

participants' goal was to execute the correct response associated with a target

stimulus. The different readout from WM thus encouraged different strategies, as

suggested by previous studies (González-García et al., 2020; Liefooghe et al.,

2012; Muhle-Karbe et al., 2017). Therefore, it is conceivable that templates will

contain unique information: a persistent maintenance of the memoranda in the

declarative localizer, and a proactive action-oriented representation in the

procedural localizer. However, procedural and declarative representations likely

share further information, for instance, related to specific perceptual stimulation

and domain-general processes, such as arousal or attention. We took several

measures to reduce the influence of such components. First, template activation

was derived from semi-partial correlations between data from the main task and

the localizers. Thus, our measure reflects unique shared variance between the

task and the representation of an S-R pairing in a given localizer, partialling out the

variance explained by the representation of the same S-R in the remaining

localizer. Importantly, our study was aimed at assessing the presence (or lack

thereof) of procedural and/or declarative signals and not at comparing to what

extent one signal might be more predictive than the other, and therefore we base

our results in activation of templates relative to empirical baselines provided by

not-presented S-Rs. Second, templates were built for S-R pairings rather than

unique mappings, and therefore a contribution of perceptual features to template

activation seems unlikely. Moreover, semi-partial correlations were computed

between data from the retro-cue screen (in the main task), and inter-stimulus

interval (in the localizers), which reduces the likelihood of significant correlations

due to perceptual similarity between templates and specific S-Rs. Therefore,

although other non-mutually exclusive explanations cannot be fully discarded (e.g.

"procedural" templates containing procedural signals but also any other code

present in the procedural localizer and not in the declarative one), we believe it is

the most parsimonious interpretation to consider that our procedure succeeded at

tracking format-specific signals, especially given the validation results in the motor

cortex.

An important aspect then concerns the specific functional significance of each

format. Regarding procedural templates, although the configuration of the

procedural localizer was similar to the main task, the highly action-oriented

encoding format encouraged during this localizer was strategically optimal only

after the selection process elicited by the retro-cue in the main task. Thus, this

localizer allowed us to test whether the selection of an S-R from WM engaged the

same procedural signals elicited by encoding tasks with the intention to implement.

With respect to the declarative templates, an intriguing question is what exactly is

being reactivated, and how is this not present in the procedural localizer (which

necessarily has to contain some declarative information as well (Formica et al.,

2020a)). One possibility is that the specific demands of each localizer encourage

differentiated coding strategies, that is, different readouts from WM could modulate

the specific way in which each format is represented. However, we believe a more

likely, non-mutually exclusive possibility regards the previously mentioned

distinction between the procedural localizer and the main task. Given that the

process of maintenance prior to selection is likely diminished in the procedural

localizer, it is feasible that such maintenance signals are present in the main task

relatively independent from the codes established in the procedural localizer. In

turn, it is possible that declarative codes account at least partially for such

maintenance components, leading to the observed declarative activations in the

main task.

From this standpoint, our results suggest that during novel instruction

implementation, FPN regions contain information about the declarative

memoranda conveyed by the instruction and an independent action-oriented S-R

code that primarily drives task execution.

Heterogeneous S-R coding within the FPN

Although we did not have specific hypotheses for the role of individual FPN

regions, a second important finding concerns the heterogeneity of results within

this network. Frontal nodes showed the implementation profile predicted by the

serial-coding hypothesis, namely, a primarily procedural representation of

instructed content. This is in line with previous studies that propose a crucial role of

the frontolateral cortex in the integration of stimulus and response information into

a task set based on verbal instructions (De Baene et al., 2012; Hartstra et al.,

2012, 2011), as well as in representing task rules (Jackson and Woolgar, 2018;

Loose et al., 2017; Wisniewski et al., 2019; Woolgar et al., 2015) and goals

(Muhle-Karbe et al., 2014).

In contrast, parietal nodes carried both procedural and declarative information in

their patterns of activity. Whereas the role of parietal regions in representing goals

and task set information is widely acknowledged (González-García et al., 2017a;

Jackson and Woolgar, 2018; Muhle-Karbe et al., 2017, 2014; Palenciano et al.,

2019b; Wisniewski et al., 2015; Woolgar et al., 2015), it is unclear what drives such

declarative activation. One possibility is that it reflects a category-specific top-down

selection scheme, driven by increased attention towards the cued S-R (Nobre et

al., 2004; Tamber-Rosenau et al., 2011). The fact that a similar pattern was found

in higher-order visual regions, which usually coordinate with parietal cortices to

represent relevant task dimensions in anticipation of future demands (González-

García et al., 2015; Kuo et al., 2014; Lepsien and Nobre, 2007), further supports

this possibility. This tentative interpretation would be coherent with goal neglect

effects reported in patients with frontal lobe damage (Duncan et al., 1996). These

patients are capable of selecting, maintaining, and remembering task-relevant

information, yet their ability to transform relevant information into goal-driven

actions is impaired. Such dissociation goes at least partially in line with our results

in that (1) goal-oriented representations depends critically on prefrontal cortices

(impaired in goal neglect patients), and (2) the involvement of other control-related

regions, intact in these patients, boosts the declarative representation of specific

task information, such as particular S-R pairings, presumably in coordination with

posterior category-selective regions. However, these results should be interpreted

with caution, since the difference between frontal and parietal regions could partly

reflect a difference in activation magnitude not captured by our method, due to a

generally weaker coding in frontal lobes (Bhandari et al., 2018). Still, the impact of

this alternative interpretation seems relatively limited, given we observed a similar

raw semi-partial correlation magnitude of cued pairings with the main task, and no

differences in terms of signal-to-noise ratio, informational content, and

correlationability of the templates.

Implementation as a selective output gating process

Remarkably, although we found both signals in the FPN during implementation,

only procedural representations predicted efficient behavior and, if anything,

stronger procedural activations did not predict stronger declarative signals. The

fact that implementation is signaled by retro-cues renders this effect relevant to

current debates on information prioritization and WM architecture. In this regard,

our results are consistent with the interpretation of implementation as a particular

instance of output gating mechanisms. Similar to the idea of an input gate that

limits what information enters WM, some computational models propose an

additional gate that determines which pieces of this information will drive behavior

(Chatham et al., 2014). Recent theoretical frameworks suggest a role of

prioritization not only in selecting relevant content from WM but also in reformatting

such content into a "behavior-guiding representational state" (Myers et al., 2017),

analogous to an output gating mechanism. Interestingly, these models propose

that whereas other control-related regions might be involved in attention-driven

representations of relevant content, frontal regions are thought to be especially

important in transferring this content into a state that is optimal for behavior.

Accordingly, our results suggest that an action-oriented representation of novel

instructions dominates activity in frontal cortices and that this representational

format is tightly linked to behavioral efficiency. A limitation of the current study

concerns the lack of specificity on what precise information is captured on each

template: it is possible that part of the correlation with behavior we observe is

driven not only by procedural codes but also by any other code of different nature

that is present in the procedural localizer and not in the declarative one, although

what this code would be specifically remains unknown. This question awaits further

investigation.

Importantly, our results reveal that the neural substrate of instruction prioritization

involves further brain regions, such as category-selective and parietal cortices, and

that procedural and declarative information coexist in these regions. This raises the

question of what the contribution of declarative representations might be. One

possibility is that declarative codes support the generation and maintenance of

procedural codes, but once these are created, they do not directly contribute to

behavior. It should be noted, however, that fMRI data lacks the temporal resolution

to discern the dynamic profile of these two representational formats. Thus, the

conclusions about the dynamics of declarative and procedural codes in the FPN

we can extract from the current dataset are limited. Further research is needed to

elucidate whether, in smaller timescales, a temporal hierarchy between these two

signals can be established or, in contrast, whether both signals are held

simultaneously in these regions. Future studies should employ time-resolved

techniques that can succeed at characterizing the contribution of different brain

regions to separate control and WM processes (Quentin et al., 2019).

Last, the current work relies on a relatively high number of tests and decisions

along the analysis pipeline, which could potentially impact the results and the

conclusions extracted from them (Botvinik-Nezer et al., 2020). As such, the new

method proposed here would benefit from independent conceptual replications and

extension of the current findings in the future.

CONCLUSIONS

In summary, the present study reveals the strong impact of instruction

implementation on frontoparietal regions. We observed that these regions contain

information about prioritized S-R pairings in detriment of the irrelevant ones during

implementation. This information contained two non-overlapping neural codes, one

reflecting the declarative maintenance of task, and another, more pragmatic,

action-oriented coding of the instruction. Importantly, the strength of procedural

activation predicted behavioral performance. Altogether, our results highlight the

contribution of frontoparietal regions to output gating mechanisms that drive

flexible behavior.

Financial interests or conflicts of interest: none declared.

Acknowledgments: C.G.G. and S.F. were supported by the Special Research

Fund of Ghent University BOF.GOA.2017.0002.03. C.G.G. was additionally

supported by the European Union's Horizon 2020 research and innovation

programme under the Marie Sklodowska-Curie grant agreement no. 835767. D.W.

was supported by FWO and the European Union's Horizon 2020 Research and

Innovation Program under the Marie Skłodowska-Curie grant agreement no.

665501. We thank Senne Braem for feedback on previous drafts of the manuscript.

References

Bhandari, A., Gagne, C., Badre, D., 2018. Just above Chance: Is It Harder to

Decode Information from Human Prefrontal Cortex Blood Oxygenation Level-

dependent Signals? J. Cogn. Neurosci. 1–26.

https://doi.org/10.1162/jocn_a_01291

Botvinik-Nezer, R., Holzmeister, F., Camerer, C.F., Dreber, A., Huber, J.,

Johannesson, M., Kirchler, M., Iwanir, R., Mumford, J.A., Adcock, R.A.,

Avesani, P., Baczkowski, B.M., Bajracharya, A., Bakst, L., Ball, S., Barilari, M.,

Bault, N., Beaton, D., Beitner, J., Benoit, R.G., Berkers, R.M.W.J., Bhanji, J.P.,

Biswal, B.B., Bobadilla-Suarez, S., Bortolini, T., Bottenhorn, K.L., Bowring, A.,

Braem, S., Brooks, H.R., Brudner, E.G., Calderon, C.B., Camilleri, J.A.,

Castrellon, J.J., Cecchetti, L., Cieslik, E.C., Cole, Z.J., Collignon, O., Cox,

R.W., Cunningham, W.A., Czoschke, S., Dadi, K., Davis, C.P., Luca, A. De,

Delgado, M.R., Demetriou, L., Dennison, J.B., Di, X., Dickie, E.W.,

Dobryakova, E., Donnat, C.L., Dukart, J., Duncan, N.W., Durnez, J., Eed, A.,

Eickhoff, S.B., Erhart, A., Fontanesi, L., Fricke, G.M., Fu, S., Galván, A., Gau,

R., Genon, S., Glatard, T., Glerean, E., Goeman, J.J., Golowin, S.A.E.,

González-García, C., Gorgolewski, K.J., Grady, C.L., Green, M.A., Guassi

Moreira, J.F., Guest, O., Hakimi, S., Hamilton, J.P., Hancock, R., Handjaras,

G., Harry, B.B., Hawco, C., Herholz, P., Herman, G., Heunis, S., Hoffstaedter,

F., Hogeveen, J., Holmes, S., Hu, C., Huettel, S.A., Hughes, M.E., Iacovella,

V., Iordan, A.D., Isager, P.M., Isik, A.I., Jahn, A., Johnson, M.R., Johnstone,

T., Joseph, M.J.E., Juliano, A.C., Kable, J.W., Kassinopoulos, M., Koba, C.,

Kong, X., Koscik, T.R., Kucukboyaci, N.E., Kuhl, B.A., Kupek, S., Laird, A.R.,

Lamm, C., Langner, R., Lauharatanahirun, N., Lee, H., Lee, S., Leemans, A.,

Leo, A., Lesage, E., Li, F., Li, M.Y.C., Lim, P.C., Lintz, E.N., Liphardt, S.W.,

Losecaat Vermeer, A.B., Love, B.C., Mack, M.L., Malpica, N., Marins, T.,

Maumet, C., McDonald, K., McGuire, J.T., Melero, H., Méndez Leal, A.S.,

Meyer, B., Meyer, K.N., Mihai, G., Mitsis, G.D., Moll, J., Nielson, D.M.,

Nilsonne, G., Notter, M.P., Olivetti, E., Onicas, A.I., Papale, P., Patil, K.R.,

Peelle, J.E., Pérez, A., Pischedda, D., Poline, J.-B., Prystauka, Y., Ray, S.,

Reuter-Lorenz, P.A., Reynolds, R.C., Ricciardi, E., Rieck, J.R., Rodriguez-

Thompson, A.M., Romyn, A., Salo, T., Samanez-Larkin, G.R., Sanz-Morales,

E., Schlichting, M.L., Schultz, D.H., Shen, Q., Sheridan, M.A., Silvers, J.A.,

Skagerlund, K., Smith, A., Smith, D. V., Sokol-Hessner, P., Steinkamp, S.R.,

Tashjian, S.M., Thirion, B., Thorp, J.N., Tinghög, G., Tisdall, L., Tompson,

S.H., Toro-Serey, C., Torre Tresols, J.J., Tozzi, L., Truong, V., Turella, L., van

't Veer, A.E., Verguts, T., Vettel, J.M., Vijayarajah, S., Vo, K., Wall, M.B.,

Weeda, W.D., Weis, S., White, D.J., Wisniewski, D., Xifra-Porxas, A.,

Yearling, E.A., Yoon, S., Yuan, R., Yuen, K.S.L., Zhang, L., Zhang, X., Zosky,

J.E., Nichols, T.E., Poldrack, R.A., Schonberg, T., 2020. Variability in the

analysis of a single neuroimaging dataset by many teams_supl. Nature 1–7.

https://doi.org/10.1038/s41586-020-2314-9

Bourguignon, N.J., Braem, S., Hartstra, E., De Houwer, J., Brass, M., 2018.

Encoding of Novel Verbal Instructions for Prospective Action in the Lateral

Prefrontal Cortex: Evidence from Univariate and Multivariate Functional

Magnetic Resonance Imaging Analysis. J. Cogn. Neurosci. 30, 1170–1184.

https://doi.org/10.1162/jocn_a_01270

Brady, T.F., Konkle, T., Alvarez, G.A., Oliva, A., 2013. Real-world objects are not

represented as bound units: Independent forgetting of different object details

from visual memory. J. Exp. Psychol. Gen. 142, 791.

https://doi.org/10.1037/a0029649

Brady, T.F., Konkle, T., Alvarez, G.A., Oliva, A., 2008. Visual long-term memory

has a massive storage capacity for object details. Proc. Natl. Acad. Sci. 105,

14325–14329. https://doi.org/10.1073/pnas.0803390105

Brass, M., Liefooghe, B., Braem, S., De Houwer, J., 2017. Following new task

instructions: Evidence for a dissociation between knowing and doing.

Neurosci. Biobehav. Rev. 81, 16–28.

https://doi.org/10.1016/j.neubiorev.2017.02.012

Brodeur, M.B., Guérard, K., Bouras, M., 2014. Bank of Standardized Stimuli

(BOSS) phase ii: 930 new normative photos. PLoS One 9, e106953.

https://doi.org/10.1371/journal.pone.0106953

Chatham, C.H., Frank, M.J., Badre, D., 2014. Corticostriatal Output Gating during

Selection from Working Memory. Neuron 81, 930–942.

https://doi.org/10.1016/J.NEURON.2014.01.002

Cole, M.W., Laurent, P., Stocco, A., 2013. Rapid instructed task learning: A new

window into the human brain's unique capacity for flexible cognitive control.

Cogn. Affect. Behav. Neurosci. 13, 1–22. https://doi.org/10.3758/s13415-012-

0125-7

Combrisson, E., Jerbi, K., 2015. Exceeding chance level by chance: The caveat of

theoretical chance levels in brain signal classification and statistical

assessment of decoding accuracy. J. Neurosci. Methods 250, 126–136.

https://doi.org/10.1016/j.jneumeth.2015.01.010

De Baene, W., Albers, A.M., Brass, M., 2012. The what and how components of

cognitive control. Neuroimage 63, 203–211.

https://doi.org/10.1016/j.neuroimage.2012.06.050

Demanet, J., Liefooghe, B., Hartstra, E., Wenke, D., De Houwer, J., Brass, M.,

2016. There is more into 'doing' than 'knowing': The function of the right

inferior frontal sulcus is specific for implementing versus memorising verbal

instructions. Neuroimage 141, 350–356.

https://doi.org/10.1016/j.neuroimage.2016.07.059

Duncan, J., Emslie, H., Williams, P., Johnson, R., Freer, C., 1996. Intelligence and

the frontal lobe: the organization of goal-directed behavior. Cogn. Psychol. 30,

257–303. https://doi.org/10.1006/cogp.1996.0008

Eklund, A., Nichols, T.E., Knutsson, H., 2016. Cluster failure: Why fMRI inferences

for spatial extent have inflated false-positive rates. Proc. Natl. Acad. Sci. 113,

7900–7905. https://doi.org/10.1073/pnas.1602413113

Everaert, T., Theeuwes, M., Liefooghe, B., De Houwer, J., 2014. Automatic motor

activation by mere instruction. Cogn. Affect. Behav. Neurosci. 14, 1300–1309.

https://doi.org/10.3758/s13415-014-0294-7

Fedorenko, E., Duncan, J., Kanwisher, N., 2013. Broad domain generality in focal

regions of frontal and parietal cortex. Proc. Natl. Acad. Sci. 110, 16616–

16621. https://doi.org/10.1073/pnas.1315235110

Formica, S., González-García, C., Brass, M., 2020a. The effects of declaratively

maintaining and proactively proceduralizing novel stimulus-response

mappings. Cognition 201, 104295.

https://doi.org/10.1016/J.COGNITION.2020.104295

Formica, S., González-García, C., Senoussi, M., Brass, M., 2020b. Neural

oscillations dissociate between memorization and proceduralization of novel

instructions. bioRxiv 2020.01.20.912162.

https://doi.org/10.1101/2020.01.20.912162

González-García, C., Arco, J.E., Palenciano, A.F., Ramírez, J., Ruz, M., 2017a.

Encoding, preparation and implementation of novel complex verbal

instructions. Neuroimage 148, 264–273.

https://doi.org/10.1016/j.neuroimage.2017.01.037

González-García, C., Arco, J.E., Palenciano, A.F., Ramírez, J., Ruz, M., 2017b.

Encoding, preparation and implementation of novel complex verbal

instructions. Neuroimage 148, 264–273.

https://doi.org/10.1016/j.neuroimage.2017.01.037

González-García, C., Formica, S., Liefooghe, B., Brass, M., 2020. Attentional

prioritization reconfigures novel instructions into action-oriented task sets.

Cognition 194, 104059. https://doi.org/10.1016/j.cognition.2019.104059

González-García, C., Mas-Herrero, E., de Diego-Balaguer, R., Ruz, M., 2015.

Task-specific preparatory neural activations in low-interference contexts. Brain

Struct. Funct. https://doi.org/10.1007/s00429-015-1141-5

Gorgolewski, K.J., Alfaro-Almagro, F., Auer, T., Bellec, P., Capotă, M.,

Chakravarty, M.M., Churchill, N.W., Cohen, A.L., Craddock, R.C., Devenyi,

G.A., Eklund, A., Esteban, O., Flandin, G., Ghosh, S.S., Guntupalli, J.S.,

Jenkinson, M., Keshavan, A., Kiar, G., Liem, F., Raamana, P.R., Raffelt, D.,

Steele, C.J., Quirion, P.-O., Smith, R.E., Strother, S.C., Varoquaux, G., Wang,

Y., Yarkoni, T., Poldrack, R.A., 2017. BIDS apps: Improving ease of use,

accessibility, and reproducibility of neuroimaging data analysis methods.

PLOS Comput. Biol. 13, e1005209.

Griffin, G., Holub, A., Perona, P., 2006. Caltech-256 object category dataset,

Caltech Technical Report. https://doi.org/10.1021/jp953720e

Hartstra, E., Kühn, S., Verguts, T., Brass, M., 2011. The implementation of verbal

instructions: An fMRI study. Hum. Brain Mapp. 32, 1811–1824.

https://doi.org/10.1002/hbm.21152

Hartstra, E., Waszak, F., Brass, M., 2012. The implementation of verbal

instructions: Dissociating motor preparation from the formation of stimulus–

response associations. Neuroimage 63, 1143–1153.

https://doi.org/10.1016/j.neuroimage.2012.08.003

Hebart, M.N., Görgen, K., Haynes, J.-D., 2015. The Decoding Toolbox (TDT): a

versatile software package for multivariate analyses of functional imaging

data. Front. Neuroinform. 8. https://doi.org/10.3389/fninf.2014.00088

Jackson, J.B., Woolgar, A., 2018. Adaptive coding in the human brain: Distinct

object features are encoded by overlapping voxels in frontoparietal cortex.

Cortex 108, 25–34. https://doi.org/10.1016/J.CORTEX.2018.07.006

JASP Team, 2018. JASP. [Computer software].

Konkle, T., Brady, T.F., Alvarez, G.A., Oliva, A., 2010. Conceptual distinctiveness

supports detailed visual long-term memory for real-world objects. J. Exp.

Psychol. Gen. 139, 558. https://doi.org/10.1037/a0019165

Kuo, B.-C., Stokes, M.G., Murray, A.M., Nobre, A.C., 2014. Attention Biases Visual

Activity in Visual Short-term Memory. J. Cogn. Neurosci. 26, 1377–1389.

https://doi.org/10.1162/jocn_a_00577

Ledoit, O., Wolf, M., 2004. A well-conditioned estimator for large-dimensional

covariance matrices. J. Multivar. Anal. 88, 365–411.

https://doi.org/10.1016/S0047-259X(03)00096-4

Lepsien, J., Nobre, A.C., 2007. Attentional Modulation of Object Representations in

Working Memory. Cereb. Cortex 17, 2072–2083.

https://doi.org/10.1093/cercor/bhl116

Liefooghe, B., De Houwer, J., 2018. Automatic effects of instructions do not require

the intention to execute these instructions. J. Cogn. Psychol. 1–14.

https://doi.org/10.1080/20445911.2017.1365871

Liefooghe, B., Houwer, J. De, Wenke, D., 2013. Instruction-based response

activation depends on task preparation. Psychon. Bull. Rev. 20, 481–487.

https://doi.org/10.3758/s13423-013-0374-7

Liefooghe, B., Wenke, D., De Houwer, J., 2012. Instruction-based task-rule

congruency effects. J. Exp. Psychol. Learn. Mem. Cogn. 38, 1325–1335.

https://doi.org/10.1037/a0028148

Loose, L.S., Wisniewski, D., Rusconi, M., Goschke, T., Haynes, J.D., 2017.

Switch-independent task representations in frontal and parietal cortex. J.

Neurosci. 37, 8033–8042. https://doi.org/10.1523/JNEUROSCI.3656-16.2017

Meiran, N., Cole, M.W., Braver, T.S., 2012. When planning results in loss of

control: intention-based reflexivity and working-memory. Front. Hum.

Neurosci. 6, 104. https://doi.org/10.3389/fnhum.2012.00104

Meiran, N., Pereg, M., Kessler, Y., Cole, M.W., Braver, T.S., 2015a. The power of

instructions: Proactive configuration of stimulus–response translation. J. Exp.

Psychol. Learn. Mem. Cogn. 41, 768–786. https://doi.org/10.1037/xlm0000063

Meiran, N., Pereg, M., Kessler, Y., Cole, M.W., Braver, T.S., 2015b. Reflexive

activation of newly instructed stimulus–response rules: evidence from

lateralized readiness potentials in no-go trials. Cogn. Affect. Behav. Neurosci.

15, 365–373. https://doi.org/10.3758/s13415-014-0321-8

Morey, R.D., 2008. Confidence Intervals from Normalized Data: A correction to

Cousineau (2005). Tutor. Quant. Methods Psychol.

https://doi.org/10.20982/tqmp.04.2.p061

Muhle-Karbe, P.S., Andres, M., Brass, M., Andres, M., 2014. Transcranial

magnetic stimulation dissociates prefrontal and parietal contributions to task

preparation. J. Neurosci. 34, 12481–12489.

https://doi.org/10.1523/JNEUROSCI.4931-13.2014

Muhle-Karbe, P.S., Duncan, J., Baene, W. De, Mitchell, D.J., Brass, M., 2017.

Neural Coding for Instruction-Based Task Sets in Human Frontoparietal and

Visual Cortex. Cereb. Cortex 27, 1891–1905.

https://doi.org/10.1093/cercor/bhw032

Muhle-Karbe, P.S., Duncan, J., Baene, W. De, Mitchell, D.J., Brass, M., 2016.

Neural Coding for Instruction-Based Task Sets in Human Frontoparietal and

Visual Cortex. Cereb. Cortex bhw032. https://doi.org/10.1093/cercor/bhw032

Myers, N.E., Chekroud, S.R., Stokes, M.G., Nobre, A.C., 2018. Benefits of flexible

prioritization in working memory can arise without costs. J. Exp. Psychol.

Hum. Percept. Perform. 44, 398–411. https://doi.org/10.1037/xhp0000449

Myers, N.E., Stokes, M.G., Nobre, A.C., 2017. Prioritizing Information during

Working Memory: Beyond Sustained Internal Attention. Trends Cogn. Sci. 21,

449–461. https://doi.org/10.1016/j.tics.2017.03.010

Nichols, T.E., Das, S., Eickhoff, S.B., Evans, A.C., Glatard, T., Hanke, M.,

Kriegeskorte, N., Milham, M.P., Poldrack, R.A., Poline, J.-B., Proal, E., Thirion,

B., Van Essen, D.C., White, T., Yeo, B.T.T., 2017. Best practices in data

analysis and sharing in neuroimaging using MRI. Nat. Neurosci. 20, 299–303.

https://doi.org/10.1038/nn.4500

Nobre, A.C., Coull, J.T., Maquet, P., Frith, C.D., Vandenberghe, R., Mesulam,

M.M., 2004. Orienting Attention to Locations in Perceptual Versus Mental

Representations. J. Cogn. Neurosci. 16, 363–373.

https://doi.org/10.1162/089892904322926700

Palenciano, A.F., González-García, C., Arco, J.E., Pessoa, L., Ruz, M., 2019a.

Representational organization of novel task sets during proactive encoding. J.

Neurosci. 719–725. https://doi.org/10.1523/JNEUROSCI.0725-19.2019

Palenciano, A.F., González-García, C., Arco, J.E., Ruz, M., 2019b. Transient and

Sustained Control Mechanisms Supporting Novel Instructed Behavior. Cereb.

Cortex 29, 3948–3960. https://doi.org/10.1093/cercor/bhy273

Peirce, J.W., 2007. PsychoPy-Psychophysics software in Python. J. Neurosci.

Methods. https://doi.org/10.1016/j.jneumeth.2006.11.017

Qiao, L., Zhang, L., Chen, A., Egner, T., 2017. Dynamic trial-by-trial recoding of

task-set representations in the frontoparietal cortex mediates behavioral

flexibility. J. Neurosci. 37, 11037–11050.

https://doi.org/10.1523/JNEUROSCI.0935-17.2017

Quentin, R., King, J.-R., Sallard, E., Fishman, N., Thompson, R., Buch, E.R.,

Cohen, L.G., 2019. Differential Brain Mechanisms of Selection and

Maintenance of Information during Working Memory. J. Neurosci. 39, 3728 LP

– 3740. https://doi.org/10.1523/JNEUROSCI.2764-18.2019

Ruge, H., Schäfer, T.A.J., Zwosta, K., Mohr, H., Wolfensteller, U., 2019. Neural

representation of newly instructed rule identities during early implementation

trials. Elife 8. https://doi.org/10.7554/eLife.48293

Ruge, H., Wolfensteller, U., 2010. Rapid formation of pragmatic rule

representations in the human brain during instruction-based learning. Cereb.

Cortex 20, 1656–1667. https://doi.org/10.1093/cercor/bhp228

Tamber-Rosenau, B.J., Esterman, M., Chiu, Y.-C., Yantis, S., 2011. Cortical

Mechanisms of Cognitive Control for Shifting Attention in Vision and Working

Memory. J. Cogn. Neurosci. 23, 2905–2919.

https://doi.org/10.1162/jocn.2011.21608

Townsend, J., Ashby, F.G., 1983. Stochastic modeling of elementary psychological

processes. Cambridge: Cambridge University Press., Cambridge.

Walther, A., Nili, H., Ejaz, N., Alink, A., Kriegeskorte, N., Diedrichsen, J., 2016.

Reliability of dissimilarity measures for multi-voxel pattern analysis.

Neuroimage 137, 188–200.

https://doi.org/10.1016/J.NEUROIMAGE.2015.12.012

Wimber, M., Alink, A., Charest, I., Kriegeskorte, N., Anderson, M.C., 2015.

Retrieval induces adaptive forgetting of competing memories via cortical

pattern suppression. Nat. Neurosci. 18, 582–589.

https://doi.org/10.1038/nn.3973

Wisniewski, D., Forstmann, B., Brass, M., 2019. Outcome contingency selectively

affects the neural coding of outcomes but not of tasks. Sci. Rep. 9, 1–15.

https://doi.org/10.1038/s41598-019-55887-0

Wisniewski, D., Reverberi, C., Tusche, A., Haynes, J.-D., 2015. The Neural

Representation of Voluntary Task-Set Selection in Dynamic Environments.

Cereb. Cortex 25, 4715–4726. https://doi.org/10.1093/cercor/bhu155

Woolgar, A., Afshar, S., Williams, M.A., Rich, A.N., 2015. Flexible Coding of Task

Rules in Frontoparietal Cortex: An Adaptive System for Flexible Cognitive

Control. J. Cogn. Neurosci. 27, 1895–1911.

https://doi.org/10.1162/jocn_a_00827

Yu, Q., Postle, B.R., 2018. Different states of priority recruit different neural codes

in visual working memory. bioRxiv 334920. https://doi.org/10.1101/334920

Zhang, J., Kriegeskorte, N., Carlin, J.D., Rowe, J.B., 2013. Choosing the Rules:

Distinct and Overlapping Frontoparietal Representations of Task Rules for

Perceptual Decisions. J. Neurosci. 33, 11852–11862.

https://doi.org/10.1523/JNEUROSCI.5193-12.2013

1196