Title: Distinct representational structure and localization for visual encoding and

recall during visual imagery

Authors: Wilma A. Bainbridge (1,2), Elizabeth H. Hall (3,2), Chris I. Baker (2)

Affiliations:

1 – Department of Psychology, University of Chicago; Chicago, IL 60637

2 – Laboratory of Brain and Cognition, National Institute of Mental Health; Bethesda, MD 20814

3 – Department of Psychology, University of California Davis; Davis, CA 95616

Corresponding Author: Wilma A. Bainbridge, wilma@uchicago.edu, (773)-702-3189

5848 S University Ave, Beecher Hall 303, Chicago, IL 60637

Running title: Distinct representations for encoding and recall

<u>Abstract</u>

During memory recall and visual imagery, reinstatement is thought to occur as an

echoing of the neural patterns during encoding. However, the precise information represented

in these recall traces is relatively unknown, with previous work investigating broad distinctions

(scenes versus objects) or individual images, rarely bridging these levels of information. Using

ultra-high-field (7T) fMRI with an item-based visual recall task, we conducted an in-depth

comparison of encoding and recall along a spectrum of granularity, from broad stimulus class

(scenes, objects) to object or scene type (natural, manmade) to individual categories (living

room, cupcake). In the scanner, participants viewed a trial-unique item, and after a distractor

task, visually imagined the initial item. During encoding, we observed decodable information at

all levels of granularity in category-selective visual cortex, while during recall, only stimulus

class was decodable. A closer look revealed a segregation between those voxels showing the

strongest effects during encoding and those during visual recall. Finally, in a whole-brain

analysis, we find peaks of encoding-recall similarity in regions anterior to category-selective

cortex. Collectively, these results suggest visual recall is not merely a reactivation of encoding

patterns, displaying a different granularity of information and localization from encoding,

despite some overlap.

Keywords: 7T fMRI, encoding-recall similarity, objects, representational similarity analyses,

scenes

                              <u>Introduction</u>

When we visually recall an object or scene, our memory contains rich object and spatial

information (Bainbridge et al., 2019). During such recollection, our brain is thought to reinstate

neural patterns elicited by the initial perception (McClelland et al., 1995; Buckner and Wheeler,

2001; Tompary et al., 2016; Dijkstra et al., 2019). One common view is that the hippocampus

indexes populations of neocortical neurons associated with that memory (Teyler and Rudy,

2007; Danker and Anderson, 2010; Schultz et al., 2019). Under this view, representations in

hippocampus are largely independent of a memory's perceptual content (Davachi, 2006; Liang

et al., 2013; Huffman and Stark, 2014). In contrast, the neocortex is thought to show sensory

reinstatement, where the same regions show the same representations during recall as during

encoding (Wheeler et al., 2000; Kahn et al., 2004; Staresina et al., 2012; Ritchey et al., 2013; Lee

et al., 2012; O'Craven and Kanwisher, 2000; Dijkstra et al., 2017). However, previous work

looking at decodable information during recall has mainly focused on the broad stimulus class

(Polyn et al., 2005; Johnson et al., 2009; Reddy et al., 2010; LaRocque et al., 2013) or traces for

individual exemplars (Dickerson et al., 2007; Buchsbaum et al., 2012; Lee et al., 2012; Kuhl and

Chun, 2014). The extent to which representations during recall reflect the same information as

during perception, at all its levels of granularity (from individual exemplar up to broad stimulus

class), is unclear. Here, using ultra-high-field (7T) fMRI, we conducted an in-depth investigation

of the content of encoded and recalled representations of objects and scenes across cortex and

hippocampus, assessing the granularity of detail in the representations of individual items.

First, we employed a hierarchically organized stimulus set (Figure 1) with three levels of

granularity from broad stimulus class (scenes/objects) to stimulus type (e.g., natural/manmade

scenes) to individual items (e.g., bedrooms/conference rooms). Prior work comparing encoding

and recall have primarily investigated memory content at opposite ends of this granularity

spectrum. At a broad level, recall of stimulus classes (faces, scenes, objects) have been reported

to reactivate high-level visual regions (Polyn et al., 2005; Johnson et al., 2009; Reddy et al., 2010;

LaRocque et al., 2013) and produce differentiable responses in hippocampus (Ross et al, 2018).

At a finer level, other work has shown reinstatement at the individual image or exemplar level,

with specific items decodable in neocortical regions (Dickerson et al., 2007; Buchsbaum et al.,

2012; Lee et al., 2012; Kuhl and Chun, 2014) and hippocampus (Zeineh et al., 2003; Gelbard-

Sagiv et al., 2008; Chadwick et al., 2010; Wing et al., 2015; Mack and Preston, 2016; Tompary et

al., 2016; Lee et al., 2019). However, it is unclear what information drives discrimination,

whether it is low-level visual content, perceptual categories, or memory strength. For example,

while recalled grating orientation is decodable from early visual cortex (V1-V3), reinstatement

strength but not content is decodable from the hippocampus (Bosch et al., 2014). Our approach

using nested levels of stimulus information reveals what granularity of information is contained

in these regions, and whether reinstatement is simply an echo of the same response from

encoding to recall.

Second, to isolate the activity specific to recall, we adopted a visual imagery task

focusing on recall of individual items without requiring the learning of cue-stimulus associations,

which have commonly been used (e.g., Ganis et al., 2004; Kuhl et al., 2012; Zeidman et al.,

2015a; Jonker et al., 2018). Recalled representations in associative tasks are likely to contain

information not only about the recalled item, but also the cue and the association itself. Further,

there are differences in neocortex when performing an associative versus item-based memory

task (Staresina and Davachi, 2006). In fact, the neural representation of a target may be largely

dependent on what cue it is associated with (Xiao et al., 2017). Here, we employ an item-based

recall task in which participants encode trial-unique images, and following a distractor task,

recall that specific image. This approach allows us to investigate the recall of individual items,

without the learning of associations.

Using this direct recall task and nested stimulus structure, we find striking differences in

the representational structure and spatial localization for visual encoding and recall, suggesting

recall patterns are not just a repetition of patterns during encoding, despite some similarities.

92   Materials and Methods

Participants

Thirty-four adults were recruited for the experiment. All participants were healthy,

right-handed, and had corrected or normal vision. Twelve participants were unable to complete

the experiment due to discomfort in the 7T scanner or scanner malfunction, and their data

were excluded from the study. This level of participant dropout is not unusual for 7T scans,

given that nausea and vertigo occasionally occur, and the bore is more restrictive than the

more standard 3T scanners. The final set of participants included twenty-two adults (fifteen

female). All participants provided consent following the guidelines of the National Institutes of

Health (NIH) Institutional Review Board (ZIA-MH-002909, National Institute of Mental Health

Clinical Study Protocol NCT00001360, 93M-0170), and were compensated for their

participation.

Stimuli

Stimulus images comprised 192 images, 50% objects and 50% scenes, with nested

categorical structure (Figure 1a). The objects were made up of four object types, varying along

two factors known to show differential responses in the brain during perception: 1) small / big

objects (Konkle et al., 2012), and 2) tool / non-tool objects (Valyear et al., 2007; Mahon et al.,

2007; Beauchamp and Martin, 2007). Small versus big object categories were defined based on

prior literature (Konkle et al., 2012; Bainbridge et al., 2015). Tools were defined as objects

commonly grasped by one's hands using a power grip (e.g., Grèzes et al., 2003), although note

that there are multiple ways tools are defined in the field (Lewis, 2006). The other half of the

stimulus images were scenes, varying along two factors shown to elicit differential responses in

the brain: 1) natural / manmade (Park et al., 2011), and 2) open / closed (Kravitz et al., 2011).

Each object or scene type contained three categories, with eight exemplars for each object or

scene category (e.g., <u>small, non-tool objects</u>: bowl, cupcake, flowers; <u>closed, manmade scenes</u>:

bathroom, conference hall, living room). Note that for clarity, we will refer to the most fine-

grained level of categorization (e.g., cupcake, bathroom) as stimulus *category*, the mid-level of

categorization (e.g., big/small objects, open/closed scenes) as stimulus *type*, and the distinction

of objects versus scenes as stimulus *class*. Images were all square 512 x 512 pixel images

presented at 8 degrees visual angle, and objects were presented cropped in isolation on a white

background.

a)

b)

Trial Timing

| 6s Encoding | 1s | 4s Distractor (250ms /16 images) | 1-4s jittered | 6s Visual Imagery | 2s Response High/ Low/ No |

Figure 1. Experimental stimuli and task. (a) Nested structure of stimuli and example images. 192 trial-unique

images were encoded and recalled by participants, arranged under nested structure based on broad stimulus *class*

(object / scene), stimulus *type* (e.g., open / closed or natural / manmade scene), and stimulus *category* (mountains

/ lake). Each stimulus category contained 8 different exemplar images (e.g., 8 different lake photographs). (b) The

timing of each trial. Participants studied an image for 6 s, performed a distractor task requiring detection of an

intact image amongst scrambled images for 4 s, and then after a randomized jitter of 1-4 s, recalled the original

image through visual imagery for 6 s. Finally, they indicated the vividness of their memory with a button press.

In-scanner recall task and post-scan recognition task

Participants first completed a single run of a 7-min 6-sec block-design localizer scan to

identify scene- and object-selective regions. In this localizer, participants viewed blocks of

images of objects, scenes, faces, and mosaic-scrambled scenes and identified consecutive

repeated images. All images used in the localizer were distinct from those used in the main

experiment. Participants then completed eight runs of an item-based memory recall task

requiring visual imagery (Figure 1b). In each trial, participants studied a trial-unique stimulus

image for 6 s. After a 1 s fixation, they performed a distractor task in which they viewed a

stream of 16 quickly presented images (250 ms each), and had to press a button as soon as they

saw the sole intact image in a stream of mosaic-scrambled images. Scrambled and intact target

images were taken from a separate stimulus set, and were chosen to be of the same broader

stimulus class (i.e., object or scene) as the studied image, but of random type and category.

Intact object images were presented as an intact object against a mosaic-scrambled background,

so that participants would have to fixate the object to successfully perform the task (rather

than identify white edges). The distractor task lasted for 4 s total and was followed by a 1-4 s

jittered interval in which participants were instructed to wait and maintain fixation. The word

"RECALL" then appeared on the screen for 6 s, and participants were instructed to silently

visually imagine the originally studied image in as much detail as possible. Finally, following the

"RECALL" phase, participants were given 2 s to press a button indicating the vividness of their

memory as either no memory, low vividness, or high vividness. The next trial then continued

after a 1 s delay. Participants were instructed that the task was difficult, and they should focus

on reporting their vividness truthfully. Trials in which participants indicated "no memory" were

not included in any analyses of the data, except for an analysis classifying response behavior

from brain patterns. However, no results meaningfully change when "no memory" are kept in

all analyses. Each run contained 24 trials, lasting 8 min 38 s, and participants completed 8 runs

total. Each run included three "catch trials" that skipped the recall phase, in order to keep

participants vigilant, to discourage them from pre-emptively recalling the target image, and to

better separate encoding from distractor and recall phases during deconvolution. Each stimulus

category (e.g., guitar, cupcake) was shown once per run, and each stimulus exemplar image

was only used once in the entire experiment, so that there would be no memory effects on

subsequent presentations of the same image.

After the scan, participants performed a post-scan recognition task to test their memory

for the images studied in the scanner. Participants were presented with all 192 images studied

in the scanner randomly intermixed with 192 foil images of the same stimulus categories and

were asked to indicate for each image whether it was old or new. Two participants were unable

to complete the post-scan recognition task due to time constraints.

MRI acquisition and preprocessing

The experiment was conducted at the NIH, using a 7T Siemens MRI scanner and 32-

channel head coil. Whole-brain anatomical scans were acquired using the MP2RAGE sequence,

with 0.7 mm isotropic voxels. Whole-brain functional scans were acquired with a multiband EPI

scan of in-plane resolution 1.2 x 1.2 mm and 81 slices of 1.2 mm thickness (multiband factor=3,

repetition time=2 s, echo time=27 ms, matrix size=160 × 160, field of view=1728 × 1728, flip

angle=55 degrees). Slices were aligned parallel with the hippocampus and generally covered

the whole brain (when they did not, sensorimotor parietal cortices were not included).

Functional scans were preprocessed with slice timing correction and motion correction using

AFNI and surface-based analyses were performed using SUMA (Cox, 1996; Saad and Reynolds,

2012).

FMRI Region of Interest (ROI) Definitions

Key ROIs for early visual cortex, object selective cortex, scene selective cortex, and

hippocampus were determined *a priori* and defined using functional and anatomical criteria

(Figures 3 and 4). Using the independent functional localizer, we identified three scene-

selective regions with a univariate contrast of scenes > objects: PPA (Epstein & Kanwisher,

1998), medial place area (MPA; Silson et al., 2016), and occipital place area (OPA; Dilks et al.,

2013). We localized object-selective regions lateral occipital (LO) and posterior fusiform (pFs)

with a univariate contrast of objects > scrambled images (Grill-Spector et al., 2001). Finally, we

localized early visual cortex (EVC) with a univariate contrast of scrambled images > baseline.

The ROIs were based on activation within areas defined by the literature (e.g., Epstein and

Kanwisher, 1998; Grill-Spector et al., 2001), and were selected first at a threshold of False

Discovery Rate (FDR)-corrected threshold of $q = 0.01$, and then selection criteria were gradually

relaxed (up to $p=0.05$) until any voxels in that area were found. Left and right ROIs were

combined to create bilateral ROIs. Overlapping voxels between scene- and object-selective

regions were discarded. LO, pFs, PPA, and EVC were identified bilaterally in 22 participants, OPA

in 21 participants (20 bilateral), and MPA in 20 participants (17 bilateral). Anatomical ROIs were

localized using FreeSurfer's recon-all function using the hippocampal-subfields-T1 flag (Iglesias

et al., 2015), and then visually inspected for accuracy. This hippocampus parcellation function

splits the hippocampus into the head/body (Hip-HB) and tail (Hip-T), and within the head/body

region further segments the hippocampus into different subfields (dentate gyrus, CA1, CA3, and

subiculum; Iglesias et al., 2015). We did not find meaningful differences across subfields, but

report those results in the Supplementary Information. For the main body of the text, we report

the results from the Hip-HB (with subfields combined) and Hip-T. We also looked at medial

temporal lobe regions perirhinal cortex and parahippocampal cortex (outputted by the same

automatic segmentation pipeline), and include those results in the Supplementary Information.

Whole-Brain Univariate Analyses

We conducted whole-brain univariate contrasts using a generalized linear model (GLM)

that split the trials into four regressors along two factors: 1) encoding / recall, and 2) scenes /

objects. Six additional regressors for movement were also included. Trials in which participants

indicated they had "no memory" for the item were not included in the GLM. We then

performed whole-brain T-contrasts of scenes vs. objects separately during encoding and recall.

All whole-brain images were projected onto the cortical surface using AFNI surface mapper

SUMA (Saad and Reynolds, 2012).

Representational Similarity Analyses and Discrimination Indices

Multivariate analyses were conducted to look at the representations of different

stimulus information during encoding and recall, across brain regions. For these analyses, the

experimental data were first split into two independent halves – even runs and odd runs. For

each split half, a GLM was calculated, modeling separate regressors for each stimulus category

(e.g., cupcake) for the encoding period (6 s boxcar function), distractor period (4 s boxcar), and

recall period (6 s boxcar). Each event (e.g., encoding a cupcake) thus had two resulting beta

estimates: one across even runs, and one across odd runs. Trials in which participants indicated

they had no memory for the image (M=9.31% of trials per participant, SD=8.38%, Min=0%,

Max=35.16%, Median=6.46%) were not included in the GLMs. The estimated motion

parameters from the motion correction were included as six additional regressors.

We then investigated the similarity between different types of stimulus information

during both encoding and recall, using representational similarity analyses (RSA; Kriegeskorte et

al., 2008). For each ROI, we created a representational similarity matrix (RSM) comparing the

similarity of all pairs of stimulus category (e.g., cupcake vs. guitar). Similarity was calculated as

the Pearson's correlation between the voxel values (t-statistic) in an ROI for one category (e.g.,

cupcake) from one half of the runs (e.g., odd runs), with the voxel values for another category

(e.g., guitar) from the other half (e.g., even runs). Specifically, pairwise item similarity was taken

as the average of the correlation with one split (odd runs for item A, even runs for item B) and

correlation with the opposite split (even runs for item A, odd runs for item B). This metric

indicates the similarity in the neural representations of two categories, and importantly,

because the comparisons use separate halves of the data, we can observe a category's

similarity to itself across runs. This self-similarity measure thus shows the degree to which a

given region shows similarity across exemplars within category (i.e., are cupcakes similar to

other cupcakes). These similarity matrices were created in three ways: 1) correlations of the

encoding trials (Encoding RSM), 2) correlations of the recall trials (Recall RSM), 3) correlations

of the encoding trials with the recall trials (Cross-Discrimination RSM). These different

classifications allow us to see what stimulus information exists separately during encoding and

recall, as well as what information is shared between encoding and recall.

From these RSMs, we conducted discriminability analyses, which show the degree to

which each ROI can discriminate the different conditions of class, type, and category (e.g., do

the responses in PPA discriminate natural vs. manmade scenes?). For each comparison of

interest, we computed a discriminability index D, calculated as the difference of the mean

across-condition correlations (e.g., scenes with objects) from mean within-condition

correlations (e.g., scenes with other scenes; Kravitz et al., 2011; Cichy et al., 2014; Harel et al.,

2013; Harel et al., 2014; Henriksson et al., 2015). The intuition behind this index is that if an ROI

contains information about that comparison, then within-condition similarity should be higher

than across-condition similarity (e.g., if the PPA *does* discriminate natural vs. manmade scenes,

then natural scenes should be more similar to other natural scenes than manmade scenes).

Significant discriminability was determined by a two-tailed t-test comparing discrimination

indices across participants versus a null result of 0. Type discriminability was only computed

within same-class items (e.g., only scenes were used for the natural vs. manmade comparison),

and category discriminability was only computed within same-type items (e.g., when looking at

the discriminability of living rooms, they were only compared to other closed, manmade

scenes). For the encoding and recall discrimination indices, all statistics reported are FDR-

corrected within each ROI at a value of $q < 0.05$ unless noted otherwise. Refer to Figure 2 for a

depiction of these discrimination indices and to see example RSMs.

Figure 2 – Calculating information discriminability from representational similarity matrices. (Left) Depictions of the cells of the representational dissimilarity matrices (RSMs) used to calculate discrimination indices for key regions of interest (ROIs). The RSMs represent pairwise Pearson's correlations of stimulus groupings calculated from ROI voxel t-values, compared across separate run split halves (odd versus even runs). These depictions show which cells in the matrices are used in the calculation of discriminability of different properties, with green cells indicating within-condition comparisons, which are compared with grey cells indicating across-condition comparisons. For all discriminability calculations except discrimination of individual categories (i.e., individuation), the diagonal was not included. All operations were conducted on the lower triangle of the matrix, although both sides of the diagonal are shown here for clarity. (Right) Examples of encoding and recall RSMs from the data in the current study, specifically the rank-transformed average RSM for the parahippocampal place area (PPA), lateral occipital (LO), and the hippocampus head and body. Blue cells are more similar, while red cells are more dissimilar.

ROI-to-ROI similarity analysis

We investigated ROI-to-ROI correlations to assess similarity between ROI representations separately during encoding and recall. For each participant, we constructed an RSM for each ROI, as described in the previous section. We then constructed an ROI-to-ROI

similarity matrix by conducting secondary correlations between the RSMs for each pair of ROIs.

Specifically, we correlated the ROI RSM calculated with half of the runs with the one created

using the other half of the runs, so we could also look at an ROI's similarity to itself across runs

and avoid any common fluctuations within runs (Henriksson et al., 2015). We additionally

conducted multidimensional scaling (MDS), to visualize the similarity structure of these ROIs in

two dimensions. This ROI-to-ROI similarity analysis was conducted separately for encoding trials

and recall trials.

Discrimination-based Searchlight Analyses

We also conducted discriminability analyses using spherical searchlights (3-voxel radius)

in two ways. First, we conducted discriminability analyses (as described above) for searchlights

centered on voxels in the ROIs. For each searchlight, we obtained a scene-object

discriminability metric during encoding and one during recall, allowing us to examine the

relationship between encoding and recall information in these ROIs.

Second, we conducted discriminability analyses in searchlights iteratively moved

through each individual's brain, to examine ability to discriminate information outside of our

pre-defined ROIs. Group maps were combined with a two-tailed t-test comparing group

discrimination indices versus no discrimination (0). Group maps were thresholded at $p < 0.01$

uncorrected for visualization purposes, however we also provide unthresholded maps. We

conducted these searchlights looking at both discriminability of information within memory

process type (encoding or recall), as well as ability to cross-discriminate (e.g., correlating

encoding and recall patterns).

Modeling behavior

We conducted analyses to relate fMRI activity to behavioral measures of reported recall

vividness and post-scan recognition performance. An additional GLM was conducted to obtain

an estimate for each trial for each run, so that they could be compared with trial-by-trial

behavior measures. In this case, no memory trials were not removed, so that we could look at

ability to classify memory vividness responses. We employed support vector machines (SVMs)

to classify recall vividness responses (no memory, low vividness, high vividness) from ROI

patterns during encoding or recall. These SVMs were conducted on all pairs of the three classes,

and then classification accuracies were averaged, although we also report the results of

classifying just low versus high vividness trials. We also used SVMs to measure the ability to

classify later successful recognition versus failed recognition (hits vs. misses) from ROI patterns

during encoding or recall. All SVMs were conducted using a leave-one-run-out approach.

<u>Results</u>

In the following sections, we present several analyses elucidating the relationship

between representations elicited during encoding and recall. First, we investigate what

stimulus-based content can be discriminated from encoding and recall response patterns in

object- and scene-selective visual ROIs and the hippocampus. Second, we calculate the degree

to which these patterns can be used to decode memory strength and performance for

individual items. Third, we analyze the relationships between these ROIs to see how they

change during encoding and recall. Finally, we conduct searchlight analyses to investigate the

distribution of voxels showing the strongest discrimination during encoding, recall and between

these two phases, both within and outside the ROIs.

Decoding stimulus content from scene- and object-selective visual regions and hippocampus

What aspects of a visual memory are represented in scene- and object-selective areas

and hippocampus during encoding and recall? We asked this question by discriminating

stimulus information from the patterns of blood oxygen level dependent (BOLD) responses at

various scales of stimulus granularity, ranging from broad stimulus class (scenes, objects), to

stimulus type (e.g., natural/manmade scene, big/small object), to specific stimulus category

(e.g., cupcake, guitar). This discrimination was conducted across independent exemplars, never

including the same images in the training and testing sets of the decoding model. This allowed

us to see what levels of information are represented in these regions, separate from an ability

to distinguish identical images.

Scene- and object-selective ROIs: Detailed information during encoding, limited information

during recall

We investigated discriminability in object-selective regions LO and pFs and scene-

selective regions PPA, MPA, and OPA (Figure 3). Analyses for other regions including early visual

cortex, perirhinal cortex, and parahippocampal cortex (separate from the PPA) are reported in

the Supplementary Information. All object- and scene-selective regions could discriminate

broad stimulus class (objects vs. scenes) during encoding (LO: $t(21)=5.99$, $p=6.00 \times 10^{-6}$; pFs:

$t(21)=5.98$, $p=6.24 \times 10^{-6}$; PPA: $t(21)=7.08$, $p=5.50 \times 10^{-7}$; MPA: $t(19)=6.50$, $p=3.18 \times 10^{-6}$; OPA:

$t(20)=7.10$, $p=9.34 \times 10^{-7}$). Object type of tool/non-tool could be discriminated in object-

selective regions LO ($t(21)=3.59$, $p=0.002$), and pFs ($t(21)=2.69$, $p=0.014$), and object size did not

show significant discriminability in any region. Individual object categories could be

discriminated in all regions except MPA (MPA: $p=0.085$; LO: $t(21)=5.22$, $p=3.61 \times 10^{-5}$; pFs:

$t(21)=5.29$, $p=3.00 \times 10^{-5}$; PPA: $t(21)=4.10$, $p=5.10 \times 10^{-4}$; OPA: $t(19)=4.44$, $p=2.80 \times 10^{-4}$). Scene

types could also be decoded from most regions, including open/closed (LO: $t(21)=4.37$, $p=2.70 \times$

10^{-4}; pFs: $t(21)=3.32$, $p=0.003$; PPA: $t(21)=4.08$, $p=5.36 \times 10^{-4}$) and natural/manmade (LO:

$t(21)=4.29$, $p=3.26 \times 10^{-4}$; pFs: $t(21)=3.13$, $p=0.005$; PPA: $t(21)=3.65$, $p=0.001$; MPA: $t(19)=4.16$,

$p=5.33 \times 10^{-4}$). Finally, individual scene categories could also be discriminated in scene-selective

regions PPA ($t(21)=3.60$, $p=0.002$) and OPA ($t(20)=3.55$, $p=0.002$). Overall, these results

confirmed the findings of prior studies (e.g., Valyear et al., 2007; Walther et al., 2009; Park et al.,

2011; Kravitz et al., 2011; Troiani et al., 2012), in which responses in scene- and object-selective

regions can be used to distinguish various levels of information about visually presented scenes

and objects.

During recall, all high-level visual regions could distinguish recalled objects from scenes

(LO: $t(21)=3.44$, $p=0.002$; pFs: $t(21)=2.66$, $p=0.015$; PPA: $t(21)=4.27$, $p=3.40 \times 10^{-4}$; OPA:

$t(20)=3.31$, $p=0.004$), although MPA did not pass FDR correction (MPA: $t(19)=2.54$, $p=0.020$). No

region showed significant discriminability for object type (big/small, tool/non-tool) nor scene

type (open/closed, natural/manmade) during recall. No region showed discrimination of object

category nor scene category. We also compared stimulus discriminability between encoding

and recall for the cases in which there was significant information during encoding. For all ROIs,

encoding showed significantly higher discriminability of stimulus class than recall (all $p < 0.001$).

For stimulus type, encoding discriminability was again significantly higher than recall

discriminability for all ROIs and comparisons, except a marginal difference for tool

discriminability in LO ($t(21)$=1.99, p = 0.058). Finally, for stimulus category, PPA showed no

significant difference between encoding and recall for object individuation (p = 0.053) and

scene individuation (p = 0.295). Similarly, OPA did not show a significant difference for scene

individuation (p = 0.286). This indicates that encoding and recall discriminability of individual

categories may be at similar levels in these regions. However, pFs and LO show significantly

higher discriminability of object category during encoding compared to recall (both p < 0.005).

Overall, these results reveal that while multiple regions maintain information about broad

stimulus class during recall, and there may be some evidence for similar levels of information

between encoding and recall for fine-grained stimulus category, we find no evidence for

decoding intermediate stimulus information during recall.

To investigate which regions show a shared neural representation during encoding and

recall, we conducted a cross-discrimination analysis identifying the degree to which a region

shows similar patterns between encoding and recall. The only significant cross-discrimination

was for stimulus class (objects versus scenes), which was found in pFs ($t(21)$=2.94, p=0.008),

PPA ($t(21)$=2.83, p=0.010), and MPA ($t(19)$=3.99, p=7.89 × 10^{-4}). Significant cross-discrimination

did not emerge for any finer-grained stimulus information in scene- and object-selective ROIs.

Figure 3 – Information discriminability in scene- and object-selective regions. Discriminability for scene- and

object-selective regions of interest (ROIs) for each stimulus property was calculated from the RSMs (as in Figure 2).

ROIs correspond to those shown in the upper left; shown here are probabilistic ROIs chosen as voxels shared by at

least 12% participants, however analyses were conducted in individually localized ROIs. Bar graphs indicate mean

discrimination index for different comparisons across ROIs, are split by broad stimulus class, and show three levels

of discrimination: 1) broad discrimination of stimulus *class* (objects versus scenes), 2) mid-level discrimination of

stimulus *type* (objects: big/small, tools/non-tools; scenes: open/closed, natural/manmade), and 3) fine-grained

discrimination of stimulus *category* (object and scene individuation). The y-axis represents the average

discrimination index (*D*), which ranges from -1 to 1 and can be compared to a null level of 0. Pink bars indicate

discriminability during encoding trials, blue bars indicate discriminability during recall trials, and hatched purple

bars indicate cross-discriminability (i.e., there is a shared representation between encoding and recall). Error bars

indicate standard error of the mean. Asterisks (*) indicate significance at a FDR corrected level of *q*<0.05.

Hippocampus Shows Stimulus Class Information During Encoding

We conducted the same analyses in hippocampal ROIs (Figure 4). During encoding, the

Hip-HB showed significant discrimination of objects versus scenes ($t(21)=4.16$, $p=4.44 \times 10^{-4}$)

However, the Hip-HB showed significant sensitivity to no other information during encoding.

Interestingly, this pattern in the Hip-HB during encoding was similar to the scene- and object-

selective visual areas during recall, in their specific ability to discriminate broad stimulus class.

The Hip-T showed no significant discriminability at any level during encoding. During recall,

neither hippocampal region showed significant discriminability of any level of information ($q >$

0.05), and was significantly lower than encoding discriminability for stimulus class ($t(21)=3.84$,

$p=9.42 \times 10^{-4}$). No significant cross-discrimination between encoding and recall was observed

($q > 0.05$). No meaningful differences were found when looking at individual hippocampal

subfields (Supplementary Information). Overall, the only information that emerged in the

hippocampus was a difference between objects and scenes during encoding, and we found no

evidence for discriminability of intermediate information during encoding, nor any level of

information during recall.

Figure 4 – Information discriminability in the hippocampus. Discriminability for hippocampal ROIs of each

stimulus property was calculated from the RSMs. On the left is an example participant's 7T functional scan overlaid

with their automatically segmented hippocampal regions (head/body and tail). Bar graphs are displayed in the

same manner as Figure 3, and indicate mean discrimination index for comparisons of different levels of stimulus

information (class, type, and category for objects and scenes). Pink bars indicate discriminability during encoding

trials, blue bars indicate discriminability during recall trials, and hatched purple bars indicate cross-discriminability

(i.e., there is a shared representation between encoding and recall). Error bars indicate standard error of the mean.

Asterisks (*) indicate significance at a FDR corrected level of $q<0.05$.

Relationship of fMRI response patterns to memory behavior

In contrast to the specific visual content of a stimulus, to what degree do these regions

represent information about the strength of the memory? We examined the ability to use the

voxel values in each region to decode participant-reported memory vividness, a rating provided

by participants after each recall trial in the scanner (Figure 5a). We also examined the ability to

decode recognition success for each image based on a post-scan old/new recognition task

(Figure 5b).

FMRI response patterns and memory vividness

On average, participants reported 'high vividness' on 60.8% of trials (SD=16.9%), 'low

vividness' on 29.9% of trials (SD=12.8%), and 'no memory' on 9.31% of trials (SD=8.38%). We

tested the ability to classify this memory vividness from patterns in the different ROIs during

encoding and recall. In only this analysis, we included trials rated as "no memory" in the

classifier. Encoding patterns from all scene- and object-selective regions were predictive of

recall vividness: LO (M=62.28%, $t(21)=5.43$, $p=3.09 \times 10^{-5}$), pFs (M=60.90%, $t(21)=4.90$, $p=9.99 \times$

10^{-5}), PPA (M=57.11%, $t(20)=4.99$, $p=8.12 \times 10^{-5}$), MPA (M=55.72%, $t(19)=2.40$, $p=0.027$), and

OPA (M=57.51, $t(20)=4.31$, $p=4.20 \times 10^{-4}$). In contrast, within the hippocampus, (Hip-HB and

Hip-T), encoding patterns could not be used to classify recall vividness (both $p>0.05$). Recall

patterns from all scene- and object-selective regions were also predictive of recall vividness: LO

(M=56.43%, $t(21)$=4.22, p=4.61 × 10^{-4}), pFs (M=55.83%, $t(21)$=3.36, p=0.003), PPA (M=55.63%,

$t(19)$=2.63, p=0.016), MPA (M=57.50%, $t(19)$=3.06, p=0.007), and OPA (M=58.26%, $t(20)$=3.85,

p=0.0012). Additionally, the hippocampus showed memory vividness decodability from

patterns during recall, in both the Hip HB (M=53.34%, $t(21)$=2.76, p=0.012) and Hip T

(M=54.26%, $t(21)$=2.49, p=0.022). While hippocampus showed decodability during recall and

not during encoding, there was no significant difference in classification accuracy between

encoding and recall (both regions: p>0.05).

If we look specifically at the ability to classify low vividness from high vividness trials, a

subset of these ROIs shows above-chance classification accuracy. Specifically, during memory

encoding, patterns in the pFs (M=62.35%, $t(21)$=2.82, p=0.013) and OPA (M=58.70%, $t(20)$=4.90,

p=2.33 × 10^{-4}) can differentiate low and high vividness trials. During recall, pFs (M=57.22%,

$t(21)$=2.15, p=0.048), PPA (M=61.07%, $t(19)$=2.85, p=0.012) , and OPA (M=59.20%, $t(20)$=2.19,

p=0.046) patterns can differentiate low vividness from high vividness trials. The hippocampus

did not show ability to differentiate low vividness or high vividness trials during encoding nor

recall (both regions: p>0.10).

These results indicate that scene- and object-selective regions contain information

about memory vividness during both encoding and recall. In contrast, the hippocampus only

contains information about memory vividness during the recall period, when classifying all trial

types (high vivid, low vivid, and no memory). However, it is less clear whether the hippocampus

shows decoding of more fine-grained differences in vividness (differentiating high versus low

vividness).

 FMRI response patterns and subsequent memory

Encoding patterns from scene- and object-selective regions were predictive of later

successful recognition, from the LO (M=53.08%, *t*(21)=2.31, *p*=0.032), PPA (M=52.08%,

t(21)=2.29, *p*=0.033), and OPA (M=53.35%, *t*(21)=3.86, *p*=0.001). MPA, pFs, Hip HB and Hip T

did not show significant decodability of successful recognition (all *p*>0.10). No recall patterns

from any ROI were predictive of later successful recognition (all *p*>0.10). These results confirm

prior findings demonstrating an ability to predict subsequent memory performance from visual

areas (Brewer et al., 1998), and show little ability to decode later recognition success from

neural information during the recall period.

Figure 5 – Relationship of fMRI response patterns to behavior. (a) Classification accuracies for predicting

subjectively reported recall vividness, based on patterns of encoding (pink) and recall (blue) from the ROIs. Chance

level is 50%, and marked with the dashed grey line. Asterisks indicate a significantly higher classification accuracy

than chance (*p* < 0.05). In scene- and object-selective visual regions, patterns during both encoding and recall can

significantly predict the vividness of recall. In the hippocampus, only patterns during recall can significantly predict

memory vividness. (b) Classification accuracies for predicting post-scan memory performance in a recognition task

from patterns of encoding (pink) and recall (blue) from the ROIs. Only patterns from some scene- and object-

selective regions during encoding (LO, PPA, OPA) show significant ability to predict later recognition success. No

patterns during recall were linked with recognition success.

Region-to-region similarity during encoding and recall

Beyond investigating the stimulus content representations within individual regions, an

equally important question is how these visual and memory regions relate to each other in their

representations during encoding and recall. While two regions may both contain information

about a stimulus property, they may represent that information differently. The relationships

between regions may also change meaningfully based on memory task (e.g., encoding versus

recall). Thus, understanding the interactions among regions provides additional information on

how stimulus representations are instantiated in the brain.

We looked at correlations of the RSMs between each pair of ROIs, separately for objects

and scenes during both encoding and recall (Figure 6). These correlations were conducted using

separate halves of the data, so diagonal values indicate an ROI's similarity to itself across runs

of independent stimuli. We also conducted MDS to visualize the similarities across regions

(Figure 6). For encoding objects and scenes, all regions were significantly self-correlated across

runs (all $p < 0.001$), indicating that these regions show consistent patterns across runs and

exemplars. Within the MDS for encoding both objects and scenes, scene- and object-selective

regions are grouped together, with object regions LO and pFs similar to each other for object

encoding, and scene regions PPA, MPA, OPA similar to each other for scene encoding.

Meanwhile, hippocampal regions are highly dissimilar from all scene- and object-selective

regions.

During recall, the representational structure of these regions transforms. All ROIs are

still significantly correlated with themselves for recalling objects and scenes (all $p < 0.05$).

However, scene- and object-selective regions are more dissimilar from each other, and these

regions and hippocampus are more similar (Figure 6). To quantify cortical-hippocampal

similarity, we compared the mean ranked correlation coefficient of the scene- and object-

selective ROIs (pFs, LO, PPA, MPA, OPA) with the hippocampal ROIs (Hip-HB, Hip-T) between

encoding and recall. In a 2-way ANOVA for stimulus class (object/scene) and memory process

(encoding/recall), there was a significant difference in cortical-hippocampal similarity between

encoding and recall ($F(1,84)$=5.45, p=0.030), but no main effect of stimulus category

($F(1,84)$=0.002, p=0.961) nor an interaction ($F(1,84)$=0.76, p=0.394). A post-hoc t-test indicated

that cortical-hippocampal similarity was significantly higher during recall than encoding ($t(43)$ =

2.59, p=0.013). Thus, across both objects and scenes, representations in scene- and object-

selective cortex and hippocampus are more similar during recall than encoding.

Figure 6 – Comparison of stimulus representations between regions. Matrices showing Pearson correlations

between the RSMs of every ROI pair, using separate halves of the data. Matrices for encoding and recall are shown

separately for objects and scenes, and are ranked for visualization purposes. In the matrices, dark blue indicates

the most similar ROIs, while white indicates the most dissimilar ROIs. ROIs can be conceptually divided into four

groups as indicated by the colored squares – early visual areas (red: EVC), object-selective areas (orange: LO, pFs),

scene-selective areas (green: PPA, MPA, OPA), and hippocampus (blue: Hip-HB, Hip-T). Next to the encoding and

recall RSMs are multidimensional scaling (MDS) plots, which transform a given RSM into a two-dimensional

representation where shorter distances indicate higher similarity. With this, one can visualize which ROIs have

similar representations to another. During encoding, while hippocampal regions (blue) are very distinct in their

representations from visual regions, they become more similar to visual regions during recall.

Direct comparison of encoding and recall discriminability in scene- and object-selective ROIs

and hippocampus

If we directly compare the ability to discriminate information during encoding and recall,

do we find a correlation or an overlap in discriminability? We conducted a discriminability

analysis in 3-voxel radius spherical searchlights throughout the scene- and object-selective and

hippocampal ROIs to see whether there were differences in which searchlights could best

discriminate encoding information versus recall information. Given that these regions only

showed discriminability for broad stimulus class (scenes, objects) during recall, we focused on

this specific comparison in our searchlight. MPA, LO, pFs, and Hip-HB showed significant

correlations between encoding and recall discriminability (MPA: Mean Spearman's rank

correlation, ρ=0.121, Wilcoxon signed rank test: Z=2.22, p=0.026; LO: ρ=0.100, Z=2.94, p=0.003;

pFs: ρ=0.163, Z=2.26, p=0.024; Hip-HB: ρ=0.070, Z=2.52, p=0.012). Scene-selective regions PPA

and OPA did not show a significant correlation between encoding and recall discriminability,

nor did Hip-T (PPA: ρ=0.019, Z=0.18, p=0.858; OPA: ρ=0.020, Z=0.18, p=0.858; Hip-T: ρ=-0.009,

Z=-0.41, p=0.685. Thus, we found mixed results—while some regions showed similarities

between encoding and recall, others did not.

To investigate this further, we focused on the top 10% of searchlights that showed

encoding discriminability and compared their overlap with the top 10% of searchlights that

showed recall discriminability within each ROI (Figure 7). If the same voxels perform encoding

and recall discrimination, we should find significantly higher overlap than chance. Conversely, if

encoding and recall information comprise distinct sets of voxels, we should find lower overlap

than chance. PPA and OPA showed significantly lower overlap of these encoding-recall

searchlights than a permuted chance level of 10% (PPA: M=4.90%, Wilcoxon rank sum test:

Z=3.61, p=3.06 × 10^{-4}; OPA: M=6.74%, Z=3.44, p=5.79 × 10^{-4}). All other regions showed no

significantly different overlap than predicted by chance (MPA: M=12.3%; LO: M=14.3%; pFS:

M=19.0%; Hip-HB: M=15.9%; Hip-T: M=15.6%; all p > 0.10). Importantly, no region showed

significantly higher overlap than chance, indicating that for none of these ROIs were the top

voxels for encoding the same as the top voxels for recall.

These results suggest a segregation in late visual cortex between voxels that maintain

encoding information and those that maintain recall information.

Figure 7 – Comparing encoding and recall discriminability within the ROIs. (a) Example ROIs from a single

example participant, where each point represents a voxel-centered spherical searchlight in that ROI and is plotted

by the object/scene discrimination index during encoding (x-axis) versus the object/scene discrimination index

during recall (y-axis). The top 10% of searchlights showing recall discriminability are colored in blue, while the top

10% of searchlights showing encoding discriminability are colored in red. Searchlights that overlap between the

two (those that demonstrate both encoding and recall discrimination) are colored in purple. Note that while the

PPA and LO shows no overlap for this participant, Hip-HB show greater overlap. (b) Histograms for these ROIs

showing participant distribution of the percentage of overlap between the top 10% of encoding discriminating and

top 10% of recall discriminating voxels. The orange arrow represents the participant's data plotted in (a), while the

dashed grey line shows the mean overlap percentage. Note that in general, there is low overlap across participants

and regions in the top voxels for encoding and those for recall.

Whole-Brain Investigation of Encoding and Recall Effects

Given the differences we observed between encoding and recall within ROIs, we

conducted follow-up analyses at the whole-brain level. Looking at a group univariate contrast of

objects versus scenes during encoding (Figure 8), we confirm that stimulus class selectivity is

strongest in ROIs predicted by the literature: LO and pFs show high sensitivity to objects, while

PPA, MPA, and OPA show high sensitivity to scenes (e.g., Epstein and Kanwisher, 1998; Grill-

Spector et al., 2001). However, a group univariate contrast of objects versus scenes during

recall reveals that recall scene-selectivity is strongest in areas anterior to PPA and MPA, and

recall object-selectivity is strongest in areas anterior to LO and in early visual cortex. Rather

than the peaks of recalled stimulus class overlapping with those of encoding, the greatest

scene-object differences occur in a spatially separate set of voxels largely anterior to those

during encoding.

A searchlight analysis looking at information discriminability across the brain replicates

this spatial separation (Figure 9). During encoding, scenes and objects are most discriminable in

the same regions identified by the independent perceptual localizer (LO, pFS, PPA, MPA, OPA).

However, during recall, peak discriminability occurs in voxels anterior to these regions,

especially for the PPA, MPA, and left LO and OPA. Next, we employed a cross-discrimination

searchlight to identify regions with shared stimulus representations between encoding and

recall. Again, areas anterior to those most sensitive during encoding showed highest similarity

between encoding and recall representations.

These results suggest a spatial separation between encoding and recall with strongest

reinstatement occurring outside of scene- and object-selective regions typically localized in

visual tasks.

Figure 9 – Whole-brain discrimination analyses for encoding, recall, and cross-decoding of information. Whole-brain searchlight analyses investigating discrimination of objects versus scenes during encoding (top left), recall (top right), and cross-discrimination (bottom). Brighter yellows indicate higher discrimination indices. Outlined ROIs are defined using independent stimuli in an independent localizer run. All maps are thresholded at $p<0.01$ uncorrected, and unthresholded maps are also shown. The cross-discrimination searchlight shows regions that have a shared representation between encoding and recall.

Discussion

In this work, we conducted an in-depth investigation of how and where recalled memory content for complex object and scene images is represented in the brain. First, we observed a striking difference in the granularity of representations in cortex between encoding and recall. While information in cortex during encoding reflected multiple levels of information, during recall we observed clear evidence for coarse level information (objects versus scenes)

only. Second, a direct comparison between encoding and recall discriminability within cortical

and hippocampal ROIs found mixed results. Further, there was a segregation between the

subregions containing the most information during encoding and those during recall. Third,

there was an increase in the similarity between hippocampal and cortical regions from

encoding to recall. Finally, a whole brain comparison of encoding and recall discriminability

revealed that the peaks for recall as well as the strongest encoding-recall similarity were

spatially anterior to the peaks during encoding. Collectively, our results reveal key spatial and

representational differences between encoding and recalling stimulus content.

The ability to decode scenes versus objects during recall is consistent with several

findings showing broad stimulus class decodability during recall (Polyn et al., 2005; Reddy et al.,

2010; Boccia et al., 2019; O'Craven and Kanwisher, 2000). Additionally, we replicate several

findings observing discriminability of different levels of information during perception (e.g.,

Mahon et al., 2007; Walther et al., 2009 Kravitz et al., 2011; Park et al., 2011). We also find a

significant ability to decode memory vividness and future recognition success from many

cortical regions as shown in prior work (Brewer et al., 1998; Wais, 2008; Dijkstra et al., 2017;

Fulford et al., 2018). However, at face-value our findings appear to be at odds with prior work

that reported fine-grained information during recall as well as encoding-recall similarity in

category-selective cortex. We discuss each of these issues in turn in the paragraphs below.

In terms of fine-grained information during recall, prior work has reported an ability to

decode individual items (Chadwick et al., 2010; Lee et al., 2012; Kuhl and Chun, 2014; Wing et

al., 2015; Mack and Preston, 2016; Tompary et al., 2016). However, in these studies, the

information decoded could reflect image-specific features and not necessarily a general

representation of the items. In our study, we specifically tested for generalizable stimulus

content representations and not individual images, never comparing encoding or recalling an

image with itself. Instead, we compared representations across exemplars and focused on

stimulus category, to minimize the contribution of image-specific features. The resulting

inability to detect fine-grained information during recall suggests that imagery-based

representations in scene- and object-selective visual areas may not contain more abstracted or

generalized levels of information. Instead, participants may be recalling limited image features,

sufficient for image-level classification or classification at the broad level of scenes versus

objects (given large differences between their features), but not more abstracted classifications

like base-level category (e.g., living room), or properties (e.g., natural or manmade).

In terms of encoding-recall similarity, our results also appear to be inconsistent with

some previous findings of sensory reinstatement, in which the neurons or voxels sensitive

during encoding have been reported to show the same patterns during recall (Wheeler et al.,

2000; Danker and Anderson, 2010; Buchsbaum et al., 2012; Johnson and Johnson, 2014; Schultz

et al., 2019). Within scene- and object-selective cortex, we observed limited overlap between

the sub-regions with peak encoding and those with peak recall information, with the strongest

encoding-recall similarity in more anterior regions. These results are not in conflict with many

studies reporting encoding-recall similarity in areas outside of category-selective cortex such as

the medial temporal lobe (e.g., Tompary et al., 2016; Schultz et al., 2019). However, some

studies do report encoding-recall similarity within scene- and object-selective cortex (e.g.,

O'Craven and Kanwisher, 2000; Johnson and Johnson, 2014) which may be attributable to key

methodological differences from the current study. First, as noted above, we targeted

recollection of stimulus content rather than individual items. While scene- and object-selective

regions may maintain item-specific visual information during both encoding and recall, our

results suggest a difference in representations during encoding and recall at more generalized

levels of information. Second, we employed an item-based recall task, rather than associative

tasks commonly used to study recall (e.g., Ganis et al., 2004; Zeidman et al., 2015a; Xiao et al.,

2017; Jonker et al., 2018). This allowed us to ensure that information we decoded was not

related to other factors such as decoding a cue or association.

Our findings suggest a posterior-anterior gradient within cortical regions, in which

recalled representations extend anterior to encoding or perceptual representations. These

results agree with recent research showing that regions involved in scene memory are anterior

to those involved in scene perception, with the possibility of separate perception and memory

networks (Baldassano et al., 2016; Burles et al., 2018; Chrastil, 2018; Silson et al., 2019a). This

anterior bias for recall may reflect top-down refreshing of a memory representation in contrast

to the largely bottom-up processes that occur during perception (Mechelli et al., 2004; Johnson

et al., 2007; Dijkstra et al., 2019). Indeed, recent work using electroencephalography (EEG) has

identified a reversal of information flow during object recall as compared to encoding (Linde-

Domingo et al., 2019). Alternatively, other research has suggested a gradient within the

neocortex that reflects a split of conceptual information represented anterior (or downstream)

to perceptual information (Peelen and Caramazza, 2012; Borghesani et al., 2016; Martin, 2016).

While recent work shows highly detailed visual content within recalled memories (Bainbridge et

al., 2019), it is possible recalled memories may be more abstracted and conceptual compared

to their encoded representations. This recalled memory could thus contain less fine-grained

perceptual information or be abstracted into a different representation, explaining why we can

decode memory strength but not fine-grained perceptually-defined distinctions (e.g., natural

versus manmade) during recall. Collectively, our results support these two possible accounts for

anterior-posterior gradients of memory/perception or conceptual/perceptual information in

the brain, in contrast with other accounts claiming an identical representation between

encoding and recall (e.g., Schultz et al., 2019).

The current work also provides further support for a content-independent role of the

hippocampus in memory. During encoding, we observe broad content selectivity in the

hippocampus, as has been observed in other recent work claiming a perceptual role for the

hippocampus (Zeidman et al., 2015b; Hodgetts et al., 2017). However, we do not observe

strong evidence of any other content representations during encoding or recall; the

hippocampus does not show sensitivity to more fine-grained information, and during recall, it

does not even show differences at the broadest distinction of objects versus scenes. These

results lend support for the notion that the hippocampus is largely content-independent

(Davachi, 2006; Danker and Anderson, 2010; Liang et al., 2013; Schultz et al., 2019), with

individual item decoding in previous work possibly driven by decoding of indexes within the

hippocampus connected to fuller representations in the neocortex, or a coding of memory

strength (e.g., Teyler and Rudy, Jonker et al., 2018). In fact, while stimulus content during recall

is not discriminable, we find that memory strength is decodable from the hippocampus,

mirroring similar results finding strength but not content representations in the hippocampus

for oriented gratings (Bosch et al., 2014). There is also evidence to suggest that the

hippocampus may require longer delays (e.g., several hours to a week) to develop decodable

representations of memory content (Tompary and Davachi, 2017; Lee et al., 2019), and so a

similar experiment conducted with longer delays between study and test (e.g., days) may find

decodable stimulus content from the hippocampus.

The current study combining nested categorical structure for real-world images and an

item-based recall approach allows us to observe different levels of stimulus representations

across the brain; however, there are limitations to this methodology that could be addressed in

future work. First, the relative lack of fine-grained information during recall could partly reflect

a lack of power that could benefit from a larger stimulus set or a memory task that emphasizes

these different stimulus properties. However, it is important to note that we are able to decode

memory strength from these regions during both encoding and recall, suggesting that the

difference between encoding and recall is not simply a question of power. In fact, the current

sample size (N=22) falls in the higher range compared to related studies (e.g., Lee et al., 2012:

N=11; Johnson and Johnson, 2014: N=16; Schultz et al., 2019: N=16). Second, while our current

methodology allows us to powerfully test stimulus content divorced from memory for

individual items, this means we cannot assess discriminability for individual images. Future

studies should investigate whether individual item representations are identical between

encoding and recall, even if more general content representations are not. Such findings could

have meaningful implications on the nature of representations during recall, suggesting the

imagery for an individual item is vivid enough to be item-specific, but results in a limited level of

abstraction. Finally, it will be important to see whether these newly defined anterior recall

regions show more fine-grained representations of stimulus content during recall, and whether

there may be region-specific differences (e.g., the MPA in particular has been a key target for

comparisons of scene perception and scene recall; Burles et al., 2018; Chrastil, 2018; Silson et

al., 2019b).

749   Examining item-based recall and representations of memory content in the brain has

ultimately unveiled a rather complex, nuanced relationship of encoding and recall, with

strongest encoding-recall similarity occurring largely anterior to scene- and object-selective

visual cortex. In the study of memory, it is important to examine not only how we remember,

but *what* we are remembering, and this study reveals that the way in which this content is

manifested may vary greatly between encoding and recall.

<u>Acknowledgements</u>

757   We thank Adam Steel, Caroline Robertson, and Alexa Tompary for their helpful

comments on the manuscript. This research was supported by the Intramural Research

Program of the National Institutes of Health (ZIA-MH-002909), under National Institute of

Mental Health Clinical Study Protocol 93-M-1070 (NCT00001360).

<u>References</u>

Bainbridge WA, Oliva A. 2015. Interaction envelope: Local spatial representations of objects at

all scales in scene-selective regions. *Neuroimage.* 122:408-416.

Bainbridge WA, Hall EH, Baker CI. 2019. Drawings of real-world scenes during free recall reveal

detailed object and spatial information in memory. *Nat Commun.* 10:5.

Baldassano C, Esteva A, Fei-Fei L, Beck DM. 2016. Two distinct scene-processing networks

connecting vision and memory. *eNeuro*. 3:ENEURO.0178-16.2016.

Beauchamp MS, Martin A. 2007. Grounding object concepts in perception and action: Evidence

from fMRI studies of tools. *Cortex*. 43:461-468.

Boccia M, Sulpizio V, Teghil A, Palermo L, Piccardi L, Galati G, Guariglia C. 2019. The dynamic

contribution of the high-level visual cortex to imagery and perception. *Hum Brain Mapp*.

40:2449-2463.

Borghesani V, Pedregosa F, Buiatti M, Amaxon A, Eger E, Piazza M. 2016. Word meaning in the

ventral visual path: a perceptual to conceptual gradient of semantic coding. *Neuroimage*.

143:128-140.

Bosch SE, Jehee JFM, Fernández G, Doeller CF. 2014. Reinstatement of associative memories in

early visual cortex is signaled by the hippocampus. *J Neurosci*. 34:7493-7500.

Brewer JB, Zhao Z, Desmond JE, Glover GH, Gabrieli JDE. 1998. Making memories: Brain activity

that predicts how well visual experience will be remembered. *Science*. 281:1185-1187.

Brodt S, Gais S, Beck J, Erb M, Scheffler K, Shönauer M. 2018. Fast track to the neocortex: A

memory engram in the posterior parietal cortex. *Science*. 362:1045-1048.

Buckner RL, Wheeler ME. 2001. The cognitive neuroscience of remembering. *Nat Rev Neurosci.*

2:624.

Burles F, Ultimá A, McFarlane LH, Potocki K, Iara G. 2018. Ventral-dorsal functional contribution

of the posterior cingulate cortex in human spatial orientation: A meta-analysis. *Front Hum*

Neurosci. 12:190.

Buschbaum BR, Lemire-Rodger S, Fang C, Abdi H. 2012. The neural basis of vivid memory is

patterned on perception. *J Cogn Neurosci.* 24:1867-1883.

Chadwick MJ, Hassabis D, Weiskopf N, Maguire E. 2010. Decoding individual episodic memory

traces in the human hippocampus. *Curr Biol.* 20:544-547.

Chrastil ER. 2018. Hetereogeneity in human retrosplenial cortex: A review of function and

connectivity. *Behav Neurosci.* 132:317-338.

Cichy RM, Pantazis D, Oliva A. 2014. Resolving human object recognition in space and time. *Nat*

Neurosci. 17:455.

Cox RW. 1996. AFNI: Software for analysis and visualization of functional magnetic resonance

neuroimages. *Comput Biomed Res.* 29:162-173.

Danker JF, Anderson JR. 2010. The ghosts of brain states past: Remembering reactivates the

brain regions engaged during encoding. *Psychol Bull*. 136:87.

Davachi L, Mitchell JP, Wagner AD. 2003. Multiple routes to memory: Distinct medial temporal

lobe processes build item and source memories. *Proc Natl Acad Sci USA*. 100:2157-2162.

Davachi L. 2006. Item, context and relational episodic encoding in humans. *Curr Opin Neurobiol*.

16:693-700.

Dickerson BC, Miller SL, Greve DN, Dale AM, Albert MS, Schacter DL, Sperling RA. 2007.

Prefrontal-hippocampal-fusiform activity during encoding predicts intraindividual differences in

free recall ability: an event-related functional-anatomic MRI study. *Hippocampus*. 17:1060-1070.

Dijkstra N, Bosch SE, van Gerven MA. 2017. Vividness of visual imagery depends on the neural

overlap with perception in visual areas. *J Neurosci*. 37:1367-1373.

Dijkstra N, Bosch SE, van Gerven MAJ. 2019. Shared neural mechanisms of visual perception

and imagery. *Trends Cogn Sci*. 23:423-434.

Dilks DD, Julian JB, Paunov AM, Kanwisher N. 2013. The occipital place area is causally and

selectively involved in scene perception. *J Neurosci*. 33:1331-1336.

Epstein R, Kanwisher N. 1998. A cortical representation of the local visual environment. *Nature*.

392:598.

Fulford J, Milton F, Salas D, Smith A, Simler A, Winlove C, Zeman A. 2018. The neural correlates

of visual imagery vividness – an fMRI study and literature review. *Cortex*. 105:26-40.

Ganis G, Thompson WL, Kosslyn SM. 2004. Brain areas underlying visual mental imagery and

visual perception: an fMRI study. *Cogn Brain Res*. 20:226-241.

Gelbard-Sagiv H, Mukamel R, Harel M, Malach R, Fried I. 2008. Internally generated reactivation

of single neurons in human hippocampus during free recall. *Science*. 322:96-101.

Gold JJ, Hopkins RO, Squire LR. 2006. Single-item memory, associative memory, and the human

hippocampus. *Learn Mem.* 13:644-649.

Grèzes J, Tucker M, Armony J, Ellis R, Passingham RE. 2003. Objects automatically potentiate

action: an fMRI study of implicit processing. *Eur J Neurosci*. 17:2735-2740.

Grill-Spector K, Kourtzi Z, Kanwisher N. 2001. The lateral occipital complex and its role in object

recognition. *Vis Res*. 41:1409-1422.

Harel A, Kravitz DJ, Baker CI. 2013. Deconstructing visual scenes in cortex: Gradients of object

and spatial layout information. *Cereb Cortex*. 23:947-957.

Harel A, Kravitz DJ, Baker CI. 2014. Task context impacts visual object processing differentially

across the cortex. *Proc Natl Acad Sci USA*. 111:E962-E971.

Henriksson L, Khaligh-Razavi S-M, Kay K, Kriegeskorte N. 2015. Visual representations are

dominated by intrinsic fluctuations correlated between areas. *NeuroImage*. 114:275-286.

Hodgetts CJ, Voets NL, Thomas AG, Clare S, Lawrence AD, Graham KS. 2017. Ultra-high-field

fMRI reveals a role for the subiculum in scene perceptual discrimination. *J Neurosci*. 37:3150-

3159.

Huffman DJ, Stark CE. 2014. Multivariate pattern analysis of the human medial temporal lobe

revealed representationally categorical cortex and representationally agnostic hippocampus.

Hippocampus. 24:1394-1403.

Iglesias JE, Augustinack JC, Nguyen K, Player CM, Player A, Wright M, Roy N, Frosch MP, McKee

AC, Wald LL, Fischl B, van Leemput K. 2016. A computational atlas of the hippocampal

formation using ex vivo, ultra-high resolution MRI: Application to adaptive segmentation of in

vivo MRI. *Neuroimage*. 115:117-137.

Ishai A, Ungerleider LG, Haxby JV. 2000. Distributed neural systems for the generation of visual

images. *Neuron*. 28:979-990.

Ison MJ, Quiroga RQ, Fried I. 2015. Rapid encoding of new memories by individual neurons in

the human brain. *Neuron*. 87:220-230.

Johnson MR, Mitchell KJ, Raye CL, D'Esposito M, Johnson MK. 2007. A brief thought can

modulate activity in extrastriate visual areas: Top-down effects of refreshing just-seen visual

stimuli. *Neuroimage*. 37:290-299.

Johnson JD, McDuff SG, Rugg MD, Norman KA. 2009. Recollection, familiarity, and cortical

reinstatement: A multivoxel pattern analysis. *Neuron*. 63:697-708.

Johnson MR, Johnson MK. 2014. Decoding individual natural scene representations during

perception and imagery. *Front Hum Neurosci*. 8:59.

Jonker TR, Dimsdale-Zucker H, Ritchey M, Clarke A, Ranganath C. 2018. Neural reactivation in

parietal cortex enhances memory for episodically linked information. *Proc Natl Acad Sci USA*.

115:11084-11089.

Kahn I, Davachi L, Wagner AD. 2004. Functional-neuroanatomic correlates of recollection:

Implications for models of recognition memory. *J Neurosci*. 24:4172-4180.

Konkle T, Oliva A. 2012. A real-world size organization of object responses in occipitotemporal

cortex. *Neuron*. 74:1114-1124.

Kravitz DJ, Peng CS, Baker CI. 2011. Real-world scene representations in high-level visual cortex:

It's the spaces more than the places. *J Neurosci*. 31:7322-7333.

Kriegeskorte N, Mur M, Bandettini P. 2008. Representational similarity analysis – connecting

the branches of systems neuroscience. *Front Syst Neurosci*. 2:4.

Kuhl BA, Rissman J, Wagner AD. 2012. Multi-voxel patterns of visual category representation

during episodic encoding are predictive of subsequent memory. *Neuropsychologia*. 50:458-469.

Kuhl BA, Chun MM. 2014. Successful remembering elicits event-specific activity patterns in

lateral parietal cortex. *J Neurosci*. 34:8051-8060.

LaRocque KF, Smith ME, Carr VA, Witthoft N, Grill-Spector K, Wagner AD. 2013. Global similarity

and pattern separation in the human medial temporal lobe predict subsequent memory. *J

Neurosci*. 33:5466-5474.

Lee SH, Kravitz DJ, Baker CI. 2012. Disentangling visual imagery and perception of real-world

objects. *Neuroimage*. 59:4064-4073.

Lee SH, Kravitz DJ, Baker CI. 2019. Differential representations of perceived and retrieved visual

information in hippocampus and cortex. *Cereb Cortex*. 29:4452-4461.

Lewis JW. 2006. Cortical networks related to human use of tools. *Neuroscientist*. 12:211-231.

Liang JC, Wagner AD, Preston AR. 2013. Content representation in the human medial temporal

lobe. *Cereb Cortex*. 23:80-96.

Linde-Domingo J, Treder, MS, Kerrén C, Wimber M. 2019. Evidence that neural information flow

is reversed between object perception and object reconstruction from memory. *Nat Commun*.

10:179.

Mack ML, Preston AR. 2016. Decisions about the past are guided by reinstatement of specific

memories in the hippocampus and perirhinal cortex. *Neuroimage*. 127:144-157.

Mahon BZ, Milleville SSC, Negri GAL, Rumiati RI, Caramazza A, Martin A. 2007. Action-related

properties shape object representations in the ventral stream. *Neuron*. 55:507-520.

Martin A. 2016. GRAPES—Grounding representations in action, perception, and emotion

systems: How object properties and categories are represented in the human brain. *Psychon*

Bull Rev. 23:979-990.

McClelland JL, McNaughton BL, O'Reilly RC. 1995. Why there are complementary learning

systems in the hippocampus and neocortex: Insights from the successes and failures of

connectionist models of learning and memory. *Psychol Rev*. 102:419.

Mechelli A, Price CJ, Friston KJ, Ishai A. 2004. Where bottom-up meets top-down: Neuronal

interactions during perception and imagery. *Cereb Cortex*. 14:1256-1265.

O'Craven KM, Kanwisher N. 2000. Mental imagery of faces and places activates corresponding

stimulus-specific brain regions. *J Cogn Neurosci*. 12:1013-1023.

Park S, Brady TF, Greene MR, Oliva A. 2011. Disentangling scene content from spatial boundary:

Complementary roles for the parahippocampal place area and lateral occipital complex in

representing real-world scenes. *J Neurosci*. 31:1333-1340.

Peelen MV, Caramazza A. 2012. Conceptual object representations in human anterior temporal

cortex. *J Neurosci*. 32:15728-15736.

Polyn SM, Natu VS, Cohen JD, Norman KA. 2005. Category-specific cortical activity precedes

retrieval during memory search. *Science*. 310:1963-1966.

Ranganath C, Ritchey M. 2012. Two cortical systems for memory-guided behavior. *Nat Rev*

Neurosci. 13:713-726.

Reddy L, Tsuchiya N, Serre T. 2010. Reading the mind's eye: Decoding category information

during mental imagery. *Neuroimage*. 50:818-825.

Ritchey M, Wing EA, LaBar KS, Cabeza R. 2013. Neural similarity between encoding and retrieval

is related to memory via hippocampal interactions. *Cereb Cortex*. 23:2818-2828.

Ross DA, Sadil P, Wilson DM, Cowell RA. 2017. Hippocampal engagement during recall depends

on memory content. *Cereb Cortex*. 28:2685-2698.

Rugg MD, King DR. 2018. Ventral lateral parietal cortex and episodic memory retrieval. *Cortex*.

107:238-250.

Saad ZS, Reynolds RC. 2012. SUMA. *Neuroimage*. 62:768-773.

Schultz H, Tibon R, LaRocque KF, Gagnon SA, Wagner AD, Staresina BP. 2019. Content tuning in

the medial temporal lobe cortex: Voxels that perceive, retrieve. *eNeuro*. 6.

Silson EH, Steel AD, Baker, CI. 2016. Scene-selectivity and retinotopy in medial parietal cortex.

Front Hum Neurosci. 10:412.

Silson EH, Steel A, Kidder A, Gilmore AW, Baker CI. 2019a. Distinct subdivisions of human

medial parietal cortex support recollection of people and places. *eLife*. 8.

Silson EH, Gilmore AW, Kalinowski SE, Steel A, Kidder A, Martin A, Baker, CI. 2019b. A posterior-

anterior distinction between scene perception and scene construction in human medial parietal

cortex. *J Neurosci*. 39:705-717.

Staresina BP, Davachi L. 2006. Differential encoding mechanisms for subsequent associative

recognition and free recall. *J Neurosci*. 26:9162-9172.

Staresina BP, Henson RN, Kriegeskorte N, Alink A. 2012. Episodic reinstatement in the medial

temporal lobe. *J Neurosci*. 32:18150-18156.

1001

1002   Sullivan Giovanello K, Schnyer DM, Verfaellie M. 2003. A critical role for the anterior

1003   hippocampus in relational memory: Evidence from an fMRI study comparing associative and

1004   item recognition. *Hippocampus*. 14:5-8.

1005

1006   Teyler TJ, Rudy JW. 2007. The hippocampal indexing theory and episodic memory: Updating the

1007   index. *Hippocampus*. 17:1158-1169.

1008

1009	Tompary A, Davachi L. 2017. Consolidation promotes the emergence of representational

1010	overlap in the hippocampus and medial prefrontal cortex. *Neuron.* 96:228-241.

1011

1012	Tompary A, Duncan K, Davachi L. 2016. High-resolution investigation of memory-specific

1013	reinstatement in the hippocampus and perirhinal cortex. *Hippocampus.* 26:995-1007.

1014

1015	Troiani V, Stigliani A, Smith ME, Epstein RA. 2012. Multiple object properties drive scene-

1016	selective regions. *Cereb Cortex.* 24:883-897.

1017

1018	Valyear KF, Cavina-Pratesi C, Stiglick AJ, Culham J. 2007. Does tool-related fMRI activity within

1019	the intraparietal sulcus reflect the plan to grasp? *Neuroimage.* 36:T94-T108.

1020

1021	Vilberg KL, Rugg MD. 2009. Functional significance of retrieval-related activity in lateral parietal

1022	cortex: Evidence from fMRI and ERPs. *Hum Brain Map*. 30:1490-1501.

1023

1024	Wais PE. 2008. fMRI signals associated with memory strength in the medial temporal lobes: A

1025	meta-analysis. *Neuropsychologia.* 46:3185-3196.

1026

1027	Walther DB, Caddigan E, Fei-Fei L, Beck DM. 2009. Natural scene categories revealed in

1028	distributed patterns of activity in the human brain. *J Neurosci.* 29:10573-10581.

1029

1030   Wheeler ME, Petersen SE, Buckner RL. 2000. Memory's echo: Vivid remembering reactivates

1031   sensory-specific cortex. *Proc Natl Acad Sci USA*. 97:11125-11129.

1032

1033   Wing EA, Ritchey M, Cabeza R. 2015. Reinstatement of individual past events revealed by the

1034   similarity of distributed activation patterns during encoding and retrieval. *J Cogn Neurosci*.

1035   27:679-691.

1036

1037   Xiao X, Dong Q, Gao J, Men W, Poldrack R, Xue G. 2017. Transformed neural pattern

1038   reinstatement during episodic memory retrieval. *J Neurosci*. 37:2986-2998.

1039

1040   Zeidman P, Lutti A, Maguire EA. 2015a. Investigating the functions of subregions within anterior

1041   hippocampus. *Cortex*. 73:240-256.

1042

1043   Zeidman P, Mullally SL, Maguire EA. 2015b. Constructing, perceiving, and maintaining scenes:

1044   hippocampal activity and connectivity. *Cereb Cortex*. 252:3836-3855.

1045

1046   Zeineh MM, Engel SA, Thompson PM, Bookheimer SY. 2003. Dynamics of the hippocampus

1047   during encoding and retrieval of face-name pairs. *Science*. 299:577-580.