1   **Do deep neural networks see the way we do?**

3   Georgin Jacob[1,2], R. T. Pramod[1,2], Harish Katti[1] and S. P. Arun[1]*

4   [1]Centre for Neuroscience & [2]Department of Electrical Communication Engineering

5   Indian Institute of Science, Bangalore 560012

6   *Correspondence to sparun@iisc.ac.in

8   Abbreviated Title   : Perception in deep neural networks

9   Number of Figures   : 6 main and 10 supplementary figures

11   **ABSTRACT**

Deep neural networks have revolutionized computer vision, and their object

representations match coarsely with the brain. As a result, it is widely believed that

any fine scale differences between deep networks and brains can be fixed with

increased training data or minor changes in architecture. But what if there are

qualitative differences between brains and deep networks? Do deep networks even

see the way we do? To answer this question, we chose a deep neural network

optimized for object recognition and asked whether it exhibits well-known perceptual

and neural phenomena despite not being explicitly trained to do so. To our surprise,

many phenomena were present in the network, including the Thatcher effect, mirror

confusion, Weber's law, relative size, multiple object normalization and sparse coding

along multiple dimensions. However, some perceptual phenomena were notably

absent, including processing of 3D shape, patterns on surfaces, occlusion, natural

parts and a global advantage. Our results elucidate the computational challenges of

vision by showing that learning to recognize objects suffices to produce some

perceptual phenomena but not others and reveal the perceptual properties that could

be incorporated into deep networks to improve their performance.

INTRODUCTION

How do I know this is true?
I look inside myself and see.
Tao Te Ching (Mitchell, 1988)

Convolutional or deep neural networks have revolutionized computer vision with their human-like accuracy on vision tasks, and their object representations match coarsely with the brain (see Serre, 2019; Sinz et al., 2019 for detailed reviews). Yet, at a finer scale, they are still outperformed by humans (Katti et al., 2017; Katti and Arun, 2019) and show systematic deviations from human perception (Pramod and Arun, 2016a; Geirhos et al., 2018b; Rajalingham et al., 2018; Dodge and Karam, 2019). Even these differences are largely quantitative in that there are no explicit or emergent properties that are present in humans but absent in deep networks. This has given rise to the prevailing belief that any remaining differences between brains and deep networks can be fixed by training on larger datasets, incorporating more constraints (Sinz et al., 2019) or by making relatively minor modifications to network architecture such as by including recurrent feedback (Kar et al., 2019a; Kietzmann et al., 2019).

Despite these insights, we do not yet know whether there are qualitative differences between how brains and deep networks see. This is an important question because resolving qualitative differences might require non-trivial changes in network training or architecture. One approach could be to train deep networks on multiple visual tasks and compare them with humans, but the answer would be insightful only if networks fail to learn certain tasks (Fleuret et al., 2011a). Alternatively, we could compare qualitative or emergent properties of our perception with that of deep networks, provided these properties can indeed be checked in any deep network without explicit training for these properties.

Fortunately, many classic findings from visual psychology and neuroscience

report emergent phenomena and properties that can be directly tested on deep

networks. Consider for instance, the classic Thatcher effect (Figure 1A), in which a

face with rotated parts looks grotesque in an upright orientation but looks entirely

normal when inverted (Thompson, 1980). This effect can be recast as a statement

about the underlying face representation: in perceptual space, the distance between

the normal and Thatcherized face is presumably larger when they are upright than

when they are inverted (Figure 1B). This has been confirmed using dissimilarity ratings

in humans (Bartlett and Searcy, 1993). These distances can be compared for any

representation, including for a deep network (Figure 1C). Since deep networks are

organized layer-wise with increasing complexity across layers, this would also reveal

the layers at which the deep network begins to experience or "see" a Thatcher effect

(Figure 1D).

Knowing whether a deep network exhibits the Thatcher effect can be insightful

for a variety of reasons. First, it would confirm that the deep network indeed does see

faces the way we do. Second, this question can be asked of any deep network without

explicit training to produce a Thatcher effect. For instance, testing this question on

face and object detection networks would reveal whether object or face-specific

training is sufficient for the emergence of the Thatcher effect. Finally, this question has

relevance to neuroscience, because object representations in the early and late layers

of deep networks match with early and late visual processing stages in the brain (Cichy

et al., 2014; Kar et al., 2019b). The layer at which this effect arises could therefore

reveal its underlying computational complexity and offer clues as to its neural

substrates.

Here, we identified a number of emergent perceptual and neural properties from

visual psychology and neuroscience that can be recast as statements about distances

between images in the underlying perceptual/neural representation. We then tested

each of these properties on a state-of-the-art deep neural network optimized for object

recognition. This revealed a highly interesting and insightful list of properties that were

either present or absent in the network.

Figure 1: Evaluating whether deep networks see the way we do
(A) In the classic Thatcher effect, when the parts of a face are individually inverted, the face appears grotesque when upright (*top row*) but not when inverted (*bottom row*). Figure credit: Reproduced with permission from Peter Thompson.
(B) When the brain views these images, it presumably extracts specific features from each face so as to give rise to this effect. We can use this idea to recast the Thatcher effect as a statement about the underlying perceptual space. The distance between the normal and Thatcherized face is larger when they are upright compared to when the faces are inverted. This property can easily be checked for any computational model.
(C) Architecture of a common deep neural network (VGG-16). Symbols used here and in all subsequent figures indicate the underlying mathematical operations of that layer: *unfilled circle* for convolution, *filled circle* for ReLu, *diamond* for maxpooling and *unfilled square* for fully connected layers. Broadly, unfilled symbols depict linear operations and filled symbols depict non-linear operations.
(D) By comparing the distance between upright and inverted Thatcherized images, we can ask whether any given layer of the deep network sees a Thatcher effect.

RESULTS

We identified a large number of emergent perceptual and neural properties that

can be tested across layers of a deep network. We organized these properties broadly

into five groups: (1) those that reveal sensitivity to object or scene statistics,

comprising the Thatcher effect, mirror confusion and object-scene incongruence; (2)

neural principles observed in high-level visual cortex, related to multiple object tuning

and sparseness; (3) relational properties such as Weber's law, relative size and

surface invariant pattern processing; (4) encoding of 3d shape or scene structure and

(5) processing of object parts and global structure.

We evaluated these properties for a state-of-the-art pre-trained deep network,

VGG-16, optimized for object classification on the ImageNet dataset (Simonyan and

Zisserman, 2014). For each property, we performed an experiment in which we used

carefully controlled sets of images as input to the network, obtained the activations of

the units in each layer, and asked whether each layer shows that property. We

obtained qualitatively similar results on several other pre-trained feedforward networks

with diverse architectures: AlexNet, GoogleNet, Resnet-50 and Resnet-152 (Section

S1). To ensure that the results are truly due to training and not simply a consequence

of the architecture of the network, we also repeated these experiments on a randomly

initialized VGG-16 model (Section S2). For simplicity, we report our results only for the

VGG-16 network in the sections below, with results for all other networks detailed in

supplementary material (Sections S1-2).

128   Experiment 1: Do deep networks see a Thatcher effect?

The Thatcher effect is an elegant demonstration of how upright faces are

processed differently from inverted faces, presumably because we encounter mostly

upright faces. As detailed in the Introduction, it can be recast as a statement about the

underlying distances in perceptual space: that normal vs Thatcherized faces are closer

when inverted than when upright (Figure 2A). For each layer of the deep network

(VGG-16), we calculated a "Thatcher index" of the form $(d_{upright} - d_{inverted})/(d_{upright} +$

$d_{inverted})$, where $d_{upright}$ is the distance between normal and Thatcherized face in the

upright orientation, and $d_{inverted}$ is the distance between them in an inverted orientation.

Note that the Thatcher index for a pixel-like representation (where the activation of

each unit is proportional to the brightness of each pixel in the image) will be zero since

$d_{upright}$ and $d_{inverted}$ will be identical. For human perception, since $d_{upright} > d_{inverted}$, the

Thatcher index will be positive and can be estimated from previous studies (see

Methods).

Next, we calculated the Thatcher index across layers for two networks with

similar architecture but trained on different tasks (see Methods). The first was VGG-

16 which is trained for object classification (Simonyan and Zisserman, 2014). The

second was VGG-face which is trained for face recognition (Parkhi et al., 2015). The

Thatcher index for both networks across layers is shown in Figure 2B. It can be seen

that the VGG-16 shows a positive Thatcher index in the conv4 and conv5 layers but

eventually does not show a Thatcher effect in the final fully connected layers (Figure

2B, red curve). By contrast, the VGG-face network shows a steadily rising Thatcher

effect that remains close to human levels even in the fully connected layers. Thus, the

Thatcher effect is present only in deep networks trained on upright face recognition

but not on generic object recognition.

Experiment 2: Do deep networks show mirror confusion?

Mirror reflections along the vertical axis appear more similar to us than reflections along the horizontal axis (Figure 2C). This effect has been observed both in behaviour as well as in high-level visual cortex in monkeys (Rollenhagen and Olson, 2000). To assess whether deep networks show mirror confusion, we calculated a mirror confusion index of the form $(d_{horizontal} - d_{vertical})/(d_{horizontal} + d_{vertical})$, where $d_{horizontal}$ and $d_{vertical}$ represent the distance between horizontal mirror image pairs and between vertical mirror image pairs respectively (see Methods). Since vertical mirror images are more similar in perception, this index would be positive. Across the deep network VGG-16, we found an increasing mirror confusion index across layers (Figure 2D). Thus, the deep network does experience (as we do) more mirror confusion for vertical compared to horizontal mirror images.

Experiment 3: Do deep networks show scene incongruence?

Our ability to recognize an object is hampered when it is placed in an incongruent context (Davenport and Potter, 2004; Munneke et al., 2013), suggesting that our perception is sensitive to the statistical regularities of objects co-occurring in specific scene context. To explore whether deep networks are also sensitive to scene context, we gave as input the same images as tested on humans, and asked how the deep network classification output changes with scene context (see Methods for more details). An example object (hatchet) placed against a congruent context (forest) and incongruent context (supermarket) are shown in Figure 2E. The VGG-16 network returned a high probability score for the correct target object in the congruent context (Figure 2E, top row) but gave a low probability score for the same object in an incongruent context (Figure 2E bottom row). We obtained similar results across all

congruent/incongruent scene pairs: the VGG-16 top-1 accuracy dropped substantially

for incongruent compared to congruent contexts (drop in accuracy from congruent to

incongruent scenes: 20% for top-5 accuracy; 27% for top-1 accuracy; Figure 2F). On

the same scenes, human object naming accuracy has been reported to drop for

incongruent scenes, but the drop was smaller compared to the VGG-16 network (drop

in human accuracy from congruent to incongruent scenes: 14% in the Davenport &

Potter, 2004; 13% in Munneke et. al. 2013; Figure 2G). We note that assessing the

statistical significance of the accuracy difference in humans and deep networks is not

straightforward since the variations in accuracy reported are across subjects for

humans and across scenes for the VGG-16 network. We conclude that deep networks

show scene incongruence albeit to a smaller extent than humans.

Figure 2: Object and scene regularities in deep networks

(A) Schematic showing the perceptual arrangement of normal and Thatcherized faces in the upright and inverted orientations. A Thatcherized face is more similar to its normal counterpart in the inverted orientation.

(B) Thatcher index (averaged across 20 pairs of normal-Thatcherized face pairs) plotted across layers for two pre-trained networks, VGG-16 (red) and VGG-face (blue). Shaded error bars indicated s.e.m across 20 face pairs. The gray zone indicates human-like performance, with dotted lines indicating the strength of the Thatcher effect estimated from humans (see Methods).

(C) Schematic showing the representation of vertical and horizontal mirror images in perception. Vertical mirror image pairs are closer than horizontal mirror image pairs. The same effect holds even if the dog is rotated by 90°, showing that this effect is not simply due to the object's axis of elongation.

(D) Mirror Confusion Index (averaged across 50 naturalistic objects and their 90° rotated versions) across layers for the VGG-16 network. Dotted lines show the strength of the mirror confusion index estimated from monkey inferior temporal neurons (see Methods).

(E) An example object (*hatchet*) embedded in a congruent context (*forest*) and an
incongruent context (*supermarket*), highlighting the vulnerability of deep
network classification to scene context. The CNN class probability returned by
the VGG-16 network is shown beside each image. It can be seen that the deep
network returns the correct class label on the congruent but not the incongruent
scene.
(F) Accuracy of object classification by the VGG-16 network across congruent
(blue) and incongruent(red) context scenes, for top-5 accuracy (*left*) and top-1
accuracy (*right*). Error bars represent s.e.m across 40 congruent/incongruent
scene pairs.
(G) Accuracy of object naming by humans in congruent (blue) and incongruent (red)
contexts across two separate studies (Davenport and Potter, 2004; Munneke
et al., 2013). Humans are less accurate on naming objects placed on
incongruent scene contexts, but show a smaller drop compared to the VGG-16
network. Error bars represent s.e.m reproduced from the published studies.
226

Experiment 4: Do deep networks show multiple object normalization?

Next we asked whether individual units in deep networks conform to two general principles observed in single neurons of high-level visual cortex. The first one is multiple object normalization, whereby the neural response to multiple objects is the average of the individual object responses at those locations (Zoccolan et al., 2005). This principle is illustrated in Figure 3A. Note that this analysis is meaningful only for units that respond to all three locations: a unit in an early layer with a small receptive field would respond to objects at only one location regardless of how many other objects were present in the image. To identify units that are responsive to objects at each location, we calculated the variance of its activation across all objects presented at that location. We then performed this analysis on units that showed a non-zero response variance at all three locations, which meant units in Layer 23 (conv4.3) onwards.

To assess whether deep networks show multiple object normalization, we plotted for each unit in a given layer its response to multiple objects against the sum of its responses to the individual objects. If there is multiple object normalization, the slope of the resulting plot should be 1/2 for two objects and 1/3 for three objects. The

resulting plot is shown for Layer 37 of the VGG-16 network (Figure 3B). The overall

slope was 0.60 for two objects and 0.42 for three objects for all units. To evaluate this

effect across layers, we plotted the two-object and three-object slopes obtained in this

manner across layers (Figure 3C). For the later layers we observed a nearly monotonic

decrease in the slopes, approaching the levels observed in monkey high-level visual

areas (Figure 3C). We conclude that deep networks exhibit multiple object

normalization.

Experiment 5: Do deep networks show selectivity across multiple dimensions?

In a recent study we showed that neurons in the monkey inferior temporal cortex have

intrinsic constraints on their selectivity that manifests in two ways (Zhivago and Arun,

2016). First, neurons that respond to fewer shapes have sharper tuning to parametric

changes in these shapes. To assess whether units in the deep network VGG-16 show

this pattern, we calculated the sparseness of each unit across a reference set of

disparate shapes (Figure 3D), and its sparseness for parametric changes between

pairs of these stimuli (an example morph line is shown in Figure 3D). This revealed a

consistently high correlation across units of each layer in the VGG-16 network (Figure

3E). Second, we found that neurons that are sharply tuned across textures are also

sharply tuned to shapes. To assess this effect across layers, we calculated the

correlation across units between sparseness on textures with the sparseness on

shapes. Although there was no such consistently positive correlation in the early

layers, we did find a positive correlation in the later (conv5 & fc) layers (Figure 3F).

We conclude that deep networks show selectivity along multiple dimensions just like

neurons in high-level visual cortex.

Figure 3: Single unit properties of deep networks
    (A) Schematic illustrating a general principle observed in neurons in high-level visual areas of the brain. The response of a neuron to multiple objects is typically the average of its responses to the individual objects at those locations.
    (B) Response to multiple object displays plotted against the sum of the individual object responses for two-object displays (black) and three-object displays (red), across 10,000 units randomly selected from Layer 37 of the VGG-16 network.
    (C) Normalization slope plotted across layers for two object displays (black) and three-object displays (red).
    (D) Stimuli used to compare selectivity across multiple dimensions in a previous study of IT neurons (Zhivago and Arun, 2016).
    (E) Correlation between sparseness on the reference set and maximum sparseness along morphlines across units of each layer in the VGG-16 network.
    (F) Correlation between sparseness along textures and sparseness along shapes plotted across layers of the VGG-16 network.

Experiment 6: Do deep networks show Weber's law?

Next we asked whether deep networks are sensitive to relational properties in visual displays. The first and most widely known of these is Weber's law, which states that sensitivity to changes in any sensory quantity is proportional to the baseline level being used for comparison. Weber's law for line length is illustrated in Figure 4A. This in turn predicts that the distance between any two lines differing in length should be proportional to the relative but not absolute change in length. In a previous study, we

showed that this is true for humans in visual search for both length and intensity

changes (Pramod and Arun, 2014).

We therefore asked for the deep network VGG-16, whether pairwise distances

between lines of varying length are correlated with absolute or relative changes in

length. Specifically, if the correlation between pairwise distances and relative changes

in length is larger than the correlation with absolute changes in length, we deemed

that layer to exhibit Weber's law. This difference in correlation is positive for humans

in visual search, and we plotted this difference across layers of the VGG-16 network

(Figure 4B). The correlation difference was initially negative in the early layers of the

network, meaning that the early layers were more sensitive to absolute changes in

length. To our surprise, however, distances in the later layers were sensitive to relative

changes in length in accordance to Weber's law (Figure 4B).

We conclude that deep networks exhibit Weber's law for length.

306 Experiment 7: Do deep networks encode relative size?

We have previously shown that neurons in high-level visual areas are sensitive

to the relative size of items in a display (Vighneshvel and Arun, 2015). Specifically, we

found that, when two items in a display undergo congruent changes in size, the neural

response is more similar than expected given the two individual changes in size. This

pattern was present only in a small fraction (7%) of the neurons. This effect is

illustrated in Figure 4C. To explore whether this effect can be observed in a given layer

of the deep network VGG-16, we performed a similar analysis. We selected units in a

given layer with the strongest interactions (see Methods) and calculated a relative size

index of the form $(d1-d2)/(d1+d2)$ where $d1$ is the distance between stimuli with

incongruent changes in size, and $d2$ is the distance between stimuli with congruent

size changes (i.e. where both items or parts are scaled up or down in size by the same

factor). The relative size index was calculated for each tetrad as to replicate the same

analysis done in the previous study(Vighneshvel and Arun, 2015). The relative size

index for the VGG-16 network remained close to zero in the initial layers and increased

modestly to a positive level in the later layers (Figure 4D). However the size of this

effect was far smaller than that observed in IT neurons, but in the same direction. We

conclude that the deep network VGG-16 encodes relative size.

Experiment 8: Do deep networks decouple pattern shape from surface shape?

A recent study showed that IT neurons respond more similarly when a pattern

and a surface undergo congruent changes in curvature or tilt (Ratan Murty and Arun,

2017). This effect is illustrated for a pattern surface pair in Figure 4E, where it can be

seen that the distance between incongruent pattern-surface pairs (where the pattern

and surface change in opposite directions) is larger than the distance between

congruent pairs where the pattern and surface undergo congruent changes. To assess

whether the deep network VGG-16 shows this property, we identified units with

increased interactions (see Methods) and calculated a surface invariance index of the

form $(d1-d2)/(d1+d2)$, where $d1$ is the distance between incongruent pairs, and $d2$ is

the distance between congruent pairs. A positive value of this index for a given layer

implies that the layer shows surface invariance. However the surface invariance index

was consistently below zero across layers for the VGG-16 network (Figure 4F). We

conclude that the VGG-16 network does not show surface invariance.

Figure 4: Relational properties in deep networks

(A) Example illustrating the Weber's law for line length. Although the original statement of Weber's law is that the just-noticeable difference in length will depend on the baseline length, it also applies to perceptual distances between any two stimuli (Pramod and Arun, 2014). In this formulation, the perceptual distance between two lines differing in length will be proportional to the relative change in length rather than the absolute change.

(B) To calculate a single quantity that measures adherence to Weber's law, we calculated the difference in correlation between pairwise distances between lines with the relative and absolute differences in line length. A positive difference indicates adherence to Weber's law (indicated by the gray shading). This difference in correlation is plotted across layers for line length.

(C) Schematic of the relative size encoding observed in monkey IT neurons (Vighneshvel and Arun, 2015). For a fraction of neurons, the distance between two-part objects when both parts covary in size is smaller than the distance

356   when they show inconsistent changes in size. Thus, these neurons are
357   sensitive to the relative size of items in a display.
358 (D) Relative size index across units with interaction effects (averaged across top
359   7% tetrads tetrads, error bars representing s.e.m) across layers of the VGG-
360   16 network. Dotted lines show the strength of the relative index estimated from
361   monkey inferior temporal neurons (Vighneshvel and Arun, 2015).
362 (E) Schematic of the surface invariance index observed in monkey IT neurons
363   (Ratan Murty and Arun, 2017). For a fraction of neurons, the distance between
364   two stimuli with congruent changes in pattern and surface curvature is smaller
365   than between two stimuli with incongruent pattern/surface changes. Thus,
366   these neurons decouple pattern shape from surface shape.
367 (F) Surface invariance index across units with interaction effects (averaged across
368   top 9% pattern/surface tetrads, error bars representing s.e.m) across layers of
369   the VGG-16 network. Dotted lines show the strength of the surface invaraince
370   index estimated from monkey inferior temporal neurons (Ratan Murty and Arun,
371   2017).
372

Experiment 9: Do deep networks show 3d processing?

We are sensitive to three-dimensional shape and not simply two-dimensional

contours in the image. This was demonstrated in an elegant experiment in which

search for a target differing in 3d structure is easy whereas search for a target with the

same difference in 2d features is hard (Enns and Rensink, 1990, 1991). This effect

can be recast as a statement about distances in perceptual space as illustrated in

Figure 5A. All three pairs of shapes depicted in Figure 5A differ in the same Y-shaped

feature, but the two cuboids are more dissimilar because they differ also in 3d shape.

To assess whether units in a given layer of the deep network show this effect, we

calculated a 3d processing index of the form (d1-d2)/(d1+d2) where d1 is the distance

between the cuboids and d2 is the distance between the two equivalent 2d conditions.

A positive 3D processing index indicates an effect similar to human perception.

However we found that the 3D processing index was consistently near zero or

negative across all layers of the VGG-16 network (Figure 5B). We conclude that deep

networks are not sensitive to 3d shape. We speculate that explicit training of deep

networks on 3d shape processing may be required for the network to exhibit this effect.

Experiment 10: Do deep networks understand occlusions?

A classic finding in human perception is that we automatically process occlusion relations between objects (Rensink and Enns, 1998). Specifically, search for a target containing occluded objects among distractors that contain the same objects unoccluded is hard, whereas searching for the equivalent 2d feature difference is much easier (Figure 5C, top row). Likewise, searching for a target that is different in the order of occlusion is hard, whereas searching for the equivalent 2d feature difference is easy (Figure 5C, bottom row). These observations demonstrate that our visual system has a similar representation for occluded and unoccluded objects.

We therefore asked whether similar effects could be observed in the VGG-16 network, by calculating an occlusion index of the form $(d2-d1)/(d2+d1)$ where $d1$ is the distance between two displays that are equivalent except for occlusion, and $d2$ is the distance between equivalent displays with the same 2d feature difference. A positive occlusion index implies an effect similar to human perception. The occlusion index remained consistently below across all layers of the VGG-16 network, for both the occlusion effect and occlusion ordering (Figure 5D). We conclude that deep networks do not understand occlusions.

407
Figure 5: 3D processing in deep networks
(A) Schematic demonstrating sensitivity to 3d shape in our perception (Enns and
Rensink, 1991). Three equivalent image pairs are shown in perceptual space.
The first image pair (with distance marked d1) consists of two cuboids at
different orientations, and corresponds to an easy visual search i.e. the two
objects are less similar. The second pair (marked with distance d2) contains
the same feature difference as in the first pair, but represents a hard search i.e.
is perceived as much more similar. Likewise, the third pair, with the same
feature difference as the other two, is a hard search i.e. perceived as similar.
(B) 3D processing index for the VGG-16 network across layers, for condition 1 (d_1
vs d_2, *blue*) and condition 2 (d_1 vs d_3, *red*). Dotted lines of the corresponding
color represent the estimated human effect size.
(C) Schematic showing processing of occlusions in perception. *Top:* A square
alongside a disk is perceptually similar to a display with the same objects but
occluded, but dissimilar to a 2d control image with an equivalent feature
difference. *Bottom:* A square occluding a disk or disk occluding square are
perceptually similar, but dissimilar to an equivalent 2d control with the same set
of feature differences.
(D) Occlusion index for both basic occlusion (*blue*) and depth ordering (*red*) for
each layer of the VGG-16 network.
428
429

Experiment 11: Do deep networks understand object parts?

We not only recognize objects but are able to easily describe their parts. We conducted two related experiments to investigate part processing in deep networks. In Experiment 11A, we compared deep network feature representations for whole objects and for the same object broken down into either natural or unnatural parts. In perception, searching for an object broken into its natural parts with the original object as distractors is much harder than searching for the same object broken at an unnatural location (Xu and Singh, 2002). This result is depicted schematically in terms of the underlying distances (Figure 6A). To assess whether the VGG-16 network also shows this part decomposition, we calculated a part processing index of the form $(d_u - d_n)/(d_u + d_n)$ where d_u is the distance between the original object and the object broken at an unnatural location, and d_n is the distance between the original object and the same object broken at a natural location. A positive part processing index implies an effect similar to that seen in perception. The part processing index across layers of the VGG-16 network is depicted in Figure 6B. We found that the index becomes positive in the intermediate layers, but becomes negative in the subsequent layers (conv4/conv5 onwards).

In Experiment 11B, we asked what happens to objects that can be decomposed into two possible ways without introducing a break (Figure 6C). In visual search, search between pairs of whole objects is better explained by breaking the object down into its natural parts compared to its unnatural parts (Pramod and Arun, 2016b). To capture this effect, we defined the natural part advantage as the difference in model correlation (see Methods) between natural and unnatural parts. A positive value indicates effects similar to perception. This natural part advantage is shown across layers of the VGG-16 network in Figure 6D. It can be seen that there is little or no

advantage for natural parts in most layers except temporarily in the later layers

(conv5/fc).

Based on Experiments 11A & 11B, we conclude that the VGG-16 network

shows no systematic part processing.

Experiment 12: Do deep networks show a global shape advantage?

In perception a classic finding is that we see the forest before the trees, i.e. we

can detect global shape before local shape (Navon, 1977; Kimchi, 1994). We can

recast this effect into a statement about distances in perception: the distance between

two hierarchical stimuli differing only in global shape will be larger than the distance

between two such stimuli differing only in local shape. This is depicted schematically

in Figure 6E. To calculate a single measure for this effect, we defined a global

advantage index as $(d_{global} - d_{local})/(d_{global} + d_{local})$, where d_{global} is the average distance

between all image pairs differing only in global shape and d_{local} is the average distance

between all image pairs differing only in local shape. A positive global advantage index

implies an effect similar to perception. The global advantage index is depicted across

layers of the VGG-16 network in Figure 6F. While there is a slight global advantage in

the initial layers, the network representation swings rapidly in the later layers towards

the opposite extreme, which is a local advantage. Thus, deep networks see the trees

and not the forest.

475
Figure 6: Part-whole relations in deep networks

(A) Schematic showing the perceptual representation of objects with a break introduced either at natural or unnatural parts.

(B) Part processing index across layers of the VGG-16 network. The shaded gray bar represents effects similar to human perception, and the dotted line represents the effect size estimated from human visual search (Xu and Singh, 2002).

(C) Schematic showing how the same object can be broken into either natural or unnatural parts.

(D) Natural part advantage across layers of the VGG-16 network. The shaded gray bar represents effects similar to human perception, and the dotted line

represents the effect size estimated from human visual search (Pramod and
Arun, 2016b).

(E) Schematic showing the perceptual representation of hierarchical stimuli. The
left and middle images differ only in global shape whereas the middle and right
images differ only at the local level.

(F) Global Advantage index across layers of the VGG-16 network. The shaded gray
bar represents effects similar to human perception, and the dotted line
represents the effect size estimated from human visual search (Jacob and
Arun, 2019).

DISCUSSION

Because object representations in deep networks match coarsely with the

brain, it is widely believed that any remaining differences between brains and deep

networks must be of degree but not of kind. Here, we show that this is not always the

case: In some respects, deep networks do see the way we do. They exhibit perceptual

phenomena such as the Thatcher effect, mirror confusion, scene incongruence and

Weber's law. Their units show multiple object normalization, sparseness along multiple

dimensions and encode relative size. Yet in other ways, they don't see the way we do.

They fail to encode relational properties such as surface invariance, do not show

processing of 3d features, occlusions or natural parts and do not show a global

advantage.

These findings are important for several reasons. First, they describe the

similarities and differences between our vision and deep networks, and challenge the

prevailing belief that they can be treated as accurate models for biological vision.

Second, they show that object recognition training alone is sufficient to produce some

emergent properties but not others, thereby elucidating the computational problem of

vision itself. Finally, the missing properties could be incorporated as training or

architecture constraints on deep networks to yield better or more robust performance.

Below we discuss our findings in the context of the existing literature.

We begin by discussing some general concerns regarding our findings. First

and foremost, it could be argued that our results are based on testing with artificial

objects or images, and that it is unreasonable to expect deep networks to respond

sensibly to unnatural images. However, these concerns apply equally to humans as

well, who in fact do respond sensibly to these artificial displays despite no prior

exposure. Indeed, there is a long tradition in psychology and neuroscience of using

artificial images to elucidate visual processing (Rust and Movshon, 2005). Second, it

could be argued that deep networks could potentially be trained to report all the tested

properties. However, such a finding would only be circular if the network did indeed

exhibit the property it was trained for. We do note however that it would be interesting

if deep networks were unable to learn certain properties. Indeed, certain relational

properties have been reported as difficult to learn by computer vision algorithms

(Fleuret et al., 2011b), although this study did not evaluate deep neural networks. By

contrast, we consider our experiments to be far more interesting, since they reveal

that deep networks trained for specific other purposes show emergent properties that

they were not explicitly trained for, such as Weber's law.

Our finding that deep networks trained for object recognition exhibit Weber's

law or encode relative size is puzzling at first glance. Why would the demands of

recognizing objects require sensitivity to relative changes? One possibility is that

object recognition requires a representation invariant to changes in size, position,

viewpoint and even illumination of objects in the image, which in turn requires

processing all object features relative to the surrounding features. This could be tested

by training deep networks on controlled sets of images with variations of one kind but

not the other. We note that there could be other visual task requirements that could

also give rise to Weber's law (Pardo-Vazquez et al., 2019).

Our finding that deep networks exhibit the Thatcher effect, mirror confusion and

scene incongruence are consistent with them being sensitive to image regularities in

scenes. In fact, the VGG-16 network may be over-reliant on scene context, because

it showed a larger drop in accuracy for incongruent scenes compared to humans

(Figure 2F). This is consistent with a previous study in which human scene

expectations benefited deep network performance (Katti et al., 2019). However, the

VGG-16 network did not exhibit 3d processing, occlusions and surface invariance,

suggesting that these properties might emerge only with additional task demands such

as extracting 3d shape from the image. Likewise, the absence of any part processing

or global advantage in the network suggests that these too are properties that might

emerge with additional task demands, such as part recognition or global form

recognition (Belongie et al., 2002).

We have found that deep networks do not show a global advantage effect but

instead seem to process local features. This finding is surprising considering that units

in later layers receive convergent inputs from the entire image. However, our finding

is consistent with reports of a bias towards local object texture in deep networks

(Geirhos et al., 2018a). It is also consistent with the large perturbations in classification

observed when new objects are added to a scene (Rosenfeld et al., 2018), which

presumably change the distribution of local features. Our finding that deep networks

experience large scene incongruence effects is therefore likely to be due to

mismatched local features rather than global features. Indeed, incorporating scene

expectations from humans (presumably driven by global features) can lead to

substantial improvements in object recognition (Katti et al., 2019). Finally, a reliance

on processing local features is probably what makes deep networks detect

incongruously large objects in scenes better than humans (Eckstein et al., 2017). We

speculate that training on global shape could make deep networks more robust and

human-like in their performance.

Comparing human vision and deep neural networks depends critically on the

choice of network architecture, learning algorithm, dataset and the task learned. An

important but neglected finding is that even a randomly initialized network can

generate features useful for certain tasks. For tasks like texture generation and

discrimination, even a randomly initialized network can yield reliable features (Jarrett

et al., 2009; Mongia et al., 2016). Likewise, a significant amount of explainable

variance in the early visual responses of MEG signals in humans can be predicted

using features extracted from a randomly initialized and untrained deep neural network

(Cichy et al., 2016). By contrast, we have found that most perceptual effects are absent

in randomly initialized networks, except for global advantage (Section S2). Thus,

training on object classification abolishes the global advantage and introduces

sensitivity to local features.

How can deep networks be made to match neural and perceptual

representations? There could be several ways of doing so. The first and perhaps most

promising direction would be to explicitly train deep networks to produce such

properties in addition to categorisation (Ruder, 2017). Another alternative would be to

train deep networks on tasks such as navigation or agent-object interaction rather than

(or in addition to) object recognition as this is ostensibly what humans also do (Haber

et al., 2018; Yang et al., 2019).

Finally, we note that deep networks are notorious for their susceptibility to

adversarial attacks. State-of-the-art deep neural networks have been shown to fail

catastrophically when input images are subjected to carefully constructed changes

that are barely perceivable to human eyes (Szegedy et al., 2013; Su et al., 2019).

Likewise, deep networks can give erroneous predictions on completely nonsensical

images (Nguyen et al., 2015). Finally, realistic multi-part 3D objects are consistently

misclassified by deep networks across viewpoint changes (Athalye and Carlini, 2018).

What could underlie such unusual behaviour? One possible reason could be the

tendency for deep networks to prioritize local features as described earlier. We

speculate that training deep networks to exhibit all the perceptual and neural

properties described in this study might not only improve their performance but also

make them more robust to adversarial attacks.

METHODS

VGG-16 network architecture & training

All experiments were performed on the VGG-16 network, a feedforward pre-trained deep convolutional neural network trained for object classification on the ImageNet dataset(Deng et al., 2009). We briefly describe the network architecture here, and the reader is referred to the original paper for more details (Simonyan and Zisserman, 2014). The input to the network is an RGB image of size 224 x 224 x 3 and the final output is a vector of confidence scores across 1000 categories. We subtracted the mean RGB value across all images (mean values across all images: R=123.68, G=116.78, B=103.94). The image is passed through a stack of convolutional filters (Figure 1C), where the initial layers have small receptive field (3x3) and later layers are fully connected. A non-linear rectification (ReLu) operation is done after each convolution operation. Five max-pooling layers are present to spatial pool the maximum signal over a 2x2 window of neurons. We used the MATLAB-based MatConvNet software platform (Vedaldi and Lenc, 2014) to extract features and do the analysis. In addition to VGG-16, we also used VGG-face which has the same architecture but trained instead on face identification (Parkhi et al., 2015).

Feature Extraction

For each image, we passed it as input into the network, stored the activations of each layer as a column vector. Hence, a single image we will have 37 feature vectors (one column vector from each layer). To calculate the distance between images A and B, we calculated the Euclidean distance between the corresponding activation vectors.

In all the experiments, we define specific measure based on distances and this

quantity is plotted across layers with a specific chain of symbols as shown in Figure

1C. Symbols used indicates the underlying mathematical operations done in that layer:

unfilled circle for convolution, filled circle for ReLu, diamond for maxpooling and

unfilled square for fully connected layers. Broadly, filled symbols denote linear

operations and unfilled ones indicate non-linear operations.

Experiment 1: Thatcher effect

The stimuli comprised 20 co-registered Indian faces (19 male, 1 female) from

the IISc Indian face dataset (Katti and Arun, 2019). All faces were grayscale, upright

and front-facing. To Thatcherize a face, we inverted the eyes and mouth while keeping

rest of the face intact. We implemented inversion by first registering facial landmarks

on frontal faces using an Active appearance model-based algorithm (Cootes et al.,

2001). Briefly, this method models face appearance as a two-dimensional mesh with

76 nodes, each node represents local visual properties of stereotyped locations such

as corners of eyes, nose, and mouth. We then defined bounding boxes for left and

right eye as well as mouth, by identifying landmarks that correspond to the four corners

of each box. We then locally inverted eye and mouth shape by replacing the top row

of eye or mouth image pixels by the last row and likewise repeating this procedure for

each pair of equidistant pixels rows above and below the middle of the local region.

The inversion procedure was implemented as a custom script written in MATLAB. The

full stimulus set is shown in Section S3.

To calculate a single measure for the Thatcher effect, we calculated a Thatcher

index defined as $\frac{d_{upright} - d_{inverted}}{d_{upright} + d_{inverted}}$, where $d_{upright}$ is the distance between an normal

face and Thatcherized face in upright orientation and $d_{inverted}$ is the distance between

a normal face and Thatcherized face in inverted orientation. We estimated the

Thatcher index for humans from the similarity ratings reported from humans albeit on

a different set of faces (Bartlett and Searcy, 1993). We calculated Thatcher index after

converting the similarity rating (humans gave a rating between 1 to 7 on pair of images)

into a dissimilarity rating (dissimilarity rating = 7- similarity rating).

Experiment 2: Mirror Confusion

The stimuli consisted of 100 objects (50 naturalistic objects and 50 versions of

these objects made by rotating each one by 90°). This was done to avoid any effect

due to the objects own axis of elongation. We created a horizontal and vertical mirror

image of each object. We then gave as input the original image and the two mirror

images to the VGG-16 network and calculated for each layer the distance between the

object and two mirror images. The full stimulus set is shown in Section S3.

To calculate a single measure for mirror confusion, we defined a mirror

confusion index of the form $\frac{d_{horizontal} - d_{vertical}}{d_{horizontal} + d_{vertical}}$, where $d_{horizontal}$ is the distance

between an object and its horizontal mirror image and $d_{vertical}$ is the distance between

an object and its vertical mirror image. We estimated the strength of mirror confusion

index in the brain using previously published data from monkey IT neurons

(Rollenhagen and Olson, 2000). Specifically, we took $d_{horizontal}$ to be the reported

average firing rate difference between the original objects and its horizontal mirror

image, and analogously for $d_{vertical}$.

Experiment 3: Scene Incongruence

The stimuli consisted of 40 objects which was taken from previous studies: 17

objects were from the Davenport study (Davenport and Potter, 2004) and the

remaining 33 from the Munneke study (Munneke et al., 2013). We discarded a few

objects from each set since they did not have a matching category in the ImageNet

database. Each object was embedded against a congruent and an incongruent

background. The full stimulus set is shown in Section S3.

We measured the classification accuracy (Top-1 and Top-5) of the VGG-16

network for the objects pasted onto congruent and incongruent scenes. The final layer

of VGG-16 (Layer 38) returns a probability score for all 1000 categories in the

ImageNet database. The top-1 accuracy is calculated as the average accuracy with

which the object class with the highest probability matches the ground-truth object

label. The top-5 accuracy is calculated as the average accuracy with which the ground-

truth object is present among the object classes with the top 5 probability values. We

report the human (object naming) accuracy on the same dataset from previous studies

(Davenport and Potter, 2004; Munneke et al., 2013).

Experiment 4: Multiple object normalization

The stimuli consisted of forty-nine natural grayscale images and placed them

at three different locations in the image (Figure 4A). We have 147 (49 x 3 = 147)

singletons and randomly selected 200 pairs and 200 triplet composites. We extracted

features for all images (singletons, pairs and triplets) from every layer of the CNN. We

selected a unit for further analysis only if the unit responded differently to at least one

of the images in all the three positions. We then plotted the sum of activations of

selected units in a layer to the singleton images against the activation for the

corresponding pairs (or triplets). The slope of this scatterplot across layers was used

to infer the nature of normalization in CNNs – a slope of 0.5 for pairs and 0.33 for

triplets indicated divisive normalization matching that observed in high-level visual

cortex. The full stimulus set is shown in Section S3.

Experiment 5: Selectivity along multiple dimensions

Here we used the stimuli used in a previous study to assess the selectivity of

IT neurons along multiple dimensions (Zhivago & Arun, 2016). These stimuli consisted

of 8 reference shapes (Figure 3D; top row) and created intermediate parametric

morphs between pairs of these shapes (Figure 3D; example morph between camel to

cat). In addition, to compare texture and shape selectivity, we used 128 natural

textures and 128 silhouette shapes. The full stimulus set is shown in Section S3.

As before we calculated the activation of every layer of the VGG-16 network to

each of the above stimuli are input. Visually active neurons were selected by finding

units with a non-zero variance across this stimulus set. We found the visually active

neurons for each set separately and we selected a unit for further analysis only if that

unit is visually active for both sets. The response of each unit was normalized between

0 and 1. We then calculated the sparseness of each unit across different stimulus sets:

the reference set, the four morphlines, shape set and texture set. For a given stimulus

set with responses r_1, r_2, r_3, . . . r_n, where n is the number of stimuli, the sparseness is

defined as follows: $S = (1 - \frac{\left(\frac{\sum r_i}{n}\right)^2}{\sum \frac{r_i^2}{n}}) / \left(1 - \frac{1}{n}\right)$ (Vinje et al., 2000; Zhivago and Arun,

2016). We then calculated the correlation across neurons between the sparseness on

one stimulus set versus another stimulus set.

Experiment 6: Weber's Law

To test for the presence of Weber's law in the deep network, we manipulated

two elementary features: length and intensity. We created two sets of images, one

varying in the length and the other varying in brightness of a rectangular bar. We chose

the values of lengths and brightness's such that the feature difference computed on

pairs of images spanned a wide range both in terms of absolute as well as relative

differences. The full stimulus set is shown in Section S3.

For each layer of the neural network, we extracted the pattern of activations for

each image and then computed the pairwise activation pattern dissimilarity for all pairs

of images. We then computed the correlation between pattern dissimilarities and

actual feature differences (i.e, difference between the actual lengths or brightnesses

of the rectangular bars in the two images). We computed this correlation for both

absolute (denoted by r_{abs}) as well as for relative feature differences (denoted as r_{rel}).

A positive value for the difference between the two correlation coefficients ($r_{rel} - r_{abs}$)

indicated that the Weber's law was present in a given layer of the neural network.

We also analysed deep networks for the presence of Weber's law for image

intensity, but found highly inconsistent and variable effects. Specifically, the pre-

trained VGG-16 network showed Weber's law for low image intensity levels but not for

high intensity levels.

Experiment 7: Relative Size

We used the stimuli used in a previous study to test whether units in the VGG-

16 network encode relative size (Vighneshvel and Arun, 2015). This stimulus set

consisted of 24 tetrads. A sample tetrad is shown in Figure 2D, with the stimuli

arranged such that images that elicit similar activity are closer. The full stimulus set is

shown in Section S3.

In our previous study (Vighneshvel and Arun, 2015), only a small fraction of

neurons (around 7%) encoded relative size. To identify similar neurons in the deep

network, we first identified the visually responsive units by taking all units with a non-

zero variance across the stimuli. For each unit and each tetrad, we calculated a

measure of size interactions of the form abs(r11 + r22 − r12 − r21), where r11 is the

response to both parts at size 1, r12 is the response to part 1 at size 1 and part 2 at

size 2 etc. We then selected the top 7% of all tetrads with the largest interaction effect.

Note that this step of selection does not guarantee the direction of the relative size

effect. For the selected tetrads, we calculated the relative size index, defined as $\frac{d_1 - d_2}{d_1 + d_2}$

where d_1 and d_2 are distances between the incongruent and congruent stimuli

respectively.

Experiment 8: Decouple pattern shape from surface shape

The stimuli consisted of six patterns superimposed on four surfaces. Each

pattern-surface pair was used to create a tetrad of stimuli as depicted in Figure 4E.

The full stimulus set consisted of 24 tetrads, which were a subset of those tested in

our previous study (Ratan Murty and Arun, 2017). The full stimulus set is shown in

Section S3.

In each VGG-16 layer, we selected visually responsive neurons and normalized

their responses across all stimuli as before in Experiment 5. We then selected the top

9% of all tetrads with an interaction effect calculated as before, as with the previous

study (Ratan Murty and Arun, 2017). For all the selected tetrads we calculated the

surface invariance index, defined as $\frac{d_1 - d_2}{d_1 + d_2}$ where d_1 and d_2 are distances between

incongruent and congruent stimuli.

Experiment 9: 3D processing

We investigated 3D processing in the VGG-16 network by comparing line

drawing stimuli used in a previous perceptual study (Enns and Rensink, 1991). We

compared three pairs of shapes: cuboid, cube and frustum of square in isometric view

with the corresponding Y junctions. The full stimulus set is shown in Section S3. For

each shape, we calculated three distances between equivalent shape pairs with the

same feature difference (Figure 5A). We calculated a 3D processing index, defined as

$\frac{d_1 - d_2}{d_1 + d_2}$ where d_1 and d_2 are distances between the 3D shape and control conditions

respectively.

Experiment 10: Occlusions

We recreated the stimulus set used in a previous study (Rensink and Enns,

1998) as depicted in Figure 5C. The full stimulus set is shown in Section S3. As before

we compared the distance between two pairs of shapes: a pair that differed in

occlusion status (occluded vs unoccluded, or two images that differed in their order of

occlusion), and an equivalent 2D feature control containing the same feature

difference. We then calculated an occlusion index defined as $\frac{d_1 - d_2}{d_1 + d_2}$ where d_1 and d_2

are the distances between the occluded and control conditions respectively.

Experiment 11: Object Parts

We performed two experiments to investigate part processing in deep networks.

In Experiment 11A, we tested what happens when a break is introduced into an object

at a natural cut or an unnatural cut (Xu and Singh, 2002). The full stimulus set is shown

in Section S3. The critical comparison is shown in Figure 6A. For each layer of the

CNN, we extracted features for the three objects and computed the distance of the

intact object with each of the broken objects (d_n and d_u denote distances to the broken

objects with natural and unnatural parts respectively). We then computed a part

processing index, defined as $\frac{d_u - d_n}{d_u + d_n}$.

In Experiment 11B, we asked whether whole object dissimilarities computed on

CNN feature representations could be understood as a linear combination of

dissimilarities between their natural or unnatural part decompositions as reported

previously for visual search (Pramod and Arun, 2016b). We considered seven whole

objects that could be broken down into either natural or unnatural parts and

recombined the parts to form other objects. That is, we created two sets each

containing 49 objects made either from natural or unnatural parts of the original seven

objects. The full stimulus set is shown in Section S3. We then selected 492 pairs of

objects from each set (including all 21 pairs from the common set) and calculated the

feature distances from each layer of the CNN. We fit a part summation model to

explain pairwise whole-object distances as a function of pairwise part relations, as

described previously (Pramod and Arun, 2016b). We then compared model

performance on the 21 pairwise distances between the common objects. We denoted

by $r_{natural}$ the correlation between observed and predicted distances assuming natural

part decomposition and by $r_{unnatural}$ the model correlation assuming unnatural part

decomposition. The natural part advantage was computed as ($r_{natural} - r_{unnatural}$). The

same measure was computed for human perception.

Experiment 12: Global Shape Advantage

We created a set of 49 hierarchical stimuli by combining seven shapes at global

scale and the same seven shapes at the local scale (Jacob and Arun, 2019). The full

stimulus set is shown in Section S3. We extracted features from all layers of CNNs

and calculated the Euclidean distance between all pairs of hierarchical shapes. We

calculated the global distance as the mean distance between image pairs having only

global change.   Similarly, we calculated the local distance as the mean distance

between image pairs having only local change. A sample global/local change pair is

shown in Figure 6E. We calculated a global advantage index as $\frac{d_{Global} - d_{Local}}{d_{Global} + d_{Local}}$.

REFERENCES

Athalye A, Carlini N (2018) On the Robustness of the CVPR 2018 White-Box Adversarial Example Defenses. arXiv:2–3.

Baker N, Lu H, Erlikhman G, Kellman PJ (2018) Deep convolutional networks do not classify based on global object shape Einhäuser W, ed. PLOS Comput Biol 14:e1006613.

Bartlett JC, Searcy J (1993) Inversion and configuration of faces. Cogn Psychol 25:281–316.

Belongie S, Malik J, Puzicha J (2002) Shape matching and object recognition using shape contexts. IEEE Trans Pattern Anal Mach Intell 24:509–522.

Cichy RM, Khosla A, Pantazis D, Torralba A, Oliva A (2016) Comparison of deep neural networks to spatio-temporal cortical dynamics of human visual object recognition reveals hierarchical correspondence. Sci Rep 6:27755.

Cichy RM, Pantazis D, Oliva A (2014) Resolving human object recognition in space and time. Nat Neurosci 17:455–462.

Cootes TF, Edwards GJ, Taylor CJ (2001) Active appearance models. IEEE Trans Pattern Anal Mach Intell 23:681–685.

Davenport JL, Potter MC (2004) Scene consistency in object and background perception. Psychol Sci 15:559–564.

Deng J, Dong W, Socher R, Li L-J, Kai Li, Li Fei-Fei (2009) ImageNet: A large-scale hierarchical image database. In: 2009 IEEE Conference on Computer Vision and Pattern Recognition, pp 248–255. IEEE.

Dodge S, Karam L (2019) Human and DNN Classification Performance on Images With Quality Distortions. ACM Trans Appl Percept 16:1–17.

Eckstein MP, Koehler K, Welbourne LE, Akbas E (2017) Humans, but Not Deep Neural Networks, Often Miss Giant Targets in Scenes. Curr Biol 27:2827-2832.e3.

Enns JT, Rensink R a (1991) Preattentive recovery of three-dimensional orientation from line drawings. Psychol Rev 98:335–351.

Enns JT, Rensink RA (1990) Sensitivity to Three-Dimensional Orientation in Visual Search. Psychol Sci 1:323–326.

Fleuret F, Li T, Dubout C, Wampler EK, Yantis S, Geman D (2011a) Comparing machines and humans on a visual categorization test. Proc Natl Acad Sci U S A 108:17621–17625.

Fleuret F, Li T, Dubout C, Wampler EK, Yantis S, Geman D (2011b) Comparing machines and humans on a visual categorization test. Proc Natl Acad Sci U S A 108:17621–17625.

Geirhos R, Rubisch P, Michaelis C, Bethge M, Wichmann FA, Brendel W (2018a) ImageNet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. arXiv:1–22.

Geirhos R, Temme CRM, Rauber J, Schütt HH, Bethge M, Wichmann FA (2018b) Generalisation in humans and deep neural networks. arXiv.

Haber N, Mrowca D, Fei-Fei L, Yamins DLK (2018) Learning to Play with Intrinsically-Motivated Self-Aware Agents. Adv Neural Inf Process Syst 2018-Decem:8388–8399.

Jacob G, Arun SP (2019) How the forest interacts with the trees: Multiscale shape integration explains global and local processing. bioRxiv:777110.

Jarrett K, Kavukcuoglu K, Ranzato MA, LeCun Y (2009) What is the best multi-stage architecture for object recognition? In: 2009 IEEE 12th International Conference on Computer Vision, pp 2146–2153. IEEE.

Kar K, Kubilius J, Schmidt K, Issa EB, DiCarlo JJ (2019a) Evidence that recurrent circuits are critical to the ventral stream's execution of core object recognition behavior. Nat Neurosci 22:974–983.

Kar K, Kubilius J, Schmidt K, Issa EB, DiCarlo JJ (2019b) Evidence that recurrent circuits are critical to the ventral stream's execution of core object recognition behavior. Nat Neurosci 22:974–983.

Katti H, Arun SP (2019) Are you from North or South India? A hard face-classification task reveals systematic representational differences between humans and machines. J Vis 19:1.

Katti H, Peelen M V, Arun SP (2017) How do targets, nontargets, and scene context influence real-world object detection? Atten Percept Psychophys 79:2021–2036.

Katti H, Peelen M V, Arun SP (2019) Machine vision benefits from human contextual expectations. Sci Rep 9:2112.

Kietzmann TC, Spoerer CJ, Sörensen LKA, Cichy RM, Hauk O, Kriegeskorte N (2019) Recurrence is required to capture the representational dynamics of the human visual system. Proc Natl Acad Sci:201905544.

Kimchi R (1994) The role of wholistic/configural properties versus global properties in visual form perception. Perception 23:489–504.

Mitchell S (1988) Tao te ching: A new English version. Harper Collins.

Mongia M, Kumar K, Erraqabi A, Bengio Y (2016) On Random Weights for Texture Generation in One Layer Neural Networks. arXiv.

Munneke J, Brentari V, Peelen M V. (2013) The influence of scene context on object recognition is independent of attentional focus. Front Psychol 4:552.

Navon D (1977) Forest before trees: The precedence of global features in visual perception. Cogn Psychol 9:353–383.

Nguyen A, Yosinski J, Clune J (2015) Deep neural networks are easily fooled: High confidence predictions for unrecognizable images. In: 2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp 427–436. IEEE.

Pardo-Vazquez JL, Castiñeiras-de Saa JR, Valente M, Damião I, Costa T, Vicente MI, Mendonça AG, Mainen ZF, Renart A (2019) The mechanistic foundation of Weber's law. Nat Neurosci 22:1493–1502.

Parkhi OM, Vedaldi A, Zisserman A (2015) Deep Face Recognition. In: Procedings of the British Machine Vision Conference 2015, pp 41.1-41.12. British Machine Vision Association.

Pramod RT, Arun SP (2014) Features in visual search combine linearly. J Vis 14:1–20.

Pramod RT, Arun SP (2016a) Do computational models differ systematically from human object perception? Proc IEEE Comput Soc Conf Comput Vis Pattern Recognit 2016-Decem:1601–1609.

Pramod RT, Arun SP (2016b) Object attributes combine additively in visual search. J Vis 16:8.

Rajalingham R, Issa EB, Bashivan P, Kar K, Schmidt K, DiCarlo JJ (2018) Large-scale, high-resolution comparison of the core visual object recognition behavior of humans, monkeys, and state-of-the-art deep artificial neural networks. J Neurosci.

Ratan Murty NA, Arun SP (2017) Seeing a straight line on a curved surface: decoupling of patterns from surfaces by single IT neurons. J Neurophysiol 117:104–116.

Rensink RA, Enns JT (1998) Early completion of occluded objects. Vision Res 38:2489–2505.

Rollenhagen JE, Olson CR (2000) Mirror-Image Confusion in Single Neurons of the
Macaque Inferotemporal Cortex. Science (80-) 287:1506–1509.
Rosenfeld A, Zemel R, Tsotsos JK (2018) The Elephant in the Room. ArXiv.
Ruder S (2017) An Overview of Multi-Task Learning in Deep Neural Networks. arXiv.
Rust NC, Movshon JA (2005) In praise of artifice. Nat Neurosci 8:1647–1650.
Serre T (2019) Deep Learning: The Good, the Bad, and the Ugly. Annu Rev Vis Sci
5:399–426.
Simonyan K, Zisserman A (2014) Very Deep Convolutional Networks for Large-Scale
Image Recognition. arXiv:1–14.
Sinz FH, Pitkow X, Reimer J, Bethge M, Tolias AS (2019) Engineering a Less Artificial
Intelligence. Neuron 103:967–979.
Su J, Vargas DV, Sakurai K (2019) One Pixel Attack for Fooling Deep Neural
Networks. IEEE Trans Evol Comput 23:828–841.
Szegedy C, Zaremba W, Sutskever I (2013) Intriguing properties of neural networks.
arXiv Prepr arXiv:1–10.
Thompson P (1980) Margaret Thatcher: a new illusion. Perception 9:483–484.
Vedaldi A, Lenc K (2014) MatConvNet - Convolutional Neural Networks for MATLAB.
arXiv.
Vighneshvel T, Arun SP (2015) Coding of relative size in monkey inferotemporal
cortex. J Neurophysiol 113:2173–2179.
Vinje WE, Gallant JL, Vinje WE, Gallant JL (2000) Sparse coding and decorrelation in
primary visual cortex during natural vision. Science (80-) 287:1273–1276.
Xu Y, Singh M (2002) Early computation of part structure: Evidence from visual search.
Percept Psychophys 64:1039–1054.
Yang J, Ren Z, Xu M, Chen X, Crandall D, Parikh D, Batra D (2019) Embodied Visual
Recognition. arXiv.
Zhivago KA, Arun SP (2016) Selective IT neurons are selective along many
dimensions. J Neurophysiol 115:1512–1520.
Zoccolan D, Cox DD, DiCarlo JJ (2005) Multiple Object Response Normalization in
Monkey Inferotemporal Cortex. J Neurosci 25:8150–8164.
958
959

ACKNOWLEDGEMENTS
Funding. This work was supported by the Wellcome Trust-DBT India Alliance
Fellowship (Grant # IA/S/17/1/503081) awarded to SPA, and by travel grants to GJ
from the Department of Science and Technology, Government of India and from the
Pratiksha Trust.
Author Contributions. GJ, PRT, HK & SPA designed the study, GJ performed
Experiments 5,7,8-12 and replicated the analyses for all experiments, HK & GJ
performed Experiments 1-3, PRT performed Experiments 4, 6 & 11, and GJ & SPA
wrote the manuscript with inputs from PRT & HK.
Conflicts of interest. The authors declare no conflicts of interest.
970

SUPPLEMENTARY MATERIAL
for

"Do deep neural networks see the way we do?"
Georgin Jacob, RT Pramod, Harish Katti & SP Arun

CONTENTS

SECTION S1. RESULTS WITH OTHER FEED FORWARD NETWORKS

1   The results in the main text were based on testing a specific feedforward network,
2 namely VGG-16. Here, we investigated other feedforward network architectures for the
3 presence of the same perceptual and neural phenomena. We did not test the recurrent
4 networks since unfolding recurrent networks over time make them equivalent to a deep
5 feedforward network (LeCun, Bengio and Hinton, 2015; Liang and Hu, 2015).
6
Methods
We selected four popular pre-trained feedforward networks, all trained on the
ImageNet ILSVRC challenge data (Deng *et al.*, 2009; Russakovsky *et al.*, 2014). We
selected architectures that are shallower and deeper than VGG-16, to investigate whether
the depth of the network influences the emergence of the perceptual and neural
properties. All networks were implemented using MatConvNet framework in MATLAB,
and their performance is summarized in Table S1.
14
15 *Network 1: AlexNet.* This network won the ILSVRC 2012 challenge by a large margin
16 (Krizhevsky, Alex, Ilya Sutskever, 2012). The network consists of five convolutional layers
17 and three fully-connected layers. Drop-out technique is used fully connected layers to
18 reduce overfitting. The architecture of this network is shallower compared to VGG-16.
19
20 *Network 2: GoogLeNet.* This network follows the inception architecture which is well
21 known for better utilization of computing resources inside the network. This network won
22 the classification track of the ILSVRC 2014 challenge (Szegedy *et al.*, 2015).
23
24 *Network 3: ResNet-50.* ResNet-50 is a shallower variant of the ResNet-152 detailed
25 below.
26
27 *Network 4: ResNet-152.* The network uses a residual learning principle which make them
28 capable of training deeper networks without the problem of vanishing gradients (He *et al.*,
29 2016). The ResNet architecture won three tracks (classification, detection and
30 localization) of the ILSVRC 2015 challenge and two tracks (detection and segmentation)
31 of the COCO 2015 challenge.
32

Name of network	Performance	
	Top-1 error (%)	Top-5 error (%)
AlexNet	42.6	19.6
VGG-16	28.5	9.9
GoogLeNet	34.2	12.9
ResNet-50	24.6	7.7
ResNet-152	23.0	6.7

33 **Table S1. Performance of deep networks on the ILSVRC 2012 validation dataset**
34 **(accuracy reported from MatConvNet website, accessed on 27th November 2019).**
35
36
37

Results

Experiment 1: Thatcher effect. The Thatcher index for each network across layers is shown in Figure S1A. It can be seen that the Thatcher index is negative for all networks in their final layers except for GoogLeNet which showed a small positive level in the final layers. For the networks with higher classification performance (GoogLeNet, ResNet-50, ResNet-152), we observed an interesting pattern whereby the Thatcher index is positive in the intermediate layers. This is true even for the VGG-16 network (Figure 2B).

Experiment 2: Mirror Confusion. The mirror confusion index for each network is shown in Figure S1B. All networks exhibited an increasing mirror confusion index across layers, just as we observed for VGG-16 (Figure 2D).

Experiment 3: Scene incongruence. The classification accuracy for objects in congruent and incongruent scenes is shown for each network in Figure S1C. It can be seen that the deeper architectures show smaller incongruence effects.

Experiment 4: Multiple object normalization. The normalization slope for pairs and triplets for all networks is shown in Figure S1C. It can be seen that there is increased normalization in the later layers in all networks.

Experiment 5: Selectivity across multiple dimensions. The correlation between sparseness of units in each layer for textures and shapes is shown in Figure S1E. It can be seen that all networks show an increasing trend in later layers. We obtained qualitatively similar results for comparing sparseness on the reference shape set and morph lines (not shown for brevity).

Experiment 6. Weber's law. The Weber's law measure (difference in correlation for relative vs absolute length) for all networks is shown in Figure S1F. It can be seen that the Weber's law arises in the later layers for all the networks.

Experiment 7. Relative size. The relative size effect for each network across layers is shown in Figure S2A. It can be seen that the relative size effect is extremely weak and variable across networks, and never approaches the levels observed in the brain (relative size index = 0.39).

Experiment 8: Decoupling patterns from surfaces. The surface invariance index for each network across layers is shown in Figure S2B. It can be seen that the index is consistently negative for all networks, as observed for VGG-16.

Experiment 9: 3D processing. The 3D processing indices (for Condition 1 & 2) for each network across layers is shown in Figure S2C. It can be seen that the 3D processing indices are generally negative for all networks, and even if the index is positive, the levels are much smaller than observed in humans.

83   *Experiment 10: Occlusions.* The occlusion indices for each network across layers is
84   shown in Figure S2D. It can be seen that both indices are consistently negative across
85   layers, as observed for VGG-16.
86
87   *Experiment 11: Object parts.* The natural part advantage for Experiment 11B is shown for
88   each network across layers in Figure S2E. It can be seen that the natural part advantage
89   is highly variable across networks, with GoogLeNet showing levels comparable to
90   humans in the later layers.
91
92   *Experiment 12: Global shape advantage.* The global advantage index for each network
93   across layers is shown in Figure S2F. Across all networks, there is a slight global
94   advantage in the intermediate layers, which reverses into a local advantage in the later
95   layers. Thus, it appears that all the feedforward networks are using local features for
96   classification.
97

98
99
100 **Figure S1: Experiments 1-6 with other feed-forward networks.** Each column
101 represents a deep network (from left to right: AlexNet, GoogLeNet, ResNet-50 and Reset-
102 152) and each row represents an experiment (A-F: experiment 1-6). In each subplot an
103 experiment specific index or measure is plotted across layers.
104

105
106 **Figure S2: Experiments 7-12 for other feedforward networks.** All conventions as in
107 Figure S1.

SECTION S2. RESULTS WITH RANDOMLY INITIALIZED NETWORKS

108   We have shown that deep neural networks trained for object-recognition show
109 some perceptual phenomena but not others, but we wondered whether any of these
110 phenomena can be observed even in an untrained network, simply as a consequence of
111 the architecture. To address this issue, we repeated Experiments 1-12 on an untrained
112 VGG-16 architecture with randomly initialized weights.
113

Methods
We estimated the probability distribution functions of the weights in each layer of
the pre-trained VGG-16 network and picked the weights randomly from this estimated
distribution. This process was done layer-wise to obtain the randomly initialized network.
We then performed all Experiments on this network except for Experiment 3 (scene
incongruence) since this experiment requires object classification. We then performed all
data analyses exactly as before.
121

Results
The results for the random network and the pre-trained VGG-16 network are
shown together in Figure S3. In most cases (Experiments 1, 2, 6-11), we observed no
specific trend for the random network towards or away from human/neural levels, which
is what would be expected since the random network has no specific bias or training. We
observed systematic and interesting differences for the other experiments, which we
discuss in detail below.
129

Experiment 4: Multiple Object normalization. The divisive normalization slope for the
random network is shown in Figure S3C-D. Here, the random network showed perfect
divisive normalization, in that the net response to AB is exactly the average of the
responses to A & B separately. To investigate this puzzling observation further, we looked
at the unit activations in the random network. We found that the activations for any pair
of natural images was highly correlated (correlation of layer-37, mean ± sd: r = 0.98 ±
0.01), suggesting that these units were not very selective for images. This means that
every image activates the network in the same way. As a result, the response to AB and
the response to A & B separately would be identical, giving rise to a perfect slope of 0.5
in the relationship between the response AB and the sum of responses A + B. Thus, the
divisive normalization observed in the random network is a trivial outcome of its lack of
image selectivity.
142

Experiment 5: Selectivity across multiple dimensions. Here too the random network
shows a high correlation between shape and texture selectivity (Figure S3E). We suspect
that this too is a consequence of the very low selectivity for images in the random network,
whereby some units have zero selectivity (and therefore respond equally to all images)
and others have weak selectivity (and therefore show slight differences in the response
across images).
149

Experiment 12: Global shape advantage. Here we observed an interesting pattern: the
random network showed a global advantage that increased across layers. This is likely

due to increased pooling in the higher layers, but interestingly the pre-trained VGG-16
network shows the opposite pattern. Thus, it appears that object classification training
abolishes the global advantage that is intrinsic to the network architecture. We speculate
that this local advantage might arise because of the demands of distinguishing between
highly similar categories present in the ImageNet dataset (e.g. there are 90 categories of
dogs among the total of 1000 categories in ImageNet). Testing this possibility will require
training the VGG-16 architecture on highly distinctive object classes.
159
160

161
162 **Figure S3. Experiments 1-12 for randomly initialized networks.** Results for
163 Experiments 1-12 (except for #3) are shown. In each panel, the corresponding
164 experiment-specific index is plotted for the randomly initialized VGG-16 (*red*) with the pre-
165 trained VGG-16 (*blue*). All other conventions are as in the main text.
166

A **Experiment 1: Thatcher effect**

Faces are removed due to bioRxiv policy

B **Experiment-2 : Mirror confusion**

Figure S4. Stimulus set used for Experiments 1 & 2.

Experiment 3 : Scene incogruence

Davenport & Potter, 2004

Munneke et. al., 2013

169
170 **Figure S5. Stimulus set used for Experiment 3**. Each pair of images depicts an object
171 against a congruent and incongruent background. Stimulus set reproduced with consent.
172
173

Experiment 4: Multiple object normalization

Experiment-5: Selectivity across multiple dimesions

174
Figure S6. Stimulus set used for Experiments 4 & 5
Plots A-D shows the images used for experiment 4 and plots E-G shows the images
used in experiment-5.

A) 49 natural images used for experiment-4
B) Singletons are formed by placing the 49 objects either at top, middle or bottom.
34 selected singletons are shown from 147 singletons used in this experiment.
C) 34 selected pairs are shown from 200 pairs used in experiment-4.
D) 34 selected triplets are shown from 200 triplets used in experiment-4.
E) Shows all four morphlines used in experiment-5.
F) Shown 51 selected shapes of the total set of 120 shapes.
G) Shown 51 selected textures out of the total set of 120 textures.
186

Figure S7. Stimulus set used for Experiments 6-8

A) Shows the images used in Weber's law experiment. There are two baselines and
188 each column is an image pairs which has equal length difference from the
189 baseline.
190
191 B) Shows 24 tetrads used in Relative Size experiment.
192 C) Shows 24 tetrad used in surface invariance experiments. Tetrads are made by
193 transforming eight shapes onto five different surfaces.

Experiment 9: 3d processing

A   Condition-1   B   Condition-2

Experiment 10: Occlusions

C   D

Occlusion   Depth Ordering

Figure S8. Stimulus set used for Experiments 9-10

A) Two sets of images used to compare the 3D perception in the CNNs. Images in top row have 3D effect whereas the images in the bottom row have an equivalent same feature difference without a perceived 3D difference.

B) Two sets of images used to compare the 3D perception in the CNNs. Images in top row have 3D effect whereas the images in the bottom row has the same feature difference and an additional common outer shape but not the 3D perception.

C) Each row shows a set of images used for testing basic occlusion effect.

D) Each row shows a set of images used for testing depth ordering effect.

A   **Experiment 11: Object parts**

Xu & Singh, 2002

B

Unnatural Cut   **Natural Cut**

Objects common to both sets

Pramod & Arun, 2016

196
197 **Figure S9. Stimulus set used for Experiments 11**

    A) Shows the images used to check part processing in experiment-11

    B) Shows the images used to check part advantage in experiment-11. The seven shapes in the diagonal position of both Unnatural and natural set are the same.

Experiment 12: Global shape advantage

global shape varies

local shape varies

Jacob & Arun, 2019

198   **Figure S10. Stimulus set used for Experiments 12.** A total of 49 images used to check
199   global advantage. These images are formed by all combinations of seven shapes are
200   global and local scales.
201

REFERENCES

Deng, J. *et al.* (2009) 'ImageNet: A large-scale hierarchical image database', in *2009 IEEE Conference on Computer Vision and Pattern Recognition.* IEEE, pp. 248–255. doi: 10.1109/CVPR.2009.5206848.

He, K. *et al.* (2016) 'Deep Residual Learning for Image Recognition', in *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR).* IEEE, pp. 770–778. doi: 10.1109/CVPR.2016.90.

Krizhevsky, Alex, Ilya Sutskever, and G. E. H. (2012) 'ImageNet Classification with Deep Convolutional Neural Networks', *Advances in Neural Information Processing Systems 25 (NIPS 2012)*, pp. 1–9.

LeCun, Y., Bengio, Y. and Hinton, G. (2015) 'Deep learning.', *Nature*, 521(7553), pp. 436–44. doi: 10.1038/nature14539.

Liang, M. and Hu, X. (2015) 'Recurrent convolutional neural network for object recognition', *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition.* IEEE, 07-12-June(Figure 1), pp. 3367–3375. doi: 10.1109/CVPR.2015.7298958.

Russakovsky, O. *et al.* (2014) 'ImageNet Large Scale Visual Recognition Challenge', *International Journal of Computer Vision.* Springer US, 115(3), pp. 211–252. doi: 10.1007/s11263-015-0816-y.

Szegedy, C. *et al.* (2015) 'Going deeper with convolutions', in *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR).* IEEE, pp. 1–9. doi: 10.1109/CVPR.2015.7298594.