The neural representation of emotion is high-dimensional, categorical, and distributed across transmodal brain regions

Tomoyasu Horikawa[1*], Alan S. Cowen[2], Dacher Keltner[2], Yukiyasu Kamitani[1,3, 4*]

[1] Department of Neuroinformatics, ATR Computational Neuroscience Laboratories, Kyoto, Japan

[2] Department of Psychology, University of California, Berkeley, CA, USA

[3] Graduate School of Informatics, Kyoto University, Kyoto, Japan

[4] Lead contact

* Correspondence: horikawa-t@atr.jp, kamitani@i.kyoto-u.ac.jp

Summary

Central to our subjective lives is the experience of different emotions. Recent

behavioral work mapping emotional responses to 2185 videos found that people

experience upwards of 27 distinct emotions, which occupy a high-dimensional space,

and that emotional categories, more so than affective dimensions, organize reports of

subjective experience. Here, we sought to identify the neural substrates of this high-

dimensional space of emotional experience using fMRI responses to the videos from

this previous study. Our statistical analyses demonstrated that (1) dozens of video-

evoked emotions were accurately predicted from fMRI patterns in multiple brain

regions, (2) voxel-wise encoding models trained using categories better predicted voxel-

wise responses than dimensions with unique superiority over visual and semantic

covariates in transmodal regions, and (3) emotion-related fMRI responses had a cluster-

like organization efficiently characterized by distinct categories. These results support

an emerging theory of the high-dimensional emotion space, illuminating its neural

foundations distributed across transmodal regions.

Keywords: emotional categories, affective dimensions, decoding, encoding, functional

magnetic resonance imaging

Introduction

Emotions are brief mental states internally generated by the brain, constituting an evaluative aspect of our diverse subjective experiences. Traditionally, subjective emotional experiences have been described in theoretical and empirical studies using a limited set of emotion categories (e.g., happiness, anger, fear, sadness, disgust, and surprise) as proposed in the basic emotion theory (Ekman et al., 1969; Plutchik, 1980) and by broad affective dimensions (e.g., valence and arousal) that underpin the circumplex model of affect and the more recent core affect theory (Posner et al., 2005; Russell, 1980, 2003). Grounded in these theoretical claims, affective neuroscientists have investigated neural signatures underlying those representative emotion categories and affective dimensions (Barrett, 2017; Celeghin et al., 2017; Giordano et al., 2018; Hamaan, 2012; Kragel and LaBar, 2015; Lindquist and Barrett, 2012; Saarimäki et al., 2016; Satpute and Lindquist, 2019; Wager et al., 2015), finding that distributed brain regions and functional networks are crucial for representing individual emotions. Importantly, though, studies within this tradition have limited their focus to a small set of emotions. This narrow focus does not capture the increasingly complex array of states associated with distinct experiences (Cowen and Keltner, 2017, 2019; Cowen et al., 2018, 2019). As a result, much of the variability in the brain's representation of emotional experience likely has yet to be explained (Cowen et al., 2019; Lindquist and Barrett, 2012).

To elucidate the structure of diverse emotional experiences, Cowen and Keltner (2017, 2018; Cowen et al., 2019) offered a new conceptual and methodological approach to capture the more complex "high-dimensional emotion space" that characterizes emotional experiences in response to a diverse array of stimuli in large-scale human behavioral experiments. In their study, Cowen and Keltner (2017) applied statistical methods to analyze reported emotional states elicited by 2185 videos each annotated by multiple raters using self-report scales of 34 emotion categories (e.g., joy, amusement, and horror) and 14 affective dimensions (e.g., valence and arousal) derived from basic, constructivist, and dimensional theories of emotion. They identified 27 distinct varieties of emotional experience reliably associated with distinct videos. Furthermore, they found that the affective dimensions explained only a fraction of the variance in self-

reports of subjective experience when compared to emotion categories, a finding that

has been replicated in studies of facial expression, speech prosody, nonverbal

vocalization, and music (Cowen et al., 2019; Cowen et al., in press). This work lays a

foundation for examining the neural bases of the emotional experiences in terms of a

rich variety of states, as well as whether — at the level of neural response — categories

or dimensions organize the experience of emotion, and how a diverse array of states

cluster in their meaning.

The methodological criteria established in this study of emotion — the use of broad

ranging stimuli sufficient to compare theoretical models of emotion — can be readily

extended to the study of the neural basis of emotion. In addition, it is important for

studies of the neural basis of emotion to consider activity across the whole brain, given

that diverse psychological processes and distributed brain regions and functional

networks are known to contribute to the representation of various emotional states

(Barrett, 2017; Celeghin et al., 2017; Hamaan, 2012; Lindquist and Barrett, 2012;

Satpute and Lindquist, 2019). Although some recent studies have examined a richer

variety of emotions than typically tested before (more than twenty), their investigations

have been limited to specific brain regions (Kragel et al., 2019; Skerry and Saxe, 2015)

and have relied on relatively small numbers of stimuli or conditions (tens or hundreds,

but not thousands) (Koide-Majima, et al., 2018; Saarimäki et al., 2018). Moreover,

studies have not adequately controlled for sensory and semantic features that are known

to be encoded throughout the cortex (Huth et al., 2012) and may contaminate neural

responses to emotional stimuli. Given these considerations, a comprehensive analysis of

whole-brain responses to diverse emotional stimuli is still needed.

We sought to understand the neural underpinnings of the high-dimensional space of

diverse emotional experiences associated with a wide range of emotional stimuli using

the experimental resources generated in the study by Cowen and Keltner (2017).

Specifically, we measured whole-brain functional magnetic resonance imaging (fMRI)

signals while five subjects watched 2181 emotionally evocative short videos. We then

analyzed the measured fMRI signals using data-driven approaches, including neural

decoding, voxel-wise encoding, and unsupervised modeling methodologies (Figure 1A)

to investigate neural representations of emotional experiences characterized by 34

emotion categories and 14 affective dimensions with which the videos were previously

annotated by a wide range of raters (Figure 1B).

Using multiple analytical approaches, we investigated different facets of the neural

representation of emotional experience. Neural decoding was used to examine whether

and where individual features (e.g., ratings of an emotion) are represented in the brain,

and provides a powerful way to identify mental states of subjects from brain activity

patterns (Horikawa and Kamitani, 2017; Kragel et al., 2016; Sitaram et al., 2011).

Voxel-wise encoding modeling made it possible to evaluate how specific sets of

features (e.g., emotion category scores) modulate activity of individual voxels, and to

characterize representational properties of individual voxels by comparing encoding

accuracies from different feature sets (de Heer et al., 2017; Güçlü and van Gerven,

2015; Kell et al., 2018; Lescroart and Gallant, 2019). Unsupervised modeling methods,

including dimensionality reduction and clustering analyses, were used to characterize

the distributional structure of brain representations of emotion in an exploratory manner

(Kriegeskorte et al., 2008).

Here, we first show that dozens of distinct emotions were reliably predicted from

activity patterns in multiple brain regions, which enabled accurate identification of

emotional states. While the brain regions representing individual emotions overlapped,

configurations of regions proved to be unique to each emotion and consistent across

subjects. We show that voxel activity in most brain regions was better predicted by

voxel-wise encoding models trained on ratings of emotion categories than on ratings of

affective dimensions. Comparisons with other models trained on visual or semantic

features revealed that the emotion category model uniquely explained response

modulations of voxels in transmodal regions. Finally, unsupervised modeling of

emotion-related neural responses showed that distributions of brain activity patterns

associated with diverse emotional experiences were organized with clusters

corresponding to specific emotion categories, which were bridged by continuous

gradients. These results provide support for the theory that emotion categories occupy a

high-dimensional space (Cowen and Keltner, 2017) and shed new light on the neural

underpinnings of reported emotional experience.

Figure 1. Decoding and encoding emotional responses in fMRI signals evoked by

videos

(A) Schematic of the experiment and analyses. fMRI signals were recorded while

subjects viewed emotional videos. Decoding/encoding models were trained to predict

scores/responses of individual emotions/voxels for presented videos from patterns of

responses/scores, respectively.

(B) Score distributions of emotion categories and affective dimensions. Score

distributions from a total of 2181 unique videos are shown for 34 emotion categories

and 14 affective dimensions (see Methods: "Video stimulus labeling"). For emotion

categories, each dot indicates a proportion the category was evaluated with non-zero

scores for each video. For affective dimensions, black bars indicate mean values across

all videos. In the main analyses, mean scores averaged across multiple raters were used

for each video.

124 Results

To understand neural representations of diverse emotional experiences associated with

rich emotional content, we recorded whole-brain fMRI signals from five subjects while

they were freely viewing emotionally evocative short videos (Figure 1A). The stimuli

consisted of a total of 2181 unique videos annotated with a total of 48 emotion ratings

(Figure 1B; 34 emotion categories and 14 affective dimensions), each by multiple

human raters, which were collected in a previous study (Cowen and Keltner, 2017; see

Methods: "Video stimulus labeling"). The fMRI volumes measured over the course of

each video presentation were shifted by 4 s and averaged to estimate fMRI responses to

individual video stimuli. We performed decoding and encoding analyses between the

fMRI responses to each video and its emotion ratings by using regularized linear

regression in a cross-validated manner (6-fold cross-validation; see Methods:

"Regularized linear regression analysis"). We also performed unsupervised modeling of

the fMRI responses to examine the distribution of emotion-related brain activity

patterns and whether their organization was better described by emotion categories or

by broad affective dimensions (see Methods: "Dimensionality reduction analysis" and

"Clustering analysis").

Neural decoding analysis to predict emotion scores

We first used a neural decoding analysis to examine whether the emotions associated

with presented videos could be predicted from brain activity patterns within specific

regions and across the brain. We constructed a decoding model (decoder) for each

emotion (34 emotion categories and 14 affective dimensions) to predict emotional

experience ratings from brain activity patterns. The decoders of individual emotions

were separately trained using activity patterns in multiple brain regions defined by a

parcellation provided by the Human Connectome Project (Glasser, et al., 2016), which

delineated 180 cortical areas per hemisphere (HCP180). This procedure thus yielded a

total of 360 region-wise decoders from cortical activity per emotion. The performance

for each emotion and brain region was evaluated by computing a Pearson correlation

coefficient between predicted and true emotion scores across the 2181 unique videos.

The decoding accuracies for the categories and dimensions obtained from multiple brain

regions are shown in Figures 2A and B, respectively. Although scores of three emotion

categories (envy, contempt, and guilt) were not reliably predicted from any brain region

of any of the five subjects, scores of the remaining emotions were accurately predicted

from brain activity patterns in multiple brain regions ($r > 0.097$, permutation test, $p <$

0.01, Bonferroni correction by the number of brain regions). The results established that

ratings of the 27 emotion categories that were reported to be reliably elicited by video

stimuli (Cowen and Keltner, 2017) were highly decodable from multiple brain regions.

The poor accuracies of a few categories of emotion may be attributable in part to

relatively lower proportions of videos evoking these categories (Figure 1B).

To integrate information represented in multiple brain regions, we constructed an

ensemble decoder for each emotion by averaging predictions from multiple region-wise

decoders selected based on decoding accuracy via a nested cross-validation procedure

(black squares in Figure 2A and B; see Methods: "Construction of ensemble decoders").

Overall, the ensemble decoders tended to show higher accuracy than the best region-

wise decoders (119/170 = 70.0% for categories, 48/70 = 68.6% for dimensions, pooled

across emotions and subjects). These results indicate that information about individual

emotions is represented in multiple brain regions in a complementary manner,

supporting the notion of distributed, network-based representations of emotion (Barrett,

2017; Celeghin et al., 2017; Hamaan, 2012; Lindquist and Barrett, 2012; Saarimäki et

al., 2016; Satpute and Lindquist, 2019).

Region-wise decoding accuracy maps

To investigate which brain regions represented individual emotions, we visualized

decoding accuracy maps by projecting accuracies from the 360 individual brain regions

onto flattened cortical surfaces (Figures 2C and D; five subjects averaged). In general,

brain regions showing high accuracy for specific emotions were not focal but rather

distributed across cortical regions including visual, parietal, and frontal regions, further

supporting the notion that distributed brain regions and functional networks are

recruited to represent individual emotions.

Inter-individual consistency in brain regions representing distinct emotions

To examine the extent to which the brain regions informative for decoding were unique to each emotion and consistent across subjects, we next tested whether emotions could be identified across subjects based on the region-wise decoding accuracy patterns of individual emotions estimated for individual subjects. A region-wise accuracy pattern for one emotion from one subject was used to identify the same emotion among a variable number of candidates (a pattern for the same emotion and randomly selected patterns for other emotions) from another subjects using Pearson correlation coefficients (see Methods: "Emotion identification analysis"). The analysis was performed for all pairs among five subjects ($n = 20$) separately using the accuracies for the categories and dimensions. For most of the categories and dimensions, correlations between the same emotion pairs (congruent; mean correlations, 0.618 for categories, 0.636 for dimensions) were larger than correlations between different emotion pairs (incongruent; mean correlations, 0.435 for categories, 0.463 for dimensions) (Figure 2E). Furthermore, mean identification accuracy averaged across all pairs of subjects far exceeded chance levels across all candidate set sizes for both of the categories and dimensions (Figure 2F; e.g., 5-way identification accuracy, 72.0% for categories, 59.1% for dimensions; chance level, 20%). These results suggest that distinct emotions were differentially represented across the brain in a consistent manner across different individuals.

202
Figure 2. Neural decoding analysis to predict emotion scores

(A) Decoding accuracy for individual categories. Dots indicate accuracies obtained

from individual brain regions defined by the HCP parcellation ($n = 360$, five subjects

averaged). Black squares indicate accuracies by ensemble decoders that aggregate

predictions from multiple brain regions (error bars, 95% confidence intervals [C.I.]

across subjects). Brain regions with significant accuracy from all five subjects are

colored ($r > 0.097$, permutation test, $p < 0.01$, Bonferroni correction by the number of

brain regions).

(B) Decoding accuracy for individual dimensions. Conventions are the same as (A).

(C) Cortical surface maps of decoding accuracies for individual categories (five subjects

averaged; LH, left hemisphere; RH, right hemisphere; D, dorsal; V; ventral; A,

anterior).

(D) Cortical surface maps of decoding accuracies for individual dimensions (five

subjects averaged).

(E) Correlations of region-wise decoding accuracy patterns between paired subjects. In

congruent conditions, each dot indicates a mean correlation between the same emotion

pairs averaged across all pairs of subjects. In incongruent conditions, each dot indicates

a mean correlation between different emotion pairs averaged across all pairs of subjects

and emotions.

(F) Emotion identification accuracy based on inter-individual similarities of region-wise

decoding accuracy patterns (error bars, 95% C.I. across pairs of subjects [$n = 20$]).

Identification of videos via decoded emotion scores

Given that a complex emotional state can be represented by a blend or combination of multiple emotions (e.g., anger with sadness), we next tested a decoding procedure that took into account multiple emotions simultaneously. To do so, we examined whether a specific video stimulus could be predicted, or identified, from the concatenated predictions of emotion categories or those of affective dimensions. The identification analysis was performed in a pairwise manner, in which a vector of predicted scores was compared with two candidate vectors (one from a true video and the other from a false video randomly selected from the other 2180 videos) to test whether a correlation for the true video was higher than that for the false video (see Methods "Video identification analysis"). For each video, the analysis was performed with all combinations of false candidates ($n = 2180$), and percentages of correct answers were used as an identification accuracy for one sample.

Identification accuracies obtained from predictions by the region-wise decoders are shown in Figure 3A (five subjects averaged, see Figure S1A for individual subjects). The results showed better accuracies via the categories than via the dimensions with most region-wise decoders. The superior accuracy of the categories over the dimensions was also observed with the ensemble decoders, which showed greater than 10% differences in mean accuracy in all subjects (Figure 3B; 80.9% via categories, 68.3% via dimensions, five subjects averaged; see Figure 3C for accuracies of individual videos). This tendency was preserved even when the number of emotions used for identification was matched between the category and dimension models by randomly selecting a subset of 14 categories from the original 34 categories (Figure S1B; 74.1%, five subjects averaged). These results indicate that emotion categories capture far more variance in, and presumably details of, the neural representation of emotionally evocative videos than broad affective features such as valence and arousal.

Visualization of decoded emotional experiences

To explore the extent to which richly varying emotional states were accurately decoded, we used a nonlinear dimensionality reduction method to visualize the distribution of emotional experiences evoked by the 2181 videos, originally represented in terms of 34

emotion categories, in a two-dimensional space (Cowen and Keltner, 2017), and tested

whether the map could be reconstructed from the decoded scores. For this purpose, we

used a novel dimensionality reduction algorithm, called Uniform Manifold

Approximation and Projection (UMAP; McInnes et al., 2018), which enables the

projection of new data points after constructing a mapping function from an

independent training dataset. We first constructed a mapping function that projects 34-

dimensional emotion category scores into a two-dimensional space using the original

emotion category scores (Figure 3D left), and then the function was used to project

decoded scores from ensemble decoders of individual subjects onto the map (Figure 3D

right).

We first confirmed that the UMAP algorithm applied to the 34 emotion category scores

replicated a similar two-dimensional map produced in the previous study (Cowen and

Keltner, 2017), in which distinct categories were found to be organized along gradients

between clusters associated with each category. Upon inspection of the maps

reconstructed from decoded scores, it is apparent that distributions of colors (scores) of

the original map were precisely replicated for all subjects. This was confirmed

quantitatively by calculating correlations of horizontal (x) and vertical (y) data positions

in the two-dimensional space between true and reconstructed maps ($r = 0.46$ for

horizontal axis, $r = 0.53$ for vertical axis, five subjects averaged). The results

demonstrate how precisely different emotional states were decoded from brain activity

and provide a useful means to visualize decoded emotional states.

Figure 3. Identification of videos via decoded emotion scores

(A) Mean video identification accuracies from region-wise decoders. Dots indicate accuracies from individual brain regions (five subjects averaged; dashed lines, chance level, 50%; see Figure S2A for individual subjects).

(B) Mean video identification accuracies from ensemble decoders. Dots indicate accuracies of individual subjects (error bars, 95% C.I. across subjects; dashed line, chance level, 50%).

(C) Histogram of video identification accuracies for individual videos (ensemble decoder; five subjects averaged; dashed line, chance level, 50%).

(D) Maps of emotional experiences constructed from reported and decoded scores. Each dot corresponds to each video, and was colored according to its original reported scores using a weighted interpolation of unique colors assigned to 27 distinct categories (see Cowen and Keltner, 2017 for the color schema).

Construction of voxel-wise encoding models

We next used voxel-wise encoding models to characterize how varying features associated with the presented videos modulate activities in each voxel. We constructed an encoding model for each voxel to predict activities induced by the emotionally evocative videos using a set of features (e.g., scores for 34 emotion categories), and model performance was evaluated by computing a Pearson correlation coefficient between measured and predicted activities (see Methods: "Regularized linear regression analysis").

Encoding models predicting brain activity from emotional scores

We first tested how well encoding models constructed from the 34 emotion categories (e.g., joy, anger) and the 14 affective dimensions (e.g., valence, arousal) predicted brain activities induced by the presented videos (Figure 4A; Subject 1; see Figure S2A for the other subjects). We found that both the category and dimension models accurately predicted activities in many regions, indicating that a broad array of brain regions are involved in encoding information relevant to emotion, as represented by categories and dimensions.

In comparing the model performances, we found that on average the category model outperformed the dimension model by a considerable margin (Figure 4B; Subject 1; slope angle, 34.6 degree; two-tailed t-test, $p < 0.01$ by jackknife method; see Figure S2B for the other subjects). In comparison with the dimension model, the category model predicted voxel responses significantly better in all subjects (Figure 4C, paired t-test across all voxels; $p < 0.01$ for all subjects), and also predicted 68.4% more voxels significantly predicted voxels ($r > 0.109$, permutation test, $p < 0.01$, Bonferroni correction by the number of voxels; five subjects averaged). In addition, when we constructed a joint encoding model by concatenating scores of 34 categories and 14 dimensions, the increase in the number of significantly predicted voxels was marginal when compared to the category model (1.8%, five subjects averaged), but substantial when compared to the dimension model (71.4%, five subjects averaged). Together, these findings suggest that the brain representation of affective dimensions is subsumed by, and can be inferred from, the brain representation of emotion categories.

We next explored whether there were particular brain regions in which the dimension

model outperformed the category model. We first divided the whole cortex into 360

regions using the HCP180 parcellation (Glasser et al., 2016), and separately compared

the performances in each region using a slope angle of best linear fit of the accuracies

from the two models (see Methods: "Slope estimates for performance comparisons").

The distributions of the slope angle suggest that activity in nearly every region was

better predicted by the category model (Figure 4D; 359/360 for category, 0/360 for

dimension; five subjects pooled). This tendency was even observed in seven subcortical

regions, including the amygdala (see Methods: "Regions of interest (ROI)"), which are

often thought to prioritize simpler appraisals of valence and arousal (6/7 for category,

0/7 for dimension; five subjects pooled).

To further compare the performance of the category and dimension models, a video

identification analysis was performed via predicted brain activities obtained from each

of the two models (cf., Figure 3B; see Methods: "Video identification analysis"). We

confirmed that identification accuracies from the category model were substantially

better than the dimension model for all subjects (Figure 4E; 76.8% for category, 68.4%

for dimension, five subjects averaged).

In sum, these encoding analyses demonstrate that emotion categories substantially

outperform affective dimensions in capturing voxel activity induced by emotional

videos (see Figure S3 for control analyses of potential confounds). Taken together,

these results build on previous behavioral findings (Cowen and Keltner, 2017), which

showed that self-reported emotional experience was more precisely characterized by a

rich array of emotion categories than by a range of broad affective dimensions proposed

in constructivist and componential theories to be the underlying components of

emotional experience (Barrett, 2017; Posner et al., 2005; Smith and Ellsworth, 1985). In

particular, using a wide range of analytic approaches, we repeatedly found that emotion

categories capture nuanced, high-dimensional neural representations that cannot be

accounted for by a lower-dimensional set of broad affective features.

Figure 4. Encoding models predicting brain activity from emotional scores

(A) Prediction accuracies of emotion encoding models (Subject 1, see Figure S2 for the other subjects). Several brain regions are outlined and labeled (abbreviations: VC, visual cortex; TPJ, temporo-parietal junction; STC, superior temporal cortex; TE, temporal area; MTC, medial temporal cortex; IPL, precuneus, PC; inferior parietal lobule; DLPFC/DMPFC/VMPFC, dorsolateral/dorsomedial/ventromedial prefrontal cortex; and OFC, orbitofrontal cortex).

(B) Prediction accuracies of individual voxels (red line, best linear fit; dotted lines, r = 0.109, permutation test, $p < 0.01$, Bonferroni correction by the number of voxels; see Figure S2B for the other subjects).

(C) Distributions of prediction accuracies of all voxels (black bars, mean of all voxels).

(D) Comparisons of prediction accuracies for individual brain regions. Each dot indicates a deviation of the estimated slope angle from the parity for each brain region (baseline, 45 degree). Brain regions with significant deviation are colored (two-tailed t-test, $p < 0.01$ by jackknife method).

(E) Mean video identification accuracy via predicted brain activities. Dots indicate accuracies of individual subjects (error bars, 95% C.I. across subjects; dashed line, chance level, 50%).

Disentangling emotional, visual, and semantic feature encoding

Disentangling emotional, visual, and semantic feature encoding

Given that our video stimuli consisted of scenes and events that also included many

visual and semantic features, we next sought to disentangle brain representations of

emotion from those correlated features. For this analysis, we constructed two additional

encoding models from outputs of a pre-trained deep neural network for object

recognition ("visual model") and from semantic features (or concepts; e.g., cats, indoor,

and sports) annotated by human raters via crowdsourcing ("semantic model"; see

Methods: "Video stimulus labeling" for these features). We then evaluated model

performances for each model and compared them to those of the "emotion model"

constructed from the emotion category scores.

As found in previous studies that used similar visual (Güçlü and van Gerven, 2015) and

semantic (Huth et al., 2012) encoding models, our visual and semantic models were

also effective in predicting voxel activity elicited by video stimuli even outside of the

visual cortex (Figure 5A; Subject 1; see Figure S4A for the other subjects). While the

accuracies from these two models positively correlated with those from the emotion

model (inset in Figure 5A), the emotion model consistently outperformed the other two

models in certain brain regions (Figure 5B), including TE, IPL, and several frontal

regions (DLPFC, DMPFC, VMPFC, and OFC), which are known to represent

multimodal emotion information (Chikazoe et al., 2014; Skerry and Saxe, 2014) and

abstract semantic features (Huth et al., 2016; Skerry and Saxe, 2015), and in multiple

functional networks (Figure 5C; Yeo et al., 2011), including the salience network (8),

subparts of the limbic network (10), executive control network (13), and default mode

network (16 and 17), which is also consistent with previous reports (Barrett, 2017;

Barrett and Satpute, 2013; Lindquist and Barrett, 2012; Satpute and Lindquist, 2019).

This analysis demonstrates that brain regions preferentially encoding emotion are

broadly distributed but highly consistent across subjects (Figure 5D).

Visual, semantic, and emotion encoding models along the cortical hierarchy

To better understand which brain regions preferentially represent emotion, we drew on

the concept of the "principal gradient (PG)", which is estimated from functional

connectivity patterns (Margulies et al., 2016) and describes global hierarchical gradients

in cortical organization (Huntenburg et al., 2019). Margulies et al. (2016) used a

dimensionality reduction method to explore principal components of variances in

cortical connectivity patterns, and found that the first component differentiates between

unimodal and transmodal brain regions (Figure 5E left), and the second component

differentiates between brain regions that represent different modalities (from visual to

auditory and somatomotor cortices, Figure 5E right). The meta-analysis by Margulies et

al. (2016) and a review study by Huntenburg et al. (2019) suggest that different regions

along the PGs are responsible for broadly different brain functions.

Here, we tested empirically whether the PGs could account for the spatial arrangement

of voxels preferentially representing visual, semantic, and emotion information using

encoding performances of models constructed from those different features. We plotted

voxels with significant accuracies by the visual, semantic, or emotion models within the

two-dimensional space defined by their values along the first and second PGs (Figure

5F, five subjects pooled, see Figure S4D for individual subjects). Voxels best predicted

by each model occupied different locations in the PG space. Most importantly, along

the first PG axis, voxels best predicted by the visual, semantic, and emotion models

were each densely distributed in regions with low, medium, and high values,

respectively (ANOVA, interaction between frequency and level of the first PG axis, $p <$

0.01). In terms of raw prediction accuracy, voxel activity was better predicted by both

the emotion and semantic models at low and high values of the first PG than at the

midpoint. However, at low/high values of the first PG, the semantic/emotion model

outperformed the emotion/semantic model, respectively (Figure 5G; ANOVA,

interaction between accuracy and level of the first PG axis, $p < 0.01$ for all subjects).

Because emotional responses are correlated with semantic features high in emotional

affordance (e.g., injury, sexual activity), any brain regions predicted better by the

emotion model than by the semantic model, even marginally, should be considered

selective for emotional experience. Hence, the present findings suggest that brain

regions high along the first gradient axis — that is, transmodal regions — are central to

the brain's representation of emotion.

It is important to note that the results presented thus far were replicated using

alternative analytic approaches, including the decoding (Figures S5A and B) and

representational similarity analyses (Figures S5C and D; Kriegeskorte, et al., 2008).

These analyses showed higher identification decoding accuracies (cf., Figure 2A) and

representational similarities across the brain for the category than the dimension model

(Figures S5A and C). In both cases, a highly similar set of brain regions was better fit

by emotion models than by visual or semantic models (Figures S5B and D). These

analyses demonstrate that our results establishing the primacy of emotion categories in

neural representation are highly robust to alternative methodological choices.

Taken together, these results characterize how regions representing emotion are

spatially arranged within the brain. While emotion-specific representations are broadly

distributed across the cortex, they are centered in regions that lie on the far end of a

hierarchical gradient ranging from unimodal to transmodal regions. The

representational shift along this gradient from visual to semantic to emotion-specific

representations may speak to the higher levels of information integration and feature

abstraction necessary for an emotional response.

Figure 5. Disentangling emotional, visual, and semantic feature encoding

(A) Differences in prediction accuracies of emotion, visual, and semantic models
(Subject 1, see Figure S4A for the other subjects). Inserted scatter plots follow the same
conventions as Figure 4B.

(B) Mean prediction accuracies in individual brain regions. Dots indicate accuracies of
individual subjects.

(C) Mean prediction accuracies in individual global networks. Inset offers the
definitions of individual networks (see Figure S4C for a larger view). Conventions are
the same as (B).

(D) Best models among emotion (category), visual, and semantic models (see Figure

S4B for results with the dimension models).

(E) Gradient values of the first and second PG axes. The sign of second PG axis is

negative, following the convention of Margulies et al. (2016).

(F) Joint and marginal distributions of the best models in PG space (five subjects

pooled, see Figure S4D for individual subjects). Voxels with significant accuracy from

either the vision, semantic, or emotion models are shown (permutation test, $p < 0.01$,

Bonferroni correction by the number of voxels).

(G) Mean prediction accuracies along the first PG axis. Voxels were assigned to ten

bins, or levels of the first axis, such that each bin consists of a roughly equal number of

voxels. White circles indicate significant performance over the opponent model (two-

tailed paired t-test, $p < 0.01$, Bonferroni correction by the numbers of PG levels and

subjects).

Distribution of brain activity patterns induced by emotional videos

While the above analyses addressed how particular dimensions, or kinds, of emotion are represented in the brain, the results thus far are not sufficient to reveal the distribution of neural responses to emotional stimuli along these dimensions, that is, how kinds of emotion are distributed in a high dimensional space (Cowen and Keltner, 2017). To address the distribution of emotion-related brain activity, we performed unsupervised modeling using nonlinear dimensionality reduction and clustering analyses.

We first visually inspected the distribution of brain activity patterns induced by the 2181 emotional videos using UMAP algorithm that we previously used to the category emotion scores (cf., Figure 3D). In doing so, we selected voxels best predicted by either of the category or dimension encoding models with significant accuracy (cf., Figure S4B), to focus on activity primarily representing emotion information. We then used activity patterns of those selected voxels as inputs to the UMAP algorithm, thus projecting a total of 2181 brain activity patterns into a two-dimensional space (see Methods: "Dimensionality reduction analysis"). The resulting maps colored based on ratings of the videos in terms of 27 emotion categories reveal a number of brain activity clusters that correspond to experiences of specific emotions (Figures 6A; e.g., sexual desire, disgust, and aesthetic appreciation) consistently across subjects. By contrast, maps colored by three representative affective dimensions (separately for positive and negative parts after 5 [neutral] was subtracted) do not highlight many distinct clusters (Figure 6B), indicating that the distribution of brain activity patterns was better captured by emotion categories.

We next quantified the degree to which brain activity patterns were distributed into cluster-like formations associated with specific emotions. For each subject, we applied k-means clustering to the 2181 brain activity patterns of the voxels selected as above, without any reference to the emotion scores of the eliciting videos. We set the number of clusters to 27, given that the previous study revealed 27 distinct varieties of emotional experiences elicited using the same videos (Cowen and Keltner, 2017), and we would expect at most one cluster per distinct emotion. Note, however, that similar results were obtained using different numbers of clusters (Figure S6). To characterize

the emotional properties of each cluster, we examined how brain activity patterns

corresponding to videos with top 5% high scores (109 videos) for each emotion are

assigned to these clusters using scores of the previously reported 27 distinct categories

and the positive and negative parts of affective dimensions (absolute values after 5

[neutral] was subtracted).

Histograms of the samples assigned to the 27 clusters for each emotion are shown in

Figure 6C (see Figure S6A for the other subjects), revealing an important disparity

between the categories and dimensions. Namely, top samples of several categories,

including entrancement, sexual desire, and disgust, tended to belong to a small number

of clusters, while those of affective dimensions tended to be broadly assigned to many

clusters. This difference was quantified in two ways. First, the histograms of each

emotion — independently sorted according to their frequencies within each cluster —

were steeper for the categories than dimensions (Figure 6D; five subjects averaged;

ANOVA, interaction between frequency and sorted clusters, $p < 0.01$; see Figure S6B

for individual subjects). Second, entropy calculated for each histogram of individual

emotions tended to be low for many categories (e.g., O: entrancement, Z: sexual desire,

and C: aesthetic appreciation) compared to most of the dimensions (Figure 6E, five

subjects averaged, see Figure S6C for individual subjects).

Together, these results indicate that brain activity patterns induced by emotional videos

have cluster-like distributions that align to a greater degree with categories than with

dimensions. Meanwhile, close inspection of the map (Figure 6A) also reveals that the

patterns of brain activity corresponding to certain emotions (e.g., fear and horror) seem

to be not entirely discrete but overlapping in their distribution. Indeed, top samples of

several categories (e.g., W: romance and Z: sexual desire; C: aesthetic appreciation and

J: calmness) tended to fall into overlapping clusters (Figure 6C and Figure S6A). This

finding may shed light on the biological basis of gradients between distinct emotional

experiences, originally revealed in self-report (Cowen and Keltner, 2017), by

suggesting that they correspond to gradients in evoked patterns of brain activity.

A. Admiration B. Adoration C. Aesthetic Apprec. D. Amusement E. Anger F. Anxiety G. Awe
H. Awkwardness I. Boredom J. Calmness K. Confusion L. Craving M. Disgust N. Empathic Pain
O. Entrancement P. Excitement Q. Fear R. Horror S. Interest T. Joy U. Nostalgia
V. Relief W. Romance X. Sadness Y. Satisfaction Z. Sexual Desire Ω. Surprise

a. Approach (+) b. Arousal (+) c. Attention (+) d. Certainty (+) e. Commitment (+) f. Control (+) g. Dominance (+)
h. Effort (+) i. Fairness (+) j. Identity (+) k. Obstruction (+) l. Safety (+) m. Upswing (+) n. Valence (+)
o. Approach (-) p. Arousal (-) q. Attention (-) r. Certainty (-) s. Commitment (-) t. Control (-) u. Dominance (-)
v. Effort (-) w. Fairness (-) x. Identity (-) y. Obstruction (-) z. Safety (-) ω. Upswing (-) +. Valence (-)

Figure 6. Distribution of brain activity patterns induced by emotional videos

(A) Maps of emotional experiences constructed from brain activity patterns. Each dot

corresponds to each video. The same color schema as Figure 3D is used.

(B) Maps of emotional experiences colored by positive or negative parts of valence,

arousal, and dominance scores.

(C) Distributions of top 5% high score samples of each emotion on 27 clusters derived

from the brain (Subject 1, see Figure S6A for the other subjects). Clusters were

separately sorted for the sets of the categories and positive/negative dimensions.

(D) Sorted histograms for individual emotions. Lines indicate sorted histograms of 27

categories or 28 positive/negative dimensions (five subjects averaged, see Figures S6B

and D for individual subjects and for results with different numbers of clusters).

(F) Entropy of the top 5% high score sample distributions for each emotion (five

536   subjects averaged; red lines, baseline, permutation test, $p < 0.01$, Bonferroni correction

537   by the number of emotions; see Figures S6C and E for individual subjects and for

538   results with different numbers of clusters).

Discussion

We have sought to characterize the neural substrates of emotional experience by analyzing activity induced by the richest set of emotional stimuli investigated to date in neuroscience — 2181 emotionally evocative videos annotated with 34 emotion categories and 14 affective dimensions — using neural decoding, voxel-wise encoding modeling, and unsupervised modeling methods. We found that ratings of individual emotions could accurately be predicted from activity patterns in many brain regions, revealing that distributed brain networks contributed in distinct ways to the representation of individual emotions in a highly consistent manner across subjects. Using voxel-wise encoding models constructed from the category and dimension ratings, we found that the brain representation of emotion categories explained greater variability in brain activity than that of affective dimensions in most brain regions. By comparing encoding performances between visual, semantic, and emotion models, we confirmed that responses in a variety of brain regions were specific to emotion rather than visual and semantic covariates. Those emotion-specific representations were broadly distributed, but commonly situated at the far end of a cortical gradient that runs from unimodal to transmodal regions. Analyses using unsupervised modeling revealed that the distribution of brain activity patterns evoked by emotional videos was structured with clusters associated with particular emotion categories bridged by gradients between related emotions. Taken together, our results demonstrate that neural representations of diverse emotional experiences are high-dimensional, categorical, and distributed across transmodal brain regions.

Our decoding analysis revealed that brain regions that contributed to the representation of individual emotions were distinct for different emotions and similar across individuals (Figure 2). Emotions were represented not by simple one-to-one mappings between particular emotions and brain regions (e.g., fear and the amygdala) but by more complex configurations across multiple networks, consistent with notions of distributed, network-based representations of specific emotions (Hamaan, 2012; Lindquist and Barrett, 2012; Saarimäki et al., 2016). These findings may reflect how experiences of individual emotions involve multiple interacting systems (e.g., systems underlying

perception, attention, memory, and motor planning) that enter distinct states in response

to significant threats and opportunities in the environment (Cowen, 2019; Seo et al.,

2019).

Our encoding analysis demonstrates that emotion categories capture neural

representations that are richer than those captured by affective dimensions throughout

the brain (Figure 4). The results converge with recent behavioral studies revealing how

emotion categories organize reported emotional experiences and emotion recognition

from nonverbal signaling behavior (Cowen et al., 2019; Cowen and Keltner, 2017).

Previous studies have pitted categorical and dimensional emotion models against one

another (Hamaan, 2012), but done so with only a few emotions (e.g., happiness, anger,

fear, sadness, disgust, and surprise) or two dimensions (valence, arousal), conflating

distinct emotional experiences within and across studies. In the current study, we drew

upon recent advances in the range of emotions considered to be distinct and accounted

for a fuller array of appraisal dimensions of theoretical relevance to enable a more

robust and thorough comparison of categorical and dimensional models of emotion

representation. Our results provide strong support for a categorical approach to

emotional experience. Additionally, using unsupervised modeling methods, we found

that the distribution of emotion-related brain activity patterns had clusters

corresponding to particular emotion categories (Figure 6A). Taken together, these

results point to a high-dimensional, categorical space in the neural representation of

emotion.

As done in previous studies using voxel-wise modeling in specific sensory regions (de

Heer et al., 2017; Güçlü and van Gerven, 2015; Kell et al., 2018; Lescroart and Gallant,

2019), we compared performances of encoding models constructed from different

features (emotion scores and visual/semantic features), and uncovered a distributed set

of brain regions selective for emotional experience (Figure 5). The spatial arrangement

of these emotion-selective brain regions overlapped with that of the default mode

network (Figure 5C) and corresponded to the far end of a gradient from unimodal to

transmodal regions (Figures 5F and G) that are located at geodesically distant points

from primary sensory cortices (Margulies et al., 2016). Our analysis in a single study

revealed a gradual representational shift along the unimodal-transmodal gradient from

visual to semantic to emotion information, perhaps reflecting a global hierarchy of

integration and feature abstraction from sensory inputs (Huntenburg et al., 2017).

One limitation of the present study was that the emotion ratings we used were averages

from multiple raters and not from the subjects of our fMRI experiment. While our

decoding and encoding models were able to establish systematic statistical relationships

between those ratings and the brain activity patterns of our subjects, the reported

feelings of those raters may not completely match those of our subjects. Hence, to the

extent that neural representations of emotion are subject to individual differences in

culture, demographic variables (gender, age), and personality, future studies might

uncover more robust neural representations by incorporating these variables.

Another potential concern regarding the present investigation is the confounding of

first-person and third-person emotions. The brain regions in which the category model

outperformed the visual and semantic models (e.g., IPL, VMPFC) overlapped with

brain regions that have been implicated in a "theory of mind network" (Skerry and

Saxe, 2015). It is possible that the neural representations uncovered here reflect

information not only regarding first-person emotional experiences but also regarding

predictions of how others might feel. While the observed overlap may also indicate

common neural substrates for first- and third-person emotions, future experiments are

needed to dissociate the difference using more carefully designed experiments, perhaps

including psychophysiological measures indicative of first-person emotional

experience.

Another issue worth noting is that, because each stimulus was presented only once, we

were unable to estimate the proportion of systematic variance in voxel responses that

was left unexplained by our models. Many voxel-wise encoding modeling studies have

relied on repeated stimulus presentations to determine the upper bound of model

prediction accuracies (Huth et al., 2016; Kell et al., 2018; Lescroart and Gallant, 2019).

However, responses to emotional stimuli are likely to change with repeated exposure to

the stimuli, given that many emotional responses (e.g., surprise) can be affected by past

exposure and expectations. For this reason, we performed our analyses on data from

single trials. Nevertheless, the model prediction accuracies we observed were

moderately high by fMRI standards. This might be attributable in part to the potency of

naturalistic stimuli in evoking widespread brain responses (Hamilton and Huth, 2018),

and, more specifically, to the emotional intensity of many of the video stimuli we used

(Cowen and Keltner, 2017).

On this point, it is worth considering how investigations of brain representations of

emotion may depend on the richness of the experimental stimuli used. The 2181 videos

studied here captured a wide spectrum of psychologically significant contexts. By

contrast, most previous work has investigated neural underpinnings of emotion using a

far narrower range of eliciting stimuli and a small set of emotions (Barrett, 2017;

Celeghin et al., 2017; Giordano et al., 2018; Hamaan, 2012; Kragel and LaBar, 2015;

Lindquist and Barrett, 2012; Saarimäki et al., 2016; Satpute and Lindquist, 2019; Wager

et al., 2015). Only recently have several studies investigated neural representations of

emotion with richer models of emotion, but they have still relied on a relatively narrow

range of stimuli (Koide-Majima, et al., 2018; Kragel et al., 2019; Saarimäki et al., 2018;

Skerry and Saxe, 2015). As the field of affective science moves forward, the present

study reveals how a more extensive analysis of whole brain responses to much richer

experimental stimuli, open to diverse analytical approaches, can yield more definitive

results.

This approach allowed rich and nuanced emotion categories to be accurately predicted

from brain activity patterns (Figures 2A and B) and even made it possible to accurately

identify eliciting stimuli based on patterns of decoded emotion scores (Figure 3).

Previous decoding studies of emotion have relied on discrete classification into a small

set of emotion categories (Kragel et al., 2016; Kragel and LaBar, 2015; Saarimäki et al.,

2016; Saarimäki et al., 2018; Sitaram et al., 2011), which may conflate representations

of diverse emotional states grouped into each category (Clark-Polner et al., 2016). By

predicting continuous intensities of many distinct emotions simultaneously, a more

comprehensive picture of emotional states can be characterized. We visualized these

nuanced emotional states by combining decoded scores of richly varying emotion

categories with a UMAP algorithm (Figure 3D). This approach can provide a tool for

various applications, such as product evaluation in neuro-marketing (Nishida and

Nishimoto, 2018). Furthermore, in light of recent findings of a broad overlap between

neural representations of perceived and internally-generated experiences (Horikawa et

al., 2013; Kragel et al., 2016; Tusche et al., 2014), decoders trained for perceived

emotions may generalize to emotional states that occur spontaneously during dreams

and mind wandering, with potential clinical applications (Kragel et al., 2016; Sitaram et

al., 2011).

A critical question in neuroscience is where emotions evoked by different modalities of

sensory input are encoded in the brain (Chikazoe et al., 2014; Kragel et al., 2016;

Skerry and Saxe, 2014). Although here we used only visual stimuli, we found that

emotion-specific representations were not primarily found in visual cortex (Kragel et

al., 2019) but in many transmodal and frontal regions that have been implicated in

representing other modalities of emotionally evocative stimuli and tasks, including

verbal stimuli (Huth et al., 2016; Skerry and Saxe, 2015), visual and gustatory stimuli

(Chikazoe et al., 2014), and volitional and spontaneous imagery (Tusche et al., 2014). A

few studies have investigated commonalities in the neural representation of emotion

across multiple stimulus modalities, but have focused on narrower ranges of stimuli and

emotions (e.g., basic emotions: Peelen et al., 2010; valence: Chikazoe et al., 2014;

Skerry and Saxe, 2014). As behavioral studies generate richer and diverse experimental

resources for investigating multiple modalities of emotions (Cowen et al., 2018, 2019;

Cowen et al., in press), cross-modal neural representations of emotions should be

investigated in finer detail.

A potentially interesting future approach to understand how emotion representations are

generated in the brain is to construct computational models for emotion recognition

using deep neural networks (DNNs). Several recent studies have demonstrated that

task-optimized DNNs can be used as a good proxy for the hierarchical sensory systems

of the brain, and that hierarchical representations from low to middle to high DNN

layers resembled neural representations of hierarchical sensory cortices (Güçlü and van

Gerven, 2015; Horikawa and Kamitani, 2017; Kell et al., 2018; Yamins et al., 2014;

Yamins and DiCarlo, 2016). Given the functional differentiation we uncovered along a

global hierarchical gradient from visual to semantic to emotion representations,

hierarchical DNN models trained to predict emotional responses may learn internal

representations resembling these global hierarchical representations in the brain. A

recent study constructed a feedforward DNN model to predict emotion scores of input

images by fine-tuning a pre-trained object recognition DNN model (Kragel et al., 2019).

Given that their analyses were mainly focused on visual cortical activity and the top-

level features of the DNN, other representational similarities between emotion

representation in human cortex and the multiple DNN layers have yet to be explored.

Acknowledgments

The authors thank Mitsuaki Tsukamoto, Hiroaki Yamane, and Shuntaro C. Aoki for

help with data collection and software setups. This study was conducted using the MRI

scanner and related facilities of Kokoro Research Center, Kyoto University. This

research was supported by grants from the New Energy and Industrial Technology

Development Organization (NEDO), JSPS KAKENHI Grant number JP15H05710,

JP15H05920, and JP17K12771, JST CREST Grant Number JPMJCR18A5, and JST

PRESTO Grant Number JPMJPR185B Japan.

Author Contributions

Conceptualization, T.H. and Y.K.; Methodology, T.H.; Validation, T.H.; Formal

Analysis, T.H.; Investigation, T.H.; Resources, T.H. and A.S.C.; Writing – Original

Draft, T.H.; Writing – Review & Editing, T.H., A.S.C., D.K., and Y.K.; Visualization,

T.H.; Supervision, T.H. and Y.K.; Funding Acquisition, T.H. and Y.K.

Declaration of Interests

The authors declare no competing interests.

References

● Avants, B.B., Epstein, C.L., Grossman, M., and Gee, J.C. (2008). Symmetric

diffeomorphic image registration with cross-correlation: evaluating automated

labeling of elderly and neurodegenerative brain. Med. Image Anal. *12*, 26–41.

● Barrett, L.F. (2017). The theory of constructed emotion: an active inference

account of interoception and categorization. Soc. Cogn. Affect. Neurosci. *12*, 1–12.

● Barrett, L.F., and Satpute, A.B. (2013). Large-scale brain networks in affective and

social neuroscience: towards an integrative functional architecture of the brain.

Curr. Opin. Neurobiol. *23*, 361–372.

● Celeghin, A., Diano, M., Bagnis, A., Viola, M., and Tamietto, M. (2017). Basic

Emotions in Human Neuroscience: Neuroimaging and Beyond. Front. Psychol. *8*,

1432.

•   Clark-Polner, E., Johnson, T.D., and Barrett, L.F. (2017). Multivoxel pattern
analysis does not provide evidence to support the existence of basic emotions.
Cereb. Cortex *27*, 1944–1948.

•   Cowen, A.S. (2019). Neurobiological explanation for diverse responses associated
with a single emotion. Science, eLetter.

•   Cowen, A.S., and Keltner, D. (2017). Self-report captures 27 distinct categories of
emotion bridged by continuous gradients. Proc. Natl. Acad. Sci. USA *114*, E7900–
E7909.

•   Cowen, A.S., and Keltner, D. (2018). Clarifying the Conceptualization,
Dimensionality, and Structure of Emotion: Response to Barrett and Colleagues.
Trends. Cogn. Sci. *22*, 274–276.

•   Cowen, A.S., Elfenbein, H.A., Laukka, P., and Keltner, D. (2018). Mapping 24
emotions conveyed by brief human vocalization. American Psychologist *74*, 698–
712.

•   Cowen, A.S., Fang, X., Sauter, D., and Keltner, D. (in press). What music makes us
feel: At least thirteen dimensions organize subjective experiences associated with
music across cultures. Proc. Natl. Acad. Sci. USA.

•   Cowen, A.S., Laukka, P., Elfenbein, H.A., Liu, R., and Keltner, D. (2019). The
primacy of categories in the recognition of 12 emotions in speech prosody across
two cultures. Nat. Hum. Behav. *13*, 1–16.

•   Cox, R.W. (1996). AFNI: software for analysis and visualization of functional
magnetic resonance neuroimages. Comput. Biomed. Res. *29*, 162–173.

•   de Heer, W.A., Huth, A.G., Griffiths, T.L., Gallant, J.L., and Theunissen, F.E.
(2017). The Hierarchical Cortical Organization of Human Speech Processing. J.
Neurosci. *37*, 6539–6557.

•   Ekman, P., and Friesen, W.V. (1969). The repertoire of nonverbal behavior:
Categories, origins, usage and coding. Semiotica *1*, 49–98.

•   Esteban, O., Markiewicz, C.J., Blair, R.W., Moodie, C.A., Isik, A.I., Erramuzpe,
A., Kent, J.D., Goncalves, M., DuPre, E., Snyder, M., et al. (2019). fMRIPrep: a
robust preprocessing pipeline for functional MRI. Nat. Methods *16*, 111–116.

•   Fischl, B. (2012). FreeSurfer. Neuroimage *62*, 774–781.

• Gao, J.S., Huth, A.G., Lescroart, M.D., and Gallant, J.L. (2015). Pycortex: an
interactive surface visualizer for fMRI. Front. Neuroinform. *9*, 23.

• Giordano, B.L., Whiting, C., Kriegeskorte, N., Kotz, S.A., Belin, P., and Gross, J.
(2018). From categories to dimensions: spatio-temporal dynamics of the cerebral
representations of emotion in voice. bioRxiv, https://doi.org/10.1101/265843.

• Greve, D.N., and Fischl, B. (2009). Accurate and robust brain image alignment
using boundary-based registration. Neuroimage *48*, 63–72.

• Güçlü, U., and van Gerven, M.A.J. (2015). Deep neural networks reveal a gradient
in the complexity of neural representations across the ventral stream. J. Neurosci.
35, 100005–100014.

• Hamann, S. (2012). Mapping discrete and dimensional emotions onto the brain:
controversies and consensus. Trends. Cogn. Sci. *16*, 458–466.

• Hamilton, L.S., and Huth, A.G. (2018). The revolution will not be controlled:
natural stimuli in speech neuroscience. Language, Cognition and Neuroscience *0*,
1–10.

• Huntenburg, J.M., Bazin, P.-L., and Margulies, D.S. (2017). Large-Scale Gradients
in Human Cortical Organization. Trends Cogn. Sci. *22*, 1–11.

• Huth, A.G., Nishimoto, S., Vu, A.T., and Gallant, J.L. (2012). A Continuous
Semantic Space Describes the Representation of Thousands of Object and Action
Categories across the Human Brain. Neuron *76*, 1210–1224.

• Horikawa, T., and Kamitani, Y. (2017). Generic decoding of seen and imagined
objects using hierarchical visual features. Nat. Commun. *8*, 15037.

• Horikawa, T., Tamaki, M., Miyawaki, Y., and Kamitani, Y. (2013). Neural
decoding of visual imagery during sleep. Science. *340*, 639–642.

• Jenkinson, M., Bannister, P., Brady, M., and Smith, S. (2002). Improved
optimization for the robust and accurate linear registration and motion correction of
brain images. Neuroimage *17*, 825–841.

• Jenkinson, M., Beckmann, C.F., Behrens, T.E., Woolrich, M.W., and Smith, S.M.
(2012). FSL. Neuroimage *62*, 782–790.

● Jia, Y., Shelhamer, E., Donahue, J., Karayev, S., Long, J., Girshick, R.,

Guadarrama, S., and Darrell, T. (2014). Caffe: Convolutional Architecture for Fast

Feature Embedding. arXiv, arXiv:1408.5093. https://arxiv.org/abs/1408.5093.

● Cornbleet, P.J., and Gochman, N. (1979). Incorrect Least-Squares Regression

Coefficients in Method-Comparison Analysis. Clin. Chem. *25*, 432–438.

● Kell, A.J.E., Yamins, D.L.K., Shook, E.N., Norman-Haignere, S.V., and

McDermott, J.H. (2018). A Task-Optimized Neural Network Replicates Human

Auditory Behavior, Predicts Brain Responses, and Reveals a Cortical Processing

Hierarchy. Neuron *98*, 630–644.

● Kragel, P.A., and LaBar, K.S. (2015). Multivariate neural biomarkers of emotional

states are categorically distinct. Soc. Cogn. Affect. Neurosci. *10*, 1437–1448.

● Kragel, P.A., Knodt, A.R., Hariri, A.R., and LaBar, K.S. (2016). Decoding

Spontaneous Emotional States in the Human Brain. PLoS Biol. *14*, e2000106–

e2000119.

● Kriegeskorte, N., Mur, M., Ruff, D.A., Kiani, R., Bodurka, J., Esteky, H., Tanaka,

K., and Bandettini, P.A. (2008). Matching Categorical Object Representations in

Inferior Temporal Cortex of Man and Monkey. Neuron *60*, 1126–1141.

● Lancaster, J.L., Summerin, J.L., Rainey, L., Freitas, C.S., and Fox, P.T. (1997). The

Talairach Daemon, a database server for Talairach Atlas Labels. Neuroimage *5*.

● Lancaster, J.L., Woldorff, M.G., Parsons, L.M., Liotti, M., Freitas, C.S., Rainey, L.,

Kochunov, P.V., Nickerson, D., Mikiten, S.A., and Fox, P.T. (2000). Automated

Talairach atlas labels for functional brain mapping. Hum. Brain. Mapp. *10*, 120–

131.

● Lescroart, M.D., and Gallant, J.L. (2018). Human Scene-Selective Areas Represent

3D Configurations of Surfaces. Neuron *101*, 1–33.

● Lindquist, K.A., and Barrett, L.F. (2012). A functional architecture of the human

brain: emerging insights from the science of emotion. Trends Cogn. Sci. *16*, 533–

540.

● Maldjian, J.A., Laurienti, P.J., Burdette, J.B., and Kraft, R.A. (2003). An automated

method for neuroanatomic and cytoarchitectonic atlas-based interrogation of fMRI

data Sets. Neuroimage *19*, 1233–1239.

● Margulies, D.S., Ghosh, S.S., Goulas, A., Falkiewicz, M., Huntenburg,

J.M., Langs, G., Bezgin, G., Eickhoff, S.B., Castellanos, F.X., Petrides, M., et

al. (2016). Situating the default-mode network along a principal gradient of

macroscale cortical organization. Proc. Natl. Acad. Sci. USA *101*, 12574–12579.

● McInnes, L., Healy, J., and Melville, J. (2018). UMAP: Uniform Manifold

Approximation and Projection for Dimension Reduction. arXiv, arXiv:1802.03426,

https://arxiv.org/abs/1802.03426.

● Nishida, S., and Nishimoto, S. (2018). Decoding naturalistic experiences from

human brain activity via distributed representations of words. Neuroimage *180*,

232–242.

● Peelen, M.V., Atkinson, A.P., and Vuilleumier, P. (2010). Supramodal

Representations of Perceived Emotions in the Human Brain. J. Neurosci. *30*,

10127–10134.

● Plutchik, R. (1980). Emotion: A Psychoevolutionary Synthesis. (New York: Harper

and Row).

● Posner, J., Russell, J.A., and Petersona, B.S. (2005). The circumplex model of

affect: An integrative approach to affective neuroscience, cognitive development,

and psychopathology. Dev. Psychopathol. *17*, 715–734.

● Russell, J.A. (1980). A circumplex of affect. J. Pers. Soc. Psychol. *36*, 1152–1168.

● Russell J.A. (2003). Core affect and the psychological construction of emotion.

Psychol. Rev. *110*, 145–172.

● Saarimäki, H., Ejtehadian, L.F., Glerean, E., Jääskeläinen, I.P., Vuilleumier, P.,

Sams, M., and Nummenmaa, L. (2018). Distributed affective space represents

multiple emotion categories across the human brain. Soc. Cogn. Affect. Neurosci.

13, 471–482.

● Saarimäki, H, Gotsopoulos, A., Jääskeläinen, I.P., Lampinen, J., Vuilleumier, P.,

Hari, R., Sams, M., and Nummenmaa, L. (2016). Discrete Neural Signatures of

Basic Emotions. Cereb. Cortex *26*, 2563–2573.

● Satpute, A.B., and Lindquist, K.A. (2019). The Default Mode Network's Role in

Discrete Emotion. Trends Cogn. Sci. *23*, 851–864.

●   Seo, C., Guru, A., Jin, M., Ito, B., Sleezer, B.J., Ho, Y.Y., Wang, E., Boada, C.,
Krupa, N.A., Kullakanda, D.S., et al. (2019). Intense threat switches dorsal raphe
serotonin neurons to a paradoxical operational mode. Science *363*, 538–542.

●   Simonyan, K., and Zisserman, A. (2014). Very Deep Convolutional Networks for
Large-Scale Image Recognition. arXiv, arXiv:1409.1556,
https://arxiv.org/abs/1409.1556.

●   Sitaram, R., Lee, S., Ruiz, S., Rana, M., Veit, R., and Birbaumer, N. (2011). Real-
time support vector classification and feedback of multiple emotional brain states.
Neuroimage, *56*, 753–765.

●   Skerry, A.E., and Saxe, R. (2014). A Common Neural Code for Perceived and
Inferred Emotion. J. Neurosci. *34*, 15997–16008.

●   Skerry, A.E., and Saxe, R. (2015). Neural Representations of Emotion Are
Organized around Abstract Event Features. Curr. Biol. *25*, 1945–1954.

●   Smith, C.A., and Ellsworth, P.C. (1985). Patterns of cognitive appraisal in emotion.
J. Pers. Soc. Psychol. *48*, 813–38.

●   Tusche, A., Smallwood, J., Bernhardt, B.C., and Singer, T. (2014). Classifying the
wandering mind: Revealing the affective content of thoughts during task-free rest
periods. Neuroimage *97*, 107–116.

●   Wager, T.D., Kang, J., Johnson, T.D., Nichols, T.E., Satpute, A.B., and Barrett,
L.F. (2015). A Bayesian Model of Category-Specific Emotional Brain Responses.
PLoS Comput. Biol. *11*, e1004066.

●   Yamins, D.L., DiCarlo, J.J. (2016). Using goal-driven deep learning models to
understand sensory cortex. Nat. Neurosci. *19*, 356–365.

●   Yamins, D.L.K., Hong, H., Cadieu, C.F., Solomon, E.A., Seibert, D., DiCarlo, J.J.
(2014). Performance-optimized hierarchical models predict neural responses in
higher visual cortex. Proc. Natl. Acad. Sci. USA *111*, 8619–8624.

●   Yeo, B.T., Krienen, F.M., Sepulcre, J., Sabuncu, M.R., Lashkari, D., Hollinshead,
M., Roffman, J.L., Smoller, J.W., Zöllei, L., Polimeni, J.R., et al. (2011). The
organization of the human cerebral cortex estimated by intrinsic functional
connectivity. J. Neurophysiol. *106*, 1125–1165.

 Figure legends

Figure 1. Decoding and encoding emotional responses in fMRI signals evoked by

videos

(A) Schematic of the experiment and analyses. fMRI signals were recorded while

subjects viewed emotional videos. Decoding/encoding models were trained to predict

scores/responses of individual emotions/voxels for presented videos from patterns of

responses/scores, respectively.

(B) Score distributions of emotion categories and affective dimensions. Score

distributions from a total of 2181 unique videos are shown for 34 emotion categories

and 14 affective dimensions (see Methods: "Video stimulus labeling"). For emotion

categories, each dot indicates a proportion the category was evaluated with non-zero

scores for each video. For affective dimensions, black bars indicate mean values across

all videos. In the main analyses, mean scores averaged across multiple raters were used

for each video.

Figure 2. Neural decoding analysis to predict emotion scores

(A) Decoding accuracy for individual categories. Dots indicate accuracies obtained

from individual brain regions defined by the HCP parcellation ($n = 360$, five subjects

averaged). Black squares indicate accuracies by ensemble decoders that aggregate

predictions from multiple brain regions (error bars, 95% confidence intervals [C.I.]

across subjects). Brain regions with significant accuracy from all five subjects are

colored ($r > 0.097$, permutation test, $p < 0.01$, Bonferroni correction by the number of

brain regions).

(B) Decoding accuracy for individual dimensions. Conventions are the same as (A).

(C) Cortical surface maps of decoding accuracies for individual categories (five subjects

averaged; LH, left hemisphere; RH, right hemisphere; D, dorsal; V; ventral; A,

anterior).

(D) Cortical surface maps of decoding accuracies for individual dimensions (five

subjects averaged).

(E) Correlations of region-wise decoding accuracy patterns between paired subjects. In

congruent conditions, each dot indicates a mean correlation between the same emotion

pairs averaged across all pairs of subjects. In incongruent conditions, each dot indicates

a mean correlation between different emotion pairs averaged across all pairs of subjects

and emotions.

(F) Emotion identification accuracy based on inter-individual similarities of region-wise

decoding accuracy patterns (error bars, 95% C.I. across pairs of subjects [$n = 20$]).

Figure 3. Identification of videos via decoded emotion scores

(A) Mean video identification accuracies from region-wise decoders. Dots indicate

accuracies from individual brain regions (five subjects averaged; dashed lines, chance

level, 50%; see Figure S2A for individual subjects).

(B) Mean video identification accuracies from ensemble decoders. Dots indicate

accuracies of individual subjects (error bars, 95% C.I. across subjects; dashed line,

chance level, 50%).

(C) Histogram of video identification accuracies for individual videos (ensemble

decoder; five subjects averaged; dashed line, chance level, 50%).

(D) Maps of emotional experiences constructed from reported and decoded scores. Each

dot corresponds to each video, and was colored according to its original reported scores

using a weighted interpolation of unique colors assigned to 27 distinct categories (see

Cowen and Keltner, 2017 for the color schema).

Figure 4. Encoding models predicting brain activity from emotional scores

(A) Prediction accuracies of emotion encoding models (Subject 1, see Figure S2 for the

other subjects). Several brain regions are outlined and labeled (abbreviations: VC,

visual cortex; TPJ, temporo-parietal junction; STC, superior temporal cortex; TE,

temporal area; MTC, medial temporal cortex; IPL, precuneus, PC; inferior parietal

lobule; DLPFC/DMPFC/VMPFC, dorsolateral/dorsomedial/ventromedial prefrontal

cortex; and OFC, orbitofrontal cortex).

(B) Prediction accuracies of individual voxels (red line, best linear fit; dotted lines, $r =$

0.109, permutation test, $p < 0.01$, Bonferroni correction by the number of voxels; see

Figure S2B for the other subjects).

(C) Distributions of prediction accuracies of all voxels (black bars, mean of all voxels).

(D) Comparisons of prediction accuracies for individual brain regions. Each dot
indicates a deviation of the estimated slope angle from the parity for each brain region
(baseline, 45 degree). Brain regions with significant deviation are colored (two-tailed t-
test, $p < 0.01$ by jackknife method).

(E) Mean video identification accuracy via predicted brain activities. Dots indicate
accuracies of individual subjects (error bars, 95% C.I. across subjects; dashed line,
chance level, 50%).

Figure 5. Disentangling emotional, visual, and semantic feature encoding
(A) Differences in prediction accuracies of emotion, visual, and semantic models
(Subject 1, see Figure S4A for the other subjects). Inserted scatter plots follow the same
conventions as Figure 4B.

(B) Mean prediction accuracies in individual brain regions. Dots indicate accuracies of
individual subjects.

(C) Mean prediction accuracies in individual global networks. Inset offers the
definitions of individual networks (see Figure S4C for a larger view). Conventions are
the same as (B).

(D) Best models among emotion (category), visual, and semantic models (see Figure
S4B for results with the dimension models).

(E) Gradient values of the first and second PG axes. The sign of second PG axis is
negative, following the convention of Margulies et al. (2016).

(F) Joint and marginal distributions of the best models in PG space (five subjects
pooled, see Figure S4D for individual subjects). Voxels with significant accuracy from
either the vision, semantic, or emotion models are shown (permutation test, $p < 0.01$,
Bonferroni correction by the number of voxels).

(G) Mean prediction accuracies along the first PG axis. Voxels were assigned to ten
bins, or levels of the first axis, such that each bin consists of a roughly equal number of
voxels. White circles indicate significant performance over the opponent model (two-
tailed paired t-test, $p < 0.01$, Bonferroni correction by the numbers of PG levels and
subjects).

Figure 6. Distribution of brain activity patterns induced by emotional videos

(A) Maps of emotional experiences constructed from brain activity patterns. Each dot

corresponds to each video. The same color schema as Figure 3D is used.

(B) Maps of emotional experiences colored by positive or negative parts of valence,

arousal, and dominance scores.

(C) Distributions of top 5% high score samples of each emotion on 27 clusters derived

from the brain (Subject 1, see Figure S6A for the other subjects). Clusters were

separately sorted for the sets of the categories and positive/negative dimensions.

(D) Sorted histograms for individual emotions. Lines indicate sorted histograms of 27

categories or 28 positive/negative dimensions (five subjects averaged, see Figures S6B

and D for individual subjects and for results with different numbers of clusters).

(F) Entropy of the top 5% high score sample distributions for each emotion (five

subjects averaged; red lines, baseline, permutation test, $p < 0.01$, Bonferroni correction

by the number of emotions; see Figures S6C and E for individual subjects and for

results with different numbers of clusters).

METHODS

CONTACT FOR REAGENT AND RESOURCE SHARING

Further information and requests for resources and reagents should be directed to and will be fulfilled by the Lead Contact, Yukiyasu Kamitani (kamitani@i.kyoto-u.ac.jp).

EXPERIMENTAL MODEL AND SUBJECT DETAILS

Human subjects

Five healthy subjects with normal or corrected-to-normal vision participated in our experiments: Subject 1 (male, age 34), Subject 2 (male, age 23), Subject 3 (female, age 23), Subject 4 (male, age 22), and Subject 5 (male, age 27). This sample size was chosen on the basis of previous fMRI studies with similar experimental designs (Horikawa and Kamitani, 2017; Huth et al., 2016). All subjects provided written informed consent for participation in the experiments, and the study protocol was approved by the Ethics Committee of ATR.

METHOD DETAILS

Emotional movie stimuli

The stimuli consisted of sequences of emotionally evocative short videos. The videos were originally collected by Cowen and Keltner (2017). The video dataset consisted of a total of 2196 videos (downloaded at 13 September, 2017; https://goo.gl/forms/XErJw9sBeyuOyp5Q2) whose durations ranged from ~0.15 s to ~90 s. Each video was resized so that the width and height of videos were both within 12 degree (the original aspect ratio was preserved) and was visually presented at the center of the screen on gray background (no sound was delivered in our experiment, while some videos originally contained sounds).

Experimental design

All video stimuli were rear-projected onto a screen in the fMRI scanner bore using a luminance-calibrated liquid crystal display projector. To minimize head movements during fMRI scanning, subjects were required to fix their heads using a custom-molded

bite-bar individually made for each subject except for the case where subjects were
reluctant to use the bite-bar (a subset of sessions with Subject 5). Data from each
subject were collected over multiple scanning sessions spanning approximately 2
months. On each experimental day, one consecutive session was conducted for a
maximum of 2 hours. Subjects were given adequate time for rest between runs (every
7–10 min) and were allowed to take a break or stop the experiment at any time.

The video presentation experiment consisted of a total of 61 separate runs. Each run
comprised 36 stimulus blocks whose durations differed across blocks depending on the
durations of videos presented in each stimulus block. For stimulus blocks with videos
shorter than 8 s, the same video stimulus was repeatedly presented until the total
presentation duration went beyond 8 s. For stimulus blocks with videos longer than 8 s,
the video stimulus was presented once and followed by ~2-s rest period so that the total
durations of stimulus blocks can be divided by 2 s (TR). All stimulus blocks were
followed by an additional 2-s rest period. Additional 32- and 6-s rest periods were
added to the beginning and end of each run respectively. Consequently, the durations of
individual runs ranged from 7 min 10 s to 9 min 54 s, and the total duration of all
scanning sessions was about 8 hours.

To maximize subject's emotional responses to video stimuli, subjects were allowed to
view video stimuli without fixation to let subjects freely focus on any details of events
in videos. subjects were requested to maintain steady fixation on the center fixation spot
(0.3×0.3 degree) during rest periods to maintain their attention on the screen.

MRI acquisition
fMRI data were collected using a 3.0-Tesla Siemens MAGNETOM Verio scanner
located at the Kokoro Research Center, Kyoto University. An interleaved T2*-weighted
gradient-echo echo planar imaging (EPI) scan was performed to acquire functional
images covering the entire brain (TR, 2000 ms; TE, 43 ms; flip angle, 80 deg; FOV,
192×192 mm; voxel size, $2 \times 2 \times 2$ mm; slice gap, 0 mm; number of slices, 76;
multiband factor, 4). T1-weighted (T1w) magnetization-prepared rapid acquisition
gradient-echo (MP-RAGE) fine-structural images of the entire head were also acquired

(TR, 2250 ms; TE, 3.06 ms; TI, 900 ms; flip angle, 9 deg; FOV, 256 × 256 mm; voxel

size, 1.0 × 1.0 × 1.0 mm).

MRI data preprocessing

We performed the MRI data preprocessing through the pipeline provided by fMRIPrep

(version 1.2.1; Esteban et al., 2018). For functional data of each run, first, a BOLD

reference image was generated using a custom methodology of fMRIPrep. A

deformation field to correct for susceptibility distortions was estimated based on

fMRIPrep's fieldmap-less approach, and the estimated susceptibility distortion was

used to calculate an unwarped BOLD reference for a more accurate coregistration with

the anatomical reference. Using the estimated BOLD reference, data were motion

corrected using mcflirt from FSL (version 5.0.9; Jenkinson et al., 2002) and then slice

time corrected using 3dTshift from AFNI (version 16.2.07; Cox, 1996). This was

followed by co-registration to the corresponding T1w image using boundary-based

registration implemented by bbregister from FreeSurfer (version 6.0.1; Greve and

Fischl, 2009). The coregistered BOLD time-series were then resampled onto their

original space (2 × 2 × 2 mm voxels) using antsApplyTrainsforms from ANTs (version

2.1.0; Avants et al., 2008) using Lanczos interpolation.

Using the preprocessed BOLD signals, data samples were created by first regressing out

nuisance parameters from each voxel amplitude for each run, including a constant

baseline, a linear trend, and temporal components proportional to the six motion

parameters calculated during the motion correction procedure (three rotations and three

translations). The data were temporally shifted by 4 s (2 volumes) to compensate for

hemodynamic delays, were despiked to reduce extreme values (beyond ± 3 SD for each

run), and were averaged within each stimulus block (a video presentation period and a

subsequent 2-s rest period). The data for all video stimuli were then further z-scored for

each voxel. These procedures yielded a total of 2196 data samples each corresponding

to each video stimulus. Because the presented video stimulus set happened to include

identical videos (15 duplicates), we discarded samples that were presented later in the

experiment from each of those duplicates, and used remaining 2181 unique samples in

the following analyses.

For visualization of analytical results from the whole cortical areas, we visualized

results using flattened cortical surfaces reconstructed from anatomical images of

individual subjects. Cortical surface meshes of individual subjects were first generated

from the T1w anatomical images using recon-all from FreeSurfer (version 6.0.1; Fischl,

2012). Relaxation cuts were made into the surface of each hemisphere to make flattened

cortical surfaces for individual subjects. Functional data were aligned, and were

projected onto the surface for visualization using Pycortex (Gao et al., 2012).

Regions of interest (ROI)

To define regions of interest (ROI) on cortical surfaces, we used two types of brain

parcellations: 1) the whole cortical brain parcellation provided by the Human

Connectome Project (Glasser et al., 2016), which delineated 180 cortical areas on each

hemisphere (HCP180; cf., Figures 2 and 3), and 2) the network-based cortical

parcellation estimated by intrinsic functional connectivity (Yeo et al., 2011), which

delineated 17 networks on the cerebral cortex (cf., Figure 5C). To define ROI masks on

individual subject's brain, labels corresponding to brain areas or brain networks

originally defined on the standard cortical surface (fsaverage) were converted to the

cortical surfaces of individual subjects using FreeSurfer (version 6.0.1; Fischl, 2012).

The converted labels were then reinterpolated to $2 \times 2 \times 2$ mm voxels using flirt from

FSL (version 5.0.9; Jenkinson et al., 2002).

In the encoding analysis of individual brain areas (Figure 5B), the visual cortex (VC),

temporo-parietal junction (TPJ), superior temporal sulcus (STS), temporal cortex (TE),

medial temporal cortex (MTC), inferior parietal lobule (IPL), precuneus (PC),

dorsolateral prefrontal cortex (DLPFC), dorsomedial prefrontal cortex (DMPFC),

ventromedial prefrontal cortex (VMPFC), and orbitofrontal cortex (OFC) were defined

based on the following sets of the HCP180 ROI labels on both left and right

hemispheres: V1, V2, V3, V3A, V3B, V3CD, V4, V4t, V6, V6A, V7, V8, FST, IPS1,

FFC, LO1, LO2, LO3, PH, PIT, MT, MST, VMV1, VMV2, VMV3, and VVC for VC;

TPOJ1, TPOJ2, and TPOJ3 for TPJ; STSda, STSdp, STSva, and STSvp for STS; TE1a,

TE1m, TE1p, and TE2a for TE; EC, and H for MTC; PFm, PGi, and PGs for IPL; 7m,

v23ab, d23ab, 31pv, 31pd, 31a, and PCV for PC; 9-46d, 46, a9-46v, and p9-46v for

DLPFC; d32, 9m, and 10d for DMPFC; 10r, 10v, p32, s32, and a24 for VMPFC; and

OFC, and pOFC for OFC. Boundaries of these individual brain areas were drawn on the

figures of cortical surfaces (e.g., Figure 4). For visualization of subareas in VC, lines

delineating V1, V2, V3, V4, and others were also drawn on the cortical surfaces.

To define ROIs based on the levels of the principal gradient axes, we utilized the

principal gradient maps provided from Margulies et al. (2016), which are also originally

defined on the standard cortical surface (fsaverage). We first converted original

principal gradient maps of the first and second gradient axes to the cortical surfaces of

individual subjects using FreeSurfer (version 6.0.1; Fischl, 2012), and then

reinterpolated to $2 \times 2 \times 2$ mm voxels using flirt from FSL (version 5.0.9; Jenkinson et

al., 2002). The resultant gradient maps registered to individual subjects' brains are

shown in Figure 5E (Subject 1), and principal gradient values of individual voxels were

used to generate results in Figure 5F and Figure S4D. For each subject, values of the

first gradient axis assigned to individual voxels were also used to construct ROI masks

that correspond to ten levels (bins) of the first axis, such that a roughly equal number of

voxels were assigned to each level (cf., Figure 5G).

To define ROI masks for subcortical areas, including the thalamus, hippocampus,

hypothalamus, pallidum, brainstem, nucleus accumbens (Brodmann area 34), and

amygdala, we used anatomical masks defined by the AAL and the Talairach Daemon

provided through the WFU PickAtlas (Maldjian et al., 2003; Lancaster et al, 1997;

Lancaster et al., 2000). The anatomical masks, which were originally defined in the

stereotaxic space, were transformed to the individual T1w anatomical images, using

FreeSurfer (version 6.0.1; Fischl, 2012), and then reinterpolated to $2 \times 2 \times 2$ mm voxels

using flirt from FSL (version 5.0.9; Jenkinson et al., 2002).

Video stimulus labeling

Video stimuli were labeled by multiple types of scores, or features, including two types

of emotion scores (34 emotion categories and 14 affective dimensions), 1000 visual

features, and 73 semantic features. Values of these labels were z-scored for each

emotion/feature to remove baseline differences across emotions/features (unless

otherwise stated).

Emotion scores. We used the human emotion ratings of 34 emotion categories and 14

affective dimensions, which were provided from the previous study (see Cowen and

Keltner, 2017 for details). The ratings were collected using online experiments via

Amazon Mechanical Turk (AMT). For the 34 emotion categories, subjects of the online

experiments rated each video in terms of the degree to which it made them feel the 34

emotion categories (100-point scale). The reported scale was converted to 1, when

raters scored higher than 0, such that a score for a video from an individual rater

become a dichotomous yes/no response. For the 14 affective dimensions, another group

of subjects rated each video in terms of its placement along 14 scales of affective

dimensions (9-scale Likert scale). Each video was evaluated by multiple raters (9–17

raters), and the ratings obtained for individual emotions from multiple raters were

averaged for each emotion to set one mean score for one video for one emotion.

Visual features. For constructing visual features, we used the Caffe implementation (Jia

et al., 2014) of the VGG19 deep neural network (DNN) model (Simonyan and

Zisserman, 2014), which was pre-trained to classify 1000 object categories (the pre-

trained model is available from https://github.com/BVLC/caffe/wiki/Model-Zoo). The

VGG19 model consisted of a total of sixteen convolutional layers and three fully

connected layers. To compute outputs by the VGG19 model, all frames of videos were

resized to 224 × 224 pixels and provided to the model. The outputs from the last fully

connected layer (fc8, 1000 units, before softmax operation) were averaged across all

frames within each video to construct a feature vector for a video.

Semantic features. We have also collected semantic ratings for the video stimuli

according to 73 semantic contents associated with relatively concrete concepts in the

video stimuli. The semantic features include objects, scenes, actions, and events (see

below for the full list). The data collection was also conducted through online

experiments via AMT with 12 raters for each video. Participants rated each video

according to whether the video contains each semantic concept by dichotomous yes/no

responses. The ratings from 12 raters were averaged to construct feature for individual

concept for each video. The full list of the 73 semantic features is as follows: above

water scenes, aquatic animals, art, automobiles, babies, birds, black people, blood,

boats, bottles/cans, boys, buildings, cartoons, cats, celebrities, cities, clouds, couples,

crowds of people, daytime scenes, dead bodies, dogs, elderly people, explosions, fast-

moving objects, feces/urine/vomit, fire, flags, food, furniture, genitalia, girls, guns,

gymnasiums, hands/feet, historical footage, hospitals, indoor scenes, injuries, insects,

land animals, large animals, machines, men, mountains, naked people, nature, nighttime

scenes, outdoor scenes, paper, paranormal creatures, people, planes, plants, politicians,

reporters, roads, sexual activity, sharp objects, small animals, smoke, snow, soldiers,

sports, stores, stunts, television, underwater scenes, vast landscapes, video games,

weapons, white people, and women.

Regularized linear regression analysis

We used the L2 regularized linear regression (ridge regression) to predict stimulus

labels from voxel activity patterns (decoding models) and to predict voxel activity from

stimulus labels (encoding models). All models were evaluated using 6-fold cross-

validation procedure (61 runs data were grouped into five sets of 10 runs and one set of

11 runs data). In each fold of the cross-validation, models for individual labels

(decoding) and voxels (encoding) were trained with five sets of data, and the estimated

models were used to predict stimulus labels (decoding) and voxel activities (encoding)

for left out test set. This was repeated by rotating training-test assignments for 6 times

to produce model predictions for all data samples. Then, model performance was

evaluated by calculating Pearson correlation coefficients between true and predicted

scores of individual labels in the decoding analysis and between measured and

predicted brain activities of individual voxels in the encoding analysis.

Ridge regression uses a regularization parameter to constrain the magnitude of the

weight coefficients. In decoding analysis, we individually estimated a regularization

coefficient for each combination of stimulus labels, ROIs, and subjects (e.g., a single

value for "fear" score predictions from V1 activities of Subject 1). In encoding analysis

from each label set (category, dimension, visual, and semantic), we estimated a single

value of the regularization coefficient for all voxels in each subject. The regularization

parameters were optimized based on the model performances obtained by 5-fold cross-

validation procedure (inner loop) nested within training data for the outer loops of the

6-fold cross-validation. In each fold of the nested (or inner) cross-validation loop,

models for individual labels (decoding) and voxels (encoding) were trained with four

sets of the data (within training data) using each of 20 possible regularization

coefficients (log spaced between 10 and 10000), and the estimated models were used to

predict stimulus labels (decoding) and voxel activities (encoding) for left out test set

(one out of five sets). This was repeated by rotating training-test assignments for 5

times to produce model predictions for all data samples within each fold of outer loops

of the cross-validation. Then, model performance was evaluated by calculating Pearson

correlation coefficients between true and predicted labels of individual labels in the

decoding analysis and between measured and predicted brain activities of individual

voxels in the encoding analysis. These procedures were also repeated for each outer

loop of the cross-validation to estimate model performances for each fold of outer

loops. Then, model performances obtained from the nested cross-validation procedures

were averaged across cross-validation folds, and the regularization parameters

producing the maximal model performances were selected.

Construction of ensemble decoders

To construct a decoder that aggregates information represented in multiple brain regions

($n = 360$), we constructed an ensemble decoder for each emotion by averaging

prediction values from multiple decoders (region-wise decoder), each of which was

trained with brain activity patterns in each brain region. For each individual emotion,

the brain regions used for the aggregations were selected based on the model

performances evaluated in a nested cross-validated manner. For each subject and

emotion, predictions from region-wise decoders that showed higher decoding accuracy

than a threshold ($r > 0.097$, permutation test, $p < 0.01$, Bonferroni correction by the

number of brain regions [$n = 360$]; see Methods: "Permutation tests" for details) were

averaged to construct ensemble predictions. When no brain regions produced decoding

accuracy higher than the threshold, the decoder showing the best accuracy was used as a

substitute for the ensemble decoder (this was only the case for the "guilt" decoder of

Subject 5).

Video identification analysis

1220

Identification of emotional experience induced by individual video stimuli was

performed via predictions from the decoding (cf., Figures 3A, B and C) and encoding

(cf., Figure 4E) analyses. In the decoding and encoding analyses, scores of individual

emotions or signal intensity of individual voxels were predicted from observed brain

activity patterns or stimulus labels, respectively. Those predictions for individual

emotions or voxels were concatenated to construct emotion score patterns or voxel

activity patterns. The procedure yielded a total of 2181 predicted patterns corresponding

to the presented video clips. Identification was performed in the pairwise manner, in

which the video clip was identified between true and false candidates, using the

predicted voxel activity pattern or emotion score pattern. The predicted pattern was

compared with two candidate patterns: one for the true video and the other for a false

video selected from the rest of 2180 videos. The video with a higher correlation

coefficient was selected as the identified video. The analysis was repeated for all

combinations of the 2181 videos. The accuracy for each video was evaluated by the

ratio of correct identification.

Emotion identification analysis

1236

Identification of emotions was performed via patterns of decoding accuracies obtained

from multiple brain regions of different subjects (cf., Figure 2F). In the decoding

analysis, we have performed decoding analysis of scores of the 34 emotion categories

and 14 affective dimensions, and evaluated decoding accuracies of individual emotions

from multiple brain regions ($n = 360$). The decoding accuracies from multiple brain

regions were concatenated to construct a pattern of decoding accuracies (number of

elements = 360) as an emotion representation of one subject. For each pair of subjects,

accuracy patterns from one subject (test subject) were compared with accuracy patterns

from another subjects (reference subject) using all combinations of 34 emotion

categories or 14 affective dimensions. For each accuracy pattern of the test subject, the

emotion whose accuracy pattern of the reference subject was most correlated with the

accuracy pattern of the test subject was selected. This procedure was conducted for all

combinations of five subjects ($n = 20$). The identification accuracy was evaluated with

various candidate set sizes.

Slope estimates for performance comparisons

Comparisons of encoding accuracy from the emotion category models and affective dimension models were performed based on the slope angles of best linear fit between two sets of model prediction accuracies of individual voxels. The best linear fit was estimated by Deming regression (Cornbleet and Gochman, 1979; or two-dimensional case of the total least square regression) to accounts for observation errors on both x- and y-axis (e.g., on the category model accuracy and dimension model accuracy; Figure 4B). The slope estimates were converted to angles by first calculating the arctangent of the slopes to obtain angles in radians, and then converting it to degrees. The calculated angles were further subtracted from 45 (degree) to obtain deviations from the parity (Figure 4D). Statistical significance of the slope estimates was computed based on standard errors of estimated slopes calculated by the jackknife method (two-tailed t-test). For the results of the pooled condition in Figure 4D, voxels within each brain region were aggregated from all five subjects to calculate slope estimates.

Dimensionality reduction analysis

We used Uniform Manifold Approximation and Projection (UMAP) algorithm (McInnes et al., 2018) to perform dimensionality reduction analysis. We applied the UMAP algorithm on emotion category scores (Figure 3D) and brain activity patterns (Figures 6A and B) to reduce the dimensionality of original data into two dimensions.

In the analysis with emotion category scores, we trained a mapping function from original 34 emotion category scores of 2181 video stimuli using correlation distance $(1 - r)$ as the distance metric. The trained mapping function was used to project 34-dimensional category scores to two dimensions for both true (Figure 3D left) and decoded (Figure 3D right) emotion category scores.

In the analysis with brain activity patterns, we trained mapping functions based on correlation distances among brain activity patterns to 2181 video stimuli estimated from individual subjects and their average. Before applying UMAP algorithm, voxels associated with emotions were selected based on the results of encoding analysis for individual subjects, in which voxels showing the higher accuracy from the category/dimension emotion models than the visual and semantic models with

significantly high accuracy by the category/dimension emotion models (cf., Figure

S4B) were selected. The activity patterns of selected voxels were used to construct

matrices of correlation distance $(1 - r)$ for individual subjects. The estimated distance

matrices from individual subjects and their average (2181×2181 matrix) were used as

inputs to the UMAP algorithm to construct two-dimensional maps of emotional

experiences.

In the generated two-dimensional maps, each data sample was colored by a weighted

interpolation of the unique colors assigned to 27 distinct emotion categories (Figures

3D, 6A and B) or three representative affective dimensions, including valence, arousal,

and dominance (Figure 6C).

Clustering analysis

We used k-means clustering algorithm to perform clustering analysis with brain activity

patterns of individual subjects. The analysis was performed with activity patterns of

voxels that were selected based on the results of encoding analyses (see Methods:

"Dimensionality reduction analysis" for the selection criteria of emotion related voxels)

using correlation distances $(1 - r)$ as metric. The number of clusters ($n = 27$ in Figure

6) was determined based on the findings in the previous study (Cowen and Keltner,

2017; see Figures S6D and E for results with $n = 15$ and 50).

Representational similarity analysis

The representational similarity analysis (Kriegeskorte et al., 2008) was performed to

evaluate the similarity of the representational similarity matrices (RSM) constructed

from brain activity patterns and score/feature patterns for each set of features. The RSM

was calculated by Pearson correlation coefficients between patterns of voxel activities

or scores/features corresponding to individual video stimuli (2181×2181 matrix). For

calculating the representational similarity between two RSMs (e.g., one from brain

activity pattern in a single ROI, and the other from emotion category scores), the off-

diagonal elements (triangular part of a matrix) of the RSMs were vectorized and a

Pearson correlation coefficient was calculated between those vectors from two RSMs.

The analysis was performed using brain activity patterns within individual ROIs defined

by the HCP180 parcellation (Glasser et al., 2016). The estimated representational

1311 similarities for individual brain regions were averaged across five subjects, and were

1312 projected on the cortical surface of Subject 1 (Figure S5C).

QUANTIFICATION AND STATISTICAL ANALYSIS

1314 Two-sided paired t-test was used to examine differences in encoding accuracy from two

1315 models (Figures 4C and 5G). ANOVA was used to examine interaction effects between

1316 encoding performances from the emotion and semantic models and the levels of

1317 principal gradients (Figures 5G and F).

Permutation tests

Statistical significance of correlation coefficients (e.g., encoding accuracy in Figure 4A)

was computed by comparing estimated correlations (or accuracy) to the null

distributions of correlations between two independent Gaussian random vectors of the

same length (2181 elements, $n = 100000000$). Resulting p-values were corrected for

multiple comparisons using the Bonferroni method.

The baseline entropy (cf., Figure 6F) was determined from null distributions of

entropies ($n = 100000$) calculated from random assignments of the same number of

samples ($n = 109$) into clusters (27 clusters for Figure 6F; 15 and 50 clusters for Figures

S6D and E). An entropy was calculated from a histogram by randomly assigning

samples into bins. This procedure was repeated for 100000 times to construct null

distributions, and determined the baseline entropy ($p = 0.01$, Bonferroni correction by

the number of emotions times the number of subjects).

DATA AND SOFTWARE AVAILABILITY

1332 The experimental data and code that support the findings of this study are available

1333 upon request to the corresponding authors (horikawa-t@atr.jp, kamitani@i.kyoto-

1334 u.ac.jp).

 SUPPLEMENTAL INFORMATION

 Supplemental Figures

 Figure S1. Identification of videos via decoded emotion scores for individual
 subjects. (Related to Figure 3)
 (A) Mean video identification accuracies from region-wise decoders of individual
 subjects. Conventions are the same with Figure 3A.
 (B) Distributions of video identification accuracies obtained from randomly selected 14
 emotion category scores. The video identification analysis by ensemble decoders (cf.,
 Figure 3B) was performed for 10,000 times while randomly selecting different
 combinations of 14 emotion category scores from the original 34 emotion category
 scores. The identification accuracies obtained with this procedure were compared with
 the accuracy from the 14 affective dimensions. The estimated accuracies from more
 than 99% of 14 randomly selected emotion categories outperformed the accuracy from
 the 14 affective dimensions. The results suggest that the superiority of the 34 emotion
 categories over the 14 affective dimensions (Figure 3B) were not solely due to the
 differences of the number of emotions used for identification.

 Figure S2. Performance of encoding models constructed from emotional scores for
 individual subjects. (Related to Figure 4)
 (A) Prediction accuracies of emotion encoding models. Conventions are the same with
 Figure 4A.
 (B) Prediction accuracies of individual voxels. Conventions are the same with Figure
 4B.

 Figure S3. Control analyses for the performance comparisons between category
 and dimension encoding models. (Related to Figure 4)
 (A) Distributions of prediction accuracies of all voxels from multiple variants of
 category models and dimension models. Because the methods for collecting scores of
 emotion categories and affective dimensions were different (see Methods: "Video
 stimulus labeling"), differences of encoding performances might be attributable to such
 differences. To compensate for the differences, we constructed encoding models from

different versions of emotion category and affective dimension scores used in the main

analyses, and compared encoding model performances from those multiple variants. For

the emotion category scores, we have used binarized scores reported by individual

human raters (originally ranged between 0 to 100) in the main analysis ("category

[binary]"; cf., Figure 4). We here also tested another type of emotion category scores

without binarization (mean of reported scores [ranged between 0 to 100], "category

[continuous]"). In either case, high and low values of the emotion category scores can

be interpreted whether that emotions exist or not. On the other hand, because scores of

the affective dimensions were collected with 9-scale Likert scale (ranged between 1 to

9, "14 dimensions [continuous]"), the high and low values should be interpreted

differently (e.g., positive and negative), and low values should be interpreted as strong

negative emotions rather than no emotion. To compensate for the difference from the

category scores, we tested other types of affective dimension scores by first subtracting

5 [neutral] from original values (-4 to 4), taking both positive and negative values

separately, and concatenating the positive (0 to 4) and negative (-4 to 0) parts to yield a

total of 28 unipolar affective dimension scores ("28 dimensions [continuous]"). This

score conversion was done for scores of individual raters and converted scores were

averaged across multiple raters. Furthermore, similar to the emotion category scores, we

also tested the binarized version of affective dimension scores by binarizing zero or

non-zero values of the continuous 28-dimensional scores of individual raters to zero/one

values and averaging them across multiple raters ("28 dimensional [binary]"). These

score conversions had little effect on encoding accuracies, showing higher mean

encoding accuracies for the emotion category models than the affective dimension

models.

(B) Comparisons of prediction accuracies between the emotion category models and the

other control models. The encoding performance obtained from the original emotion

category model was directly compared with the performances from models constructed

with the other variants of emotion scores (cf., Figure S3A) based on slope angles of best

linear fit estimated from encoding accuracies of all voxels across the whole brain. The

results showed equivalent performances between the two category models, whereas the

original category model outperformed all affective dimension models, suggesting that

the differences of the data collection methods were not main factor of the superiority of

the emotion category model.

(C) Distributions of deviations of slope angles from the parity compared between the

dimension models and category models constructed with randomly selected 14 emotion

category scores. Encoding models were constructed from 14 randomly selected emotion

categories for 1,000 times, and obtained encoding accuracies were each compared with

the accuracy from the 14 affective dimensions based on slope angles of best linear fit

estimated from encoding accuracies of all voxels across the whole brain. The results

showed that on average more than 93.5% models constructed from 14 randomly

selected emotion categories outperformed the accuracy from the 14 affective

dimensions (five subjects averaged).

(D) Distributions of video identification accuracies obtained from encoding models

constructed from randomly selected 14 emotion categories. The video identification

analysis (cf., Figure 4E) was performed with models constructed with 14 randomly

selected emotion categories for 1,000 times (cf., Figure S3C). The identification

accuracies obtained with this procedure were compared with the accuracy from the 14

affective dimension model (Figure 4E). The results showed that on average more than

96.2% models obtained from 14 randomly selected emotion categories outperformed

the accuracy from the 14 affective dimensions (five subjects averaged). Taken together

with (C), the results suggest that the superiority of the 34 emotion categories over the

14 affective dimensions were not solely due to the differences of the number of

emotions used for the encoding analysis.

Figure S4. Comparisons of encoding accuracy based on emotion, visual, and

semantic models for individual subjects. (Related to Figure 5)

(A) Differences in prediction accuracies of emotion, visual, and semantic models.

(B) Best models among visual, semantic, category, and dimension models.

(C) Definition of global networks (see Yeo et al., 2011 for details).

(D) Joint and marginal distributions of the best models in principal gradient space for

individual subjects. Conventions are the same as Figure 5F.

Figure S5. Performances of decoding analysis and representational similarity

analysis across the whole cortex. (Related to Figure 5)

(A) Video identification accuracies via decoding analysis of individual features (five subjects averaged). The video identification analysis performed using decoded emotional scores (cf., Figures 3A and S1A) was also performed with visual/semantic features via decoding analysis of individual features. Mean accuracies of the identification analysis via decoded scores/features from five subjects (cf., Figure S1A) were averaged for each brain region, and were projected onto the cortical surface of Subject 1.

(B) Differences in video identification accuracies via decoding analysis between two different features. Conventions are the same as (A).

(C) Representational similarities for individual feature set. The representational similarity analysis (Kriegeskorte et al., 2008) was performed to evaluate the similarity of representational similarity matrices (RSM) constructed from patterns of brain activities and scores/features (see Methods: "Representational similarity analysis" for details). For each set of features (e.g., 34 emotion category scores), correlation coefficients between two RSMs (one from the brain, and the other from scores/features) were calculated for individual brain regions ($n = 360$; defined by HCP180; Grasser et al., 2016). The estimated representational similarities for individual brain regions were averaged across five subjects, and were projected onto the cortical surface of Subject 1.

(D) Differences in representational similarities between two different feature sets. Conventions are the same as (C).

Figure S6. Clustering analysis on brain activity patterns induced by emotion evocative short videos for individual subjects. (Related to Figure 6)

(A) Distributions of top 5% high score samples of individual emotions on 27 clusters derived from brain activity patterns for individual subjects. Conventions are the same with Figure 6C.

(B) Sorted histograms of individual emotions for individual subjects. Conventions are the same with Figure 6D.

(C) Entropy of the top 5% high score sample distributions of each emotion for individual subjects. Conventions are the same with Figure 6E.

(D) Sorted histograms of individual emotions obtained with 15 and 50 clusters. Conventions are the same with Figures 6D.

1457   (E) Entropy of the top 5% high score sample distributions of each emotion obtained

1458   with 15 and 50 clusters. Conventions are the same with Figures 6E.