Machine learning for integrative multi-omics clustering and feature gene identification

Yang Zhang[1,2], Lin Liu[1,2,§], Zhaoqi Liu[1,2,3], Qi Liu[4], Lina Ma[1,2,3,*] and Zhang Zhang[1,2,3,*]

[1] *National Genomics Data Center, China National Center for Bioinformation, Beijing 100101, China*

[2] *Beijing Institute of Genomics, Chinese Academy of Sciences, Beijing 100101, China*

[3] *University of Chinese Academy of Sciences, Beijing 101408, China*

[4] *Department of Hematology, Tongji Hospital, Frontier Science Center for Stem Cell Research, Bioinformatics Department, School of Life Sciences and Technology, Tongji University, Shanghai 200092, China*

[§] *Present address: Beijing Forestry University, Beijing 100083, China*

[*]Corresponding authors: malina@big.ac.cn, zhangzhang@big.ac.cn

Abstract

Multi-omics integrative analysis is pivotal for elucidating complex molecular mechanisms and biological processes, yet remains challenging due to the high dimensionality and heterogeneity of multi-omics data. Here we describe MIA, a machine learning framework for multi-omics integrative analysis. Unlike existing algorithms that rely on two-dimensional representations, MIA employs a three-dimensional tensor representation coupled with tensor decomposition, Fuzzy C-Means, and an enhanced random forest model to jointly enable accurate sample stratification and feature discovery. Benchmarking on simulated datasets demonstrates that MIA achieves higher accuracy in both clustering and feature identification by comparison with extant algorithms. Application to TCGA datasets further shows the ability of MIA to stratify samples and identify features associated with significantly clinical outcomes. Notably, as applied to glioblastoma, MIA is capable to detect three previously uncharacterized subtypes with distinct prognostic profiles and uncover critical feature genes linked to glioblastoma subtyping and therapeutic response. Collectively, these results establish MIA as a generalizable computational framework for multi-omics integrative analysis, enabling systematic molecular subtyping and significant feature discovery across complex biological systems.

Keywords: multi-omics integrative analysis; feature gene; machine learning; tensor; clustering

Introduction

Powered by high-throughput sequencing technologies, data from multiple omics layers, such as genomics, transcriptomics, proteomics, and epigenomics, have been generated at exponential rates and scales[1]. Integrative analysis of multi-omics data holds great promise for elucidating complex molecular mechanisms and biological processes[2, 3], particularly in the context of precision medicine[4], through precise sample clustering[5-7] and accurate identification of feature genes as potential molecular biomarkers[8, 9]. In machine learning and artificial intelligence, a feature is an individual characteristic of a data set and selection of informative and discriminative features is crucial for effective sample clustering. Hence, in biomedical research, a feature gene reflects a specific biological process and a set of feature genes is defined as those that contribute significantly to clustering. Therefore, multi-omics integrative analysis represents a powerful approach for systematically delineating feature genes from diverse omics data and thereby enabling a comprehensive understanding of complex physiopathological processes and mechanisms[10, 11].

Over the past several years, several algorithms have been developed for multi-omics data integrative analysis, which roughly fall into two groups in light of data integration strategy[12]: similarity network and consensus factor. For the former, representative algorithms include SNF[13], PINS[14], NEMO[15], and MANAclust[16]. They calculate sample similarities and fuse networks across different omics types, but are sensitive to data perturbations, outliers and noise, which may reduce robustness and increase computational complexity. For the latter, representative algorithms are MOFA[17], iClusterPlus[18], and intNMF[19]. They derive shared factor matrices across multi-omics types but often rely on specific statistical assumptions that may not apply universally across diverse biological datasets, thus susceptible to model misspecification and noise influence. Importantly, among these existing algorithms, only SNF, MANAclust, and iClusterPlus are capable for feature gene identification as well as clustering. Yet, these three algorithms filter genes at individual omics level and are unable to systematically identify feature genes from multi-omics levels. Overall, the two strategies transform multi-omics data into two-dimensional representations, but fail to effectively integrate complementary information between different omics types, resulting in inaccurate multi-omics data analysis.

Nowadays, a promising strategy is tensor integration based on machine learning, which provides a powerful framework to effectively capture high-dimensional features inherent in multi-omics data[20]. Specifically, tensor integration allows for the representation of data in multi-dimensional arrays, enabling the simultaneous encapsulation of sample, gene and omics type, without any prior assumption[21-23]. In addition, tensor exhibits unique advantages in handling high-dimensional heterogeneity of biomedical data, flexibly adapting to variable sample sizes ranging from dozens to over thousands, and accommodating ultra-high feature dimensionality greater than 10,000 features per omics type[24]. Recently, tensor integration has been applied in sample classification[20, 25], survival prediction[26], and gene interaction prediction[27]. However, utilizing tensor integration for multi-omics data analysis remains unexplored.

Toward this end, here we present MIA, a **M**ulti-omics **I**ntegrative **A**nalysis algorithm for machine learning clustering and feature gene identification. Unlike extant algorithms that rely on the two-

dimensional data representation, MIA adopts a tensor framework for multi-omics data integration,
structuring into a three-dimensional matrix comprising samples, genes and omics types, and utilizes
tensor decomposition to factorize the matrix. It further uses Fuzzy C-means (FCM) for clustering
to accurately capture sample similarity while minimizing the influence of initializing cluster centers.
For feature gene identification, we develop a new enhanced random forest model (ERFM) for three-
dimensional matrix, allowing for a comprehensive assessment of gene importance at multi-omics
level. To assess the power of MIA, we conduct extensive comparative analyses using both simulated
and empirical datasets, and apply it to glioblastoma (GBM) subtyping and feature gene
identification.

Results

MIA framework

We modularize the framework of MIA into three modules, namely, multi-omics integration, tensor
decomposition & clustering, and feature gene identification (**Fig. 1**). For multi-omics integration,
MIA utilizes a tensor framework to organize multi-omics data into a three-dimensional matrix
comprising samples, genes, and omics types (**Fig. 1a**). It preserves critical biological information
by maintaining data topology and facilitates extraction of joint features across omics types.

To analyze unlabeled biomedical samples, MIA applies tensor decomposition for dimensionality
reduction, followed by FCM clustering for sample stratification. Among available tensor
decomposition techniques, Tucker decomposition is widely adopted, owing to its flexibility and
accuracy in capturing complex data structures and interdependencies[22, 23]. Therefore, MIA adopts
Tucker decomposition to factorize the tensor into three matrices: sample-feature matrix, gene-
feature matrix, and omics type-feature matrix, and then employs FCM for clustering based on the
sample-feature matrix (**Fig. 1b** and **Supplementary Fig. 1**). Unlike K-means, FCM allows samples
to be classified into multiple clusters, providing more accurate characterization of ambiguous
samples. As noted, there are two critical parameters for FCM—uncertain fuzzy index (m) and cluster
count (K)—that are typically pre-defined. In MIA, they are optimally determined for each dataset:
m is estimated from sample and feature counts[28] and K is estimated by maximizing the silhouette
coefficient, thereby providing data-driven parameter estimation tailored to each dataset (see details
in Methods; **Supplementary Figs. 2 and 3**).

Using the clustering results as sample labels, MIA further utilizes the Gini index to perform
preliminary gene filtering and employs ERFM for feature gene identification. Unlike traditional
random forest model (RFM) that handle only a single data type, ERFM is capable to take good
account of multi-dimensional data types to quantify the contribution of each gene in clustering and
thus to yield a set of feature genes (**Fig. 1c**). There are two significant improvements in ERFM: an
enhanced tree structure and an iterative computational procedure (**Supplementary Fig. 4**). First,
the enhanced tree structure accounts for multi-dimensional data types by creating multiple tree
nodes based on different omics types for each gene, rather than a single tree node in RFM. The

importance score of each gene is determined by the increase of classification error after
simultaneous randomization of all corresponding nodes, which allows for an effective assessment
of the gene contribution within overall influence of multi-omics data. Second, instead of a single
forest generation in RFM, ERFM employs an iterative computational procedure that repeatedly
constructs and refines the forest, thus enhancing the consistency of the identified feature gene set.
Specifically, after each iteration, genes with negative importance scores are eliminated, and the
iterative refinement continues until there is no remaining gene with negative importance scores,
ensuring that only the most relevant feature genes are retained for further analysis (**Supplementary**
Fig. 4c,d; see details in Methods).

Benchmarking of MIA on simulated datasets

To evaluate the performance of MIA, we consider multiple parameters, including cluster count (K),
omics type count (T), sample count (N), and the numbers of real (true) features (M_t) and noise (false)
features (M_f), and generate simulated datasets with different parameter combinations in terms of
possible scenarios of real data (see details in Methods). We examine the clustering accuracy of MIA
by comparison against existing six popular algorithms—SNF, MANAclust, iClusterPlus, PINS,
NEMO and MOFA—among which only the former three support feature gene identification.

When varying K and T with fixed N, M_t and M_f, MIA overall achieves the stable and higher accuracy
across all parameter combinations (**Fig. 2a**). Among these competing algorithms, NEMO and SNF
present comparable performance, while iClusterPlus exhibits marked instability when varying K.
Consistently, MIA performs much better than other algorithms at varied values of N, M_t, M_f with
fixed K and T (**Fig. 2b**). In contrast, MANAclust shows significant deviations from the true labels.
Considering the significance of K in data analysis (that is often arbitrarily set), we further evaluate
their accuracy in optimal K selection and reveal that MIA achieves an average accuracy of 0.987
across all datasets, outperforming other algorithms (**Fig. 2c**). Since MANAclust often overestimates
the value of K, we exclude it from the following analysis in real datasets. Regarding feature gene
identification, it is clearly shown that feature genes identified by MIA yield higher significance than
those identified by the other algorithms (**Fig. 2d and Supplementary Table 2**).

Benchmarking of MIA on TCGA datasets

We evaluate MIA in ten empirical datasets from The Cancer Genome Atlas (TCGA), covering
different omics data types (copy number variation (CNV), gene expression, and methylation) and
involving ten cancer types: Bladder Cancer (BLCA), Cervical Squamous Cell Carcinoma (CESC),
Breast Cancer (BRCA), Colon Cancer (COAD), GBM, Head and Neck Squamous Cell Carcinoma
(HNSC), Lower Grade Glioma (LGG), Liver Cancer (LIHC), Lung Adenocarcinoma (LUAD), and
Prostate Cancer (PRAD). To facilitate the comparison, we run MIA as well as existing related
algorithms to perform clustering and survival analyses on each dataset.

In these ten datasets, MIA overall outperforms existing algorithms by achieving more significant
survival differences across different omics data combinations (**Fig. 3a-c** and **Supplementary Table**

3), particularly for COAD and LUAD (**Supplementary Figs. 5 and 6**). Compared to all possible combinations of single-omics and two-omics data, clustering by MIA on three-omics data generally demonstrates higher survival significance ($p<0.05$, Log-rank test) in nearly all cancer types, which is more striking than that of other algorithms. Particularly, MIA achieves significantly different survival outcomes ($p<0.0001$, Log-rank test) in LIHC and GBM based on three-omics data, whereas single-omics or two-omics combinations fail to achieve similar differences (**Supplementary Figs. 7 and 8**). Additionally, we observe that although nearly all algorithms exhibit comparable survival differences in LGG on multi-omics combinations, clusters determined by MIA show more divergences (**Supplementary Fig. 9**). Detailed survival analyses for all these ten cancer types (**Supplementary Figs. 5-14**) show that multi-omics data integrative analysis by MIA is superior to other algorithms in precise clustering.

Following a previous study[12], we adopt six clinical records to evaluate the performance of MIA, viz., gender, age at diagnosis, progression of the tumor (pathologic T), metastases (pathologic M) and cancer in lymph nodes (pathologic N), and the total progression (pathologic stage), which can be used to indicate demographic characteristics, disease severity and progression. We investigate the enrichment of these clinical records in all clusters determined by different algorithms and find that MIA clustering achieves more significant clinical outcomes across ten cancer types (**Fig. 3d**, **Supplementary Fig. 15** and **Supplementary Table 5**). In BLCA, all the algorithms reveal more enriched records in a consistent manner, possibly due to its distinct clinical stages and molecular differences between non-muscle invasive and muscle-invasive types[29]. Notably, no clinical records are enriched in GBM across all algorithms, most likely owing to the missing clinical data as well as high malignancy of GBM that is difficult to distinguish subtypes based on tumor morphology and pathology. Given the significance of these six clinical records, our results show that MIA clustering has a stronger correlation with disease progression than other algorithms.

We further assess the MIA performance of feature gene identification in seven cancer types with sufficient samples. Compared with existing algorithms, feature genes identified by MIA present greater significant differences between cancer and normal samples across nearly all examined cancer types (**Fig. 3e**). Clearly, this result demonstrates the superior capability of MIA in feature gene identification from multi-omics data integrative analysis.

GBM subtyping and feature gene identification

GBM is the most aggressive primary brain cancer, with a five-year survival rate of only ~5%[30]. Therefore, it is crucial to identify feature genes that can be used as potential biomarkers for GBM diagnosis and prognosis. We apply MIA to the GBM dataset described above, covering 15,372 genes with multi-omics profiles (CNV, gene expression and methylation). For clustering, MIA determines the optimal value of K at 3 (**Fig. 4a**), as further supported by the well-separated clusters (**Fig. 4b**). Most important, clinically, the clustering of $K=3$ yields more significant survival differences (p-value<0.0001, Log-rank test; **Fig. 4c**), namely, clusters 1, 2 and 3 at high, medium and low survivals, respectively. In contrast, classical subtypes based solely on gene expression[31]

show no significant survival differences (p-value=0.59, Log-rank test; **Supplementary Fig. 16**).
Therefore, our results show that MIA is more powerful in multi-omics integrative clustering.

It has been reported that the fraction of altered genome reflects the extent of genetic alterations in
cancer[32] and stemness index signifies the stem cell-like characteristics of cancer cells[33], together
indicating tumor aggressiveness and prognosis. Thus, we further evaluate the MIA clustering in
GBM based on these metrics. We find that the fraction of altered genome decreases significantly
from cluster 1 to cluster 3 (p<0.05; **Fig. 4d**), corresponding well with the declining survival rates.
Consistently, the stemness index gradually reduce, namely, higher in cluster 1, medium in cluster 2,
and lower in cluster 3 (**Fig. 4e** and **Supplementary Table 6**). These results indicate that GBM with
fewer genomic alterations may exhibit more aggressive behavior and lower survival rates, consistent
with observations in advanced tumors[32]. In addition, GBM with poor prognosis has lower stemness
and higher cancer cell differentiation[34, 35]. Overall, the clinical analysis demonstrates that MIA is
effective to identify GBM subtypes with distinct aggressiveness and prognosis.

In addition, MIA is capable to identify a set of 167 feature genes from the GBM three-omics profiles
that contribute to the clustering (**Fig. 4f and Supplementary Table 7**). Among them, 87 (52.1%)
genes have already been documented to be associated with GBM, in which 70 are recognized as
GBM markers (**Fig. 5a**). Clusters 1, 2, and 3, built on these 167 feature genes, exhibit distinct
molecular characteristics, with representative reported markers as listed below; cluster 1 shows copy
number amplification in *LTBR* and *MICALCL* and increased expression in *FAH*, *SENP8*, and
DIABLO, cluster 2 exhibits increased expression in *HDAC9*, *LSAMP*, and *CHD6*, and cluster 3
presents increased expression in *VGF*, *TRPV4*, and *CCR2* and increased methylation in *PCDH8*,
GPD1, and *C1QB* (**Fig. 4f**). Furthermore, tissue enrichment and functional annotation analyses
reveal that the 167 feature genes are closely associated with brain tissues and crucial for
pathobiological processes, such as neuroblast proliferation, immune microenvironment dynamics,
and tumor-related pathways (**Supplementary Fig. 17a,b**).

We also use MIA to identify feature genes based on single-omics and two-omics data. Among these
167 feature genes, 96 (57.5%) and 43 (25.7%) genes are specifically identified based on three-omics
data, by comparison against single-omics and two-omics data, respectively (**Fig. 5b,c**). Functional
enrichment analysis shows that these feature genes specifically identified by three-omics data
exhibit stronger associations with brain tissue and tumor development (**Supplementary Fig. 17c**).
We further analyze the clustering power of feature genes specifically identified by different omics
combinations. We observe that feature genes identified from single-omics data exhibit strong
significance within their respective omics layers, but feature genes from three-omics always show
higher clustering scores, clearly indicating that multi-omics integrative analysis achieves more
enhanced clustering power (**Fig. 5d,e**). Notably, several literature-reported GBM marker genes,
such as *VGF* (promoting GBM stem cell survival and tumor growth[36]) and *BRD8* (hindering *p53*
transcriptional activation and promoting GBM cell proliferation[37])*, are successfully identified by
three-omics data integrative analysis, yet absent in single-omics or two-omics data analysis
(**Supplementary Table 8**). It is worth mentioning that based on three-omics integrative analysis,
LTBR (activating anti-tumor immune response in glioma[38]) and *GPD1* (whose inhibition prolongs
GBM mouse survival[39]) are computationally identified as feature genes with markedly enhanced

priority (**Supplementary Fig. 18**), thus highlighting the great potential of MIA to uncover biologically significant features from multi-omics data and thereby guiding in-depth experimental validation and mechanism investigation.

Characterization of Temozolomide treatment sensitivity through GBM feature genes

Temozolomide (TMZ) is one of the most effective chemotherapy agents for GBM treatment[29]. Based on these 167 feature genes identified by MIA, we further explore whether these genes can be used to predict TMZ chemotherapy response. Toward this end, firstly, we collect a publicly available dataset (expression data only) with GBM TMZ treatment, containing samples of control, TMZ + radiotherapy, and TMZ + radiotherapy + inhibitor[40]. MIA clustering based on the 167 gene expression profiles separates the samples into three clusters that correspond closely to the three treatment groups. We find that the control samples are most enriched in cluster 1, the TMZ + radiotherapy samples are most in cluster 2, and the TMZ + radiotherapy + inhibitor samples are exclusively included in cluster 3 (**Fig. 6a** and **Supplementary Table 9**). A multi-class ROC analysis yields an average AUC of 0.85, indicating that these genes effectively distinguish different TMZ treatment regimens. (**Fig. 6b**). To further assess the relevance of these genes to TMZ treatment sensitivity, we collect three independent datasets containing TMZ-resistant and TMZ-sensitive GBM cell-line samples. For these three datasets, clustering results align perfectly with the outcomes of TMZ treatment (**Fig. 6c-e** and **Supplementary Table 9**), implying that these 167 genes are closely associated with TMZ chemotherapy response.

To systematically identify genes associated with TMZ chemotherapy sensitivity, we discover that 64 genes display consistent expression patterns in the above datasets. We collect these 64 genes' associations with chemotherapy drugs across different cancers (**Supplementary Table 10)**. Notably, ten genes (*GPD1*, *MSI1*, *IFFO1*, *NCBP2*, *SGTA*, *BCL9L*, *FOXP4*, *KCP*, *MAPK13*, and *PAFAH1B1*) have already been reported to be related to chemotherapy sensitivity (**Fig. 6f**). Specifically, *GPD1* is specifically expressed in brain tumor stem cells and involved in tumor initiation, metastasis, and recurrence; increased expression of *GPD1* correlates with TMZ resistance in GBM[39]. *MSI1* is a stem cell gene that controls the balance between self-renewal and differentiation; GBM lines with *MSI1* knockout display increased sensitivity to cell cycle and DNA replication inhibitors[41]. The rest eight genes, albeit unexplored with GBM chemotherapy, associate closely with gynecological cancers[42-44], LIHC[45], gastrointestinal cancers[46, 47], hematological malignancies[48], and other cancers[49], presumably indicating their potential relevance in GBM treatment.

Discussion

In this study, we presented MIA, a powerful framework for multi-omics integrative analysis capable of accurate sample clustering and feature gene identification. MIA utilizes various machine learning techniques, including Tucker decomposition, FCM, and ERFM, to effectively integrate and analyze multi-omics data and identify biologically important features contributing to sample clustering.

Comparative analyses on simulated and real datasets revealed that MIA outperforms existing algorithms in both integrative clustering and feature identification. As testified in GBM multi-omics data analysis, MIA is powerful to cluster samples into clinically relevant subtypes with distinct survival outcomes and identify feature genes associated with TMZ treatment sensitivity.

MIA adopts a machine learning-based strategy to achieve powerful multi-omics integrative analysis. Although deep learning has achieved remarkable progress in biomedical research, its reliance on large, well-annotated datasets limits its applicability to omics data, which are typically high-dimensional, unlabeled, and sample-limited. In contrast, the machine learning models used in MIA, such as random forest, are more robust to small sample size, less prone to overfitting, and offer interpretable results with biological insights. Despite this, technically, future explorations and improvements for MIA include the following. First, the tensor framework requires both matched samples and genes across omics types, limiting its applicability to data with heterogeneous features. Second, after Tucker decomposition, only sample-feature matrix is used for clustering, whereas gene-feature and omics type-feature matrices remain underutilized. Notably, clustering heatmaps from gene-feature matrix in simulated data clear separated real from noise features (**Supplementary Fig. 1b**), suggesting potential for feature filtering. Additionally, omics type-feature matrix may quantify contributions from different omics layers; in GBM multi-omics, for example, eigenvalues for CNV, gene expression, and methylation were 0.446, 0.674, and 0.589, respectively (**Supplementary Table 7**), indicating a stronger influence of gene expression, which aligns well with single-omics analyses showing its most relevance to survival (**Fig. 3c**). Thus, omics type-feature matrix contains substantial biological relevance and further exploration of its application for optimizing feature gene identification would be desirable.

Across the ten cancer types, clusters derived from CNV and methylation data generally showed smaller survival differences than those from gene expression (**Fig. 3c**). From the data perspective, this may stem from limited or/and uneven distribution of samples exhibiting heterogeneous copy number amplifications/deletions, and signal attenuation introduced during the conversion of methylation measurements from the site level to the gene level. From the biological perspective, gene expression is closely correlated with CNV and promoter methylation status[50], together exerting an influence on protein production, cell function, and thereby, phenotypic and clinical outcomes[51]. Furthermore, we observe that nearly all algorithms exhibit comparable survival differences in LGG on multiple omics combinations, primarily due to substantial molecular variations between grade II and grade III LGG, with the latter associated with a worse prognosis[52].

In GBM, we observed that the fraction of genome altered, a measure of the extent of copy number changes in the genome, decreased with declining survival rates (**Fig. 4d**). In early-stage tumors, studies have demonstrated that a higher fraction of genome altered is typically associated with poorer pathological characteristics and survival rates[53, 54], and is also a sign of poor prognosis[55, 56]. On the contrary, in advanced tumors, several studies have also found that tumors with lower genomic alterations can exhibit more aggressive behavior and decreased survival rates[32]. For example, in metastases compared to primary lung adenocarcinoma, the fraction of genome altered was significantly lower[57]. Additionally, excessive genomic instability may cumulate damage, exceeding the threshold of tumor cell activity, thereby inhibiting advanced tumor growth and

metastasis[58]. Our observations in GBM are consistent with these findings of advanced tumors, but
more research is needed to explore the association between this indicator and the prognosis of
advanced tumors.

To sum up, with the vast volume of multi-omics data generated by higher-throughput sequencing
technologies, multi-omics integrative analysis becomes increasingly routine and popular. Thus,
MIA bears great utility for providing multi-layered insights into complex biological and
physiopathological processes and promoting precision diagnostics and targeted therapies.

Methods

Simulated datasets

Simulated multi-omics datasets were generated by a Python script. Several parameters—number of
clusters (K), number of omics types (T), sample size (N), and number of real features (M_t), and
number of noise features (M_f)—were considered and five replicates were produced for each
parameter combination. Samples were assigned to K clusters using a Gaussian probability
distribution. Each omics layer was represented as an $N \times (M_t + M_f)$ matrix, where M_t features were
differentially expressed across clusters with group-specific means and Gaussian noise and M_f
features were randomly generated. For clustering evaluation, we considered the effects of K and T
(K varies from 2~6 and T varies from 1~3 with fixed N=500, M_t=5,000 and M_f=5,000) and then the
effects of N, M_t, and M_f (N=50, 500, 5,000, M_t=1,000, 5,000, 10,000, and M_f =1,000, 5,000, 10,000,
with fixed K=4 and T=2). For feature gene identification, datasets were simulated with K=4 and 5,
N=500, M_t=1,000, and M_f=10,000. The code for dataset simulation is provided in
simulate_datasets.py within the MIA package (available at https://ngdc.cncb.ac.cn/mia/download).

The TCGA datasets

Multi-omics datasets for ten TCGA cancer types, including CNV (gene-level), gene expression
(FPKM), and DNA methylation data, were downloaded from UCSC Xena
(https://xenabrowser.net/). For DNA methylation data, the methylation level of each gene was
determined by averaging methylation levels of all sites within the first 1,500bp upstream of the gene.
For integrative analysis, only samples and genes shared across all three omics types were retained
for each cancer type. Survival data and clinical information were obtained from cBioPortal
(https://www.cbioportal.org/). Tumor stemness index (mRNA expression-based stemness index,
mRNAsi) were adopted by referencing a previous study[33]. Feature genes identified for GBM were
annotated by PubMed (https://pubmed.ncbi.nlm.nih.gov/), BrainBase[59], MSigDB[60], and EWAS[61].

GBM temozolomide treatment datasets

333 Gene expression datasets related to GBM temozolomide (TMZ) treatment were retrieved from the
334 Gene Expression Omnibus (GEO) (https://www.ncbi.nlm.nih.gov/gds/). Specifically, GSE211272[40]

contained 72 samples from 12 GBM cell lines, including 24 control samples, 24 samples treated with TMZ and radiotherapy, and 24 samples treated with TMZ, radiotherapy and molecular inhibitor of Ataxia-telangiectasia and Rad3-Related protein. GSE113510[62] comprised 3 control samples and 3 TMZ-resistant samples cultured from GBM cells. GSE100736 included 3 TMZ-resistant GBM cell lines and 3 TMZ-sensitive cell lines. GSE68029[63] included 3 samples that survived one cycle treatment with 500uM TMZ, and 3 samples that survived two cycle treatment with 500uM TMZ, representing low to high TMZ resistant. The datasets from GSE211272 and GSE68029 were corrected for batch effects using the Combat[64] method. Feature gene expression matrices were then constructed by mapping the predefined set of 167 GBM feature genes to each dataset, with 165, 161, 165, and 162 matched genes in GSE211272, GSE113510, GSE100736, and GSE68029, respectively.

Tensor integration and decomposition

Multi-omics data are integrated into a three-dimensional tensor: sample, gene, data type, denoted as $A \in R^{N \times M \times T}$, where N is the number of samples, M is the number of genes, T is the number of omics types, and R is the set of real numbers. For unlabeled data, Tucker decomposition is applied to factorize the tensor A into factor matrices, as defined in Equation 1.

$$A = \mathcal{G} \times S_p \times G_q \times O_r \qquad \text{Eq. (1)}$$

Here, $S \in R^{N \times p}$, $G \in R^{M \times q}$ and $O \in R^{T \times r}$ are the factor matrices of sample-feature, gene-feature, and type-feature, respectively, where $p \in [1, N]$, $q \in [1, M]$, and $r \in [1, T]$ are the number of columns in each factor matrices. $\mathcal{G} \in R^{p \times q \times r}$ is the core tensor, whose entries show interaction between the different components. By default, p, q and r are set to $log_2(N)$, $log_2(M)$ and $log_2(W)$, respectively, but they can be specified by users. The sample-feature matrix S is subsequently used for clustering analysis. Tucker decomposition was performed using the Python package "TensorLy"[65] (http://tensorly.org/stable/index.html).

FCM clustering and parameter optimization

The sample-feature matrix S obtained from Tucker decomposition is used for FCM clustering, which attempts to partition the N samples, denoted as x_i ($i=1, 2, \ldots, N$), into K ($K>1$) fuzzy clusters. FCM initializes a set of cluster centers C_k ($k=1, 2, \cdots, K$) and a membership matrix $U = u_{ik} \in [0,1]$ ($i=1, 2, \ldots, N$ and $k=1, 2, \cdots, K$), where each element u_{ik} tells the degree to which sample x_i belongs to cluster C_k, satisfying $\sum_{k=1}^{K} u_{ik} = 1$. Given a fuzzy index $m \in (1, \infty)$ and the number of clusters K, FCM aims to minimize a loss function: $J(U, C) = \sum_{i=1}^{N} \sum_{k=1}^{K} u_{ik}^m ||x_i - C_k||^2$, where $u_{ik} =$

$\dfrac{1}{\sum_{q=1}^{K} \left(\frac{||x_i - C_k||}{||x_i - C_q||}\right)^{\frac{2}{m-1}}}$ and $C_k = \dfrac{\sum_{k=1}^{K} u_{ik}^m x_i}{\sum_{k=1}^{K} u_{ik}^m}$. When $J_n - J_{n-1} < e^{-15}$, where n represents the number of iterations,

it means the function convergence as indicated by high inter-cluster dispersion and high intra-cluster compactness.

FCM involves two key parameters: the fuzzy index (m) and the number of clusters (K). For the
fuzzy index, Schwammle's formula[28] is employed to estimate a potential optimal value, namely,
$m=1+(1418/N+22.05)M^{\wedge}(-2)+(12.33/N+0.243)M^{\wedge}(-0.0406ln(N)-0.1134)$, where N is the number of
samples and M is the number of features. Additionally, an automatic procedure is implemented to
determine K when it is not provided. Five clustering evaluation indicators—Silhouette Coefficient[66],
Davies-Bouldin Index[67], Elbow method[68], Separation index, and Compactness index—were adopted
to compare the accuracy of optimal K estimation. Among them, the Silhouette Coefficient
consistently achieved the highest accuracy (**Supplementary Fig. 3**), and therefore was used to
estimate the optimal K value.

Gene filtering by Gini index

379 The Gini index was used to filter genes (**Supplementary Fig. 4a,b**), defined as $gini(split) = 1 -$
380 $\sum_{k=1}^{K} p_k^2$, where p represents the proportion of samples belonging to the k-th category defined by
381 clustering results or sample labels. For the t-th omics type, the Gini index of the j-th gene under a
382 partition threshold X is calculated as:

$$Gini(j, t, X) = gini(K) - \frac{N_{value \leq X}}{N} gini(value \leq X) - \frac{N_{value > X}}{N} gini(value > X), \quad \text{Eq. (2)}$$

where N represents the number of samples, and $value \leq X$ (or $value > X$) denotes the subset of samples
with values less (or greater) than X. The objective is to identify the optimal threshold X that
maximizes $Gini(j,t,X)$:$Gini(j,t)=max(Gini(j,t,X_1), Gini(j,t,X_2), …, Gini(j,t,X_n))$. For each omics type,
the mean Gini index of M genes is denoted as $meanGini(t) = \frac{1}{M}(\sum_{j=1}^{M} Gini(j, t))$. Genes satisfying
the condition $Gini(j,t)>meanGini(t)$ across all omics types are retained. These retained genes,
denoted as M', are considered as potential features for subsequent ERFM analysis.

Feature gene identification based on multi-omics using ERFM

In this study, ERFM, an enhanced RFM, was developed to identify feature genes that play a
significant role in clustering on multi-omics data. After gene filtering, ERFM is constructed using
N samples, M' filtered genes, and T omics types, and the corresponding sample labels or clustering
results. ERFM consists of multiple decision trees, and the workflow is as follows (**Supplementary**
Fig. 4c):

(a) Data preparation: Using bootstrap sampling, 70% of N samples are randomly selected for
training each decision tree, while the remaining 30% samples are used for testing. Each decision
tree has different training and testing samples. M_s ($M_s \leq sqrt(M')$) genes are randomly selected from
the M' genes, and the Gini index is used to select the best combination among the M_s genes for
constructing the decision tree.

(b) Enhanced tree structure: In a traditional decision tree, each node contains only one-
dimensional feature information. To handle multi-omics data, the tree structure is modified and

enhanced to integrate multi-omics features of each gene. When a gene M_i is selected, data from all
T omics layers of that gene are used to construct tree nodes, yielding T nodes per gene. The optimal
splits for each node are determined using $Gini(j,1)$, $Gini(j,2)$, ..., and $Gini(j, T)$. For example, in the
case of three omics types, three nodes are built for a single gene. The trees are grown until either
the depth reaches $log2(M')$-1 or the number of features reaches $sqrt(M')$.

(c) Gene importance in a decision tree: Once a decision tree d is trained, the remaining 30% of
samples are used for classification prediction to calculate out-of-bag error rate (obb_error_d). To
evaluate the importance of a gene M_i, the values of all omics layers corresponding to M_i in the test
set are simultaneously randomized, and the out-of-bag error rate ($obb\_error_{random(Mi)}$) is calculated.
The importance of gene M_i in the decision tree d is then defined as:
$importance_d(M_i,d)=obb\_error_{random(Mi)} - obb\_error_d$.

(d) Gene importance in a random forest: A random forest r creates 100 decision trees $d \in \{1,$
$2, …,100\}$ by default, repeating **steps (a-c)**. The importance of gene M_i in forest r is calculated as:

$importance_r(M_i, r) = \frac{1}{100}\sum_{d=1}^{100} importance_d(M_i, d)$. The number of genes whose

$importance_r(M_i,r) \lesssim 0$ is recorded as $M_{\leq 0}$.

(e) Iterative computational procedure: To enhance consistency of the identified feature gene set,
an iterative procedure is applied with a termination condition: if $M_{\leq 0}>0$, these $M_{\leq 0}$ genes are
removed, and $M'=M'-M_{\leq 0}$ is updated to repeat **steps (a-d)**; if $M_{\leq 0}=0$, the iterative procedure stops,
and the remaining M' genes are considered as the final feature gene set. The overall importance of

gene M_i is computed as: $importance(M_i) = \frac{1}{R}\sum_{r=1}^{R} importance_r(M_i, r)$, where R represents the

number of iterations.

Finally, MIA normalizes and ranks the importance scores of the remaining M' genes, and the
Wilcoxon rank-sum test is used to identify genes showing significant differences among clusters
(**Supplementary Fig. 4d**).

Clustering evaluation

To benchmark the performance of MIA, we compared it with existing algorithms using their default
or recommended parameter settings. All algorithms were applied to the same preprocessed multi-
omics datasets, and clustering results were evaluated using a unified evaluation framework to ensure
consistency and comparability. For simulated datasets, clustering accuracy was assessed using the
ARI, which measures concordance between predicted and true labels on a scale from -1 to 1, with
higher values indicating higher accuracy. For TCGA empirical datasets, we evaluated both survival
and clinical relevance of the derived clusters. Survival differences were assessed using Kaplan-
Meier estimation and log-rank testing. Significances between clusters and clinical records were
examined using chi-square tests for categorical variables and Kruskal-Wallis tests for continuous
variables, with empirical significance estimated via permutation to obtain confidence intervals,
following established procedures[12]. For TMZ response datasets, clustering accuracy was quantified

using multi-class ROC analysis. Each cluster was evaluated in a one-vs-rest framework, ROC
curves were generated for all classes, and overall performance was summarized using the macro-
averaged area under the curve (AUC).

Feature gene evaluation

For each gene, the Kruskal-Wallis test was employed to quantify its discriminative ability among
groups by using true labels in simulated datasets and identified clusters in empirical datasets. Based
on this test, significance level was obtained at each omics layer (e.g., CNV, expression, methylation).
For any multi-omics dataset, significance level was averaged across its corresponding omics layers.
The clustering power of a feature-gene set was quantified by the Kruskal-Wallis test and the Gini
index across all feature genes.

Code development and server implementation

450 MIA was developed by using standard C++ and Python. The pybind11 library was used to create
451 Python bindings for C++ codes. In addition, a user-friendly web interface was developed, allowing
452 users to perform online analysis. The MIA web interface and its command-line source codes are
453 publicly available at https://ngdc.cncb.ac.cn/mia/.

References

1. Hasin, Y., Seldin, M. & Lusis, A. Multi-omics approaches to disease. *Genome Biology* **18**, 83
(2017).
2. Subramanian, I., Verma, S., Kumar, S., Jere, A. & Anamika, K. Multi-omics data integration,
interpretation, and its application. *Bioinformatics and Biology Insights* **14**, 1177932219899051
(2020).
3. Karczewski, K.J. & Snyder, M.P. Integrative omics for health and disease. *Nature Reviews*
Genetics **19**, 299-310 (2018).
4. Sandhu, C., Qureshi, A. & Emili, A. Panomics for precision medicine. *Trends in Molecular*
Medicine **24**, 85-101 (2018).
5. Xu, Y. et al. Multi-omics analysis at epigenomics and transcriptomics levels reveals prognostic
subtypes of lung squamous cell carcinoma. *Biomedicine & Pharmacotherapy* **125**, 109859 (2020).
6. Hoadley, K.A. et al. Cell-of-origin patterns dominate the molecular classification of 10,000 tumors
from 33 types of cancer. *Cell* **173**, 291-304 (2018).
7. Yoon, S.J. et al. Comprehensive multi-omics analysis reveals aberrant metabolism of Epstein–Barr-
virus-associated gastric carcinoma. *Cells* **8**, 1220 (2019).
8. Miao, R. et al. Identification of prognostic biomarkers in hepatitis B virus-related hepatocellular
carcinoma and stratification by integrative multi-omics analysis. *Journal of Hepatology* **61**, 840-
849 (2014).
9. Gisby, J.S. et al. Multi-omics identify falling LRRC15 as a COVID-19 severity marker and
persistent pro-thrombotic signals in convalescence. *Nature Communications* **13**, 7775 (2022).

10. Chen, C. et al. Applications of multi-omics analysis in human diseases. *MedComm* **4**, e315 (2023).

11. Eddy, S., Mariani, L.H. & Kretzler, M. Integrated multi-omics approaches to improve classification

of chronic kidney disease. *Nature Reviews Nephrology* **16**, 657-668 (2020).

12. Rappoport, N. & Shamir, R. Multi-omic and multi-view clustering algorithms: review and cancer

benchmark. *Nucleic Acids Research* **46**, 10546-10562 (2018).

13. Wang, B. et al. Similarity network fusion for aggregating data types on a genomic scale. *Nature*

Methods **11**, 333-337 (2014).

14. Nguyen, T., Tagett, R., Diaz, D. & Draghici, S. A novel approach for data integration and disease

subtyping. *Genome Research* **27**, 2025-2039 (2017).

15. Rappoport, N. & Shamir, R. NEMO: cancer subtyping by integration of partial multi-omic data.

Bioinformatics **35**, 3348-3356 (2019).

16. Tyler, S.R. et al. Merged affinity network association clustering: Joint multi-omic/clinical

clustering to identify disease endotypes. *Cell Reports* **35**, 108975 (2021).

17. Argelaguet, R. et al. Multi-omics factor analysis-a framework for unsupervised integration of multi-

omics data sets. *Molecular Systems Biology* **14**, e8124 (2018).

18. Shi, Q. et al. Pattern fusion analysis by adaptive alignment of multiple heterogeneous omics data.

Bioinformatics **33**, 2706-2714 (2017).

19. Chalise, P. & Fridley, B.L. Integrative clustering of multi-level 'omic data based on non-negative

matrix factorization algorithm. *PLoS One* **12**, e0176278 (2017).

20. Fang, J. Tightly integrated genomic and epigenomic data mining using tensor decomposition.

Bioinformatics **35**, 112-118 (2019).

21. Harshman, R.A. Foundations of the PARAFAC procedure: Models and conditions for an

"explanatory" multi-modal factor analysis. *UCLA working papers in phonetics* **16**, 84 (1970).

22. Kroonenberg, P.M. Three-mode principal component analysis: Theory and applications, Vol. 2.

(DSWO press, 1983).

23. Carroll, J.D. & Chang, J.J. Analysis of individual differences in multidimensional scaling via an n-

way generalization of "Eckart-Young" decomposition. *Psychometrika* **35**, 283-319 (1970).

24. Cichocki, A. et al. Tensor networks for dimensionality reduction and large-scale optimization: part

1 low-rank tensor decompositions. *Foundations and Trends in Machine Learning* **9**, 249-429

(2016).

25. Jung, I., Kim, M., Rhee, S., Lim, S. & Kim, S. MONTI: A multi-omics non-negative tensor

decomposition framework for gene-level integrative analysis. *Frontiers in Genetics* **12**, 682841

(2021).

26. Zhang, J.Z., Xu, W. & Hu, P. Tightly integrated multiomics-based deep tensor survival model for

time-to-event prediction. *Bioinformatics* **38**, 3259-3266 (2022).

27. Chang, S.M. et al. Gene-set integrative analysis of multi-omics data using tensor-based association

test. *Bioinformatics* **37**, 2259-2265 (2021).

28. Schwammle, V. & Jensen, O.N. A simple and fast method to determine the parameters for fuzzy c-

means cluster analysis. *Bioinformatics* **26**, 2841-2848 (2010).

29. Adair, J.E. et al. Gene therapy enhances chemotherapy tolerance and efficacy in glioblastoma

patients. *Journal of Clinical Investigation* **124**, 4082-4092 (2014).

30. Grochans, S. et al. Epidemiology of Glioblastoma Multiforme–Literature Review. *Cancers* **14**,
2412 (2022).
31. Verhaak, R. et al. Integrated genomic analysis identifies clinically relevant subtypes of
glioblastoma characterized by abnormalities in PDGFRA, IDH1, EGFR, and NF1. *Cancer Cell* **17**,
98-110 (2010).
32. Mehta, K.R. et al. Fractional genomic alteration detected by array-based comparative genomic
hybridization independently predicts survival after hepatic resection for metastatic colorectal
cancer. *Clinical Cancer Research* **11**, 1791-1797 (2005).
33. Malta, T.M. et al. Machine learning identifies stemness features associated with oncogenic
dedifferentiation. *Cell* **173**, 338-354 (2018).
34. Joseph, J.V. et al. Serum-induced differentiation of glioblastoma neurospheres leads to enhanced
migration/invasion capacity that is associated with increased MMP9. *PLoS One* **10**, e0145393
(2015).
35. Wang, Z. et al. Machine learning revealed stemness features and a novel stemness-based
classification with appealing implications in discriminating the prognosis, immunotherapy and
temozolomide responses of 906 glioblastoma patients. *Brief Bioinform* **22**, bbab032 (2021).
36. Wang, X. et al. Reciprocal signaling between glioblastoma stem cells and differentiated tumor dells
promotes malignant progression. *Cell Stem Cell* **22**, 514-528 (2018).
37. Sun, X. et al. BRD8 maintains glioblastoma by epigenetic reprogramming of the p53 network.
Nature **613**, 195-202 (2023).
38. Tang, Q. et al. Comprehensive analysis reveals that LTBR is a immune-related biomarker for
glioma. *Computers in Biology and Medicine* **174**, 108457 (2024).
39. Rusu, P. et al. GPD1 specifically marks dormant glioma stem cells with a distinct metabolic profile.
Cell Stem Cell **25**, 241-257 (2019).
40. Lozinski, M. et al. ATR inhibition using gartisertib enhances cell death and synergises with
temozolomide and radiation in patient-derived glioblastoma cell lines. *Oncotarget* **15**, 1-18 (2024).
41. Baroni, M. et al. Musashi1 Contribution to Glioblastoma Development via Regulation of a Network
of DNA Replication, Cell Cycle and Division Genes. *Cancers* **13**, 1494 (2021).
42. Zhang, Y. et al. METTL3-mediated N6-methyladenosine modification and HDAC5/YY1 promote
IFFO1 downregulation in tumor development and chemo-resistance. *Cancer Lett* **553**, 215971
(2023).
43. He, Y. et al. Examination of the functions and mechanism of KCP in mediating paclitaxel
resistance in cervical squamous carcinoma cells. *Front Oncol* **15**, 1550032 (2025).
44. Majmudar, P.R. & Keri, R.A. The neural stem cell gene PAFAH1B1 controls cell cycle
progression, DNA integrity, and paclitaxel sensitivity of triple-negative breast cancer cells. *J Biol*
Chem **301**, 110235 (2025).
45. Zhang, L. et al. NRBP2 Overexpression Increases the Chemosensitivity of Hepatocellular
Carcinoma Cells via Akt Signaling. *Cancer Research* **76**, 7059-7071 (2016).
46. Lu, M. et al. Long non-coding RNA LINC00665 promotes gemcitabine resistance of
Cholangiocarcinoma cells via regulating EMT and stemness properties through miR-424-
5p/BCL9L axis. *Cell Death Dis* **12**, 72 (2021).

47. Liu, X. et al. FOXP4 Is a Direct YAP1 Target That Promotes Gastric Cancer Stemness and Drives
Metastasis. *Cancer Research* **84**, 3574-3588 (2024).

48. Wang, Y. et al. Expression of small glutamine-rich TPR-containing protein A (SGTA) in Non-
Hodgkin's Lymphomas promotes tumor proliferation and reverses cell adhesion-mediated drug
resistance (CAM-DR). *Leuk Res* **38**, 955-963 (2014).

49. Kim, J. et al. MAPK13 stabilization via m(6)A mRNA modification limits anticancer efficacy of
rapamycin. *J Biol Chem* **299**, 105175 (2023).

50. You, J.S. & Jones, P.A. Cancer genetics and epigenetics: two sides of the same coin? *Cancer Cell*
22, 9-20 (2012).

51. Claussen, H., Ghosh, S. & Chen, J. Exploring combined effects of DNA methylation and copy
number on gene expression with a two-stage approach. *IEEE/ACM Transactions on Computational*
Biology and Bioinformatics **21**, 1667-1675 (2024).

52. Brat, D.J. et al. Comprehensive, integrative genomic analysis of diffuse lower-grade gliomas. *New*
England Journal of Medicine **372**, 2481-2498 (2015).

53. Hurst, C.D. et al. Stage-stratified molecular profiling of non-muscle-invasive bladder cancer
enhances biological, clinical, and therapeutic insight. *Cell Reports Medicine* **2**, 100472 (2021).

54. Chakraborty, G. et al. Fraction genome altered (FGA) to regulate both cell autonomous and non-
cell autonomous functions in prostate cancer and its effect on prostate cancer aggressiveness.
Journal of Clinical Oncology **38**, 347 (2020).

55. Zhou, W. et al. Counting alleles to predict recurrence of early-stage colorectal cancers. *Lancet* **359**,
219-225 (2002).

56. Choi, S.W. et al. Genetic classification of colorectal cancer based on chromosomal loss and
microsatellite instability predicts survival. *Clinical Cancer Research* **8**, 2311-2322 (2002).

57. Zhao, R. et al. Clonal dynamics and Stereo-seq resolve origin and phenotypic plasticity of
adenosquamous carcinoma. *Npj Precision Oncology* **7**, 80 (2023).

58. Cahill, D.P., Kinzler, K.W., Vogelstein, B. & Lengauer, C. Genetic instability and darwinian
selection in tumours. *Trends in Cell Biology* **9**, M57-M60 (1999).

59. Liu, L. et al. BrainBase: a curated knowledgebase for brain diseases. *Nucleic Acids Research* **50**,
D1131-D1138 (2022).

60. Liberzon, A. et al. The Molecular Signatures Database (MSigDB) hallmark gene set collection. *Cell*
Systems **1**, 417-425 (2015).

61. Li, M. et al. EWAS Atlas: a curated knowledgebase of epigenome-wide association studies. *Nucleic*
Acids Res **47**, D983-d988 (2019).

62. Wu, P. et al. Lnc-TALC promotes O(6)-methylguanine-DNA methyltransferase expression via
regulating the c-Met pathway by competitively binding with miR-20b-3p. *Nature Communications*
10, 2045 (2019).

63. Tso, J.L. et al. Bone morphogenetic protein 7 sensitizes O6-methylguanine methyltransferase
expressing-glioblastoma stem cells to clinically relevant dose of temozolomide. *Molecular Cancer*
14, 189 (2015).

64. Leek, J.T., Johnson, W.E., Parker, H.S., Jaffe, A.E. & Storey, J.D. The sva package for removing
batch effects and other unwanted variation in high-throughput experiments. *Bioinformatics* **28**, 882-
883 (2012).

65. Kossaifi, J., Panagakis, Y., Anandkumar, A. & Pantic, M. TensorLy: Tensor Learning in Python.
Journal of Machine Learning Research **20**, 1-6 (2019).
66. Zhu, L., Ma, B. & Zhao, X. Clustering validity analysis based on silhouette coefficient. *Journal of*
Computer Applications **30**, 139-141 (2010).
67. Xiao, J., Lu, J. & Li, X. Davies Bouldin Index based hierarchical initialization K-means. *Intelligent*
Data Analysis **21**, 1327-1338 (2017).
68. Archdeacon, T.J. Correlation and regression analysis: a historian's guide. (University of Wisconsin
Press, USA; 1994).
607

Acknowledgments

This work was supported by the National Natural Science Foundation of China (T2425005).

Author contributions

Yang Zhang: Data curation, Formal analysis, Investigation, Methodology, Software, Visualization, Validation, Writing - original draft, Writing - review & editing; Lin Liu: Data curation; Zhaoqi Liu: Writing - review & editing; Qi Liu: Writing - review & editing; Lina Ma: Conceptualization, Project administration, Writing - review & editing; Zhang Zhang: Conceptualization, Funding acquisition, Project administration, Writing - review & editing. All authors have read and approved the final manuscript.

Competing interests

The authors declare no competing interests.

Figures

Fig. 1. Schematic of the MIA framework.

(a) Various types of omics data (e.g., CNV, expression, and methylation data) are integrated into a tensor,
forming a three-dimensional matrix comprising samples, genes, and omics types. (b) Tucker
decomposition is used to factorize the tensor into three two-dimensional factor matrices: sample-feature
matrix, gene-feature matrix, and type-feature matrix. Subsequently, the FCM clustering is used to cluster
the sample-feature matrix. (c) Feature gene identification is performed based on the tensor and
clustering/labeled information. After gene filtering by the Gini index, an ERFM designed for three-
dimensional matrix is applied to quantify the contribution of each gene in clustering and thus to yield a
set of feature genes (see details in Methods).

Fig. 2. Performance of MIA in clustering and feature gene identification on simulated datasets by comparison against several existing algorithms.

(a) Clustering performance across different numbers of clusters (K=2~6) and omics types (T=1~3), with fixed sample size (N=500), real features (M_t=5,000), and noise features (M_f=5,000). Clustering accuracy is assessed by the Adjusted Rand Index (ARI). (b) Clustering performance across varied sample sizes (N=50, 500, and 5,000), real features (M_t=1,000, 5000, and 10,000), and noise features (M_f=1,000, 5,000,

and 10,000), with fixed K=4 and T=2. (c) Evaluation of optimal K estimation by different algorithms
based on simulated datasets consisting of K=2~6, M_f=1,000, 5,000, and 10,000, with fixed N=500 and
M_t=1,000. The proportion of predicted K values identified by each algorithm is calculated across
simulated replicates. (d) Performance of feature genes identified by different algorithms is evaluated by
the Kruskal-Wallis test on five simulated replicates (data1~data5) with K=4~5, T=2, N=500, M_t=1,000,
and M_f=10,000.

Fig. 3. Evaluation of survival outcomes and feature genes determined by MIA on TCGA datasets
in comparison with existing algorithms.

Comparison of clustering results from different algorithms based on survival significance in (a) three-
omics, (b) two-omics, and (c) single-omics datasets. (d) Number of significantly enriched clinical records
(p<0.05) across ten cancer types. Horizontal lines indicate the median and dashed lines represent the
mean. (e) Feature gene signifiance between cancer and normal samples across seven cancer types. The
Kruskal-Wallis test was used to evaluate the average significance of feature genes identified by each
algorithm (p-value, with ****<0.0001, ***<0.001, **<0.01, *<0.05, and ns not signifiacnt).

Fig. 4. TCGA GBM subtyping analysis by MIA.

(a) Clustering evaluation at different *K* values using the silhouette coefficient and Davies-Bouldin index. A higher silhouette coefficient and lower Davies-Bouldin index indicate better cluster separation. (b) Principal component analysis (PCA) of the sample-feature matrix obtained from Tucker decomposition. (c) Kaplan-Meier survival curves for the three clusters identified by MIA. The log-rank test was used to assess the statistical significance and the accompanying table shows the number of samples and their survivals at specific time points. (d) Fractions of genome altered across the three clusters. (e) Stemness index (mRNA expression-based stemness index, mRNAsi) across the three clusters, with statistical significance assessed by the Wilcoxon rank-sum test. (f) Heatmaps of 167 GBM feature genes identified by MIA.

Fig. 5. Characterization of 167 GBM feature genes identified by MIA.

(a) Feature genes ranked by MIA scores (0~1), with literaure evidence, database support, and genes
identified by single-omics data analysis (genes identified by CNV did not reach the threshold)
(**Supplementary Table 9**). (b-c) Feature genes identified from three-omics, by comparsion with single-
omics and two-omics, respectively. (d-e) Clustering power of feature genes specifically identified from
three-omics, by comparsion with single-omics and two-omics, respectively. The Kruskal-Wallis test and
the Gini index were employed to evaluate the clustering power.

Fig. 6. MIA Clustering of 167 GBM feature genes in TMZ treatment datasets.

(a) MIA Clustering of 167 GBM feature genes in GSE211272, including control, TMZ + radiotherapy,

and TMZ + radiotherapy + inhibitor samples. (b) Multi-class ROC curve illustrating clustering

performance on GSE211272. (c-e) MIA Clustering of 167 GBM feature genes in three TMZ treatment

datasets, viz., GSE113510 (control vs resistant), GSE100736 (resistant vs sensitive), and GSE68029 (low

resistant vs high resistant). (f) The literature-reported feature genes, exhibiting consistent expression

patterns in both GSE100736 and GSE68029.

680   Supplementary Figures

Supplementary Fig. 1. Schematic of Tucker decomposition for multi-omics data.

(a) Tensor integration of multi-omics data into a three-dimensional matrix, and Tucker decomposition

factorizing the tensor into three factor matrices: sample-feature matrix, gene-feature matrix, and type-

feature matrix. (b) Tucker decomposition results on simulated datasets with T=2, K=5, N=500, M_t=1,000,

and M_f=10,000.

Supplementary Fig. 2. Schematic of multi-omics data integration and FCM clustering.

(a) FCM clustering using the sample-feature matrix with specified cluster count (K) and fuzzy index (m).

(b) Membership matrix U initialized to represent samples-cluster probability. (c) Cluster center vectors

calculated from U. (d) U iteratively updated based on cluster centers and m, stopping when the loss

function converges below a threshold. (e) Each sample assigned to the cluster with the highest

membership probability in U.

694
Supplementary Fig. 3. Evaluation of five clustering evaluation indicators for optimal *K* selection
on simulated datasets when *K* varies from 3 to 6.

Simulated datasets comprise $K=3\sim6$ and $M_f=1{,}000$, 5,000, and 10,000, with fixed $N=500$ and $M_f=1{,}000$.

The optimal K values are evaluated by five indicators: Silhouette Coefficient, Davis Bouldin Index,

Elbow method, Separation index and Compactness index.

Supplementary Fig. 4. Feature gene identification by ERFM.

(a) Input multi-omics data with corresponding clustering results or sample labels. (b) Preliminary gene

filtering based on the Gini index. Genes with values exceeding the mean across all omics are retained.

(c) Construction of the ERFM adapted for three-dimensional matrix. Gene importance is quantified by

the reduction in classification accuracy following simultaneous randomization of all omics types for each

gene. The computational procedure iterates until all genes have positive importance values. (d) Final

feature-gene scoring, in which importance values are standardized and significant differences across

clusters are evaluated using the Wilcoxon rank-sum test (see details in Methods).

COAD

Supplementary Fig. 5. Kaplan-Meier survival analysis on TCGA COAD dataset clustered by different algorithms across various omics combinations.

The log-rank test was used to assess the statistical significance between survival curves. Abbreviations: CNV, copy number variation; Ex, gene expression; Me, DNA methylation.

Supplementary Fig. 6. Kaplan-Meier survival analysis on TCGA LUAD dataset clustered by different algorithms across various omics combinations.

The log-rank test was used to assess statistical significance between survival curves. Abbreviations: CNV, copy number variation; Ex, gene expression; Me, DNA methylation.

Supplementary Fig. 7. Kaplan-Meier survival analysis on TCGA LIHC dataset clustered by
different algorithms across various omics combinations.

The log-rank test was used to assess statistical significance between survival curves. Abbreviations: CNV,
copy number variation; Ex, gene expression; Me, DNA methylation.

Supplementary Fig. 8. Kaplan-Meier survival analysis on TCGA GBM dataset clustered by different algorithms across various omics combinations.

The log-rank test was used to assess statistical significance between survival curves. Abbreviations: CNV, copy number variation; Ex, gene expression; Me, DNA methylation.

**Supplementary Fig. 9. Kaplan-Meier survival analysis on TCGA LGG dataset clustered by
different algorithms across various omics combinations.**

The log-rank test was used to assess statistical significance between survival curves. Abbreviations: CNV,
copy number variation; Ex, gene expression; Me, DNA methylation.

734
Supplementary Fig. 10. Kaplan-Meier survival analysis on TCGA BLCA dataset clustered by
different algorithms across various omics combinations.

737 The log-rank test was used to assess statistical significance between survival curves. Abbreviations: CNV,
738 copy number variation; Ex, gene expression; Me, DNA methylation.

739
Supplementary Fig. 11. Kaplan-Meier survival analysis on TCGA BRCA dataset clustered by
different algorithms across various omics combinations.

The log-rank test was used to assess statistical significance between survival curves. Abbreviations: CNV,
copy number variation; Ex, gene expression; Me, DNA methylation.

Supplementary Fig. 12. Kaplan-Meier survival analysis on TCGA CESC dataset clustered by different algorithms across various omics combinations.

The log-rank test was used to assess statistical significance between survival curves. Abbreviations: CNV, copy number variation; Ex, gene expression; Me, DNA methylation.

Supplementary Fig. 13. Kaplan-Meier survival analysis on TCGA HNSC dataset clustered by different algorithms across various omics combinations.

The log-rank test was used to assess statistical significance between survival curves. Abbreviations: CNV, copy number variation; Ex, gene expression; Me, DNA methylation.

Supplementary Fig. 14. Kaplan-Meier survival analysis on TCGA PRAD dataset clustered by different algorithms across various omics combinations.

The log-rank test was used to assess statistical significance between survival curves. Abbreviations: CNV, copy number variation; Ex, gene expression; Me, DNA methylation.

Supplementary Fig. 15. Enrichment of clinical records by different algorithms across ten cancer types.

Clinical records include Pathologic M, metastasis progression; Pathologic N, lymph node involvement; Pathologic T, tumor progression; Pathologic stage, overall disease stage.

Supplementary Fig. 16. Kaplan-Meier survival analysis of GBM classical subtypes.

The log-rank test was used to assess statistical significance between survival curves.

767
768 **Supplementary Fig. 17. Functional enrichment of 167 GBM feature genes.**

769 (a) Enrichment scores of 167 feature genes across tissues/systems. (b) Enrichment analysis of 167 feature
770 genes identified from multi-omics data. (c) Enrichment analysis of feature genes identified specifically
771 from multi-omics, expression, and methylation data, respectively.

Supplementary Fig. 18. Importance ranking of *LTBR* (a) and *GPD1* (b) identified from different omics combinations.

Feature genes identified by CNV (not shown) did not reach the threshold.

Supplementary Tables

Supplementary Table 1. Clustering performance evaluation using the Adjusted Rand Index (ARI) for different algorithms on simulated datasets.

Supplementary Table 2. Important features identified by different algorithms and their significance on simulated datasets.

Supplementary Table 3. Optimal *K* values and corresponding *p*-values for survival outcomes across different omics combinations on real datasets.

Supplementary Table 4. Sample clustering results generated by different algorithms on real datasets.

Supplementary Table 5. *P*-values for enrichment of clinical records across different algorithm clusters in ten cancer types.

Supplementary Table 6. GBM subtyping results with associated clinical information.

Supplementary Table 7. Summary of 167 GBM feature genes.

Supplementary Table 8. Importance ranking of feature genes across different omics combinations.

Supplementary Table 9. Sample clustering results of 167 feature genes in GSE211272, GSE113510, GSE100736 and GSE68029 datasets.

Supplementary Table 10. Associations between genes and chemotherapy drugs across different cancers.