PAPER

Scaling the PBWT for Long-Range Shared Ancestry Detection in Large Haplotype Panels

Uwaise Ibna Islam,[1] Davide Cozzi,[2] Travis Gagie,[3] Rahul Varki,[1]
Vincenza Colonna,[4,5,6] Erik Garrison,[4,5,6] Paola Bonizzoni[2] and Christina Boucher[1,*]

[1]Department of Computer and Information Science and Engineering,University of Florida,Gainesville, , FL, USA, [2]Department of Informatics, Systems and Communication,University of Milano–Bicocca,Milan, 20126, , Italy, [3]Faculty of Computer Science,Dalhousie University,Halifax, , NS, Canada, [4]Department of Genetics, Genomics and Informatics,University of Tennessee Health Science Center (UTHSC),Memphis, , TN, USA, [5]Institute of Genetics and Biophysics,National Research Council,Naples, 80111, , Italy and [6]Department of Pediatrics,University of Tennessee Health Science Center (UTHSC),Memphis, , TN, USA

[*]Corresponding author. christinaboucher@ufl.edu

Abstract

Detecting long shared ancestry tracts in large haplotype panels is central to IBD analysis, imputation, and local ancestry inference, and can be approximated computationally by finding Set-Maximal Exact Matches (SMEMs) between sequences. The Positional Burrows–Wheeler Transform (PBWT) provides an efficient index for these panels, yet current methods often enumerate all SMEMs, producing a large number of short, uninformative matches. We introduce Positional Boyer–Moore–Li (PBML), which restricts enumeration to SMEMs occurring in at least k haplotypes and spanning at least L sites (kL-SMEMs). PBML is the first algorithm for computing KL-SMEMs on top of a single compressed run-length encoded PBWT index reusable for any (k, L) without rebuilding. On the 1000 Genomes Project, PBML achieves $4.6\times$ faster query time than μ-PBWT and $2.4\times$ over Durbin's PBWT with lower memory, scaling to $15.9\times$ over μ-PBWT at 16 threads. On a 10,000-haplotype panel from the Tennessee BIG Initiative, a diverse admixed cohort, PBML outperforms μ-PBWT by up to $4.7\times$ in k-SMEM finding. By applying both thresholds during traversal, PBML extracts biologically informative, population-shared segments while filtering millions of short matches, a capability not available in current tools. On the BIG panel, in about 10 seconds PBML finds 2,441 long tracts at ($k = 50, L = 5000$) shared by an average of 60 haplotypes against 1000 queries, significantly reducing the 4.8 million unfiltered SMEMs shared on average by 2 haplotypes. These results establish PBML as a scalable tool for targeted long-range shared ancestry detection in large, diverse panels.

Key words: Positional Burrows–Wheeler Transform (PBWT), set-maximal exact matches (SMEMs), Identity-by-Descent (IBD), Population Genomics, Pangenomics, Run-length encoding, Phased haploytpes, Shared ancestry

Introduction

By preserving phase at the chromosome scale, haplotype-resolved assemblies allow for precise mapping of admixture tracts [24, 7], elucidation of disease genetics [22, 13], estimation of homozygosity [23], and inference of local ancestry [36]. In line with this, several large-scale efforts are generating haplotype-resolved assemblies, including the UK Biobank [18], the Mexican Biobank [32], TOPMed [33], and All of Us [1]. To index and search these large panels efficiently, the Positional Burrows–Wheeler Transform (PBWT) provides a phase-aware representation. Originally proposed by Durbin [12], the PBWT stores a set of h sequences with w variant sites as an $h \times w$ binary matrix $S[1 \ldots h][1 \ldots w]$, with rows maintained in co-lexicographic order. For a given haplotype panel, it supports efficient querying and haplotype matching in $O(hw)$ time, and has been applied to haplotype phasing [6, 19], haplotype estimation [11], genotype imputation [30], genome database search [28], ancestry inference [35], and Identity-By-Descent (IBD) segment detection [25, 37, 14, 32]. Reflecting the central role of the PBWT in haplotype indexing and matching, recent work has focused on compressing the structure, extending its functionality, and accelerating support for various query types [28, 27, 26, 34].

A unifying formulation underlying many of these applications is the detection of shared inheritance between individuals in a PBWT panel. This can be cast as the problem of finding all set maximal exact matches (SMEMs) between a query sequence and the haplotype panel, where a SMEM is the longest subsequence shared between the query and at least one sequence represented in the PBWT. The seminal PBWT includes an algorithm for locating SMEMs [12], and subsequent work has optimized SMEM discovery using run-length encoding, sampling, and parallelism to achieve fast, memory-efficient haplotype matching [9, 31]. A remaining challenge is to

restrict the search space, as enumerating all SMEMs often yields an extremely large number of short matches that inflate downstream analysis [15, 5]. To address this, previous work has been extended to consider SMEMs that occur at least k times in the panel, termed k-SMEMs [3].

Here, we further focus on k-SMEMs of length at least L, which we call kL-SMEMs: matches that occur in at least k panel haplotypes and span at least L sites. This restriction greatly reduces the number of reported matches while retaining those that are most useful in practice. To solve this problem, we introduce PBML (Positional Boyer-Moore-Li), a space- and time-efficient algorithm to find all kL-SMEMs. Conceptually, PBML builds on the Boyer-Moore-Li (BML) algorithm, which combines Li's forward–backward MEM-finding strategy with Boyer-Moore-style skipping via Longest Common Prefix (LCP) and Longest Common Suffix (LCS) queries on the PBWT index [20, 4, 15, 21]. In particular, PBML skips right along the query haplotype and then extends matches leftward on run-length encoded forward and reverse PBWTs, enabling efficient length-constrained k-SMEM enumeration. Crucially, a single prebuilt index supports queries at any combination of k and L without rebuilding, enabling rapid exploration of the (k, L) parameter space.

We evaluated PBML on the 1000 Genomes Project (1KGP, 5,008 haplotypes) and on a 10,000 haplotype panel from the Tennessee BIG Initiative [8], a diverse Mid-South cohort with substantial African American representation. On 1KGP, we benchmark against existing PBWT-based methods and show that PBML achieves the fastest query time with the lowest memory among compressed indexes, with strong multi-threaded scaling due to a shared read-only index. On BIG, we demonstrate that a single prebuilt PBML index dominates μ-PBWT [3] across a sweep of k values in k-SMEM finding, avoiding the repeated index construction that μ-PBWT [3] requires for each threshold. We then show that increasing the minimum SMEM length L provides output-sensitive speedups while retaining over 95% site coverage at moderate thresholds, and that combining both parameters yields biologically targeted output: simultaneous (k, L) filtering isolates long, recurrently shared tracts characteristic of IBD segments, reducing millions of uninformative matches to a compact set of high-confidence candidates in seconds. The source code for PBML is publicly available at https://github.com/uwaiseibna/PBML.git.

Preliminaries

Representation of haplotypes. We represent phased haplotype data as a binary matrix $S \in \{0, 1\}^{h \times w}$, where each of the h rows corresponds to a haplotype and each of the w columns corresponds to a biallelic variant site ordered along the genome. An entry $S[i, j]$ is equal to 0 if the haplotype i carries the reference allele at the site j, and 1 if it carries the alternate allele. For each column j, we write 0_j for the number of 0-bits in column j.

We note that we use 0-based indexing throughout, so rows are indexed $0, \ldots, h-1$ and columns are indexed $0, \ldots, w-1$.

Forward PBWT. PBWT [12] is a data structure for storing and querying a haplotype panel $S \in \{0, 1\}^{h \times w}$. For each column $j \in \{0, \ldots, w-1\}$, the PBWT maintains a permutation a_j of $\{0, \ldots, h-1\}$, called the *prefix array*, which orders the haplotypes by the co-lexicographic order of their prefixes up to column $j-1$. Formally, $a_j[i]$ is the index of the ith haplotype

Fig. 1. Worked example ($h = 8$, $w = 8$). **(a)** S with query Q and SMEMs shaded. **(b)** Forward PBWT P, rows ordered by a_j (subscripts show $a_j[i]$), runs shaded with counts r_j below, blue boxes tracing LCP interval $[s, e]$ from column 0, orange bars tracking PBWT interval: $\{h_1, h_2\}$ across columns, and RLE representation of column 0 at bottom.

in the ordering obtained by sorting the prefixes $S[0, 0..j-1], S[1, 0..j-1], \ldots, S[h-1, 0..j-1]$ in co-lexicographic order, i.e., lexicographic order when comparing prefixes from right to left (from position $j-1$ down to 0). Because each column refines the previous ordering via a stable partition according to the current column, haplotypes sharing a common prefix remain contiguous as j increases.

The PBWT matrix $P \in \{0, 1\}^{h \times w}$ is defined by permuting each column of S according to the corresponding prefix array. Specifically, at column 0 the prefix is empty, so a_0 is the identity permutation and $P[i, 0] = S[i, 0]$. For $j \geq 1$, $P[i, j] = S[a_j[i], j]$. We refer to this as the forward PBWT to distinguish it from the reverse PBWT defined below.

Reverse PBWT. The reverse PBWT is defined analogously by processing the panel right-to-left (equivalently, by applying the PBWT to the column-reversed panel). It maintains, for each column j, a permutation a_j^{rev} that orders haplotypes by the co-lexicographic order of their suffixes starting at column $j+1$. The reverse PBWT matrix $P^{\text{rev}} \in \{0, 1\}^{h \times w}$ is defined by permuting each column of S according to a_j^{rev}, with $P^{\text{rev}}[i, w-1] = S[i, w-1]$ and, for $0 \leq j \leq w-2$, $P^{\text{rev}}[i, j] = S[a_j^{\text{rev}}[i], j]$.

RLE-PBWT. A *run* in column j of P is a maximal block of consecutive identical bits in that column. We write r_j for the number of runs in column j and $r = \sum_j r_j$ for the total number of runs in all columns. Thus, we refer to run-length encoding (RLE) as the representation of a PBWT column as a sequence of its runs, storing for each run its length and starting bit of each column.

PBWT intervals. As a consequence of stable refinement as j increases, haplotypes sharing a common prefix (or suffix, in the reverse PBWT) occupy a contiguous interval $[s, e]$ in the prefix array. Given a query $Q \in \{0, 1\}^w$ and a starting column c, the set of haplotypes matching with a match length ℓ, $Q[c..c+\ell-1]$ can be computed by iteratively refining an initial interval $[0, h-1]$ while scanning successive columns of the PBWT.

LCP and LCS. Both *Longest Common Prefix (LCP)* and *Longest Common Suffix (LCS)* queries operate directly on the run-length–encoded PBWT columns, where each column j stores its starting bit, the run lengths, and the number of zeros 0_j. Let $Q[0..w-1]$ be the query haplotype. During a Longest Common Prefix query starting at column c, we maintain a PBWT interval $[s, e]$ containing exactly the haplotypes that match the current query prefix, initialized to $[0, h-1]$. At each

column, we use rank queries to count how many 1-bits occur before and within this interval; these counts determine how the interval is mapped into the next column, either into the block of 0s or the block of 1s, depending on the query bit. The extension stops when fewer than k haplotypes remain in the interval or when we reach the query boundary (column $w - 1$ for LCP, column 0 for LCS). The LCP query returns the match length ℓ, the final interval $[s, e]$, and the haplotype index $a_j[e]$ at the upper boundary of this interval, tracked throughout the extension for later retrieval of all matching haplotypes.

SMEMs. Given a panel $S \in \{0, 1\}^{h \times w}$ and a query $Q \in \{0, 1\}^w$, we define a SMEM is a substring $Q[i..j]$ with $0 \leq i \leq j < w$ such that: (1) there exists at least one haplotype $s \in S$ such that $s[i..j] = Q[i..j]$, and (2) the match is maximal with respect to the extension in either direction, i.e., no $s \in S$ satisfies $s[i - 1..j] = Q[i - 1..j]$ when $i > 0$, and no $s \in S$ satisfies $s[i..j + 1] = Q[i..j + 1]$ when $j < w - 1$.

Next, we define a k-SMEM a SMEM that occurs at least k haplotypes in S contain the match, and a kL-SMEM as a k-SMEM of length at least L.

Methods

This section describes how PBML computes kL-SMEMs on the RLE-PBWT, and how we recover matching haplotypes efficiently. In particular, we first describe how to perform LCP and LCS queries directly on RLE-PBWT, which form the core primitive for matching a query haplotype against the panel. We then show how to combine them to enumerate all k-SMEMs of length $\geq L$ with Boyer-Moore-Li. After computing the interval of matching haplotypes, we give an algorithm to recover them. Lastly, we give the complexity analysis of PBML.

LCP and LCS Queries on the RLE-PBWT

Both LCP and LCS queries operate on RLE columns, where each column j stores its starting bit, run lengths, and zero-count (i.e., 0_j). We let $Q[0 .. w-1]$ be the query haplotype. During an LCP query starting at column c, we maintain a PBWT interval $[s, e]$ representing haplotypes matching the current prefix. The interval $[s, e]$ is initialized to $[0, h-1]$. Then at each column j, we compute rank values $r_s = \text{rank}_1(s-1, j)$ and $r_e = \text{rank}_1(e, j)$, and update the interval based on query bit $Q[j]$:

$$[s', e'] = \begin{cases} [s - r_s, \ (e+1) - r_e - 1] & \text{if } Q[j] = 0 \\ [0_j + r_s, \ 0_j + r_e - 1] & \text{if } Q[j] = 1 \end{cases}$$

The extension ends when fewer than k haplotypes remain (i.e., $s' + k > e' + 1$) or the query boundary is reached, i.e., column $w - 1$ for LCP, and column 0 for LCS. LCP returns the match length ℓ, the final interval $[s, e]$, and the haplotype index $a_j[e]$ at the boundary of the final interval, tracked during extension for subsequent haplotype retrieval.

LCS queries apply the same interval-narrowing procedure on the reverse RLE-PBWT, processing columns from c toward 0, returning only the match length ℓ since haplotype retrieval only requires the RLE forward PBWT.

Both queries run in $O(r)$-time. Full algorithmic details appear in Supplementary Section B.

Boyer–Moore–Li in the PBWT

Given the query haplotype $Q[0..w - 1]$ and integers L and k, we now describe how to compute all kL-SMEMs between the PBWT and the query haplotype Q. We note that any SMEM of length at least L whose start lies in $Q[0..L - 1]$ must include position $Q[L - 1]$. Consequently, we initiate the search at $Q[L - 1]$ and match from right-to-left using an LCS query on the reverse RLE-PBWT, updating the interval at each step until fewer than k haplotypes remain at position $Q[i]$. At this point, there are two cases depending on the position i at which the match ends.

If $i = 0$, the backward extension reaches the beginning of Q. We then extend the current interval forward from $Q[0]$ via an LCP query on the forward RLE-PBWT, which proceeds through column $p-1$ before fewer than k haplotypes remain at column p, producing the first SMEM $Q[0..p-1]$. To find the next SMEM, the algorithm checks whether any SMEM of length $\geq L$ covers position p. It performs a backward extension from $Q[p]$ of length ℓ. If $\ell \geq L$, the corresponding forward extension yields the next SMEM. If $\ell < L$, no SMEM of length $\geq L$ can cover $Q[p]$, and moreover the first $L - \ell$ positions starting at p cannot begin such an SMEM either. The algorithm skips past them, analogous to the shift rule in Boyer–Moore, and continues from position $Q[p + L - \ell]$.

Otherwise, we know that $i \geq 1$ and it follows that there does not exist any SMEM of length at least L begins in $Q[0..i-1]$. We therefore recurse on the suffix $Q[i..w-1]$, starting at $Q[i+L-1]$.

The recursion ends once the remaining suffix has length less than L. We note that when $L = 1$, the procedure simplifies to the standard forward-backward algorithm. We give the pseudocode in Supplementary Section A.

Identifying Matching Haplotypes

To obtain the haplotypes in the interval $[s, e]$ produced by an LCP query, we require access to the prefix array at the corresponding columns. However, storing the complete prefix array for all columns is memory-prohibitive for large panels. Instead, PBML adapts the Toehold Lemma and ϕ predecessor operation from the r-index [16, 29] to recover the haplotypes, which removes the necessity of storing the full prefix arrays.

We first show how to recover the haplotypes using ϕ. Given PBWT column j, ϕ query on ith haplotype of prefix array $a_j[i]$, returns the previous haplotype in the prefix array, $a_j[i - 1]$; $\phi(a_j[i]) = a_j[i - 1]$. During an LCP query starting at column c, we maintain the haplotype $a_j[e]$ at the interval endpoint e as the interval narrows across successive columns. When extending from column j to column $j+1$, if the bit at position e in column j matches the query bit $Q[j]$ then the same haplotype remains at the updated endpoint e' in column $j + 1$. Otherwise, the interval endpoint moves to the previous run in the PBWT column, and we update the haplotype to the one at the end of the preceding run via a ϕ query. By the end of the LCP query, we have identified the haplotype at the final interval endpoint without accessing the full prefix array.

Given this tracked haplotype and the final interval $[s, e]$, we enumerate all matching haplotypes by repeatedly applying ϕ: starting from $a_j[e]$, we compute its co-lexicographic predecessor in the prefix array, then the predecessor of that, and so on, until we have traversed the entire interval. This recovers all $e - s + 1$ haplotype identities without materializing the prefix array.

To support ϕ efficiently, PBML maintains two auxiliary structures. The first is a per-haplotype *successor structure* that stores, for each haplotype, the PBWT columns where it starts a run, the haplotype immediately preceding it in the prefix array at each such column, and a pointer into that predecessor's successor structure indicating the closest later column where

the predecessor also began a run. The second is a per-run *run-sampled structure* that stores each run's starting row offset, the haplotype index at the run start, and a pointer into the corresponding successor structure. Each column additionally stores the index of its first run for direct access. Full details are provided in Supplementary Section C.

Complexity Analysis

We analyze PBML for a single query against a panel of h haplotypes over w sites. Let r denote the total number of runs across the forward and reverse run-length encoded PBWTs. Because PBML operates directly on the RLE-PBWT, both the index size and query cost depend on the number of runs rather than the full panel size. In large biobank datasets, long shared haplotype segments often make r much smaller than hw, enabling compact storage and efficient rank queries. During matching, PBML performs forward and backward extensions using LCP and LCS queries.

The efficiency of PBML is summarized by the following theorem. We give the proof of this Theorem in Supplementary Section D.

Theorem 1 *Given integers k and L, a query $Q \in \{0,1\}^w$, and a panel S of h haplotypes over w sites, PBML finds all kL-SMEMs in S in $O(r)$-space and $O(N_{vis}r + occ)$-time, where N_{vis} is the total number of columns visited, and occ is the number of kL-SMEMs occurrences in S.*

In practice, the threshold L allows PBML to skip positions that cannot begin a valid match, reducing the number of visited columns and improving runtime, especially when long matches are sparse.

Results

Experimental setup

PBML is implemented in C++17 using SDSL [17] for bit vectors, OpenMP for multi-threaded queries, and htslib [2] for VCF/BCF parsing. The experiments were run on an AMD EPYC 75F3 32-Core Processor with 503 GB RAM, Red Hat Enterprise Linux 9, and g++ 11.5.0. Running time and peak memory were measured with /usr/bin/time -v. We compared PBML to μ-PBWT [9], dynamic μ-PBWT [31], and PBWT^{orig} [12] by recording the construction time, peak memory, and query time.

Datasets

We evaluated on two datasets. The first consists of panels from the 1,000 Genomes Project (1KGP) Phase 3: 2,504 individuals (5,008 haplotypes), filtered to biallelic SNPs using bcftools [10], with 1 to 6 million variants per chromosome. For each experiment, 1,000 haplotypes serve as queries and the remaining 4,008 as the reference panel.

The second dataset consists of the BIG data [8], a multi-institutional resource from a diverse mid-south population with substantial African American representation from Memphis: 5,500 individuals (11,000 haplotypes), phased with ShapeIT5 [19] with variant sites 0.9 million to 4.4 million per chromosome. Similarly to the 1KGP dataset, we use 1,000 haplotypes as queries and the remaining 10,000 haplotypes as the reference panel.

Enumerating SMEMs in the 1KGP Data

Figure 2 summarizes single-threaded performance across all 22 autosomes. Build and query times are normalized per million variant sites (Table inside Figure 2); per-chromosome trends are shown in Figures 2 and Supplementary section F (multi-thread). PBWT^{orig} achieves the fastest construction (1.6× faster than PBML), but is not compressed. Among compressed methods, PBML constructs 1.4 times faster than μ-PBWT and 5 times faster than dynamic μ-PBWT.

For 1,000 queries, PBML achieves the fastest query time, which is 4.6× faster than μ-PBWT and 2.4× faster than PBWT^{orig}. This advantage stems from the forward-backward algorithm, which resolves each SMEM through a single LCS-LCP pair rather than scanning the full query to compute matching statistics, and from Boyer-Moore skipping, which avoids revisiting sites already covered by a previously reported SMEM. Moreover, the peak memory of PBML is 23% lower than μ-PBWT and 96% lower than PBWT^{orig}.

We analyze multi-thread (16 threads) performance in Supplementary section F (PBWT^{orig} and dynamic μ-PBWT are excluded because they do not support multi-threading). PBML achieves 8.2× speedup with near-constant memory (an average increase of 0.6%), because all threads share a single read-only index and allocate only thread-local output buffers. In contrast, μ-PBWT achieves a 2.4× speedup with a 15.9% memory increase due to per-thread matching statistics. At 16 threads, PBML queries 15.9× faster than μ-PBWT while using 1.5× less memory.

Enumerating k-SMEMs in the BIG Dataset

In biobank data, many SMEMs that occur only once or a few times correspond to private or near-private mutations and provide little value for downstream analyses. Hence, requiring each SMEM to occur in at least k panel haplotypes filters these rare matches and retains only those supported by recurrent sharing across the cohort. We evaluate this on BIG chromosome 22 (10,000 haplotypes, 893,511 sites, 1,000 queries, single-threaded). Here, we set $L = 1$, allowing k-SMEMs to have arbitrary length.

	PBML		μ-PBWT	
k	Time (s)	Mem (GB)	Time (s)	Mem (GB)
1	**590**	**2.8**	736	3.8
5	**827**	**2.5**	1,531	4.4
10	**861**	**2.5**	2,067	4.9
50	**912**	**2.5**	3,524	7.6
100	**979**	**2.5**	4,572	11.1

Table 1. k-SMEM query performance on BIG chromosome 22. PBML uses a prebuilt index (141.5 seconds build, mean 3.8 seconds load time); whereas μ-PBWT [3] rebuilds index from panel per k, incurring a mean build time of 759.7 seconds.

Table 1 shows that PBML is faster for every value of k, the advantage increasing from 1.2× to 4.7× as k increases from 1 to 100. In this range, the runtime of μ-PBWT [3] increases by a factor of 6.2, while PBML increases by a factor of 1.7. A key design advantage is index reuse: PBML builds the index once and then answers queries repeatedly, whereas μ-PBWT [3] rebuilds the index for each k, accumulating over 3,500 seconds of redundant construction time. In addition, the memory usage of PBML remains constant at 2.5GB for all values of k greater than 1. The slightly higher usage when k equals 1 (2.8 GB) reflects the per-haplotype output format used in the default

Fig. 2. Single-threaded performance across all 22 autosomes of the 1000 Genomes Project (1KGP) panel. Per-chromosome (a) index construction time, (b) total query time for 1,000 haplotypes, and (c) peak memory usage are shown for PBML, μ-PBWT, dynamic μ-PBWT, and PBWT$^{\mathrm{orig}}$ (times normalized per million variant sites). The table summarizes median (min–max) build time, query time, and peak memory across chromosomes (1KGP, $L = 1$, 1,000 queries), with best values in **bold**.

Method	Build time (s/M sites)	Query time (s/M sites)	Peak Memory (GB)
PBML	45.19 (43.86–46.12)	**49.08** (44.86–67.42)	**6.4** (2.4–12.4)
μ-PBWT	63.76 (62.72–65.88)	233.90 (200.48–276.75)	9.1 (2.8–17.4)
dynamic μ-PBWT	212.45 (203.46–351.44)	582.28 (485.38–756.82)	24.2 (9.4–46.0)
PBWT$^{\mathrm{orig}}$	**20.20** (14.95–20.60)	121.75 (113.36–135.03)	176.2 (52.3–336.2)

Fig. 3. Effect of minimum SMEM length threshold (L) on chromosome 22 for the 1KGP (4,008 haplotypes, solid) and BIG (10,000 haplotypes, dashed) panels. (a) Query time decreases with L as fewer SMEMs are enumerated. (b) SMEM count on log scale. (c) Coverage (fraction of query sites spanned by ≥ 1 SMEM) for 1, 5, and 20 aggregated query haplotypes; the vertical line marks $L = 500$.

case, whereas for all other values of k we output a single line per SMEM with all matching haplotypes listed. In contrast, the memory usage of μ-PBWT [3] increases from 3.8 GB to 11.1 GB when $k = 100$ for identical output format.

Investigating the Effect of L

Next, we evaluate the effect of the minimum SMEM length threshold L on chromosome 22 for both the 1KGP and BIG panels at $k = 1$ (Figure 3). We define *coverage* as the fraction of variant sites in a query haplotype spanned by at least one reported SMEM; when aggregating multiple queries, we take the union of all SMEMs before computing this fraction.

In 1KGP, increasing L reduces the number of SMEMs, from 21.1 million at $L = 1$ to 5.3 million at $L = 500$, and further

to 7,674 at $L = 10,000$. The query time decreases accordingly, from 60.3 seconds to 10.2 seconds (about an 83% reduction). The coverage at $L = 500$ is 96.9% for a single query and 99.8% when aggregating five. Increasing L reduces query time and maintains high coverage at moderate L values (Supplementary section H).

In BIG, the effect is more pronounced due to the larger panel and the higher density of short matches. The SMEM count decreases from 10.2 million in $L = 1$ to 4.9 million in $L = 500$ and to 14,283 in $L = 5,000$, yielding a 37$\times$ reduction in the query time (590 to 16 seconds). At $L = 500$, BIG retains 95.5% single-query coverage and 99.4% when aggregating five queries, despite a 53% reduction in SMEM count. Compared to 1KGP, coverage degrades more steeply at the same L because the larger

Fig. 4. kL-SMEMs across all BIG autosomes (10,000 haplotypes, 1,000 queries, single-threaded). (a) Each point represents one chromosome under one (k, L) configuration, plotted by mean SMEM length (x-axis) and mean haplotypes per SMEM (y-axis). (b) Per-chromosome query time comparing the unfiltered baseline ($k = 1, L = 1$) with the IBD-focused configuration ($k = 50, L = 5,000$).

panel generates more short matches whose removal impacts site coverage more substantially.

In both panels, moderate values of L (e.g., 500 to 1,000) provide a favorable tradeoff between coverage and computational savings. However, L alone cannot distinguish long private matches from long shared matches; combining L with a minimum frequency threshold k addresses this limitation.

Enumerating kL-SMEMs in the BIG Dataset

The preceding sections evaluate k and L independently and show that increasing k excludes rare SMEMs while increasing L excludes short ones. Yet neither parameter alone identifies SMEMs that are both long and widely shared. For example, setting $k = 1$ and $L = 5,000$ on chromosome 22 yields 8,983 long SMEMs (mean length 6,179), but each is shared by only 1.6 haplotypes on average, likely uninformative for downstream analyses such as IBD detection. Conversely, $k = 50$ with $L = 1$ produces 9.8M SMEMs shared across 91.4 haplotypes on average, but with a mean length of only 440.

PBML applies both thresholds simultaneously on a single reusable prebuilt index. Figure 4 evaluates all nine (k, L) combinations with $k \in \{1, 10, 50\}$ and $L \in \{1, 500, 5000\}$ across all 22 autosomes of the BIG panel. Panel 4(a) plots mean SMEM length against mean haplotypes per SMEM for each chromosome under each (k, L) configuration. The nine configurations separate into distinct clusters that reveal the complementary roles of the two parameters: increasing L shifts clusters rightward (longer SMEMs) while increasing k shifts them upward (more widely shared). Only the $(k = 50, L = 5,000)$ cluster occupies the upper-right region, corresponding to long, recurrently shared tracts characteristic of IBD segments. On chromosome 22, this configuration yields 2,441 SMEMs with a mean length of 5,815 shared by 58.5 haplotypes, compared with 4.8 million short, mostly private SMEMs at $(k = 1, L = 1)$. The tight within-cluster grouping of all 22

chromosomes confirms that these filtering characteristics are consistent genome-wide.

Panel (b) shows the corresponding query times. IBD-focused threshold ($k = 50, L = 5,000$) reduces the genome-wide query time from 25,806 seconds ($\sim$7.2 hours) to 1,642 seconds ($\sim$27 minutes), a 15.7$\times$ speedup driven by a 1,050$\times$ reduction in output size (221.5M to 211K SMEMs). Per-chromosome speedups range from 10.8$\times$ to 59.0$\times$ (median 16.0$\times$). The full per-chromosome characterization of haplotype sharing across all configurations is provided in Supplementary section G.

Conclusion

By building a single $O(r)$-space index that supports queries in any combination of k and L without rebuilding, PBML shifts the SMEM enumeration from exhaustive listing to targeted extraction: the user specifies what constitutes a biologically meaningful match and the algorithm delivers only those. This is particularly relevant for applications such as IBD detection and haplotype imputation, where short or private matches are noise and the segments of interest are both long and recurrently shared across the panel. No prior method supports both of these parameterizations. Future work includes validating detected segments against recombination maps through integration with local-ancestry inference pipelines, and extending the algorithm to multi-allelic and graph-based PBWT representations to support structurally complex variation.

Acknowledgements

We gratefully acknowledge the Tennessee Biorepository and Integrative Genomics (BIG) Initiative for providing access to the biobank data from the Mid-South population. We thank the participants, clinical staff, and investigators whose efforts made these data available.

References

1. All of Us Research Program Investigators. The "All of Us" research program. *New England Journal of Medicine*, 381(7):668–676, 2019.

2. J. K. Bonfield et al. HTSlib: C library for reading/writing high-throughput sequencing data. *GigaScience*, 10(2), 02 2021. giab007.

3. P. Bonizzoni, C. Boucher, D. Cozzi, T. Gagie, and Y. Pirola. Solving the Minimal Positional Substring Cover Problem in Sublinear Space. In *Proc. of CPM*, pages 12:1–12:16.

4. R. S. Boyer and J. S. Moore. A fast string searching algorithm. *Communications of the ACM*, 20(10):762–772, 1977.

5. N. K. Brown et al. KeBaB: k-mer Based Breaking for Finding Long MEMs. In *Proc of SPIRE*, pages 10–17, 2025.

6. B. L. Browning, X. Tian, Y. Zhou, and S. R. Browning. Fast two-stage phasing of large-scale sequence data. *The American Journal of Human Genetics*, 108(10):1880–1890, 2021.

7. S. R. Browning, R. K. Waples, and B. L. Browning. Fast, accurate local ancestry inference with flare. *The American Journal of Human Genetics*, 110(2):326–335, 2023.

8. S. Buonaiuto et al. Insights from the Biorepository and Integrative Genomics pediatric resource. *Nature Communications*, 16:4750, 2025.

9. D. Cozzi et al. μ-PBWT: a lightweight r-indexing of the PBWT for storing and querying UK Biobank data. *Bioinformatics*, 39(9):btad552, 2023.

10. P. Danecek et al. Twelve years of SAMtools and BCFtools. *GigaScience*, 10(2):giab008, 2021.

11. O. Delaneau, J. Zagury, M. Robinson, J. Marchini, and E. Dermitzakis. Accurate, scalable and integrative haplotype estimation. *Nature Communications*, 10:5436, 2019.

12. R. Durbin. Efficient haplotype matching and storage using the positional Burrows–Wheeler transform (PBWT). *Bioinformatics*, 30(9):1266–1272, 2014.

13. P. Ebert et al. Haplotype-resolved diverse human genomes and integrated analysis of structural variation. *Science*, 372(6537):eabf7117, 2021.

14. W. A. Freyman et al. Fast and robust identity-by-descent inference with the templated positional burrows–wheeler transform. *Molecular Biology and Evolution*, 38(5):2131–2151, 2021.

15. T. Gagie. How to find long maximal exact matches and ignore short ones. In *Proc of DLT*, pages 131–140, 2024.

16. T. Gagie, G. Navarro, and N. Prezza. Optimal-time text indexing in BWT-runs bounded space. In *Proc. of SODA*, pages 1459–1477. SIAM, 2018.

17. S. Gog, T. Beller, A. Moffat, and M. Petri. From theory to practice: Plug and play with succinct data structures. In *Proc. of SEA*, pages 326–337, 2014.

18. B. V. Halldorsson et al. The sequences of 150,119 genomes in the UK Biobank. *Nature*, 607(7920):732–740, 2022.

19. R. J. Hofmeister, D. M. Ribeiro, S. Rubinacci, and O. Delaneau. Accurate rare variant phasing of whole-genome and whole-exome sequencing data in the UK Biobank. *Nature Genetics*, 55:1243–1249, 2023.

20. H. Li. Exploring single-sample SNP and INDEL calling with whole-genome de novo assembly. *Bioinformatics*, 28(14):1838–1844, 2012.

21. H. Li. BWT construction and search at the terabase scale. *Bioinformatics*, 40(12):btae717, 2024.

22. W.-W. Liao et al. A draft human pangenome reference. *Nature*, 617(7960):312–324, 2023.

23. I. M. MacLeod et al. Inferring Demography from Runs of Homozygosity in Whole-Genome Sequence, with Correction for Sequence Errors. *Molecular Biology and Evolution*, 30(9):2209–2223, 2013.

24. B. K. Maples, S. Gravel, E. E. Kenny, and C. D. Bustamante. RFMix: A Discriminative Modeling Approach for Rapid and Robust Local-Ancestry Inference. *The American Journal of Human Genetics*, 93(2):278–288, 2013.

25. A. Naseri, E. Holzhauser, D. Zhi, and S. Zhang. Efficient haplotype matching between a query and a panel for genealogical search. *Bioinformatics*, 35(14):i233–i241, 2019.

26. A. Naseri, W. Yue, S. Zhang, and D. Zhi. Efficient haplotype block matching in bi-directional PBWT. In *Proc of WABI*, pages 19–1, 2021.

27. A. Naseri, D. Zhi, and S. Zhang. Multi-allelic positional burrows-wheeler transform. *BMC bioinformatics*, 20(Suppl 11):279, 2019.

28. A. M. Novak, E. Garrison, and B. Paten. A graph extension of the positional burrows–wheeler transform and its applications. *Algorithms for Molecular Biology*, 12(1):18, 2017.

29. A. Policriti and N. Prezza. Lz77 computation based on the run-length encoded bwt. *Algorithmica*, 80(7):1986–2011, 2018.

30. S. Rubinacci, R. J. Hofmeister, B. Sousa da Mota, and O. Delaneau. Imputation of low-coverage sequencing data from 150,119 uk biobank genomes. *Nature Genetics*, 55(7):1088–1090, 2023.

31. P. Shakya, A. Sanaullah, D. Zhi, and S. Zhang. Dynamic μ-PBWT: Dynamic Run-Length Compressed PBWT for Biobank Scale Data. In *Proc. of RECOMB*, pages 209–226, 2025.

32. M. Sohail et al. Mexican biobank advances population and medical genomics of diverse ancestries. *Nature*, 622(7984):775–783, 2023.

33. D. Taliun et al. Sequencing of 53,831 diverse genomes from the NHLBI TOPMed Program. *Nature*, 590(7845):290–299, 2021.

34. V. Wang, A. Naseri, S. Zhang, and D. Zhi. Syllable-pbwt for space-efficient haplotype long-match query. *Bioinformatics*, 39(1):btac734, 2023.

35. Y. Yang, R. Durbin, A. K. Iversen, and D. J. Lawson. Sparse haplotype-based fine-scale local ancestry inference at scale reveals recent selection on immune responses. *Nature Communications*, 16(1):2742, 2025.

36. J. Zhang and D. O. Stram. The role of local ancestry adjustment in association studies using admixed populations. *Genetic Epidemiology*, 38(6):502–515, 2014.

37. Y. Zhou, S. R. Browning, and B. L. Browning. A fast and simple method for detecting identity-by-descent segments in large-scale data. *The American Journal of Human Genetics*, 106(4):426–437, 2020.