Protein Diffusion Models as Statistical Potentials

James P. Roney
MIT Computational and Systems Biology
jamesron@mit.edu

Chenxi Ou
MIT Biology
chenxiou@mit.edu

Sergey Ovchinnikov
MIT Biology
so3@mit.edu

Abstract

Machine learning has driven rapid progress in protein structure prediction and design, but key challenges remain such as predicting protein structures when evolutionary information is unavailable, modeling full conformational landscapes, and capturing the thermodynamics of mutations and conformational changes. To address these problems we developed ProteinEBM, an Energy-Based Model of protein conformational space. ProteinEBM's energies can be used to rank protein structure correctness, predict the energetic effects of mutations, sample from protein conformational landscapes, predict protein structures, and simulate protein folding pathways. Across all of these tasks, ProteinEBM shows performance competitive with or exceeding previous machine learning and physics-based methods, including state-of-the-art performance at predicting the effects of mutations on protein stability.

1 Introduction

The use of machine learning has triggered a revolution in protein science and engineering, with AlphaFold often being described as a "solution" to the protein-folding problem [1]. In fact, many aspects of the problem are still open questions. For instance, AlphaFold succeeds at predicting structures for which Multiple Sequence Alignments (MSAs) contain sufficient coevolutionary signal to infer contacts, but protein structure prediction remains difficult when MSAs are shallow or nonexistent. This is a crucial limitation when designing novel proteins, and has constrained designed proteins to much simpler folds than those found in nature [2, 3]. AlphaFold also struggles to accurately predict the structural effects of mutations, since the coevolutionary signal only reflects the wildtype structure. In addition, modern ML methods cannot reliably predict the dynamical pathways by which proteins fold into their native structures. And while important progress has been made toward modeling protein conformational ensembles with machine learning, characterizing the conformational landscapes of proteins with high qualitative and quantitative accuracy, as well as designing proteins with finetuned conformational dynamics, are still open research problems.

A theoretically general solution to these outstanding challenges and others is the development of energy-based models that characterize protein conformational landscapes, as well as efficient samplers for optimizing structures and simulating dynamics from these EBMs. More concretely, energy-based models aim to approximate a function $E_\theta(x, s)$ over protein structures x and sequences s such that

$$p(x|s) = \frac{1}{Z_{\theta,s}} \exp\left(-\beta E_\theta(x, s)\right)$$

Where $Z_{\theta,s}$ is a generally unknown normalizing constant. Thermodynamically, $E_\theta(x, s)$ is a free energy corresponding to a coarse-grained description of a protein conformational state x, integrating out degrees of freedom from the solvent and fine-grained conformational states. There is a rich and highly successful history behind the development of energy functions for proteins, including models based primarily on physical laws, as in the case of molecular dynamics, or a mix of physical terms and knowledge-based terms derived from the PDB, as in the case of potentials like Rosetta [4].

The power and flexibility of EBMs is illustrated by the breadth of their applications. Protein structure prediction corresponds to finding the minimum energy structure $x^* = \mathrm{argmin}_x E_\theta(x, s)$. Compared with models like AlphaFold, which predicts x^* in an end-to-end manner, the EBM formulation decouples prediction into the (easier) task of learning a discriminative energy function E_θ, followed by the application of an optimization procedure. While the optimization problem is highly nontrivial, the decoupled formulation has the advantage that the compute invested in optimization can be scaled arbitrarily at inference time in proportion to the difficulty of the prediction problem, whereas end-to-end models are fundamentally limited by the scale of the network.

EBMs can also be used to directly simulate coarse-grained protein motion via Langevin dynamics $m\ddot{x} = -\nabla_x E_\theta(x, s) - \gamma m\dot{x} + \sqrt{2\gamma m\beta}\eta(t)$. On top of this, EBMs allow for the approximation of free energy differences between conformational states, either by directly calculating energy differences $E_\theta(x_1, s) - E_\theta(x_2, s)$ or by employing enhanced sampling techniques like metadynamics or umbrella sampling. These energy differences encompass important quantities like folding stabilities and binding affinities, as well as the relative occupancies of alternative conformations. The ability to quickly estimate relative occupancies in a differentiable manner also holds great promise in protein design, since it allows sequences to be optimized for the adoption of specific energy landscapes. The breadth of EBMs' applications also allows them to be trained on diverse sources of data, including protein structures, forces from MD simulations, and experimental measurements of energy differences.

In this paper, we aim to combine the flexibility of EBMs with the expressivity of modern ML architectures. We introduce ProteinEBM, an energy-based model of protein structure and sequence. The architecture of ProteinEBM is inspired by recent advances in protein diffusion and is trained using denoising score matching, but unlike previous protein diffusion models, its learned score function is explicitly computed as the gradient of a learned energy. ProteinEBM's energy function shows robust performance across a number of tasks, including protein structure ranking, protein stability ranking, protein structure prediction, conformational sampling, and the prediction of folding pathways.

2 Preliminaries and Related Work

2.1 Molecular Dynamics

Molecular dynamics allows for the simulation of biomolecules with atomic resolution through the forward integration of Newtonian dynamics. The energy functions used to compute atomic forces in MD simulations are called force fields. Force fields are generally composed of simple harmonic and trigonometric terms that define the geometric constraints on bond lengths and angles, as well as electrostatic and dispersive forces mediated by Coulomb's law and Lennard-Jones potentials. The simplicity of these so-called "molecular mechanics" force fields allows for them to be computed extremely quickly, which is essential since MD simulations must run for billions of timesteps to reach useful timescales. Despite the relative simplicity of molecular mechanics force fields, MD simulations have yielded numerous important insights about the folding and function of biomolecules [5]. Recently, force fields parameterized by neural networks trained on reference quantum mechanical data have enabled simulations of some systems at far greater accuracy, but with even greater computational expense [6].

It is also possible to use machine learning to train coarse-grained models that match the average forces of all-atom simulations on a lower-dimensional representation of a system [7, 8]. This allows for faster simulation, since the coarse-grained energy landscape is significantly smoother. However, existing coarse-grained models trained using force matching require large datasets of MD frames to train, require bespoke prior potentials, and cannot learn from the wealth of experimental and predicted structures in the Protein Data Bank and AlphaFold Database.

2.2 Statistical Potentials

In the domain of protein modeling, there is a rich family of models that try to improve the accuracy of molecular mechanics potentials by explicitly incorporating terms derived from the empirical distributions of protein conformations found in the PDB. The most famous method to utilize these "statistical potential" terms is Rosetta, which has been successfully applied to a myriad of tasks in protein modeling and design [4]. In addition to conventional molecular mechanics terms and implicit

solvation terms, Rosetta has additional energies based on the Ramachandran distribution for the backbone torsions of each residue, as well as energies derived from the empirical distributions of sidechain rotameric states. Other statistical potentials include Upside, which implements a pairwise distance potential for each combination of two amino acids [9]. Upside was trained using contrastive divergence to minimize the energy of native protein structures relative to alternative samples.

Several papers have also developed creative statistical potentials using modern deep learning methods. Ingraham et al. trained a fully differentiable simulator to learn an energy function that attempts to reproduce experimental structures when optimized under Langevin dynamics [10]. While an impressive engineering feat, this meta-learning approach is computationally intensive and unstable without careful regularization, limiting scalability compared to the far simpler training paradigm of diffusion models. Yang et al. trained an autoregressive model on sequence-structure pairs, and used the model's structure likelihood as an energy function [11]. While their model has promising structure ranking capabilities, they did not demonstrate *ab initio* protein folding or structure prediction abilities. Du et al. trained a transformer-based EBM to calculate the energies of different sidechain rotameric states and achieved competitive results with Rosetta for rotamer packing accuracy, although their model is not applicable to general backbone conformations [12].

2.3 Energy-Parameterized Diffusion Models

Diffusion models have emerged as a leading class of generative models for sampling from complex distributions. These models define a forward noising process that converts samples from the data distribution into an invariant noise distribution:

$$dX = f(X,t)dt + g(t)dB_t$$

Where B_t is the standard Weiner process and $X_0 \sim p_{\text{data}}$ is drawn from the data distribution. By Anderson's theorem the reverse process is given by

$$dX = [f(X,t) - g(t)^2 \nabla_x \log p_t(X)]dt + g(t)B_t$$

Which converts samples from the noise distribution at $t = \infty$ into samples from p_{data} at $t = 0$ when integrated backward in time [13]. In a denoising diffusion model, the time-dependent score function $\nabla_x \log p_t(X)$ is approximated by a neural network. Tweedie's formula states that

$$\nabla_x \log p_t(x) = \frac{E[X_0|X_t = x] - x}{\sigma_t^2}$$

where σ_t^2 is the conditional variance of the distribution $p_t(X|X_0 = x_0)$. This provides a convenient means of training a neural network $s_\theta(x,t)$ to approximate the score function $\nabla_x \log p_t(x)$. While most diffusion models parameterize $s_\theta(x,t)$ as the direct output of a neural network, some authors have noted that is possible to parameterize the score as $s_\theta(x,t) = -\nabla_x E_\theta(x,t)$, where E_θ is a learned energy function, which can yield a number of advantages at the expense of increased computational demands from calculating second-order derivatives during training.

Du. et al. used energy-parameterized diffusion models to enable an MCMC-based correction of their diffusion sampler, which allowed them to achieve composability between multiple independent generative models [14]. Thornton et al. used energy-based diffusion models to facilitate composition and low-temperature sampling via MCMC correction, and also introduced various engineering improvements to the energy-training paradigm [15].

Arts. et al. trained an energy-parameterized diffusion model on MD simulations of proteins to act as a coarse-grained forcefield for specific systems [16]. They found the energy-based parameterization to be crucial for obtaining a model that recapitulates atomistic simulation results, since dynamical simulations require forces to be conservative in order to remain stable. Plainer et al. extended this approach with regularization to ensure the reverse diffusion process follows the Fokker-Plank equation, promoting consistency between reverse-diffusion sampling and Langevin dynamics [17]. Jin et al. and Chu et al. both developed energy-based diffusion models for docking pairs of interacting proteins, and showed that the learned energy functions are useful approximations of binding affinity and pose correctness [18, 19]. Concurrently to our work, Sarma et al. used the continuous-time change of variables formula to compute log probabilities from a rigid-docking diffusion model, and showed that they produced energy funnels similar to Rosetta [20]. While the approach is viable for the low-dimensional generative process of rigid docking, integrating the Jacobian trace for log probability computation quickly becomes intractable for higher-dimensional processes.

2.4 Conformational Ensemble Generation

Many recent models have aimed to generate samples that reflect the conformational heterogeneity of proteins. Several works have found that subsampling the input MSA to AlphaFold results in diverse structural outputs which can reveal alternative conformations [21, 22]. While highly useful, these alternative structure predictions do not come with any quantitative estimates of relative occupancy, and do not represent unfolded or partially unfolded states. Further, MSA subsampling works by weakening subsets of the evolutionary constraints present in the MSA to produce varied results, which is only effective when the starting coevolutionary signal is sufficiently strong.

Other transferable conformation generators like BioEmu and AlphaFlow have been trained on MD data, allowing them to capture more dynamics than MSA subsampling [23, 24]. These models are very useful tools for MD acceleration, but their lack of an explicit energy function means that there is no direct way of knowing which of their generated samples are more realistic and energetically favorable. Having an energy function built into the diffusion sampler allows us to rerank and resample the structures produced by reverse diffusion, guiding us toward favorable structures that may be sparsely populated by standard diffusion sampling. Compared to standard diffusion models, EBMs can also be used in arbitrary enhanced sampling protocols, like MCMC-corrected sampling and replica exchange between different models, while energy-free methods are limited to enhanced sampling schemes that use additive biasing potentials [25]. Finally, the energies from EBMs can be used to quickly and accurately predict quantities like stability differences, in contrast to models like BioEmu, which must draw thousands of independent samples to estimate free energy differences.

Boltzmann generators use normalizing flows to model conformational ensembles [26]. In theory, Boltzmann generators are the ideal method for ensemble modeling: They provide a normalized probability density (which is strictly more powerful than an energy), and can rapidly produce independent samples. In practice, however, the architectural constraints of normalizing flows have made it difficult to scale Boltzmann generators to large proteins, and most published models only generate small peptides [27]. We see EBMs as a middle ground that combine some of the capabilities of Boltzmann generators with more architectural flexibility.

2.5 Structure Scoring Methods

Several machine learning methods have been developed to assess the accuracy of candidate protein structures for a given sequence [28]. Methods like AF2Rank have successfully applied AlphaFold's confidence scores to identify correct proposal structures for both monomers and protein complexes [29, 30, 31]. While the function learned by AlphaFold to identify correct protein structures may contain some physical principles, it can yield physically unrealistic results when applied to sequence design and mutation effect prediction tasks. Confidence metrics like pLDDT and pTM are also not energies in any mathematically rigorous sense (i.e., they do not approximate the log-density of any relevant distribution), which limits their ability to be used or finetuned for quantitatively accurate dynamics simulation or energy prediction tasks. While log probabilities based on AlphaFold's distogram predictions can be interpreted as energies, they require AlphaFold to have a largely correct prediction of the native structure in order to be meaningful [32]. AlphaFold-based scoring is also quite slow, especially if many scoring iterations are needed to optimize a structure prediction.

2.6 Our Contributions

In this paper, we introduce a powerful diffusion-based EBM for protein modeling. While prior energy-parameterized diffusion models have been applied to specific proteins and rigid docking tasks, we tackle the broader task of learning a universal model of protein conformational energies, with the goal of generalizing to folds and conformations that are not well represented in the PDB. Our model shows robust capabilities across a wide range of tasks, including structure ranking, stability prediction, structure prediction, conformational sampling, and folding pathway prediction. An illustration of our approach can be found in Figure 1.

3 Methods

ProteinEBM is an energy-parameterized, sequence-conditioned protein diffusion model based on the diffusion modules from AlphaFold3 and Boltz-1 [33, 34]. This means that, unlike previous diffusion

Figure 1: Overview of ProteinEBM. a.) Schematic of the score matching training process. b.) ProteinEBM can generate samples via reverse diffusion over the learned energy landscapes. c.) ProteinEBM can rank arbitrary input structures via its learned energy.

models, ProteinEBM does not utilize an inherently equivariant model architecture, and relies on data augmentations to learn 3D symmetries. We found a non-equivariant architecture to be superior to Invariant Point Attention for achieving stable denoising trajectories with an energy-parameterized model, likely because optimizing second-order derivatives through IPA can result in instability. We downscaled the model from the version used in Boltz-1, resulting in a model with 85M parameters.

We trained ProteinEBM on a set of protein domains from the PDB and AlphaFold Database, using domain definitions from CATH and The Encyclopedia of Domains (TED) [35, 36]. We pretrained on a total of 32k CATH domains, 590k AFDB domains derived from the dataset of Lin et al., as well as 18k two-chain protein complexes from the set published by Jin et al. [18, 37]. Following pretraining, we finetuned a subset of our models on molecular dynamics simulations of 1k CATH domains that were previously used to train BioEmu [23]. These simulations were run at 300K using various AMBER forcefields, and contain both folded and unfolded structures.

We pretrained our models for at least 60 epochs, with each pretraining epoch containing all 32k CATH structures, all 18k complex structures, and 32k AFDB structures. We then finetuned on up to 3M frames of MD data, with the exact amount of finetuning varying depending on the application. We found that MD finetuning was unnecessary for obtaining strong performance on structure ranking and stability prediction tasks, but did help increase the diversity of generated samples.

ProteinEBM was trained using the denoising score matching framework. For a sample $x_0 \sim p_{data}$ and its noised version $x_t \sim \mathcal{N}(\sqrt{\beta_t}x_0, 1 - \beta_t)$, the score matching loss is

$$\frac{1}{N_r} \left\| -\nabla_x E_\theta(x_t, s, t) - \frac{1}{1 - \beta_t} \left(x_t - \sqrt{\beta_t}x_0 \right) \right\|^2$$

Where N_r is the number of residues. Optimizing this loss drives $E_\theta(x_t, s, t)$ to equal $-\log p_t(x|s)$ up to a constant, where $p_t(x|s)$ is the sequence-conditional data density noised to level t. At low enough t, the learned energy should theoretically approach $-\log p_{data}(x|s)$. However, this ideal outcome is not guaranteed, and whether this denoising task results in an energy that usefully resembles the true free energy is ultimately an empirical question.

As mentioned previously, AlphaFold-based scoring can suffer from pathological modes in which proteins with exposed hydrophobic residues or non-compact structures are scored confidently, despite their physical unfavorability. This is likely due to AlphaFold implicitly inferring the presence of an unseen binding partner or domain, since the model was trained on cropped portions of single chains with many interactions missing. To avoid this pathology in ProteinEBM, all training residues with a cropped out interaction partner were marked with an "external contact flag" that was passed into the

model as input. At inference time these flags are set to zero, keeping the model from inferring any extra context.

4 Results

4.1 Decoy Ranking

Discriminating correct native structures from plausible but incorrect "decoy" structures is a fundamental capability for energy-based protein models. This capability is important for selecting models generated by structure predictors and weighting conformational ensembles produced by MSA subsampling methods, as well as for predicting protein structures in regimes where coevolutionary information is scarce. In this setting, where tools like AlphaFold can fail, investing a larger amount of compute searching over structure space for low-energy structures is a promising approach to improving prediction results [29]. This is similar to the idea of test-time scaling in Large Language Models, for which optimization over EBMs has recently been proposed as a general solution [38].

To validate ProteinEBM's ranking ability we used the Rosetta decoy set, which contains 133 native protein structures with thousands of decoys for each native structure [39]. We subdivided the dataset into 50% validation and 50% test structures, and filtered our training data to have less than 40% sequence identity to proteins in either set (normalized by the length of the shorter protein to prevent the inclusion of subsequences). Additionally, we performed a structure-based split against 20 test targets by filtering out all training structures sharing a topology-level CATH classification with the targets. We refer to the proteins subjected to the CATH split as hard targets, and those subjected to the sequence split as easy targets. For our initial attempt at decoy ranking, we used a ProteinEBM model finetuned on 1M MD frames with only the first and last transformer layers unfrozen. To rank a decoy structure x we computed $E_\theta(x, s, t)$, with the time level t becoming a hyperparameter.

With this protocol, we found that decoy ranking performance peaked at time levels slightly above 0, and then decayed for larger values of t. Setting $t = 0$ should theoretically make the model energy converge to the data density, but in practice at extremely low noise levels the model only needs to correct very local structural features and thus its energy does not correlate well with global structural correctness. At very high levels of t the model energy converges to a Gaussian density, so it effectively ranks decoys based on their radius of gyration. Low but nonzero values of t interpolate between these extremes and give the best performance. After our initial training, we found that decoy ranking performance on the validation set peaked at times between t=0 and t=0.15 (Figure 1b). Based on this observation we then trained an "expert model," referred to as ProteinEBM-x, only on times below t=0.15, which significantly improved performance by concentrating model capacity on the relevant noise levels. The exact training protocols for our models can be found in Appendix A. Unless otherwise stated, we use ProteinEBM-x in all reported results with t=0.05 as the time level, which we chose to optimize ranking ability on the validation set.

ProteinEBM-x performed very well on ranking decoys in the test set, with an average Spearman correlation of the 0.838 between the model energy and decoy TMScore [40]. This is significantly higher than the Rosetta energy function, which had an average Spearman of 0.757 ($p = .0005$). The average TMScore of ProteinEBM-x's minimum-energy decoy for each target was 0.905, compared to Rosetta's top-1 TMScore of 0.899 ($p = 0.46$, n.s). Our models consider the sequence-structure relationship and do not merely use backbone realism for ranking, as performance degrades significantly when the sequence is masked out (Figure 2b). Energy-based ranking also far outperforms a simple strategy of ranking structures by the norm of the score, highlighting the necessity of the energy parameterization (Figure S1). We found no significant performance degradation on targets subjected to the stricter CATH-based split (Figure 2c-d), indicating good generalization.

4.2 Stability Prediction

We next examined the ability of ProteinEBM-x to predict stability changes in proteins upon mutation. We did this by evaluating the energy difference

$$\Delta\Delta E = [E_\theta(x, s, t) - E_\theta(x, s', t)] - \frac{1}{N} \sum_{x_{UF}^{(i)} \sim p_{UF}} \left[E_\theta\left(x, s, t\right) - E_\theta\left(x_{UF}^{(i)}, s', t\right) \right]$$

Figure 2: ProteinEBM-x can be used to accurately rank protein structure accuracy. a.) Example correlation between ProteinEBM-x energy and decoy TMScore for a test set protein. b.) Mean Spearman correlations between energy and TMScore at different values of t. Ribbons are standard error of the mean. c.) Comparison of Spearman correlations for ProteinEBM-x and Rosetta on each target in the test set. Dots are separated into easy and hard targets. Hard targets were subjected to a structure-based split and are farther from the training set d.) Comparison of the TMScore of the top-ranked decoy for each test target for ProteinEBM-x and Rosetta.

Where the right represents a heuristic Monte Carlo estimate of the free energy difference integrated over the unfolded states. We implemented p_{UF} as a Ramachandran-random sample of backbone torsion angles. This is only an approximation, and requires that the folded and unfolded conformational ensembles remain nearly constant under mutation. While not fully rigorous, such an approximation is commonly used when estimating point mutation energies [18], [7].

Table 1: State-of-the-art performance on the ProteinGym stability benchmark

Rank	Model	Average Spearman	Model Type
1	**ProteinEBM-x**	**0.686**	EBM
2	ProSST.2048	0.653	PLM (w/ structure)
3	ProSST.4096	0.652	PLM (w/ structure)
4	VenusREM	0.650	PLM (w/ structure & MSA)
5	ProSST.1024	0.642	PLM (w/ structure)
6	ESM3	0.641	PLM (w/ structure)
10	ESM-IF1	0.624	Structure-to-Sequence
22	ProteinMPNN	0.565	Structure-to-Sequence
-	ProteinEBM	0.545	EBM

We benchmarked our predicted $\Delta\Delta G$s on the stability datasets in ProteinGym, most of which were computed by Tsuboyama et al. via cDNA proteolysis [41, 42]. Our estimated energy differences showed a very robust correlation with experimental values. With an average Spearman correlation of .684, ProteinEBM-x outperforms all previously benchmarked models and sets a new state-of-the-art on zero-shot stability ranking on ProteinGym (Table 1). The previously highest-performing models are all structure-aware protein language models like ESM3, which has over 15 times as many parameters as ProteinEBM-x [43]. In contrast, ProteinEBM-x is an energy-based structure denoiser that was never explicitly trained to predict masked amino acids, and thus represents a new paradigm

for accurate, parameter-efficient unsupervised stability prediction. ProteinEBM's success at this task also stands in contrast to confidence metrics from AlphaFold-like structure predictors, which generally exhibit mediocre correlation with stability changes.

To expand the number of proteins used for evaluation we supplemented ProteinGym with the remaining datasets from Tsyuboyama et al. that were not included in the original benchmark, many of which are *de novo* proteins [41]. Adding these extra proteins resulted in an even larger performance gap between ProteinEBM-x and ESM3, which we used as a baseline on the expanded set. This was likely due the addition of more *de novo* proteins with no evolutionary history, as the performance gap between ProteinEBM-x and ESM3 was correlated with MSA depth (Figure 3d). For proteins with 0 or 1 MMSeqs2 hits, which likely all represent *de novo* proteins, ProteinEBM-x improved on ESM3 by an average of .178 Spearman points (.697 vs .519, $p < 0.0002$). This suggests that ESM3's performance is more dependent on evolutionary conservation relative to ProteinEBM-x.

Figure 3: ProteinEBM-x energies accurately predict changes in protein stability. a.) Method for approximating $\Delta\Delta G$ with folded and unfolded structures b.) Example correlation between predicted and experimental $\Delta\Delta G$ for protein CBPA2. c.) Spearman correlations between ProteinEBM-x energy differences and experimental $\Delta\Delta G$s vs ESM3 Spearmans for all stability targets in ProteinGym and MegaScale c.) ProteinEBM-x and ESM3 Spearmans on ProteinGym and MegaScale v.s. the MSA depth of each protein. Error bars are standard error of the mean.

4.3 Conformational Sampling

Our model can be used to generate structural samples in two ways: either by performing i.i.d. sampling via the reverse diffusion process, or by exploring the local energy landscape via dynamical simulation. The former method allows for perfectly decorrelated samples to be drawn without concern for the convergence of the sampling process, while the latter allows for local exploration of specific regions of conformation space and the elucidation of transition paths and kinetic parameters. Simulating directly from a low-noise energy level may also reveal new energetic basins that have been learned by the low-noise model, but are never revealed in reverse diffusion due to the divergence of the higher-noise energies from the Fokker-Planck equation. We performed local sampling using Langevin dynamics, and the details of our simulation algorithm can be found in Appendix B.1.

To examine ProteinEBM's ability to predict structures and sample conformational landscapes, we examined its performance on 11 fast-folding proteins first examined by Lindorff-Larson et al. [5]. These proteins were also split from the training set at a sequence identity threshold of 40%.

To generate structural landscapes, we performed Langevin annealing trajectories, in which we started from random noise and took 100 Langevin steps at each noise level before taking a reverse diffusion step to the next noise level in the reverse diffusion process. This approach enables better exploration by allowing the samples to equilibrate to each energy level. The ProteinEBM base model was used for timesteps with $t > 0.1$, with ProteinEBM-x used below $t = 0.1$. To analyze our models' exploration of conformational space, we used Time-Lagged Independent Components Analysis to compare our samples to the simulations published by Majewski et al [8].

Figure 4: ProteinEBM effectively samples conformations of fast-folding proteins with Langevin annealing. TICA plots showing conformational landscape for MD simulations (left) and ProteinEBM samples (right) for each fast folder, with red dot indicating native structure. Energy funnels show the relationship between model energy ($t = .05$) and RMSD to native for sampled structures. For funnel plots, the red dot indicates the native structure and green dot indicates the native after running a fast relaxation procedure. For protein structure graphics, the lowest-energy ProteinEBM sample is in red, and the native is in gray.

We found that, with Langevin annealing, our model generally captured the correct native structure. For all but 1 target the lowest-energy samples were within 3.5 Angstroms RMSD of the native structure. The only exception was the WWDomain, for which the lowest-energy structure exhibited all of the correct secondary structure arrangements but had some differences in loop conformations. In addition, NuG2 also shows a deep energy well at a strand-swapped nonnative conformation, which appears as the lowest-energy sample in some annealing runs (Figure S2). For all targets, the minimum-RMSD structure sampled during annealing was within 2.5Å of the native structure. Interestingly, we found that the sampled structures often had significantly lower energies than the native structures themselves, but this difference disappeared after subjecting the native structure to a fast relaxation protocol with the ProteinEBM-x energy.

For some targets the lowest-energy samples were highly accurate despite the fact that most samples were unfolded or otherwise distant from the native. For example, the vast majority of sampled TrpCage structures were unfolded, but the lowest-energy sample was 2.54Å from the folded NMR structure. This highlights the power of EBMs to perform massive sampling and subsequent reranking to facilitate accurate structure prediction, which is not possible with models like BioEmu that lack an explicit energy. The energy funnels in Figure 4 are also qualitatively reminiscent of energy funnels produced by methods like Rosetta.

In addition to capturing the native structures our model explores a significant portion of the non-native conformational space, although not as much as all-atom simulation. This not unexpected because ProteinEBM is a native-centric model with limited exposure to unfolded states in its training data, and its MD finetuning data were simulated at 300K while the reference simulations were run at 350K.

4.4 Folding Simulations

While Langevin annealing simulations allow for some exploration of conformational space, they cannot capture the pathways by which proteins fold, since the samples are generated by transforming from a Gaussian noise distribution rather than the distribution of the unfolded ensemble. However, ProteinEBM and ProteinEBM-x are also capable of performing direct folding simulations by running Langevin dynamics at a low noise level starting from an unfolded state. To investigate this capability, we performed Langevin simulations starting from Ramachandran-random chains using the energy function from ProteinEBM-x at $t = .05$. The simulations thus take place on a manifold of protein structures with a small amount of Gaussian noise, but the noise can be removed to produce a final trajectory by projecting each noisy simulation step to $t = 0$ using the model's predicted score.

To assess the accuracy of our folding simulations, we folded Protein G, its engineered variant NuG2, and Protein L, all of which have extensively characterized folding pathways. These bacterial immunoglobulin-binding proteins all have the same topology consisting of a single helix packed against N- and C-terminal hairpins. Experimental techniques like ϕ-value analysis have shown that the C-terminal hairpin adopts a more stable, native-like fold at the transition state in Protein G, while Protein L primarily folds through the N-terminal hairpin [44]. NuG2 was engineered starting from Protein G, and the N-terminal hairpin was stabilized to make its folding pathway resemble that of Protein L [45].

For each protein, we ran a sufficient number of simulations to observe >20 independent trajectories that folded to the native state within 3Å RMSD. We ran 1200 simulation trajectories for Protein G, 800 for NuG2, and 4800 for Protein L. For Protein G and NuG2 the lowest-energy sampled structures had the native fold, while the lowest-energy structure for Protein L was a strand-swapped version of the native structure (Figure S3). To analyze the folding trajectories we extracted transition intervals in which the simulated chain went from >10 Å from the native structure to <3 Å from the native or vice-versa. To summarize the sequence of native contact formation during folding and unfolding we computed the fraction of time native contacts were present along transition paths. A higher value indicates that a contact tends to form earlier during folding and break later during unfolding.This analysis was inspired by Lindorff-Larsen et al. and Chang and Perez [5, 46].

We found that, consistent with experiment, the C-terminal hairpin contacts had the greatest presence along transition paths in Protein G, while NuG2 and Protein L exhibited folding pathways that were shifted toward the formation of N-terminal contacts (Figure 5). While it is difficult to make quantitative inferences about folding pathways from our simulations (which may have physically unrealistic kinetics due to coarse-graining), the qualitative agreement with experiments highlights the potential of EBM-based simulation for exploring the process of protein folding.

4.5 Structure Prediction

Finally, we tested ProteinEBM's ability to predict structures for proteins in our Rosetta test set without using MSAs. In our initial experiments on the validation set, we found that using models finetuned on more MD data facilitated better exploration. Ultimately, we settled on a protocol of running Langevin annealing with a ProteinEBM model finetuned on 3M frames of MD data, followed by resampling the lowest-energy structures and re-annealing with the a ProteinEBM-x model that was not trained on any molecular dynamics data, which was also used to score the final outputs. As an optional step to improve ranking and increase backbone quality, we tried clustering the final structures and passing the lowest-energy cluster centers to AF2Rank. Despite the high computational cost of AF2Rank, this step was computationally cheap because we scored at most 40 samples per target using AF2Rank out of thousands of total ProteinEBM samples. We selected the final prediction to be the AF2Rank output structure with the highest pTM. Details of the sampling protocol can be found in Appendix B.2.

To create strong baseline methods, we ran AlphaFold2 in single-sequence mode for 10,000 seeds per target, and AlphaFold3 in single-sequence mode for 15,000 seeds per target, taking the prediction

Figure 5: ProteinEBM-x can be used to rapidly simulate folding trajectories of proteins. a.) Left: An example folding trajectory for Protein G, with snapshots taken at different frames from the simulation. Formation of example contacts labeled in Magenta. Right: Contact presence fraction during folding transitions, with example contacts indicated with magenta arrows. b.) Same as part a for NuG2. c.) Same as part a for Protein L.

with the highest pTM as the final output. We calculated these sample numbers based on empirical measurements of the runtime for each method. Details of the calculation are provided in Appendix H.

On the easy targets (split from the ProteinEBM training data at 40% identity), ProteinEBM sampling outperformed both the AF2 and AF3 baselines (Figure 6c-d). The lowest-energy samples from ProteinEBM had an average TMScore of .613, compared to top-1 TMScores of .584 for AF2 and .529 for AF3 ($p = .43$ and .01, respectively). AF2Rank refinement on the low-energy ProteinEBM samples further boosted the average top-1 TMScore to .690 ($p = .001$ and $p < 0.0002$ vs AF2 and AF3). While these targets are "easy" relative to the other test targets split by topology, they are still absent from the ProteinEBM training set and present in the training sets of AF2 and AF3, underscoring the effectiveness of ProteinEBM at large-scale sampling and ranking.

On the hard targets split from the ProteinEBM training data by topology, ProteinEBM sampling underperformed AF2 and AF3 regardless of AF2Rank refinement. Since decoy ranking performance remained strong on these targets (Figure 1c-d), this performance degradation suggests that ProteinEBM is capable of ranking the accuracy of structures far outside the training distribution, but has a harder time sampling unknown folds.

On unsuccessful prediction targets ProteinEBM exhibited multiple failure modes. Sometimes the model failed to explore structures close to the native, despite the fact that the native structure was scored with a lower energy than the structures produced by the model. In other cases, the model explored native-like structures but erroneously ranked other worse structures with lower energy. Examples of these failure cases can be found in Figure S9. These failure modes point to improvements in both the model's ranking ability and exploration ability as important areas of future work. Broader exploration could also benefit from the use of generative models that explicitly enumerate diverse protein folds.

Figure 6: ProteinEBM and ProteinEBM-x can be used to sample and score structure predictions. a.) ProteinEBM Langevin annealing (left) explores broadly, and the best samples are passed to AF2Rank. Standard AlphaFold sampling (right) can fail to sample global minima. b.) Left: TMScore vs Energy for ProteinEBM samples on PDB 2i24. Red dot is native, green dot is relaxed native, colors are clusters, gray dots are cluster centers. Center: AF2Rank refines and reranks lowest-energy cluster centers. Right: Predicted vs native structure for ProteinEBM+AF2Rank, AF2, and AF3. c.) Average top-1 TMScore for ProteinEBM, ProteinEBM+AF2Rank, AF2 and AF3, with performance split between easy and hard targets. Error bars are standard error of the mean. d.) Scatter plot of top-1 TMScores for ProteinEBM+AF2Rank vs AF2, split by easy and hard targets.

5 Discussion and Future Directions

We have developed an energy function for protein structural landscapes that shows strong performance in structure ranking, protein structure prediction, and conformational sampling, as well as state-of-the-art performance in zero-shot protein stability ranking. Our EBM is trained using a simple denoising score-matching paradigm, and is highly efficient compared to frontier structure prediction models. Our strong results demonstrate that EBMs are a promising framework for grounding ML protein structure models in thermodynamic principles. Protein conformational preferences, stabilities, binding affinities, and coarse-grained dynamical motions can all be formulated in terms of free energies, which allows EBMs like ours to generalize to a wide array of tasks in protein modeling. And by decoupling structure scoring from sampling, we can scale computing resources arbitrarily at inference time to facilitate a broader search over structures for difficult prediction targets. This paradigm can potentially relax the dependence of structure prediction on multiple sequence alignments, thereby unlocking greater regions of protein fold space for *de novo* design.

There are many possible avenues for improving the capabilities of ProteinEBM. While ProteinEBM-x exhibits state-of-the-art unsupervised performance on $\Delta\Delta G$ prediction, large experimental stability datasets could be used to actively supervise the model's energy differences. The model could also be finetuned using contrastive divergence, with large sets of decoys generated from sampling serving as a replay buffer of contrastive samples. Our models' capabilities could be evaluated and optimized for

protein complexes. Future work should also explore the use of more enhanced sampling techniques to improve exploration during structure prediction and simulation. It will also be useful to train EBMs on both finer and coarser levels of protein structure representation, such as all-atom models and models that operate on smoother latent representation spaces.

6 Code and Data Availability

All code and model weights are available at `https://github.com/jproney/ProteinEBM`.

7 Acknowledgements

James P. Roney acknowledges support from the Fannie and John Hertz Foundation. Chenxi Ou acknowledges support from the Herman N. Eisen Fellowship Fund. We thank all members of the Ovchinnikov lab for useful discussions and feedback. Sergey Ovchinnikov acknowledges funding from NSF grant MCB2032259, CocaCola and Amgen.

References

[1] John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, Alex Bridgland, Clemens Meyer, Simon A. A. Kohl, Andrew J. Ballard, Andrew Cowie, Bernardino Romera-Paredes, Stanislav Nikolov, Rishub Jain, Jonas Adler, Trevor Back, Stig Petersen, David Reiman, Ellen Clancy, Michal Zielinski, Martin Steinegger, Michalina Pacholska, Tamas Berghammer, Sebastian Bodenstein, David Silver, Oriol Vinyals, Andrew W. Senior, Koray Kavukcuoglu, Pushmeet Kohli, and Demis Hassabis. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, 2021.

[2] Tianyu Lu, Melissa Liu, Yilin Chen, Jinho Kim, and Po-Ssu Huang. Assessing generative model coverage of protein structures with shapes. *Cell Systems*, 16(8), 2026/01/18 2025.

[3] Zhidian Zhang, Chenxi Ou, Yehlin Cho, Yo Akiyama, and Sergey Ovchinnikov. Artificial intelligence methods for protein folding and design. *Current Opinion in Structural Biology*, 93:103066, 2025.

[4] Rebecca F. Alford, Andrew Leaver-Fay, Jeliazko R. Jeliazkov, Matthew J. O'Meara, Frank P. DiMaio, Hahnbeom Park, Maxim V. Shapovalov, P. Douglas Renfrew, Vikram K. Mulligan, Kalli Kappel, Jason W. Labonte, Michael S. Pacella, Richard Bonneau, Philip Bradley, Roland L. Jr. Dunbrack, Rhiju Das, David Baker, Brian Kuhlman, Tanja Kortemme, and Jeffrey J. Gray. The rosetta all-atom energy function for macromolecular modeling and design. *Journal of Chemical Theory and Computation*, 13(6):3031–3048, 2017.

[5] Kresten Lindorff-Larsen, Stefano Piana, Ron O. Dror, and David E. Shaw. How fast-folding proteins fold. *Science*, 334(6055):517–520, 2011.

[6] J. S. Smith, O. Isayev, and A. E. Roitberg. Ani-1: an extensible neural network potential with dft accuracy at force field computational cost. *Chem. Sci.*, 8:3192–3203, 2017.

[7] Nicholas E. Charron, Klara Bonneau, Aldo S. Pasos-Trejo, Andrea Guljas, Yaoyi Chen, Félix Musil, Jacopo Venturin, Daria Gusew, Iryna Zaporozhets, Andreas Krämer, Clark Templeton, Atharva Kelkar, Aleksander E. P. Durumeric, Simon Olsson, Adrià Pérez, Maciej Majewski, Brooke E. Husic, Ankit Patel, Gianni De Fabritiis, Frank Noé, and Cecilia Clementi. Navigating protein landscapes with a machine-learned transferable coarse-grained model. *Nature Chemistry*, 17(8):1284–1292, 2025.

[8] Maciej Majewski, Adrià Pérez, Philipp Thölke, Stefan Doerr, Nicholas E. Charron, Toni Giorgino, Brooke E. Husic, Cecilia Clementi, Frank Noé, and Gianni De Fabritiis. Machine learning coarse-grained potentials of protein thermodynamics. *Nature Communications*, 14(1):5739, 2023.

[9] John M. Jumper, Nabil F. Faruk, Karl F. Freed, and Tobin R. Sosnick. Trajectory-based training enables protein simulations with accurate folding and boltzmann ensembles in cpu-hours. *PLOS Computational Biology*, 14(12):e1006578, 2018.

[10] John Ingraham, Adam J. Riesselman, Chris Sander, and Debora S. Marks. Learning protein structure with a differentiable simulator. In *7th International Conference on Learning Representations, (ICLR)*, 2019.

[11] Huan Yang, Zhaoping Xiong, and Francesco Zonta. Construction of a deep neural network energy function for protein physics. *Journal of Chemical Theory and Computation*, 18(9):5649–5658, 2022.

[12] Yilun Du, Joshua Meier, Jerry Ma, Rob Fergus, and Alexander Rives. Energy-based models for atomic-resolution protein conformations. In *8th International Conference on Learning Representations, (ICLR)*, 2020.

[13] Yang Song, Jascha Sohl-Dickstein, Diederik P. Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *9th International Conference on Learning Representations, (ICLR)*, 2021.

[14] Yilun Du, Conor Durkan, Robin Strudel, Joshua B. Tenenbaum, Sander Dieleman, Rob Fergus, Jascha Sohl-Dickstein, Arnaud Doucet, and Will Sussman Grathwohl. Reduce, reuse, recycle: Compositional generation with energy-based diffusion models and MCMC. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202, pages 8489–8510. PMLR, July 2023.

[15] James Thornton, Louis Béthune, Ruixiang Zhang, Arwen Bradley, Preetum Nakkiran, and Shuangfei Zhai. Composition and control with distilled energy diffusion models and sequential monte carlo. In *Proceedings of The 28th International Conference on Artificial Intelligence and Statistics*, volume 258, pages 3259–3267. PMLR, 03–05 May 2025.

[16] Marloes Arts, Victor Garcia Satorras, Chin-Wei Huang, Daniel Zügner, Marco Federici, Cecilia Clementi, Frank Noé, Robert Pinsler, and Rianne van den Berg. Two for one: Diffusion models and force fields for coarse-grained molecular dynamics. *Journal of Chemical Theory and Computation*, 19(18):6151–6159, 2023.

[17] Michael Plainer, Hao Wu, Leon Klein, Stephan Günnemann, and Frank Noé. Consistent sampling and simulation: Molecular dynamics with energy-based diffusion models. *arXiv*, abs/2506.17139, 2025.

[18] Wengong Jin, Siranush Sarkizova, Xun Chen, Nir HaCohen, and Caroline Uhler. Unsupervised protein-ligand binding energy prediction via neural euler's rotation equation. In *Advances in Neural Information Processing Systems*, volume 36, pages 33514–33528, 2023.

[19] Lee-Shin Chu, Sudeep Sarma, Da Xu, and Jeffrey J. Gray. Unified sampling and ranking for protein docking with dfmdock. *bioRxiv*, 2025.

[20] Sudeep Sarma, Harrison Truscott, Da Xu, Kendall Reid, Lee-Shin Chu, Jacky Chen, and Jeffrey J. Gray. Can we extract physics-like energies from generative protein diffusion models? *bioRxiv*, 2025.

[21] Diego del Alamo, Davide Sala, Hassane S Mchaourab, and Jens Meiler. Sampling alternative conformational states of transporters and receptors with alphafold2. *eLife*, 11:e75751, 2022.

[22] Hannah K. Wayment-Steele, Adedolapo Ojoawo, Renee Otten, Julia M. Apitz, Warintra Pitsawong, Marc Hömberger, Sergey Ovchinnikov, Lucy Colwell, and Dorothee Kern. Predicting multiple conformations via sequence clustering and alphafold2. *Nature*, 625(7996):832–839, 2024.

[23] Sarah Lewis, Tim Hempel, José Jiménez-Luna, Michael Gastegger, Yu Xie, Andrew Y. K. Foong, Victor García Satorras, Osama Abdin, Bastiaan S. Veeling, Iryna Zaporozhets, Yaoyi Chen, Soojung Yang, Adam E. Foster, Arne Schneuing, Jigyasa Nigam, Federico Barbero, Vincent Stimper, Andrew Campbell, Jason Yim, Marten Lienen, Yu Shi, Shuxin Zheng, Hannes

Schulz, Usman Munir, Roberto Sordillo, Ryota Tomioka, Cecilia Clementi, and Frank Noé. Scalable emulation of protein equilibrium ensembles with generative deep learning. *Science*, 389(6761):eadv9817, 2025.

[24] Bowen Jing, Bonnie Berger, and Tommi Jaakkola. Alphafold meets flow matching for generating protein ensembles. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235, pages 22277–22303. PMLR, 2024.

[25] Daniel D. Richman, Jessica Karaguesian, Carl-Mikael Suomivuori, and Ron O. Dror. Unlocking hidden biomolecular conformational landscapes in diffusion models at inference time. *arXiv*, abs/2512.03312, 2025.

[26] Frank Noé, Simon Olsson, Jonas Köhler, and Hao Wu. Boltzmann generators: Sampling equilibrium states of many-body systems with deep learning. *Science*, 365(6457):eaaw1147, 2019.

[27] Leon Klein and Frank Noé. Transferable boltzmann generators. In *Advances in Neural Information Processing Systems*, volume 37, pages 45281–45314, 2024.

[28] Naozumi Hiranuma, Hahnbeom Park, Minkyung Baek, Ivan Anishchenko, Justas Dauparas, and David Baker. Improved protein structure refinement guided by deep learning based accuracy estimation. *Nature Communications*, 12(1):1340, 2021.

[29] James P. Roney and Sergey Ovchinnikov. State-of-the-art estimation of protein model accuracy using AlphaFold. *Phys. Rev. Lett.*, 129:238101, Nov 2022.

[30] Nathaniel R. Bennett, Brian Coventry, Inna Goreshnik, Buwei Huang, Aza Allen, Dionne Vafeados, Ying Po Peng, Justas Dauparas, Minkyung Baek, Lance Stewart, Frank DiMaio, Steven De Munck, Savvas N. Savvides, and David Baker. Improving de novo protein binder design with deep learning. *Nature Communications*, 14(1):2625, 2023.

[31] Simon Levine, Jonathan Edward King, Jacob Stern, David Grayson, Raymond Wang, Rui Yin, Umberto Lupo, Paulina Kulyte, Ryan Matthew Brand, Tristan Bertin, Robert Pfingsten, Jovan Cejovic, Chelsea Chung, Breanna K. Luton, Andrew Hagemann, Robel Haile, Elliot Medina, Pankaj Panwar, Oleksii Dubrovskyi, Chase LaCombe, Zahra Anderson, Derrik Mildh, Scott Benjamin, Joe Kaiser, Joseph Ferron, Marta Sarrico, Alexandria Kershner, Apurva Mishra, Kai R. Ejan, Emily K. Marsh, Paul Bringas, Phetsamay Vilaychack, Kyra Chapman, Jacob Ripley, Muttappa Gowda, Kathryn M. Collins, Cailen M. McCloskey, Jeremiah S. Joseph, Rylee Ripley, Shaheed A. Abdulhaqq, Audree Feltner, Michael Guerin, Jeffrey Goby, Jesse Hendricks, Danielle Castillo, Sean McClain, Douglas Ganini, Derek Shpiel, James Mategko, Eder Cruz Garcia, Masoud Zabet-Moghaddam, John M. Sutton, Zheyuan Guo, Sean M. West, Janani S. Iyer, and Amir Shanehsazzadeh. Origin-1: a generative ai platform for de novo antibody design against novel epitopes. *bioRxiv*, 2026.

[32] Büşra Savaş, Ayşe Berçin Barlas, and Ezgi Karaca. Exploring the potential of alphafold distograms for predicting binding-induced hinge motions. *bioRxiv*, 2025.

[33] Josh Abramson, Jonas Adler, Jack Dunger, Richard Evans, Tim Green, Alexander Pritzel, Olaf Ronneberger, Lindsay Willmore, Andrew J. Ballard, Joshua Bambrick, Sebastian W. Bodenstein, David A. Evans, Chia-Chun Hung, Michael O'Neill, David Reiman, Kathryn Tunyasuvunakool, Zachary Wu, Akvilė Žemgulytė, Eirini Arvaniti, Charles Beattie, Ottavia Bertolli, Alex Bridgland, Alexey Cherepanov, Miles Congreve, Alexander I. Cowen-Rivers, Andrew Cowie, Michael Figurnov, Fabian B. Fuchs, Hannah Gladman, Rishub Jain, Yousuf A. Khan, Caroline M. R. Low, Kuba Perlin, Anna Potapenko, Pascal Savy, Sukhdeep Singh, Adrian Stecula, Ashok Thillaisundaram, Catherine Tong, Sergei Yakneen, Ellen D. Zhong, Michal Zielinski, Augustin Žídek, Victor Bapst, Pushmeet Kohli, Max Jaderberg, Demis Hassabis, and John M. Jumper. Accurate structure prediction of biomolecular interactions with alphafold 3. *Nature*, 630(8016):493–500, 2024.

[34] Jeremy Wohlwend, Gabriele Corso, Saro Passaro, Noah Getz, Mateo Reveiz, Ken Leidal, Wojtek Swiderski, Liam Atkinson, Tally Portnoi, Itamar Chinn, Jacob Silterra, Tommi Jaakkola, and Regina Barzilay. Boltz-1: Democratizing biomolecular interaction modeling. *bioRxiv*, 2025.

[35] Ian Sillitoe, Nicola Bordin, Natalie Dawson, Vaishali P Waman, Paul Ashford, Harry M Scholes, Camilla S M Pang, Laurel Woodridge, Clemens Rauer, Neeladri Sen, Mahnaz Abbasian, Sean Le Cornu, Su Datt Lam, Karel Berka, Ivana Hutařová Varekova, Radka Svobodova, Jon Lees, and Christine A Orengo. Cath: increased structural coverage of functional space. *Nucleic Acids Research*, 49(D1):D266–D273, 11 2020.

[36] Andy M. Lau, Nicola Bordin, Shaun M. Kandathil, Ian Sillitoe, Vaishali P. Waman, Jude Wells, Christine A. Orengo, and David T. Jones. Exploring structural diversity across the protein universe with the encyclopedia of domains. *Science*, 386(6721):eadq4946, 2024.

[37] Yeqing Lin, Minji Lee, Zhao Zhang, and Mohammed AlQuraishi. Out of many, one: Designing and scaffolding proteins at the scale of the structural universe with genie 2, 2024.

[38] Alexi Gladstone, Ganesh Nanduru, Md Mofijul Islam, Peixuan Han, Hyeonjeong Ha, Aman Chadha, Yilun Du, Heng Ji, Jundong Li, and Tariq Iqbal. Energy-based transformers are scalable learners and thinkers. *arXiv*, abs/2507.02092, 2025.

[39] Hahnbeom Park, Philip Bradley, Per Jr. Greisen, Yuan Liu, Vikram Khipple Mulligan, David E. Kim, David Baker, and Frank DiMaio. Simultaneous optimization of biomolecular energy functions on features from small molecules and macromolecules. *Journal of Chemical Theory and Computation*, 12(12):6201–6212, 2016.

[40] Yang Zhang and Jeffrey Skolnick. Scoring function for automated assessment of protein structure template quality. *Proteins: Structure, Function, and Bioinformatics*, 57(4):702–710, 2004.

[41] Kotaro Tsuboyama, Justas Dauparas, Jonathan Chen, Elodie Laine, Yasser Mohseni Behbahani, Jonathan J. Weinstein, Niall M. Mangan, Sergey Ovchinnikov, and Gabriel J. Rocklin. Mega-scale experimental analysis of protein folding stability in biology and design. *Nature*, 620(7973):434–444, 2023.

[42] Pascal Notin, Aaron Kollasch, Daniel Ritter, Lood van Niekerk, Steffanie Paul, Han Spinner, Nathan Rollins, Ada Shaw, Rose Orenbuch, Ruben Weitzman, Jonathan Frazer, Mafalda Dias, Dinko Franceschi, Yarin Gal, and Debora Marks. Proteingym: Large-scale benchmarks for protein fitness prediction and design. In *Advances in Neural Information Processing Systems*, volume 36, pages 64331–64379, 2023.

[43] Thomas Hayes, Roshan Rao, Halil Akin, Nicholas J. Sofroniew, Deniz Oktay, Zeming Lin, Robert Verkuil, Vincent Q. Tran, Jonathan Deaton, Marius Wiggert, Rohil Badkundri, Irhum Shafkat, Jun Gong, Alexander Derry, Raul S. Molina, Neil Thomas, Yousuf A. Khan, Chetan Mishra, Carolyn Kim, Liam J. Bartie, Matthew Nemeth, Patrick D. Hsu, Tom Sercu, Salvatore Candido, and Alexander Rives. Simulating 500 million years of evolution with a language model. *Science*, 387(6736):850–858, 2025.

[44] Erika L. McCallister, Eric Alm, and David Baker. Critical role of -hairpin formation in protein g folding. *Nature Structural Biology*, 7(8):669–673, 2000.

[45] Sehat Nauli, Brian Kuhlman, and David Baker. Computer-based redesign of a protein folding pathway. *Nature Structural Biology*, 8(7):602–605, 2001.

[46] Liwei Chang and Alberto Perez. Rapid estimation of protein folding pathways from sequence alone using alphafold2. *Nature Communications*, 17(1):170, 2025.

[47] Joseph L. Watson, David Juergens, Nathaniel R. Bennett, Brian L. Trippe, Jason Yim, Helen E. Eisenach, Woody Ahern, Andrew J. Borst, Robert J. Ragotte, Lukas F. Milles, Basile I. M. Wicky, Nikita Hanikel, Samuel J. Pellock, Alexis Courbet, William Sheffler, Jue Wang, Preetham Venkatesh, Isaac Sappington, Susana Vázquez Torres, Anna Lauko, Valentin De Bortoli, Emile Mathieu, Sergey Ovchinnikov, Regina Barzilay, Tommi S. Jaakkola, Frank DiMaio, Minkyung Baek, and David Baker. De novo design of protein structure and function with rfdiffusion. *Nature*, 620(7976):1089–1100, 2023.

[48] Jason Yim, Brian L. Trippe, Valentin De Bortoli, Emile Mathieu, Arnaud Doucet, Regina Barzilay, and Tommi Jaakkola. SE(3) diffusion model with application to protein backbone generation. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202, pages 40001–40039. PMLR, 23–29 Jul 2023.

[49] Matteo Cagiada, Sergey Ovchinnikov, and Kresten Lindorff-Larsen. Predicting absolute protein folding stability using generative models. *Protein Science*, 34(1):e5233, 2025.

[50] Hannes Stark, Felix Faltings, MinGyu Choi, Yuxin Xie, Eunsu Hur, Timothy O'Donnell, Anton Bushuiev, Talip Uçar, Saro Passaro, Weian Mao, Mateo Reveiz, Roman Bushuiev, Tomáš Pluskal, Josef Sivic, Karsten Kreis, Arash Vahdat, Shamayeeta Ray, Jonathan T. Goldstein, Andrew Savinov, Jacob A. Hambalek, Anshika Gupta, Diego A. Taquiri-Diaz, Yaotian Zhang, A. Katherine Hatstat, Angelika Arada, Nam Hyeong Kim, Ethel Tackie-Yarboi, Dylan Boselli, Lee Schnaider, Chang C. Liu, Gene-Wei Li, Denes Hnisz, David M. Sabatini, William F. DeGrado, Jeremy Wohlwend, Gabriele Corso, Regina Barzilay, and Tommi Jaakkola. Boltzgen: Toward universal binder design. *bioRxiv*, 2025.

[51] Peter E. Cavanagh, Andrew G. Xue, Shizhong A. Dai, Albert Qiang, Tsutomu Matsui, and Alice Y. Ting. Computational design of conformation-biasing mutations to alter protein functions. *Science*, 0(0):eadv7953.